Preventative Maintenance Procedures

Visible Light Processors

All Models

Customer Name: _____

Processor S/N: _____

Processor F/W Rev: _____

1. ☐ Verify program **parameters**.
2. ☐ Confirm if customer is replacing **Dev Scrub cover and Dev Filter** on a scheduled basis. These are consumable items customer should be familiar with.
3. ☐ On Raptors, check **consumable timers** and address if necessary.

Drive Sections

1. ☐ Operate machine and **observe transport rollers**.
2. ☐ In Dev section, ensure **scrub rollers are operating properly**.
3. ☐ In Dev section, check **Hold Down Rollers** and make sure they are seated properly.
4. ☐ Check **motor drive** operation. Watch for any roller skipping as plate feeds through.

Pre-Heat

1. ☐ Check **Blower/ Fan operation**
2. ☐ Confirm **temperature** on plate

Pre-Rinse

1. ☐ Check **Spray Bar** for proper water flow. Ensure they are kept clean. Ensure no holes are clogged.
2. ☐ Check condition of **pre-rinse scrub roller**
3. ☐ Check **water Temp**. If too cold, then coating may not be cleaned off plate properly
4. ☐ Check **draining** of pre-rinse tank. Ensure water is not overflowing.

Developer Tank

1. ☐ Check Developer **Temp**
2. ☐ Check Developer **Circulation**
3. ☐ Confirm Developer **Dwell Time**
4. ☐ Check **Dev entrance rollers** for any coating buildup. This may indicate improper pre-rinse activity.
5. ☐ Check **V-Seals** for leaks.

Post- Rinse

1. ☐ Check all **Spray Bars** for proper flow. Ensure they are kept clean. Ensure no holes are clogged.
2. ☐ Check **draining** of pre-rinse tank. Ensure water is not overflowing.
3. ☐ Check condition of **post-rinse scrub roller.**

Replenishment

1. ☐ Make sure **replenish pumps** function properly.
2. ☐ Check **Gum Pump** replenish flow. Poppet valves may need to be changed if gum does not flow.
3. ☐ Check for **kinks, leaks** in replenish tubing
4. ☐ Confirm **Dev Replenish pumps** are calibrated correctly

Gum

1. ☐ Check for proper **gum flow** across roller.
2. ☐ Make sure **application roller** is clean. If **Gum Blade**, check to see if it is working properly.

Cleaning

Customer is responsible for cleaning of processor. If processor is not maintained well, problems may occur. Point out items to customer that are dirty and could be maintained better.

1. ☐ Check **Dev Exit Rollers.** These rollers will get dirty if not cleaned monthly.
2. ☐ Check **Pre-Rinse Rollers** and **Dev Entrance Rollers** for coating buildup.
3. ☐ Check **Wash Tanks**. Depending on water condition, algae may buildup here.

Chiller

1. ☐ Check **Water Level**
2. ☐ The chiller should be **drained, cleaned** and re-filled at least quarterly by customer.
3. ☐ **RTE- 7** chiller is air cooled. The front grill must be removed and condenser area cleaned/vacuumed.

See the following page for a list of commonly used PM Parts

Notes:

_____

_____

_____

_____

_____

_____

Common PM Parts for Visible Light Processors

FLP1260 Poppet	133F1314
FLP1260 Water Solenoid	040800

Raptor Poppet	10003917