

# Interactive Proofmode for Temporal Logic in Rocq

Jonas Kastberg Hinrichsen

Assistant Professor  
Aalborg University

Elli Anastasiadi

Assistant Professor  
Aalborg University

20. August, CoPLaWS 2026

Slides:



# Context:

We care about liveness and mechanisation properties

# Context:

We care about liveness and mechanisation properties

# Problem:

Limited support for mechanising temporal properties

# Context:

We care about liveness and mechanisation properties

# Problem:

Limited support for mechanising temporal properties

# Solution:

Interactive Proofmode for Temporal Logic in Rocq

# Context:

We care about liveness and mechanisation

# Liveness Properties and Temporal Logic


**Liveness: something good eventually happens**

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$


# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces

- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS



$a, b, a, \dots$

$b, b, b, \dots$

$b \dots, a \dots, b \dots$



# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens


- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces

- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS

## Most temporal logics are based on modalities, such as

- ▶ Next  $P$ :  $\circ P \equiv \lambda tr. P(\text{tail } tr)$
- ▶ Globally  $P$ :  $\Box P \equiv \lambda tr. \forall n. P(\text{tail}^n tr)$
- ▶ Eventually  $P$ :  $\Diamond P \equiv \lambda tr. \exists n. P(\text{tail}^n tr)$



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$

# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces


- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS

## Most temporal logics are based on modalities, such as

- ▶ Next  $P$ :  $\circ P \equiv \lambda tr. P(\text{tail } tr)$
- ▶ Globally  $P$ :  $\Box P \equiv \lambda tr. \forall n. P(\text{tail}^n tr)$
- ▶ Eventually  $P$ :  $\Diamond P \equiv \lambda tr. \exists n. P(\text{tail}^n tr)$

## Example:

- ▶ Property:  $\Diamond A \vdash \circ \Diamond B$



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$

# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces


- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS

## Most temporal logics are based on modalities, such as

- ▶ Next  $P$ :  $\circ P \equiv \lambda tr. P(\text{tail } tr)$
- ▶ Globally  $P$ :  $\Box P \equiv \lambda tr. \forall n. P(\text{tail}^n tr)$
- ▶ Eventually  $P$ :  $\Diamond P \equiv \lambda tr. \exists n. P(\text{tail}^n tr)$

## Example:

- ▶ Property:  $\Diamond A \vdash \circ \Diamond B$
- ▶ Axioms:  $A \wedge a \vdash \circ B$       $A \wedge b \vdash \circ A$



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$

# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces


- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS

## Most temporal logics are based on modalities, such as

- ▶ Next  $P$ :  $\circ P \equiv \lambda tr. P(\text{tail } tr)$
- ▶ Globally  $P$ :  $\Box P \equiv \lambda tr. \forall n. P(\text{tail}^n tr)$
- ▶ Eventually  $P$ :  $\Diamond P \equiv \lambda tr. \exists n. P(\text{tail}^n tr)$

## Example:

- ▶ Property:  $\Diamond A \vdash \circ \Diamond B$
- ▶ Axioms:  $A \wedge a \vdash \circ B$       $A \wedge b \vdash \circ A$
- ▶ Fairness assumption:  $\Box \Diamond a$



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$

# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces


- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS

## Most temporal logics are based on modalities, such as

- ▶ Next  $P$ :  $\circ P \equiv \lambda tr. P(\text{tail } tr)$
- ▶ Globally  $P$ :  $\Box P \equiv \lambda tr. \forall n. P(\text{tail}^n tr)$
- ▶ Eventually  $P$ :  $\Diamond P \equiv \lambda tr. \exists n. P(\text{tail}^n tr)$

## Example:

- ▶ Property:  $\Diamond A \vdash \circ \Diamond B$
- ▶ Axioms:  $A \wedge a \vdash \circ B$       $A \wedge b \vdash \circ A$
- ▶ Fairness assumption:  $\Box \Diamond a$



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$

# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces


- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS

## Most temporal logics are based on modalities, such as

- ▶ Next  $P$ :  $\circ P \equiv \lambda tr. P(\text{tail } tr)$
- ▶ Globally  $P$ :  $\Box P \equiv \lambda tr. \forall n. P(\text{tail}^n tr)$
- ▶ Eventually  $P$ :  $\Diamond P \equiv \lambda tr. \exists n. P(\text{tail}^n tr)$

## Example:

- ▶ Property:  $\Diamond A \vdash \circ \Diamond B$
- ▶ Axioms:  $A \wedge a \vdash \circ B$       $A \wedge b \vdash \circ A$
- ▶ Fairness assumption:  $\Box \Diamond a$
- ▶ One derivation step:  $\Box(A \rightarrow \circ \Diamond B) \vdash \Diamond A \rightarrow \circ \Diamond B$



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$

# Liveness Properties and Temporal Logic

## Liveness: something good eventually happens

- ▶ E.g.: Collaborating threads eventually make progress under fair scheduling
- ▶ Often studied in terms of labelled transition system (LTS) traces

## Linear Temporal logic: logic for reasoning about traces


- ▶  $P \vdash Q \triangleq \forall tr. P \text{ } tr \rightarrow Q \text{ } tr$  where  $P, Q \in \text{Trace} \rightarrow \text{Prop}$
- ▶ Here, Trace is a maximal labelled trace w.r.t. some LTS

## Most temporal logics are based on modalities, such as

- ▶ Next  $P$ :  $\circ P \equiv \lambda tr. P(\text{tail } tr)$
- ▶ Globally  $P$ :  $\Box P \equiv \lambda tr. \forall n. P(\text{tail}^n tr)$
- ▶ Eventually  $P$ :  $\Diamond P \equiv \lambda tr. \exists n. P(\text{tail}^n tr)$

## Example:

- ▶ Property:  $\Diamond A \vdash \circ \Diamond B$
- ▶ Axioms:  $A \wedge a \vdash \circ B$       $A \wedge b \vdash \circ A$
- ▶ Fairness assumption:  $\Box \Diamond a$
- ▶ One derivation step:  $\Box(P \rightarrow \circ \Diamond Q) \vdash \Diamond P \rightarrow \circ \Diamond Q$



$a, b, a, \dots$

$b, b, b, \dots$

$b\dots, a\dots, b\dots$

## **Mechanisation: machine-checked proofs**

- ▶ Trust through rigor; no stone unturned
- ▶ Small trusted computing base
- ▶ Reusable proof infrastructure
- ▶ Increasingly becoming a community expectation
  - ▶ “All results have been mechanised”



## **Mechanisation: machine-checked proofs**

- ▶ Trust through rigor; no stone unturned
- ▶ Small trusted computing base
- ▶ Reusable proof infrastructure
- ▶ Increasingly becoming a community expectation
  - ▶ “All results have been mechanised”

## **Interactive theorem provers (ITPs): Rocq, Lean, ...**

- ▶ Interactive step-wise deduction

## Mechanisation: machine-checked proofs

- ▶ Trust through rigor; no stone unturned
- ▶ Small trusted computing base
- ▶ Reusable proof infrastructure
- ▶ Increasingly becoming a community expectation
  - ▶ “All results have been mechanised”

## Interactive theorem provers (ITPs): Rocq, Lean, ...

- ▶ Interactive step-wise deduction

```
From Stdlib Require Import Lia.

Fixpoint fac n :=
  match n with
  | 0 => 1
  | S n' => n * fac n'
  end.

Compute fac 5.

Lemma fac_succ n : fac (S n) = S n * fac n.
Proof. = reflexivity. Qed.

Lemma fac_pos n : fac n > 0.
Proof. =
  induction n. =
  - = simpl. = lia.
  - = rewrite fac_succ. = lia.
Qed.
```

## Mechanisation: machine-checked proofs

- ▶ Trust through rigor; no stone unturned
- ▶ Small trusted computing base
- ▶ Reusable proof infrastructure
- ▶ Increasingly becoming a community expectation
  - ▶ “All results have been mechanised”

## Interactive theorem provers (ITPs): Rocq, Lean, ...

- ▶ Interactive step-wise deduction
- ▶ Time consuming

```
From Stdlib Require Import Lia.

Fixpoint fac n :=
  match n with
  | 0 => 1
  | S n' => n * fac n'
  end.

Compute fac 5.

Lemma fac_succ n : fac (S n) = S n * fac n.
Proof. = reflexivity. Qed.

Lemma fac_pos n : fac n > 0.
Proof. =
  induction n. =
  - = simpl. = lia.
  - = rewrite fac_succ. = lia.
Qed.
```

## Mechanisation: machine-checked proofs

- ▶ Trust through rigor; no stone unturned
- ▶ Small trusted computing base
- ▶ Reusable proof infrastructure
- ▶ Increasingly becoming a community expectation
  - ▶ “All results have been mechanised”

## Interactive theorem provers (ITPs): Rocq, Lean, ...

- ▶ Interactive step-wise deduction
- ▶ Time consuming, especially with limited support

```
Definition is_adjoint' {A B : Type} (f : A → B) (g : B → A)
  (issect : g * f == id) (isretr : f * g == id) (a : A) :
  isretr (f a) = ap f (issect' f g issect isretr a). =
Proof. =
  unfold issect'. =
  apply move1_M1. =
  repeat rewrite ap_pp. = rewrite <- concat_p_pp; rewrite <- ap_compose. =
  pose (concat_pA1 (fun b => (isretr b)^) (ap f (issect a))). =
  eapply concat. = 2: { => apply ap2. = reflexivity. = exact e. } =
  cbn. = clear e. =
  pose (concat_pA1 (fun b => (isretr b)^) (isretr (f a))). =
  rewrite <- concat_p_pp. =
  pose (concat_A1p (fun b => (isretr b)) (isretr (f a))). =
  apply move1_Vp in e0. =
  rewrite <- concat_p_pp in e0. = rewrite inv_inv' in e0. =
  rewrite concat_refl in e0. =
  rewrite ap_compose in e0. =
  eapply concat. =
  2: { => apply ap2. = reflexivity. = rewrite concat_p_pp. = eapply
concat. =
  2: { => apply ap2. = eapply concat. =
  2: { => apply ap2. = symmetry. = apply e0. = reflexivity. } =
  symmetry. = apply inv_inv'. = reflexivity. } =
  reflexivity. } =
  repeat rewrite <- ap_compose. =
  cbn. = symmetry. = eapply concat. = refine (ap_pp ((f * g) * f) _)^. =
  rewrite inv_inv. = reflexivity.
```

## Mechanisation: machine-checked proofs

- ▶ Trust through rigor; no stone unturned
- ▶ Small trusted computing base
- ▶ Reusable proof infrastructure
- ▶ Increasingly becoming a community expectation
  - ▶ “All results have been mechanised”

## Interactive theorem provers (ITPs): Rocq, Lean, ...

- ▶ Interactive step-wise deduction
- ▶ Time consuming, especially with limited support
- ▶ Support: libraries, tactics, verified SMT solvers, ...

```
Definition is_adjoint' {A B : Type} (f : A → B) (g : B → A)
  (issect : g * f == id) (isretr : f * g == id) (a : A) :
  isretr (f a) = ap f (issect' f g issect isretr a). =
Proof. =
  unfold issect'. =
  apply move1_M1. =
  repeat rewrite ap_pp. = rewrite <- concat_pp; rewrite <- ap_compose. =
  pose (concat_pA1 (fun b => (isretr b)^) (ap f (issect a))). =
  eapply concat. = 2: { => apply ap2. = reflexivity. = exact e. } =
  cbn. = clear e. =
  pose (concat_pA1 (fun b => (isretr b)^) (isretr (f a))). =
  rewrite <- concat_pp. =
  pose (concat_A1p (fun b => (isretr b)) (isretr (f a))). =
  apply move1_Vp in e0. =
  rewrite <- concat_pp in e0. = rewrite inv_inv' in e0. =
  rewrite concat_refl in e0. =
  rewrite ap_compose in e0. =
  eapply concat. =
  2: { => apply ap2. = reflexivity. = rewrite concat_pp. = eapply
concat. =
  2: { => apply ap2. = eapply concat. =
  2: { => apply ap2. = symmetry. = apply e0. = reflexivity. } =
  symmetry. = apply inv_inv'. = reflexivity. } =
  reflexivity. } =
  repeat rewrite <- ap_compose. =
  cbn. = symmetry. = eapply concat. = refine (ap_pp ((f * g) * f) _)^. =
  rewrite inv_inv. = reflexivity.
```

## Mechanisation: machine-checked proofs

- ▶ Trust through rigor; no stone unturned
- ▶ Small trusted computing base
- ▶ Reusable proof infrastructure
- ▶ Increasingly becoming a community expectation
  - ▶ “All results have been mechanised”

## Interactive theorem provers (ITPs): Rocq, Lean, ...

- ▶ Interactive step-wise deduction
- ▶ Time consuming, especially with limited support
- ▶ Support: libraries, tactics, verified SMT solvers, ...

```
Local Lemma try_acquire_spec y lk R :
  {{{ is_lock y lk R }}} try_acquire lk
  {{{ b, RET #b; if b is true then locked y * R else True }}}.
Proof.
  iIntros (Φ) "#Hl HΦ". iDestruct "Hl" as (l ->) "#Hinv".
  wp_rec. wp_bind (CmpXchg _ _ _). iInv N as ([]) "[Hl HR]".
  - wp_cmpxchg_fail "Hinv" : inv M (lock_inv y l R)
  - wp_pures. iApp "Hl" : V b : bool, (if b then locked y * R else True) => Φ #b
  - wp_cmpxchg_succ "Hl" : ▷ l == #true
  iModIntro. iSp "HR" : ▷ True
  rewrite /locked
Qed.

WP CmpXchg #l #false #true @ T ~ #N ((V, l) => T ~ #N) => ▷ lock_inv y l R * WP Snd

goal 2 (ID 1116) is:
  "Hinv" : inv M (lock_inv y l R)
  "Hl" : V b : bool, (if b then locked y * R else True) => Φ #b
  "HR" : ▷ l == #false
  "HR" : ▷ (taken y * R)
  WP CmpXchg #l #false #true @ T ~ #N ((V, l) => T ~ #N) => ▷ lock_inv y l R * WP Snd
Proof.
  iIntros (Φ) "#Hl HΦ". wp_apply (try_acquire_spec).
  - iIntros "[Hlkd HR]". wp_if. iApply "HΦ"; auto with iFrame.
  - iIntros "_". wp_if. iApply ("IH" with "[HΦ]"). auto.
Qed.
```



# Problem:

Limited support for mechanising temporal properties  
(in Rocq)

# Mechanising Temporal Properties in Rocq

## Option 1: Going nuclear

- ▶ Give a paper proof / (unverified) translation to model checker
- ▶ Increases the trusted computing base
- ▶ Remove “All results have been mechanised” statement



# Mechanising Temporal Properties in Rocq

## Option 1: Going nuclear

- ▶ Give a paper proof / (unverified) translation to model checker
- ▶ Increases the trusted computing base
- ▶ Remove “All results have been mechanised” statement

## Option 2: Do it yourself

- ▶ Mechanise proof ad hoc
- ▶ Given a custom trace definition with ever-growing suite of lemmas

# Mechanising Temporal Properties in Rocq

## Option 1: Going nuclear

- ▶ Give a paper proof / (unverified) translation to model checker
- ▶ Increases the trusted computing base
- ▶ Remove “All results have been mechanised” statement

## Option 2: Do it yourself

- ▶ Mechanise proof ad hoc
- ▶ Given a custom trace definition with ever-growing suite of lemmas

## Option 3: Use existing libraries

- ▶ Browse selection of existing (LTL) libraries in Rocq
- ▶ They focus on metatheory => limited helper lemmas / tactic support

# Solution:

Interactive Proofmode for Temporal Logic in Rocq

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic

```
Lemma example (P Q : tProp) :  
  □ (P → ◊ ◊ Q) ⊢ ◊ P → ◊ ◊ Q.
```

```
Proof.
```

```
  iIntros "#HPQ HP".
```

```
  iMod "HP".
```

```
  iDestruct ("HPQ" with "HP") as "HQ".
```

```
  iApply "HQ".
```

```
Qed.
```

```
- S : Type  
- L : Type  
- Rel : S → L → S → Prop  
- P, Q : tProp
```

```
"HPQ" : P → ◊ ◊ Q
```

```
-----  
"HP" : ◊ P
```

```
-----  
◊ ◊ Q
```

# Contributions

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

```
Lemma example (P Q : tProp) :
```

```
  □ (P → ◊ ◊ Q) ⊢ ◊ P → ◊ Q.
```

```
Proof.
```

```
  iIntros "#HPQ HP".
```

```
  iMod "HP".
```

```
  iDestruct ("HPQ" with "HP") as "HQ".
```

```
  iApply "HQ".
```

```
Qed.
```

```
- S : Type
- L : Type
- Rel : S → L → S → Prop
- P, Q : tProp
```

```
"HPQ" : P → ◊ ◊ Q
```

```
-----
"HP" : ◊ P
```

```
-----
◊ ◊ Q
```

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

```
Lemma example (P Q : tProp) :  
  □ (P → ◊ Q) ⊢ ◊ P → ◊ Q.
```

```
Proof.
```

```
  iIntros "#HPQ HP".
```

```
  iMod "HP".
```

```
  iDestruct ("HPQ" with "HP") as "HQ".
```

```
  iApply "HQ".
```

```
Qed.
```

```
- S : Type
```

```
- L : Type
```

```
- Rel : S → L → S → Prop
```

```
- P, Q : tProp
```

```
"HPQ" : P → ◊ Q
```

```
"HP" : P
```

```
◊ Q
```

# Contributions

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

```
Lemma example (P Q : tProp) :  
  □ (P → ◊ Q) ⊢ ◊ P → ◊ Q.
```

```
Proof.
```

```
  iIntros "#HPQ HP".
```

```
  iMod "HP".
```

```
  iDestruct ("HPQ" with "HP") as "HQ".
```

```
  iApply "HQ".
```

```
Qed.
```

```
- S : Type  
- L : Type  
- Rel : S → L → S → Prop  
- P, Q : tProp
```

```
"HPQ" : P → ◊ Q
```

```
-----  
"HQ" : ◊ Q
```

```
-----  
◊ Q
```

# Contributions

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

```
Lemma example (P Q : tProp) :  
  □ (P → ◊ Q) ⊢ ◊ P → ◊ Q.  
Proof.  
  iIntros "#HPQ HP".  
  iMod "HP".  
  iDestruct ("HPQ" with "HP") as "HQ".  
  iApply "HQ".  
Qed.
```

```
-UUU:%%-D F1 *goals*
```

```
No more goals.
```



# Contributions

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

## LTL for maximal possibly-finite traces

- ▶ Primitive Next ( $\circ$ ) modality (even for terminated traces)
- ▶ Derived Globally ( $\Box$ ) modality via Next

# Contributions

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

## LTL for maximal possibly-finite traces

- ▶ Primitive Next ( $\circ$ ) modality (even for terminated traces)
- ▶ Derived Globally ( $\Box$ ) modality via Next

## Support for least and greatest fixpoints

- ▶ Logic-level fixpoints with fixpoint theorems for free
- ▶ E.g.  $\Diamond P \triangleq \mu X. P \vee \circ X$        $\text{every\_other } P \triangleq \nu X. P \wedge \circ \circ P$

# Contributions

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

## LTL for maximal possibly-finite traces

- ▶ Primitive Next ( $\circ$ ) modality (even for terminated traces)
- ▶ Derived Globally ( $\Box$ ) modality via Next

## Support for least and greatest fixpoints

- ▶ Logic-level fixpoints with fixpoint theorems for free
- ▶ E.g.  $\Diamond P \triangleq \mu X. P \vee \circ X$        $\text{every\_other } P \triangleq \nu X. P \wedge \circ \circ P$

## Infrastructure for instantiation with custom LTS models

- ▶ Reflect LTS stepping relation as logic-level axioms
- ▶ Extract meta-level theorems about traces

# Contributions

## Introducing Modal Temporal Logic Proofmode (MoTeL)

- ▶ Proofmode context for temporal logic
- ▶ Tactics for working with temporal modalities

## LTL for maximal possibly-finite traces

- ▶ Primitive Next ( $\circ$ ) modality (even for terminated traces)
- ▶ Derived Globally ( $\Box$ ) modality via Next

## Support for least and greatest fixpoints

- ▶ Logic-level fixpoints with fixpoint theorems for free
- ▶ E.g.  $\Diamond P \triangleq \mu X. P \vee \circ X$        $\text{every\_other } P \triangleq \nu X. P \wedge \circ \circ P$

## Infrastructure for instantiation with custom LTS models

- ▶ Reflect LTS stepping relation as logic-level axioms
- ▶ Extract meta-level theorems about traces

## Proof of eventual delivery for model of Stenning protocol

- ▶ In an unreliable network with a fair delivery assumption

# Modal Temporal Logic Proofmode Demo

# Developing the Modal Temporal Logic Proofmode

## **MoSeL: Modal Separation Logic (Proofmode)**

- ▶ “Extensible Modal Framework for Interactive Proofs (in Separation Logic)”
- ▶ Foundation for the Iris Proof Mode (facilitating 150+ papers since 2015)
- ▶ Now also foundation for the Modal Temporal Logic Proofmode

# Developing the Modal Temporal Logic Proofmode

## MoSeL: Modal Separation Logic (Proofmode)

- ▶ “Extensible Modal Framework for Interactive Proofs (in Separation Logic)”
- ▶ Foundation for the Iris Proof Mode (facilitating 150+ papers since 2015)
- ▶ Now also foundation for the Modal Temporal Logic Proofmode

## Key features of MoSeL

- ▶ Managed proof context for spatial and persistent propositions
- ▶ Extensible handling of modality-based reasoning via typeclasses
- ▶ Least and greatest monotone fixpoint constructions
- ▶ (Opt-in) step-indexing and separation logic
- ▶ Coming to Lean!

# Developing the Modal Temporal Logic Proofmode

## MoSeL: Modal Separation Logic (Proofmode)

- ▶ “Extensible Modal Framework for Interactive Proofs (in Separation Logic)”
- ▶ Foundation for the Iris Proof Mode (facilitating 150+ papers since 2015)
- ▶ Now also foundation for the Modal Temporal Logic Proofmode

## Key features of MoSeL

- ▶ Managed proof context for spatial and persistent propositions
- ▶ Extensible handling of modality-based reasoning via typeclasses
- ▶ Least and greatest monotone fixpoint constructions
- ▶ (Opt-in) step-indexing and separation logic
- ▶ Coming to Lean!

## Key insights

- ▶ Modality laws of Iris modalities resemble LTL modalities
- ▶ Separation logic and other unused features do not interfere



# To Conclude

## More case studies

- ▶ Looking for input and collaboration opportunities

## More case studies

- ▶ Looking for input and collaboration opportunities

## Temporal logic beyond linear

- ▶ Computation tree logic (CTL)
- ▶ Branching time  $\mu$ -calculus  $\rightarrow$  derived LTL and CTL

## More case studies

- ▶ Looking for input and collaboration opportunities

## Temporal logic beyond linear

- ▶ Computation tree logic (CTL)
- ▶ Branching time  $\mu$ -calculus  $\rightarrow$  derived LTL and CTL

## Temporal separation logic

- ▶ Conceptually stimulating
- ▶ Practically unclear what it even means
- ▶ MoTeL might make it more feasible to test the waters

## **Support for mechanisation of temporal properties is warranted**

- ▶ Currently limited support
- ▶ ITP-level solution preserves small TCB

## **Support for mechanisation of temporal properties is warranted**

- ▶ Currently limited support
- ▶ ITP-level solution preserves small TCB

## **Modal temporal logic is suitable for interactive verification**

- ▶ Modal laws facilitate smooth proof flows

**Support for mechanisation of temporal properties is warranted**

- ▶ Currently limited support
- ▶ ITP-level solution preserves small TCB

**Modal temporal logic is suitable for interactive verification**

- ▶ Modal laws facilitate smooth proof flows

**MoSeL seems mature enough to handle new domain logics**

- ▶ Relatively easy to instantiate
- ▶ Framework can handle functionality beyond original intent
- ▶ I encourage trying it out!

$$\vdash \Box(\textit{Question} \rightarrow \circ \Diamond \textit{Answer})$$

Slides available at:



Rocq code available at:

