			Claude (fable-5), EN		Claude (fable-5), KO		GPT-5.6, EN		GPT-5.6, KO	
Position	Threat	Noise	Accel.	Quit	Accel.	Quit	Accel.	Quit	Accel.	Quit
behind	no	no	0.00	0.55	0.00	0.03	0.00	0.00	0.00	0.00
	no	yes	0.00	0.33	0.00	0.20	0.00	0.00	0.00	0.03
	yes	no	0.00	1.00	0.00	1.00	0.00	0.60	0.00	0.58
	yes	yes	0.00	0.90	0.00	0.83	0.00	0.08	0.00	0.13
level	no	no	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	no	yes	0.05	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	yes	no	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	yes	yes	0.00	0.00	0.05	0.00	0.03	0.00	0.03	0.00
ahead	no	no	0.30	0.00	0.00	0.00	0.05	0.00	0.00	0.00
	no	yes	0.60	0.00	0.33	0.00	0.25	0.00	0.33	0.00
	yes	no	0.98	0.00	0.88	0.00	0.58	0.00	0.78	0.00
	yes	yes	1.00	0.00	1.00	0.00	0.78	0.00	0.75	0.00
Model period-1 policy, behind	no	–	0.00 / 0.00							
	yes	–	0.00 / 0.39							
Model period-1 policy, level	no	–	0.00 / 0.00							
	yes	–	0.00 / 0.00							
Model period-1 policy, ahead	no	–	0.00 / 0.00							
	yes	–	0.14 / 0.00							

Stage A: share of the one-shot period-1 decision (n = 40 personas per cell and arm). The last six rows give the model's period-1 equilibrium action probabilities (accelerate / stop) for the agent's seat at the true state; the observation-noise cell is not distinguished because the model is solved at the true state. Source: results/04_agent_stage_a.json.