




Debug IN Connector




Analog Signal Connectors





I2C Connectors



Fan Connector




RS485 Connectors




Title			
Size	Number	Revision	
A			
Date:	8/29/2025	Sheet	of
File:	C:\Users\...\sheet2_connectors.SchDoc	Drawn By:	

Power Barrell Input




12V to 5V Buck Converter (3A)




Title		
Size	Number	Revision
A		
Date:	8/29/2025	Sheet of
File:	C:\Users\...\sheet4_power.SchDoc	Drawn By:


8-Channel ADC



RS485 Transceiver



Title		
Size	Number	Revision
A		
Date:	8/29/2025	Sheet of
File:	C:\Users\...\sheet3_data.SchDoc	Drawn By:



Comment	Description	Designator	Footprint	LibRef	Quantity
1.0uF	Capacitor, X7R, ±10%,	C1	CAPC1608X06L	C0603-1u0	1
12pF	Capacitor, NP0, ±2%,	C2, C3, C4, C5, C8, C11	CAPC1005X04L	C0402-12p	4
100nF	Capacitor, X7R, ±10%,	C6, C16	CAPC1005X04L	C0402-100n	2
Capacitor 100uF +/- 10% 6.3V 0805	Chip Capacitor, 100uF +/-20%, 6.3V, 0805, Thickness 1.45 mm	C7, C21, C28, C29, C33, C40, C45, C50	CAPC0805(2012)145, L	CMP-001-00054-4	8
Capacitor 22uF +/- 40% 16V 0805	Chip Capacitor, 22uF +/-40%, 16V, 0805, Thickness 1.45 mm	C9, C23, C30, C34, C41, C46, C51	CAPC0805(2012)145, L	CMP-001-00081-4	7
100pF	Capacitor, NP0, ±5%,	C10	CAPC1005X04L	C0402-100p	1
RLC	Not mounted	C12, C14	CAPC1005X04L-NC	C0402-RLC	2
0.0uF	Capacitor, NP0, ±5%,	C13	CAPC1005X04L	C0402-0.0u	1
1.2pF	Capacitor, NP0, ±0.1pF	C15	CAPC1005X04L	C0402-1.2p	1
10uF	Capacitor, XSR, ±20%,	C17, C24, C31, C35, C42, C47, C52	CAPC1608X06L	C0603-10u	7
4.7uF	Capacitor, X75, ±10%, 10V	C18, C25, C32, C36, C43, C48, C53	CAPC1608X06L	C0603-4u7-10V-X75	7
Capacitor 100 nF +/- 10% 50 V 0805	Chip Capacitor, 100 nF +/-10%, 50 V, 0805 (2012 Metric)	C19, C20, C44, C49	CAPC2013X95X50L10 T25	CMP-001-00018-6	4
UCD01020MML1G5	No Description Available	C22	PCAP_8x10- ELECT1_NCA	CMP-001-00083-1	1
C1210C107M4PACTU	SMD Common XSR, Ceramic, 100 uF, 20%, 16 VDC, XSR, SMD, MLCC, Temperature Stable, Class II, 1210	C26, C27	CAPC350280_280M_K EM	CMP-001-00126-1	2
Capacitor 10 uF +/- 10% 16 V 1206	Chip Capacitor, 10 uF, +/-10%, 16 V, 1206 (3216 Metric)	C37	CAPC3216X180X50N 20T25	CMP-001-00016-6	1
Capacitor 4.7uF +/- 40% 25V 0805	Chip Capacitor, 4.7uF +/-40%, 25V, 0805, Thickness 1.45 mm	C38	CAPC0805(2012)145, L	CMP-001-00089-4	1
Capacitor 1 uF +/- 10% 25 V 1206	Chip Capacitor, 1 uF, +/-10%, 25 V, 1206 (3216 Metric)	C39	CAPC3216X180X20M 20	CMP-001-00006-6	1
8130A-13-F	No Description Available	CR1	SDD_SMA_DIO	CMP-045-000000-1	1
SMA12CA	No Description Available	CR2, CR3, CR4	SMASeries_LTF	CMP-017-000000-1	3
LTST-C190AKT	LED Uni-Color Orange, 100 mW, 30 mA, -55 to 85 degC, 2-Pin SMD, RoHS, Tape and Reel	D51	LTST-C190AKT-2_V	CMP-007-00021-2	1
MM8130-2600	Coaxial Connector with Switch	J1	COAXIAL-SWF	MM8130-2600	1
SBH11-PBPC-D20-ST- BK	No Description Available	J2	CONN40_SBH11-PBPC- D20-ST-BK_SUL	CMP-010-000000-4	1
B4B-XH-A	Connector Header Through Hole 4 position 0.098 (2.50mm)	J3, J4, J5, J6, J7	JST_B4B-XH-A	CMP-002-00073-1	5
B5B-XH-A	Connector Header Through Hole 5 position 0.098 (2.50mm)	J8, J9, J10, J11	JST_B5B-XH-A	CMP-002-00076-1	4
B2B-XH-A		J12	JST_B2B-XH-A	CMP-032-000000-1	1
S5B-ZR-SMAA-TF LF SN	No Description Available	J13, J14, J15, J16	CONN_S5B-ZR-SMAA- TF_JST	CMP-091-000000-1	4
PJ-102BH	2.5 x 6.5 mm, 5.0 A, Horizontal, Through Hole, Tapered Pins, Dc Power Jack Connector	J17	CUL_PJ-102BH	CMP-002-00071-2	1
15uH	Inductor, 320mA, ±5%,	L1	INDC1005X04L	L0402-15n	1
10uH	Inductor, 80mA, ±10%,	L2	INDC1608X06L	L0603-10u	1
1.9uH	Inductor, 170mA, ±0.1nH	L3	INDC1005X04L	L0402-3n9	1
MWSA12065-101MT	3A 100uH ±20% 3.5A SMD, 13 x12.6mm Power Inductors ROHS	L4	MWSA12065-101MT- Footprint-1	CMP-006-00038-1	1
Pin Header 2x5, 1.27mm	Pin Header 2x5, 1.27mm (50mil), SMD, Keying Shrouded	P1	HDR_2x5-SMD- 1.27mm-K	Pin Header 2x5 SMD, 1.27mm, KS	1
S8050-J3Y	NPN SOT-23 Bipolar (BJT) ROHS	Q1	S8050-J3Y-Footprint-1	CMP-013-00038-1	1
Resistor 10k +/-1% 0402 63 mW	Chip Resistor, 10 kOhm, +/-1%, 63 mW, 55 to 155 degC, 0402 (1005 Metric)	R1, R2	RESC1005X40X25ML0 S105	CMP-009-00019-5	2
Resistor 120k +/-5 % 0403 0.1 W	Chip Resistor, 120 Ohms, +/-5 %, 0.1 W, 55 to 155 degC, 0403	R3, R7	RESC0403(1608)_L	CMP-009-00176-3	2
Resistor 2k2 +/-5 % 0402 63 mW	Chip Resistor, 2.2 kOhms, +/-5 %, 63 mW, 55 to 155 degC, 0402	R4	RESC0402(1005)_L	CMP-009-00166-3	1
Resistor 4k7 +/-1% 0402 100 mW	Chip Resistor, 4.7 kOhm, +/-1%, 0.1 W, 55 to 155 degC, 0402 (1005 Metric)	R5, R6, R8, R9	RESC1005X40X25ML0 S105	CMP-009-00030-5	4
Resistor 33R +/-5 % 0402 63 mW	Chip Resistor, 33 Ohms, +/-5 %, 63 mW, 55 to 155 degC, 0402	R10, R11, R12, R13	RESC0402(1005)_L	CMP-009-00143-4	4
Resistor 10K +/-1 % 0402 63 mW	Chip Resistor, 10 kOhms, +/-1 %, 63 mW, 55 to 125 degC, 0402	R15	RESC0402(1005)_L	CMP-009-00149-3	1
PTH-M205K5	M2 PTH (2.5mm), 5mm pad	ST1, ST2, ST3, ST4	PTH-M205K5	CMP-00028-00004-2	4
nRF52832-QFAAG0	MUFI-protocol Bluetooth Low Energy, ANT and 2.4GHz proprietary system-on-chip	U1	QFN40P600X600X90- 48N	nRF52832-QFAAG0	1
LM2576WU	No Description Available	U3	TO-263-5_U_MCH	CMP-035-000000-1	1
MCP3008T-I/SL	10-bit ADC, SPI, 8- channel 16 SOIC, 150m 17k	U5	SOIC127P600X175- 16N	CMP-021-000000-1	1
SP3485EN-L	No Description Available	U6	NSOIC8_MXL	CMP-014-000000-1	1
32MHz	XTAL SMD 2016, 32MHz, Cl=6pF, Tol: ±10ppm, Stab: ±10ppm	X1	BT-XTAL_2016	XTAL_SMD2016_32M Hz_6pF_Epson	1
32.768kHz	XTAL SMD 3215, 32.768kHz, 9pF, ±20ppm	X2	XTAL_3215	XTAL_SMD3215_32.7 68kHz_9pF_Epson	1