

Topological, Automata-Theoretic and Logical Characterizations of Finitary Languages

Presentation for YR-CONCUR 2010

Who? Krishnendu Chatterjee & Nathanaël Fijalkow

From? IST Austria (Institute of Science and Technology, Austria)

When? September 4th, 2010

Introduction: system specification

- non-terminating (e.g web server);
- discrete time;
- non-deterministic.

Introduction: system specification

- non-terminating ;
 - discrete time;
 - non-deterministic.
-
- a finite alphabet Σ represent propositions;
(e.g "available", "waiting", "critical error")

Introduction: system specification

- non-terminating ;
 - discrete time;
 - non-deterministic.
-
- a finite alphabet Σ represent propositions;
 - runs are infinite words: $w = w_0 \cdot w_1 \dots w_n \dots \in \Sigma^\omega$;
 - specification given as a language $L \subseteq \Sigma^\omega$;

Introduction: system specification

- non-terminating ;
- discrete time;
- non-deterministic.

- a finite alphabet Σ represent propositions;
- runs are infinite words: $w = w_0 \cdot w_1 \dots w_n \dots \in \Sigma^\omega$;
- specification given as a language $L \subseteq \Sigma^\omega$;
- ω -regular language: safety + liveness;
- liveness properties: "something good happens eventually".

Outline

Motivations

Characterizations

Expressions

Classical liveness properties

A first example, Büchi:

- a given set of propositions appears infinitely often;
(e.g. "job done")

Classical liveness properties


A first example, Büchi:

- a given set of propositions appears infinitely often;


A second example, parity:

- integers are assigned to propositions, representing a priority;
- along an execution, some integers appear infinitely often;
- parity specifies that the least priority appearing infinitely often is even.

A drawback of classical ω -regular specifications




A drawback of classical ω -regular specifications



Specification: Büchi with $F = \{v_{2^k} \mid k \in \mathbb{N}\}$.

A drawback of classical ω -regular specifications



Specification: Büchi with $F = \{v_{2^k} \mid k \in \mathbb{N}\}$.

Satisfied, but the time until something good happens may grow unbounded!

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an unknown, fixed bound b such that something good happens within b transitions.

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an **unknown**, fixed bound b such that something good happens within b transitions.

unknown: retain independence from granularity.

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an unknown, fixed bound b such that something good happens within b transitions.

It can be expressed as a finitary operator on languages:

$$\text{fin}(L) = \bigcup \{M \mid M \text{ closed and } \omega\text{-regular}, M \subseteq L\}$$

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an unknown, fixed bound b such that something good happens within b transitions.

It can be expressed as a finitary operator on languages:

$$\text{fin}(L) = \bigcup \{M \mid M \text{ closed and } \omega\text{-regular}, M \subseteq L\}$$

- closed: involves Cantor topology;
- ω -regular: involves ω -regularity;

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an unknown, fixed bound b such that something good happens within b transitions.


It can be expressed as a finitary operator on languages:

$$\text{fin}(L) = \bigcup \{M \mid M \text{ closed and } \omega\text{-regular}, M \subseteq L\}$$

- closed: involves Cantor topology;
- ω -regular: involves ω -regularity;
- restriction operator: $\text{fin}(L) \subseteq L$.

Back to the example

Finitary Büchi: $F = \{v_{2^k} \mid k \in \mathbb{N}\}$



Not satisfied!

Outline

Motivations

Characterizations

Expressions

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

$\text{Inf}(w)$ is the set of propositions that appear infinitely often in w .

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

We define:

$$\text{next}_k(w, F) = \inf\{k' - k \mid k' \geq k, w_{k'} \in F\}$$

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

We define:

$$\text{next}_k(w, F) = \inf\{k' - k \mid k' \geq k, w_{k'} \in F\}$$

$$w = v_0 \dots v_k \underbrace{v_{k+1} \dots v_{k'-1}}_{\notin F} \underbrace{v_{k'}}_{\in F}$$

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

We define:

$$\text{next}_k(w, F) = \inf\{k' - k \mid k' \geq k, w_{k'} \in F\}$$

Lemma

$$\text{fin}(\text{Büchi}(F)) = \{w \mid \limsup_k \text{next}_k(w, F) < \infty\}$$

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

We define:

$$\text{next}_k(w, F) = \inf\{k' - k \mid k' \geq k, w_{k'} \in F\}$$

Lemma

$$\begin{aligned} \text{fin}(\text{Büchi}(F)) = \\ \{w \mid \exists B \in \mathbb{N}, \exists n \in \mathbb{N}, \forall k \geq n, \text{next}_k(w, F) \leq B\} \end{aligned}$$

Describing classical finitary objectives: parity

Let $p : \Sigma \rightarrow \mathbb{N}$ a priority function,

$$\text{Parity}(p) = \{w \mid \min(p(\text{Inf}(w))) \text{ is even}\}$$

Describing classical finitary objectives: parity

Let $p : \Sigma \rightarrow \mathbb{N}$ a priority function,

$$\text{Parity}(p) = \{w \mid \min(p(\text{Inf}(w))) \text{ is even}\}$$

We define:

$$\text{dist}_k(w, p) = \inf\{k' - k \mid \begin{array}{l} k' \geq k, p(w_{k'}) \text{ even and} \\ p(w_{k'}) \leq p(w_k) \end{array}\}$$

Describing classical finitary objectives: parity

Let $p : \Sigma \rightarrow \mathbb{N}$ a priority function,

$$\text{Parity}(p) = \{w \mid \min(p(\text{Inf}(w))) \text{ is even}\}$$

We define:

$$\text{dist}_k(w, p) = \inf\{k' - k \mid \begin{array}{l} k' \geq k, p(w_{k'}) \text{ even and} \\ p(w_{k'}) \leq p(w_k) \end{array}\}$$

Lemma

$$\text{fin}(\text{Parity}(p)) = \{w \mid \limsup_k \text{dist}_k(w, p) < \infty\}$$

Topological characterization

Theorem *Büchi(F) is Π_2 -complete.*
Parity lies in the boolean closure of Σ_2 and Π_2 .

Topological characterization

Theorem *Büchi(F) is Π_2 -complete.*

Parity lies in the boolean closure of Σ_2 and Π_2 .

Theorem

1 *For all $p : \Sigma \rightarrow \mathbb{N}$, we have $\text{fin}(\text{Parity}(p)) \in \Sigma_2$.*

2 *For all $\emptyset \subset F \subset \Sigma$, we have that $\text{fin}(\text{Büchi}(F))$ is Σ_2 -complete.*

3 *There exists $p : \Sigma \rightarrow \mathbb{N}$ such that $\text{fin}(\text{Parity}(p))$ is Σ_2 -complete.*


Automata-theoretic characterization

We consider automata on infinite words, whose acceptance conditions are finitary Büchi and finitary parity.

Automata-theoretic characterization

We consider automata on infinite words, whose acceptance conditions are finitary Büchi and finitary parity.

$$\left\{ \begin{array}{c} D \\ N \end{array} \right\} \cdot \left\{ \begin{array}{c} \varepsilon \\ F(\textit{finitary}) \end{array} \right\} \cdot \left\{ \begin{array}{c} B(\textit{Büchi}) \\ P(\textit{parity}) \end{array} \right\}$$



Outline

Motivations

Characterizations

Expressions

ω -regular expressions

Regular expressions defines regular languages over finite words:

$$L := \emptyset \mid \varepsilon \mid \sigma \mid L \cdot L \mid L^* \mid L + L; \quad \sigma \in \Sigma$$

ω -regular languages are finite union of $L \cdot L'^\omega$, where L and L' are regular languages of finite words.

The bound operator B [BC06]

$$L^\omega = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid u_0, u_1, \dots, u_k, \dots \in L\}$$

The bound operator B [BC06]

$$L^\omega = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid u_0, u_1, \dots, u_k, \dots \in L\}$$

$$L^B = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid \begin{array}{l} u_0, u_1, \dots, u_k, \dots \in L \\ \text{and } (|u_n|)_{n \in \mathbb{N}} \text{ is bounded} \end{array} \}$$

The bound operator B [BC06]

$$L^\omega = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid u_0, u_1, \dots, u_k, \dots \in L\}$$

$$L^B = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid \begin{array}{l} u_0, u_1, \dots, u_k, \dots \in L \\ \text{and } (|u_n|)_{n \in \mathbb{N}} \text{ is bounded} \end{array} \}$$

(complete definitions require the use of infinite sequences of finite words)

Star-free ωB -regular expressions

Star-free ωB -regular languages are finite union of $L \cdot M^\omega$,
where

- L is a regular language over finite words;
- M is a star-free B -regular language over infinite words.

Star-free ωB -regular expressions

Star-free ωB -regular languages are finite union of $L \cdot M^\omega$,
where

- L is a regular language over finite words;
- M is a star-free B -regular language over infinite words.

Star-free B -regular languages are described by the
grammar:

$$M := \emptyset \mid \varepsilon \mid \sigma \mid M \cdot M \mid M^B \mid M + M; \quad \sigma \in \Sigma$$

Star-free ωB -regular expressions

Star-free ωB -regular languages are finite union of $L \cdot M^\omega$, where

- L is a regular language over finite words;
- M is a star-free B -regular language over infinite words.

Star-free B -regular languages are described by the grammar:

$$M := \emptyset \mid \varepsilon \mid \sigma \mid M \cdot M \mid M^B \mid M + M; \quad \sigma \in \Sigma$$

Theorem *NFP (non-deterministic finitary parity) has exactly the same expressive power as star-free ωB -regular expressions.*

Conclusion

- finitary objectives is a refinement for specification purposes;
- for ω -regular languages, topological, logical and automata-theoretic characterizations were known;
- for finitary languages, all were missing; we established:
 - topological characterization;
 - automata-theoretic characterization, comparison to ω -regular languages, closure properties;
 - logical characterization using by ωB -regular expressions.

Conclusion

- finitary objectives is a refinement for specification purposes;
- for ω -regular languages, topological, logical and automata-theoretic characterizations were known;
- for finitary languages, all were missing; we established:
 - topological characterization;
 - automata-theoretic characterization, comparison to ω -regular languages, closure properties;
 - logical characterization using by ωB -regular expressions.

Future work:

- algorithmic issues: equivalence with ωB -regular expressions, emptiness problem of finitary automata;
- a tool for finitary objectives...

Bibliography



R. Alur and T.A. Henzinger.

Finitary fairness.

In *LICS'94*, pages 52–61. IEEE, 1994.



Mikolaj Bojańczyk and Thomas Colcombet.

Bounds in ω -regularity.

In *LICS'06*, pages 285–296. IEEE, 2006.

The end

Thank you for your attention!