


# Playing Safe


FSTTCS'2014

Thomas Colcombet, Nathanaël Fijalkow and Florian Horn

Delhi, India

December 16th, 2014







controlled by Eve



controlled by Adam






controlled by Eve




controlled by Adam




controlled by Eve



controlled by Adam





controlled by Eve



controlled by Adam

$$W \subseteq \{a, b\}^\omega$$



# Strategy (for Eve)

General form

$$\sigma : V^+ \rightarrow V$$

General form

$$\sigma : V^+ \rightarrow V$$

Positional or memoryless

$$\sigma : V \rightarrow V$$

General form

$$\sigma : V^+ \rightarrow V$$

Positional or memoryless

$$\sigma : V \rightarrow V$$

Finite-memory

$$\begin{cases} \sigma : V \times M \rightarrow V \\ \mu : M \times E \rightarrow M \end{cases}$$

# How much memory is needed to win?

Let  $W \subseteq A^\omega$ , compute:

$$\text{mem}(W) \doteq \sup_{\mathcal{G}=(\mathcal{A},W) \text{ game}} \inf_{\substack{\sigma \text{ winning} \\ \text{strategy}}} \text{mem}(\sigma) .$$

# How much memory is needed to win?

Let  $W \subseteq A^\omega$ , compute:


$$\text{mem}(W) \doteq \sup_{\mathcal{G}=(\mathcal{A},W) \text{ game}} \inf_{\substack{\sigma \text{ winning} \\ \text{strategy}}} \text{mem}(\sigma) .$$

Equivalently:

- *upper bound*: for all games  $\mathcal{G} = (\mathcal{A}, W)$ , if Eve has a winning strategy, then she has a winning strategy using at most  $\text{mem}(W)$  memory states,
- *lower bound*: there exists a game  $\mathcal{G} = (\mathcal{A}, W)$  where Eve has a winning strategy, but no winning strategy using less than  $\text{mem}(W)$  memory states.


# A Simple Example

arena




winning condition

$$W = a^+ \cdot b$$




# A Simple Example

arena




winning condition

$$W = a^+ \cdot b$$




# A Simple Example

5




A winning strategy for Eve uses two memory states.






# A Simple Example

5




A winning strategy for Eve uses two memory states.




# A Simple Example

5



A winning strategy for Eve uses two memory states.



# What is Known about Computing $\text{mem}(W)$

Theorem (Dziembowski, Jurdziński, Walukiewicz, 1997)

*For  $W$  a boolean combination of “infinitely many  $a \in A$ ”,  $\text{mem}(W)$  is computable (and characterized through the Zielonka tree).*

Theorem (Kopczyński, 2007)

*For  $W$  which is  $\omega$ -regular,  $\text{mem}_{\text{chromatic}}(W)$  is computable.*

# What is Known about Computing $\text{mem}(W)$

Theorem (Dziembowski, Jurdziński, Walukiewicz, 1997)

*For  $W$  a boolean combination of “infinitely many  $a \in A$ ”,  $\text{mem}(W)$  is computable (and characterized through the Zielonka tree).*

Theorem (Kopczyński, 2007)

*For  $W$  which is  $\omega$ -regular,  $\text{mem}_{\text{chromatic}}(W)$  is computable.*

Conjecture (Kopczyński, 2008)

*For  $W$  which is  $\omega$ -regular,  $\text{mem}_{\text{chromatic}}(W) = \text{mem}(W)$ .*

$\text{Res}(W)$  is the set of residuals of  $W$ : for  $u \in \Sigma^*$ ,

$$u^{-1}W = \{v \mid u \cdot v \in W\}.$$

Theorem (Colcombet, F., Horn)

*For all safety conditions  $W$ ,  
 $\text{mem}(W)$  is the width of  $(\text{Res}(W), \subseteq)$ ,  
i.e. the size of the largest antichain.*

$\text{Res}(W)$  is the set of residuals of  $W$ : for  $u \in \Sigma^*$ ,

$$u^{-1}W = \{v \mid u \cdot v \in W\}.$$

Theorem (Colcombet, F., Horn)

*For all safety conditions  $W$ ,  
 $\text{mem}(W)$  is the width of  $(\text{Res}(W), \subseteq)$ ,  
i.e. the size of the largest antichain.*

- We make no regularity assumption!
- This holds for infinite arenas of finite degree.

The memory structure  $\mathcal{M}_W$  uses  $\text{Res}(W)$  as set of memory states, and:

- the initial memory state is  $\varepsilon^{-1}W = W$ ,
- each time a letter  $a$  is read from  $u^{-1}W$ , the memory is updated to  $(u \cdot a)^{-1}W$ .

# An upper bound

The memory structure  $\mathcal{M}_W$  uses  $\text{Res}(W)$  as set of memory states, and:

- the initial memory state is  $\varepsilon^{-1}W = W$ ,
- each time a letter  $a$  is read from  $u^{-1}W$ , the memory is updated to  $(u \cdot a)^{-1}W$ .

**Lemma (An upper bound)**

*For all games  $\mathcal{G} = (\mathcal{A}, W)$ , Eve has a winning strategy using  $\mathcal{M}_W$ .*



## Another example

“read at most ten consecutive  $a$ ’s, and then an  $b$ ”.

$$W = a + b \cdot a + bb \cdot a + \dots + b^{10} \cdot a.$$

“read at most ten consecutive  $a$ ’s, and then an  $b$ ”.

$$W = a + b \cdot a + bb \cdot a + \dots + b^{10} \cdot a.$$

In every game with condition  $W$ , Eve wins without memory.

“read at most ten consecutive  $a$ ’s, and then an  $b$ ”.

$$W = a + b \cdot a + bb \cdot a + \dots + b^{10} \cdot a.$$

In every game with condition  $W$ , Eve wins without memory.

↪ This shows that the memory structure  $\mathcal{M}_W$  is not optimal.

## Order left quotients inclusion-wise

If Eve wins from  $(q, u^{-1}L)$  and  $u^{-1}L \subseteq v^{-1}L$ , then she wins from  $(q, v^{-1}L)$

If Eve wins from  $(q, u^{-1}L)$  and  $u^{-1}L \subseteq v^{-1}L$ , then she wins from  $(q, v^{-1}L)$  *using the same strategy*.

If Eve wins from  $(q, u^{-1}L)$  and  $u^{-1}L \subseteq v^{-1}L$ , then she wins from  $(q, v^{-1}L)$  *using the same strategy*.

Intuition: whenever in  $(q, v^{-1}L)$ , play as from  $(q, u^{-1}L)$ , where  $u^{-1}L$  is minimally winning from  $q$ .

If Eve wins from  $(q, u^{-1}L)$  and  $u^{-1}L \subseteq v^{-1}L$ , then she wins from  $(q, v^{-1}L)$  *using the same strategy*.

Intuition: whenever in  $(q, v^{-1}L)$ , play as from  $(q, u^{-1}L)$ , where  $u^{-1}L$  is minimally winning from  $q$ .

Problems:

- there may not exist minimally winning left quotients!
- winning or losing depends on the current position, which makes updating the memory state not trivial.

Theorem (Colcombet, F., Horn)

*For all safety conditions  $W$ ,  
 $\text{mem}(W)$  is the width of  $(\text{Res}(W), \subseteq)$ ,  
i.e. the size of the largest antichain.*



## Theorem (Colcombet, F., Horn)

*For all safety conditions  $W$ ,  
 $\text{mem}(W)$  is the width of  $(\text{Res}(W), \subseteq)$ ,  
i.e. the size of the largest antichain.*

- Fails for infinite arenas of infinite degree.
- Unifies several results from the literature: boundedness condition, energy condition, generalized reachability.

The end

Thanks!