

# Emptiness Of Alternating Tree Automata Using Games With Imperfect Information

Nathanaël Fijalkow   Olivier Serre   Sophie Pinchinat

Institute of Informatics, Warsaw University – Poland

LIAFA, Université Paris 7 Denis Diderot – France

FSTTCS, December 13th, 2013

# Objectives


This talk is about *one* approach to deal with alternating tree automata.

This talk is about *one* approach to deal with alternating tree automata.

We consider two settings: the first is “classical”, the second is “qualitative”.


# Alternating tree automata: a powerful tool

- *What is it?* A finite-state machine that defines a property, given as a set of infinite (binary) trees.



# Alternating tree automata: a powerful tool

- *What is it?* A finite-state machine that defines a property, given as a set of infinite (binary) trees.




- *What for?* Define **regular** properties, used for instance for program verification.

# Definition of alternating tree automata (1/2)

$$\mathcal{A} = (Q, Q_{\exists}, Q_{\forall}, q_0, \delta, \text{Parity})$$

The transition relation  $\delta \subseteq Q \times A \times Q \times Q$  gives local constraints:



$$(q, a, p, r) \in \delta$$

$$(p, b, q, q) \in \delta$$

$$(r, a, p, r) \in \delta$$

Let  $\mathcal{A}$  be an alternating automaton and  $t$  a tree.

This induces a two-player zero-sum game, where Eve tries to show that the tree is accepted:

- Eve picks the transitions from  $Q_{\exists}$ ,
- Adam picks the transitions from  $Q_{\forall}$ ,
- Adam also chooses directions.

Let  $\mathcal{A}$  be an alternating automaton and  $t$  a tree.

This induces a two-player zero-sum game, where Eve tries to show that the tree is accepted:

- Eve picks the transitions from  $Q_{\exists}$ ,
- Adam picks the transitions from  $Q_{\forall}$ ,
- Adam also chooses directions.

*Classical* versus *Qualitative* semantics:

- $\mathcal{A}$  accepts  $t$  if Eve has a strategy such that **all plays** consistent with the strategy are winning.
- $\mathcal{A}$  qualitatively accepts  $t$  if Eve has a strategy such that **almost all plays** consistent with the strategy are winning.



- $L(\mathcal{A})$  is the set of trees accepted by  $\mathcal{A}$ .
- $L^=1(\mathcal{A})$  is the set of trees qualitatively accepted by  $\mathcal{A}$ .

- $L(\mathcal{A})$  is the set of trees accepted by  $\mathcal{A}$ .
- $L^{=1}(\mathcal{A})$  is the set of trees qualitatively accepted by  $\mathcal{A}$ .
  
- $\{L(\mathcal{A}) \mid \mathcal{A}\}$  describes the class of regular languages.
- $\{L^{=1}(\mathcal{A}) \mid \mathcal{A}\}$  describes the class of qualitative regular languages.

# The emptiness problem

**Input:** An alternating automaton  $\mathcal{A}$

**Output:** Is  $L(\mathcal{A})$  empty?

**Input:** An alternating automaton  $\mathcal{A}$

**Output:** Is  $L(\mathcal{A})$  empty?

## Theorem (Müller and Schupp)

*The emptiness problem for alternating parity automata with the classical semantics is EXPTIME-complete.*

## Theorem (Our paper)

- *The emptiness problem for alternating Büchi automata with the qualitative semantics is EXPTIME-complete.*
- *The emptiness problem for alternating CoBüchi automata with the qualitative semantics is undecidable.*

# The emptiness problem

**Input:** An alternating automaton  $\mathcal{A}$

**Output:** Is  $L(\mathcal{A})$  empty?

## Theorem (Müller and Schupp)

*The emptiness problem for alternating parity automata with the classical semantics is EXPTIME-complete.*

## Theorem (Our paper)

- *The emptiness problem for alternating Büchi automata with the qualitative semantics is EXPTIME-complete.*
- *The emptiness problem for alternating CoBüchi automata with the qualitative semantics is undecidable.*

We use a different technique, through games of imperfect information.

- 1 Introduction
- 2 A solution through the simulation technique (Müller and Schupp)
- 3 A different technique through games of imperfect information

Let  $\mathcal{A}$  be an alternating automaton.

- ① simulation: construct an equivalent non-deterministic automaton  $\mathcal{B}$  (*i.e.* where  $Q_{\forall} = \emptyset$ ),
- ② solve the emptiness problem for  $\mathcal{B}$ .

Let  $\mathcal{A}$  be an alternating automaton.

- ① simulation: construct an equivalent non-deterministic automaton  $\mathcal{B}$  (i.e. where  $Q_{\forall} = \emptyset$ ),
- ② solve the emptiness problem for  $\mathcal{B}$ .

The emptiness problem for non-deterministic automata reduces to solving a two-player game, where Eve tries to show that there exists an accepted tree:

- Eve picks the tree  $t$  and the transitions,
- Adam only chooses directions.



- Can we directly reduce the emptiness problem for alternating automata to solving a two-player game?
- How to handle the qualitative semantics, for which no simulation is known?

In the naively extended previous game, Eve can cheat if she sees what Adam is doing!

In the naively extended previous game, Eve can cheat if she sees what Adam is doing!

Consider a universal word automaton where Adam can:

- ① check that the word contains a  $b$ ,
- ② or check that the word does not contain any  $b$

The language accepted is empty but Eve can wait to see whether Adam chooses option 1 or 2 and pick the next letters to contradict Adam's choice.

- 1 Introduction
- 2 A solution through the simulation technique (Müller and Schupp)
- 3 A different technique through games of imperfect information

We directly reduce the emptiness problem for alternating automata to solving a two-player imperfect-information game, where Eve tries to show that there exists an accepted tree:

- Eve picks the tree  $t$  *and* a positional strategy for her transitions,
- Adam chooses transitions and directions.
- Eve does not see what Adam does!

We directly reduce the emptiness problem for alternating automata to solving a two-player imperfect-information game, where Eve tries to show that there exists an accepted tree:

- Eve picks the tree  $t$  and a positional strategy for her transitions,
- Adam chooses transitions and directions.
- Eve does not see what Adam does!

The new key technical ingredient is a positional determinacy theorem for infinite (chronological) arenas:

## Theorem

*If Eve has an almost surely winning strategy for Büchi, then she has a positional one.*

To solve the emptiness problem of alternating automata with a semantics  $Acc$ , one can reduce it to a two-player imperfect-information game, and:

- ① to prove the construction correctness, show a positional determinacy result for  $Acc$ ,
- ② solve the obtained imperfect-information game with winning condition  $Acc$ .

To solve the emptiness problem of alternating automata with a semantics  $Acc$ , one can reduce it to a two-player imperfect-information game, and:

- ① to prove the construction correctness, show a positional determinacy result for  $Acc$ ,
- ② solve the obtained imperfect-information game with winning condition  $Acc$ .

Thank you!