

Cost-parity games and Cost-Streett games

FSTTCS'2012

Nathanaël Fijalkow, Martin Zimmermann

Institute of Informatics, Warsaw University – Poland

LIAFA, Université Paris 7 Denis Diderot – France

December 15th, 2012

Cost-parity games ~~and Cost Streett games~~

FSTTCS'2012

Nathanaël Fijalkow, Martin Zimmermann

Institute of Informatics, Warsaw University – Poland

LIAFA, Université Paris 7 Denis Diderot – France

December 15th, 2012

This paper is about two-player games over finite graphs,
as used in automata theory and verification (synthesis problem).

We are after efficient algorithms to:

- decide the winner, *and*
- synthesize a winning strategy.


This paper is about two-player games over finite graphs,
as used in automata theory and verification (synthesis problem).

We are after efficient algorithms to:

- decide the winner, *and*
- synthesize a winning strategy.

Starting point: good understanding of ω -regular specifications.


Objective: add boundedness specifications.



controlled by Eve




controlled by Adam



controlled by Eve




controlled by Adam



controlled by Eve




controlled by Adam



controlled by Eve




controlled by Adam



controlled by Eve



controlled by Adam





controlled by Eve




controlled by Adam

Parity conditions



Almost all requests are answered.

Parity conditions



- Parity conditions allow to express all ω -regular specifications.
- Both players have positional winning strategies.
- Deciding the winner is in $\text{NP} \cap \text{coNP}$.

Finitary specifications: proposed by Alur and Henzinger, games studied by Chatterjee, Henzinger and Horn.

Parity:

Almost all requests are answered.

Finitary parity:


There exists a bound b , s.t. almost all requests are answered *within b steps*.

Parity:

Almost all requests are answered.

Finitary parity:

There exists a bound b , s.t. almost all requests are answered *within b steps*.



Eve wins for the parity condition,

but loses for the finitary parity condition!

Parity:

Almost all requests are answered.


- Both players have positional winning strategies.
- Deciding the winner is in $\text{NP} \cap \text{coNP}$.

Finitary parity:

There exists a bound b , s.t. almost all requests are answered *within b steps*.

- Eve has positional winning strategies.
- Adam needs infinite memory.
- Deciding the winner is in PTIME.

Cost-parity games



Parity:

Almost all requests are answered.

Finitary parity:

There exists a bound b , s.t.
almost all requests are
answered *within b steps*.

Parity:


Almost all requests are answered.

Finitary parity:


There exists a bound b , s.t.
almost all requests are answered *within b steps*.

Cost-parity:


There exists a bound b , s.t.
almost all requests are answered *with cost at most b* .



Parity game



Finitary parity game



Objective: **strategy optimization**

Assume σ is a winning strategy.

How to construct a memoryless winning strategy σ' from σ ?

Objective: **strategy optimization**

Assume σ is a winning strategy.

How to construct a memoryless winning strategy σ' from σ ?

Tool: **scoring functions**

“à la Müller and Schupp” past-oriented proof

A general framework



Consider a winning strategy $\sigma : V^* \rightarrow V$.

Define a scoring function $\text{Sc} : V^* \rightarrow (S, \leq)$ satisfying:

A general framework

Consider a winning strategy $\sigma : V^* \rightarrow V$.

Define a scoring function $\text{Sc} : V^* \rightarrow (S, \leq)$ satisfying:

- ① (S, \leq) is a total order and Sc is a congruence:
if $\text{Sc}(w) \leq \text{Sc}(w')$, then $\text{Sc}(w \cdot v) \leq \text{Sc}(w' \cdot v)$.

A general framework

Consider a winning strategy $\sigma : V^* \rightarrow V$.

Define a scoring function $\text{Sc} : V^* \rightarrow (S, \leq)$ satisfying:

- ① (S, \leq) is a total order and Sc is a congruence:
if $\text{Sc}(w) \leq \text{Sc}(w')$, then $\text{Sc}(w \cdot v) \leq \text{Sc}(w' \cdot v)$.
- ② If there exists a bound b such that the scores of all prefixes of a play ρ are bounded by b , then ρ is winning.

A general framework

Consider a winning strategy $\sigma : V^* \rightarrow V$.

Define a scoring function $\text{Sc} : V^* \rightarrow (S, \leq)$ satisfying:

- ① (S, \leq) is a total order and Sc is a congruence:
if $\text{Sc}(w) \leq \text{Sc}(w')$, then $\text{Sc}(w \cdot v) \leq \text{Sc}(w' \cdot v)$.
- ② If there exists a bound b such that the scores of all prefixes of a play ρ are bounded by b , then ρ is winning.
- ③ Assume a play ρ is consistent with σ , then the scores of all prefixes of ρ are (uniformly) bounded.

A general framework

Consider a winning strategy $\sigma : V^* \rightarrow V$.

Define a scoring function $\text{Sc} : V^* \rightarrow (S, \leq)$ satisfying:

- ① (S, \leq) is a total order and Sc is a congruence:
if $\text{Sc}(w) \leq \text{Sc}(w')$, then $\text{Sc}(w \cdot v) \leq \text{Sc}(w' \cdot v)$.
- ② If there exists a bound b such that the scores of all prefixes of a play ρ are bounded by b , then ρ is winning.
- ③ Assume a play ρ is consistent with σ , then the scores of all prefixes of ρ are (uniformly) bounded.

Construct a memoryless strategy σ' :

“play according to σ assuming the worst play prefix”.

Deciding the winner in cost-parity games



n : number of vertices

m : number of edges

d : number of colors

Theorem

*Given a parity games solver of complexity $T(n, m, d)$,
there exists a cost-parity games solver of complexity*

$$O(n \cdot T(n \cdot d, m \cdot d, d + 2)) .$$

winning condition	complexity	Eve	Adam
parity	$\text{NP} \cap \text{coNP}$	memoryless	memoryless
finitary parity	PTIME	memoryless	infinite
cost-parity	$\text{NP} \cap \text{coNP}$	memoryless	infinite
Streett	coNP-complete	finite	memoryless
finitary Streett	EXPTIME-complete	finite	infinite
cost-Streett	EXPTIME-complete	finite	infinite

