

Boundedness Games

Séminaire de l'équipe MoVe, LIF,
Marseille, May 2nd, 2013

Nathanaël Fijalkow

Institute of Informatics, Warsaw University – Poland


LIAFA, Université Paris 7 Denis Diderot – France

(based on joint works with Krishnendu Chatterjee, Thomas Colcombet,
Florian Horn and Martin Zimmermann)

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



controlled by Eve




controlled by Adam

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



controlled by Eve




controlled by Adam


Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs




Two-player turn-based games over **finite** or **infinite** graphs



Definition of ωB -games

1


Two-player turn-based games over **finite** or **infinite** graphs



Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



controlled by Eve




controlled by Adam

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs




ωB winning condition:

parity
and
all counters
are bounded

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs




parity condition:

the minimal priority
seen infinitely often
is even

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



$$c_1 = 0$$

$$c_2 = 0$$

ϵ : nothing


i : increment

r : reset

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



$$c_1 = 0$$

$$c_2 = 0$$

ϵ : nothing


i : increment

r : reset

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



$$c_1 = 0$$

$$c_2 = 1$$

ϵ : nothing


i : increment

r : reset

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



$$c_1 = 0$$

$$c_2 = 1$$

ϵ : nothing


i : increment

r : reset

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



$$c_1 = 1$$

$$c_2 = 0$$

ε : nothing


i : increment

r : reset

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



$$c_1 = 1$$

$$c_2 = 0$$

ϵ : nothing


i : increment

r : reset

Definition of ωB -games

1

Two-player turn-based games over **finite** or **infinite** graphs



ωB winning condition:

parity
and
all counters
are bounded

Strategy (for Eve)

2

General form

$$\sigma : V^+ \rightarrow V$$

Strategy (for Eve)

General form

$$\sigma : V^+ \rightarrow V$$

Positional or memoryless

$$\sigma : V \rightarrow V$$

General form

$$\sigma : V^+ \rightarrow V$$

Positional or memoryless

$$\sigma : V \rightarrow V$$

Theorem (Müller and Schupp)

In parity games, both players have memoryless winning strategies.

General form

$$\sigma : V^+ \rightarrow V$$

Positional or memoryless

$$\sigma : V \rightarrow V$$

Theorem (Müller and Schupp)

In parity games, both players have memoryless winning strategies.

What about ωB games?

Strategy (for Eve)

General form

$$\sigma : V^+ \rightarrow V$$

Positional or memoryless

$$\sigma : V \rightarrow V$$

Theorem (Müller and Schupp)

In parity games, both players have memoryless winning strategies.

What about ωB games?

Finite-memory

$$\begin{cases} \sigma : V \times M \rightarrow V \\ \mu : M \times E \rightarrow M \end{cases}$$

Why finite-memory strategies?

Thomas Colcombet's habilitation:

le fait 2.22 et en deduire que la domination entre formules de la logique monadique de cost est décidable sur les arbres infinis. Ainsi, la conjecture 9.2 implique la conjecture 9.1.

En fait, il est possible de pointer avec encore plus de précision où se trouve la difficulté. Si l'on cherche à démontrer la conjecture 9.2, tout comme dans le cas des arbres finis, le point crucial est l'existence de stratégies gagnantes à mémoire finie. Il suffirait d'établir la conjecture suivante.

Conjecture 9.3. *Les objectifs $\text{hB} \wedge \text{parité}$ et $\neg \text{B} \wedge \text{parité}$ sont à \approx -mémoire finie, sur toutes les arènes/sur les arènes chronologiques/sur les arènes «arborescentes».*

Existence of finite-memory strategies in (some) boundedness games

⇒ Decidability of cost MSO over infinite trees

⇒ Decidability of the index of the non-deterministic Mostowski's hierarchy (open for 40 years)!

Quantification

Eve wins means:



$\exists \sigma$ (strategy for Eve),
 $\forall \pi$ (paths),
 $\exists N \in \mathbb{N}$,



$\exists \sigma$ (strategy for Eve),
 $\exists N \in \mathbb{N}$,
 $\forall \pi$ (paths),

π satisfies parity and each counter is bounded by N .

Quantification

Eve wins means:



$\exists \sigma$ (strategy for Eve),
 $\forall \pi$ (paths),
 $\exists N \in \mathbb{N}$,



$\exists \sigma$ (strategy for Eve),
 $\exists N \in \mathbb{N}$,
 $\forall \pi$ (paths),

π satisfies parity and each counter is bounded by N .

Is this:

- ① Equivalent?
- ② Decidable?

Eve wins means:



$\exists \sigma$ (strategy for Eve),
 $\forall \pi$ (paths),
 $\exists N \in \mathbb{N}$,



$\exists \sigma$ (strategy for Eve),
 $\exists N \in \mathbb{N}$,
 $\forall \pi$ (paths),

π satisfies parity and each counter is bounded by N .

Is this:

- ① Equivalent? Sometimes ...
- ② Decidable? Not always ...

The questions I am interested in

Boundedness games:

- ① Over finite graphs: decide the winner **efficiently** and construct **small** finite-memory strategies.

The questions I am interested in

Boundedness games:

- ① Over finite graphs: decide the winner **efficiently** and construct **small** finite-memory strategies.
 - \leadsto Cost-parity games [F. and Zimmermann, 2012].

The questions I am interested in

Boundedness games:

- ① Over finite graphs: decide the winner **efficiently** and construct **small** finite-memory strategies.
 \leadsto Cost-parity games [F. and Zimmermann, 2012].
- ② Over pushdown graphs: decide the winner and construct finite-memory strategies.

Boundedness games:

- ① Over finite graphs: decide the winner **efficiently** and construct **small** finite-memory strategies.
 \leadsto Cost-parity games [F. and Zimmermann, 2012].
- ② Over pushdown graphs: decide the winner and construct finite-memory strategies.
 \leadsto Pushdown ωB games [Chatterjee and F., 2013].

Boundedness games:

- ① Over finite graphs: decide the winner **efficiently** and construct **small** finite-memory strategies.
 \leadsto Cost-parity games [F. and Zimmermann, 2012].
- ② Over pushdown graphs: decide the winner and construct finite-memory strategies.
 \leadsto Pushdown ωB games [Chatterjee and F., 2013].
- ③ Over infinite graphs: prove the existence of finite-memory winning strategies.

Boundedness games:

- ① Over finite graphs: decide the winner **efficiently** and construct **small** finite-memory strategies.
↪ Cost-parity games [F. and Zimmermann, 2012].
- ② Over pushdown graphs: decide the winner and construct finite-memory strategies.
↪ Pushdown ωB games [Chatterjee and F., 2013].
- ③ Over infinite graphs: prove the existence of finite-memory winning strategies.
↪ Ongoing work with Thomas Colcombet and Florian Horn.

- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max


- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max


- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max



Eve needs some memory




Adam needs infinite memory




Adam needs infinite memory




Eve needs infinite memory



Eve needs infinite memory



Eve needs infinite memory



Conjecture (Thomas Colcombet's conjecture)

Over arbitrary graphs / chronological graphs / tree-like graphs,

*if Eve has a strategy ensuring $\text{Parity} \cap \text{Bound}(N)$,
then she has a finite-memory strategy (of size independent of N)
ensuring $\text{Parity} \cap \text{Bound}(\alpha(N))$.*

Conjecture (Thomas Colcombet's conjecture)

Over arbitrary graphs / chronological graphs / tree-like graphs,

*if Eve has a strategy ensuring $\text{Parity} \cap \text{Bound}(N)$,
then she has a finite-memory strategy (of size independent of N)
ensuring $\text{Parity} \cap \text{Bound}(\alpha(N))$.*

Theorem

The conjecture does not hold over arbitrary graphs.

Conjecture (Thomas Colcombet's conjecture)

Over arbitrary graphs / chronological graphs / tree-like graphs,

*if Eve has a strategy ensuring $\text{Parity} \cap \text{Bound}(N)$,
then she has a finite-memory strategy (of size independent of N)
ensuring $\text{Parity} \cap \text{Bound}(\alpha(N))$.*

Theorem


The conjecture does not hold over arbitrary graphs.

With some more effort:

Theorem

The conjecture does not hold over chronological graphs.

Potato-trees



- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max

A subclass of ωB conditions where the counters and parity are not independent.

A subclass of ωB conditions where the counters and parity are not independent.

Theorem

Over general graphs:

- *Eve has positional winning strategies in counting Büchi games.*
- *Eve has finite-memory winning strategies in finitary parity games.*

A subclass of ωB conditions where the counters and parity are not independent.

Theorem

Over general graphs:

- *Eve has positional winning strategies in counting Büchi games.*
- *Eve has finite-memory winning strategies in finitary parity games.*


In some sense, the class of counting conditions is the maximal subclass of ωB conditions for such results.

- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max

Some more examples (1)

13



Eve should maintain a low stack.

Theorem

For all pushdown games, the following are equivalent:

- $\exists \sigma$ (strategy for Eve), $\forall \pi$ (paths), $\exists N \in \mathbb{N}$,
 π satisfies parity and each counter is bounded by N .
- $\exists \sigma$ (strategy for Eve), $\exists N \in \mathbb{N}$, $\forall \pi$ (paths),
 π satisfies parity and **eventually** each counter is bounded by N .


Theorem

For all pushdown games, the following are equivalent:

- $\exists \sigma$ (strategy for Eve), $\forall \pi$ (paths), $\exists N \in \mathbb{N}$,
 π satisfies parity and each counter is bounded by N .
- $\exists \sigma$ (strategy for Eve), $\exists N \in \mathbb{N}$, $\forall \pi$ (paths),
 π satisfies parity and **eventually** each counter is bounded by N .



Counter-example for the general case



Eve wins but she does not know the bound!

- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max

Condition: parity and all counters are bounded.

Define:

- $\mathcal{W}_E(N)$ the set of vertices where Eve wins for the bound N .
- \mathcal{W}_E the set of vertices where Eve wins for some (non-uniform) bound.

Condition: parity and all counters are bounded.

Define:

- $\mathcal{W}_E(N)$ the set of vertices where Eve wins for the bound N .
- \mathcal{W}_E the set of vertices where Eve wins for some (non-uniform) bound.

Lemma

$$\textcircled{1} \quad \mathcal{W}_E(0) \subseteq \mathcal{W}_E(1) \subseteq \cdots \subseteq \mathcal{W}_E(N) \subseteq \mathcal{W}_E(N+1) \subseteq \cdots \subseteq \mathcal{W}_E.$$

Condition: parity and all counters are bounded.

Define:

- $\mathcal{W}_E(N)$ the set of vertices where Eve wins for the bound N .
- \mathcal{W}_E the set of vertices where Eve wins for some (non-uniform) bound.

Lemma

- ① $\mathcal{W}_E(0) \subseteq \mathcal{W}_E(1) \subseteq \dots \subseteq \mathcal{W}_E(N) \subseteq \mathcal{W}_E(N+1) \subseteq \dots \subseteq \mathcal{W}_E$.
- ② *There exists N such that $\mathcal{W}_E(N) = \mathcal{W}_E(N+1) = \dots$.*

Condition: parity and all counters are bounded.

Define:

- $\mathcal{W}_E(N)$ the set of vertices where Eve wins for the bound N .
- \mathcal{W}_E the set of vertices where Eve wins for some (non-uniform) bound.


Lemma

- ① $\mathcal{W}_E(0) \subseteq \mathcal{W}_E(1) \subseteq \dots \subseteq \mathcal{W}_E(N) \subseteq \mathcal{W}_E(N+1) \subseteq \dots \subseteq \mathcal{W}_E$.
- ② *There exists N such that $\mathcal{W}_E(N) = \mathcal{W}_E(N+1) = \dots$.*
- ③ *For such N , Adam wins from $V \setminus \mathcal{W}_E(N)$, hence $\mathcal{W}_E = \mathcal{W}_E(N)$.*

- 1 Finite-memory strategies
 - Some examples
 - Counting conditions


- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max

Some more examples (2)




Adam may use the stack as “credit”.

Some more examples (2)




Adam may use the stack as “credit”.

Some more examples (2)




Adam may use the stack as “credit”.

Some more examples (2)




Adam may use the stack as “credit”.

Some more examples (2)




Adam may use the stack as “credit”.

Some more examples (2)



Adam may use the stack as “credit”.

Some more examples (2)



Adam may use the stack as “credit”.

Condition: parity and all counters are bounded.

Define:

- $\mathcal{W}_E(N)$ the set of vertices where Eve wins for the bound N **in the limit**.
- \mathcal{W}_E the set of vertices where Eve wins for some (non-uniform) bound.

Condition: parity and all counters are bounded.

Define:

- $\mathcal{W}_E(N)$ the set of vertices where Eve wins for the bound N **in the limit**.
- \mathcal{W}_E the set of vertices where Eve wins for some (non-uniform) bound.

Proposition

- 1 $\mathcal{W}_E(0) \subseteq \mathcal{W}_E(1) \subseteq \dots \subseteq \mathcal{W}_E(N) \subseteq \mathcal{W}_E(N+1) \subseteq \dots \subseteq \mathcal{W}_E$.
- 2 *There exists N such that $\mathcal{W}_E(N) = \mathcal{W}_E(N+1) = \dots$.*
- 3 *For such N , Adam wins from $V \setminus \mathcal{W}_E(N)$, hence $\mathcal{W}_E = \mathcal{W}_E(N)$.*

Why is 2. true?



Theorem (derived from Serre)

*For all N , $\mathcal{W}_E(N)$ is a regular set of configurations, recognized by an alternating automaton of size $|Q|$ (**independent of N**).*

Theorem

For all pushdown games, the following are equivalent:

- $\exists \sigma$ (strategy for Eve), $\forall \pi$ (paths), $\exists N \in \mathbb{N}$,
 π satisfies parity and each counter is bounded by N .
- $\exists \sigma$ (strategy for Eve), $\exists N \in \mathbb{N}$, $\forall \pi$ (paths),
 π satisfies parity and **eventually** each counter is bounded by N .

Theorem

For all pushdown games, the following are equivalent:

- $\exists \sigma$ (strategy for Eve), $\forall \pi$ (paths), $\exists N \in \mathbb{N}$,
 π satisfies parity and each counter is bounded by N .
- $\exists \sigma$ (strategy for Eve), $\exists N \in \mathbb{N}$, $\forall \pi$ (paths),
 π satisfies parity and **eventually** each counter is bounded by N .

Corollary

Determining the winner in a pushdown ωB -game is decidable.

Theorem

For all pushdown games, the following are equivalent:

- $\exists \sigma$ (strategy for Eve), $\forall \pi$ (paths), $\exists N \in \mathbb{N}$,
 π satisfies parity and each counter is bounded by N .
- $\exists \sigma$ (strategy for Eve), $\exists N \in \mathbb{N}$, $\forall \pi$ (paths),
 π satisfies parity and **eventually** each counter is bounded by N .

Corollary

Determining the winner in a pushdown ωB -game is decidable.

Remark: one can show that the collapse bound is doubly-exponential!

- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max


The max operator


We add a new feature for counters: $\gamma \leftarrow \max(\gamma_1, \gamma_2)$.

Theorem (derived from Bojańczyk and Toruńczyk)

Deterministic max-automata are equivalent to Weak MSO + \mathbb{U} .

We consider ωB -games with max.





To prove that a counter value is high, one can count backwards!

We reduce ωB -games with max to pushdown ωB -games (without max).

We reduce ωB -games with max to pushdown ωB -games (without max).

Idea: simulate the game and store the play in the stack.

Whenever he wants, Adam can declare “this counter has a very large value”: from there, play backwards using the stack until a reset is met.

We reduce ωB -games with max to pushdown ωB -games (without max).

Idea: simulate the game and store the play in the stack.

Whenever he wants, Adam can declare “this counter has a very large value”: from there, play backwards using the stack until a reset is met.

Theorem

Determining the winner in an ωB -game with max is decidable.

The end.

Thank you!

- 1 Finite-memory strategies
 - Some examples
 - Counting conditions

- 2 Equivalence for pushdown ωB games
 - The case of finite graphs
 - The case of pushdown graphs
 - Application: ωB -games with max