

Finitary Languages

Presentation for LATA 2011

Krishnendu Chatterjee & Nathanaël Fijalkow

IST Austria (Institute of Science and Technology, Austria)

May 30th, 2011


Introduction: system specification

- non-terminating (*e.g* web server);
- discrete time;
- non-deterministic.


Introduction: system specification

- non-terminating;
 - discrete time;
 - non-deterministic.
-
- a finite alphabet Σ represent propositions;
(e.g “available”, “waiting”, “critical error”)
 - runs are infinite words $w = w_0 \cdot w_1 \dots w_n \dots \in \Sigma^\omega$;
 - specification given as a language $L \subseteq \Sigma^\omega$.


Introduction: system specification




Introduction: system specification




Introduction: system specification




Introduction: system specification




Introduction: system specification




Introduction: system specification



Introduction: system specification



Introduction: system specification



Introduction: system specification

- ω -regular language: safety + liveness;
- liveness properties: “something good happens eventually”.

Classical liveness properties

A first example, Büchi:

- a given set of propositions appears infinitely often;
(e.g “job done”)

Classical liveness properties

A first example, Büchi:

- a given set of propositions appears infinitely often;

A second example, Streett (fairness):

- propositions are either requests R_i or grants G_i ;
- if R_i is requested infinitely often, then it is serviced (G_i) infinitely often.

Classical liveness properties

A first example, Büchi:

- a given set of propositions appears infinitely often;

A second example, Streett (fairness):

- propositions are either requests R_i or grants G_i ;
- if R_i is requested infinitely often, then it is serviced (G_i) infinitely often.

(special case: parity)


Outline

1 Motivations


2 Characterizations

3 Expressions

A drawback of classical ω -regular specifications




A drawback of classical ω -regular specifications



Streett specification: for $i \in \{1, 2\}$, if R_i is requested infinitely often, then it is serviced infinitely often.

A drawback of classical ω -regular specifications



Streett specification: for $i \in \{1, 2\}$, if R_i is requested infinitely often, then it is serviced infinitely often.

Satisfied, but the “service time” may grow unbounded!

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an unknown, fixed bound b such that good things happen within b transitions.

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an **unknown**, fixed bound b such that good things happen within b transitions.

unknown: retain independence from granularity.

A stronger formulation of liveness: finitary liveness [AH94]

Intuitively: there exists an unknown, fixed bound b such that good things happen within b transitions.

It can be expressed as a finitary operator on languages:

$$\text{fin}(L) = \bigcup \{M \mid M \text{ closed and } \omega\text{-regular}, M \subseteq L\}$$

A stronger formulation of liveness: finitary liveness [AH94]


Intuitively: there exists an unknown, fixed bound b such that good things happen within b transitions.

It can be expressed as a finitary operator on languages:

$$\text{fin}(L) = \bigcup \{M \mid M \text{ closed and } \omega\text{-regular}, M \subseteq L\}$$


- closed: involves Cantor topology;
- ω -regular: involves ω -regularity;
- restriction operator: $\text{fin}(L) \subseteq L$.

Back to the example




Finitary Streett specification: there exists a bound b , such that *in the limit*, for $i \in \{1, 2\}$, if R_i is requested, then it is serviced within b transitions.

Back to the example




Finitary Streett specification: there exists a bound b , such that *in the limit*, for $i \in \{1, 2\}$, if R_i is requested, then it is serviced within b transitions.

Back to the example



Finitary Streett specification: there exists a bound b , such that *in the limit*, for $i \in \{1, 2\}$, if R_i is requested, then it is serviced within b transitions.

Back to the example



Finitary Streett specification: there exists a bound b , such that *in the limit*, for $i \in \{1, 2\}$, if R_i is requested, then it is serviced within b transitions.

Outline

1 Motivations

2 **Characterizations**

3 Expressions

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

$\text{Inf}(w)$ is the set of propositions that appear infinitely often in w .

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

$$\text{next}_k(w, F) = \inf\{k' - k \mid k' \geq k, w_{k'} \in F\}$$

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

$$\text{next}_k(w, F) = \inf\{k' - k \mid k' \geq k, w_{k'} \in F\}$$

$$w = v_0 \dots v_k \underbrace{v_{k+1} \dots v_{k'-1}}_{\notin F} \underbrace{v_{k'}}_{\in F}$$

waiting time from the k^{th} position.

Describing classical finitary objectives: Büchi

Let $F \subseteq \Sigma$,

$$\text{Büchi}(F) = \{w \mid \text{Inf}(w) \cap F \neq \emptyset\}$$

$$\text{next}_k(w, F) = \inf\{k' - k \mid k' \geq k, w_{k'} \in F\}$$

Lemma

$$\text{fin}(\text{Büchi}(F)) = \{w \mid \limsup_k \text{next}_k(w, F) < \infty\}$$

Topological classification in Borel hierarchy

Theorem

$\text{fin}(\text{Büchi}(F))$, $\text{fin}(\text{Parity}(p))$ and $\text{fin}(\text{Streett}(R, G))$ are Σ_2 -complete.

Automata-theoretic expressive power

We consider automata over infinite words, whose acceptance conditions are finitary Büchi, finitary parity or finitary Streett.

Automata-theoretic expressive power

We consider automata over infinite words, whose acceptance conditions are finitary Büchi, finitary parity or finitary Streett. A finitary Büchi automaton is $\mathcal{A} = (Q, \Sigma, Q_0, \delta, \text{finBüchi}(F))$.

Automata-theoretic expressive power

We consider automata over infinite words, whose acceptance conditions are finitary Büchi, finitary parity or finitary Streett. A finitary Büchi automaton is $\mathcal{A} = (Q, \Sigma, Q_0, \delta, \text{finBüchi}(F))$.

$$\left\{ \begin{array}{c} D \\ N \end{array} \right\} \cdot \left\{ \begin{array}{c} \varepsilon \text{ (classical)} \\ F(\text{finitary}) \end{array} \right\} \cdot \left\{ \begin{array}{c} B \text{ (Büchi)} \\ P \text{ (parity)} \\ S \text{ (Streett)} \end{array} \right\}$$




Figure: Expressive power classification

Outline

1 Motivations

2 Characterizations

3 Expressions

Regular and ω -regular expressions

Regular expressions defines regular languages over finite words:

$$L := \emptyset \mid \varepsilon \mid \sigma \mid \underbrace{L \cdot L}_{\text{concatenation}} \mid \underbrace{L^*}_{\text{star}} \mid \underbrace{L + L}_{\text{union}}; \quad \sigma \in \Sigma$$

ω -regular languages are finite union of $L_1 \cdot L_2^\omega$, where L_1 and L_2 are regular languages over finite words.

The bound operator B [BC06]

$$L^\omega = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid u_0, u_1, \dots, u_k, \dots \in L\}$$

The bound operator B [BC06]

$$L^\omega = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid u_0, u_1, \dots, u_k, \dots \in L\}$$

Example: $(a^* \cdot b)^\omega$ expresses “infinitely many b ’s”.

The bound operator B [BC06]

$$L^\omega = \{u_0 \cdot u_1 \cdot \dots \cdot u_k \dots \mid u_0, u_1, \dots, u_k, \dots \in L\}$$

Example: $(a^* \cdot b)^\omega$ expresses “infinitely many b ’s”.

Example: $(a^B \cdot b)^\omega$ expresses “infinitely many b ’s with an upper bound on the length of a ’s blocks”.

Star-free ωB -regular expressions

B -regular languages are described by the grammar:

$$M := \emptyset \mid \varepsilon \mid \sigma \mid M \cdot M \mid M^* \mid M^B \mid M + M; \quad \sigma \in \Sigma$$

ωB -regular languages are finite union of $L \cdot M^\omega$, where

- L is a regular language over finite words;
- M is a B -regular language over infinite words.

Star-free ωB -regular expressions

B -regular languages are described by the grammar:

$$M := \emptyset \mid \varepsilon \mid \sigma \mid M \cdot M \mid M^* \mid M^B \mid M + M; \quad \sigma \in \Sigma$$

ωB -regular languages are finite union of $L \cdot M^\omega$, where

- L is a regular language over finite words;
- M is a B -regular language over infinite words.

Star-free ωB -regular languages are finite union of $L \cdot M^\omega$, where

- L is a regular language over finite words;
- M is a **star-free** B -regular language over infinite words.

“no star operator under the ω -operator”.

Equivalence

Theorem

NFB (non-deterministic finitary Büchi automata) has exactly the same expressive power as star-free ωB -regular expressions.

Examples

First example: $c^* \cdot (a^B \cdot b)^\omega$ is a star-free ωB -regular expression,

Examples

First example: $c^* \cdot (a^B \cdot b)^\omega$ is a star-free ωB -regular expression, it expresses “a finite number of c ’s followed by an infinite word over alphabet $\{a, b\}$, with infinitely many b ’s and an upper bound on the length of a ’s blocks”.

Examples

First example: $c^* \cdot (a^B \cdot b)^\omega$ is a star-free ωB -regular expression, it expresses “a finite number of c ’s followed by an infinite word over alphabet $\{a, b\}$, with infinitely many b ’s and an upper bound on the length of a ’s blocks”.

Second example: $(a^B \cdot b \cdot (a^* \cdot b)^*)^\omega$ is **not** a star-free ωB -regular expression,

Examples

First example: $c^* \cdot (a^B \cdot b)^\omega$ is a star-free ωB -regular expression, it expresses “a finite number of c ’s followed by an infinite word over alphabet $\{a, b\}$, with infinitely many b ’s and an upper bound on the length of a ’s blocks”.

Second example: $(a^B \cdot b \cdot (a^* \cdot b)^*)^\omega$ is **not** a star-free ωB -regular expression, it expresses “words of the form $a^{n_0} \cdot b \cdot a^{n_1} \cdot b \dots$ such that $\liminf_i n_i < \infty$ ”.

Conclusion

- finitary objectives is a refinement for specification purposes;
- for ω -regular languages, topological, logical and automata-theoretic studies are well-known;
- for finitary languages, all were missing; we established:
 - topological classification;
 - automata-theoretic characterization, comparison to ω -regular languages, closure properties;
 - characterization using by ωB -regular expressions.

Conclusion

- finitary objectives is a refinement for specification purposes;
- for ω -regular languages, topological, logical and automata-theoretic studies are well-known;
- for finitary languages, all were missing; we established:
 - topological classification;
 - automata-theoretic characterization, comparison to ω -regular languages, closure properties;
 - characterization using by ωB -regular expressions.

Future work:

- games (work in progress);
- a finitary logic, Myhill-Nerode equivalence relations, ...

Bibliography



R. Alur and T.A. Henzinger.

Finitary fairness.

In *LICS'94*, pages 52–61. IEEE, 1994.



Mikołaj Bojańczyk and Thomas Colcombet.

Bounds in ω -regularity.

In *LICS'06*, pages 285–296. IEEE, 2006.

The end

Thank you for your attention!