

Research Methods and Data Analysis (IAWEL)

Jill R D MacKay

2026-02-19

Table of contents

1 Research Methods and Data Analysis (IAWEL)	5
Preface	6
Packages in this textbook	6
Licensing	6
2 Week 1: The Philosophy of Science	8
Lecture 3: The Replication Crisis	9
Lecture 5: Introduction to Research Methods	12
2.1 Create data and plot	12
2.2 Run an ANOVA on Plant data	13
2.3 Read and Run Crude Chicken Correlations	13
3 Week 2: The Use and Abuse of Data	14
Lecture 2: Data Visualisation	15
Height vs Weight by Sex	15
Histogram of male height	16
Density plot of male height	17
Boxplot of height	18
Mean height (bar chart)	19
Mosaic Plot	20
Pie Charts are Just Bad Bar Charts	21
Wordclouds	23
Raincloud Plots	24
Bubble plots	25
Correlation plots	26
Lecture 3: The Mean as a Basic Model	28
Data and custom function for this lecture	28
Finding central tendency	28
The Mean and Outliers	29
Mean UK Salary	31
The Mode	32

Multiple Modes	33
The Median	34
Median UK Salary	35
4 Week 3: Introduction to Analyses	37
Lecture 2: Introduction to statistics	38
Set up your environment and packages	38
Summarise example data	38
Visualise example data	38
A Linear Model	39
A Bayesian Model	42
A Linear model with a factor	50
Bayesian Framework	53
Lecture: Calculating variance	62
Why does it matter?	62
Residuals	63
Adding the residuals	64
Compare Variances	65
Compare Standard Deviations	65
Compare Standard Errors	66
Lecture: Meta Analyses	67
5 Week 4: Considerations for Collecting Data	68
Lecture 1: Effect Sizes and Covariance	69
Mock Data and visualisation	69
Calculate Cohen's d	70
Calculate Hedge's g	70
Effects of Differences	71
Correlation coefficient (r)	72
Other Correlation Coefficients	72
Cramer's V	72
R ² adj Example	73
Covariance	75
6 Week 5: Sources of Data	77
Lecture 1 Digital Media Research	78
6.1 Who's in digital spaces	78
Lecture 4: Meta Analyses	80

7 Week 6: Reading Week	81
8 Weeks 7 and 8: R Stats	82
9 Week 9 Analysing Quantitative Data	83
Lecture 1: Partitioning Variation	84
A Perfect World	84
Our Unicorn Farm	85
No Radio Group	86
No Radio Mean	87
Deviations from the mean	88
Variance	89
Imaginary Scenarions	89
MFY	94
Lecture 2: Choosing a Statistical Test	97
Numerical Response	98
Numerical Response Categorical Explanatory	99
Numerical Response Numerical Explanatory	101
Categorical Response	102
Categorical Response Categorical Explanatory	102
Categorical Response Numerical Explanatory	104
Parametric vs Non Parametric	106
Power Calculations	106
Assumptions	106
10 Week 10: Analysing Quanlitative Data	107
11 References	108
References	109

1 Research Methods and Data Analysis (IAWEL)

Research
Methods
and Data
Analysis
(IAWEL)




Figure 1.1: Research Methods and Data Analysis (IAWEL) Cover

Preface

This book accompanies the Research Methods and Data Analysis course on the [International Animal Welfare Ethics and Law MSc](#) at the [Royal \(Dick\) School of Veterinary Studies](#).

It is a companion document to the course, and not core to the materials, however we choose to make this publically available as part of our commitment to open science frameworks and accessibility in education.

Throughout the RMDA Lectures, you will see a number of statistical tests, data visualisations, data manipulation, text mining, and simple calculations. Almost inevitably, each one of these steps will have been performed in R.

Your R textbook is [R@R\(D\)SVS](#), and that textbook will explain [how to download and install R](#), [how to run simple commands in R](#), and more. This RMDA textbook is like an accompanying document to your lecture materials, and is a place to help you move your R and statistical knowledge along.

Packages in this textbook

There are a range of packages used in this book, including Tidyverse (Wickham et al. 2019), effsize (Torchiano 2020), ggstatsplot (Patil 2021), vcd (Zeileis et al. 2007), wordcloud (Fellows 2018), easystats (Lüdecke et al. 2022), rstan (Stan Development Team 2023), rstanarm (Brilleman et al. 2018)

You may need to [download and install a package](#) or [load a package](#) for some of these commands to work.

Licensing

This book is licensed under the Unlicense.

This is free and unencumbered software released into the public domain.

Anyone is free to copy, modify, publish, use, compile, sell, or distribute this software, either in source code form or as a compiled binary, for any purpose, commercial or non-commercial, and by any means.

In jurisdictions that recognize copyright laws, the author or authors of this software dedicate any and all copyright interest in the software to the public domain. We make this dedication for the benefit of the public at large and to the detriment of our heirs and successors. We intend this dedication to be an overt act of relinquishment in perpetuity of all present and future rights to this software under copyright law.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

For more information, please refer to <https://unlicense.org>

2 Week 1: The Philosophy of Science


Lecture 3: The Replication Crisis

Bland-Altman Plots are generated with the following code.

```
library(tidyverse)


bland <- tibble(
  subject = c(1:17),
  Wright1 = c(484,395,516,434,476,557,413,442,650,433,417,656,267,478,178,423,427),
  Wright2 = c(490,397,512,401,470,611,415,431,638,429,420,633,275,492,165,372,421),
  Mini1 = c(512,430,520,428,500,600,364,380,658,445,432,626,260,477,259,350,451),
  Mini2 = c(525,415,508,444,500,625,460,390,642,432,420,605,227,467,268,370,443)
)

bland |>
  ggplot(aes(x = Wright1, y = Mini1)) +
  stat_smooth(method="lm", se=FALSE) +
  geom_point(colour = "turquoise4", size = 3) +
  scale_x_continuous(limits = c(0,700)) +
  scale_y_continuous(limits = c(0,700)) +
  theme_classic() +
  labs(x = "Wright Meter (1st Measure)", y = "Mini Wright Meter (1st Measure)")
```



And then if we add 100 to each measure, we see a very similar plot:

```
bland |>
  mutate (Wright1 = (Wright1+100)) %>%
  ggplot(aes(x = Wright1, y = Mini1)) +
  stat_smooth(method="lm", se=FALSE) +
  geom_point(colour = "turquoise4", size = 3) +
  scale_x_continuous(limits = c(0,800)) +
  scale_y_continuous(limits = c(0,700)) +
  theme_classic() +
  labs(x = "Wright Meter (1st Measure)", y = "Mini Wright Meter (1st Measure)")
```




Lecture 5: Introduction to Research Methods

2.1 Create data and plot

```
library(tidyverse)

plants <- tibble(none = c(4.8, 4.8, 3.94, 4.4,4.5,4.6),
                 nutrients1 = c( 10.1, 9.7, 9.8, 9.9, 9.3, 10.1),
                 nutrients2 = c(14.8, 14.6, 14.8, 14, 13.8, 14.6))

plants |>
  pivot_longer(cols = c(none, nutrients1,nutrients2),
               names_to = "nutrients",
               values_to = "height") |>
  ggplot(aes(x = nutrients, y = height)) +
  geom_boxplot()
```



2.2 Run an ANOVA on Plant data

```
longplants <- plants |>
  pivot_longer(cols = c(none, nutrients1, nutrients2),
               names_to = "nutrients",
               values_to = "height")

plant_model <- aov(height ~ nutrients, data = longplants)

summary(plant_model)
```

```
              Df Sum Sq Mean Sq F value Pr(>F)
nutrients      2  296.10   148.05    1184 <2e-16 ***
Residuals     15    1.88    0.13
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

2.3 Read and Run Crude Chicken Correlations

```
crudechicks <- tibble(year = c("2000", "2001", "2002", "2003",
                                "2004", "2005", "2006", "2007",
                                "2008", "2009"),
                      chicken = c(54.2, 54, 56.8, 57.5, 59.3, 60.5, 60.9,
                                   59.9, 58.7, 56),
                      crude = c(3311, 3405, 3336, 3521, 3674, 3670, 3685,
                                 3656, 3571, 3307))

cor.test(crudechicks$chicken, crudechicks$crude, method = "spearman")
```

Spearman's rank correlation rho

```
data: crudechicks$chicken and crudechicks$crude
S = 20, p-value = 0.001977
alternative hypothesis: true rho is not equal to 0
sample estimates:
      rho
0.8787879
```


3 Week 2: The Use and Abuse of Data

Lecture 2: Data Visualisation

This code will help you replicate the charts in Lecture 2


Height vs Weight by Sex

```
starwars |>
  filter(species == "Human") |>
  ggplot(aes(x = height, y = mass, colour = sex)) +
  geom_point() +
  theme_classic() +
  scale_x_continuous(limits = c(0,250)) +
  scale_y_continuous(limits = c(0,150)) +
  scale_colour_brewer(palette = "Accent", name = "Sex") +
  theme(legend.position = "bottom") +
  labs(x = "Height (cm)",
       y = "Weight (kg)",
       title = "Height and Weight of Human Characters in Star Wars by Sex")
```




Histogram of male height

```
starwars |>
  filter(species == "Human",
         sex == "male") |>
  ggplot(aes(x = height)) +
  geom_histogram(binwidth = 3, fill = "#bb9cd1") +
  theme_classic() +
  labs(x = "Height (cm)",
       y = "Count",
       title = "Histogram of height of male human Star Wars characters")
```


Density plot of male height

```
starwars |>
  filter(species == "Human",
         sex == "male") |>
  ggplot(aes(x = height)) +
  geom_density(fill = "#bb9cd1") +
  theme_classic() +
  labs(x = "Height (cm)",
       y = "Count",
       title = "Density plot of height of male human Star Wars characters")
```




Boxplot of height

```
starwars |>
  filter(species == "Human") |>
  ggplot(aes(y = height, x = sex, colour = sex)) +
  geom_boxplot() +
  theme_classic() +
  scale_colour_brewer(palette = "Accent", name = "Sex") +
  labs(y = "Height (cm)",
       x = "Sex",
       title = "Boxplot of height by sex of human characters in Star Wars") +
  theme(legend.position = "none")
```



Mean height (bar chart)

```
starwars |>
  filter(species == "Human") |>
  group_by(sex) |>
  summarise(ht = mean(height, na.rm = TRUE),
            sd = sd(height, na.rm = TRUE)) |>
  ggplot(aes(x = sex, y = ht, fill = sex)) +
  geom_bar(stat = "identity") +
  geom_errorbar(aes(ymin = ht-sd, ymax = ht+sd), width = 0.2)+
  scale_fill_brewer(palette = "Accent") +
  labs(y = "Mean Height (cm)",
       x = "Sex",
       title = "Mean height by sex of human characters in Star Wars") +
  theme_classic() +
  theme(legend.position = "none")
```




Mosaic Plot

```
library(vcd)


starttbl <- starwars |>
  mutate(Species = fct_lump_n(species, 2),
         EyeColour = fct_lump_n(eye_color, 2))

mosaic(~ Species + EyeColour, data = starttbl, shade = TRUE, legend = TRUE)
```




Pie Charts are Just Bad Bar Charts

```
starwars |>
  mutate(species = fct_lump_n(species, 4)) |>
  group_by(species) |>
  filter(!is.na(species)) |>
  tally() |>
  ggplot(aes(x = "", fill = species, y = n)) +
  geom_bar(stat = "identity", width = 1) +
  theme_void() +
  coord_polar("y", start = 0)
```



```
starwars |>
  mutate(species = fct_lump_n(species, 4)) |>
  group_by(species) |>
  filter(!is.na(species)) |>
  tally() |>
  ggplot(aes(x = species, fill = species, y = n)) +
  geom_bar(stat = "identity") +
  theme_classic() +
  labs(x = "Species", y = "Count") +
  theme(legend.position = "none")
```




Wordclouds

```
library(wordcloud)
starwars |>
  count(homeworld) |>
  with(wordcloud(words = homeworld, freq = n, min.freq=1, random.order = FALSE, rot.per = 0,
                 colors = brewer.pal(6, "Accent"), use.r.layout = FALSE))
```




Raincloud Plots

```
starwars |>
  mutate(species = fct_lump_n(species,2)) |>
  filter(!is.na(species)) |>
  ggplot(aes(x = species)) +
    geom_point(aes(y = height, colour = species), position = position_jitter(width = .13), size = 100) +
    see::geom_violinhalf(aes(y = height, alpha= 0.3, fill = species), linetype = "dashed", position = position_jitter(width = .13)) +
    geom_boxplot(aes(y = height, alpha = 0.3, colour = species), position = position_nudge(x = 1)) +
    theme_classic() +
    labs(x = "Species", y = "Height (cm)") +
    theme(legend.position = "none") +
    coord_flip()
```


Bubble plots

```
starwars |>
  mutate(col = fct_lump_n(species, 2)) |>
  ggplot(aes(x = birth_year, y = mass, size = height, colour = col)) +
  geom_point() +
  scale_size(range = c(.1, 24), name="Height") +
  theme_classic() +
  scale_x_continuous(limits = c(0,250)) +
  scale_y_continuous(limits = c(0,300)) +
  scale_colour_brewer(palette = "Accent", name = "Species") +
  theme(legend.position = "bottom") +
  labs(x = "Birth Year (Before Battle of Yavin)",
       y = "Weight (kg)",
       title = "Weight by Age of Characters in Star Wars")
```



Correlation plots

```
starwars |>  
  select(height, mass, birth_year) |>  
  ggcorrmat()
```



Lecture 3: The Mean as a Basic Model

Data and custom function for this lecture

```
library(tidyverse)

heifers <- tibble(heifers = c(211.3, 200.4, 220.1, 200.8, 222.0, 209.3,
                             195.8, 220.4, 226.2, 218.7, 193.7, 209.7))

wage <- readxl::read_excel("assets/UKWageData2023ONS.xlsx",
                           skip = 5)

find_mode <- function(x) {
  ux <- unique(x)
  tab <- tabulate(match(x, ux))
  ux[tab == max(tab)]
}
```

Finding central tendency

```
heifers |>
  summarise(mean = mean(heifers),
            median = median(heifers),
            min = min(heifers),
            max = max(heifers),
            mode = find_mode(round(heifers, 0)))
```


```
# A tibble: 1 x 5
  mean median  min  max mode
<dbl> <dbl> <dbl> <dbl> <dbl>
1  211.   210.  194.  226.  220
```

```
wage |>
  summarise(mean = mean(Median),
            median = median(Median),
            min = min(Median),
            max = max(Median),
            mode = find_mode(round(Median,0)))
```


```
# A tibble: 4 x 5
   mean median  min   max  mode
  <dbl>  <dbl> <dbl> <dbl> <dbl>
1 34475.   31988 17859 84131 28216
2 34475.   31988 17859 84131 35248
3 34475.   31988 17859 84131 26000
4 34475.   31988 17859 84131 25000
```

The Mean and Outliers

```
heifers |>
  ggplot(aes(x = heifers)) +
  geom_density(fill = "#bb9cd1") +
  theme_classic() +
  labs(x = "Heifer Weight (kg)",
       y = "Density")
```




```
heifers |>
  ggplot(aes(x = heifers)) +
  geom_density(fill = "#bb9cd1") +
  geom_vline(aes(xintercept = 210.7)) +
  theme_classic() +
  labs(x = "Heifer Weight (kg)",
       y = "Density")
```




Mean UK Salary

```
wage |>
  ggplot(aes(x = Median)) +
  geom_density(fill = "#bb9cd1") +
  theme_classic() +
  geom_vline(aes(xintercept = 34475)) +
  labs(x = "UK Salaries (£)",
       y = "Density",
       title = "Distribution of UK Salaries",
       caption = "Data taken from ONS 2023 Median Salaries by Field, n = 329 fields")
```




The Mode

```
heifers |>
  ggplot(aes(x = heifers)) +
  geom_histogram(fill = "#bb9cd1", binwidth = 1) +
  geom_vline(aes(xintercept = 220)) +
  theme_classic() +
  labs(x = "Heifer Weight (kg)",
       y = "Density")
```


Multiple Modes

```
wage |>
  ggplot(aes(x = Median)) +
  geom_histogram(fill = "#bb9cd1", bins = 200) +
  geom_vline(aes(xintercept = 25000)) +
  geom_vline(aes(xintercept = 26000)) +
  geom_vline(aes(xintercept = 28216)) +
  geom_vline(aes(xintercept = 35248)) +
  theme_classic() +
  labs(x = "UK Salaries (£)",
       y = "Count")
```




The Median

```
heifers |>
  ggplot(aes(x = heifers)) +
  geom_density(fill = "#bb9cd1") +
  geom_vline(aes(xintercept = 210)) +
  theme_classic() +
  labs(x = "Heifer Weight (kg)",
       y = "Density")
```



Median UK Salary

```
wage |>
  ggplot(aes(x = Median)) +
  geom_density(fill = "#bb9cd1") +
  theme_classic() +
  geom_vline(aes(xintercept = 34475), colour = "lightblue") +
  geom_vline(aes(xintercept = 31988), colour = "purple") +
  labs(x = "UK Salaries (£)",
       y = "Density",
       title = "Distribution of UK Salaries",
       caption = "Data taken from ONS 2023 Median Salaries by Field, n = 329 fields")
```



Data taken from ONS 2023 Median Salaries by Field, n = 329 fields

4 Week 3: Introduction to Analyses

Lecture 2: Introduction to statistics

Set up your environment and packages

```
library(tidyverse)
library(easystats)
library(rstan)
library(rstanarm)

cat_weights <- tibble(avg_daily_snacks = c(3, 2, 4, 2, 3, 1, 1, 0, 1, 0, 2, 3, 1, 2, 1, 3),
                      weight = c(3.8, 3.9, 5, 3.7, 4.1, 3.6, 3.7, 3.6, 3.8, 4.1, 4.3, 3.9, 3.8, 4.2, 4.4, 4.0),
                      environ = c("Indoor", "Indoor", "Outdoor", "Indoor",
                                   "Outdoor", "Indoor", "Outdoor", "Indoor",
                                   "Indoor", "Indoor", "Outdoor", "Indoor",
                                   "Outdoor", "Indoor", "Indoor", "Outdoor"))
```


Summarise example data

```
cat_weights |>
  summarise("Mean Weight (kg)" = mean(weight),
            "SD Weight (kg)" = sd(weight),
            "Mean Daily Snacks" = mean(avg_daily_snacks),
            )
```

```
# A tibble: 1 x 3
  `Mean Weight (kg)` `SD Weight (kg)` `Mean Daily Snacks`
      <dbl>          <dbl>          <dbl>
1      3.92         0.373          1.81
```

Visualise example data

```
cat_weights |>
  ggplot(aes(x = avg_daily_snacks, y = weight)) +
  geom_point() +
  labs(x = "Average Daily Snacks", y = "Cat Weight") +
  theme_classic() +
  scale_y_continuous(limits = c(0,5))
```



A Linear Model

```
model_fcat <- lm(weight ~ avg_daily_snacks, data = cat_weights)
summary(model_fcat)
```

Call:

```
lm(formula = weight ~ avg_daily_snacks, data = cat_weights)
```

Residuals:

Min	1Q	Median	3Q	Max
-0.36758	-0.18723	-0.06116	0.06705	0.62813

Coefficients:

```
              Estimate Std. Error t value Pr(>|t|)
(Intercept)    3.55474    0.14045  25.309 4.33e-13 ***
avg_daily_snacks 0.20428    0.06576   3.107 0.00773 **
---
```

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.2973 on 14 degrees of freedom

Multiple R-squared: 0.4081, Adjusted R-squared: 0.3658

F-statistic: 9.652 on 1 and 14 DF, p-value: 0.007729

```
report::report(model_fcat)
```

We fitted a linear model (estimated using OLS) to predict weight with avg_daily_snacks (formula: weight ~ avg_daily_snacks). The model explains a statistically significant and substantial proportion of variance ($R^2 = 0.41$, $F(1, 14) = 9.65$, $p = 0.008$, adj. $R^2 = 0.37$). The model's intercept, corresponding to avg_daily_snacks = 0, is at 3.55 (95% CI [3.25, 3.86], $t(14) = 25.31$, $p < .001$). Within this model:


- The effect of avg daily snacks is statistically significant and positive (beta = 0.20, 95% CI [0.06, 0.35], $t(14) = 3.11$, $p = 0.008$; Std. beta = 0.64, 95% CI [0.20, 1.08])

Standardized parameters were obtained by fitting the model on a standardized version of the dataset. 95% Confidence Intervals (CIs) and p-values were computed using a Wald t-distribution approximation.


```
parameters(model_fcat)
```

Parameter	Coefficient	SE	95% CI	t(14)	p
(Intercept)	3.55	0.14	[3.25, 3.86]	25.31	< .001
avg daily snacks	0.20	0.07	[0.06, 0.35]	3.11	0.008


```
plot(model_parameters(model_fcat), show_intercept = TRUE)
```

```
plot(model_parameters(model_fcat))
```



```
cat_weights |>
  ggplot(aes(x = avg_daily_snacks, y = weight)) +
  geom_point() +
  labs(x = "Average Daily Snacks", y = "Cat Weight",
       caption = "Weight ~ Average Daily Snacks shown") +
  theme_classic() +
  scale_y_continuous(limits = c(0,5)) +
  geom_abline(slope = 0.20, intercept = 3.55)
```



A Bayesian Model

```
set.seed(10)

model_bcat <- stan_glm(weight ~ avg_daily_snacks, data = cat_weights)
```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 1).

Chain 1:

Chain 1: Gradient evaluation took 0.002048 seconds

Chain 1: 1000 transitions using 10 leapfrog steps per transition would take 20.48 seconds.

Chain 1: Adjust your expectations accordingly!

Chain 1:

Chain 1:

Chain 1: Iteration: 1 / 2000 [0%] (Warmup)

Chain 1: Iteration: 200 / 2000 [10%] (Warmup)

Chain 1: Iteration: 400 / 2000 [20%] (Warmup)

Chain 1: Iteration: 600 / 2000 [30%] (Warmup)

Chain 1: Iteration: 800 / 2000 [40%] (Warmup)

Chain 1: Iteration: 1000 / 2000 [50%] (Warmup)

Chain 1: Iteration: 1001 / 2000 [50%] (Sampling)

Chain 1: Iteration: 1200 / 2000 [60%] (Sampling)

Chain 1: Iteration: 1400 / 2000 [70%] (Sampling)

Chain 1: Iteration: 1600 / 2000 [80%] (Sampling)

Chain 1: Iteration: 1800 / 2000 [90%] (Sampling)

Chain 1: Iteration: 2000 / 2000 [100%] (Sampling)

Chain 1:

Chain 1: Elapsed Time: 0.053 seconds (Warm-up)

Chain 1: 0.04 seconds (Sampling)

Chain 1: 0.093 seconds (Total)

Chain 1:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 2).

Chain 2:

Chain 2: Gradient evaluation took 1.4e-05 seconds

Chain 2: 1000 transitions using 10 leapfrog steps per transition would take 0.14 seconds.

Chain 2: Adjust your expectations accordingly!

Chain 2:

Chain 2:

Chain 2: Iteration: 1 / 2000 [0%] (Warmup)

Chain 2: Iteration: 200 / 2000 [10%] (Warmup)

Chain 2: Iteration: 400 / 2000 [20%] (Warmup)

Chain 2: Iteration: 600 / 2000 [30%] (Warmup)

Chain 2: Iteration: 800 / 2000 [40%] (Warmup)

Chain 2: Iteration: 1000 / 2000 [50%] (Warmup)

Chain 2: Iteration: 1001 / 2000 [50%] (Sampling)

Chain 2: Iteration: 1200 / 2000 [60%] (Sampling)

Chain 2: Iteration: 1400 / 2000 [70%] (Sampling)

Chain 2: Iteration: 1600 / 2000 [80%] (Sampling)

Chain 2: Iteration: 1800 / 2000 [90%] (Sampling)

Chain 2: Iteration: 2000 / 2000 [100%] (Sampling)

Chain 2:

Chain 2: Elapsed Time: 0.037 seconds (Warm-up)

Chain 2: 0.042 seconds (Sampling)

Chain 2: 0.079 seconds (Total)

Chain 2:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 3).

Chain 3:

Chain 3: Gradient evaluation took 1.4e-05 seconds

Chain 3: 1000 transitions using 10 leapfrog steps per transition would take 0.14 seconds.

Chain 3: Adjust your expectations accordingly!

Chain 3:

Chain 3:

Chain 3: Iteration: 1 / 2000 [0%] (Warmup)

Chain 3: Iteration: 200 / 2000 [10%] (Warmup)

Chain 3: Iteration: 400 / 2000 [20%] (Warmup)

Chain 3: Iteration: 600 / 2000 [30%] (Warmup)

Chain 3: Iteration: 800 / 2000 [40%] (Warmup)

Chain 3: Iteration: 1000 / 2000 [50%] (Warmup)

Chain 3: Iteration: 1001 / 2000 [50%] (Sampling)

Chain 3: Iteration: 1200 / 2000 [60%] (Sampling)

Chain 3: Iteration: 1400 / 2000 [70%] (Sampling)

Chain 3: Iteration: 1600 / 2000 [80%] (Sampling)

Chain 3: Iteration: 1800 / 2000 [90%] (Sampling)

Chain 3: Iteration: 2000 / 2000 [100%] (Sampling)

Chain 3:

Chain 3: Elapsed Time: 0.038 seconds (Warm-up)

Chain 3: 0.038 seconds (Sampling)

Chain 3: 0.076 seconds (Total)

Chain 3:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 4).

Chain 4:

Chain 4: Gradient evaluation took 1.1e-05 seconds

Chain 4: 1000 transitions using 10 leapfrog steps per transition would take 0.11 seconds.

Chain 4: Adjust your expectations accordingly!

Chain 4:

Chain 4:

Chain 4: Iteration: 1 / 2000 [0%] (Warmup)

Chain 4: Iteration: 200 / 2000 [10%] (Warmup)

Chain 4: Iteration: 400 / 2000 [20%] (Warmup)

Chain 4: Iteration: 600 / 2000 [30%] (Warmup)

Chain 4: Iteration: 800 / 2000 [40%] (Warmup)

Chain 4: Iteration: 1000 / 2000 [50%] (Warmup)

Chain 4: Iteration: 1001 / 2000 [50%] (Sampling)

Chain 4: Iteration: 1200 / 2000 [60%] (Sampling)

```

Chain 4: Iteration: 1400 / 2000 [ 70%] (Sampling)
Chain 4: Iteration: 1600 / 2000 [ 80%] (Sampling)
Chain 4: Iteration: 1800 / 2000 [ 90%] (Sampling)
Chain 4: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 4:
Chain 4: Elapsed Time: 0.039 seconds (Warm-up)
Chain 4:           0.039 seconds (Sampling)
Chain 4:           0.078 seconds (Total)
Chain 4:

```

```
summary(model_bcat)
```

Model Info:

```

function:      stan_glm
family:        gaussian [identity]
formula:       weight ~ avg_daily_snacks
algorithm:     sampling
sample:        4000 (posterior sample size)
priors:        see help('prior_summary')
observations:  16
predictors:    2

```

Estimates:

	mean	sd	10%	50%	90%
(Intercept)	3.6	0.2	3.4	3.6	3.7
avg_daily_snacks	0.2	0.1	0.1	0.2	0.3
sigma	0.3	0.1	0.2	0.3	0.4

Fit Diagnostics:

	mean	sd	10%	50%	90%
mean_PPD	3.9	0.1	3.8	3.9	4.1

The mean_ppd is the sample average posterior predictive distribution of the outcome variable

MCMC diagnostics

	mcse	Rhat	n_eff
(Intercept)	0.0	1.0	3066
avg_daily_snacks	0.0	1.0	2981
sigma	0.0	1.0	2539
mean_PPD	0.0	1.0	3573
log-posterior	0.0	1.0	1450

For each parameter, mcse is Monte Carlo standard error, n_eff is a crude measure of effective

```
describe_posterior(model_bcat)
```

Summary of Posterior Distribution

Parameter	Median	95% CI	pd	ROPE	% in ROPE	Rhat	
(Intercept)	3.55	[3.26, 3.86]	100%	[-0.04, 0.04]	0%	1.001	3066
avg_daily_snacks	0.20	[0.06, 0.35]	99.62%	[-0.04, 0.04]	0%	1.000	2981

```
report::report(model_bcat)
```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 1).

Chain 1:

Chain 1: Gradient evaluation took 1.4e-05 seconds

Chain 1: 1000 transitions using 10 leapfrog steps per transition would take 0.14 seconds.

Chain 1: Adjust your expectations accordingly!

Chain 1:

Chain 1:

Chain 1: Iteration: 1 / 2000 [0%] (Warmup)

Chain 1: Iteration: 200 / 2000 [10%] (Warmup)

Chain 1: Iteration: 400 / 2000 [20%] (Warmup)

Chain 1: Iteration: 600 / 2000 [30%] (Warmup)

Chain 1: Iteration: 800 / 2000 [40%] (Warmup)

Chain 1: Iteration: 1000 / 2000 [50%] (Warmup)

Chain 1: Iteration: 1001 / 2000 [50%] (Sampling)

Chain 1: Iteration: 1200 / 2000 [60%] (Sampling)

Chain 1: Iteration: 1400 / 2000 [70%] (Sampling)

Chain 1: Iteration: 1600 / 2000 [80%] (Sampling)

Chain 1: Iteration: 1800 / 2000 [90%] (Sampling)

Chain 1: Iteration: 2000 / 2000 [100%] (Sampling)

Chain 1:

Chain 1: Elapsed Time: 0.039 seconds (Warm-up)

Chain 1: 0.051 seconds (Sampling)

Chain 1: 0.09 seconds (Total)

Chain 1:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 2).

Chain 2:
Chain 2: Gradient evaluation took 1.2e-05 seconds
Chain 2: 1000 transitions using 10 leapfrog steps per transition would take 0.12 seconds.
Chain 2: Adjust your expectations accordingly!
Chain 2:
Chain 2:
Chain 2: Iteration: 1 / 2000 [0%] (Warmup)
Chain 2: Iteration: 200 / 2000 [10%] (Warmup)
Chain 2: Iteration: 400 / 2000 [20%] (Warmup)
Chain 2: Iteration: 600 / 2000 [30%] (Warmup)
Chain 2: Iteration: 800 / 2000 [40%] (Warmup)
Chain 2: Iteration: 1000 / 2000 [50%] (Warmup)
Chain 2: Iteration: 1001 / 2000 [50%] (Sampling)
Chain 2: Iteration: 1200 / 2000 [60%] (Sampling)
Chain 2: Iteration: 1400 / 2000 [70%] (Sampling)
Chain 2: Iteration: 1600 / 2000 [80%] (Sampling)
Chain 2: Iteration: 1800 / 2000 [90%] (Sampling)
Chain 2: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 2:
Chain 2: Elapsed Time: 0.037 seconds (Warm-up)
Chain 2: 0.047 seconds (Sampling)
Chain 2: 0.084 seconds (Total)
Chain 2:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 3).

Chain 3:
Chain 3: Gradient evaluation took 9e-06 seconds
Chain 3: 1000 transitions using 10 leapfrog steps per transition would take 0.09 seconds.
Chain 3: Adjust your expectations accordingly!
Chain 3:
Chain 3:
Chain 3: Iteration: 1 / 2000 [0%] (Warmup)
Chain 3: Iteration: 200 / 2000 [10%] (Warmup)
Chain 3: Iteration: 400 / 2000 [20%] (Warmup)
Chain 3: Iteration: 600 / 2000 [30%] (Warmup)
Chain 3: Iteration: 800 / 2000 [40%] (Warmup)
Chain 3: Iteration: 1000 / 2000 [50%] (Warmup)
Chain 3: Iteration: 1001 / 2000 [50%] (Sampling)
Chain 3: Iteration: 1200 / 2000 [60%] (Sampling)
Chain 3: Iteration: 1400 / 2000 [70%] (Sampling)
Chain 3: Iteration: 1600 / 2000 [80%] (Sampling)
Chain 3: Iteration: 1800 / 2000 [90%] (Sampling)
Chain 3: Iteration: 2000 / 2000 [100%] (Sampling)

```
Chain 3:
Chain 3: Elapsed Time: 0.039 seconds (Warm-up)
Chain 3:           0.05 seconds (Sampling)
Chain 3:           0.089 seconds (Total)
Chain 3:
```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 4).

```
Chain 4:
Chain 4: Gradient evaluation took 1.2e-05 seconds
Chain 4: 1000 transitions using 10 leapfrog steps per transition would take 0.12 seconds.
Chain 4: Adjust your expectations accordingly!
Chain 4:
Chain 4:
Chain 4: Iteration:    1 / 2000 [  0%] (Warmup)
Chain 4: Iteration:   200 / 2000 [ 10%] (Warmup)
Chain 4: Iteration:   400 / 2000 [ 20%] (Warmup)
Chain 4: Iteration:   600 / 2000 [ 30%] (Warmup)
Chain 4: Iteration:   800 / 2000 [ 40%] (Warmup)
Chain 4: Iteration:  1000 / 2000 [ 50%] (Warmup)
Chain 4: Iteration:  1001 / 2000 [ 50%] (Sampling)
Chain 4: Iteration:  1200 / 2000 [ 60%] (Sampling)
Chain 4: Iteration:  1400 / 2000 [ 70%] (Sampling)
Chain 4: Iteration:  1600 / 2000 [ 80%] (Sampling)
Chain 4: Iteration:  1800 / 2000 [ 90%] (Sampling)
Chain 4: Iteration:  2000 / 2000 [100%] (Sampling)
Chain 4:
Chain 4: Elapsed Time: 0.039 seconds (Warm-up)
Chain 4:           0.058 seconds (Sampling)
Chain 4:           0.097 seconds (Total)
Chain 4:
```

We fitted a Bayesian linear model (estimated using MCMC sampling with 4 chains of 2000 iterations and a warmup of 1000) to predict weight with avg_daily_snacks (formula: weight ~ avg_daily_snacks). Priors over parameters were set as normal (mean = 0.00, SD = 0.80) distributions. The model's explanatory power is substantial ($R^2 = 0.38$, 95% CI [6.54e-06, 0.62], adj. $R^2 = 0.15$). The model's intercept, corresponding to avg_daily_snacks = 0, is at 3.55 (95% CI [3.26, 3.86]). Within this model:


- The effect of avg daily snacks (Median = 0.20, 95% CI [0.06, 0.35]) has a 99.62% probability of being positive (> 0), 99.30% of being significant (> 0.02), and 90.10% of being large (> 0.11). The estimation successfully

converged (Rhat = 1.000) and the indices are reliable (ESS = 2981)

Following the Sequential Effect eXistence and sIgnificance Testing (SEXIT) framework, we report the median of the posterior distribution and its 95% CI (Highest Density Interval), along the probability of direction (pd), the probability of significance and the probability of being large. The thresholds beyond which the effect is considered as significant (i.e., non-negligible) and large are |0.02| and |0.11| (corresponding respectively to 0.05 and 0.30 of the outcome's SD). Convergence and stability of the Bayesian sampling has been assessed using R-hat, which should be below 1.01 (Vehtari et al., 2019), and Effective Sample Size (ESS), which should be greater than 1000 (Burkner, 2017).

```
posteriors <- get_parameters(model_bcat)

posteriors |>
  ggplot(aes(x = avg_daily_snacks)) +
  geom_density(fill = "lightblue") +
  theme_classic() +
  labs(x = "Posterior Coefficient Estimates for Average Daily Snacks",
       y = "Density",
       caption = "Median Estimate Shown") +
  geom_vline(xintercept = 0.21, color = "darkblue", linewidth = 1)
```



A Linear model with a factor

```
model_fcat2 <- lm(weight ~ avg_daily_snacks + environ, data = cat_weights)
summary(model_fcat2)
```

Call:

```
lm(formula = weight ~ avg_daily_snacks + environ, data = cat_weights)
```

Residuals:

Min	1Q	Median	3Q	Max
-0.2678	-0.1897	-0.0700	0.0821	0.5725

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	3.52748	0.13078	26.972	8.49e-13 ***
avg_daily_snacks	0.16168	0.06512	2.483	0.0275 *
environOutdoor	0.27860	0.15203	1.833	0.0899 .

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 0.275 on 13 degrees of freedom

Multiple R-squared: 0.5296, Adjusted R-squared: 0.4572

F-statistic: 7.318 on 2 and 13 DF, p-value: 0.007431

```
report::report(model_fcat2)
```

We fitted a linear model (estimated using OLS) to predict weight with avg_daily_snacks and environ (formula: weight ~ avg_daily_snacks + environ). The model explains a statistically significant and substantial proportion of variance ($R^2 = 0.53$, $F(2, 13) = 7.32$, $p = 0.007$, adj. $R^2 = 0.46$). The model's intercept, corresponding to avg_daily_snacks = 0 and environ = Indoor, is at 3.53 (95% CI [3.24, 3.81], $t(13) = 26.97$, $p < .001$). Within this model:


- The effect of avg daily snacks is statistically significant and positive (beta = 0.16, 95% CI [0.02, 0.30], $t(13) = 2.48$, $p = 0.027$; Std. beta = 0.51, 95% CI [0.07, 0.95])
- The effect of environ [Outdoor] is statistically non-significant and positive (beta = 0.28, 95% CI [-0.05, 0.61], $t(13) = 1.83$, $p = 0.090$; Std. beta = 0.75, 95% CI [-0.13, 1.63])

Standardized parameters were obtained by fitting the model on a standardized version of the dataset. 95% Confidence Intervals (CIs) and p-values were computed using a Wald t-distribution approximation.


```
parameters(model_fcat2)
```

Parameter	Coefficient	SE	95% CI	t(13)	p
(Intercept)	3.53	0.13	[3.24, 3.81]	26.97	< .001
avg daily snacks	0.16	0.07	[0.02, 0.30]	2.48	0.027
environ [Outdoor]	0.28	0.15	[-0.05, 0.61]	1.83	0.090


```
plot(model_parameters(model_fcat2), show_intercept = TRUE)
```



```
plot(model_parameters(model_fcat2))
```



```
cat_weights |>
  ggplot(aes(x = avg_daily_snacks, y = weight, colour = environ)) +
  geom_point() +
  labs(x = "Average Daily Snacks", y = "Cat Weight",
       caption = "Weight ~ Average Daily Snacks shown") +
  theme_classic() +
  scale_y_continuous(limits = c(0,5)) +
  geom_smooth()
```



Bayesian Framework

```
model_bcat2 <- stan_glm(weight ~ avg_daily_snacks + environ, data = cat_weights)
```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 1).

Chain 1:

Chain 1: Gradient evaluation took 1.8e-05 seconds

Chain 1: 1000 transitions using 10 leapfrog steps per transition would take 0.18 seconds.

Chain 1: Adjust your expectations accordingly!

Chain 1:

Chain 1:

Chain 1: Iteration: 1 / 2000 [0%] (Warmup)

Chain 1: Iteration: 200 / 2000 [10%] (Warmup)

Chain 1: Iteration: 400 / 2000 [20%] (Warmup)

Chain 1: Iteration: 600 / 2000 [30%] (Warmup)

Chain 1: Iteration: 800 / 2000 [40%] (Warmup)

Chain 1: Iteration: 1000 / 2000 [50%] (Warmup)

Chain 1: Iteration: 1001 / 2000 [50%] (Sampling)

Chain 1: Iteration: 1200 / 2000 [60%] (Sampling)

Chain 1: Iteration: 1400 / 2000 [70%] (Sampling)

Chain 1: Iteration: 1600 / 2000 [80%] (Sampling)
Chain 1: Iteration: 1800 / 2000 [90%] (Sampling)
Chain 1: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 1:
Chain 1: Elapsed Time: 0.059 seconds (Warm-up)
Chain 1: 0.065 seconds (Sampling)
Chain 1: 0.124 seconds (Total)
Chain 1:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 2).

Chain 2:
Chain 2: Gradient evaluation took 1.3e-05 seconds
Chain 2: 1000 transitions using 10 leapfrog steps per transition would take 0.13 seconds.
Chain 2: Adjust your expectations accordingly!
Chain 2:
Chain 2:
Chain 2: Iteration: 1 / 2000 [0%] (Warmup)
Chain 2: Iteration: 200 / 2000 [10%] (Warmup)
Chain 2: Iteration: 400 / 2000 [20%] (Warmup)
Chain 2: Iteration: 600 / 2000 [30%] (Warmup)
Chain 2: Iteration: 800 / 2000 [40%] (Warmup)
Chain 2: Iteration: 1000 / 2000 [50%] (Warmup)
Chain 2: Iteration: 1001 / 2000 [50%] (Sampling)
Chain 2: Iteration: 1200 / 2000 [60%] (Sampling)
Chain 2: Iteration: 1400 / 2000 [70%] (Sampling)
Chain 2: Iteration: 1600 / 2000 [80%] (Sampling)
Chain 2: Iteration: 1800 / 2000 [90%] (Sampling)
Chain 2: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 2:
Chain 2: Elapsed Time: 0.052 seconds (Warm-up)
Chain 2: 0.047 seconds (Sampling)
Chain 2: 0.099 seconds (Total)
Chain 2:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 3).

Chain 3:
Chain 3: Gradient evaluation took 1.1e-05 seconds
Chain 3: 1000 transitions using 10 leapfrog steps per transition would take 0.11 seconds.
Chain 3: Adjust your expectations accordingly!
Chain 3:
Chain 3:
Chain 3: Iteration: 1 / 2000 [0%] (Warmup)
Chain 3: Iteration: 200 / 2000 [10%] (Warmup)

```

Chain 3: Iteration: 400 / 2000 [ 20%] (Warmup)
Chain 3: Iteration: 600 / 2000 [ 30%] (Warmup)
Chain 3: Iteration: 800 / 2000 [ 40%] (Warmup)
Chain 3: Iteration: 1000 / 2000 [ 50%] (Warmup)
Chain 3: Iteration: 1001 / 2000 [ 50%] (Sampling)
Chain 3: Iteration: 1200 / 2000 [ 60%] (Sampling)
Chain 3: Iteration: 1400 / 2000 [ 70%] (Sampling)
Chain 3: Iteration: 1600 / 2000 [ 80%] (Sampling)
Chain 3: Iteration: 1800 / 2000 [ 90%] (Sampling)
Chain 3: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 3:
Chain 3: Elapsed Time: 0.047 seconds (Warm-up)
Chain 3:                0.042 seconds (Sampling)
Chain 3:                0.089 seconds (Total)
Chain 3:

```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 4).

```

Chain 4:
Chain 4: Gradient evaluation took 2.1e-05 seconds
Chain 4: 1000 transitions using 10 leapfrog steps per transition would take 0.21 seconds.
Chain 4: Adjust your expectations accordingly!
Chain 4:
Chain 4:
Chain 4: Iteration: 1 / 2000 [ 0%] (Warmup)
Chain 4: Iteration: 200 / 2000 [ 10%] (Warmup)
Chain 4: Iteration: 400 / 2000 [ 20%] (Warmup)
Chain 4: Iteration: 600 / 2000 [ 30%] (Warmup)
Chain 4: Iteration: 800 / 2000 [ 40%] (Warmup)
Chain 4: Iteration: 1000 / 2000 [ 50%] (Warmup)
Chain 4: Iteration: 1001 / 2000 [ 50%] (Sampling)
Chain 4: Iteration: 1200 / 2000 [ 60%] (Sampling)
Chain 4: Iteration: 1400 / 2000 [ 70%] (Sampling)
Chain 4: Iteration: 1600 / 2000 [ 80%] (Sampling)
Chain 4: Iteration: 1800 / 2000 [ 90%] (Sampling)
Chain 4: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 4:
Chain 4: Elapsed Time: 0.058 seconds (Warm-up)
Chain 4:                0.046 seconds (Sampling)
Chain 4:                0.104 seconds (Total)
Chain 4:

```

```
summary(model_bcat2)
```

Model Info:

```
function:    stan_glm
family:      gaussian [identity]
formula:     weight ~ avg_daily_snacks + environ
algorithm:   sampling
sample:      4000 (posterior sample size)
priors:      see help('prior_summary')
observations: 16
predictors:  3
```

Estimates:

	mean	sd	10%	50%	90%
(Intercept)	3.5	0.1	3.4	3.5	3.7
avg_daily_snacks	0.2	0.1	0.1	0.2	0.2
environOutdoor	0.3	0.2	0.1	0.3	0.5
sigma	0.3	0.1	0.2	0.3	0.4

Fit Diagnostics:

	mean	sd	10%	50%	90%
mean_PPD	3.9	0.1	3.8	3.9	4.1

The mean_ppd is the sample average posterior predictive distribution of the outcome variable

MCMC diagnostics

	mcse	Rhat	n_eff
(Intercept)	0.0	1.0	3785
avg_daily_snacks	0.0	1.0	3047
environOutdoor	0.0	1.0	2937
sigma	0.0	1.0	2680
mean_PPD	0.0	1.0	3807
log-posterior	0.0	1.0	1463

For each parameter, mcse is Monte Carlo standard error, n_eff is a crude measure of effective

```
describe_posterior(model_bcat2)
```

Summary of Posterior Distribution

Parameter	Median	95% CI	pd	ROPE	% in ROPE	Rhat
(Intercept)	3.53	[3.25, 3.81]	100%	[-0.04, 0.04]	0%	1.000
avg_daily_snacks	0.16	[0.02, 0.30]	98.90%	[-0.04, 0.04]	1.55%	1.001
environOutdoor	0.28	[-0.04, 0.62]	95.65%	[-0.04, 0.04]	4.18%	1.000

```
report::report(model_bcat2)
```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 1).

Chain 1:

Chain 1: Gradient evaluation took 1.6e-05 seconds

Chain 1: 1000 transitions using 10 leapfrog steps per transition would take 0.16 seconds.

Chain 1: Adjust your expectations accordingly!

Chain 1:

Chain 1:

Chain 1: Iteration: 1 / 2000 [0%] (Warmup)

Chain 1: Iteration: 200 / 2000 [10%] (Warmup)

Chain 1: Iteration: 400 / 2000 [20%] (Warmup)

Chain 1: Iteration: 600 / 2000 [30%] (Warmup)

Chain 1: Iteration: 800 / 2000 [40%] (Warmup)

Chain 1: Iteration: 1000 / 2000 [50%] (Warmup)

Chain 1: Iteration: 1001 / 2000 [50%] (Sampling)

Chain 1: Iteration: 1200 / 2000 [60%] (Sampling)

Chain 1: Iteration: 1400 / 2000 [70%] (Sampling)

Chain 1: Iteration: 1600 / 2000 [80%] (Sampling)

Chain 1: Iteration: 1800 / 2000 [90%] (Sampling)

Chain 1: Iteration: 2000 / 2000 [100%] (Sampling)

Chain 1:

Chain 1: Elapsed Time: 0.057 seconds (Warm-up)

Chain 1: 0.043 seconds (Sampling)

Chain 1: 0.1 seconds (Total)

Chain 1:

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 2).

Chain 2:

Chain 2: Gradient evaluation took 1.1e-05 seconds

Chain 2: 1000 transitions using 10 leapfrog steps per transition would take 0.11 seconds.

Chain 2: Adjust your expectations accordingly!

Chain 2:

Chain 2:

Chain 2: Iteration: 1 / 2000 [0%] (Warmup)

```

Chain 2: Iteration: 200 / 2000 [ 10%] (Warmup)
Chain 2: Iteration: 400 / 2000 [ 20%] (Warmup)
Chain 2: Iteration: 600 / 2000 [ 30%] (Warmup)
Chain 2: Iteration: 800 / 2000 [ 40%] (Warmup)
Chain 2: Iteration: 1000 / 2000 [ 50%] (Warmup)
Chain 2: Iteration: 1001 / 2000 [ 50%] (Sampling)
Chain 2: Iteration: 1200 / 2000 [ 60%] (Sampling)
Chain 2: Iteration: 1400 / 2000 [ 70%] (Sampling)
Chain 2: Iteration: 1600 / 2000 [ 80%] (Sampling)
Chain 2: Iteration: 1800 / 2000 [ 90%] (Sampling)
Chain 2: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 2:
Chain 2: Elapsed Time: 0.062 seconds (Warm-up)
Chain 2: 0.071 seconds (Sampling)
Chain 2: 0.133 seconds (Total)
Chain 2:

```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 3).

```

Chain 3:
Chain 3: Gradient evaluation took 1.9e-05 seconds
Chain 3: 1000 transitions using 10 leapfrog steps per transition would take 0.19 seconds.
Chain 3: Adjust your expectations accordingly!
Chain 3:
Chain 3:
Chain 3: Iteration: 1 / 2000 [ 0%] (Warmup)
Chain 3: Iteration: 200 / 2000 [ 10%] (Warmup)
Chain 3: Iteration: 400 / 2000 [ 20%] (Warmup)
Chain 3: Iteration: 600 / 2000 [ 30%] (Warmup)
Chain 3: Iteration: 800 / 2000 [ 40%] (Warmup)
Chain 3: Iteration: 1000 / 2000 [ 50%] (Warmup)
Chain 3: Iteration: 1001 / 2000 [ 50%] (Sampling)
Chain 3: Iteration: 1200 / 2000 [ 60%] (Sampling)
Chain 3: Iteration: 1400 / 2000 [ 70%] (Sampling)
Chain 3: Iteration: 1600 / 2000 [ 80%] (Sampling)
Chain 3: Iteration: 1800 / 2000 [ 90%] (Sampling)
Chain 3: Iteration: 2000 / 2000 [100%] (Sampling)
Chain 3:
Chain 3: Elapsed Time: 0.089 seconds (Warm-up)
Chain 3: 0.052 seconds (Sampling)
Chain 3: 0.141 seconds (Total)
Chain 3:

```

SAMPLING FOR MODEL 'continuous' NOW (CHAIN 4).

```

Chain 4:
Chain 4: Gradient evaluation took 1e-05 seconds
Chain 4: 1000 transitions using 10 leapfrog steps per transition would take 0.1 seconds.
Chain 4: Adjust your expectations accordingly!
Chain 4:
Chain 4:
Chain 4: Iteration:    1 / 2000 [  0%] (Warmup)
Chain 4: Iteration:   200 / 2000 [ 10%] (Warmup)
Chain 4: Iteration:   400 / 2000 [ 20%] (Warmup)
Chain 4: Iteration:   600 / 2000 [ 30%] (Warmup)
Chain 4: Iteration:   800 / 2000 [ 40%] (Warmup)
Chain 4: Iteration:  1000 / 2000 [ 50%] (Warmup)
Chain 4: Iteration:  1001 / 2000 [ 50%] (Sampling)
Chain 4: Iteration:  1200 / 2000 [ 60%] (Sampling)
Chain 4: Iteration:  1400 / 2000 [ 70%] (Sampling)
Chain 4: Iteration:  1600 / 2000 [ 80%] (Sampling)
Chain 4: Iteration:  1800 / 2000 [ 90%] (Sampling)
Chain 4: Iteration:  2000 / 2000 [100%] (Sampling)
Chain 4:
Chain 4: Elapsed Time: 0.073 seconds (Warm-up)
Chain 4:                0.098 seconds (Sampling)
Chain 4:                0.171 seconds (Total)
Chain 4:

```


We fitted a Bayesian linear model (estimated using MCMC sampling with 4 chains of 2000 iterations and a warmup of 1000) to predict weight with `avg_daily_snacks` and `environ` (formula: `weight ~ avg_daily_snacks + environ`). Priors over parameters were all set as normal (mean = 0.00, SD = 0.80; mean = 0.00, SD = 1.87) distributions. The model's explanatory power is substantial ($R^2 = 0.50$, 95% CI [0.17, 0.74], adj. $R^2 = 0.26$). The model's intercept, corresponding to `avg_daily_snacks` = 0 and `environ` = Indoor, is at 3.53 (95% CI [3.25, 3.81]). Within this model:

- The effect of `avg daily snacks` (Median = 0.16, 95% CI [0.02, 0.30]) has a 98.90% probability of being positive (> 0), 97.72% of being significant (> 0.02), and 76.35% of being large (> 0.11). The estimation successfully converged ($R_{\text{hat}} = 1.001$) and the indices are reliable (ESS = 3047)
- The effect of `environ [Outdoor]` (Median = 0.28, 95% CI [-0.04, 0.62]) has a 95.65% probability of being positive (> 0), 94.53% of being significant (> 0.02), and 85.28% of being large (> 0.11). The estimation successfully converged ($R_{\text{hat}} = 1.000$) and the indices are reliable (ESS = 2937)

Following the Sequential Effect eXistence and sIgnificance Testing (SEXIT) framework, we report the median of the posterior distribution and its 95% CI (Highest Density Interval), along the probability of direction (pd), the probability of significance and the probability of being large. The thresholds beyond which the effect is considered as significant (i.e., non-negligible) and large are |0.02| and |0.11| (corresponding respectively to 0.05 and 0.30 of the outcome's SD). Convergence and stability of the Bayesian sampling has been assessed using R-hat, which should be below 1.01 (Vehtari et al., 2019), and Effective Sample Size (ESS), which should be greater than 1000 (Burkner, 2017).

```
posteriors2 <- get_parameters(model_bcat2)

posteriors2 |>
  pivot_longer(cols = c(avg_daily_snacks, environOutdoor),
               names_to = "Parameter",
               values_to="estimate") |>
  ggplot() +
  geom_density(aes(x = estimate, fill = Parameter)) +
  theme_classic() +
  labs(x = "Posterior Coefficient Estimates",
       y = "Density") +
  facet_wrap(facets = ~Parameter, ncol = 1) +
  theme(legend.position = "none")
```




Lecture: Calculating variance

Why does it matter?

```
vardat <- tibble(cat = c(13, 17, 30, 36, 11, 43, 23, 50, 19, 23),
                  dog = c(30, 31, 45, 43, 48, 50, 37, 32, 40, 44))


vardat |>
  pivot_longer(cols = c(cat, dog),
               names_to = "Species",
               values_to = "Score") |>
  ggplot(aes(x = Species)) +
  geom_point(aes(y = Score, colour = Species), position = position_jitter(width = .13), size = 100) +
  see::geom_violinhalf(aes(y = Score, fill = Species), linetype = "dashed", position = position_jitter(width = .13)) +
  geom_boxplot(aes(y = Score, alpha = 0.3, colour = Species), position = position_nudge(x = 1)) +
  theme_classic() +
  labs(x = "Species", y = "Score") +
  theme(legend.position = "none") +
  coord_flip()
```



Residuals

```
resid <- tibble(x = c(1, 2, 3),
                y = c(3, 2, 6))


resid |>
  ggplot(aes(x, y)) +
  geom_point(size = 4, colour = "lightblue") +
  theme_classic() +
  geom_hline(yintercept = 3.67) +
  labs(title = "Plot of 3 points, mean of y shown") +
  theme(axis.text.x=element_blank(),
        axis.ticks.x=element_blank(),
        axis.title.x = element_blank())
```



Adding the residuals

```
resid |>
  ggplot(aes(x, y)) +
  geom_point(size = 4, colour = "lightblue") +
  theme_classic() +
  geom_hline(yintercept = 3.67) +
  geom_segment(aes(x = 1, y = 3.67, xend = 1, yend = 3)) +
  geom_segment(aes(x = 2, y = 3.67, xend = 2, yend = 2)) +
  geom_segment(aes(x = 3, y = 3.67, xend = 3, yend = 6)) +
  labs(title = "Plot of 3 points, mean of y shown, residuals shown") +
  theme(axis.text.x=element_blank(),
        axis.ticks.x=element_blank(),
        axis.title.x = element_blank())
```


Plot of 3 points, mean of y shown, residuals shown



Compare Variances

```
vardat |>
  summarise(var_dogs = var(dog),
            var_cat = var(cat))
```

```
# A tibble: 1 x 2
  var_dogs var_cat
  <dbl>    <dbl>
1      52     169.
```

Compare Standard Deviations

```
vardat |>
  summarise(sd_dogs = sd(dog),
            sd_cat = sd(cat))
```

```
# A tibble: 1 x 2
  sd_dogs sd_cat
  <dbl>   <dbl>
1    7.21   13.0
```

Compare Standard Errors

```
std.error <- function(x) sd(x)/sqrt(length(x))

vardat |>
  summarise(se_dogs = std.error(dog),
            se_cat = std.error(cat))
```

```
# A tibble: 1 x 2
  se_dogs se_cat
  <dbl>   <dbl>
1    2.28    4.11
```

Lecture: Meta Analyses

Calculate rs from R2

```
sqrt(0.11)
```

5 Week 4: Considerations for Collecting Data

Lecture 1: Effect Sizes and Covariance


Mock Data and visualisation

```
job_dat <- tibble(job = c("vet", "vet", "vet","vet", "vet", "vet", "vet", "vet", "vet", "vet",  
                          "assc", "assc", "assc", "assc", "assc", "assc", "assc", "assc", "assc", "as  
burnout = c(13, 12, 4, 16, 16, 20, 8, 10, 11, 10,  
            10, 11, 8, 7, 8, 10, 9, 11, 17, 10),  
empathy = c(4, 5, 1, 4,3, 5, 2, 3,3,2,  
            2, 3, 3, 2, 2, 3, 3, 4, 5, 2),  
satisfaction = c("yes", "no", "no", "no", "yes", "no", "yes", "no", "yes",  
                 "yes", "yes", "yes", "no", "yes", "yes", "yes", "no", "yes")
```



```
job_dat |>  
ggplot(aes(x = burnout, y = empathy, shape = job, colour = satisfaction)) +  
geom_point() +  
theme_classic() +  
labs(title = "Burnout and empathy scores for vets and associated professions",  
      subtitle = "Job Satisfaction shown",  
      caption = "Mock data for teaching",  
      x = "Burnout Score",  
      y = "Empathy Score") +  
scale_shape_discrete(name = "Vet or Associated Profession") +  
scale_color_discrete(name = "Satisfied with job?")
```

Burnout and empathy scores for vets and associated profession:
Job Satisfaction shown



Calculate Cohen's d

```
library(effsize)

cohen.d(d = job_dat$burnout, f = job_dat$job)
```

Cohen's d

```
d estimate: -0.5048995 (medium)
95 percent confidence interval:
      lower      upper
-1.4593128  0.4495138
```

Calculate Hedge's g


```
cohen.d(d = job_dat$burnout, f = job_dat$job, hedges.correction = TRUE)
```

Hedges's g

g estimate: -0.4835657 (small)
95 percent confidence interval:
lower upper
-1.3964834 0.4293519

Effects of Differences

```
job_dat |>
  ggplot(aes(x = burnout, y = empathy)) +
  geom_point() +
  theme_classic() +
  labs(x = "Burnout Score", y = "Empathy Score")
```



Correlation coefficient (r)

```
cor(job_dat$burnout, job_dat$empathy, method = "pearson")
```

```
[1] 0.7991678
```

Other Correlation Coefficients

```
cor(job_dat$burnout, job_dat$empathy, method = "spearman")
```

```
[1] 0.8202187
```

```
cor.test(job_dat$burnout, as.numeric(as.factor(job_dat$job)))
```

Pearson's product-moment correlation

```
data: job_dat$burnout and as.numeric(as.factor(job_dat$job))
t = 1.129, df = 18, p-value = 0.2737
alternative hypothesis: true correlation is not equal to 0
95 percent confidence interval:
 -0.2091671  0.6281908
sample estimates:
      cor
0.2571562
```

Cramer's V

```
library(lsr)

job_dat <- job_dat |>
  mutate(burnoutcat = case_when(burnout > 10 ~ "burnout",
                                TRUE ~ "no burnout"))
```



```
job_tbl <- xtabs(~job_dat$job + job_dat$satisfaction + job_dat$burnoutcat)
ftable(job_tbl)
```

		job_dat\$burnoutcat	
		burnout	no burnout
job_dat\$job	job_dat\$satisfaction		
assc	no	1	1
	yes	2	6
vet	no	3	2
	yes	3	2

```
chisq.test(ftable(job_tbl))
```

Pearson's Chi-squared test

```
data: ftable(job_tbl)
X-squared = 2.2222, df = 3, p-value = 0.5276
```

```
cramersV(ftable(job_tbl))
```

```
[1] 0.3333333
```

R²adj Example

```
jobmod <- lm(burnout ~ empathy + satisfaction, data = job_dat)
summary(jobmod)
```

Call:

```
lm(formula = burnout ~ empathy + satisfaction, data = job_dat)
```

Residuals:

Min	1Q	Median	3Q	Max
-3.7526	-1.0832	-0.3836	1.4822	4.7305

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	1.9944	1.8904	1.055	0.306
empathy	2.7516	0.4865	5.656	2.85e-05 ***
satisfactionyes	1.0202	1.1393	0.895	0.383


Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 2.354 on 17 degrees of freedom

Multiple R-squared: 0.6549, Adjusted R-squared: 0.6144

F-statistic: 16.13 on 2 and 17 DF, p-value: 0.000118

```
job_dat |>
  mutate(mod = predict(jobmod)) |>
  ggplot() +
    geom_point(aes(x = empathy, y = burnout, colour = satisfaction)) +
    geom_line(aes(x = empathy, y = mod)) +
    theme_classic() +
    facet_wrap(facets = ~ satisfaction, ncol = 1) +
    labs(x = "Empathy Score", y = "Burnout Score")
```



Covariance

```
jobmod2 <- lm(burnout ~ empathy + job, data = job_dat)
summary(jobmod2)
```

Call:

```
lm(formula = burnout ~ empathy + job, data = job_dat)
```

Residuals:

Min	1Q	Median	3Q	Max
-4.6359	-1.3894	-0.4212	1.6035	4.5151

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	2.631	1.552	1.695	0.108
empathy	2.575	0.471	5.469	4.16e-05 ***
jobvet	1.127	1.052	1.072	0.299


Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 2.331 on 17 degrees of freedom

Multiple R-squared: 0.6615, Adjusted R-squared: 0.6217

F-statistic: 16.61 on 2 and 17 DF, p-value: 0.0001002

```
job_dat |>
  mutate(mod = predict(jobmod2)) |>
  ggplot() +
  geom_point(aes(x = empathy, y = burnout, colour = job)) +
  geom_line(aes(x = empathy, y = mod)) +
  theme_classic() +
  facet_wrap(facets = ~ job, ncol = 1) +
  labs(x = "Empathy Score", y = "Burnout Score")
```



6 Week 5: Sources of Data

Lecture 1 Digital Media Research



6.1 Who's in digital spaces

```
library(tidyverse)

internet <- tibble(year = c(2013, 2014, 2015, 2016, 2017, 2018, 2019, 2020),
  "16-24" = c(98.3, 98.9, 98.8, 99.2, 99.2, 99.3, 99.2, 99.5),
  "25-34" = c(97.7, 98.3, 98.6, 98.9, 99.1, 99.2, 99.4, 99.5),
  "35-44" = c(95.8, 96.7, 97.3, 98.2, 98.4, 98.6, 98.9, 99.1),
  "45-54" = c(90.2, 92.3, 93.6, 94.9, 96.2, 96.8, 97.5, 97.9),
  "55-64" = c(81.3, 84.2, 86.7, 88.3, 90.0, 91.8, 93.2, 94.6),
  "65-74" = c(61.1, 65.5, 70.6, 74.1, 77.5, 80.2, 83.2, 85.5),
  "75+" = c(29.1, 31.9, 33.0, 38.7, 40.5, 43.6, 46.8, 54.0))

internet |>
  pivot_longer(cols = -year,
    names_to = "age",
    values_to = "perc")

internet |>
  ggplot(aes(x = year, y = perc, fill = age)) +
  geom_bar(stat = "identity", position = "dodge2") +
  theme_classic() +
  theme(legend.position = "bottom") +
  labs(x = "Year", y = "Percentage of Adults",
    caption = "UK adults who used the internet in the last 3 months (Jan-March)\nData from")
```



UK adults who used the internet in the last 3 months (Jan-March)
Data from ONS

Lecture 4: Meta Analyses

Calculate rs from R2

```
sqrt(0.11)
```


7 Week 6: Reading Week

There's no R content in this week this year :)

8 Weeks 7 and 8: R Stats

All your R content is elsewhere this week :)

9 Week 9 Analysing Quantitative Data


Lecture 1: Partitioning Variation

```
library(tidyverse)

examples <- tibble (x.perfect = c(1,2,3,4,5,6,7,8,9,10),
                    y.perfect = c(1,2,3,4,5,6,7,8,9,10),
                    x.realistic = c(1,2,3,4,4,6,8,8,9,11),
                    y.realistic = c(2, 2, 4, 5, 5, 5, 7, 8, 9, 9))
```

A Perfect World


```
examples |>
  ggplot (aes(x = x.perfect, y = y.perfect))+
  geom_point (shape = 8) +
  scale_y_continuous(limits = c(0,10)) +
  scale_x_continuous(limits = c(0,10)) +
  labs (title = "100% of the variation in y is explained by x",
        x = "A Perfect Explanatory Variable",
        y = "A Perfect Response Variable") +
  theme_classic()
```



Our Unicorn Farm


```
unicorns <- tibble (NoRadio = c(150, 130, 121, 90, 98, 100, 98, 100, 113, 111),
                    RadioMusic = c(112, 127, 132, 150, 112, 128, 110, 120, 98, 107),
                    RadioDiscussion = c(75, 98, 88, 83, 83, 77, 75, 84, 93, 99)) |>
  pivot_longer(cols = c(NoRadio:RadioDiscussion),
               names_to = "Radio",
               values_to = "DustYield")

unicorns |>
  ggplot (aes (x = Radio, y = DustYield)) +
  geom_point(aes(shape = Radio, colour = Radio), position = position_jitter(width = .13)) +
  labs (y = "Dust Yield (Kg)", x = "Radio Condition") +
  scale_color_brewer(palette = "Accent") +
  scale_y_continuous(limits = c(0, 200)) +
  theme_classic () +
  theme(legend.position = "none")
```



No Radio Group

```
unicorns |>
  filter(Radio == "NoRadio") |>
  mutate(UnicornNo = c(1,2,3,4,5,6,7,8,9,10)) |>
  # The mutate function adds a new variable just to plot this one specific chart
  # And then we pipe it directly into ggplot, so we're not changing the unicorns data
  # Remember you can check this with `View(unicorns)`, you'll see 'UnicornNo' doesn't exist.
  ggplot (aes (x = UnicornNo, y = DustYield)) +
  geom_point() +
  labs (y = "Dust Yield (Kg)", x = "Unicorn No") +
  scale_y_continuous(limits = c(0, 200)) +
  scale_x_continuous(breaks = c(0, 2, 4, 6, 8, 10)) +
  theme_classic ()
```




No Radio Mean

```
unicorns |>
  group_by(Radio) |>
  filter(Radio == "NoRadio") |>
  summarise(mean = mean(DustYield))
```

```
# A tibble: 1 x 2
  Radio     mean
  <chr>   <dbl>
1 NoRadio 111.
```

```
unicorns |>
  filter(Radio == "NoRadio") |>
  mutate(UnicornNo = c(1,2,3,4,5,6,7,8,9,10)) |>
  # The mutate function adds a new variable just to plot this one specific chart
  # And then we pipe it directly into ggplot, so we're not changing the unicorns data
  # Remember you can check this with `View(unicorns)`, you'll see 'UnicornNo' doesn't exist.
  ggplot(aes(x = UnicornNo, y = DustYield)) +
  geom_point() +
```

```
geom_hline(yintercept = 111.1)+
labs (y = "Dust Yield (Kg)", x = "Unicorn No") +
scale_y_continuous(limits = c(0, 200)) +
scale_x_continuous(breaks = c(0, 2, 4, 6, 8, 10)) +
theme_classic ()
```



Deviations from the mean

```
unicorns |>
  filter(Radio == "NoRadio") |>
  mutate(Diff = DustYield-111.1)
```

A tibble: 10 x 3

	Radio	DustYield	Diff
	<chr>	<dbl>	<dbl>
1	NoRadio	150	38.9
2	NoRadio	130	18.9
3	NoRadio	121	9.9
4	NoRadio	90	-21.1


```

5 NoRadio      98 -13.1
6 NoRadio     100 -11.1
7 NoRadio      98 -13.1
8 NoRadio     100 -11.1
9 NoRadio     113  1.90
10 NoRadio     111 -0.100

```

```

unicorns |>
  filter(Radio == "NoRadio") |>
  mutate(Diff = DustYield-111.1) |>
  summarise(`Sum of Differences` = sum(Diff))

```

```

# A tibble: 1 x 1
  `Sum of Differences`
      <dbl>
1          5.68e-14

```

Variance

```
#: eval: true
```

```

unicorns |>
  group_by(Radio) |>
  summarise (Variance = var(DustYield))

```

Imaginary Scenarios

```

Sce1 <- tibble (Condition1 = c(99,100,101,99,100,101,99,101,100,101),
                    Condition2 = c(120,121,122,120,121,122,120,123,121,120),
                    Condition3 = c(83,84,85,85,84,83,83,84,85,86)) |>
  pivot_longer (cols = c(Condition1:Condition3), names_to = "Condition", values_to = "DustYield")
  mutate (Count = c(1:30))

Sce2 <-tibble (Condition1 = c(84,86,123,95,87,110,99,95,121,121),
                    Condition2 = c(83,115,85,85, 110,105,84,115,101,100),
                    Condition3 = c(84,122,80,80,101,83,83,99, 120,120)) |>

```

```

pivot_longer (cols = c(Condition1:Condition3), names_to = "Condition", values_to = "DustYield")
mutate (Count = c(1:30))

```


```

ImaginaryScenario1 <- Sce1 |>
  ggplot (aes (x = Count, y = DustYield)) +
  geom_point(aes(shape = Condition, colour = Condition)) +
  labs (y = "Dust Yield (Kg)", x = "Unicorn ID Number") +
  scale_y_continuous(limits = c(0, 200)) +
  theme_classic ()

# I have also made this chart an object because we're going to update it
# It's quicker to do this as an object
# You can compare how we update this chart with how we update the ones above.

```

```
ImaginaryScenario1
```




```

experiment <- Sce2 |>
  ggplot (aes (x = Count, y = DustYield)) +
  geom_point(aes(shape = Condition, colour = Condition)) +


```

```
labs (y = "Dust Yield (Kg)", x = "Unicorn ID Number") +
scale_y_continuous(limits = c(0, 200)) +
theme_classic ()
```


experiment




```
ImaginaryScenario1 +
  geom_hline(yintercept = mean(Sce1$DustYield))
```




```
experiment +  
  geom_hline(yintercept = mean(Sce2$DustYield))
```



```
ImaginaryScenario1 +
  geom_hline(yintercept = mean(Sce1$DustYield)) +
  geom_segment(aes(x = 1, y = 100.1, xend = 30, yend = 100.1, color = "red")) +
  geom_segment(aes(x = 1, y = 121.0, xend = 30, yend = 121.0, color = "green")) +
  geom_segment(aes(x = 1, y = 84.2, xend = 30, yend = 84.2, color = "blue")) +
  theme(legend.position = "none")
```



```
experiment +
  geom_hline(yintercept = mean(Sce1$DustYield)) +
  geom_segment(aes(x = 1, y = 102, xend = 30, yend = 102, color = "red")) +
  geom_segment(aes(x = 1, y = 98.3, xend = 30, yend = 98.3, color = "green")) +
  geom_segment(aes(x = 1, y = 97.2, xend = 30, yend = 97.2, color = "blue")) +
  theme(legend.position = "none")
```



```
Sce2 |>
  group_by(Condition) |>
  summarise(mean = mean (DustYield))
```

```
# A tibble: 3 x 2
  Condition  mean
  <chr>      <dbl>
1 Condition1 102.
2 Condition2  98.3
3 Condition3  97.2
```

MFY

```
MFY <- unicorns |>
  mutate ("Y" = DustYield) |>
  mutate ("M" = mean(Y)) |>
  # If we now ask R to group the data, it will calculate the mean per group:
  group_by(Radio) |>
  mutate ("F" = mean(Y)) |>
  # Remember to ungroup after!
```

```

ungroup()

MFY <- MFY |>
  mutate (MY = (Y-M),
          MF = (F-M),
          FY = (Y - F))

MFY <- MFY |>
  mutate (MY2 = (MY*MY),
          MF2 = (MF*MF),
          FY2 = (FY*FY))

MFY |>
  summarise(SumSquareMY = sum(MY2),
            SumSquareMF = sum(MF2),
            SumSquareFY = sum(FY2))

```

```

# A tibble: 1 x 3
  SumSquareMY SumSquareMF SumSquareFY
      <dbl>      <dbl>      <dbl>
1    12053.      6301.      5752.

```

```

MFY |>
  summarise(SumSquareMY = sum(MY2),
            SumSquareMF = sum(MF2),
            SumSquareFY = sum(FY2),
            MeanSquareMY = sum(MY2)/29,
            MeanSquareMF = sum(MF2)/2,
            MeanSquareFY = sum(FY2)/27)

```

```

# A tibble: 1 x 6
  SumSquareMY SumSquareMF SumSquareFY MeanSquareMY MeanSquareMF MeanSquareFY
      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>      <dbl>
1    12053.      6301.      5752.         416.       3151.        213.

```

```
ANOVA <- aov(DustYield ~ Radio, data = unicorns)
summary(ANOVA)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
Radio	2	6301	3151	14.79	4.6e-05 ***
Residuals	27	5752	213		

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Lecture 2: Choosing a Statistical Test


```
library(tidyverse)

cows <- readxl::read_excel("cows.xlsx") |>
  mutate(parlour = as.factor(parlour),
         `housing type` = as.factor(`housing type`))

cows |>
  ggplot(aes(x = `Welfare Score`, y = `Average Daily Yield`, colour = `housing type`)) +
  geom_point() +
  theme_classic() +
  labs(x = "Welfare Score", y = "Average Daily Yield",
       title = "Milk Yield versus Welfare Score",
       subtitle = "For Robotic vs Manual Parlours") +
  facet_wrap(facets = ~parlour, ncol = 1) +
  theme(legend.position = "bottom")
```

Milk Yield versus Welfare Score

For Robotic vs Manual Parlours



Numerical Response

```
cows |>
  summarise(mean_yield = mean(`Average Daily Yield`),
            sd_yield = sd(`Average Daily Yield`))
```

```
# A tibble: 1 x 2
  mean_yield sd_yield
    <dbl>     <dbl>
1       32       3.73
```

```
t.test(cows$`Average Daily Yield`, mu = 28)
```

One Sample t-test

```
data: cows$`Average Daily Yield`
t = 21.448, df = 399, p-value < 2.2e-16
alternative hypothesis: true mean is not equal to 28
```

95 percent confidence interval:

31.63336 32.36664

sample estimates:


mean of x

32

Numerical Response Categorical Explanatory

```
diet <- tibble (before = c(5.04, 4.63, 4.04, 5.10, 5.43, 4.83, 3.45, 3.49, 5.02, 4.81),  
               after  = c( 4.78, 2.49, 4.46, 2.03, 5.13, 7.23, 3.50, 1.89, 3.30, 3.91))
```

```
diet |>  
  ggplot(aes(y = before)) +  
  geom_boxplot() +  
  geom_boxplot(aes(y = after, x =1)) +  
  theme_classic() +  
  scale_x_continuous(labels =c("Before Diet", "After Diet"), breaks = c(0,1)) +  
  labs(x = "Diet", y = "Weight (kg)")
```



```
diet |>
  summarise(before_mean = mean(before),
            after_mean = mean(after),
            before_sd = sd(before),
            after_sd = sd(after))
```

```
# A tibble: 1 x 4
  before_mean after_mean before_sd after_sd
      <dbl>      <dbl>      <dbl>    <dbl>
1      4.58      3.87      0.689     1.62
```

```
t.test(diet$before, diet$after, paired = TRUE, alternative = "two.sided")
```

Paired t-test

```
data: diet$before and diet$after
t = 1.4615, df = 9, p-value = 0.1779
alternative hypothesis: true mean difference is not equal to 0
95 percent confidence interval:
 -0.3900511  1.8140511
sample estimates:
mean difference
      0.712
```

2-Way ANOVA

```
model1 <- aov(`Average Daily Yield` ~ parlour + `housing type`, data = cows)
summary(model1)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
parlour	1	900	900.0	78.511	< 2e-16 ***
`housing type`	1	100	100.0	8.723	0.00333 **
Residuals	397	4551	11.5		

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Linear model

```
model2 <- lm(`Average Daily Yield` ~ parlour + `housing type`, data = cows)
summary(model2)
```

Call:

```
lm(formula = `Average Daily Yield` ~ parlour + `housing type`,
    data = cows)
```

Residuals:

Min	1Q	Median	3Q	Max
-10.8651	-1.7814	0.0787	1.6805	11.7654

Coefficients:

	Estimate	Std. Error	t value	Pr(> t)
(Intercept)	34.0000	0.2932	115.956	< 2e-16 ***
parlourrobot	-3.0000	0.3386	-8.861	< 2e-16 ***
`housing type`seasonally housed	-1.0000	0.3386	-2.954	0.00333 **

Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

Residual standard error: 3.386 on 397 degrees of freedom

Multiple R-squared: 0.1801, Adjusted R-squared: 0.176

F-statistic: 43.62 on 2 and 397 DF, p-value: < 2.2e-16

Numerical Response Numerical Explanatory

Correlation

```
cor.test(cows$`Average Daily Yield`, cows$`Welfare Score`)
```

Pearson's product-moment correlation

data: cows\$`Average Daily Yield` and cows\$`Welfare Score`

t = 1.7643, df = 398, p-value = 0.07845

alternative hypothesis: true correlation is not equal to 0

95 percent confidence interval:

-0.01004724 0.18454894

sample estimates:

cor

0.08809126

Linear Model

Generalised Linear Model

```
#| eval: true

model4 <- glm(`Average Daily Yield` ~ `Welfare Score`
              + `housing type` + parlour, data = cows)
summary(model4)
```

Categorical Response

Proportion Test

```
prop.test(x = 3, n = 20, p = 0.18, alternative = "two.sided")
```

1-sample proportions test with continuity correction

```
data: 3 out of 20, null probability 0.18
X-squared = 0.0033875, df = 1, p-value = 0.9536
alternative hypothesis: true p is not equal to 0.18
95 percent confidence interval:
 0.03956627 0.38862512
sample estimates:
      p
0.15
```

Categorical Response Categorical Explanatory

McNemar's Test

```
work <- matrix(c(2, 5, 38, 35),
               ncol=2,
               byrow=TRUE,
               dimnames = list(c("Dysplasia", "No Dysplasia"),
                              c("Before Work Season", "After Work Season")))

mcnemar.test(work)
```

McNemar's Chi-squared test with continuity correction

data: work

McNemar's chi-squared = 23.814, df = 1, p-value = 1.061e-06

Fisher's Exact Test

```
fisher.test(x = c(4,16), y = c(2,18))
```

Fisher's Exact Test for Count Data

data: c(4, 16) and c(2, 18)

p-value = 1

alternative hypothesis: true odds ratio is not equal to 1

95 percent confidence interval:

0.02564066 Inf

sample estimates:

odds ratio

Inf

```
# Calculate Odds Ratio
```

```
(4+18) / (16 + 2)
```

```
[1] 1.222222
```

Chi2 Test

```
gsd <- matrix(c(16, 12, 84, 86),
              ncol=2,
              byrow=TRUE,
              dimnames = list(c("Dysplasia", "No Dysplasia"),
                             c("Inbred", "Less Inbred")))

chisq.test(gsd)
```

Pearson's Chi-squared test with Yates' continuity correction

```
data: gsd
X-squared = 0.30714, df = 1, p-value = 0.5794
```

```
library(vcd)
assocstats(gsd)
```

	X ²	df	P(> X ²)
Likelihood Ratio	0.57672	1	0.44760
Pearson	0.57481	1	0.44835

```
Phi-Coefficient      : 0.054
Contingency Coeff.: 0.054
Cramer's V           : 0.054
```

Categorical Response Numerical Explanatory

Logistic Regression

```
dysp <- tibble(dysplasia = c(1, 1, 1, 1, 1, 1, 1,
                             0, 0, 0, 0, 0, 0, 0,
                             0, 0, 0, 0, 0, 0, 0),
               inflammation = c(0.91, 0.79, 1.40, 0.71, 1.01, 0.77, 0.85,
                                0.42, 1.02, 0.31, 0.05, 1.17, 0.04, 0.36,
                                0.12, 0.02, 0.05, 0.42, 0.92, 0.72, 1.05))

logit <- glm(dysplasia ~ inflammation, data = dysp, family = "binomial")
summary(logit)
```



```

Call:
glm(formula = dysplasia ~ inflammation, family = "binomial",
    data = dysp)

Deviance Residuals:
    Min       1Q   Median       3Q      Max
-1.5715  -0.5727  -0.3094   1.0397   1.4914

Coefficients:
              Estimate Std. Error z value Pr(>|z|)
(Intercept)   -3.190      1.484  -2.150   0.0316 *
inflammation    3.488      1.740   2.004   0.0450 *
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

(Dispersion parameter for binomial family taken to be 1)

    Null deviance: 26.734  on 20  degrees of freedom
Residual deviance: 20.534  on 19  degrees of freedom
AIC: 24.534

Number of Fisher Scoring iterations: 5

```

```

library(easystats)
report(logit)

```

We fitted a logistic model (estimated using ML) to predict dysplasia with inflammation (formula: `dysplasia ~ inflammation`). The model's explanatory power is moderate (Tjur's $R^2 = 0.24$). The model's intercept, corresponding to inflammation = 0, is at -3.19 (95% CI [-7.09, -0.88], $p = 0.032$). Within this model:

- The effect of inflammation is statistically significant and positive ($\beta = 3.49$, 95% CI [0.65, 7.91], $p = 0.045$; Std. $\beta = 1.47$, 95% CI [0.27, 3.33])

Standardized parameters were obtained by fitting the model on a standardized version of the dataset. 95% Confidence Intervals (CIs) and p-values were computed using a Wald z-distribution approximation.

```
parameters(logit)
```

Parameter		Log-Odds		SE		95% CI		z		p
(Intercept)		-3.19		1.48		[-7.09, -0.88]		-2.15		0.032
inflammation		3.49		1.74		[0.65, 7.91]		2.00		0.045

```
exp(cbind(OddsRatio = coef(logit), confint(logit)))
```

	OddsRatio	2.5 %	97.5 %
(Intercept)	0.04118154	0.0008355444	0.4146414
inflammation	32.71638289	1.9151146706	2735.6121035

Parametric vs Non Parametric

Power Calculations

Assumptions

Residuals

```
residuals <- tibble(resids = resid(model4))

residuals |>
  ggplot(aes(x = resids)) +
  geom_density()+
  theme_classic()

parameters::describe_distribution(residuals)
```

10 Week 10: Analysing Quantitative Data

You have no R content in this week

11 References

References

The cover image duck comes from [Pixabay](#), as a Creative Commons 0 image by Clker-Free-Vector-Images-3736

Brilleman, SL, MJ Crowther, M Moreno-Betancur, J Bueros Novik, and R Wolfe. 2018. *Joint Longitudinal and Time-to-Event Models via Stan*. https://github.com/stan-dev/stancon_talks/.

Fellows, Ian. 2018. *Wordcloud: Word Clouds*. <https://CRAN.R-project.org/package=wordcloud>.

Lüdecke, Daniel, Mattan S. Ben-Shachar, Indrajeet Patil, Brenton M. Wiernik, and Dominique Makowski. 2022. “Easystats: Framework for Easy Statistical Modeling, Visualization, and Reporting.” *CRAN*. <https://easystats.github.io/easystats/>.

Patil, Indrajeet. 2021. “Visualizations with statistical details: The ‘ggstatsplot’ approach.” *Journal of Open Source Software* 6 (61): 3167. <https://doi.org/10.21105/joss.03167>.

Stan Development Team. 2023. *RStan: The R Interface to Stan*. <https://mc-stan.org/>.

Torchiano, Marco. 2020. *Effsize: Efficient Effect Size Computation*. <https://doi.org/10.5281/zenodo.1480624>.

Wickham, Hadley, Mara Averick, Jennifer Bryan, et al. 2019. “Welcome to the tidyverse.” *Journal of Open Source Software* 4 (43): 1686. <https://doi.org/10.21105/joss.01686>.

Zeileis, Achim, David Meyer, and Kurt Hornik. 2007. “Residual-Based Shadings for Visualizing (Conditional) Independence.” *Journal of Computational and Graphical Statistics* 16 (3): 507–25. <https://doi.org/10.1198/106186007X237856>.