

MTUSB Cable Board

The mlx cables tool supports reading cable data directly via i2c when the cable is connected to a dedicated board. The board is connected to the host with an MTUSB adapter.

Examples on a Windows machine:

After adding the cables using 'mst cable add' the following mst status is presented:

```
1  mst status
2  MST devices:
3  -----
4  mtusb-1
5  Cable MST devices:
6  -----
7  mtusb-1_cable
```

Query the cable:

```
1  mlx cables -d mtusb-1_cable
2  Querying Cables ....
3  Cable #1:
4  -----
5  Cable name      : mtusb-1_cable
6  FW version     : 2.0.208
7  FW Dev ID      : 0x20
8  FW GW version  : Legacy
9  ----- Cable EEPROM -----
10 Identifier     : QSFP+ (0dh)
11 Technology     : 850 nm VCSFI (00h)
```

```
14 001 : 0x00209
15 Vendor      : Mellanox
16 Serial number : MT1707FT01544
17 Part number  : MFA1A00-E001
18 Revision    : A1
19 Temperature  : 31 C
20 Length      : 1 m
```

Read from a specific address:

```
mlx cables -d mtusb-1_cable -r -p 0 -o 165 -l 3
Page[0].Byte[165] = 0x00
```

```
Page[0].Byte[166] = 0x02
Page[0].Byte[167] = 0xc9
```

Last updated: March 28, 2019

← Previous page
[mlx cables - Cables Tool](#)

Next page →
[Cable Firmware Upgrade with
Live-Patch](#)

🔗 Use with AI ▾



- Privacy Policy
- Your Privacy Choices
- Terms of Service
- Accessibility
- Corporate Policies
- Product Security
- Contact