

cloud-function (cf)

For information about concepts and other user interfaces, see the [Overview](#) from the NVCF Documentation.

Cloud Function Commands

```
usage: ngc cloud-function [--debug] [--format_type <fmt>] [--org <name>]
                        [--team <name>] [-h]
                        {available-gpus,cluster,function,gpu,registry-credential,task,t
                        ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

cloud-function

```
{available-gpus,cluster,function,gpu,registry-credential,task,telemetry-endpoint}
```

Possible choices: available-gpus, cluster, fn, function, gpu, instance-type, registry-credential, task, telemetry-endpoint

Sub-commands

function (fn)

Cloud function function commands.

```
ngc cloud-function function [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
                             {authorization,create,deploy,info,instance,list,remove,remove-rate-limit,update,update-rate-limit,update-secret}
                             ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

function

```
{authorization,create,deploy,info,instance,list,remove,remove-rate-limit,update,update-rate-limit,update-secret}
```

Possible choices: auth, authorization, create, delete, deploy, info, instance, list, ls, remove, remove-rate-limit, rm, update, update-rate-limit, update-secret

Sub-commands

authorization (auth)

Function Authorization Commands. Admin Only.

```
ngc cloud-function function authorization [--debug] [--format_type <fmt>]
                                         [--org <name>] [--team <name>] [-h]
                                         {add,clear,info,remove} ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

authorization

{add,clear,info,remove}

Possible choices: add, clear, delete, info, remove, rm

Sub-commands

info

Gets NVIDIA Cloud Account IDs that are authorized to invoke specified functions/function versions

```
ngc cloud-function function authorization info [--debug] [--format_type <fmt>]
                                                [--org <name>] [--team <name>]
                                                [-h]
                                                <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

clear

Clear all function's extra authorizations

```
ngc cloud-function function authorization clear [--debug]
                                           [--format_type <fmt>]
                                           [--org <name>] [--team <name>]
                                           [-h]
                                           <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

remove (delete, rm)

Unauthorize account from invoking function or function version

```
ngc cloud-function function authorization remove --authorized-party <nca-id>
                                              [--debug]
                                              [--format_type <fmt>]
                                              [--org <name>]
                                              [--team <name>] [-h]
                                              <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

Required named arguments

--authorized-party

Authorized Party. NCA ID

add

Authorize accounts to function version or function

```
ngc cloud-function function authorization add --authorized-party <nca-id>
[--debug] [--format_type <fmt>]
[--org <name>] [--team <name>]
[-h]
<function-id>:<function-version-id>
```

Positional Arguments

<function-id>:<function-version-id>

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

Required named arguments

`--authorized-party`

Authorized Party. NCA ID

deploy

Function deployment commands

```
ngc cloud-function function deploy [--debug] [--format_type <fmt>]
                                   [--org <name>] [--team <name>] [-h]
                                   {create,info,list,log,remove,restart,update}
                                   ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

deploy

`{create,info,list,log,remove,restart,update}`

Possible choices: create, delete, info, list, log, ls, redeploy, remove, restart, rm, update

Sub-commands

list (ls)

List deployments

```
ngc cloud-function function deploy list [--debug] [--format_type <fmt>]
                                         [--org <name>] [--status <status>]
                                         [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--status

Possible choices: ACTIVE, ERROR

Filter deployments by status type

info

Info about a function deployment

```
ngc cloud-function function deploy info [--debug] [--format_type <fmt>]
                                         [--org <name>] [--team <name>] [-h]
                                         <function-id>:<function-version-id>
```

Positional Arguments

<function-id>:<function-version-id>

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

remove (rm, delete)

Undeploy a function

```
ngc cloud-function function deploy remove [--debug] [--format_type <fmt>]
                                           [--graceful] [--org <name>]
                                           [--team <name>] [-h]
                                           <function-id>:<function-version-id>
```

Positional Arguments

<function-id>:<function-version-id>

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--graceful

Allow current tasks to complete before deleting deployment.

restart (redeploy)

Restart a currently deployed function

```
ngc cloud-function function deploy restart [--debug] [--format_type <fmt>]
                                           [--org <name>] [--team <name>] [-h]
                                           <function-id>:<function-version-id>
```

Positional Arguments

<function-id>:<function-version-id>

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

update

Update an existing deployment

```
ngc cloud-function function deploy update [--configuration CONFIGURATION]
                                         [--configuration-file <file.yaml>]
                                         [--debug]
                                         [--deployment-specification <dep-spec>]
                                         [--format_type <fmt>] [--org <name>]
                                         [--set <key1.key2=value>]
                                         [--targeted-deployment-specification <targeted-
                                         <function-id>:<function-version-id>
```

Positional Arguments

<function-id>:<function-version-id>

Function. Format: function-id:function-version

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--configuration

Helm chart overrides json will apply cross the functions, only for Helm chart deployment

--configuration-file, -f

Helm chart overrides yaml. Can apply multiple times. The priority will be given to the last (right-most) file specified.

--set

Set configuration values (e.g., --set image.tag=latest). Can apply multiple times.

`--deployment-specification, --dep-spec`

Deployment specs with GPU and Backend details, can specify multiple times. (Format: backend:gpu:instance_type:min_instances:max_instances[:max_request_concurrency])

`--targeted-deployment-specification, --targeted-dep-spec`

Deployment specs with GPU and instance type, can specify multiple times. Clusters are mandatory for non GFN backends. (Format:

<gpu:instance_type:min_instances:max_instances[:max_request_concurrency]
[:clusters(cluster_1,cluster_2)][:regions(region_1,region_2)][:attributes(attribute_1,attribute_2)]
[:preferredOrder])

create

Create a deployment

```
ngc cloud-function function deploy create [--configuration CONFIGURATION]
                                         [--configuration-file <file.yaml>]
                                         [--debug]
                                         [--deployment-specification <backend:gpu:instance_type:min_instances:max_instances[:max_request_concurrency]>]
                                         [--format_type <fmt>] [--org <name>]
                                         [--set key1.key2=value]
                                         [--targeted-deployment-specification <gpu:instance_type:min_instances:max_instances[:clusters(cluster_1,cluster_2)][:regions(region_1,region_2)][:attributes(attribute_1,attribute_2)][:preferredOrder]>]
                                         [--team <name>] [-h]
                                         <function-id>:<function-version-id>
```

Positional Arguments

`<function-id>:<function-version-id>`

Function. Format: function-id:function-version

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

`--configuration`

Helm chart overrides json will apply cross the functions, only for Helm chart deployment

`--configuration-file, -f`

Helm chart overrides yaml. Can apply multiple times. The priority will be given to the last (right-most) file specified.

`--set`

Set configuration values (e.g., --set image.tag=latest). Can apply multiple times.

`--deployment-specification, --dep-spec`

Deployment specs with GPU and Backend details, can specify multiple times

`--targeted-deployment-specification, --targeted-dep-spec`

Deployment specs with GPU and instance type, can specify multiple times. Clusters are mandatory for non GFN backends.

log

Query Logs for Deployment

```
ngc cloud-function function deploy log [--debug] [--duration <t>]
                                         [--end-time <t>] [--format_type <fmt>]
                                         [--org <name>] [--start-time <t>]
                                         [--team <name>] [-h]
                                         function-id:[<function-id>]
```

Positional Arguments

`function-id:[<function-id>]`

Function. Format: function-id:function-version

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

`--start-time`

Specifies the start time for querying logs. Format: [yyyy-MM-dd::HH:mm:ss].

`--end-time`

Specifies the end time for querying logs. Format: [yyyy-MM-dd::HH:mm:ss]. Default: now

`--duration`

Specifies the duration of time, either after begin-time or before end-time logs. Format: [nD][nH][nM][nS]. Default 1 day, doesn't respect decimal measurements

instance

Function instance commands

```
ngc cloud-function function instance [--debug] [--format_type <fmt>]
                                     [--org <name>] [--team <name>] [-h]
                                     {execute,list,logs} ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

instance

{execute, list, logs}

Possible choices: exec, execute, list, logs, ls

Sub-commands

list (ls)

List specific function version instances

```
ngc cloud-function function instance list [--debug] [--format_type <fmt>]
                                         [--org <name>] [--team <name>] [-h]
                                         <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:[version]

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

execute (exec)

Execute command on target container

```
ngc cloud-function function instance execute --command <command>
                                           --container-name <container-name>
                                           [--debug] [--format_type <fmt>]
                                           --instance-id <instance-id>
                                           [--org <name>] --pod-name
                                           <pod-name> [--team <name>]
                                           [--timeout <timeout>] [-h]
                                           <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:[version]

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--timeout

Timeout for the command execution

Required named arguments

--container-name

Target container to execute container

--pod-name

Target pod which including the target container

--instance-id

Target instance id.

--command

Command to execute

logs

Read the target instance logs

```
ngc cloud-function function instance logs [--container-name <container-name>]
                                         [--debug] [--format_type <fmt>]
                                         --instance-id <instance-id>
                                         [--org <name>]
                                         [--pod-name <pod-name>]
                                         [--team <name>] [-h]
                                         <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:[version]

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--container-name

Target container to query logs. Must be used with --pod-name

--pod-name

Target pod which including the target container. Must be used with --container-name

Required named arguments

--instance-id

Target instance id.

list (ls)

List functions

```
ngc cloud-function function list [--access-filter <filter>]
                                [--column <column>] [--debug]
                                [--format_type <fmt>] [--name-pattern <name>]
                                [--org <name>] [--team <name>] [-h]
                                [[<function-id>]]
```

Positional Arguments

[<function-id>]

Function ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.

Default: current configuration

--access-filter

Possible choices: authorized, private, public

Filter functions by access, choices are: [private,public,authorized]

--name-pattern

Filter functions by names, supports globs.

--column

Specify output column as column[=header], header is optional, default is id[=Id]. Valid columns are activeInstances[="Active Instances"], containerImage[="Container Image URL"], helmChart[="Helm Chart URL"], helmChartServiceName[="Helm Chart Service Name"], models[="Model URLs"], id[="Function ID"], description[=Description], functionType[="Function Type"], status[=Status], version[="Version ID"]. Use quotes with spaces. Multiple column arguments are allowed.

info

Info about a version

```
ngc cloud-function function info [--debug] [--format_type <fmt>]
                                [--org <name>] [--team <name>] [-h]
                                <function-id>:<function-version-id>
```

Positional Arguments

<function-id>:<function-version-id>

Function. Format: function-id:[version]

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

remove (rm, delete)

Delete a version

```
ngc cloud-function function remove [--debug] [--format_type <fmt>]
                                   [--org <name>] [--team <name>] [-h]
                                   <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:[version]

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

update-secret

Update a function's secret values.

```
ngc cloud-function function update-secret [--debug] [--format_type <fmt>]
                                           [--json-secret-file <filename>]
                                           [--org <name>]
                                           [--secret <name:value>]
                                           [--team <name>] [-h]
                                           <function-id>:[<function-version-id>]
```

Positional Arguments

<function-id>:[<function-version-id>]

Function. Format: function-id:[version]

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--secret

Secret name/value pair

--json-secret-file

Takes in a file, assumes the key as the filename, value is the file contents. Only works with json files

update

Update a function version. Rate-limit and LLM configuration fields are mutable.

```
ngc cloud-function function update [--debug] [--format_type <fmt>]
                                   [--llm-default-priority <priority>]
                                   [--llm-model <name>:<uri,uri...>[:<tokenizer>][:<tokenizer>]]
                                   [--llm-per-account-priority <nca-id>:<priority>]
                                   [--org <name>]
                                   [--rate-limit-exempt-nca-id <rate-limit-exempt-id>]
                                   [--rate-limit-pattern <rate-limit-pattern>]
                                   [--rate-limit-per-nca-id-rate <nca-id>:<rate-limit-pattern>]
                                   [--rate-limit-sync-check | --no-rate-limit-sync-check]
                                   [--team <name>] [-h]
                                   <function-id>:<function-version-id>
```

Positional Arguments

<function-id>:<function-version-id>

Function. Format: function-id:[version]

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--rate-limit-pattern

Rate limit pattern, format NUMBER-S|M|H|D (e.g. 3-S). Comma-separated for multiple cadences (e.g. '100-S, 1000-D'). Pass an empty string to clear the rate limit.

--rate-limit-exempt-nca-id

Exempt NCA id (repeatable).

--rate-limit-per-nca-id-rate

Per-NCA-id override rate (repeatable). The pattern follows the same format as --rate-limit-pattern.

`--rate-limit-sync-check, --no-rate-limit-sync-check`

Rate limit sync check.

`--llm-model`

Update an LLM model's mutable config. Format: <name>:<uri,uri...>[:<tokenizer>][:<tokenRateLimit>][:<routingMethod>], leaving immutable fields (uris, tokenizer) empty. At least one of tokenRateLimit or routingMethod (one of [round_robin,power_of_two,groq_multiregion,pulsar,random]) is required. E.g. 'meta/llama-3.1-8b-instruct:::1000-S:power_of_two'. Repeatable.

`--llm-default-priority`

Function-level default request priority. Lower is higher priority, 0 is highest.

`--llm-per-account-priority`

Per-account request priority override (repeatable).

update-rate-limit

DEPRECATED: prefer 'ngc cf function update --rate-limit-pattern ...'. Hits the deprecated /nvcf/ratelimit endpoint.

```
ngc cloud-function function update-rate-limit [--debug] [--format_type <fmt>]
                                              [--org <name>]
                                              [--rate-limit-exempt-nca-id <rate-limit-exempt-nca-id>]
                                              --rate-limit-pattern
                                              <rate-limit-pattern>
                                              [--rate-limit-sync-check]
                                              [--team <name>] [-h]
                                              <function-id>:[<function-version-id>]
```

Positional Arguments

`<function-id>:[<function-version-id>]`

Function. Format: function-id:[version]

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

`--rate-limit-exempt-nca-id`

Exempt NCA id.

`--rate-limit-sync-check`

Rate limit sync check.

Required named arguments

`--rate-limit-pattern`

Rate limit pattern, format NUMBER-S|M|H|D (e.g. 3-S). Comma-separated for multiple cadences (e.g. '100-S, 1000-D').

remove-rate-limit

DEPRECATED: prefer 'ngc cf function update --rate-limit-pattern ""'. Hits the deprecated /nvcf/ratelimit endpoint.

```
ngc cloud-function function remove-rate-limit [--debug] [--format_type <fmt>]
                                              [--org <name>] [--team <name>]
                                              [-h]
                                              <function-id>:[<function-version-id>]
```

Positional Arguments

`<function-id>:[<function-version-id>]`

Function. Format: function-id:[version]

Named Arguments

`--debug`

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

create

Create a new function

```
ngc cloud-function function create [--api-body-format <api-body-format>]
[--container-args <container-args>]
[--container-environment-variable <key:value>]
[--container-image <org>/[<team>/]<image>:<tag>]
[--debug] [--description <description>]
[--format_type <fmt>]
[--function-type <function-type>]
[--health-expected-status-code <health-expected-status-code>]
[--health-port <health-port>]
[--health-protocol <health-protocol>]
[--health-timeout <health-timeout>]
[--health-uri <health-uri>]
[--helm-chart <org>/[<team>/]<helm-chart>:<tag>]
[--helm-chart-service <helm-chart-service-name>]
[--inference-port <inference-port>]
--inference-url <inference-url>
[--json-secret-file <filename>]
[--llm-default-priority <priority>]
[--llm-model <name>:<uri,uri...>[:<tokenizer>][:<tokenizer>]]
[--llm-per-account-priority <nca-id>:<priority>]
[--logs-telemetry-id <logs-telemetry-id>]
[--metrics-telemetry-id <metrics-telemetry-id>]
[--model [<override-name>:]<org>/[<team>/]<image>:version]
--name <name> [--no-default-created-by-tag]
[--org <name>]
[--rate-limit-exempt-nca-id <rate-limit-exempt-id>]
[--rate-limit-pattern <rate-limit-pattern>]
[--rate-limit-per-nca-id-rate <nca-id>:<rate-limit-pattern>]
[--rate-limit-sync-check | --no-rate-limit-sync-check]
[--resource <org>/[<team>/]<resource>:version]
[--secret <name:value>] [--tag <tag>]
[--team <name>]
[--traces-telemetry-id <traces-telemetry-id>]
[-h]
[ [<function-id>] ]
```

Positional Arguments

[<function-id>]

Function ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--helm-chart

Helm Chart in NGC used for deployment.

--helm-chart-service

Must be provided if a helm chart function.

--health-uri

Health endpoint for inferencing

--health-port

Health port for inferencing

--health-timeout

Health timeout for inferencing

--health-protocol

Possible choices: HTTP, gRPC

Health protocol for inferencing

--health-expected-status-code

Health status code.

--inference-port

Optional port number where the inference listener is running - defaults to 8000 for HTTPS, 8001 for GRPC

--container-args

Args to be passed in for inferencing

--container-environment-variable

Environment settings for inferencing

--secret

Secret name/value pair

--json-secret-file

Takes in a file, assumes the key as the filename, value is the file contents. Only works with json files

--model

List of models - could be empty with custom container, can accept multiple

--resource

Optional List of resources, can accept multiple

--tag

Tag to identify the function by, can accept multiple

--no-default-created-by-tag

Skip adding the default 'created_by:<user-email>' tag.

--description

Optional description for function/version

--container-image

Custom container Image

--api-body-format

Possible choices: CUSTOM, PREDICT_V2

Information about the request body format

--function-type

Possible choices: DEFAULT, LLM, STREAMING

Function type, one of [DEFAULT,STREAMING,LLM]. Defaults to DEFAULT.

`--llm-model`

LLM model served by the function. Format: <name>:<uri,uri...>[:<tokenizer>][:<tokenRateLimit>][:<routingMethod>], with comma-separated OpenAI-compatible URI paths (at least one required) and routingMethod one of [round_robin,power_of_two,groq_multiregion,pulsar,random]. E.g. 'meta/llama-3.1-8b-instruct:/v1/chat/completions,/v1/completions::1000-S:power_of_two'. Requires --function-type LLM. Repeatable.

`--llm-default-priority`

Function-level default request priority. Lower is higher priority, 0 is highest.

`--llm-per-account-priority`

Per-account request priority override (repeatable).

`--metrics-telemetry-id`

UUID representing the metrics telemetry.

`--logs-telemetry-id`

UUID representing the logs telemetry.

`--traces-telemetry-id`

UUID representing the traces telemetry.

`--rate-limit-pattern`

Rate limit pattern, format NUMBER-S|M|H|D (e.g. 3-S). Comma-separated for multiple cadences (e.g. '100-S, 1000-D').

`--rate-limit-exempt-nca-id`

Exempt NCA id (repeatable).

`--rate-limit-per-nca-id-rate`

Per-NCA-id override rate (repeatable).

`--rate-limit-sync-check, --no-rate-limit-sync-check`

Rate limit sync check.

Required named arguments

`--name`

Function name must start with lowercase/uppercase/digit and can only contain lowercase, uppercase, digit, hyphen, and underscore characters

`--inference-url`

cluster

Cloud function cluster commands.

```
ngc cloud-function cluster [--debug] [--format_type <fmt>] [--org <name>]
                           [--team <name>] [-h]
                           {create,delete,info,list} ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

cluster

{create,delete,info,list}

Possible choices: create, delete, info, list, ls, register, remove, rm

Sub-commands

list (ls)

List clusters.

```
ngc cloud-function cluster list [--debug] [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

info

Info about a cluster

```
ngc cloud-function cluster info [--debug] [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
                                <cluster-id>
```

Positional Arguments

<cluster-id>

Cluster Id

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

delete (rm, remove)

Delete a cluster

```
ngc cloud-function cluster delete [--debug] [--format_type <fmt>]
                                   [--org <name>] [--team <name>] [-h]
                                   <cluster-id>
```

Positional Arguments

<cluster-id>

Cluster Id

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

create (register)

Register a new cluster with the specified details

```
ngc cloud-function cluster create [--attribute ATTRIBUTE]
                                  [--authorized-nca-id AUTHORIZED_NCA_ID]
                                  [--capability {CachingSupport,DynamicGPUDiscovery,LogPo
                                  --cloud-provider
                                  {AWS,AZURE,DGX-CLOUD,GCP,OCI,ON-PREM}
                                  [--cluster-description CLUSTER_DESCRIPTION]
                                  --cluster-group-name CLUSTER_GROUP_NAME
                                  --cluster-name CLUSTER_NAME
                                  [--custom-attribute CUSTOM_ATTRIBUTE]
                                  [--debug] [--format_type <fmt>]
                                  [--nvca-version NVCA_VERSION] [--org <name>]
                                  --region
                                  {ap-east-1,eu-central-1,eu-north-1,eu-south-1,eu-west-1}
                                  [--ssa-client-id SSA_CLIENT_ID]
                                  [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--cluster-description

Optional description providing additional context about the cluster.

--ssa-client-id, --oauth-client-id

SSA client ID (needed for internal NVIDIA organizations only). --oauth-client-id is an alias.

--capability

Possible choices: CachingSupport, DynamicGPUDiscovery, LogPosting

Capabilities

--attribute

Attributes

--custom-attribute

Custom attributes

--authorized-nca-id

Authorized NCA IDs

--nvca-version

NVCA version

Required named arguments

--cluster-name

The name for the cluster. This field is not changeable once configured.

--cluster-group-name

The name of the cluster group, typically identical to the cluster name, allowing function deployment across grouped clusters.

--cloud-provider

Possible choices: AWS, AZURE, DGX-CLOUD, GCP, OCI, ON-PREM

The cloud platform on which the cluster is deployed.

--region

Possible choices: ap-east-1, eu-central-1, eu-north-1, eu-south-1, eu-west-1, us-east-1, us-west-1, us-west-2

The region where the cluster is deployed.

gpu (instance-type)

Cloud function gpu commands.

```
ngc cloud-function gpu [--debug] [--format_type <fmt>] [--org <name>]
                        [--team <name>] [-h]
                        {capacity,info,list,quota} ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

gpu

`{capacity,info,list,quota}`

Possible choices: capacity, get, info, list, ls, quota

Sub-commands

list (ls)

List allocated gpus.

```
ngc cloud-function gpu list [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

capacity

Show a summary of GPU capacity allocation.

```
ngc cloud-function gpu capacity [--debug] [--format_type <fmt>] [--gpu GPU]
                                [--org <name>]
                                [--region {ap-east-1,eu-central-1,eu-north-1,eu-south-1,eu-west-1,us-east-1,us-west-1,us-west-2}]
                                [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--region

Possible choices: ap-east-1, eu-central-1, eu-north-1, eu-south-1, eu-west-1, us-east-1, us-west-1, us-west-2

Filter by specific region. Can specify multiple times.

--gpu

Filter by specific GPU. Can specify multiple times.

quota

Get GPU Quota information.

```
ngc cloud-function gpu quota [--debug] [--format_type <fmt>] [--org <name>]
                               [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

info (get)

Info for a given gpu.

```
ngc cloud-function gpu info [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
```

Positional Arguments



Named Arguments

--debug

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

registry-credential

Cloud function registry-credential commands.

```
ngc cloud-function registry-credential [--debug] [--format_type <fmt>]
                                         [--org <name>] [--team <name>] [-h]
                                         {create,info,list,remove,update} ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

registry-credential

{create, info, list, remove, update}

Possible choices: add, create, delete, info, list, ls, remove, rm, update

Sub-commands

info

Info about registry credential.

```
ngc cloud-function registry-credential info [--debug] [--format_type <fmt>]
                                           [--org <name>] [--team <name>]
                                           [-h]
                                           <registry-credential-id>
```

Positional Arguments

<registry-credential-id>

Id of registry credential to get

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

list (ls)

List registry credentials.

```
ngc cloud-function registry-credential list [--debug] [--format_type <fmt>]
                                           [--org <name>] [--team <name>]
                                           [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

create (add)

Create a new registry credential.

```
ngc cloud-function registry-credential create [--aws-access-key <username>]
                                              [--debug]
                                              [--description <description>]
                                              [--format_type <fmt>] --hostname
                                              <hostname> --key <key> --name
                                              <name> [--org <name>]
                                              [--tag <tag>] [--team <name>]
                                              --type
                                              <registry-credential-type>
                                              [--username <username>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--username

Username for credentials

--aws-access-key

Access key for AWS credentials

--description

Description for credentials

--tag

Tag for credentials

Required named arguments

--name

Registry Credentials name

--key

Registry credentials key; for AWS, it equals the *secret access key*

--hostname

Registry Hostname of credentials

--type

Possible choices: CONTAINER, HELM, MODEL, RESOURCE

Set of registry credential data types

update

Update an existing registry credential .

```
ngc cloud-function registry-credential update [--aws-access-key <username>]
[--debug] [--format_type <fmt>]
--key <key> [--org <name>]
[--team <name>]
[--username <username>] [-h]
<registry-credential-id>
```

Positional Arguments

<registry-credential-id>

Id of registry credential to update

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--username

Username for credentials

--aws-access-key

Access key for AWS credentials

Required named arguments

--key

Registry credentials key

remove (delete, rm)

Delete a registry credential.

```
ngc cloud-function registry-credential remove [--debug] [--format_type <fmt>]
                                           [--org <name>] [--team <name>]
                                           [-h]
                                           <registry-credential-id>
```

Positional Arguments

<registry-credential-id>

Id of registry credential to delete

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

task

Cloud function task commands.

```
ngc cloud-function task [--debug] [--format_type <fmt>] [--org <name>]
                        [--team <name>] [-h]
                        {cancel,create,delete,events,info,instance,list,logs,results,update}
                        ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

task

`{cancel, create, delete, events, info, instance, list, logs, results, update-secret}`

Possible choices: cancel, create, delete, events, info, instance, list, logs, ls, remove, results, rm, update-secret

Sub-commands

instance

Task instance commands

```
ngc cloud-function task instance [--debug] [--format_type <fmt>]
                                   [--org <name>] [--team <name>] [-h]
                                   {execute, list, logs} ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

instance

{execute, list, logs}

Possible choices: exec, execute, list, logs, ls

Sub-commands

list (ls)

List specific task instances

```
ngc cloud-function task instance list [--debug] [--format_type <fmt>]
                                     [--org <name>] [--team <name>] [-h]
                                     <task-id>
```

Positional Arguments

<task-id>

Task ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

execute (exec)

Execute command on target container

```
ngc cloud-function task instance execute --command <command> --container-name
<container-name> [--debug]
[--format_type <fmt>] --instance-id
<instance-id> [--org <name>]
--pod-name <pod-name> [--team <name>]
[--timeout <timeout>] [-h]
<task-id>
```

Positional Arguments

<task-id>

Task ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--timeout

Timeout for the command execution

Required named arguments

--container-name

Target container to execute container

--pod-name

Target pod which including the target container

--instance-id

Target instance id.

--command

Command to execute

logs

Read the target instance logs

```
ngc cloud-function task instance logs [--container-name <container-name>]
                                       [--debug] [--format_type <fmt>]
                                       --instance-id <instance-id>
                                       [--org <name>] [--pod-name <pod-name>]
                                       [--team <name>] [-h]
                                       <task-id>
```

Positional Arguments

<task-id>

Task ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--pod-name

Target task pod which including the target container. Must be used with --container-name

--container-name

Target task container to query logs. Must be used with --pod-name

Required named arguments**--instance-id**

Target task instance id.

create

Create a new task

```
ngc cloud-function task create [--configuration CONFIGURATION]
                                [--configuration-file <file.yaml>]
                                [--container-args <container-args>]
                                [--container-environment-variable <key:value>]
                                [--container-image <org>/[<team>/]<image>:<tag>]
                                [--debug] [--description <description>]
                                [--format_type <fmt>] --gpu-specification
                                <gpu:instance_type[:backend][:cluster_1,
                                cluster_2]>
                                [--helm-chart <org>/[<team>/]<helm-chart>:<tag>]
                                [--logs-telemetry-id <logs-telemetry-id>]
                                [--max-queued-duration <max-queued-duration>]
                                [--max-runtime-duration <max-runtime-duration>]
                                [--metrics-telemetry-id <metrics-telemetry-id>]
                                [--model <model>] --name <name>
                                [--no-default-created-by-tag] [--org <name>]
                                [--resource <resource>]
                                [--result-handling-strategy <result-handling-strategy>]
                                [--result-location <result-location>]
                                [--secret <name:value>]
                                [--set <key1.key2=value>] [--tag <tag>]
                                [--team <name>]
                                [--termination-grace-period-duration <termination-grace-pe
                                --traces-telemetry-id <traces-telemetry-id>]
                                [-h]
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

`--configuration`

Helm chart overrides json will apply cross the functions, only for Helm chart deployment

`--configuration-file, -f`

Helm chart overrides yaml. Can apply multiple times. The priority will be given to the last (right-most) file specified.

`--set`

Set configuration values (e.g., --set image.tag=latest). Can apply multiple times.

`--container-image`

Custom container image

`--container-args`

Args to be passed in for inferencing

`--container-environment-variable`

Environment settings for inferencing

`--model`

Name of model(s) to use in the task.

`--resource`

Name of resource(s) to use in the task.

`--tag`

Tags to identify the function by, can accept multiple

--no-default-created-by-tag

Skip adding the default 'created_by:<user-email>' tag.

--description

Optional description for function/version

--max-runtime-duration

Specifies the maximum runtime duration. Format: [nD][nH][nM][nS].

--max-queued-duration

Specifies the maximum queued duration. Format: [nD][nH][nM][nS].

--termination-grace-period-duration

Specifies the duration for grace period after termination. Format: [nD][nH][nM][nS].

--result-handling-strategy

Possible choices: NONE, UPLOAD

Specifies how results will be handled. Choices: UPLOAD, NONE

--result-location

Specifies where result will be stored.}

--secret

Secret name/value pair

--helm-chart

Helm Chart in NGC used for deployment.

--metrics-telemetry-id

UUID representing the metrics telemetry.

--logs-telemetry-id

UUID representing the logs telemetry.

--traces-telemetry-id

UUID representing the traces telemetry.

Required named arguments

--name

Task name

--gpu-specification

GPU specification. Format: gpu:instance_type[:backend][:cluster_1, cluster_2]

update-secret

Update a task's secret value. Can specify multiple times.

```
ngc cloud-function task update-secret [--debug] [--format_type <fmt>]
                                     [--org <name>] --secret <name:value>
                                     [--team <name>] [-h]
                                     <task-id>
```

Positional Arguments

<task-id>

Task ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

Required named arguments

--secret

Secret name/value pair

list (ls)

List of tasks

```
ngc cloud-function task list [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

info

Info about a task

```
ngc cloud-function task info [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
                             <task-id>
```

Positional Arguments

<task-id>

Task ID

Named Arguments

--debug

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

delete (remove, rm)

Delete a task

```
ngc cloud-function task delete [--debug] [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
                                <task-id>
```

Positional Arguments

`<task-id>`

Task ID

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

cancel

Cancel a task

```
ngc cloud-function task cancel [--debug] [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
                                <task-id>
```

Positional Arguments

<task-id>

Task ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

events

List of events for a task

```
ngc cloud-function task events [--debug] [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
                                <task-id>
```

Positional Arguments

`<task-id>`

Task ID

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

results

List of results for a task

```
ngc cloud-function task results [--debug] [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
                                <task-id>
```

Positional Arguments

`<task-id>`

Task ID

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

logs

List of logs for a task

```
ngc cloud-function task logs [--debug] [--duration <t>] [--end-time <t>]
                             [--format_type <fmt>] [--org <name>]
                             [--start-time <t>] [--team <name>] [-h]
                             <task-id>
```

Positional Arguments

<task-id>

Task ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

`--start-time`

Specifies the start time for querying logs. Format: [yyyy-MM-dd::HH:mm:ss].

`--end-time`

Specifies the end time for querying logs. Format: [yyyy-MM-dd::HH:mm:ss]. Default: now

`--duration`

Specifies the duration of time, either after begin-time or before end-time. Format: [nD][nH][nM][nS]. Default 1 hour, doesn't respect decimal measurements

telemetry-endpoint

Cloud function telemetry-endpoint commands.

```
ngc cloud-function telemetry-endpoint [--debug] [--format_type <fmt>]
                                     [--org <name>] [--team <name>] [-h]
                                     {create,list,remove} ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

telemetry-endpoint

`{create,list,remove}`

Possible choices: add, create, delete, list, ls, remove, rm

Sub-commands

list (ls)

List telemetries.

```
ngc cloud-function telemetry-endpoint list [--debug] [--format_type <fmt>]
                                         [--org <name>] [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

create (add)

Create a new telemetry endpoint.

```
ngc cloud-function telemetry-endpoint create
```

```
[--application-id <application-id>]  
[--client-cert <client-cert>]  
[--debug] --endpoint <endpoint>  
[--format_type <fmt>]  
[--instance <instance>] --key  
<key>  
[--live-endpoint <live-endpoint>]  
--name <name> [--org <name>]  
--protocol <protocol> --provider  
<provider>  
[--self-cert <self-cert>]  
[--team <name>] --type  
<telemetry-type> [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--instance

Instance id for GRAFANA endpoints.

--client-cert

Client cert for PROMETHEUS endpoints.

--self-cert

Optional self certificate for PROMETHEUS endpoints.

--live-endpoint

Live endpoint for AZURE MONITOR endpoints.

--application-id

Application ID AZURE MONITOR endpoints.

Required named arguments

--name

Telemetry Name

--key

Telemetry key

--endpoint

Telemetry endpoint URL

--protocol

Possible choices: GRPC, HTTP

Protocol used for communication

--provider

Possible choices: AZURE_MONITOR, DATADOG, GRAFANA_CLOUD, OTEL_COLLECTOR, PROMETHEUS, SERVICENOW

Provider name for telemetry endpoint

--type

Possible choices: LOGS, METRICS, TRACES

Set of telemetry data types

remove (delete, rm)

Delete a telemetry endpoint.

```
ngc cloud-function telemetry-endpoint remove [--debug] [--format_type <fmt>]
                                           [--org <name>] [--team <name>]
                                           [-h]
                                           <telemetry-id>
```

Positional Arguments

<telemetry-id>

Id of telemtry endpoint to delete

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

available-gpus

List available GPUs in your Org, Admin Only

```
ngc cloud-function available-gpus [--debug] [--format_type <fmt>]
                                   [--org <name>] [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

Examples

Functions

How to list functions?

```
$ ngc cf fn list
```

Name	Id	Version	Container
example-helm	33352d58-10ae-4a38-ade9-ca2468798315	28980bb7-844e-40e6-a05b-411236a6cc9a	
example-container	74510cba-6d29-43f6-88b4-e1c3d055f3ab	6094e300-375f-42b2-9e7b-f3d87ce59353	canary.nvcr.io/example

How to create a function?

```
$ ngc cf function create --name peek-test-e2e --inference-url /health --container-image ]
```

```
-----
Function Information
  Name: peek-test-e2e
  Version: 6698aa4d-1ea3-4f95-b6cb-4bf879fe538a
  ID: a7346e6f-4755-47cf-9163-6212e8db0900
  Status: INACTIVE
  Inference URL: /health
  Description: test-function
  Container Image: nvcr.io/lpeb1gw2rozl/pytriton_echo_sample:latest
  Secret Keys: key2, key
Health Endpoint Information
  URI: /v2/health/ready
  Port: 8000
  Timeout: PT10S
  Protocol: HTTP
  Expected Status Code: 200
-----
```

How to create a function with a json secret?

```
$ ngc cf function create --name peek-test-e2e --inference-url /health --container-image J
```

Function Information

Name: peek-test-e2e

Version: 6698aa4d-1ea3-4f95-b6cb-4bf879fe538a

ID: a7346e6f-4755-47cf-9163-6212e8db0900

Status: INACTIVE

Inference URL: /health

Description: test-function

Container Image: nvcr.io/lpeb1gw2roz1/pytriton_echo_sample:latest

Secret Keys: key

Health Endpoint Information

URI: /v2/health/ready

Port: **8000**

Timeout: PT10S

Protocol: HTTP

Expected Status Code: **200**

How to allow others to invoke your function across all versions?

```
$ ngc cf fn auth add 7835a350-921e-4fd3-8004-554b84c1367b --authorized-party "21xz_k9-Gnz
```

Function Authorization Information

Function ID: 7835a350-921e-4fd3-8004-554b84c1367b

Author NCA ID: CMYBKSNnjtg1TQmSke-gHNGgMlFvA-dCRAI8gcH0Bcw

Authorized Party NCAs: 21xz_k9-GnzBXPft00CagYnVXWwoUxNMJ3-IeT-qSYA

Tasks

How to create a task?

```
$ ngc cf task create --name task-name --container-image stg.nvcr.io/ax3ysqem02xw/testing-
-----
Task Information
  Name: task-name
  ID: f2a41879-1ee4-46bf-9b51-5f3da7dd139b
  Status: QUEUED
  Description: description
  Created: 2024-12-04T20:15:13.910726527Z
  Last Updated:
Configuration Details
  Container: stg.nvcr.io/ax3ysqem02xw/testing-jet/server:main_11178569
  GPU Type: T10
  Instance Type: g6.full
  Max Runtime Duration: 1h
  Max Queued Duration: 1h
  Termination Grace Period: 1h
  Result Handling: NONE
  Result Path:
-----
```

How to list tasks?

```
$ ngc cf task list
+-----+-----+-----+
| Name                | Status                                | Id                                |
+-----+-----+-----+
| yura-task-3         | EXCEEDED_MAX_RUNTIME_DURATION        | 15bc4cb5-e09b-4b2c-af7d-197    |
| yura-task-2         | CANCELED                             | 93847acd-1604-4c57-a293-f43    |
+-----+-----+-----+
```

How to view a task's information?

```
$ ngc cf task info 1bd74059-c494-4b1f-bc6a-f028677546f4
-----
Task Information
  Name: randomcontainer
  ID: 1bd74059-c494-4b1f-bc6a-f028677546f4
  Status: QUEUED
  Description:
  Created: 2024-10-16T19:09:08.006Z
  Last Updated:
Configuration Details
  Container: stg.nvcr.io/ax3ysqemo02xw/testing-jet/server:main_11257917
  GPU Type: L40
  Instance Type: fl40_1.br20_2xlarge
  Max Runtime Duration: 10 minutes
  Max Queued Duration: 3 days
  Termination Grace Period: 10 minutes
  Result Handling: NONE
  Result Path:
-----
```

How to delete a task?

\$ _page_of_task_delete_1bd74850_e404_4b1f_b66c_f028677546f4



[Privacy Policy](#) | [Your Privacy Choices](#) | [Terms of Service](#) | [Accessibility](#) | [Corporate Policies](#) | [Product Security](#) | [Contact](#)

Copyright © 2018-2026, NVIDIA Corporation.