

diag

The diagnostic commands print configuration and environment information and provide suggestions on identifiable misconfigurations or common issues. No private credentials are included in the gathered diagnostic data.

```
usage: ngc diag [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
               [-h]
               {all,client,install,server} ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

diag

{all,client,install,server}

Possible choices: all, client, install, server, user

Sub-commands

all

Produce the maximum amount of diagnostic output (client, install, server, user).

```
ngc diag all [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
[-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

install

Produce diagnostic output only for the local installation environment.

```
ngc diag install [--debug] [--format_type <fmt>] [--org <name>]
[--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

client

Produce diagnostic output only for the client machine.

```
ngc diag client [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
               [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

user

Produce diagnostic output only for the user configuration.

```
ngc diag user [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
              [-h]
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

server

Produce diagnostic output only for remote server systems.

```
ngc diag server [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]  
                [-h]
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

Examples

Installation Environment

```
$ ngc diag install

Checking general information...
Timestamp: 2019-03-22 14:14:46 UTC
User name: NGC User

Checking CLI installation...
CLI version: NGC CLI 2.0.0
Using a binary version of CLI: YES
```

Client Environment

```
$ ngc diag client

Checking general information...
Timestamp: 2019-03-22 14:21:55 UTC
User name: NGC User

Checking Operating System...
Type: Linux
Version: 4.20.14-200.fc29.x86_64

Checking disk usage for /home/ngc_user...
Total: 850.32 GB
Free: 799.79 GB
Used: 0.9%

Checking current directory (/home/ngc_user/) size...
Size: 712.46 MB

Checking memory usage...
Total: 31.09 GB
Free: 19.7 GB
Used: 14.2%

Checking file permissions...
set umask: 077

Checking set NGC CLI environment variables...
None
```

Server Information

```
$ ngc diag server
```

```
Checking general information...
```

```
Timestamp: 2019-03-22 14:23:28 UTC
```

```
User name: NGC User
```

```
Checking API gateway connectivity...
```

```
API Connectivity: SUCCESS
```

```
Checking authentication...
```

```
Authentication: SUCCESS
```

```
Checking API connectivity (container registry)...
```

```
Container Registry Connectivity: SUCCESS
```

```
Checking API connectivity (container registry meta)...
```

```
Container Registry Meta Connectivity: SUCCESS
```



[Privacy Policy](#) | [Your Privacy Choices](#) | [Terms of Service](#) | [Accessibility](#) | [Corporate Policies](#) | [Product Security](#) | [Contact](#)

Copyright © 2018-2026, NVIDIA Corporation.