

fleet-command

Fleet Command Commands

```
usage: ngc fleet-command [--debug] [--format_type <fmt>] [--org <name>]
                        [--team <name>] [-h]
                        ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

fleet-command



Possible choices: apikey, appconfig, application, component, deployment, location, log, metric, remote, settings, usage

Sub-commands

apikey

Fleet Command API Key Commands

```
ngc fleet-command apikey [--debug] [--format_type <fmt>] [--org <name>]
                        [--team <name>] [-h]
                        ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

apikey



Possible choices: info, set

Sub-commands

set

Set the apikey for private helm, model and container registries. Command will prompt for API key.

```
ngc fleet-command apikey set [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

info

Show private registry apikey status.

```
ngc fleet-command apikey info [--debug] [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

appconfig

Fleet Command Application Configuration Commands

```
ngc fleet-command appconfig [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
                             ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

appconfig



Possible choices: create, download, info, list, remove, update

Sub-commands

info

Show details for the specified appconfig.

```
ngc fleet-command appconfig info [--debug] [--format_type <fmt>]
                                   [--org <name>] [--team <name>] [-h]
                                   <target>
```

Positional Arguments

<target>

appconfig name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

remove

Remove the specified appconfig.

```
ngc fleet-command appconfig remove [--debug] [--format_type <fmt>]
                                     [--org <name>] [--team <name>] [-h] [-y]
                                     <target>
```

Positional Arguments

<target>

appconfig name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

-y, --yes

Automatically say yes to all interactive questions.

list

List appconfig(s).

```
ngc fleet-command appconfig list [--column <column>] [--debug]
                                [--format_type <fmt>] [--org <name>]
                                [--team <name>] [-h]
                                [<target>]
```

Positional Arguments

<target>

appconfig(s) to list. This argument supports Unix glob style pattern matching. If no target appconfig is given, all visible appconfigs will be listed.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

--column

Specify output column as column[=header], header is optional, default is name[=Name]. Valid columns are name[=Name], creationTimestamp[="Create Date"]. Use quotes with spaces. Multiple column arguments are allowed.

download

Download the appconfig yaml contents to a file.

```
ngc fleet-command appconfig download [--debug] [--dest <path>]
                                     [--format_type <fmt>] [--org <name>]
                                     [--team <name>] [-h]
                                     <target>
```

Positional Arguments

<target>

appconfig name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

--dest

Destination to download the target appconfig yaml. Default: .

create

Create a new appconfig.

```
ngc fleet-command appconfig create [--debug] --filename <path>
                                   [--format_type <fmt>] [--org <name>]
                                   [--team <name>] [-h]
                                   <target>
```

Positional Arguments

<target>

appconfig name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

Required named arguments

--filename

appconfig filename - Provide the path to the appconfig yaml file.

update

Update the existing appconfig.

```
ngc fleet-command appconfig update [--debug] --filename <path>
                                   [--format_type <fmt>] [--org <name>]
                                   [--team <name>] [-h]
                                   <target>
```

Positional Arguments

<target>

appconfig name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

Required named arguments

--filename

appconfig filename - Provide the path to the appconfig yaml file.

application

Fleet Command Application Commands

```
ngc fleet-command application [--debug] [--format_type <fmt>] [--org <name>]
                               [--team <name>] [-h]
                               ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

application

Possible choices: create, info, list, remove, update

Sub-commands

info

Show details for the specified application.

```
ngc fleet-command application info [--debug] [--format_type <fmt>]
                                   [--org <name>] [--team <name>] [-h]
                                   <target>
```

Positional Arguments

<target>

Helm name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

remove

Remove the specified application.

```
ngc fleet-command application remove [--debug] [--format_type <fmt>]
                                     [--org <name>] [--team <name>] [-h] [-y]
                                     <target>
```

Positional Arguments

<target>

Helm name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

-y, --yes

Automatically say yes to all interactive questions.

list

List Application(s).