

registry

Registry Commands

```
usage: ngc registry [--debug] [--format_type <fmt>] [--org <name>]
                  [--team <name>] [-h]
                  {chart,collection,csp,encryption-key,image,label-set,model,resource,usage}
                  ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

registry

```
{chart,collection,csp,encryption-key,image,label-set,model,resource,usage}
```

Possible choices: chart, collection, csp, encryption-key, image, label-set, model, resource, usage

Sub-commands

chart

Helm Chart Commands

```
ngc registry chart [--debug] [--format_type <fmt>] [--org <name>]
                  [--team <name>] [-h]
                  {accept-license,info,list,pull} ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

chart

{accept-license,info,list,pull}

Possible choices: accept-license, create, info, list, publish, pull, push, remove, update, update-license-terms

Sub-commands

list

List charts.

```
ngc registry chart list [--access-type <access_type>] [--column <column>]
                        [--debug] [--format_type <fmt>] [--org <name>]
                        [--policy <policy>] [--product-name <product_name>]
                        [--release-type <release_type>] [--team <name>] [-h]
                        [<target>]
```

Positional Arguments

<target>

Filter the search by allowing wildcards for charts. Format: org/[team/]chart_name[:version]. To target charts use 'org/[team/]chart_name'. Both name and version support the wildcards '*' and '?'. Version also supports character expressions ([a-z], [!ab], etc.). Examples: 'my_org/my_chart' - target my_chart in my_org repository. 'my_org/my_team/my_chart' - target my_chart in my_org/my_team repository. 'my_org/my_team/' - *target all charts in my_org/my_team repository*. 'my_org/my_chart' - target all chart versions for my_chart in my_org namespace. 'my_org/my_chart:[1-5]' - target versions 1-5 for my_chart in my_org namespace.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--column

Specify output column as column[=header], header is optional, default is repository[=Repository] or artifactVersion[=Version] for versions. Valid columns are created[=Created], createdBy[="Created By"], description[=Description], displayName[="Display Name"], guestAccess[="Guest Access"], labels[=Labels], name[=Name], org[=Org], public[=Public], size[=Size], team[=Team], updated[="Last Modified"], version[=Version]. Use quotes with spaces. Multiple column arguments are allowed.

--access-type

Possible choices: EXCLUSIVE, LISTED, NOT_LISTED

Filter the list of resources to only resources that have specified access type.

--product-name

Filter the list of resources to only resources that are under the product name. Multiple product-name arguments are allowed. Choose from: nvaie-vpaif, nv-cloud-functions, secrets-manager,

base-command-platform, nv-ai-enterprise, nvaie-igx-safety-add-on, chipnemo-inference, ai-foundations, artifact-catalog, riva-virtual-assistant, nemo-llm-service, monai, tao, omniverse-cloud, picasso, data-services, bluefield-enterprise-sw, nv-quantum-cloud, nvaie-igx-yocto-add-on, fleet-command, forge, riva-enterprise, cuopt, met, bionemo-service, iam, nvaie-igx, e2, private-registry

--policy

Possible choices: gov_ready

Filter the list of artifacts to only artifacts that have specified policy labels. Multiple policy arguments are allowed. Choose from: GOV_READY (case-insensitive).

--release-type

Possible choices: beta, ea, feature, ga, ltsb, production

Filter the list of artifacts by release type. Choose from: BETA, GA, EA, FEATURE, PRODUCTION, LTSB (case-insensitive).

info

Retrieve metadata for a chart or chart version.

```
ngc registry chart info [--debug] [--files] [--format_type <fmt>]
                        [--org <name>] [--team <name>] [-h]
                        <target>
```

Positional Arguments

<target>

Chart or chart version. Format: org/[team/]chart_name[:version].

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--files

List files in addition to details for a version.

update

Update a chart or chart version.

```
ngc registry chart update [--add-label <add-label>] [--built-by <builtBy>]
                           [--debug] [--display-name <dispName>]
                           [--format_type <fmt>] [--label <label>]
                           [--label-set <label-set>] [--logo <logo>]
                           [--org <name>] [--overview-filename <path>]
                           [--policy <policy>] [--publisher <publisher>]
                           [--release-type <release_type>]
                           [--remove-label <remove-label>]
                           [--short-desc <shortDesc>] [--team <name>] [-h]
                           <target>
```

Positional Arguments

<target>

Name of the chart to create. Format: org/[team/]chart_name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

--overview-filename

Overview. Provide the path to a file that contains the overview for the chart.

--display-name

The name to display for the chart

--add-label

Label for the chart to add. Can be used multiple times. Imperative label argument, not to be used with declarative label arguments --label or --label-set

--remove-label

Label for the chart to remove. Can be used multiple times. Imperative label argument, not to be used with declarative label arguments --label or --label-set

--label

Label for the chart to declare. Can be used multiple times. Declarative label argument, not to be used with declarative label arguments —add-label or —remove-label

--label-set

Name of the label set for the chart to declare. Can be used multiple times. Format: org/[team/]name. Declarative label argument, not to be used with declarative label arguments —add-label or —remove-label

--short-desc

A brief description of the chart

--built-by

The entity responsible for building the chart

--publisher

The entity responsible for creating the chart

--logo

The URL of the image to set as the logo for the chart

--policy

Policy compliance label for the chart version/tag (not artifact-level). Can be used multiple times for different policies. Use --policy "" to clear all policies. Available policies: GOV_READY (case-insensitive).

--release-type

Release type for the published chart version/tag (not artifact-level). Available release types: BETA, GA, EA, FEATURE, PRODUCTION, LTSB (case-insensitive).

remove

Remove a chart from the repository.

```
ngc registry chart remove [--debug] [--format_type <fmt>] [--org <name>]
                           [--team <name>] [-h] [-y]
                           <target>
```

Positional Arguments

<target>

Chart or chart version. Format: org/[team/]chart_name[:version].

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

-y, --yes

Automatically say yes to all interactive questions.

pull

Download a chart version.

```
ngc registry chart pull [--debug] [--dest <path>] [--format_type <fmt>]
                        [--org <name>] [--team <name>] [-h]
                        <target>
```

Positional Arguments

<target>

Chart version. Format: org/[team/]chart[:version]. If no version specified, the latest version will be targeted.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--dest

Provide a destination to download the chart. Default: . (current directory)

create

Create a chart's metadata.

```
ngc registry chart create [--built-by <builtBy>] [--debug]
                          [--display-name <dispName>] [--format_type <fmt>]
                          [--label <label>] [--label-set <label-set>]
                          [--logo <logo>] [--org <name>]
                          [--overview-filename <path>]
                          [--publisher <publisher>] --short-desc <shortDesc>
                          [--team <name>] [-h]
                          <target>
```

Positional Arguments

<target>

Name of the chart to create. Format: org/[team/]chart_name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--overview-filename

Overview. Provide the path to a file that contains the overview for the chart.

--display-name

The name to display for the chart

--label

Label for the chart to declare. Can be used multiple times. Declarative label argument, not to be used with declarative label arguments —add-label or —remove-label

--label-set

Name of the label set for the chart to declare. Can be used multiple times. Format: org/[team/]name. Declarative label argument, not to be used with declarative label arguments —add-label or —remove-label

--built-by

The entity responsible for building the chart

--publisher

The entity responsible for creating the chart

--logo

The URL of the image to set as the logo for the chart

Required named arguments

--short-desc

A brief description of the chart

push

Push (upload) a chart.

```
ngc registry chart push [--debug] [--dry-run] [--format_type <fmt>]
                        [--org <name>] [--source <path>] [--team <name>] [-h]
                        <target>
```

Positional Arguments

<target>

Chart version. Format: org/[team/]chart_name:version.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--source

The path to the directory containing the packaged chart. If not specified, the chart will be uploaded from the current directory.

--dry-run

List file paths, total upload size and file count without performing the upload.

update-license-terms

Update an artifact's license terms.

```
ngc registry chart update-license-terms [--clear] [--debug]
                                         [--format_type <fmt>]
                                         [--license-terms-file <filename>]
                                         [--org <name>] [--team <name>] [-h]
                                         org/[team/]chart[:version]
```

Positional Arguments

org/[team/]chart[:version]

The target chart and version you want to publish to. Optional when getting publishing status using the `--status` flag. Format: `org/[team/]chart[:version]`

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: `ascii`, `csv`, `json`

Specify the output format type. Supported formats are: `['ascii', 'csv', 'json']`. Only commands that produce tabular data support `csv` format. Default: `ascii`

--org

Specify the organization name. Use `"--org no-org"` to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use `"--team no-team"` to override other sources and specify no team. Default: current configuration

--license-terms-file

Apply license terms from a file. JSON array of objects (licenseId, licenseVersion, governingTerms; optional needsAcceptance and configuredLicenseTerms with hosting/download; tags must be an array of tag objects).

--clear

Whether to clear an artifact's license terms.

accept-license

Accept required license terms for a chart.

```
ngc registry chart accept-license [--debug] [--format_type <fmt>]
                                  [--org <name>] [--team <name>] [-h] [-y]
                                  org/[team/]chart[:version]
```

Positional Arguments

org/[team/]chart[:version]

Chart or chart version. Format: org/[team/]chart_name[:version].

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

-y, --yes

Automatically say yes to all interactive questions.

publish

Publish a chart from the NGC chart registry to catalog. Version must be specified for version operations (e.g., org/chart:v1).

```
ngc registry chart publish [--access-type <access_type>] [--allow-guest]
                           [--debug] [--discoverable] [--format_type <fmt>]
                           [--metadata-only] [--nspect-id NSPECT_ID]
                           [--org <name>] [--policy <policy>]
                           [--product-name <product_name>] [--public]
                           [--release-type <release_type>]
                           [--source org/[team/]chart[:version]]
                           [--status <workflow_id>] [--team <name>]
                           [--version-only] [--visibility-only] [-h]
                           [org/[team/]chart[:version]]
```

Positional Arguments

org/[team/]chart[:version]

The target chart and version you want to publish to. Optional when getting publishing status using the `--status` flag. Format: `org/[team/]chart[:version]`

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: `ascii`, `csv`, `json`

Specify the output format type. Supported formats are: `['ascii', 'csv', 'json']`. Only commands that produce tabular data support `csv` format. Default: `ascii`

--org

Specify the organization name. Use `"--org no-org"` to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use `"--team no-team"` to override other sources and specify no team. Default: current configuration

--source

The source chart and version you want to publish. Format: `org/[team/]chart[:version]`

--metadata-only

Only perform a shallow copy of the metadata instead of a deep copy of the objects referenced

--version-only

Only copy the specified version of the object without copying any metadata

--visibility-only

Only change the visibility qualities of the target. Metadata and version files are not affected.

--allow-guest

Allow anonymous users to download the published object

--discoverable

Allow the published object to be discoverable in searches

--public

Allow access to the published object by everyone instead of just those with specific roles

--product-name

Publish the object under a Product. Choose from: nvaie-vpaif, nv-cloud-functions, secrets-manager, base-command-platform, nv-ai-enterprise, nvaie-igx-safety-add-on, chipnemo-inference, ai-foundations, artifact-catalog, riva-virtual-assistant, nemo-llm-service, monai, tao, omniverse-cloud, picasso, data-services, bluefield-enterprise-sw, nv-quantum-cloud, nvaie-igx-yocto-add-on, fleet-command, forge, riva-enterprise, cuopt, met, bionemo-service, iam, nvaie-igx-e2, private-registry

--status

Get the status of publishing based on provided workflow id. Possible workflowDetails.status values: WORKFLOW_EXECUTION_STATUS_UNSPECIFIED, WORKFLOW_EXECUTION_STATUS_RUNNING, WORKFLOW_EXECUTION_STATUS_COMPLETED, WORKFLOW_EXECUTION_STATUS_FAILED, WORKFLOW_EXECUTION_STATUS_CANCELED, WORKFLOW_EXECUTION_STATUS_TERMINATED, WORKFLOW_EXECUTION_STATUS_CONTINUED_AS_NEW, WORKFLOW_EXECUTION_STATUS_TIMED_OUT.

--access-type

Possible choices: EXCLUSIVE, LISTED, NOT_LISTED

Publish the object with a specific access type. Choose from: LISTED, EXCLUSIVE, NOT_LISTED

--release-type

Release type for the published chart version/tag (not artifact-level). Available release types: BETA, GA, EA, FEATURE, PRODUCTION, LTSB (case-insensitive).

--nspect-id

nSpect ID of artifact

--policy

Policy compliance label for the chart version/tag (not artifact-level). Can be used multiple times for different policies. Use --policy "" to clear all policies. Available policies: GOV_READY (case-insensitive).

collection

Collection Commands

```
ngc registry collection [--debug] [--format_type <fmt>] [--org <name>]
                        [--team <name>] [-h]
                        {find,info,list} ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

collection

{find,info,list}

Possible choices: create, find, info, list, publish, remove, update

Sub-commands

create

Create a collection.

```
ngc registry collection create [--add-chart <chart>] [--add-image <image>]
                               [--add-model <model>]
                               [--add-resource <resource>] [--built-by <name>]
                               --category <category> [--debug]
                               [--display-name <name>] [--format_type <fmt>]
                               [--label <label>] [--label-set <label-set>]
                               [--logo <logo>] [--org <name>]
                               [--overview-filename <path>]
                               [--publisher <publisher>] --short-desc <desc>
                               [--team <name>] [-h]
                               <target>
```

Positional Arguments

<target>

Collection to create. Format: Org/[team/]name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--display-name

Human-readable name for the collection.

--label-set

Name of the label set for the collection to declare. Can be used multiple times. Format: org/[team/]name. Declarative label argument, not to be used with declarative label arguments — add-label or —remove-label

--label

Label for the collection to declare. Can be used multiple times. Declarative label argument, not to be used with declarative label arguments —add-label or —remove-label

--logo

A link to the logo for the collection.

--overview-filename

A markdown file with an overview of the collection.

--built-by

Name of the owner of this collection.

--publisher

The publishing organization.

--add-image

Name of an image to include in the collection. Can be used multiple times. Format: org/[team/]name.

--add-model

Name of a model to include in the collection. Can be used multiple times. Format: org/[team/]name.

--add-resource

Name of a resource to include in the collection. Can be used multiple times. Format: org/[team/]name.

--add-chart

Name of a chart to include in the collection. Can be used multiple times. Format: org/[team/]name.

Required named arguments

--short-desc

A brief description of the collection.

--category

Possible choices: ADVANCED, ANNOTATION, AUTOMATIC_SPEECH_RECOGNITION, AUTOMOTIVE, BEGINNER, DEEP_LEARNING, FINANCE, HEALTHCARE, HIGH_PERFORMANCE_COMPUTING, IMAGE_CLASSIFICATION, IMAGE_SYNTHESIS, INFRASTRUCTURE, INTELLIGENT_VIDEO_ANALYTICS, MACHINE_LEARNING, MANUFACTURING, NATURAL_LANGUAGE_PROCESSING, OBJECT_DETECTION, OIL_AND_GAS, RETAIL, ROBOTICS, SMART_CITIES, SUPERCOMPUTING, TELECOMMUNICATIONS, WINDOWS_RTX_ACCELERATED_MODELS

Field for describing collection's use case. Choices are: HEALTHCARE, SMART_CITIES, RETAIL, MANUFACTURING, SUPERCOMPUTING, ROBOTICS, AUTOMOTIVE, TELECOMMUNICATIONS, FINANCE, OIL_AND_GAS, NATURAL_LANGUAGE_PROCESSING, AUTOMATIC_SPEECH_RECOGNITION, INTELLIGENT_VIDEO_ANALYTICS, OBJECT_DETECTION, IMAGE_CLASSIFICATION, ANNOTATION, IMAGE_SYNTHESIS, MACHINE_LEARNING, DEEP_LEARNING, INFRASTRUCTURE, HIGH_PERFORMANCE_COMPUTING, WINDOWS_RTX_ACCELERATED_MODELS, BEGINNER, ADVANCED

info

Display information about a collection in the registry.

```
ngc registry collection info [--debug] [--format_type <fmt>] [--org <name>]
                             [--team <name>] [-h]
                             <target>
```

Positional Arguments

<target>

Collection. Format: org/[team/]collection_name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

list

Display a list of available collections in the registry.

```
ngc registry collection list [--access-type <access_type>] [--column <column>]
                             [--debug] [--format_type <fmt>] [--org <name>]
                             [--policy <policy>]
                             [--product-name <product_name>]
                             [--release-type <release_type>] [--team <name>]
                             [-h]
                             [<target>]
```

Positional Arguments

<target>

Filter the search by allowing wildcards for Collection(s). Format: org/[team/]collection_name. To target Collection(s), use "org/[team/]collection_name". Org, team, and name support the wildcards "*" and "?". For team-scoped listing, pass a target such as "org/team/"; *--org* and *--team* set command context and are not artifact ownership filters. Examples: "my_org/my_collection" - target my_collection in my_org namespace. "my_org/my_team/my_collection" - target my_collection in my_org/my_team namespace. "my_org/my_team/" - target all collections in my_org/my_team namespace. "my_org/my_collection*" - target collections starting with my_collection in my_org namespace.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--column

Specify output column as column[=header], header is optional, default is name[=Name]. Valid columns are display_name[="Display Name"], name[=Name], created_date[="Created Date"], updated_date[="Updated Date"], category[=Category], org[=Org], team[=Team], labels[=Labels],

accessType=["Access Type"], productNames=["Associated Products"]. Use quotes with spaces. Multiple column arguments are allowed.

--access-type

Possible choices: EXCLUSIVE, LISTED, NOT_LISTED

Filter the list of collections to only collections that have specified access type.

--product-name

Filter the list of collections to only resources that are under the product name. Multiple product-name arguments are allowed. Choose from: nvaie-vpaif, nv-cloud-functions, secrets-manager, base-command-platform, nv-ai-enterprise, nvaie-igx-safety-add-on, chipnemo-inference, ai-foundations, artifact-catalog, riva-virtual-assistant, nemo-llm-service, monai, tao, omniverse-cloud, picasso, data-services, bluefield-enterprise-sw, nv-quantum-cloud, nvaie-igx-yocto-add-on, fleet-command, forge, riva-enterprise, cuopt, met, bionemo-service, iam, nvaie-igx, e2, private-registry

--policy

Possible choices: gov_ready

Filter the list of artifacts to only artifacts that have specified policy labels. Multiple policy arguments are allowed. Choose from: GOV_READY (case-insensitive).

--release-type

Possible choices: beta, ea, feature, ga, ltsb, production

Filter the list of artifacts by release type. Choose from: BETA, GA, EA, FEATURE, PRODUCTION, LTSB (case-insensitive).

update

Update a collection.

```
ngc registry collection update [--add-chart <chart>] [--add-image <image>]
                                [--add-label <add-label>] [--add-model <model>]
                                [--add-resource <resource>] [--built-by <name>]
                                [--category <category>] [--debug]
                                [--display-name <name>] [--format_type <fmt>]
                                [--label <label>] [--label-set <label-set>]
                                [--logo <logo>] [--org <name>]
                                [--overview-filename <path>]
                                [--publisher <publisher>]
                                [--remove-chart <chart>]
                                [--remove-image <image>]
                                [--remove-label <remove-label>]
                                [--remove-model <model>]
                                [--remove-resource <resource>]
                                [--short-desc <desc>] [--team <name>] [-h]
                                <target>
```

Positional Arguments

<target>

Collection to create. Format: Org/[team/]name.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--display-name

Human-readable name for the collection.

--add-label

Label for the collection to add. Can be used multiple times. Imperative label argument, not to be used with declarative label arguments --label or --label-set

--remove-label

Label for the collection to remove. Can be used multiple times. Imperative label argument, not to be used with declarative label arguments --label or --label-set

--label-set

Name of the label set for the collection to declare. Can be used multiple times. Format: org/[team/]name. Declarative label argument, not to be used with declarative label arguments —add-label or —remove-label

--label

Label for the collection to declare. Can be used multiple times. Declarative label argument, not to