

team

Team Commands

```
usage: ngc team [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
              [-h]
              ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

team

Possible choices: add-user, delete-invitation, info, list, list-users, remove-user, update-user

Sub-commands

list

List all accessible teams.

```
ngc team list [--column <column>] [--debug] [--format_type <fmt>]
              [--org <name>] [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--column

Specify output column as column[=header], header is optional, default is id[=Id]. Valid columns are name[=Name], description[=Description]. Use quotes with spaces. Multiple column arguments are allowed.

info

Get team details.

```
ngc team info [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
              [-h]
              <name>
```

Positional Arguments

<name>

Team Name

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

add-user

(For administrators only) Add existing user or invite new user to the current team.

```
ngc team add-user [--debug] [--format_type <fmt>] [--name] [--org <name>]
                  [--org-role <org_role>] --role <r> [--team <name>] [-h]
                  <email|id>
```

Positional Arguments

<email|id>

User Email or ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--name

[DEPRECATED] This parameter is not used and will be ignored.

--org-role

(For org administrators only) Specify the user role in the org, required to add a new user in the org. Updates user roles in the org if the user exists in the org. Options: [FLEET_COMMAND_ADMIN, FLEET_COMMAND_OPERATOR, FLEET_COMMAND_VIEWER, NVIDIA_AI_ENTERPRISE_VIEWER, OMNIVERSE_ADMIN, OMNIVERSE_READ, OMNIVERSE_USER, ORG_OWNER, REGISTRY_ADMIN, REGISTRY_READ, REGISTRY_USER, USER_ADMIN]. To specify more than one org role, use multiple --org-role arguments.

Required named arguments

--role

Specify the user role. Options: [FLEET_COMMAND_ADMIN, FLEET_COMMAND_OPERATOR, FLEET_COMMAND_VIEWER, NVIDIA_AI_ENTERPRISE_VIEWER, OMNIVERSE_ADMIN, OMNIVERSE_READ, OMNIVERSE_USER, ORG_OWNER, REGISTRY_ADMIN, REGISTRY_READ, REGISTRY_USER, USER_ADMIN]. To specify more than one role, use multiple --role arguments.

update-user

(For administrators only) Update a user's roles in the current team.

```
ngc team update-user [--add-role <add_role>] [--debug] [--format_type <fmt>]
                    [--org <name>] [--remove-role <remove_role>]
                    [--role <role>] [--team <name>] [-h]
                    <id>
```

Positional Arguments

<id>

User ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--role

Replace all existing user roles with the specified role(s). This will remove any roles not specified. Options: [FLEET_COMMAND_ADMIN, FLEET_COMMAND_OPERATOR, FLEET_COMMAND_VIEWER, NVIDIA_AI_ENTERPRISE_VIEWER, OMNIVERSE_ADMIN, OMNIVERSE_READ, OMNIVERSE_USER, ORG_OWNER, REGISTRY_ADMIN, REGISTRY_READ, REGISTRY_USER, USER_ADMIN]. To specify more than one role, use multiple --role arguments.

--add-role

Specify the user role to assign. Options: [FLEET_COMMAND_ADMIN, FLEET_COMMAND_OPERATOR, FLEET_COMMAND_VIEWER, NVIDIA_AI_ENTERPRISE_VIEWER, OMNIVERSE_ADMIN, OMNIVERSE_READ, OMNIVERSE_USER, ORG_OWNER, REGISTRY_ADMIN, REGISTRY_READ, REGISTRY_USER, USER_ADMIN]. To specify more than one role, use multiple --add-role arguments.

--remove-role

Specify the user role to remove. Options: [FLEET_COMMAND_ADMIN, FLEET_COMMAND_OPERATOR, FLEET_COMMAND_VIEWER, NVIDIA_AI_ENTERPRISE_VIEWER, OMNIVERSE_ADMIN, OMNIVERSE_READ, OMNIVERSE_USER, ORG_OWNER, REGISTRY_ADMIN, REGISTRY_READ, REGISTRY_USER, USER_ADMIN]. To specify more than one role, use multiple --remove-role arguments.

remove-user

(For administrators only) Remove a user from the current team.

```
ngc team remove-user [--debug] [--format_type <fmt>] [--org <name>]
                    [--team <name>] [-h] [-y]
                    <id>
```

Positional Arguments

<id>

User ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

-y, --yes

Automatically say yes to all interactive questions.

delete-invitation

(For administrators only) Delete a user invitation meant for the current team.

```
ngc team delete-invitation [--debug] [--format_type <fmt>] [--org <name>]
                           [--team <name>] [-h] [-y]
                           <invitation_id>
```

Positional Arguments

<invitation_id>

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

-y, --yes

Automatically say yes to all interactive questions.

list-users

(For administrators only) List all users in the current team.

```
ngc team list-users [--column <column>] [--debug] [--email <email>]
                   [--format_type <fmt>] [--invited] [--joined]
                   [--org <name>] [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--joined

Only list users that have joined.

--invited

Only list invited users.

--column

Specify output column as column[=header], header is optional, default is id[=Id]. Valid columns are name[=Name], email[=Email], roles[=Roles], created[="Created Date"], type[="Invitation Type"], firstLoginDate[="First Login Date"], lastLoginDate[="Last Activity"], idpType[="Sign In Method"]. Use quotes with spaces. Multiple column arguments are allowed.

--email

Filter users by email.

Examples

How to list teams?

```
$ ngc team list
```

Id	Name	Description
393	robot-team	Team for Integration tests

How to list teams using column arguments?

```
$ ngc team list --column name
```

```
+-----+-----+
| Id   | Name       |
+-----+-----+
| 393  | robot-team |
+-----+-----+
```

How to get team details?

```
$ ngc team info cosmos
```

```
-----
Team Information
Id: 161
Name: cosmos
Description: Cosmos team
Deleted: False
-----
```

How to list users in team?

```
$ ngc team list-users --team cosmos
```

```
+-----+-----+-----+-----+-----+
| Id   | Name   | Email               | Roles               | Created Date         |
+-----+-----+-----+-----+-----+
| 0001 | Admin1 | admin1@nvidia.com   | REGISTRY_ADMIN      | 2018-01-01T00:01:00.000Z |
| 0004 | User1  | user1@nvidia.com    | REGISTRY_USER       | 2018-01-04T00:03:00.000Z |
| 0002 | Admin2 | admin2@nvidia.com   | REGISTRY_ADMIN      | 2018-01-02T00:12:00.000Z |
| 0003 | Viewer1 | admin3@nvidia.com   | REGISTRY_READ       | 2018-01-03T00:07:00.000Z |
+-----+-----+-----+-----+-----+
```

How to list users in team using column arguments?

```
$ ngc team list-users --team cosmos --column name --column roles
```

```
+-----+-----+-----+
| Id   | Name   | Roles               |
+-----+-----+-----+
| 0001 | Admin1 | REGISTRY_ADMIN      |
| 0004 | User1  | REGISTRY_USER       |
| 0002 | Admin2 | REGISTRY_ADMIN      |
| 0003 | Viewer1 | REGISTRY_READ       |
+-----+-----+-----+
```

How to add user to an team?

```
$ ngc team add-user foobar@nvidia.com --team cosmos --role REGISTRY_USER
```

```
User: foobar@nvidia.com added to team: cosmos as {'REGISTRY_USER'}.
```

How to update user role?

```
$ ngc team update-user foobar@nvidia.com REGISTRY_ADMIN --team cosmos
```

```
User foobar@nvidia.com information updated.
```

User Id	Name	Email	Org	Teams [Roles]	Created
481	FooBar	foobar@nvidia.com	b0xlotzw8zo9	cosmos [REGISTRY_ADMIN]	2018-01-01

```
$ ngc team update-user foobar@nvidia.com REGISTRY_USER --team cosmos
```

```
User foobar@nvidia.com information updated.
```

User Id	Name	Email	Org	Teams [Roles]	Created
481	FooBar	foobar@nvidia.com	b0xlotzw8zo9	cosmos [REGISTRY_USER]	2018-01-01



[Privacy Policy](#) | [Your Privacy Choices](#) | [Terms of Service](#) | [Accessibility](#) | [Corporate Policies](#) | [Product Security](#) | [Contact](#)

Copyright © 2018-2026, NVIDIA Corporation.