

user

User Commands

```
usage: ngc user [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
               [-h]
               ...
```

Named Arguments

`--debug`

Enable debug mode.

`--format_type`

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

`--org`

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

`--team`

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

user

Possible choices: info, secret, update, who

Sub-commands

secret

Secret Commands

```
ngc user secret [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
               [-h]
               ...
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

secret

Possible choices: create, delete, info, list, update

Sub-commands

create

Create a new secret

```
ngc user secret create [--debug] --desc <description> [--format_type <fmt>]
                       [--org <name>] --pair <key:value> [--team <name>] [-h]
                       <secret-name>
```

Positional Arguments ¶

<secret-name>

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

Required named arguments

--desc

Description of a secret

--pair

A key-value pair to be added to the secret. A key name must be between 1-63 characters and contain letters, numbers or ./_ May be used multiple times in the same command.

list

List available secrets for this user

```
ngc user secret list [--debug] [--format_type <fmt>] [--org <name>]
                    [--team <name>] [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

info

Show details on a specified secret, keys redacted unless specified otherwise

```
ngc user secret info [--debug] [--format_type <fmt>] [--key <key>]
                    [--org <name>] [--team <name>] [-h]
                    <secret-name>
```

Positional Arguments

<secret-name>

Name of Secret

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

--key

Filter all keys except ones provided by this flag, can be used multiple times.

delete

Delete all secrets or a specific secret or key-value pairs from a secret

```
ngc user secret delete [--debug] [--format_type <fmt>] [--key <key>]
                        [--org <name>] [--secret <secret-name>] [--team <name>]
                        [-h] [-y]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

--secret

Specify the name of the secret to delete.

-y, --yes

Automatically say yes to all interactive questions.

--key

Delete a key-value pair from a secret rather than the secret itself. May be used multiple time to delete more than one key-value pair. Required Parameter of Secret.

update

Update a secret description, key-value pairs.

```
ngc user secret update [--debug] [--desc <description>] [--disable] [--enable]
                        [--format_type <fmt>] [--org <name>]
                        [--pair <key:value>] [--team <name>] [-h]
                        secret
```

Positional Arguments

secret

Update a secret description, key-value pairs.

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

--desc

Description of a secret

--pair

A key-value pair to be added to the secret. A key name must be between 1-63 characters and contain letters, numbers or ./-_ May be used multiple times in the same command.

--enable

Enable a secret

--disable

info

Get user details by user id.

```
ngc user info [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]  
              [-h]  
              <id>
```

Positional Arguments

<id>

User ID

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

who

Show the current authorized NGC CLI user.

```
ngc user who [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]  
            [-h]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team. Default: current configuration

update

Update current user information.

```
ngc user update [--debug] [--format_type <fmt>] [--org <name>] [--team <name>]
                [-h] [-n <name>]
```

Named Arguments

--debug

Enable debug mode.

--format_type

Possible choices: ascii, csv, json

Specify the output format type. Supported formats are: ['ascii', 'csv', 'json']. Only commands that produce tabular data support csv format. Default: ascii

--org

Specify the organization name. Use "--org no-org" to override other sources and specify no org (no-org cannot be used if API key is set). Default: current configuration

--team

Specify the team name. Use "--team no-team" to override other sources and specify no team.
Default: current configuration

-n, --name

Update to this username.

Examples

How to show current user info?

```
$ ngc user who
```

User Id	Name	Email	Org [Roles]	Teams [Roles]	Created Date
50923	ngcccli	ngcexample@nvidia.com	robot [REGISTRY_USER]	robot-team [REGISTRY_USER]	2019-04-16 18:31:50 UTC

How to get user info by email?

```
$ ngc user info foobar@nvidia.com
```

User Id	Name	Email	Org [Roles]	Teams [Roles]	Created Date
481	FooBar	foobar@nvidia.com	b0xlotzw8zo9 [REGISTRY_ADMIN]	cosmos [REGISTRY_ADMIN]	2019-04-16 18:31:50 UTC

How to update current user's name?

