
REVISION HISTORY

NUMBER	DATE	DESCRIPTION	NAME
2.8.0	2022-04-14	Current release of Network UPS Tools (NUT).	
2.6.0	2011-01-14	First release of AsciiDoc documentation for Network UPS Tools (NUT).	

Contents

1	APC	1
1.1	940-0024C clone	1
1.2	940-0024E clone	1
1.3	940-0024C clone for Macs	1
2	Belkin	1
2.1	OmniGuard F6C***-RKM	1
3	Eaton	1
3.1	MGE Office Protection Systems	2
3.1.1	DB9-DB9 cable (ref 66049)	2
3.1.2	DB9-RJ45 cable	2
3.1.3	NMC DB9-RJ45 cable	2
3.1.4	USB-RJ45 cable	2
3.1.5	DB9-RJ12 cable	2
3.2	Powerware LanSafe	2
3.3	SOLA-330	2
4	HP - Compaq	3
4.1	Older Compaq UPS Family	3
5	Phoenixtec (Best Power)	3
6	Tripp-Lite	3

Two NUT websites

This version of the page reflects NUT release v2.8.0 with codebase committed c25b30bac at 2022-04-14T17:14:08+02:00
Options, features and capabilities in current development (and future releases) are detailed on the main site and may differ from ones described here.

1 APC

1.1 940-0024C clone

From D. Stimits

APCC 940-0024C clone diagram

Note

The original 940-0024C diagram was contributed by Steve Draper.

1.2 940-0024E clone

Reported by Jonathan Laventhol

This cable is said to use the same wiring as 940-0024C clone.

1.3 940-0024C clone for Macs

From Miguel Howard

APCC 940-0024C clone cable for Macs

2 Belkin

2.1 OmniGuard F6C***-RKM

From "Daniel"

A straight-through RS-232 cable (with pins 2-7 connected through) should work with the following models:

- F6C110-RKM-2U
- F6C150-RKM-2U
- F6C230-RKM-2U
- F6C320-RKM-3U

Belkin OmniGuard F6C***-RKM cable

3 Eaton

Documents in this section are provided courtesy of Eaton.

3.1 MGE Office Protection Systems

The three first cables also applies to MGE UPS SYSTEMS and Eaton.

3.1.1 DB9-DB9 cable (ref 66049)

This is the standard serial cable, used on most units.

DB9-DB9 cable

3.1.2 DB9-RJ45 cable

This cable is used on the more recent models, including Ellipse MAX, Protection Station, ...

DB9-RJ45 cable

3.1.3 NMC DB9-RJ45 cable

The following applies to the MGE 66102 NMC (Network Management Card), and possibly other models. The NMC connection is an 8P8C RJ45-style jack.

Signal	PC	NMC
	1,4,6	
TxD	2	3
RxD	3	6
GND	5	4
	7,8	
	shield	shield

3.1.4 USB-RJ45 cable

This cable is used also on the more recent models, including Ellipse MAX, Protection Station, ...

USB-RJ45 cable

3.1.5 DB9-RJ12 cable

This cable is used on some older Ellipse models.

DB9-RJ12 cable

3.2 Powerware LanSafe

Powerware LanSafe cable

3.3 SOLA-330

Just uses a normal serial cable, with pin 1-1 through to 9-9.

SOLA-330 cable

4 HP - Compaq

4.1 Older Compaq UPS Family

This cable can be used with the following models:

T700, T1000, T1500, T1500j, T700h, T1000h, T1500h, R1500, R1500j, R1500h, T2000, T2000j, T2400h, T2400h-NA, R3000 / R3000j, R3000h, R3000h-International, R3000h-NA, R6000h-NA, R6000i, R6000j.

UPS PC 9 pin connector

```

1 ----- 3
2 ----- 2
           4 -\
4 ----- 5  |
           6 -/
6 ----- 7

```

Contributed by Kjell Claesson and Arnaud Quette.

5 Phoenixtec (Best Power)

Many Best Power units (including the Patriot Pro II) have a female DB-9 socket with a non-standard pinout.

Signal	PC	UPS
	1,4,6	NC
TxD	2	2
RxD	3	1
GND	5	4
	7,8	NC

Sources:

- http://pinoutsguide.com/UPS/best_power_pinout.shtml
- http://lit.powerware.com/ll_download.asp?file=m_patriotproii_jan99.pdf
- Stan Gammons

6 Tripp-Lite

From Tripp-Lite, via Bryan Kolodziej

This cable (black 73-0844 cable) is used on various models, using the "Lan 2.2 interface" and the genericups driver (upstype=5).

73-0724 cable