

1	ABSTRACT . . . . .	iv
2	ACKNOWLEDGEMENTS . . . . .	v
3	INTRODUCTION . . . . .	1
	3.1 Overview . . . . .	1
	3.2 Upland Watershed Characteristics . . . . .	2
	3.3 Summary of Impacts . . . . .	2
	3.4 Boone Creek Monitoring . . . . .	3
	3.5 Thermal Remediation Practices . . . . .	5
	3.6 Using Construction Aggregate for Thermal Mitigation . . . . .	6
4	EXPERIMENTATION . . . . .	7
	4.1 Stormwater Discharge Simulations . . . . .	7
	4.2 Flow Sensor Data Acquisition and Interface . . . . .	17
5	Data Analysis . . . . .	26
	5.1 Time Synchronization of Temperature Data . . . . .	26
	5.2 Vessel Temperature Differential . . . . .	29
	5.3 Cumulative Energy Transfer . . . . .	30
	5.4 Normalization of the Cumulative Energy Transfer Function . . . . .	32
	5.5 Thermal Power Calculations . . . . .	35
	5.6 Bulk $\kappa$ and $\alpha$ Calculation . . . . .	36
6	Theory . . . . .	38
	6.1 Resistor-Capacitor (RC) Circuit Analogy . . . . .	38
	6.2 An Empirical Formulation from Experimental Parameters . . . . .	42
7	Discussion and Results . . . . .	47
	7.1 Aggregate Parameters . . . . .	47
	7.2 Concepts of Thermal Sink Performance Metrics . . . . .	51
	7.3 Interpreting the Scaled, Normalized CET Function . . . . .	51
	7.4 Thermal Conductivity, Moment and Diffusivity as Performance Indicators . . . . .	57
	7.5 Recommendations for Thermal Buffering of Watersheds . . . . .	58
	7.6 Conclusion . . . . .	60
	References . . . . .	61
A	Flow Sensor DAQ Source Code . . . . .	69
B	Data Plots . . . . .	81
	B.1 Quartzite Family . . . . .	81
	B.2 Marble and Brick . . . . .	81
	B.3 Siltstone, Cobble, Glass and Steel . . . . .	81
	B.4 Comparison Plots . . . . .	81
C	Vita . . . . .	95