



UNLOCK HUMAN POTENTIAL

UHP RAILWAY — NEW ENVIRONMENT SETUP

Task Brief · all

OWNER

Joaquim Manzini, Lead Full Stack Engineer

VERSION

v1.0

DATE

May 20, 2026

PURPOSE

This document describes the end-to-end process for provisioning a new Railway environment for the UHP platform. It covers Railway service creation, environment variable configuration, Supabase connection, GitHub secrets, and post-setup verification.

ARCHITECTURE OVERVIEW

Three Railway services are deployed per environment. All three share the same Supabase project (test/staging) unless explicitly separated for production.

Service	Repo	Builder	Health Check
uhp-ops-agent	UHP-OPS-Agent	Dockerfile	/auth/login
uhp-field-execution	uhp-field-execution	Dockerfile	/
uhp-student-app	uhp-student-app	Nixpacks	/api/health

PREREQUISITES

Requirement	How to Verify
Railway account with project access	<code>railway whoami</code>
Railway CLI installed	<code>railway --version</code>
Railway CLI authenticated (see below)	<code>railway whoami</code> returns your username
Supabase project keys available	Supabase dashboard, Project Settings > API
External service keys available (Twilio, Resend, Slack, etc.)	1Password / team vault
GitHub org admin access	Required to add GitHub Actions secrets

Railway CLI Authentication

The setup script uses the Railway CLI to set environment variables. Authenticate once before running it:

```
railway login
```

The CLI will print a URL. Open it in your browser, click Authorize, and the session is saved locally. Sessions last weeks.

WSL users: the browser will not open automatically. Copy the printed URL and paste it into your Windows browser manually.

STEP 1: CREATE THE ENVIRONMENT IN RAILWAY

1. Open the [Railway dashboard](#).
2. Select the **UHP** project.
3. Click **New Environment** and name it (e.g. `Staging - New`).
4. Add the three services to the environment if not already present:
 - Deploy from GitHub repo for each service using the settings below.

Service	GitHub Repo	Branch	Builder	Start Command
uhp-ops-agent	UHP-com/UHP-OPS-Agent	staging	Dockerfile	(from Dockerfile)
uhp-field-execution	UHP-com/uhp-field-execution	staging	Dockerfile	(from Dockerfile)
uhp-student-app	UHP-com/uhp-student-app	staging	Nixpacks	npm run start

5. **Disable GitHub auto-deploy** on all three services. Deploys are triggered only by the orchestrator workflow, not on every push.
 - In each service: Settings > Source > uncheck "Deploy on push".

STEP 2: COLLECT SERVICE URLS

Railway generates a URL for each service as soon as it is created, before the first deploy. Collect all three before setting env vars (they reference each other).

Service	URL pattern	Env var it becomes
uhp-ops-agent	https://uhp-ops-agent- <hash>.up.railway.app	UHP_OPS_AGENT_URL on field + student
uhp-field-execution	https://uhp-field-execution- <hash>.up.railway.app	NEXT_PUBLIC_FIELD_EXEC_URL on ops
uhp-student-app	https://uhp-student-app- <hash>.up.railway.app	NEXT_PUBLIC_STUDENT_APP_URL on ops

Use custom domains if available (e.g. `staging.uhp.com`). Set them in Railway under each service's Settings > Networking before collecting the URL.

STEP 3: SET ENVIRONMENT VARIABLES

3a. Fill in the env template

```
cp .env.staging.example .env.staging-new
# Open .env.staging-new and fill in all values.
# Supabase values are in the team vault and are shared with the existing test enviro
```

3b. Run the setup script

```
node scripts/setup-railway-env.mjs --environment "Staging - New" --dry-run
# Review the output, then run without --dry-run to apply:
node scripts/setup-railway-env.mjs --environment "Staging - New"
```

The script routes each variable to the correct service automatically. Variables with empty values in the template are skipped with a warning. The Railway project ID (`e1c3ea55-5867-4e18-9040-bee49b755394`) is hardcoded in the script, so no `railway link` is required.

3c. Verify

```
railway variables list --project e1c3ea55-5867-4e18-9040-bee49b755394 --environment
railway variables list --project e1c3ea55-5867-4e18-9040-bee49b755394 --environment
railway variables list --project e1c3ea55-5867-4e18-9040-bee49b755394 --environment
```

STEP 4: ADD GITHUB ACTIONS SECRETS

These secrets are used by the deploy orchestrator workflow in `UHP-OPS-Agent/.github/workflows/`.

Navigate to: GitHub > UHP-com/UHP-OPS-Agent > Settings > Secrets and variables > Actions

Secret name	Value	Notes
-------------	-------	-------

<code>SUPABASE_DB_URL_UHP</code>	Postgres connection URL for the shared DB	From Supabase dashboard, Project Settings > Database > Connection string (URI mode)
<code>SUPABASE_ACCESS_TOKEN</code>	Supabase personal access token	Supabase dashboard, Account > Access Tokens
<code>RAILWAY_API_TOKEN</code>	Railway API token	Railway dashboard, Account > Developer (OAuth tokens are not supported here; use a deploy-hook-based approach or the Railway REST API with a session token)
<code>RAILWAY_DEPLOY_HOOK_OPS_STAGING</code>	Deploy hook URL for ops service	Railway: service > Settings > Deploy Hooks
<code>RAILWAY_DEPLOY_HOOK_FIELD_STAGING</code>	Deploy hook URL for field service	
<code>RAILWAY_DEPLOY_HOOK_STUDENT_STAGING</code>	Deploy hook URL for student service	
<code>SLACK_BOT_TOKEN</code>	Slack bot token for deploy notifications	Same token as env var above

Deploy hooks are per-service per-environment. Generate one for each service in this new environment.

STEP 5: TRIGGER FIRST DEPLOY

Once env vars are set, trigger a manual deploy on each service to confirm the build passes.

```
# Via Railway CLI (replace hook URLs with the ones from the Railway dashboard)
curl -X POST "$RAILWAY_DEPLOY_HOOK_OPS_STAGING"
curl -X POST "$RAILWAY_DEPLOY_HOOK_FIELD_STAGING"
curl -X POST "$RAILWAY_DEPLOY_HOOK_STUDENT_STAGING"
```

Or trigger from the Railway dashboard: each service > Deploy > Trigger Deploy.

STEP 6: POST-DEPLOY VERIFICATION

Check	Expected	Command / URL
OPS-Agent health	HTTP 200 or redirect	<code>curl -I <OPS_URL>/auth/login</code>
Field execution health	HTTP 200	<code>curl -I <FIELD_URL>/</code>
Student app health	HTTP 200, <code>{"ok":true}</code>	<code>curl <STUDENT_URL>/api/health</code>
Supabase connectivity	No 500 errors on login	Open <code>/auth/login</code> in browser
GitHub Actions — pre-MLP	Workflow passes	Push a trivial change to <code>staging</code> branch

ENVIRONMENT VARIABLE REFERENCE

Shared (all 3 services)

Variable	Description
<code>NEXT_PUBLIC_SUPABASE_URL</code>	Supabase project URL
<code>NEXT_PUBLIC_SUPABASE_ANON_KEY</code>	Supabase anon key (public)
<code>SUPABASE_SERVICE_ROLE_KEY</code>	Supabase service role key (server-side only)
<code>ANTHROPIC_API_KEY</code>	Claude API key
<code>NEXT_PUBLIC_VAPID_PUBLIC_KEY</code>	Web push VAPID public key
<code>VAPID_PRIVATE_KEY</code>	Web push VAPID private key
<code>CRON_SECRET</code>	Bearer token for cron endpoint authorization
<code>NODE_ENV</code>	<code>production</code>

OPS-Agent only

Variable	Description
<code>NEXT_PUBLIC_APP_URL</code>	This service's public URL
<code>NEXT_PUBLIC_SITE_URL</code>	Same as above (magic link base)
<code>NEXT_PUBLIC_STUDENT_APP_URL</code>	Student app URL (cross-service link)
<code>NEXT_PUBLIC_FIELD_EXEC_URL</code>	Field execution URL (nav link)
<code>ALLOWED_EMAIL_DOMAINS</code>	Comma-separated domains allowed to sign in

ADMIN_EMAIL	Primary admin email
RESEND_API_KEY , RESEND_FROM_EMAIL	Transactional email
TWILIO_ACCOUNT_SID , TWILIO_AUTH_TOKEN , TWILIO_PHONE_NUMBER , TWILIO_FROM_NUMBER	SMS
SLACK_BOT_TOKEN , SLACK_SIGNING_SECRET , SLACK_CHANNEL_*	Slack notifications
HUBSPOT_PRIVATE_APP_TOKEN	HubSpot CRM integration
HEYGEN_API_KEY + NEXT_PUBLIC_HEYGEN_*	AI video (optional on staging)
OPERATIVE_*	Forge/Operative platform (optional, degrades gracefully)

field-execution only

Variable	Description
NEXT_PUBLIC_APP_URL	This service's public URL
UHP_OPS_AGENT_URL	OPS-Agent URL (for work order creation)

student-app only

Variable	Description
NEXT_PUBLIC_APP_URL , NEXT_PUBLIC_SITE_URL	This service's public URL
UHP_OPS_AGENT_URL	OPS-Agent URL (Morgan fallback link)
UHP_ENFORCE_ACTIVE_STUDENT	true to enforce active-student auth check

TROUBLESHOOTING

Symptom	Likely cause	Fix
Build fails on first deploy	Missing env var causing compile-time error	Check Railway build logs; set missing var and redeploy
/auth/login returns 500	NEXT_PUBLIC_SUPABASE_URL or SUPABASE_SERVICE_ROLE_KEY not set	Verify with <code>railway variables list</code>
Cron endpoints return 401	CRON_SECRET not set or mismatched	Re-run setup script; verify value matches caller
Push notifications not working	VAPID keys missing or mismatched pair	Regenerate VAPID pair and set both keys on all services

OPS-Agent can't reach student app	<code>NEXT_PUBLIC_STUDENT_APP_URL</code> wrong	Update the var to the correct Railway URL and redeploy
<code>railway variables set</code> fails	Not logged in to Railway CLI	Run <code>railway login</code> , copy the printed URL, open it in your browser, click Authorize.