

Packing Slip WebService

CONFIDENTIAL

Overview

The Packing Slip Web Service allows users to create a packing slip by order, sales work order or line item and to update packing slips. The input to this web service varies by action – it can either be sales work order number or line item number or packing slip number (internal only). If the Shipment Email Notification is configured, the Portal User will receive Shipping Notifications when appropriate.

Action	Summary
CreatePackingSlipbyLineItem	Applies to Accounts and Suppliers. One or more line items can be contained in a packing slip. If a supplier is using, the line item must be for that supplier. It is possible to modify the quantity shipped for these line items. If no quantity shipped is provided, the quantity shipped will always be the quantity ordered. Packing Slip Cost can be assigned (for the entire packing slip) – if it is not provided the shipping cost of the individual line items will be used to create the total ship cost for the packing slip. A Packing Slip always has the same Ship To Address, if none is provided the Ship To Address for each line will be used.
CreatePackingSlipBySalesWorkOrder	Only applies to Suppliers. One or more sales work orders can be contained in a packing slip. It is not possible to modify the quantity shipped for these line items – the quantity shipped will always be the quantity ordered. Packing Slip Cost can be assigned (for the entire packing slip) – if it is not provided the shipping cost of the individual line items will be used to create the total ship cost for the packing slip. A Packing Slip always has the same Ship To Address, if none is provided the Ship To Address for each line will be used.
CreatePackingSlipbyOrder	Only applies to Accounts. One or more orders can be contained in a packing slip. It is not possible to modify the quantity shipped for these line items – the quantity shipped will always be the quantity ordered. Packing Slip Cost can be assigned (for the entire packing slip) – if it is not provided the shipping cost of the individual line items will be used to create the total ship cost for the packing slip. A Packing Slip always has the same Ship To Address, if none is provided the Ship To Address for each line will be used.
UpdatePackingSlip	Applies to Accounts and Suppliers. One packing slip can be updated using the MarcomCentral (Printable) Internal ID or the External ID (if provided by Client). These values are provided in response to any of the actions that Create a Packing Slip. If consumed by a supplier, the packing slip must have been created by this supplier.



US Environment Endpoint	https://services.printable.com/trans/1.0/PackingSlip.asmx
US Environment WSDL	https://services.printable.com/trans/1.0/PackingSlip.asmx?WSDL
EU Environment Endpoint	https://services-eu.marcomcentral.app.pti.com/TRANS/1.0/PackingSlip.asmx
EU Environment WSDL	https://services-eu.marcomcentral.app.pti.com/TRANS/1.0/PackingSlip.asmx?wsdl

High Level Functions

CreatePackingSlipByLineItem	4
pRequest	5
PartnerCredentials	6
Options	6
PackingSlipNode	6
ShipToAddress	7
Line Items	8
Line Item	9
CreatePackingSlipBySalesWorkOrder	4
pRequest	5
PartnerCredentials	6
Options	6
PackingSlipNode	6
ShipToAddress	7
SalesWorkOrders	8
SalesWorkOrder	9



CreatePackingSlipByOrder	4
pRequest	5
PartnerCredentials	6
Options	6
PackingSlipNode	6
ShipToAddress	8
Orders	9
Order	10
UpdatePackingSlip	4
pRequest	5
PartnerCredentials	6
Options	6
PackingSlipNode	6
ShipToAddress	8
CreatePackingSlipByLineItemResponse	11
CreatePackingSlipByLineItemResult	12
CreatePackingSlipBySalesWorkOrderResponse	11
CreatePackingSlipBySalesWorkOrderResult	12
CreatePackingSlipByOrderResponse	11
CreatePackingSlipByOrderResult	13
UpdatePackingSlipResponse	11
UpdatePackingSlipResult	13



*R(equired); O(ptional); C(onditional)

CreatePackingSlipByLineItem

CreatePackingSlipByLineItem					
Element	Type	Validation	Description	R/O/C	Details
pRequest	DETAILS		<See pRequest Section>	R	

CreatePackingSlipBySalesWorkOrder

CreatePackingSlipBySalesWorkOrder					
Element	DataType	Length	Description	R/O/C	Details
pRequest	DETAILS		<See pRequest Section>	R	

CreatePackingSlipByOrder

CreatePackingSlipByOrder					
Element	DataType	Length	Description	R/O/C	Details
pRequest	DETAILS		<See pRequest Section>	R	

UpdatePackingSlip

UpdatePackingSlip					
Element	DataType	Length	Description	R/O/C	Details
pRequest	DETAILS		<See pRequest Section>	R	



pRequest

pRequest					
Element	DataType	Length	Description	R/O/C	Details
PartnerCredentials	DETAILS		<See PartnerCredentials Section>	R	
Options	DETAILS		<See Options Section>	O	
PackingSlipNode	DETAILS		<See PackingSlipNode Section>	O	
LineItems	DETAILS		<See LineItems Section>	R	

pRequest

pRequest					
Element	DataType	Length	Description	R/O/C	Details
PartnerCredentials	DETAILS		<See PartnerCredentials Section>	R	
Options	DETAILS		<See Options Section>	O	
PackingSlipNode	DETAILS		<See PackingSlipNode Section>	O	
SalesWorkOrders	DETAILS		<See SalesWorkOrders Section>	R	

pRequest

pRequest					
Element	DataType	Length	Description	R/O/C	Details
PartnerCredentials	DETAILS		<See PartnerCredentials Section>	R	
Options	DETAILS		<See Options Section>	O	
PackingSlipNode	DETAILS		<See PackingSlipNode Section>	O	
Orders	DETAILS		<See Orders Section>	R	



pRequest

pRequest					
Element	DataType	Length	Description	R/O/C	Details
PartnerCredentials	DETAILS		<See PartnerCredentials Section>	R	
Options	DETAILS		<See Options Section>	O	
PackingSlipNode	DETAILS		<See PackingSlipNode Section>	O	

PartnerCredentials

PartnerCredentials					
Element	DataType	Length	Description	R/O/C	Details
Token	STRING		Unique identifier that authorizes webservice use	R	Provided by MarcomCentral

Options

Options					
Element	DataType	Length	Description	R/O/C	Details
Name=	STRING		Reserved for future use	O	Reserved for future use
Value=	STRING		Reserved for future use	O	Reserved for future use

PackingSlipNode

PackingSlipNode					
Element	DataType	Length	Description	R/O/C	Details
ID	STRING	1 to 255 characters	Unique identifier of the Packing Slip.	C	Optional "type" parameter with the values of "Printable" or "NonPrintable". When used when creating a Packing Slip



					by Line Item, Order or Sales Work Order this is optional and will always be NonPrintable. When used with Update Packing Slip this is required and either Printable or NonPrintable can be used. If ID provided when creating Packing Slip normally this is used to update Packing Slip.
PackingSlipNumber	STRING	1 to 255 characters	Packing Slip Number	O	If this is not provided, system will assign a number here. This number is assigned using auto numbering is configured for the Portal. If nothing is configured date/time stamp will be used.
ShipDate	DATETIME		Ship Date	O	If this is not provided, this will default to current date.
CarrierName	STRING	1 to 255 characters	An optional identifier to help the caller match the request with the response. This value was echoed back from the OrderRequest.	O	If values are provided for UPS, DHL or FedEx these exact values must be provided for the tracking link to work for end-users.
TrackingNumber	STRING	1 to 255 characters	Tracking number for the line number. The Carrier Name must be supplied along with the for tracking link to be provided to end user for FedEx, UPS or DHL.	O	
ShipCost	DECIMAL		Shipping cost for the line item.	O	If this is not provided, the current value assigned will be used.



SkipAdjustInventory	STRING	1 to 255 characters	If this is set to true inventory will not be adjusted, if this is set to false inventory will be adjusted – the quantity on hand (QOH) will be decremented by the amount shipped.	O	If this is not provided, this will default to false.
ShipToAddress	DETAIL		<See ShipToAddress Section>	O	If nothing is provided, the address associated with line item will be used

ShipToAddress

ShipToAddress					
Element	DataType	Length	Description	R/O/C	Details
Attention	STRING	1 to 255 characters	Attention Line associated with address	O	
Name	STRING	1 to 100 characters	Reference name for this address	O	
Address1	STRING	to 100 characters	Line one of address	O	
Address2	STRING	to 100 characters	Line two of address	O	
Address3	STRING	to 100 characters	Line three of address	O	
Address4	STRING	to 100 characters	Line four of address	O	
City	STRING	to 100 characters	City	O	
State	STRING	to 100 characters	State	O	
Postal Code	STRING	to 100 characters	Postal Code/Zip	O	
Country	STRING	to 100 characters	Country	O	



LineItems

LineItems					
Element	DataType	Length	Description	R/O/C	Details
LineItem	DETAIL		<See LineItem Section>	R	

SalesWorkOrders

SalesWorkOrders					
Element	DataType	Length	Description	R/O/C	Details
SalesWorkOrder	DETAIL		<See SalesWorkOrder Section>	R	

Orders

Orders					
Element	DataType	Length	Description	R/O/C	Details
Order	DETAIL		<See Order Section>	R	

LineItem

LineItem					
Element	DataType	Length	Description	R/O/C	Details
ID	STRING	1 to 255 characters	Unique identifier of the Order Line Item.	R	Optional "type" parameter with the value of "Printable". If nothing is provided, Printable will be assumed.
Quantity	NUMBER		Quantity Shipped	O	If this is not provided the quantity ordered will be used to define the quantity shipped.



SalesWorkOrder

SalesWorkOrder					
Element	DataType	Length	Description	R/O/C	Details
ID	STRING	1 to 255 characters	Unique identifier of the SalesWorkOrder.	R	Optional "type" parameter with the value of "Printable". If nothing is provided, Printable will be assumed.

Order

Order					
Element	DataType	Length	Description	R/O/C	Details
ID	STRING	1 to 255 characters	Unique identifier of the Order.	R	Optional "type" parameter with the value of "Printable". If nothing is provided, Printable will be assumed.

CreatePackingSlipByLineItemResponse

CreatePackingSlipByLineItemResponse					
Element	DataType	Length	Description	R/O/C	Details
CreatePackingSlipByLineItemResult	DETAIL		<See CreatePackingSlipByLineItemResult Section>	R	



CreatePackingSlipBySalesWorkOrderResponse

CreatePackingSlipBySalesWorkOrderResponse					
Element	DataType	Length	Description	R/O/C	Details
CreatePackingSlipBySalesWorkOrderResult	DETAIL		<See CreatePackingSlipBySalesWorkOrderResult Section>	R	

CreatePackingSlipByOrderResponse

CreatePackingSlipByOrderResponse					
Element	DataType	Length	Description	R/O/C	Details
CreatePackingSlipByOrderResult	DETAIL		<See CreatePackingSlipByOrderResult Section>	R	

UpdatePackingSlipResponse

UpdatePackingSlipResponse					
Element	DataType	Length	Description	R/O/C	Details
UpdatePackingSlipResult	DETAIL		<See UpdatePackingSlipResult Section>	R	

CreatePackingSlipByLineItemResult

CreatePackingSlipByLineItemResult					
Element	DataType	Length	Description	R/O/C	Details
TotalOrders	INTEGER		Total number of line items that were in request	R	
FailOrdersCount	INTEGER		Total number of line items that were not able to be shipped	R	



SuccessOrdersCount	INTEGER		Total number of line items that were able to be shipped	R	
Status	DETAIL		<See Status Section>	R	
Responses	DETAIL		<See Responses Section>	R	

CreatePackingSlipBySalesWorkOrderResult

CreatePackingSlipBySalesWorkOrderResult					
Element	DataType	Length	Description	R/O/C	Details
TotalOrders	INTEGER		Total number of sales work orders that were in request	R	
FailOrdersCount	INTEGER		Total number of sales work orders that were not able to be shipped	R	
SuccessOrdersCount	INTEGER		Total number of sales work orders that were able to be shipped	R	
Status	DETAIL		<See Status Section>	R	
Responses	DETAIL		<See Responses Section>	R	

CreatePackingSlipByOrderResult

CreatePackingSlipByOrderResult					
Element	DataType	Length	Description	R/O/C	Details
TotalOrders	INTEGER		Total number of orders that were in request	R	
FailOrdersCount	INTEGER		Total number of orders that were not able to be shipped	R	
SuccessOrdersCount	INTEGER		Total number of orders that were able to be shipped	R	
Status	DETAIL		<See Status Section>	R	
Responses	DETAIL		<See Responses Section>	R	



UpdatePackingSlipResult

UpdatePackingSlipResult					
Element	DataType	Length	Description	R/O/C	Details
Status	DETAIL		<See Status Section>	R	
Responses	DETAIL		<See Responses Section>	R	

Responses

Responses					
Element	DataType	Length	Description	R/O/C	Details
Response	DETAIL		<See Response Section>	R	

Response

Response					
Element	DataType	Length	Description	R/O/C	Details
OrderID	STRING		This is the unique ID of an order which contained line items requested to be shipped	R	
Status	DETAIL			O	
LineItemResponses	DETAIL			R	
Actions	DETAIL			O	
LineItemID	STRING		This is the unique ID of a line item which was requested to be shipped	O	



Status

Status					
Element	DataType	Length	Description	R/O/C	Details
Action=	STRING		Describes the requested action of the webservice request	R	Examples: PACKING_SLIP PACKING_SLIP_UPDATE
Status=	STRING		Describes the outcome of the Action	R	Examples: ProcessComplete, ProcessFailure
Code=	STRING		Code associated with the Status	R	
Message=	STRING		Additional details describing the Status	R	Example: Process completed Successfully See Additional details on Codes & Messages table at end of document
ReferenceType=	STRING			O	
ReferenceID=	STRING		Unique ID for the ReferenceType	O	
ID	STRING		Same as ReferenceID	O	

LinItemResponses

LinItemResponses					
Element	DataType	Length	Description	R/O/C	Details
LinItem	DETAIL			R	



LineItem

Line Item					
Element	DataType	Length	Description	R/O/C	Details
OrderID	STRING		This is the unique ID of an order which contained line items requested to be shipped	R	
LineItemID	STRING		This is the unique ID of a line item which was requested to be shipped	R	
Status	DETAIL			R	
Actions	DETAIL			R	

Actions

Actions					
Element	DataType	Length	Description	R/O/C	Details
Action	DETAIL			O	

Action

Action					
Element	DataType	Length	Description	R/O/C	Details
Action=	STRING		Describes the requested action of the webservice request	R	
Status=	STRING		Describes the outcome of the Action	R	Examples: ProcessComplete, ProcessFailure
Code=	STRING		Code associated with the Status	R	
Message=	STRING		Additional details describing the Status	O	Example: Process completed Successfully



					See Additional details on Codes & Messages table at end of document
ReferenceType=	STRING			R	Example: PackingSlip
ReferenceID=	STRING		Unique ID for the ReferenceType	R	If packing slip created by a web service this is the value found in <PackingSlipNumber> element or if none is provided it will be autogenerated.
ID	DETAILS		<See ID section>		

ID

ID					
Element	DataType	Length	Description	R/O/C	Details
ID	STRING	1 to 255 characters	Unique identifier of the item	R	Optional "type" parameter with the values of "Printable" or "NonPrintable". If user provides NonPrintable ID when Packing Slip created it will be provided, otherwise it will be Printable. If type is not specified it is Printable ID.



Additional Codes and Messages

Code	Error	Description
1	ProcessSuccess	Service finished successfully.
2	ProcessFailure	Service Failure
3	ProcessComplete	Process completed successfully.
4	ProcessError	Process encountered an error.
5	ProcessDone	Service has completed operations. Please look at Response section for Detail results information.
6	IncompleteRequest	Request did not contain sufficient information to perform any actions (The request ID section might not be well formed).
7	InsufficientPrivileges	Token/credentials insufficient to process request().
8	InvalidUserId	The User ID supplied is not contained in the system.
9	NoUserFoundForThisOrder	Unable to obtain a valid user ID for this order.
10	InvalidOrderId	The Order ID supplied is not contained in the system.
11	InvalidSalesWorkOrderId	The Sales Work Order ID supplied is not contained in the system.
12	InvalidOrderDetailId	The Line Item ID (Order Detail ID) supplied is not contained in the system.
13	InvalidSettlementId	The Settlement ID supplied is not contained in the system.
14	InvalidCompanyId	The CustomerNumber/Company ID supplied is not contained in the system.
15	InvalidProductId	The Product ID supplied is not contained in the system.
100	IncompleteRequestInvalidID	Unable to process request, invalid ID.
101	IncompleteRequestInvalidToken	Unable to process request, invalid token.
102	UnableToMapData	Unable to Map Request Data, might be missing data.
103	UnableToSummitData	Unable to Map submit Data, invalid/missing data.
104	UnableToSummitLineItemData	Unable to Map summit Data, A line item might be incomplete/corrupt.



Code	Error	Description
105	StatusRetrievalError	Unable to retrieve order status.
106	StatusRetrievalNoOrdersError	Unable to retrieve order status.
107	StatusRetrievalNoOrderError	Unable to retrieve order status.
108	InvalidRequestType	This type of request is not supported.
109	InvalidPackingSlipId	Packing Slip ID was not found in database.
110	InvalidExternalId	The external Id provided, is a duplicate or invalid.
111	UnableToCreateSettlement	Unable to submit new Settlement to database.
112	MultiSupplierNotSupported	Multiple Suppliers are not currently supported for this operation.
113	UnableToCreateUser	Unable to create a new user.
114	UnableToCreateLogEntry	Unable to Add an entry to the log, this could prevent the service to follow through.
115	UnableToAddProductToQueue	Unable to Queue the Base Product in the Copy Product queue.
116	UnableToFindLibrary	Unable to find/create Library.
117	UnableToUploadImageLibrary	Unable to upload Image.
118	FileNotFound	Unable to find file.
119	CustomerNumberNotFound	Unable to find customer in the system.
120	UnableToCreateProduct	Unable to Build/Create product.
121	UnableToAddToFeaturesProducts	Unable to add product to Feature products.
122	UnableToAssociateProductToUser	Unable to add product to Group User relationship.
150	OrderPendingShipment	Work is still in progress for some Line Items.
151	OrderPendingInvoice	Current state does not permit Invoice (it has not been shipped).
152	EmptyOrder	This order does not contains any items.
153	OrderPendingSettlement	Unable to settle order.
154	OrderHasAlreadyBeenShipped	Order/Line Item has already been shipped.
155	OrderHasAlreadyBeenInvoiced	Order has already been invoiced.



Code	Error	Description
156	OrderHasAlredyBeenSettled	Order has already been settled.
157	OrderNotACreditCardOrder	Not a credit card order.
158	SettlementProblem	Settlement Error.
159	LineItemIsNotReadyToBeShipped	Line Item(s) state does not permit packing slip. Missing associated job ticket.
160	LineItemIsNotReadyToBeInvoiced	Line Item(s) state does not permit Invoice. Possibly missing Packing Slip.
161	OrderIsNotReadyToBeSettlement	Order state does not permit settlement.
162	LineItemsBelongToDifferentSalesWorkOrder	The Line Items requested belongs to different Sales Work Orders.
163	DuplicateLineItem	There are duplicate Line Items in the request
164	NonPrintableLineLineItemId	Non Printable Line Item IDs are currently not supported in this context.
165	NonPrintableOrderId	Non Printable Order IDs are currently not supported in this context.
166	NonPrintableSalesWorkOrderId	Non Printable Sales Work Order IDs are currently not supported in this context.
167	InventoryConflict	The inventory constraints do not permit this operation.
168	UnableToSendEmail	Unable to Send email for request.
169	PdfFileInUseByAnotherRequest	The requested PDF file is is use by another request.
170	SettlementNotConfiguredForTheseCredentials	The credentials and settlement settings do not permit operation.
171	RequisitionIDInvalid	Requisition ID is invalid
172	ApproverIDInvalid	Approver ID is invalid
173	RequisitionDoesNotExist	Requisition does not exist
174	RequisitionDoesNotBelongToTheStore	Requisition does not belong to the portal
175	RequisitionAlreadyApprovedOrDenied	Requisition has already been approved or denied
176	RequisitionProcessingValidationError	Requisition processing validation error
177	LoginIDCannotProcessRequisitions	Login ID cannot process requisitions