

A still from the movie 'The Hobbit' showing a character in a goat costume running towards a character in a white dress. The character in the goat costume is on the left, and the character in the white dress is on the right. The background is a misty, outdoor setting.

James' Super Cool IS 201 Cheat Sheet

You






Index

	Slide	Topic
Unit 2	2	 <u>ERDs</u>
	6	 <u>SQL</u>
Unit 3	12	 <u>Flow Charts</u>
	13	 <u>VBA</u>
Unit 4	19	 <u>Statistics</u>
	20	 <u>Tableau</u>
	21	 <u>Solver</u>
Unit 5	22	 <u>HTML</u>
	31	 <u>CSS</u>



ERD: Primary / Foreign Keys



movie_id	title
1	Monty Python...
2	Count of Mon...
3	Princess Bri...

responder_id	name	movie_id
1	James	1
2	Gaskin	2
3	Megan	1

A **primary key** is a unique identifier (think social security number)

A **foreign key** is another table's primary key, used to link two tables together


Want the duration of James's favorite movie? Look up his `movie_id` (1) in `movie_info`. The movie's info is stored once there, not copied onto James's and Megan's rows. Avoiding that repetition is the power of foreign keys!

Entity
Relationship
Diagram



ERD: Cardinality


Read left-to-right AND right-to-left



One to One (1:1)

A knight has one quest


A quest belongs to one knight



One to Many (1:N)

A movie has multiple scenes

A scene belongs to one movie



Many to Many (M:N)


An actor can be in many movies

A movie can have lots of actors

Note! M:N needs a composite table (next slide)




ERD: Associative Table



To know how much Graham Chapman got paid to play King Arthur in *Monty Python and the Holy Grail*, you need both the **movie** and the **actor**. Neither alone is enough: King Arthur has also been played by Sean Connery (*First Knight*) and Clive Owen (*King Arthur*), and Chapman's pay was probably different when he played Brian in *Life of Brian*.

ERD: Minimum / Maximum Cardinality

The inner marks are minimum (0 or 1)
and the outer marks are maximum (1 or many)



A could have 1 B or 1 B

B could have 0 A or 1 A

A could have 0 B or many B

B could have 1 A or many A

A could have 0 B or 1 B

B could have 0 A or many A

A could have 1 B or many B

B could have 1 A or 1 A

Think: a knight could have 0 horses (coconuts!) or multiple.



go to gaskination.com/sql

SQL: Clauses

Always written in this order. Only SELECT and FROM are required.

- 1 **SELECT** -- which attributes to show (* = all, DISTINCT = no duplicate rows)
- 2 **FROM** -- the table to pull from (tableA)
- 3 **JOIN** -- tableB ON tableA.key = tableB.key [see Join slides](#)
- 4 **WHERE** -- keep only rows that pass a filter [see Where slides](#)
- 5 **AND/OR** -- add more filters (only write WHERE once)
- 6 **GROUP BY** -- with aggregates: list every SELECT attribute that isn't aggregated
- 7 **HAVING** -- like WHERE, but filters groups
- 8 **ORDER BY** -- sort by an attribute: ASC (default, low to high) or DESC
- 9 **LIMIT** -- only show the first N rows (e.g. LIMIT 10)

```
-- aggregates turn many rows into one value
-- function(attribute) AS new_name
SELECT avg(imdb_score) AS avg_score
-- examples: count(), sum(), avg(), min(), max()

-- you can also do math with attributes (+ - * /)
SELECT imdb_score / duration AS score_per_min
```

Structured
Query
Language



SQL: Where (1/2)

Text

in quotes

name = "James"
→ exactly "James"

name != "James"
name <> "James"
→ anything but "James"

title LIKE "%Mont%"
→ finds both "Monty" and "Monte"

% = any number of characters
_ = exactly one character

name IN ("James", "Gaskin", "Reese")
→ exact match for any of these

Blank

any data type

movie_id IS NULL
→ blank / missing

movie_id IS NOT NULL
→ has data



SQL: Where (2/2)

Numbers

no quotes

`imdb_score > 8`

`imdb_score < 8`

→ greater than / less than

`duration BETWEEN 90 AND 120`

→ 90 to 120 minutes (includes both)

`imdb_score >= 8`

`imdb_score <= 8`

→ ... or equal to

Booleans

no quotes

`owns_copy = TRUE`

→ people who own the movie

`owns_copy = FALSE`

→ everyone else

Dates

in quotes:

"YYYY-MM-DD"

`release_date > "1980-01-01"`

→ released after 1980

`birth_date < "2000-01-01"`

→ born before 2000

`release_date BETWEEN "1970-01-01" AND "1979-12-31"`

→ released in the 1970s



SQL: Join (1/2)

JOIN *combines two tables, keeping rows that match in both*

```
SELECT survey_responders.name, movie_info.title
FROM survey_responders
JOIN movie_info
  ON survey_responders.movie_id = movie_info.movie_id
```

ON says which columns have to match. Each survey_responders row is paired with the movie_info row that has the same movie_id.

survey_responders

name	movie_id
James	1
Gaskin	2
Reese	4

movie_info

movie_id	title
1	Monty Python...
2	Count of Mon...
3	Princess Bri...



result

name	title
James	Monty Python...
Gaskin	Count of Mon...

Reese's movie (4) isn't in movie_info, and no one picked Princess Bride (3), so both are left out.



SQL: Join (2/2)

A

responder_id	name	movie_id
1	James	1
2	Gaskin	2
3	Reese	4


B

movie_id	title
1	Monty Python...
2	Count of Mon...
3	Princess Bri...

```
SELECT name, title
FROM A
      JOIN B
      ON A.movie_id = B.movie_id
```

INNER JOIN


only matches (same as just JOIN)



name	title
James	Monty Python and the Holy G...
Gaskin	Count of Monte Cristo

LEFT JOIN


all of A + matches from B



name	title
James	Monty Python and the Holy G...
Gaskin	Count of Monte Cristo
Reese	NULL

RIGHT JOIN


all of B + matches from A



name	title
James	Monty Python and the Holy G...
Gaskin	Count of Monte Cristo
NULL	Princess Bride

OUTER JOIN

everything from both



name	title
James	Monty Python and the Holy G...
Gaskin	Count of Monte Cristo
Reese	NULL
NULL	Princess Bride



SQL: Example


Question: *For well-rated (7+) movies with more than one fan: how many years after each movie came out were its fans born, on average?*

```
SELECT title,  
       count(*) AS fans,  
       avg(birth_date - release_date) AS avg_years_between  
FROM survey_responders  
JOIN movie_info ON survey_responders.movie_id = movie_info.movie_id  
WHERE imdb_score >= 7  
      AND birth_date IS NOT NULL  
GROUP BY title  
HAVING count(*) > 1  
ORDER BY avg_years_between DESC  
LIMIT 5
```





Flow Charts



The shapes



you can only have **ONE** start
but you **CAN** have multiple
ends




decisions are the **ONLY**
thing that can have more
than one arrow pointing **OUT**
of them



connectors are the **ONLY**
thing that can have more
than one arrow pointing
INTO them

Example: the Bridge of Death



You only see and hear the **input/output** steps;
the **process** happens in the Bridgekeeper's head.



VBA: Basics

Option Explicit 'This makes it so that you can only use variables you've declared (VERY RECOMMENDED)

```
Sub thisIsMySubName()
```

```
'BASICS!
```

```
'Generally you will first refer to an object type (like a Sheet)
```

```
'and then tell it what you want to do (like delete or add or copy, etc):
```

```
' Sheets and Worksheets work the same for normal sheets
```

```
Sheets("MySheet").Delete
```

```
Sheets.Add.name = "MySheet"
```

```
Worksheets("MySheet").Activate
```

```
' Range and Cells are SIMILAR but different: Range("E7") = Cells(7, 5)
```

```
Range("A1").Activate
```

```
ActiveCell.Value = "We want... a shrubbery!"
```

```
Range("A1:D3").Copy
```

```
Range("E5").PasteSpecial
```

```
' Columns and Rows are what they sound like
```

```
Columns("B:D").Delete
```

Visual
Basic for
Applications



VBA: Navigation and Misc.

'NAVIGATION!

```
' Jump to the edge of the data (like Ctrl + arrow key)
ActiveCell.End(xlDown).Select
ActiveCell.End(xlToLeft).Select

' Move (rows, columns) based on a cell or range
ActiveCell.Offset(1, 2).Value = "NewSpot"
Range("A1").Offset(3, 4).Value = "NewSpot" 'The cell that now says "NewSpot" is E4
```

' MISCELLANEOUS!

```
' Bolding
Range("A1").Font.Bold = True

' Autofitting columns
Columns.AutoFit 'all columns
Columns("A:C").AutoFit 'specific columns

' Currency format
Range("A1").Style = "Currency"

' Bottom border
Range("A1").Borders(xlEdgeBottom).LineStyle = xlContinuous

' Text splicing
Dim knight As String, first_initial As String
knight = "Robin"
first_initial = Left(knight, 1) "R" (the first 1 character)
```



VBA: Variables

```
'DECLARE VARIABLES!
Dim i As Integer      'a whole number
Dim j As Double       'a number with a decimal
Dim k As String       'a line of text
Dim l As Boolean      'true or false
Dim m As Worksheet

i = 5
j = 1.2345
k = "Tis but a scratch!"
l = True
Set m = Sheets("Sheet1") 'objects (sheets, workbooks, ranges) use Set instead of =
```

```
'USER INTERFACE!

'Tell the user something
MsgBox "Halt! Who would cross the Bridge of Death?"

'Ask for an input
Dim username As String
username = InputBox("What is your name?")
```

```
' COMBINING STRINGS

Dim myOutput As String
Dim myName As String
myName = "James"

' Combine strings with ampersands (&) -- don't forget spaces
myOutput = "My name is " & myName & " and I seek the Grail!"
```



'CONDITIONALS!

VBA: Conditionals

```
' If Statements
If i < 0 Then
    ' your code here
ElseIf i < 5 Then
    ' your code here
ElseIf i < 10 Then
    ' your code here
Else
    ' your code here
End If
```

```
'Case Statements (assume fruit, color, imdb_score, verdict are declared)
Select Case fruit
    Case "apple", "strawberry"
        Color = "red"
    Case "coconut"
        Color = "brown"
    Case Else
        Color = "unknown"
End Select
```

```
'Another Case Statement
Select Case imdb_score
    Case Is >= 8
        verdict = "must watch (like Monty Python)"
    Case 6 To 8 'an 8 already matched above: first match wins
        verdict = "pretty good"
    Case Is < 6
        verdict = "I'm probably skipping this one"
End Select
```



'LOOPS!

VBA: Loops

```
'For Loop (6 times: 0 to 5)
For i = 0 To 5
    ' your code here
Next i

'For Each Loop
Dim x As Range, lastrow As Long
lastrow = Cells(Rows.Count, "A").End(xlUp).Row 'last filled row in A
For Each x In Range("A2", Cells(lastrow, "A"))
    ' your code here
Next

'For Each Loop 2
Dim myRange As Range
Set myRange = Range("A1:E5")
For Each x In myRange
    ' your code here
Next

'Do While Loop
Do While i < 5 'condition does NOT have to be numbers
    ' your code here
    i = i + 1 'change something, or it loops forever
Loop

' Do Until Loop
Do Until i = 10 'condition does NOT have to be numbers
    ' your code here
    i = i + 1
Loop

End Sub
```



VBA: Functions

```
Function knightTitle(name As String, isBrave As Boolean) As String

    ' a Function RETURNS a value you can use in a cell (a Sub just DOES things)
    ' the INPUTS go in the parentheses, each with a type
    ' the OUTPUT's type goes at the end (As String)
    ' so the function declaration works like Dims you get for free:
    '     Dim knightTitle As String
    '     Dim name As String
    '     Dim isBrave As Boolean

    ' use the inputs to decide the output...
    If isBrave Then
        knightTitle = "Sir " & name & " the Brave"
    Else
        knightTitle = "Sir " & name & " the Not-Quite-So-Brave"
    End If
    ' ...and return it by setting the FUNCTION'S NAME equal to it

End Function

' to use it in a cell:
' =knightTitle("Robin", FALSE)    gives    Sir Robin the Not-Quite-So-Brave
```



Statistics

TEST & USE CASE


OUTPUT

HOW TO READ IT

Correlation

numeric – numeric
(Pearson r coefficient)

→ r



strength = distance from 0; sign = direction

Regression

numeric – multi. numeric

→ R^2



70% of the variance in y
is explained by the x 's

usually 0.05

ANOVA

numeric – mult. categorical

T-test

numeric – 2 pair categorical

→ p



reject the null fail to reject the null
significant **not significant**

*p works like a percentage:
0.05 = 5% to see this or more extreme*

Null Hypothesis

H_0 : No x 's are
significant

Alt Hypothesis

H_A : At least one x is
significant

Scientific Notation

$aE^b = a \times 10^b$

$aE^3 = a \times 1000$ (big)

$aE^{-3} = a \times 0.001$
(small)

Tableau

“Default” means leave it alone

If the assignment says “default,” you don’t have to change anything. It’s the setting Tableau starts with.

Toolbar buttons worth knowing



Swap rows and columns: flips the x- and y-axis. A sideways chart can tell a clearer story.



Sort ascending: smallest to largest



Sort descending: largest to smallest




Solver

Two important Excel formulas:

=sum(A1:A5) → $A1 + A2 + A3 + A4 + A5$

=sumproduct(A1:A5, B11:B15) → $A1*B11 + A2*B12 + \dots + A5*B15$
the two ranges should be the same size and shape


Constraints:



The 'Add Constraint' dialog box in Excel. It has a title bar 'Add Constraint' with a close button. Inside, there are two input fields: 'Cell Reference:' containing 'changing number' and 'Constraint:' containing 'constant number'. Between them is a dropdown menu showing '<=' with a small arrow icon. Below the input fields are three buttons: 'OK', 'Add', and 'Cancel'.

If integer isn't working:

Solver > Options > uncheck this box:



The 'Solving with Integer Constraints' section of the Solver Options dialog. It contains a checkbox labeled 'Ignore Integer Constraints' which is currently unchecked. Below it is a label 'Integer Optimality (%)' followed by a text box containing the number '1'.



HTML: Setup

In an html file inside VS Code,
type an exclamation point and enter to automatically generate:

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Document</title>
</head>
<body>

</body>
</html>
```

Go here for free bootstrap themes:
startbootstrap.com/themes/portfolio-resume

HyperText
Markup
Language



HTML: Tags

```
<!-- This is a comment -->
<h1>The Holy Grail</h1>
<h2>The Knights</h2>
<h3>Sir Robin</h3>

<p>Bravely ran away.</p>

<!-- Line Break -->
<br>
```

```
<!-- Unordered List (Bullets) -->
<ul>
  <li>Sir Lancelot</li>
  <li>Sir Galahad</li>
  <li>Sir Robin</li>
</ul>

<!-- Change <ul> to <ol>
for an ordered list (Numbers) -->
```

Every tag follows this pattern:

<tag>	← start tag
stuff	← what the tag applies to
</tag>	← end tag: same name, plus a /

The start and end tags act like parentheses.

(a few, like
, have no end tag)



HTML: Anchors

```
<!-- Hyperlinks -->
```

```
<a href="https://www.google.com">Visit Google</a>
```

```
<!-- Folder References -->
```

```
<a href="otherpage.html">Visit Other Page</a>
```

```
<a href="subfolder/page.html">Visit Subfolder Page</a>
```

```
<a href="../anotherpage.html">Visit Another Page</a> ← ../ goes up one folder
```

```
<!-- On-page Anchors -->
```

```
<h1 id="top">This is the main heading</h1>
```

```
<a href="#top">Jump to the top</a> ← # + the id jumps to it on the same page
```

HTML: Images

```
<!-- Images -->



```

Notice: images do NOT have an end tag `</img>`
(neither do line breaks `</br>`)



HTML: Divisions

Divs don't inherently do anything: they're invisible boxes you put content into so that you can isolate it for positioning and CSS styling using classes.

HTML:

```
<div class="square-image">
  
</div>
```

CSS:

```
.square-image {
  width: 200px;
  height: 200px;
}
```




For more, see:

[CSS: Selectors/Properties/Values](#)

HTML: Embedding

Embeds sometimes don't show up until your site is live

YouTube


- 1 Under the video, click **Share** 
- 2 Click **Embed** 
- 3 Click **Copy** 
- 4 Paste it into your HTML

Tableau

- 1 Go to public.tableau.com/app/discover
- 2 Search for a relevant viz
- 3 Click the share icon 
- 4 Click **Copy Embed Code** 
- 5 Paste it into your HTML



HTML: Best Practices



Use folders!

Give each type of file its own folder: `css/`, `html/`, `js/`, and `assets/` (with `img/`, `fonts/`, `icons/` inside).
`index.html` stays at the top level. It's your homepage, so it's the first page the site loads.

Never use spaces in file or folder names

Use a dash or underscore instead:


✓ `about-me.html` ✗ `about me.html`
✓ `example_project/` ✗ `example project/`

Format your code

Fixes indentation and long lines.

Right click → **Format Document**

shortcut: `Shift+Alt+F`





HTML: Uploading to GitHub

A. Create the repository

1 Go to github.com and sign in (or make a free account)

2 Click **New**



3 Type a **Repository name** (no spaces!)

Repository name *

example_project

✔ example_project is available.

4 Leave it **Public** and turn **Add README** on

Add README

READMEs can be used as longer descriptions. [About READMEs](#)


On ☒

5 Click **Create repository** at the bottom



B. Upload your website


6 On your new repository's page, click **Add file** → **Upload files**



Open your project folder and drag everything *inside* it (index.html, css/, ...)

7 **Upload the CONTENTS of your project, not the folder itself**

8 Click **Commit changes** ("commit" = save)



Next: turn it into a live website → [Going Live](#)




HTML: Going Live

On your repository's page (from the last slide):

1

Click the **Settings** tab at the top



Settings

2

In the left sidebar, click **Pages**



Codespaces



Pages

3

Under **Branch**, change None to main, then click **Save**



main



/(root)

Save

4

Wait a couple of minutes, then **refresh** the page. Your website's link will appear at the top:

Your site is live at https://jimna-h.github.io/example_project/

Last **deployed** by jimna-h 1 minute ago

Visit site

Unpublish site



CSS: Basics

1. Connect it to your HTML

```
<head>
  <link rel="stylesheet" href="css/style.css">
</head>
```

Goes inside the `<head>` of every page.
`href` is the path to your `.css` file.

2. Every rule looks like this

```
selector {
  property: value;
  property2: value2;
}
```

property = what to change, **value** = what to change it to. That's all CSS is! (see next slide)

3. It's cascading: the later rule wins

```
p {
  color: blue;
}
p {
  color: red;
}
```

If you paint a door blue and then re-paint it red, it will be red instead of blue. CSS works the same way, but with everything not just colors.

Cascading
Style
Sheets



CSS: Selectors / Properties / Values

Built-in selectors

Use a tag name (body, h1, p, a, img, ...) to style every one of those tags.

```
body { ← every <body>
  background-color: #f0f0f0;
  font-family: Arial, sans-serif;
  margin: 0;
  padding: 20px;
}
```

Class (custom) selectors

Make your own: a **period** + any name.
Styles only tags with that class.

```
.highlight {
  background-color: yellow;
  font-weight: bold;
}
```

Apply it in your HTML (no period):

```
<p class="highlight">Ni!</p>
```

There are A LOT of selectors and properties. Google and AI are your friend for finding exactly what you want!



jimna-h.github.io/james_super_cool_is_201_cheatsheet



Suggestions? Reach out to me at jbruce1@byu.edu



IS 201 TA Lab