

SG-Pro Digital Hydrometer / Density Meter



SG-Pro Battery Digital Hydrometer

Product Overview

The SG-Pro Digital Hydrometer/Density Meter offers 99.999% accurate, temperaturecompensated specific gravity, density, and density-related values. Select from multiple units of measure to suit your measurement needs or create custom user-defined requirements. Results include sample identification, measurement unit, temperature correction coefficient, instrument identification and date & time. Results can be downloaded to a printer or PC easily. Reliable results appear in just 3 seconds - just immerse the sampling tube, press the button to automatically draw in the sample, and read the final result. Trend results with included management software. The SG-Pro is commonly used for battery testing (lead-acid & Ni-cad), alcohol and food testing, petroleum testing, and other custom density tests.

Advantages

- Accurate to 99.999%
- User-friendly compact, lightweight, and allows for one-hand measurement
- Automatic sampling pump for drawing in and releasing samples
- Large color display screen with back-light
- Robust & rugged, comes with protective carrying case, sustains tough field environments with a sealed housing
- Wireless communication via Bluetooth or USB data interface for data exchange with a PC and data export to a printer
- Storage of up to 1,100 results including sample ID, measurement unit, temperature correction coefficient, instrument identification, date and time

Technical Specifications		
Measurement Range	Density: 0.000 – 3.000 g/cm3 Sample Temperature: 01 – 40 °C (321 – 104 °F) Viscosity: 0 – 2,000 mPa	
Accuracy	Density: 0.001 g/cm3 Temperature: ±0.2 °C (±0.4 °F)	
Resolution	0.001 g/cm3	
Minimum Sample Volume	2 mL	
Communication	Bluetooth, USB-A, USB-C, RFID	
Display	Backlit 2.4" color screen	
Internal Storage	1,100 results	
Operating Environment	-10 – 50 °C (14 – 122 °F)	
Power Requirements	(1) rechargeable Lithium ion 2400 mAh battery	
Dimensions	56 x 288 x 62 mm (2.2 x 11.3 x .4 in)	
Weight	355 g (2.7 oz)	
Sample Tube Dimensions	190 mm / 7.5 in. or 600 mm / 23.6 in. (optional)	
*/1) Cample must not freeze in the measurin	(1) Sample must not freeze in the measuring Cell	

^{*(1)} Sample must not freeze in the measuring Cell



Kit Includes

- SG-Pro with Protective Cover
- Sample Tube (7.5" x 1/8")
- SG-Pro Management Software
- Carrying Case
- User Manual

Ordering Information

Model #	Description
SG-Pro	Digital Hydrometer, Data-Logging, Range: 0.0000 – 3.0000