



AC-LB-Rack Mount Server Load Banks



AC-LB-Rack Server Load Bank

Product Overview

The LB Rack Mount Server load banks provide accurate loading solutions for critical data center power and heat load testing applications. The units are designed to be accurate, reliable and easy to use for data center or test personnel. Available in multiple configurations from 4-20 kW with single or dual channel versions available rack mount configurations. Other configurations are also available. Contact Eagle Eye for more information.

Features

- Standard 19" rack 7U and 9U designs
- Designed for continuous operation
- Multiple load steps
- Simple and easy to use operator controls
- Normal and fault condition indicators
- Audible and visual alarms for over-temperature condition
- Fuse protection
- Overtemperature protection

Technical Specifications

| | |
|-------------------------|--------------------------------------|
| Voltage Versions | 120, 208, 240 VAC versions available |
| kW Models | 4 - 20 kW |
| Frequency | 60 Hz |
| Resolution | 1-2 kW |
| Configuration | Three phase 4 wire wye |
| Digital Display | LCD multiple function display meter |
| Cooling | Forced air cooling |
| Environmental | Indoor operation |
| Control | Manual switch control |



Ordering Information

| Model No. | Size | Description | Voltage | Configuration | | | Load Steps | Channels |
|-------------|--------|-------------|-----------------|---------------|-------|------------|-----------------|----------|
| AC-208-6kW | 19" 7U | 6 kW | 208 | Three | 60 Hz | 4 wire Wye | 1, 2, & 3 kW | 1 |
| AC-208-12kW | 19" 7U | 12 kW | 208 | Three | 60 Hz | 4 wire Wye | 1, 2, 3, & 6 kW | 1 |
| AC-208-8kW | 19" 7U | 8 kW | 208 | Three | 60 Hz | 4 wire Wye | 2, 2, & 2, 2 kW | 2 |
| AC-208-20kW | 19" 9U | 20 kW | 120/208/230/240 | Three | 60 Hz | 4 wire Wye | 1, 2, 3 kW | 2 |