

Copyright © 2015 by The Learning House.

All rights reserved. No part of these materials may be reproduced, distributed, or transmitted in any form or by any means, including photocopying, recording, or other electronic or mechanical methods, without the prior written permission of The Learning House. For permission requests, write to The Learning House, addressed “Attention: Permissions Coordinator,” at the address below.

The Learning House  
427 S 4<sup>th</sup> Street #300  
Louisville KY 40202

# LINQ (Language Integrated Query)

.NET Cohort

Coding Bootcamp

# Lesson Goals

- We will learn why LINQ is awesome
- We will learn query syntax
- Also, we will show how delegates and lambdas can make your LINQ statements more concise

# What is LINQ?

- LINQ stands for “Language Integrated Query.”
- It is an extension of the .NET framework that allows you to query collections (arrays, lists, etc.) in a manner similar to SQL.
- You can also use LINQ to query databases, XML Documents, and just about any other set that implements it.
- You can use Query syntax or Method syntax.

# LINQ and IEnumerable

- LINQ queries always return an enumeration of results (in the case of no matches, it will return an empty set).

```
int[] ints = {10, 20, 30, 40, 50, 60, 70, 80, 90, 100};
```

```
IEnumerable<int> lownumbers = from i in ints  
                             where i < 50  
                             select i;
```

```
foreach(int i in lownumbers)  
    Console.WriteLine(i);
```

```
Console.ReadLine();
```

# This is Where var Comes in

- The *var* keyword is commonly used in LINQ, especially when we return anonymous objects.

```
int[] ints = {10, 20, 30, 40, 50, 60, 70, 80, 90, 100};

var lownumbers = from i in ints
                 where i < 50
                 select i;

foreach(int i in lownumbers)
    Console.WriteLine(i);

Console.ReadLine();
```

# Anonymous Types


- Sometimes in LINQ we want to create an object “on the fly” that contains a subset of properties or combinations thereof.
- In this case, we must use the var keyword because a type doesn’t exist until the statement is executed.

LINQ Anonymous Types

**DEMO**



# LINQ Query Structure



# The *from* clause

- We use the *from* clause to specify which collection we will use in the query.
- It also defines the variable alias that represents one item in the collection.

*from item in items*

```
int[] ints = {5, 15, 7, 20};
```

```
var result = from i in ints where i > 10 select i;
```

# The *join* clause

- The *join* clause in LINQ takes two collections and creates a new collection where each element has members from both original collections.

*from type in types join type2 in types2  
on type.property equals type2.property*

LINQ Joins  
**DEMO**



# The *where* clause

- The *where* clause in LINQ works much like the *where* clause in SQL. We can chain together boolean expressions to filter the list.

```
var results = from student in students
               join course in courses on student.StudentID equals course.StudentID
               where student.StudentID == 1
               select new {course, student };
```

# The *orderby* Clause

- The *orderby* clause can be ascending or descending.

```
var results = from student in students
               join course in courses
               on student.StudentID equals course.StudentID
               orderby course.CourseName
               select new {course, student };
```

# The *group* clause

- The *group* clause takes a field and creates a wrapper object for each unique field, called a *key*.
- You can enumerate the keys to list out the members of each group.

LINQ Group

**DEMO**





# Standard Operators

- *Count*
- *Select*
- *SelectMany*
- *Take*
- *Skip*
- *TakeWhile*
- *SkipWhile*
- *Join*
- *GroupJoin*
- *Concat*
- *OrderBy*
- *Reverse*
- *GroupBy*
- *Distinct*
- *Union*
- *Intersect*

# More Operators

- *Except*
- *AsEnumerable*
- *ToArray*
- *ToList*
- *ToDictionary*
- *ToLookup*
- *OfType*
- *Cast*
- *SequenceEqual*
- *First*
- *FirstOrDefault*
- *Last*
- *LastOrDefault*
- *Single*
- *SingleOrDefault*
- *ElementAt*

# Even More!

- *ElementAtOrDefault*
- *DefaultIfEmpty*
- *Range*
- *Repeat*
- *Empty*
- *Any*
- *All*
- *Contains*
- *Count*
- *LongCount*
- *Sum*
- *Min*
- *Max*
- *Average*
- *Aggregate*

# Needless to Say...

There are way too many to go over without turning your brains into mush.

Find all the examples on MSDN:

<http://msdn.microsoft.com/en-us/library/bb397896.aspx>

Use your intellisense!

# Remember Delegates?

- We can use delegates and lambda expressions as parameters to standard operators:

```
int[] ints = {5, 15, 7, 20};  
var result = ints.Where(i => i > 10);
```

```
foreach(var i in result)  
    Console.WriteLine(i);
```

# Using Func<>

- *Func* is a built-in generic delegate. Let's say we want to count only odd numbers:

```
static bool IsOdd(int x)
{
    return x % 2 == 1;
}

static void Main()
{
    int[] ints = {5, 15, 7, 20};

    Func<int, bool> myDelegate = IsOdd;

    var result = ints.Count(myDelegate);

    Console.WriteLine("There are {0} odd numbers", result);

    Console.ReadLine();
}
```

# Conclusion on LINQ

- LINQ is everywhere. It is the de facto method for filtering data in C# these days.
  - Just remember that with every abstraction, there is a performance cost. Don't use LINQ to stuff every round peg into a square hole.
  - Databases are optimized to perform sorting and filtering functions. A good architect will determine whether to do filtering and sorting on the client via LINQ or on the server via SQL.