



全

元寶精密沖床、剪床

Jin Cheng Co., Ltd

生產線的精英，您最佳的選擇

Pneumatic Wheel Press

氣壓皮帶式精密沖床系列

CAWS系列

CAWS SERIES (20~30Tons)



全昌有限公司

彰化市彰鹿路168巷1-1號

Tel: 886-4-752-6747

Fax: 886-4-761-4325

JIN CHENG CO., LTD.

No.1-1, Lane 168, Chang Lu Rd., Chang Hua, Taiwan 500

[Http://www.jincheng.com.tw](http://www.jincheng.com.tw)

E-mail: presses@jincheng.com.tw



氣壓皮帶式精密沖床系列
Pneumatic wheel press

本機特色:



- 沖床機身採用鋼板焊接製造而成,鋼性良好,不易變形;並經內應力消除處理,於操作運轉中震動極小
- 滑塊以六面寬長型設計(60噸以上),導軌採合金銅為材質,耐磨性高並可增加沖床的精密度
- 沖床潤滑採集中給油方式,確保全機的潤滑度
- 零組件規格化生產
- 零沖床附有卡模解脫裝置,保護沖床模具安全
- 適用於各式沖壓.伸抽.押花.折彎等作業;生產穩定,生產品質高

Character:

- All steel welded structure, balance design & reinforced for greater strength rigidity body, minimum vibration for smoother operation.
- Six-face wide slide (60 tons and upper the capacity); long guide rail makes by phosphor bronze which can excellent resistance, reinforce the precision and accurate slide movement. It's not only improving work efficiency with excellent production quality but also prolonging die life.
- Centralized lubrication is adopted which can lubricate surely and provide longer service & less abrasion.
- All components are produced by standard specification.
- Stuck on bottom release device to protect the safety of presses & molds.
- Suitable for all kinds of producing. Dependably!



規格 Specifications :

機 型 型 式 Model No	CAWS-20	CAWSH-25	CAWSH-30
			
加 壓 能 力 Capacity tons	20	25	30
滑 塊 孔 徑 Diameter of Ram Hole inch	ø1½	ø2	ø2
標 準 行 程 Standard per Stroke mm	60	60	60
每 分 鐘 行 程 數 Stroke per minute S. P. M.	150	150~250	150~250
模 高 Die Height (Ram to Table) mm	260	250	250
滑 塊 調 整 量 Ram. Adjustment mm	70	50	50
滑 塊 面 積 Ram. Area (L. R x F. B.) mm	240*320	300*420	300*420
台 盤 面 積 Table Area (L. R x F. B.) mm	300*600	360*600	420*700
副 盤 面 積 (L. R x F. B.) Auxiliary table Area mm	300*600	360*600	420*700
附 盤 厚 度 Thickness of Auxiliary table mm	60	65	65
毛 重 (約) G. W. (approx) Kgs	1700	2500	3000
主 馬 達 Main Motor HP*P	5*6	VS 5*4	VS 7.5*4