```
silde6
Tuesday, June 22, 2021
                                                   5:45 PM
TutorialSli
       de6
         STATS5099: Data Mining
         Neural networks
         Xiaochen Yang
         xiaochen.yang@glasgow.ac.uk
    University
of Glasgow
                                                                         This week's content
             artificial neuron
             activation function
              feedforward neural networks
             ■ gradient descent, backpropagation
    University
of Glasgow
                                                                                  Artificial neuron
         Artificial neuron, aka perceptron, is the basic unit of a neural
             network.
          (x_1)
                                                 activation
                              weighted
                                                 function
                                Sum
                                                                       \hat{\mathbf{y}} = \phi(\mathbf{w}_0 + \sum \mathbf{w}_i \mathbf{x}_i)
                                                                                                                  3/16
    University
of Glasgow
                                                                                  Artificial neuron
         Artificial neuron, aka perceptron, is the basic unit of a neural
                 biased term
                                                 activation
                                                 function
                                                                       \hat{\mathbf{y}} = \phi(\mathbf{w}_0 + \sum \mathbf{w}_i \mathbf{x}_i)
           (x_2)
         ■ An artificial neuron consists of input values, weights and a bias,
             a weighted sum and activation function.
                                                                                                                  3/16
                                                                          Activation functions
             ■ The purpose of activation functions is to introduce
                 non-linearities into the network.
                                                                                      step
                                 identity
                                                              1.00
              5.0
                                                              0.75
                                                              0.50
              0.0
                                                              0.25
            -2.5
                                                              0.00
            -5.0
                             \phi(t) = t
                                                                                 \int 0 \quad \text{if } t < 0
         Image source: Apicella, Andrea, et al. "A survey on modern trainable activation functions."
         Neural Networks (2021).
    University
of Glasgow
                                                                          Activation functions
             ■ The purpose of activation functions is to introduce
                 non-linearities into the network.
                                                                                    ReLU
                                sigmoid
           1.00
           0.75
           0.25
           0.00
                                                                       -10
                         \phi(t) = \frac{1}{1+e^{-t}}
                                                                          \phi(t) = \max(0, t)
         softmax: generalisation of sigmoid for multi-class classification
                                              p_i(y_i) = rac{e^{y_i}}{\sum_j e^{y_j}}
    University
of Glasgow
                                     Two special cases of neural networks
              A neural network with no hidden layer and the linear
                 activation function is simply a linear regression model.
             A neural network with no hidden layer and the
                 logistic/sigmoid activation function is a logistic regression
                 model.
    University
of Glasgow
                                                        Neural network construction
                                                                     Single-layer perceptron
             Multi-output perceptron
          Image source: https://yogayu.github.io/DeepLearningCourse/03/MultilayerPerceptron.html
    University
of Glasgow
                                                        Neural network construction
                                                                                          each layer use save activate function
                                          Multi-layer perceptron
                                                                                             Sismod
               Input Layer
                                                                                          Output Layer
         ■ Multi-layer perceptron: a feedforward neural network with
             multiple fully-connected layers and at least some nonlinear
             activation function
         https://machinelearninggeek.com/multi-layer-perceptron-neural-network-using-python/
   University
of Glasgow
                                         Fitting feedforward neural networks
         Empirical loss: total cost incurred from incorrect predictions (how well your network performs) \underline{R(\mathbf{w})} = \frac{1}{n} \sum_{i=1}^{n} L(y_i, \hat{y}_i) = \frac{1}{n} \sum_{i=1}^{n} L(y_i, f(\mathbf{x}_i, \underline{\mathbf{w}}))
         Objective:
         ■ Gradient descent:
                II start with a random guess at the weights
                2 compute gradient, \frac{\partial R(w)}{\partial w} the support of the support o
                repeat steps 2-3 until reaching stopping criteria
    University
of Glasgow
                              Fitting feedforward neural networks: gradient descent
                                                       one of the local optimal, can't evance the best optimal
         Image source: MIT 6.S191. Introduction to Deep Learning
                            Fitting (feedforward) neural networks: backpropagation
             Feed loss backwards to tune the model parameters
                 (weights and biases)
             ■ Compute gradients using chain rule:
                                      hidden
         Image source: MIT 6.S191. Introduction to Deep Learning
    University
of Glasgow
                            Fitting (feedforward) neural networks: backpropagation
             ■ Feed loss backwards to tune the model parameters
                 (weights and biases)
             ■ Compute gradients using chain rule:
         Image source: MIT 6.S191. Introduction to Deep Learning
    University
of Glasgow
                                                                           Training in practice
             ■ Gradient descent algorithm may get "stuck" in local
         Image source: Li, Hao, et al. "Visualizing the loss landscape of neural nets."
                                                                                                                 10/16
    University
of Glasgow
                               Training in practice: random initialisation
             Different starting values may lead to different local optima.
             ■ Common practice 1: test multiple starting values
              ■ Common practice 2: Initialise weights to random values
                 near zero; initialise bias to 0
                                                                                                                 11/16
    University
of Glasgow
                                              Training in practice: learning rate
                       Large Learning Rate
                                                                         Small Learning Rate
             Advanced techniques: adaptive learning rate
         Image source: https://saugatbhattarai.com.np/what-is-gradient-descent-in-machine-learning/
                                                                                                                  12/16
    University
of Glasgow
                                    Training in practice: additional considerations
             ■ Stochastic gradient descent dots set be random
             ■ Regularisation awid owth
    University
of Glasgow
                                                                             Pros of deep learning
         ■ Nonlinear activation functions
         ■ Universal Approximation Theorem: neural networks with a
             single hidden layer can be used to approximate any continuous
             function to any desired precision
             Caveat: the layer may be infeasibly large and may fail to learn
             and generalize correctly
         Particularly suitable for complex problems such as image
             classification, natural language processing, and speech
             recognition
                                                                                                                  14/16
    University
of Glasgow
                                                                             Pros of deep learning
                                        Traditional pattern recognition
                                                  Feature
extractor
                                                                  Classification
                                                                  algorithm
                                                   Deep learning
                                                 Deep neural networks 
(convolutional neural networks)
    University
of Glasgow
                                                                    Cons of deep learning
             may not be easily interpreted
             typically require a large amount of data to perform well
             can be computationally expensive to train
```

training a good neural network can be hard

Next week (Week 7) will be a reading week.

Training neural networks in practice
 learning rate, optimizers
 regularisation techniques

No tutorial; drop-in Q&A on Friday 12-1pm.

Next week (Week 7) will be a reading week.

Training neural networks in practice
 learning rate, optimizers
 regularisation techniques

No tutorial; drop-in Q&A on Friday 12-1pm.

lecture material will be provided early next week.

Optional topic 1: convolutional neural networks
Optional topic 2: recurrent neural networks

Additional topics: deep reinforcement learning, etc.

Tutorial in Week 8 will take place on Wednesday 12-1pm. The

Optional topic 1: convolutional neural networks
Optional topic 2: recurrent neural networks

Additional topics: deep reinforcement learning, etc.

Deep learning in R

Revision quizzes

Deep learning in R

Revision quizzes

University of Glasgow

University
of Glasgow

15/16

16/16

Next week's plan

Next week's plan