

GETTING COMPUTER SIMULATIONS INTO THE CLINIC: On Pulmonary Hypertension Detection

L. Mihaela Paun¹, M. Colebank², M. Olufsen², N. Hill¹, D. Husmeier¹

¹School of Mathematics and Statistics at University of Glasgow and ²Department of Mathematics at North Carolina State University
l.paun.1@research.gla.ac.uk

We use computational modelling to improve the diagnosis process for pulmonary hypertension.




1 CONTEXT

“Respiratory diseases in the UK: third cause of death (20% of all deaths yearly)”

“£11 billion: annual economic burden of all lung conditions on NHS UK”

“Pulmonary hypertension: 70% of deaths from pulmonary vascular diseases”

Diagnosed by **invasively** measuring pulmonary pressure with right-heart catheterisation




Aims (UK HEALTHCARE IMPACT*):

- 1) *Use solely **non-invasive** procedures and **computational models** to predict pulmonary blood pressure.
- 2) *Work towards a **clinical** decision system with reliable disease diagnosis in **real time**.
- 3) Develop a robust and computationally fast **statistical inference procedure** to assist mathematical modelling.





Magnetic Resonance Imaging (MRI)




Prohibitive computational costs ... BUT parameter estimation and uncertainty quantification (UQ) are vital because biophysical parameters (e.g. vessel wall stiffness, increased during PH) have **genuine predictive value** for disease prognostication.

2 INNOVATIVE MODEL

Computationally fast state-of-the-art numerical methods to **estimate** unknown parameters from measured data & **predict** invasively-measured blood pressure.




WORKFLOW




- **Match** model predictions to measured data to obtain likely parameter values
- Use **state-of-the-art** Bayesian numerical methods
- Approximate mathematical model to **reduce** computational costs


3 RESULTS AND CONCLUSIONS



- Estimation and UQ of **biophysical parameters** relevant for PH diagnosis



- Successfully **predict** measured data with novel statistical methods




Existing vs proposed method

Method	Efficiency (ESS/no iterations)	Time elapsed
Reference (simulator)	4.5%	12 days
Proposed (emulator)	60%	1 day

- Highly **efficient** novel statistical method
 - Running time highly **reduced**
- ESS: Effective Sample Size

4 FUTURE STEPS

- 1) Incorporate the **venous** side in a more physiologically realistic mathematical model.
- 2) Investigate the effect of **drug** administration (for blood pressure reduction) on the parameter estimation.



5 Acknowledgements

EPSRC Engineering and Physical Sciences Research Council **SofT Mech**

This work is part of the research programme of the Centre for Multiscale Soft Tissue Mechanics with Application to Heart & Cancer (SofT Mech), funded by the Engineering and Physical Sciences Research Council (EPSRC) of the UK, grant EP/N014642/1.

6 References

1. Paun LM, Qureshi MU, Colebank M, et al. MCMC methods for inference in a mathematical model of pulmonary circulation. *Statistica Neerlandica*, 2018 72: 306–338.
2. Rasmussen C, Gaussian Processes to Speed up Hybrid Monte Carlo for Expensive Bayesian Integrals, *Bayesian Statistics*, 2003, 7(7): 651–659.
3. Qureshi M, Coleba M, Paun LM, et al. A computational study of pulmonary haemodynamics in healthy and hypoxic mice, *Biomechanics and Modelling in Mechanobiology*, 2018 18(1): 219–243.