Crossing Cross-Entropy:

The Power of Provably Faithful Interpretability

J. Setpal

October 10, 2024



Outline

1 The Approach

Results & What's Next

What is Cross Entropy?

Cross-Entropy is the *premier* cost function to quantify classification error:

$$H(y,\hat{y}) = -\sum_{c \in C} y_c \log(\hat{y}_c) \tag{1}$$

where y is a one-hot-encoded vector of the target class, & \hat{y} is the model prediction.

What is Cross Entropy?

Cross-Entropy is the *premier* cost function to quantify classification error:

$$H(y,\hat{y}) = -\sum_{c \in C} y_c \log(\hat{y}_c) \tag{1}$$

where y is a one-hot-encoded vector of the target class, & \hat{y} is the model prediction.

Despite being performant, optimization is still *very* non-convex.

What is Cross Entropy?


Cross-Entropy is the *premier* cost function to quantify classification error:


$$H(y,\hat{y}) = -\sum_{c \in C} y_c \log(\hat{y}_c) \tag{1}$$

where y is a one-hot-encoded vector of the target class, & \hat{y} is the model prediction.


Despite being performant, optimization is still very non-convex.

Can we do better?






Interpretability within Machine Learning is the **degree** to which we can understand the **cause** of a decision, and use it to consistently predict the model's prediction.



Interpretability within Machine Learning is the **degree** to which we can understand the **cause** of a decision, and use it to consistently predict the model's prediction.

Traditionally, interpretability & performance is seen as a trade-off.^a



Interpretability within Machine Learning is the **degree** to which we can understand the **cause** of a decision, and use it to consistently predict the model's prediction.

Traditionally, interpretability & performance is seen as a trade-off.^a

Our work demonstrates a deep intersect between these two seemingly orthogonal research foci.

^asd

Outline

1 The Approach

Results & What's Next

HiResCAMs are a provably faithful interpretability technique:

$$\mathcal{A}_{c}^{\mathsf{HiResCAMs}} = \sum_{f=1}^{F} \frac{\partial \hat{y}_{c}}{\partial A_{f}} \odot A_{f} \tag{2}$$

HiResCAMs are a provably faithful interpretability technique:

$$\mathcal{A}_{c}^{\mathsf{HiResCAMs}} = \sum_{f=1}^{F} \frac{\partial \hat{y}_{c}}{\partial A_{f}} \odot A_{f} \tag{2}$$

Provably faithful because:

$$\hat{y}_c = \sum_{d_1=1, d_2=1}^{D_1, D_2} \mathcal{A}_{c, d_1, d_2}^{\mathsf{HiResCAMs}} + b_c \tag{3}$$

HiResCAMs are a provably faithful interpretability technique:

$$\mathcal{A}_{c}^{\mathsf{HiResCAMs}} = \sum_{f=1}^{F} \frac{\partial \hat{y}_{c}}{\partial A_{f}} \odot A_{f} \tag{2}$$

Provably faithful because:

$$\hat{y}_c = \sum_{d_1=1, d_2=1}^{D_1, D_2} \mathcal{A}_{c, d_1, d_2}^{\mathsf{HiResCAMs}} + b_c \tag{3}$$

However, softmax-activated multi-class classification relies on **inter-class logit differences**!!!, while HiResCAMs re-construct *absolute values*.

Therefore, we define **ContrastiveCAMs**:

$$\tilde{\mathcal{A}}_{(c_t,c_{t'})}^{\text{contrastive}} := \left\{ \tilde{\mathcal{A}}_{c_t}^{\mathsf{HiResCAM}} - \tilde{\mathcal{A}}_{c_{t'}}^{\mathsf{HiResCAM}} \right\}_{c_{t'} \in c \setminus c_t}^{|c|-1} \tag{4}$$

This creates a new objective function, equivalent to cross-entropy: 1

$$\max_{\theta} \sum_{d_1, d_2}^{D_1, D_2} \tilde{\mathcal{A}}_{(c, c'), d_1, d_2}^{\text{contrastive}} \ \forall c' \in \mathbb{Z}_+(|c| - 1)$$
 (5)

With one key difference: we've preserved spatial information.

¹with subtle changes to the architecture

The Fault in Our Cross-Entropy

Outline

1 The Approach

Results & What's Next

Results (so far)

What's to Come

Next, we are going $% \left\{ 1,2,\ldots ,n\right\} =0$

Thank you!

Have an awesome rest of your day!

Slides: https://cs.purdue.edu/homes/jsetpal/slides/cont-opt.pdf **Code:** https://dagshub.com/jinensetpal/contrastive-optimization