

# Omnipredictors<sup>1</sup>: One Predictor to Rule Them All

Heavily adapted from P. Gopalan's Talk at IAS

J. Setpal

April 18, 2024



**MACHINE LEARNING  
@ PURDUE**

---

<sup>1</sup>Gopalan, Kalai, Reingold, Sharan, Wieder

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$
3. Objective: Train  $\theta$  s.t.  $f_{\theta}(x) = \hat{y} \approx y$

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$
3. Objective: Train  $\theta$  s.t.  $f_{\theta}(x) = \hat{y} \approx y$

How do we mathematically encode  $\hat{y} \approx y$ ?

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$
3. Objective: Train  $\theta$  s.t.  $f_{\theta}(x) = \hat{y} \approx y$

How do we mathematically encode  $\hat{y} \approx y$ ? A loss (distance) function!

4. Loss function  $L : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ ;  $L(\hat{y}, y) \approx 0$  iff  $\hat{y} \approx y$ ;  $L$  is continuous.

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$
3. Objective: Train  $\theta$  s.t.  $f_{\theta}(x) = \hat{y} \approx y$

How do we mathematically encode  $\hat{y} \approx y$ ? A loss (distance) function!

4. Loss function  $L : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ ;  $L(\hat{y}, y) \approx 0$  iff  $\hat{y} \approx y$ ;  $L$  is continuous.

How can we update our weights to optimize against this loss function?

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$
3. Objective: Train  $\theta$  s.t.  $f_{\theta}(x) = \hat{y} \approx y$

How do we mathematically encode  $\hat{y} \approx y$ ? A loss (distance) function!

4. Loss function  $L : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ ;  $L(\hat{y}, y) \approx 0$  iff  $\hat{y} \approx y$ ;  $L$  is continuous.

How can we update our weights to optimize against this loss function?

5. Gradient Descent!  $\theta = \theta + \alpha \cdot \frac{\partial L}{\partial \theta}$

Iterate (5) until convergence.



# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$
3. Objective: Train  $\theta$  s.t.  $f_{\theta}(x) = \hat{y} \approx y$

How do we mathematically encode  $\hat{y} \approx y$ ? A loss (distance) function!

4. Loss function  $L : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ ;  $L(\hat{y}, y) \approx 0$  iff  $\hat{y} \approx y$ ;  $L$  is continuous.

How can we update our weights to optimize against this loss function?

5. Gradient Descent!  $\theta = \theta + \alpha \cdot \frac{\partial L}{\partial \theta}$

Iterate (5) until convergence.

$L$  is minimized over  $\mathcal{D}$ , not over the real world.

# Supervised Learning Synopsis

We'll start with an *overview* of supervised learning paradigm:

1. Dataset  $\mathcal{D} := \{(x_i, y_i)\}_{i=1}^N$ ;  $N \ll \infty$ ;  $\mathcal{D} \sim$  "Real World"
2. Parameterized model  $f_{\theta} : \mathcal{X} \rightarrow \mathcal{Y}$
3. Objective: Train  $\theta$  s.t.  $f_{\theta}(x) = \hat{y} \approx y$

How do we mathematically encode  $\hat{y} \approx y$ ? A loss (distance) function!

4. Loss function  $L : \mathcal{Y} \times \mathcal{Y} \rightarrow \mathbb{R}$ ;  $L(\hat{y}, y) \approx 0$  iff  $\hat{y} \approx y$ ;  $L$  is continuous.

How can we update our weights to optimize against this loss function?

5. Gradient Descent!  $\theta = \theta + \alpha \cdot \frac{\partial L}{\partial \theta}$

Iterate (5) until convergence.

$L$  is minimized over  $\mathcal{D}$ , not over the real world. This is **empirical risk**:

$$\min_{\theta} \frac{1}{N} \sum_{i=1}^N L(f_{\theta}(x_i), y_i) \quad (1)$$


# Generalization Error

We also split  $\mathcal{D}$  into training, validation, test splits to minimize overfitting.

# Generalization Error

We also split  $\mathcal{D}$  into training, validation, test splits to minimize overfitting.

Usually  $L_{valid} \neq L_{train}$  after training. That's our generalization gap.



# Challenge Statement

**Problem:** Different loss functions typically have divergent geometries.

---

<sup>2</sup>usually, local

# Challenge Statement

**Problem:** Different loss functions typically have divergent geometries.

This means gradient descent obtains a **different<sup>2</sup> optima** for two such functions, despite sharing minima for  $\theta$  s.t.  $\hat{y} \approx y$ .

---

<sup>2</sup>usually, local

# Challenge Statement

**Problem:** Different loss functions typically have divergent geometries.

This means gradient descent obtains a **different<sup>2</sup> optima** for two such functions, despite sharing minima for  $\theta$  s.t.  $\hat{y} \approx y$ .

Let's evaluate this empirically on  $\ell_1$  and  $\ell_2$  losses, which optimize for median and mean respectively:

$$\ell_1 = |y - \hat{y}|, \ell_2 = (y - \hat{y})^2 \quad (2)$$

$$x \sim f(\epsilon \sim \mathcal{U}[0, 1]) := \begin{cases} 0 & \epsilon \leq 0.4 \\ \mathcal{U}[0.8, 1] & \text{otherwise} \end{cases} \quad (3)$$

---

<sup>2</sup>usually, local

# Challenge Statement

**Problem:** Different loss functions typically have divergent geometries.

This means gradient descent obtains a **different<sup>2</sup> optima** for two such functions, despite sharing minima for  $\theta$  s.t.  $\hat{y} \approx y$ .

Let's evaluate this empirically on  $\ell_1$  and  $\ell_2$  losses, which optimize for median and mean respectively:

$$\ell_1 = |y - \hat{y}|, \ell_2 = (y - \hat{y})^2 \quad (2)$$

$$x \sim f(\epsilon \sim \mathcal{U}[0, 1]) := \begin{cases} 0 & \epsilon \leq 0.4 \\ \mathcal{U}[0.8, 1] & \text{otherwise} \end{cases} \quad (3)$$

**Omnipredictors** provides a framework for rigorous guarantees, deriving  $\tilde{p} \approx p^*$ : a predictor that is able to *simultaneously minimize* a family of convex loss functions.

---

<sup>2</sup>usually, local



# Multigroup Fairness

We can split  $\mathcal{D}$  into various *subgroups* based on **shared characteristics**. These can be explicit or implicit (i.e. subgroups we don't know of):

	<b>Group-1</b>	<b>Group-2</b>	<b>Group-3</b>	<b>Group-4</b>
<b>Accuracy</b>	0.9593	0.6249	0.3157	0.2664
<b>Loss</b>	0.0021	0.4102	1.3457	1.7664
<b>Proportion</b>	0.9	0.08	0.0075	0.0025

# Multigroup Fairness

We can split  $\mathcal{D}$  into various *subgroups* based on **shared characteristics**. These can be explicit or implicit (i.e. subgroups we don't know of):

	Group-1	Group-2	Group-3	Group-4
<b>Accuracy</b>	0.9593	0.6249	0.3157	0.2664
<b>Loss</b>	0.0021	0.4102	1.3457	1.7664
<b>Proportion</b>	0.9	0.08	0.0075	0.0025

Empirical Risk is *only* 0.0492, but inference is unreliable for subgroups 2-4.

# Multigroup Fairness


We can split  $\mathcal{D}$  into various *subgroups* based on **shared characteristics**. These can be explicit or implicit (i.e. subgroups we don't know of):

	Group-1	Group-2	Group-3	Group-4
<b>Accuracy</b>	0.9593	0.6249	0.3157	0.2664
<b>Loss</b>	0.0021	0.4102	1.3457	1.7664
<b>Proportion</b>	0.9	0.08	0.0075	0.0025

Empirical Risk is *only* 0.0492, but inference is unreliable for subgroups 2-4.


One notion of fairness stipulates equal risk for every subgroup. However, finding subgroups is hard for high-dimensional data.

# Multiaccuracy & Multigroup Fairness



# Multiaccuracy & Multigroup Fairness

Let  $C$  be the collection of subsets. We probe it further for correlations.




# Multiaccuracy & Multigroup Fairness


Let  $C$  be the collection of subsets. We probe it further for correlations.

$\tilde{p}$  is  $(C, \alpha)$ -multiaccurate if:

$$\max_{c \in C} |\mathbb{E}[c(x)(y - \tilde{p}(x))]| \leq \alpha \quad (4)$$



# Multiaccuracy & Multigroup Fairness



Let  $C$  be the collection of subsets. We probe it further for correlations.


$\tilde{p}$  is  $(C, \alpha)$ -multiaccurate if:

$$\max_{c \in C} |\mathbb{E}[c(x)(y - \tilde{p}(x))]| \leq \alpha \quad (4)$$

$\tilde{p}$  is  $(C, \alpha)$ -multicalibrated if:

$$\max_{c \in C} E[|\mathbb{E}[c(x)(y - \tilde{p}(x))]|] \leq \alpha \quad (5)$$

# Multiaccuracy & Multigroup Fairness



Let  $C$  be the collection of subsets. We probe it further for correlations.

$\tilde{p}$  is  $(C, \alpha)$ -multiaccurate if:

$$\max_{c \in C} |\mathbb{E}[c(x)(y - \tilde{p}(x))]| \leq \alpha \quad (4)$$

$\tilde{p}$  is  $(C, \alpha)$ -multicalibrated if:

$$\max_{c \in C} E[|\mathbb{E}[c(x)(y - \tilde{p}(x))]|] \leq \alpha \quad (5)$$

If we can find correlation with the error, there's some advantage to be gained. We minimize this to train a **weak agnostic learner**.



If we know  $p^*$ , it is easy for us take take the optimal action.

If we know  $p^*$ , it is easy for us take take the optimal action.

For  $y \in \{0, 1\}$ ,  $y \sim \text{Bernoulli}(p^*)$ . We denote optimal action  $t := k_\ell^* \circ p^*$

If we know  $p^*$ , it is easy for us take take the optimal action.

For  $y \in \{0, 1\}$ ,  $y \sim \text{Bernoulli}(p^*)$ . We denote optimal action  $t := k_\ell^* \circ p^*$

This paper connects multigroup fairness with the notion of a weak agnostic learner, to formulate  $(L, C)$ -omnipredictors.

# Omnipredictors

If we know  $p^*$ , it is easy for us take take the optimal action.

For  $y \in \{0, 1\}$ ,  $y \sim \text{Bernoulli}(p^*)$ . We denote optimal action  $t := k_\ell^* \circ p^*$

This paper connects multigroup fairness with the notion of a weak agnostic learner, to formulate  $(L, C)$ -omnipredictors. Specifically, it trains  $g_\theta \approx p^*$ .

If we know  $p^*$ , it is easy for us take take the optimal action.

For  $y \in \{0, 1\}$ ,  $y \sim \text{Bernoulli}(p^*)$ . We denote optimal action  $t := k_\ell^* \circ p^*$

This paper connects multigroup fairness with the notion of a weak agnostic learner, to formulate  $(L, C)$ -omnipredictors. Specifically, it trains  $g_\theta \approx p^*$ .

**Intuitively:** the idea is to *extract the predictive power* of the data.

If we know  $p^*$ , it is easy for us take take the optimal action.

For  $y \in \{0, 1\}$ ,  $y \sim \text{Bernoulli}(p^*)$ . We denote optimal action  $t := k_\ell^* \circ p^*$

This paper connects multigroup fairness with the notion of a weak agnostic learner, to formulate  $(L, C)$ -omnipredictors. Specifically, it trains  $g_\theta \approx p^*$ .

**Intuitively:** the idea is to *extract the predictive power* of the data.

Let  $L_{\text{cvx}}$  be a set of Lipschitz, convex, bounded losses.

If we know  $p^*$ , it is easy for us take the optimal action.

For  $y \in \{0, 1\}$ ,  $y \sim \text{Bernoulli}(p^*)$ . We denote optimal action  $t := k_\ell^* \circ p^*$

This paper connects multigroup fairness with the notion of a weak agnostic learner, to formulate  $(L, C)$ -omnipredictors. Specifically, it trains  $g_\theta \approx p^*$ .

**Intuitively:** the idea is to *extract the predictive power* of the data.

Let  $L_{\text{cvx}}$  be a set of Lipschitz, convex, bounded losses. If  $f_\theta$  is  $C$ -multicalibrated with some error  $\alpha$ , it is an  $(L_{\text{cvx}}, C, \alpha)$ -omnipredictor.

If we know  $p^*$ , it is easy for us take take the optimal action.

For  $y \in \{0, 1\}$ ,  $y \sim \text{Bernoulli}(p^*)$ . We denote optimal action  $t := k_\ell^* \circ p^*$

This paper connects multigroup fairness with the notion of a weak agnostic learner, to formulate  $(L, C)$ -omnipredictors. Specifically, it trains  $g_\theta \approx p^*$ .

**Intuitively:** the idea is to *extract the predictive power* of the data.

Let  $L_{\text{cvx}}$  be a set of Lipschitz, convex, bounded losses. If  $f_\theta$  is  $C$ -multicalibrated with some error  $\alpha$ , it is an  $(L_{\text{cvx}}, C, \alpha)$ -omnipredictor.

Multicalibration implies omniprediction for all convex loss functions.



# Training Agnostic Predictors

We can use this framework to train a predictor s.t. a new model trained just on one loss function performs equivalently to the omnipredictor.

$$C = \{c : \mathcal{X} \rightarrow \mathcal{Y}\} \quad (6)$$

$$w : (0, 1] \rightarrow (0, 1] \text{ s.t. } w(\alpha) \leq \alpha \quad (7)$$

# Training Agnostic Predictors

We can use this framework to train a predictor s.t. a new model trained just on one loss function performs equivalently to the omnipredictor.

$$C = \{c : \mathcal{X} \rightarrow \mathcal{Y}\} \quad (6)$$

$$w : (0, 1] \rightarrow (0, 1] \text{ s.t. } w(\alpha) \leq \alpha \quad (7)$$

We then train with the following objective:

$$\min_{\theta} \mathbf{Cov}_{\mathcal{D}}[c(x), y] \quad (8)$$

Then, with probability  $1 - \delta$  the weak learner returns  $c$  s.t.  
 $\mathbf{Cov}_{\mathcal{D}}[c(x), y] \geq w(\alpha)$ .

# Training Agnostic Predictors

We can use this framework to train a predictor s.t. a new model trained just on one loss function performs equivalently to the omnipredictor.

$$C = \{c : \mathcal{X} \rightarrow \mathcal{Y}\} \quad (6)$$

$$w : (0, 1] \rightarrow (0, 1] \text{ s.t. } w(\alpha) \leq \alpha \quad (7)$$

We then train with the following objective:

$$\min_{\theta} \mathbf{Cov}_{\mathcal{D}}[c(x), y] \quad (8)$$

Then, with probability  $1 - \delta$  the weak learner returns  $c$  s.t.  
 $\mathbf{Cov}_{\mathcal{D}}[c(x), y] \geq w(\alpha)$ .

We use this to compute an  $\alpha$ -multicalibrated partition by a layered branching program that runs in  $\mathcal{O}(\frac{l}{w(\alpha/2)})^{\mathcal{O}(l)}$ .

# Thank you!

Have an awesome rest of your day!

## **Slides:**

<https://cs.purdue.edu/homes/jsetpal/slides/omnipredictors.pdf>