



















unknown entries. After performing tensor decomposition, we can predict the unknown entries by low-rank approximations. (3) User/Item based collaborative filtering [8, 11, 18]. The original user-item matrix is extended by including tag information so that we can apply user/item based collaborative filtering methods.

Besides annotation behaviors, user space, tag space and item space have also been explored. [9] has studied trust networks and proposed a factor analysis approach based on probabilistic matrix factorization. [6] incorporates social network for item recommendation, but fails to improve the performance significantly. [14] links social tags from Flickr into WordNet. [7] introduces item taxonomies into recommender systems.

This paper is mainly inspired by two recent work on graph-based learning [1] and semi-supervised learning [3]. [1] proposes supervised random walks to learn the edge weights for link prediction in homogenous graph. This paper extends [1] with multi-type edges and nodes. [3] has proposed similar idea to learn edge weights and node weights with an inductive learning framework in homogenous graph. Since a recommender should have the ability to predict for future events, our framework is different from [3] in that ours belongs to transductive learning.

## 7. CONCLUSION AND FUTURE WORK

In this paper, we propose an optimization-based graph method for personalized tag recommendation. To alleviate data sparsity, different sources of information are incorporated into the optimization framework. There are some problems unsolved for future work: (1) Reducing the graph size. Since the random walker frequently restarts at  $u$  and  $i$ , nodes that are far away from  $u$  and  $i$  may be cut without influencing the final ranking. (2) Comparing with tensor factorization methods under a suitable experiment setting. (3) More features can be explored to further improve the results, such as the temporal factors.

## 8. ACKNOWLEDGMENTS

This work was supported in part by National Basic Research Program of China (973 Program) under Grant No. 2011CB302206, and National Natural Science Foundation of China under Grant No. 60833003.

## 9. REFERENCES

- [1] L. Backstrom and J. Leskovec. Supervised random walks: predicting and recommending links in social networks. In *WSDM*, pages 635–644, 2011.
- [2] I. Cantador, P. Brusilovsky, and T. Kuflik. Workshop hetrec 2011. *RecSys 2011*. ACM, 2011.
- [3] B. Gao, T.-Y. Liu, W. Wei, T. Wang, and H. Li. Semi-supervised ranking on very large graphs with rich metadata. In *KDD*, pages 96–104, 2011.
- [4] Z. Guan, J. Bu, Q. Mei, C. Chen, and C. Wang. Personalized tag recommendation using graph-based ranking on multi-type interrelated objects. In *SIGIR*, pages 540–547, 2009.
- [5] R. Jäschke, L. B. Marinho, A. Hotho, L. Schmidt-Thieme, and G. Stumme. Tag recommendations in folksonomies. In *PKDD*, pages 506–514, 2007.

- [6] I. Konstas, V. Stathopoulos, and J. M. Jose. On social networks and collaborative recommendation. In *SIGIR*, pages 195–202, 2009.
- [7] H. Liang, Y. Xu, Y. Li, and R. Nayak. Personalized recommender system based on item taxonomy and folksonomy. *CIKM '10*, pages 1641–1644, 2010.
- [8] H. Liang, Y. Xu, Y. Li, R. Nayak, and X. Tao. Connecting users and items with weighted tags for personalized item recommendations. *HT '10*, pages 51–60. ACM, 2010.
- [9] H. Ma, T. C. Zhou, M. R. Lyu, and I. King. Improving recommender systems by incorporating social contextual information. *ACM Trans. Inf. Syst.*, 29:9:1–9:23, Apr. 2011.
- [10] D. Milne. *An Open-Source Toolkit for Mining Wikipedia*, volume 2889. 2009.
- [11] J. Peng, D. D. Zeng, H. Zhao, and F.-y. Wang. Collaborative filtering in social tagging systems based on joint item-tag recommendations. *CIKM '10*, pages 809–818. ACM, 2010.
- [12] S. Rendle, L. B. Marinho, A. Nanopoulos, and L. Schmidt-Thieme. Learning optimal ranking with tensor factorization for tag recommendation. In *KDD*, pages 727–736, 2009.
- [13] S. Rendle and L. Schmidt-Thieme. Pairwise interaction tensor factorization for personalized tag recommendation. In *WSDM*, pages 81–90, 2010.
- [14] B. Sigurbjörnsson and R. van Zwol. Flickr tag recommendation based on collective knowledge. *WWW '08*, pages 327–336. ACM, 2008.
- [15] P. Symeonidis, A. Nanopoulos, and Y. Manolopoulos. Tag recommendations based on tensor dimensionality reduction. In *RecSys*, pages 43–50, 2008.
- [16] P. Symeonidis, A. Nanopoulos, and Y. Manolopoulos. A unified framework for providing recommendations in social tagging systems based on ternary semantic analysis. *TKDE*, 22(2):179–192, 2010.
- [17] H. Yildirim and M. S. Krishnamoorthy. A random walk method for alleviating the sparsity problem in collaborative filtering. In *RecSys*, pages 131–138, 2008.
- [18] Y. Zhen, W.-J. Li, and D.-Y. Yeung. Tagicofi: tag informed collaborative filtering. *RecSys '09*, pages 69–76. ACM, 2009.

## APPENDIX

We prove the convergence of Equations 26 and 33. Both the equations can be rewritten to a more general form:

$$\mathbf{p}^{(t+1)} = \lambda \bar{\mathbf{A}} \mathbf{p}^{(t)} + \mu \mathbf{q}$$

where  $0 \leq \lambda, \mu \leq 1$ ,  $\bar{\mathbf{A}}$  is a transition matrix with each column summing to 1 and  $\mathbf{q}$  can be any vector with the same dimension of  $\mathbf{p}$ . Suppose  $\mathbf{p}^{(0)} = \boldsymbol{\pi}$ , we have  $\mathbf{p}^{(1)} = \lambda \bar{\mathbf{A}} \boldsymbol{\pi} + \mu \mathbf{q}$ ,  $\mathbf{p}^{(2)} = (\lambda \bar{\mathbf{A}})^2 \boldsymbol{\pi} + \lambda \bar{\mathbf{A}} \mu \mathbf{q} + \mu \mathbf{q}$ , ...,  $\mathbf{p}^{(n)} = (\lambda \bar{\mathbf{A}})^n \boldsymbol{\pi} + \sum_{k=0}^{n-1} (\lambda \bar{\mathbf{A}})^k \mu \mathbf{q}$ . Since  $0 \leq \lambda, \mu \leq 1$  and the eigenvalues of the transition matrix  $\bar{\mathbf{A}}$  are in  $[-1, 1]$ , we have  $\lim_{n \rightarrow \infty} (\lambda \bar{\mathbf{A}})^n = \mathbf{0}$  and  $\lim_{n \rightarrow \infty} \sum_{k=0}^{n-1} (\lambda \bar{\mathbf{A}})^k = (\mathbf{I} - \lambda \bar{\mathbf{A}})^{-1}$ . So  $\mathbf{p}^{(n)}$  finally converges to  $\mathbf{p}^* = (\mathbf{I} - \lambda \bar{\mathbf{A}})^{-1} \mu \mathbf{q}$ .