

Standard Operating Procedure

Set up fleet conversion on your own Windows PC

Document ID	CT-SOP-FLEET-MACHINE-SETUP-2026-09
Version / effective	1.0 · 2 September 2026
Owners	John (conversion / Cloudflare)
Audience	Anyone who will run preview, cutover, rescrape, or 26-check on their own PC
Companion files	Markdown + this HTML + PDF. After setup: SOP-CONVERT-PREVIEW-CUTOVER-RESCRAPE.pdf

This SOP does not convert a site

It only gets the kit onto a new machine. When the checklist at the end is all ticked, open SOP-CONVERT-PREVIEW-CUTOVER-RESCRAPE.pdf in this same `f1eet` folder and follow Path A / B / C. GitHub is not required. Never put `.env` in git, zip, Slack, or chat.

Contents

1. Purpose
2. What lives where
3. Prerequisites
4. Copy the kit
5. Recreate the fleet links
6. Create `.env` in each project
7. Constants
8. Prove the machine works
9. How you run jobs after setup
10. Then read the operating SOP
11. Do not
12. Setup checklist

1. Purpose

A teammate on their own Windows PC can:

1. Copy the four project folders plus the `f1eet` hub.
2. Recreate folder links so `f1eet\worker` (and the rest) open the real projects.

3. Create .env files (token from the vault only).
4. Prove APIs and tools work.
5. Run jobs from C:\Users\<You>\Downloads\fleet.

2. What lives where

Unzip so these sit **next to each other** under Downloads:

```
C:\Users\<You>\Downloads\
fleet\                Hub: SOPs, audits, CSVs, form JS. Run from here.
shared-apex-static\  Fleet Worker, KV/R2 scrape
fleet-static-preview\ static.* preview, DNS, apex cutover
static-conversion\   Per-site convert + 26-check audit
static-fleet-handoff\ Team SOP copies
```

Inside fleet\, these names are **links** to the real folders (not copies of the code):

Link in fleet\	Real folder
worker\	..\shared-apex-static\
preview\	..\fleet-static-preview\
conversion\	..\static-conversion\
handoff\	..\static-fleet-handoff\

If you skip the links, run the same scripts from the real folders. The convert SOP still works. Do **not** put a .env in fleet\ — each project has its own.

3. Prerequisites

Tool	Required?	Notes
Windows 10/11	Yes	
PowerShell 5.1+	Yes	Built-in
curl.exe	Yes	Built-in on current Windows
Python 3.x	Yes	26-check / Form QA (requests, openpyxl)
Cloudflare API token	Yes	From the vault. Never Slack, email, or git
Git / GitHub	No	Zip or shared drive
Node / Wrangler	No	Operators use PowerShell + the API token

```
Set-ExecutionPolicy -Scope CurrentUser RemoteSigned
python --version
curl.exe --version
```

If Python is missing, install 3.12+ from python.org and tick **Add python.exe to PATH**. Then:

```
python -m pip install requests openpyxl urllib3
```

4. Copy the kit

Ask the lead for:

1. The zip / shared-drive copy of the five folders (**no .env files**).
2. Vault item for CLOUDFLARE_API_TOKEN (and DevSecSi key only if you will run old per-site convert).
3. Confirmation that shared-apex-static\reports\fleet-infra.json is in the zip.

Unzip under C:\Users\<You>\Downloads\ so the folder names match this SOP. Do not nest Downloads\fleet\fleet\.

Broken links after unzip

If fleet\worker (or preview / conversion / handoff) is an empty folder, the junction did not survive the copy. Delete those empty folders, then recreate the links in section 5.

5. Recreate the fleet links

Open PowerShell in C:\Users\<You>\Downloads\fleet. This does not need “Run as administrator”:

```
cd "C:\Users\<You>\Downloads\fleet"

foreach ($pair in @(
    @{ Name = 'worker';      Target = '..\shared-apex-static' },
    @{ Name = 'preview';     Target = '..\fleet-static-preview' },
    @{ Name = 'conversion';  Target = '..\static-conversion' },
    @{ Name = 'handoff';     Target = '..\static-fleet-handoff' }
)) {
    if (Test-Path -LiteralPath $pair.Name) { cmd /c "rmdir `"$($pair.Name)`" }
    New-Item -ItemType Junction -Path $pair.Name -Target (Resolve-Path $pair.Target) | Out-Null
    Write-Output ("OK {0} -> {1}" -f $pair.Name, (Resolve-Path $pair.Target))
}
```

Check: dir worker should show README.md and scripts\ from shared-apex-static, not an empty directory.

6. Create .env in each project

A) Fleet Worker — shared-apex-static (fleet\worker)

```
cd "C:\Users\<You>\Downloads\shared-apex-static"
Copy-Item .env.example .env
notepad .env
```

Paste **only** CLOUDFLARE_API_TOKEN from the vault. Leave the rest as in .env.example (account id, both hosting IPs, Worker / KV / R2 names).

Token needs: Workers Scripts, KV, R2, Zone DNS (read), Zone Workers Routes, Zone Cache Purge, Zone WAF. Same Cloudflare account the live fleet already uses.

Fleet infra is **already live**. Do not re-provision unless reports\fleet-infra.json is missing:

```
powershell -ExecutionPolicy Bypass -File .\scripts\Invoke-ProvisionFleet.ps1
```

B) Preview / cutover — fleet-static-preview (fleet\preview)

```
cd "C:\Users\<You>\Downloads\fleet-static-preview"  
Copy-Item .env.example .env
```

Paste the **same** token. Account id, KV id, Worker name, and Server 2 hosting IP can match the worker .env. Add Server 1 origin if missing: HOSTING_IP_S1=165.140.157.43.

C) 26-check / old convert — static-conversion (fleet\conversion)

```
cd "C:\Users\<You>\Downloads\static-conversion"  
Copy-Item .env.example .env  
notepad .env
```

Same Cloudflare token. Fill DevSecSi URL/key from the vault **only** if you will call Adam's provision API. Fleet preview / cutover / origin-IP rescrape do not need DevSecSi.

```
.\Invoke-TestApis.ps1
```

Expect all checks green. If this fails, stop and fix the token with the lead. Do not convert sites.

7. Constants

Name	Value
Server 2 origin (Batches 1–7 live apex)	174.136.29.214 → Worker fleet-static-worker
Server 1 origin (new batches)	165.140.157.43 → Worker fleet-static-worker-server-1
Shared KV / R2	HTML_FLEET / fleet-static-assets
Form JS (fleet inject)	C:\Users\<You>\Downloads\fleet\assets\form-validation.js
Stay-WordPress (never convert)	roundrockfoundationrepaiexperts.com, solidfoundationrepairofsavannah.com, solidfoundationrepairoflakeworth.com, azaleaparkfoundationrepair.com

Do not move Batches 1–7 live apex onto fleet-static-worker-server-1.

8. Prove the machine works

From C:\Users\<You>\Downloads\fleet:

```
Test-Path .\worker\.env  
Test-Path .\preview\.env  
Test-Path .\conversion\.env  
Test-Path .\worker\reports\fleet-infra.json  
Test-Path .\assets\form-validation.js  
Test-Path .\SOP-CONVERT-PREVIEW-CUTOVER-RESCRAPE.pdf
```

All should be True.

Cloudflare token (does not print the secret):

```
cd "C:\Users\<You>\Downloads\shared-apex-static"
$tok = (Get-Content .env | Where-Object { $_ -match '^CLOUDFLARE_API_TOKEN=' }) -replace
'^CLOUDFLARE_API_TOKEN=', ''
$h = @{ Authorization = "Bearer $tok" }
(Invoke-RestMethod -Uri
"https://api.cloudflare.com/client/v4/accounts/f215f8ca79dd9d53b04618556593a581/workers/scripts/fleet-static-
worker" -Headers $h).success
```

Expect True. If it errors, the token is wrong or missing Workers Scripts Read.

9. How you run jobs after setup

Always start in C:\Users\<You>\Downloads\fleet (or worker / preview / conversion). Put domain lists in fleet\sites\ (column Domain). Copy finished spreadsheets into fleet\audits\.

```
cd "C:\Users\<You>\Downloads\fleet\preview"
powershell -ExecutionPolicy Bypass -File .\scripts\Invoke-PreviewStaticOnFleet.ps1 `
-SitesCsv .\sites\YOUR.csv -OriginIp 174.136.29.214 -WorkerName fleet-static-worker

cd "C:\Users\<You>\Downloads\fleet\worker"
powershell -ExecutionPolicy Bypass -File .\scripts\Invoke-WpOriginToFleet.ps1 `
-SitesCsv .\reports\YOUR.csv -HostingIp 174.136.29.214 -SkipRoutes -SkipAssets
```

Full steps, origin-IP rules, and cutover flags are in the convert SOP — not here.

10. Then read the operating SOP

Open C:\Users\<You>\Downloads\fleet\SOP-CONVERT-PREVIEW-CUTOVER-RESCRAPE.pdf.

That document is Path A (new convert → static.* → apex), Path B (rescrape via hosting IP), Path C (rollback to WordPress, edit, rescrape), form-validation inject, and Stay-WordPress.

First real job

Do not convert or cut over apex until that SOP is clear. First site: one non-critical domain, static.* only. Apex cutover requires -IConfirmApexCutover.

11. Do not

Do not	Why
Commit or zip .env	Token in git / shared drive
Paste the token into chat	Vault only
Re-provision fleet “to be safe”	Infra is already live; you can overwrite routes
Skip Stay-WordPress excludes	Never convert those four domains
Scrape public HTTPS on a live fleet site	Recopies stale KV
Use Downloads\form-validation.js	Missing popup listeners; use fleet\assets\form-validation.js
Omit workerName on a new-batch Adam scrape	Lands static.* on Server 2
Cut over apex without -IConfirmApexCutover	Script will refuse; that is intentional

12. Setup checklist

- ☐ Five folders under Downloads\ with the names in section 2
- ☐ fleet\worker, preview, conversion, handoff point at the real projects
- ☐ .env in worker, preview, conversion — token from vault, not from chat
- ☐ python --version and curl.exe --version work
- ☐ Invoke-TestApis.ps1 green if you will use conversion
- ☐ Cloudflare Workers script probe returns True
- ☐ fleet-infra.json and fleet\assets\form-validation.js exist
- ☐ Convert SOP PDF opens from fleet\
- ☐ No .env in the zip you send the next person

Related: [SOP-CONVERT-PREVIEW-CUTOVER-RESCRAPE.pdf](#) (operating workflow) · [static-fleet-handoff\02-pc-setup.md](#) (short sibling) · [shared-apex-static\README.md](#) · [fleet-static-preview\README.md](#)