PW-pipeline

PathWay pipeline using GWAS summary statistics, named analogously after FM-pipepline I have implemented.

INTRODUCTION

Pathway analysis becomes an important element in GWAS. Broadly, it involves SNP annotation, such as Variant Effect Predictor (VEP), gene analysis such as VEGAS2, and gene set analysis. Visualisation of a particular region has been facilitated with LocusZoom, while network(s) from pathway analysis via gephi or Cytoscape, which uses genes and a collection of edges, directed or undirected, to build a network. Aspects to consider include part or all databases, individual level genotype data vs GWAS summary statistics, computing speed, with and without tissue enrichment.



diagram from CytoScape/GeneMANIA

INSTALLATION

This pipeline involves several software for pathway analysis using GWAS summary statistics, as shown below,

| Full name | Abbreviation | Reference |
|---|--------------|----------------------------|
| Meta-Analysis Gene-set Enrichment of variaNT Associations | MAGENTA | Segre, et al. (2010) |
| Multi-marker Analysis of GenoMic Annotation | MAGMA | de Leeuw, et al. (2015) |

| PAthway SCoring ALgorithm | PASCAL | Lamparter, et al. |
|---------------------------|--------|-------------------|
| | | (2016) |

Data-Driven Expression Prioritized Integration for DEPICT Pers, et al.(2015)
Complex Traits

The full functionality of the pipeline requires availability of individual software for pathway analysis, which should fulfil their requirements, e.g., Matlab for MAGENTA, PLINK. It is useful to install XpdfReader or ImageMagick to produce Excel workbook. By default Sun grid engine is used but this can be any other mechanism such as GNU parallel [note with its --env to pass environment variables]. As usual, R is required.

The pipeline itself can be installed from GitHub in the usual way.

```
git clone https://github.com/jinghuazhao/PW-pipeline
```

On systems supporting modules, they can be loaded before hand but it is possible that appropriate module is loaded seamlessly, e.g.,

```
echo module load matlab/r2017b > matlab echo matlab \ >> matlab chmod +x matlab
```

NB "\$@" enables matlab to be called as usual. Alternatively, the module coammands can be part of pwp.ini which is sourced with pwp.sh.

USAGE

The pipeline requires users to specify both software and database to be used, which is now through pwp.ini in the working directory.

The syntax is then

```
bash pwp.sh <input file>
```

Input

The input will be GWAS summary statistics described at https://github.com/jinghuazhao/SUMSTATS in that order without the header,

Output

The output will be available from individual directories named after the software you choose, and optionally in case all software are used the output can also be an Excel workbook containing combined results.

For DEPICT databases, it is possible to call netowrk_plot.py to generate network diagram and perform cluster analysis.

EXAMPLES

The bmi.txt and ST4 from https://github.com/jinghuazhao/SUMSTATS can be called as follows,

pwp.sh bmi.txt
and
pwp.sh ST4 &

ADDITIONAL TOPICS

The wiki page contains the following information,

- Databases
- Features
- Tissue and network plots
- Result collection

You can make changes to the configuration files for each software in their own directries. See also software-notes on how to set up VEGAS2, as in vegas2v2.sh.

RELATED LINKS

- BioGRID: an interaction repository with data compiled through comprehensive curation efforts.
- Osprey: Network Visualization System.
- GeneMANIA: Imports interaction networks from public databases from a list of genes with their annotations and putative functions.
- rGREAT: Client for GREAT Analysis
- VisANT: Visual analyses of metabolic networks in cells and ecosystems.

ACKNOWLEDGEMENTS

The work drives from comparison of software performances using our own GWAS data. The practicality of a common DEPICT database to all software here was due to PASCAL developer(s). At the end of our implementation it came to our attention that similar effort has been made, e.g., DEPICT-pipeline and other adaptations.

SOFTWARE AND REFERENCES

DEPICT (GitHub)

Pers TH et al.(2015) Biological interpretation of genome-wide association studies using predicted gene functions. Nat Commun. 6:5890. doi: 10.1038/ncomms6890.

MAGENTA

Segre AV, et al (2010). Common Inherited Variation in Mitochondrial Genes Is Not Enriched for Associations with Type 2 Diabetes or Related Glycemic Traits. PLoS Genet. 12;6(8). pii: e1001058. doi: 10.1371/journal.pgen.1001058

MAGMA

de Leeuw C, et al. (2015) MAGMA: Generalized Gene-Set Analysis of GWAS Data. PLoS Comput Biol. 11(4): e1004219. doi: 10.1371/journal.pcbi.1004219

PASCAL (GitHub)

Lamparter D, et al. (2016) Fast and Rigorous Computation of Gene and Pathway Scores from SNP-Based Summary Statistics. PLoS Comput Biol. 2016 Jan 25;12(1):e1004714. doi: 10.1371/journal.pcbi.1004714

VEGAS2 (Versatile Gene-based Association Study)

Liu JZ, et al. (2010). A versatile gene-based test for genome-wide association studies. Am J Hum Genet 87:139–145.