

版本号	编写者	时间
V1.0	Dxq	2020/9/10
V1.1	Lhy	2021/1/29
V1.2	hzxu	2021/5/6

商派ECShop4.1部署文档

商派软件有限公司



目录

—, I	NGINX环境下的部署说明	3
1、	LNMP──键安装包进行部署	3
2、	基础安装说明	3
3、	服务 器 配置代码	4
4、	创建单独的数据库账号与密码(非ROOT)	7
	备份与日常维护(以ECSHOP为例)	
6、	FTP安装	9
7、	修改配置文件	9
8、	NGINX配置SSL模块与证书更新	.10
二、/	APACHE环境下的部署说明	.11
1.	LNMP──件安装包进行部署	11
	基础安装说明	
	服务器配置代码	
	创建单独的数据库账号与密码(非ROOT)	
5、	备份与日常维护(以ECSHOP为例)	.15
6、	FTP安装	.16
7,	修改配置文件	16



一、nginx环境下的部署说明

部署约定

操作系统: Centos 7.0 x64或6系列更高版本

服务器的mac地址不可以动态变化,必须是固定的(例如微软云则不支持) nginx、php-fpm的用户和组默认是 www和www

执行代码相关操作的的时候,例如bbc本身的update命令或代码复制的时候最好不要用root直接操作,请用

sudo -u www 您的命令 来进行, 防止目录权限错误

1、Inmp─键安装包进行部署

1 #安装screen

- 2 yum install screen -y
- 3 #进入screen模式
- 4 screen -S Inmp
- 5 #进入目录
- 6 cd /usr/local
- 7 #执行安装命令
- 8 wget http://soft.vpser.net/lnmp/lnmp1.6.tar.gz -cO lnmp1.6.tar.gz && tar zxf lnmp1.6.tar.gz && cd lnmp1.6 && ./install.sh lnmp
- 9 #执行完命令后操作参考文档地址
- 10 #一件安装命令具体操作文档 https://lnmp.org/install.html
- 11 #说明:ecshop选择mysql5.6, php5.6
- 12 #mysql数据库初始密码使用密码生成器生成(16位密码即可)
- 13 #生成器地址 https://suijimimashengcheng.51240.com/
- 14 #例如生成后为 jpPrUzJnbjMKjCez

2、基础安装说明

查看对应的软件是否安装成功



```
1 [root@iZbp165858i0knchjfots2Z~]# nginx-v nginx version:
2 nginx/1.16.1 [root@iZbp165858i0knchjfots2Z~]# mysql-V
3 mysql Ver 14.14 Distrib 5.6.44, for Linux (x86_64) using EditLine wrapper
4 [root@iZbp165858i0knchjfots2Z~]# php-fpm -v
5 PHP 5.6.40 (fpm-fcgi) (built: Mar 10 2020 17:33:44) Copyright (c) 1997-
6 2016 The PHP Group
7 Zend Engine v2.6.0, Copyright (c) 1998-2016 Zend Technologies
8 with Zend Guard Loader v3.3, Copyright (c) 1998-2014, by ZendTechnologies
```

重启脚本

1 #重启nginx
2 /etc/init.d/nginx restart/start/stop
3 #重启php
4 /etc/init.d/php-fpm restart/start/stop
5 #重启mysql
6 /etc/init.d/mysql restart/start/stop

3、服务器配置代码

```
1 #ecshop为例
2 mkdir -p /data/httpd/www/
3 cd /data/httpd/www/

下载ecshop代码
5 cd /usr/local/nginx/conf/vhost/
vim ecshop.conf
vim api.ecshop.conf
```

商派软件有限公司



```
1 #ecshop.conf server {
 2 server_name ecshop.me;
 3 root/data/httpd/www/ecshop/ecshop; index
 4 index.html index.htmindex.php; location / {
 5 autoindex on;
 6 }
 7 location /h5 {
 8 if (!-e $request_filename) { rewrite ^/(.*)
 9 /h5/ last; break;
10 }
11 }
  add\_header\ Access-Control-Allow-Origin\ '*';
       add_header Access-Control-Allow-Headers "Content-Type, Access-Control-Allow-Headers, Authorization, X-Requested-
_{14} With";
       add_header Access-Control-Expose-Headers "Authorization";
15
       add_header Access-Control-Allow-Methods "DELETE, GET, HEAD, POST, PUT, OPTIONS, TRACE, PATCH";
16
17
18
```

商派软件有限公司



```
20 location ~ \.php$ {
   fastcgi pass unix:/tmp/php-cgi.sock;
   fastcgi index index.php;
22
   fastcgi param SCRIPT FILENAME $document root$fastcgi script name;
23
   include fastcgi params; 24 }
   access log/data/httpd/www/access log/ecshop.log;
25
   error log/data/httpd/www/access log/error.logcrit; 27 }
26
   #api.ecshop.conf
   server {
29
   server_name api.ecshop.me;
30
   root /data/httpd/www/ecshop/phalapi/public/;
31
   index index.html index.htm index.php;
   add header Access-Control-Allow-Origin '*';
  add_header Access-Control-Allow-Headers "Content-Type, Access-Control-Allow-Headers, Authorization, X-
   Requested-With";
  add_header Access-Control-Expose-Headers "Authorization";
  add header Access-Control-Allow-Methods "DELETE, GET, HEAD, POST, PUT, OPTIONS, TRACE, PATCH";
33
   location / {
34
   autoindex on;
39 }
   location ~ \.php$ {
40
   fastcgi_pass unix:/tmp/php-cgi.sock;
   fastcgi_index index.php;
42
   fastcgi_param SCRIPT_FILENAME $document_root$fastcgi_script_name;
43
   include fastcgi_params; 45 }
   access_log/data/httpd/www/access_log/api.ecshop.log;
   error_log /data/httpd/www/access_log/error.logcrit; 48 }
```



4、创建单独的数据库账号与密码(非root)

以ecshop为例

如下操作后可以得到 数据库名:ecshop 用户名:ecshop 密码:fRn1Go4OyyS5BkQA 这里ecshop的密码fRn1Go4OyyS5BkQA 为随机生成

- [root@iZbp13tx21s4p0qjd90p08Z vhost]# mysql -uroot -pshop123
 Warning: Using a password on the command line interface can be insecure. Welcome to the MySQL
- 3 monitor. Commands end with; or\g.
- 4 Your MySQL connection id is 2
- 5 Server version: 5.6.44-log Source distribution
- 6 Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of
- 7 Oracle Corporation and/orits
- 8 affiliates. Other names may be trademarks of their respective owners.
- ⁹ Type 'help;' or '\h' for help. Type '\c' to clear the current input statement. mysql> create database ecshop;
- 10 Query OK, 1 row affected (0.00sec) mysql> use
- 11 ecshop;
- 12 Database changed
- mysql> GRANT ALL PRIVILEGES ON ecshop.* TO 'ecshop'@'localhost' IDENTIFIED BY 'fRn1Go Query OK, 0 rows
- ¹⁴ affected (0.00 sec)
- 15 mysql> flush privileges;
- 16 Query OK, 0 rows affected (0.00 sec)

17

18



5、备份与日常维护(以ecshop为例)

文件代码与数据库备份

```
mkdir /data/httpd/www/shell
mkdir /data/httpd/www/backup
cp /usr/local/lnmp1.6/tools/backup.sh /data/httpd/www/shell/
vim /data/httpd/www/shell/backup.sh

#修改后
Backup_Home="/data/httpd/www/backup"
Backup_Dir=("/data/httpd/www/ecshop")
MYSQL_UserName='root'
MYSQL_PassWord='jpPrUzJnbjMKjCez'
Enable FTP=1
```

nginx日志切割

```
mkdir /data/httpd/www/access_log

cp /usr/local/lnmp1.6/tools/cut_nginx_logs.sh /data/httpd/www/shell/

vim /data/httpd/www/shell/cut_nginx_logs.sh

#修改后

log_files_path="/data/httpd/www/access_log"

log_files_name=(ecshop api.ecshop)
```

php挂掉后自启脚本

- - 4 CheckURL="http://ecshop.me"

crontab



```
1 #crontab -e
2 #五分钟检测一次
3 */5 * * * * /data/httpd/www/shell/check502.sh > /dev/null 2>&1
4 #凌晨自动切割nginx日志
5 0 0 * * * /data/httpd/www/shell/cut_nginx_logs.sh > /dev/null 2>&1
6 #凌晨2点进行一次数据与文件备份
7 0 2 * * * /data/httpd/www/shell/backup.sh > /dev/null 2>&1
```

6、ftp安装

```
1 cd /usr/local/lnmp1.6/
```

- 2 ./pureftpd.sh
- 3 Inmp ftp add
- 4 #输入用户名+密码+访问路径
- 5 #常用命令
- 6 #Usage: Inmp ftp {add|list|del}

7、修改配置文件

在phalapi\config\app.php文件中修改域名。(修改为PC端访问域名)



```
FOLDERS
ecshop
                      22
                               ),
ecshop
                      23
▶ ■ mp-weixir
▼ phalapi
                               /**
                      24
 app.php
app.sample.g
                      25
                                * 接口服务白名单,格式:接口服务类名.接口服务方法名
                      26
  di.php
                                * 示例:
                      27
  sys.php
 language
                                 _ * *
                                                  通配,全部接口服务,慎用!
                      28
 ▶ □ public
▶ □ runtime
                                * - Site.*
                                                  Api Default接口类的全部方法
                      29
 ⊳ 🕅 sdk
                                * - *.Index
                                                  全部接口类的Index方法
                      30
                                * - Site.Index 指定某个接口服务,即Api Default::Index()
                      31
 vendor
                      32
  III LICENSE
                               'service whitelist' => array(
                      33
  README.md
 .gitignore
                      34
                                   'Site.Index',
 .htaccess
                      35
                               ),
 nginx.htacces
 ETT README and
                               'host_url' => 'http://ecshop/',
                      37
                      38
                               'host url res' => 'http://ecshop/',
                      39
                               'default_category_img' => 'https://imgt1.oss-cn-shanghai.aliyuncs.cc
                      40
                               default_category.png',
'default_category_banner' => 'https://imgt1.oss-cn-shanghai.aliyuncs
                      41
                                   default_category_banner.jpg',
                               'default_article_img' => 'https://imgt1.oss-cn-shanghai.aliyuncs.com
                      42
                                   default_category_banner.jpg',
                               'default_category_goodsImage' => 'https://imgt1.oss-cn-shanghai.aliv
                                   default category hanner ing! //戰认商品图片
```

8、Nginx配置SSL模块与证书更新

证书的生成与获取:

```
在各平台获取SSL证书后,证书一般包含两个文件:****.key,*****.pem
将两个文件分别上传到服务器中
```

修改nginx的配置文件,让其分别指向两个文件

```
[root@ecs-**** vhost]# ls
Api.ecshop.conf ecshop.conf
[root@ecs-**** vhost]# pwd
/usr/local/nginx/conf/vhost
修改内容
```

```
server {
    listen 443;
    ssl on;
    ssl_certificate /usr/local/nginx/conf/ssl_aliyun/server.pem;
    ssl_certificate_key /usr/local/nginx/conf/ssl_aliyun/server.key;
}
```

重启nginx。SSL证书到期替换时,同样操作,上传证书、修改配置,重启即可。



二、apache环境下的部署说明

约定

操作系统: Centos 7.0 x64或6系列更高版本

服务器的mac地址不可以动态变化,必须是固定的(例如微软云则不支持)

apache,php-fpm的用户和组默认是 www和www

执行代码相关操作的的时候,例如bbc本身的update命令或代码复制的时候最好不要用root直接操作,请用sudo -u www 您的命令来进行,防止目录权限错误

1、Inmp—件安装包进行部署

(注:服务器上已存在环境的 不能执行 Inmp一件安装包进行部署命令 否则将会覆盖服务器上已存在的环境 可参考下面配置文件进行参考)

- 1 #安装screen
- 2 yum install screen -y
- 3 #进入screen模式
- 4 screen -S Inmp
- 5 #讲入目录
- 6 cd /usr/local
- 7 #执行安装命令
- 8 wget http://soft.vpser.net/lnmp/lnmp1.6.tar.gz -cO lnmp1.6.tar.gz && tar zxf lnmp1.6.tar.gz && cd lnmp1.6 && ./install.sh lnmpa
- 9 #执行完命令后操作参考文档地址
- 10 #一件安装命令具体操作文档 https://lnmp.org/install.html
- 11 #说明:ecshop选择mysql5.6, php5.6
- 12 #mysql数据库初始密码使用密码生成器生成(16位密码即可)
- 13 #生成器地址 https://suijimimashengcheng.51240.com/
- 14 #例如生成后为 jpPrUzJnbjMKjCez

2、基础安装说明

查看对应的软件是否安装成功



```
1 [root@iZbp165858i0knchjfots2Z~]#httpd -v Server
2 version: Apache/2.4.46 (Unix)
3 Server built: Sep 4 2020 11:26:40
4 [root@iZbp165858i0knchjfots2Z~]# mysql-V
5 mysql Ver 14.14 Distrib 5.6.44, for Linux (x86_64) using EditLine wrapper
6 [root@iZbp165858i0knchjfots2Z~]# php-fpm -v
7 PHP 5.6.40 (fpm-fcgi) (built: Mar 10 2020 17:33:44) Copyright (c) 1997-
8 2016 The PHP Group
9 Zend Engine v2.6.0. Copyright (c) 1998-2016 Zend Technologies
```

重启脚本

```
1 #重启apache
2 /etc/init.d/httpd restart/storp
3 #重启php
4 /etc/init.d/php-fpm restart/storp
5 #重启mysql
6 /etc/init.d/mysql restart/storp
```

3、服务器配置代码

```
1 #ecshop为例
2 mkdir -p /data/httpd/www/
3 cd /data/httpd/www/
4 上传ecshop代码
5 /usr/local/apache/conf/vhost
6 vim ecshop.conf
7 vim api.ecshop.conf
```



```
1 #ecshop.conf
 2 <VirtualHost *:80>
 3
       DocumentRoot "/data/httpd/www/ecshop/ecshop"
       ServerName ecshop.me
 5
 6
       <Directory "/data/httpd/www/ecshop/ecshop">
 7
           SetOutputFilter DEFLATE
 8
           Options FollowSymLinks
 9
           AllowOverride All
10
           Order allow, deny
11
           Allow from all
12
           DirectoryIndex index.html index.php
13
           RewriteEngine on
14
           RewriteCond %{REQUEST_FILENAME} -f [OR]
15
           RewriteCond %{REQUEST_FILENAME} -d
16
           RewriteRule ^ - [L]
17
           RewriteRule ^ index.php [L]
18
       </Directory>
```

#api.ecshop.conf

28

32

34

35

```
29 <VirtualHost *:80>
```

30 DocumentRoot "/data/httpd/www/ecshop/phalapi/public"

31 ServerName api.ecshop.me

<Directory "/data/httpd/www/ecshop/phalapi/public">

33 RewriteEngine on

RewriteCond %{REQUEST_FILENAME} -f [OR]

RewriteCond %{REQUEST_FILENAME} -d

36 RewriteRule ^ - [L]

37 RewriteRule ^ index.php [L]

38 Header set Access-Control-Allow-Origin '*'

39 </Directory>

40

41 </VirtualHost>



4、创建单独的数据库账号与密码(非root)

这里以ecshop为例

如下操作后可以得到 数据库名:ecshop 用户名:ecshop 密码:fRn1Go4OyyS5BkQA 这里ecshop的密码fRn1Go4OyyS5BkQA 为随机生成

- 1 [root@iZbp13tx21s4p0qjd90p08Z vhost]# mysql -uroot -pshop123
 2 Warning: Using a password on the command line interface can be insecure. Welcome to the MySQL
 3 monitor. Commands end with; or\g.
 4 Your MySQL connection id is 2
 5 Server version: 5.6.44-log Source distribution
- 6 Copyright (c) 2000, 2019, Oracle and/or its affiliates. All rights reserved. Oracle is a registered trademark of
- 7 Oracle Corporation and/orits
- 8 affiliates. Other names may be trademarks of their respective owners.
- ⁹ Type 'help;' or '\h' for help. Type '\c' to clear the current input statement. mysql> create database ecshop;
- Query OK, 1 row affected (0.00sec) mysql> use
- 11 ecshop;
- 12 Database changed
- mysql> GRANT ALL PRIVILEGES ON ecshop.* TO 'ecshop'@'localhost' IDENTIFIED BY 'fRn1Go Query OK, 0 rows
- affected (0.00 sec)
- mysql> flush privileges;
- 16 Query OK, 0 rows affected (0.00 sec)

17

18



5、备份与日常维护(以ecshop为例)

文件代码与数据库备份

```
mkdir /data/httpd/www/shell
mkdir /data/httpd/www/backup
cp /usr/local/lnmp1.6/tools/backup.sh /data/httpd/www/shell/
vim /data/httpd/www/shell/backup.sh

#修改后
Backup_Home="/data/httpd/www/backup"
Backup_Dir=("/data/httpd/www/ecshop")
MYSQL_UserName='root'
MYSQL_PassWord='jpPrUzJnbjMKjCez'
Enable_FTP=1
```

php挂掉后自启脚本

cp/usr/local/lnmp1.6/tools/check502.sh/data/httpd/www/shell/ vim

/data/httpd/www/shell/check502.sh

#这里修改为你的域名

CheckURL="http://ecshop.me"

crontab

```
1 #crontab -e
2 #五分钟检测一次
3 */5 * * * * /data/httpd/www/shell/check502.sh > /dev/null 2>&1
4 #凌晨2点进行一次数据与文件备份
5 0 2 * * * /data/httpd/www/shell/backup.sh > /dev/null 2>&1
```



6、ftp安装

```
1 cd /usr/local/lnmp1.6/
2 ./pureftpd.sh
3 lnmp ftp add
4 #输入用户名+密码+访问路径
5 #常用命令
6 #Usage: lnmp ftp {add|list|del}
```

7、修改配置文件

在phalapi\config\app.php文件中修改域名。(修改为PC端访问域名)

```
▼ ា ecshop
                      22
                              ),
ecshop
                      23
 ▶ IIII mp-weixin
                      24
app.sample.php
                               * 接口服务白名单,格式:接口服务类名.接口服务方法名
                      25
                      26
   di.php
                               * 示例:
                      27
 ► I language
                      28
                               * _ * *
                                                 通配,全部接口服务,慎用!
 ▶ □ public
▶ □ runtime
                               * - Site.*
                                                 Api Default接口类的全部方法
                      29
 ▶ IIII sdk
                                                 全部接口类的Index方法
                      30
                               * - *.Index
                               * - Site.Index 指定某个接口服务,即Api Default::Index()
                      31
 ▶ I vendor
  omposer.jsor
                               */
                      32
  composer.lock
  III LICENSE
                               'service whitelist' => array(
                      33
  README.md
  .gitignore
                      34
                                   'Site.Index',
                      35
                              ),
  eheck_file.php
 README.md
                      37
                              'host url' => 'http://ecshop/',
                      38
                              'host_url_res' => 'http://ecshop/',
                      39
                              'default_category_img' => 'https://imgt1.oss-cn-shanghai.aliyuncs.cc
                      40
                                   default_category.png',
                              'default_category_banner' => 'https://imgt1.oss-cn-shanghai.aliyuncs
                      41
                                   default_category_banner.jpg',
                              'default_article_img' => 'https://imgt1.oss-cn-shanghai.aliyuncs.com
                      42
                                   default_category_banner.jpg',
                              'default_category_goodsImage' => 'https://imgt1.oss-cn-shanghai.aliy
                      43
                                   default category hanner ing! //默认商品图片
```