

Contents

Usage of CRG_APPEND	1
Test proceedings	2
Test1 (defined by z matrix and scalar u and v specs)	3
Test1.1 (. . . and evenly spaced v vector)	4
Test1.2 (. . . and unevenly spaced v vector)	5
Test1.3 (. . . generate diagonal reference line by one p value)	6
Test1.4 (. . . generate diagonal reference line by nu-1 p values)	7
Test1.5 (. . . generate curved reference line)	8
Test1.6 (. . . generate banking)	9
Test1.7 (. . . generate slope)	10
Test1.8 (+ WGS84)	11
Test2 (curved crg + straight crg)	12
Test2.1 (curved crg + diagonal reference line)	13
Test3 (straight crg + diagonal reference line)	14
Test3.1 (straight crg + curved crg)	15
Test4 (diagonal reference line + straight crg)	16
Test4.1 (diagonal reference line + curved crg)	17
Test5 (no banking + constant banking)	18
Test5.1 (no banking + variable banking)	19
Test6 (constant banking + no banking)	20
Test6.1 (constant banking + variable banking)	21
Test7 (variable banking + no banking)	22
Test7.1 (variable banking + constant banking)	23
Test8 (no slope + constant slope)	24

Test8.1 (no slope + variable slope)	25
Test9 (constant slope + no slope)	26
Test9.1 (constant slope + variable slope)	27
Test10 (variable slope + no slope)	28
Test10.1 (variable slope + constant slope)	29

Usage of CRG_APPEND

Introducing the usage of `crg_append`. Examples are included for a set of common CRG-file formats. The file comments are optimized for the matlab publishing makro.

```
% NOTE
% One u-increment is used to adjust both crg-files into the right
% direction. Hence make sure you have a overlap by one (see examples).
%
% Copyright 2005-2011 OpenCRG - VIREs Simulationstechnologie GmbH -
% Holger Helmich
%
% Licensed under the Apache License, Version 2.0 (the "License");
% you may not use this file except in compliance with the License.
% You may obtain a copy of the License at
%
%     http://www.apache.org/licenses/LICENSE-2.0
%
% Unless required by applicable law or agreed to in writing, software
% distributed under the License is distributed on an "AS IS" BASIS,
% WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
% See the License for the specific language governing permissions and
% limitations under the License.
%
% More Information on OpenCRG open file formats and tools can be found at
%
%     http://www.opencrg.org
%
% $Id: crg_test_append.m 1 2011-06-07 10:48:00Z hhelmich $
```

Test proceedings

Example 1 - 1.9:

- Load crg file (`crg_read`)
- Cut reference crg file (first `crg_cut_iuiv` call)
- Cut starting crg file patch (second `crg_cut_iuiv` call)
- Cut ending crg file patch (third `crg_cut_iuiv` call)
- Concatenate both patches (`crg_append`)
- Display result

Example 2 - 10:

- Load different kind of crg files (`crg_read`)
- Concatenate both patches (`crg_append`)
- Display result

```
% DEFAULT SETTINGS
% clear enviroment
clear all;
close all;
```

Test1 (defined by z matrix and scalar u and v specs)

```
data = crg_read('demo1.crg');
```


```
crg0 = crg_cut_iuiv(data, [1, 1000]);
```

```
crg1 = crg_cut_iuiv(crg0, [1, 501]);
```

```
crg2 = crg_cut_iuiv(crg0, [500, 1000]);
```

```
crg3 = crg_append(crg1, crg2);
```

```
crg_show_elgrid_surface(crg3, [1, 1000]);
```



<unknown CRG file name>


2011-06-07 11:18:07

Test1.1 (. . . and evenly spaced v vector)

```
data = crg_read('demo2.crg');

crg0 = crg_cut_iuiv(data, [1, 1000]);
crg1 = crg_cut_iuiv(crg0, [1, 501]);
crg2 = crg_cut_iuiv(crg0, [500, 1000]);
crg3 = crg_append(crg1, crg2);

crg_show_elgrid_surface( crg3, [1, 1000] );
```



<unknown CRG file name>


2011-06-07 11:18:10

Test1.2 (. . . and unevenly spaced v vector)

```
data = crg_read('demo3.crg');

crg0 = crg_cut_iuiv(data, [1, 1000]);
crg1 = crg_cut_iuiv(crg0, [1, 501]);
crg2 = crg_cut_iuiv(crg0, [500, 1000]);
crg3 = crg_append(crg1, crg2);

crg_show_elgrid_surface( crg3, [1, 1000] );
```



<unknown CRG file name>


2011-06-07 11:18:13

Test1.3 (. . . generate diagonal reference line by one p value)

```
data = crg_read('demo4.crg');

crg0 = crg_cut_iuiv(data, [1, 1000]);
crg1 = crg_cut_iuiv(crg0, [1, 501]);
crg2 = crg_cut_iuiv(crg0, [500, 1000]);
crg3 = crg_append(crg1, crg2);

crg_show_road_surface( crg3, [1, 1000] );
```



<unknown CRG file name>


2011-08-07 11:18:16

Test1.4 (. . . generate diagonal reference line by nu-1 p values)

```
data = crg_read('demo5.crg');

crg0 = crg_cut_iuiv(data, [1, 1000]);
crg1 = crg_cut_iuiv(crg0, [1, 501]);
crg2 = crg_cut_iuiv(crg0, [500, 1000]);
crg3 = crg_append(crg1, crg2);

crg_show_road_surface( crg3, [1, 1000] );
```



<unknown CRG file name>


2011-06-07 11:16:24

Test1.5 (. . . generate curved reference line)

```
data = crg_read('demo6.crg');

crg0 = crg_cut_iuiv(data, [1, 1000]);
crg1 = crg_cut_iuiv(crg0, [1, 501]);
crg2 = crg_cut_iuiv(crg0, [500, 1000]);
crg3 = crg_append(crg1, crg2);

crg_show_road_surface(crg3, [1 1000]);
```




<unknown CRG file name>

2011-06-07 11:18:33

Test1.6 (. . . generate banking)

```
data = crg_read('demo7.crg');  
crg0 = crg_cut_iuiv(data, [1, 1000]);  
crg1 = crg_cut_iuiv(crg0, [1, 301]);  
crg2 = crg_cut_iuiv(crg0, [300, 1000]);
```

```
crg3 = crg_append(crg1, crg2 );  
crg_show_road_surface(crg3, [1 1000]);
```



<unknown CRG file name>


2011-06-07 11:18:42

Test1.7 (. . . generate slope)

```
data = crg_read('demo8.crg');

crg0 = crg_cut_iuiv(data, [1, 1000]);
crg1 = crg_cut_iuiv(crg0, [1, 301]);
crg2 = crg_cut_iuiv(crg0, [300, 1000]);

crg3 = crg_append(crg1, crg2 );
crg_show_road_surface(crg3, [1 1000]);
```




<unknown CRG file name>

2011-06-07 11:17:01

Test1.8 (+ WGS84)

```
crg = crg_read('../crg-bin/country_road.crg');  
  
crg0 = crg_cut_iuiv(crg, [1, 2000]);  
crg1 = crg_cut_iuiv(crg0, [1, 1001]);  
crg2 = crg_cut_iuiv(crg0, [1000, 2000]);  
  
crg3 = crg_append(crg1, crg2 );  
  
crg_show_road_surface(crg3, [1 1000]);
```




<unknown CRG file name>

2011-06-07 11:17:22

Test2 (curved crg + straight crg)

```
crg1 = crg_read('demo6.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);

crg3 = crg_append(crg1, crg2 );
crg_show_road_surface(crg3, [1 2000]);
```




<unknown CRG file name>

2011-06-07 11:17:33

Test2.1 (curved crg + diagonal reference line)

```
crg1 = crg_read('demo6.crg');
crg2 = crg_read('demo3.crg');

crg3 = crg_append(crg1, crg2 );
crg_show_road_surface(crg3, [1 2000]);
```



<unknown CRG file name>

2011-06-07 11:17:49


Test3 (straight crg + diagonal reference line)

```

crg1 = crg_read('demo1.crg');
crg2 = crg_read('demo3.crg');
crg2 = crg_rerender(crg2, [], crg1.v);

crg3 = crg_append(crg1, crg2 );
crg_show_road_surface(crg3, [1 2000]);

```




<unknown CRG file name>

2011-06-07 11:18:09

Test3.1 (straight crg + curved crg)

```
crg1 = crg_read('demo6.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);

crg3 = crg_append(crg2, crg1 );
crg_show_road_surface(crg3, [1 2000]);
```




<unknown CRG file name>

2011-06-07 11:18:28

Test4 (diagonal reference line + straight crg)

```
crg1 = crg_read('demo4.crg');  
crg2 = crg_read('demo1.crg');  
crg2 = crg_rerender(crg2, [], crg1.v);  
  
crg3 = crg_append(crg1, crg2);  
crg_show_road_surface(crg3, [1 2000]);
```




<unknown CRG file name>

2011-06-07 11:18:47

Test4.1 (diagonal reference line + curved crg)

```
crg1 = crg_read('demo6.crg');
crg2 = crg_read('demo4.crg');

crg3 = crg_append(crg2, crg1);
crg_show_road_surface(crg3, [1 2000]);
```



<unknown CRG file name>


2011-06-07 11:19:03

Test5 (no banking + constant banking)

```
crg1 = crg_read('demo3.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);
```

```
crg2.b = 0.05;
crg2.head.bbeg = 0.05;
crg2.head.bend = 0.05;
crg2 = crg_check(crg2);
```

```
crg3 = crg_append(crg1, crg2);
crg_show_road_surface(crg3, [1 2000]);
```




<unknown CRG file name>

2011-06-07 11:19:22

Test5.1 (no banking + variable banking)

```
crg1 = crg_read('demo3.crg');  
crg2 = crg_read('demo7.crg');  
  
crg3 = crg_append(crg1, crg2);  
crg_show_road_surface(crg3, [1 2000]);
```



<unknown CRG file name>


2011-06-07 11:19:50

Test6 (constant banking + no banking)

```
crg1 = crg_read('demo3.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);
```

```
crg2.b = 0.05;
crg2.head.bbег = 0.05;
crg2.head.bend = 0.05;
crg2 = crg_check(crg2);
```

```
crg3 = crg_append(crg2, crg1);
crg_show_road_surface(crg3, [1 2000]);
```



<unknown CRG file name>


2011-06-07 11:29:38

Test6.1 (constant banking + variable banking)

```
crg1 = crg_read('demo7.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);
```

```
crg2.b = 0.05;
crg2.head.bbeg = 0.05;
crg2.head.bend = 0.05;
crg2 = crg_check(crg2);
```

```
crg3 = crg_append(crg2, crg1);
crg_show_road_surface(crg3, [1 2000]);
```




<unknown CRG file name>

2011-06-07 11:21:16

Test7 (variable banking + no banking)

```
crg1 = crg_read('demo3.crg');  
crg2 = crg_read('demo7.crg');  
  
crg3 = crg_append(crg2, crg1);  
crg_show_road_surface(crg3, [1 2000]);
```



<unknown CRG file name>

2011-06-07 11:21:54

Test7.1 (variable banking + constant banking)


```

crg1 = crg_read('demo7.crg');
crg2 = crg_read('demo3.crg');

crg2.b = 0.05;
crg2.head.bbег = 0.05;
crg2.head.bend = 0.05;
crg2 = crg_check(crg2);

crg3 = crg_append(crg1, crg2);
crg_show_road_surface(crg3, [1 2000]);

```



<unknown CRG file name>

2011-06-07 11:22:30

Test8 (no slope + constant slope)


```

crg1 = crg_read('demo3.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);

crg2.s = 0.05;
crg2.head = rmfield(crg2.head, 'send');
crg2.head = rmfield(crg2.head, 'sbeg');
crg2.head = rmfield(crg2.head, 'zbeg');
crg2.head = rmfield(crg2.head, 'zend');
crg2 = crg_check(crg2);

crg3 = crg_append(crg1, crg2);
crg_show_road_surface(crg3, [1 2000]);

```




<unknown CRG file name>

2011-06-07 11:23:10

Test8.1 (no slope + variable slope)

```
crg1 = crg_read('demo3.crg');  
crg2 = crg_read('demo9.crg');  
  
crg3 = crg_append(crg1, crg2);  
crg_show_road_surface(crg3, [1 2000]);
```



<unknown CRG file name>

2011-06-07 11:23:44

Test9 (constant slope + no slope)


```

crg1 = crg_read('demo3.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);

crg2.s = 0.05;
crg2.head = rmfield(crg2.head, 'send');
crg2.head = rmfield(crg2.head, 'sbeg');
crg2.head = rmfield(crg2.head, 'zbeg');
crg2.head = rmfield(crg2.head, 'zend');
crg2 = crg_check(crg2);

crg3 = crg_append(crg2, crg1);
crg_show_road_surface(crg3, [1 2000]);

```



<unknown CRG file name>

2011-06-07 11:24:21

Test9.1 (constant slope + variable slope)


```

crg1 = crg_read('demo9.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);

crg2.s = 0.05;
crg2.head = rmfield(crg2.head, 'send');
crg2.head = rmfield(crg2.head, 'sbeg');
crg2.head = rmfield(crg2.head, 'zbg');
crg2.head = rmfield(crg2.head, 'zend');
crg2 = crg_check(crg2);

crg3 = crg_append(crg2, crg1);
crg_show_road_surface(crg3, [1 2000]);

```




<unknown CRG file name>

2011-06-07 11:24:59

Test10 (variable slope + no slope)

```
crg1 = crg_read('demo3.crg');
crg2 = crg_read('demo9.crg');

crg3 = crg_append(crg2, crg1);
crg_show_road_surface(crg3, [1 2000]);
```



<unknown CRG file name>

2011-06-07 11:25:32

Test10.1 (variable slope + constant slope)


```

crg1 = crg_read('demo9.crg');
crg2 = crg_read('demo1.crg');
crg2 = crg_rerender(crg2, [], crg1.v);

crg2.s = 0.05;
crg2.head = rmfield(crg2.head, 'send');
crg2.head = rmfield(crg2.head, 'sbeg');
crg2.head = rmfield(crg2.head, 'zbeg');
crg2.head = rmfield(crg2.head, 'zend');
crg2 = crg_check(crg2);

crg3 = crg_append(crg1, crg2);
crg_show_road_surface(crg3, [1 2000]);

```



<unknown CRG file name>

2011-06-07 11:28:10