

Contents

Usage of CRG_MAP_UV2UVV AND CRG_MAP_XY2XY	1
Test proceedings	2
Test1 (no additional parameter)	3
Test2 (u-start/stop index)	8
Test3 (v-start/stop index)	9
Test4 (u/v-start/stop index)	10
Test5 (add curved crg)	15
Test6 (adding real dataset)	20

Usage of CRG_MAP_UV2UVV AND CRG_MAP_XY2XY

Introducing the usage of `crg_map_uv2uv` and `crg_map_xy2xy`. Examples are included. The file comments are optimized for the matlab publishing makro.

```
% Copyright 2005-2011 OpenCRG - VIREs Simulationstechnologie GmbH -
% Holger Helmich
%
% Licensed under the Apache License, Version 2.0 (the "License");
% you may not use this file except in compliance with the License.
% You may obtain a copy of the License at
%
%     http://www.apache.org/licenses/LICENSE-2.0
%
% Unless required by applicable law or agreed to in writing, software
% distributed under the License is distributed on an "AS IS" BASIS,
% WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
% See the License for the specific language governing permissions and
% limitations under the License.
%
% More Information on OpenCRG open file formats and tools can be found at
%
%     http://www.opencrg.org
%
% $Id: crg_test_map_uv2uvAxy2xy.m 1 2011-06-08 11:06:00Z hhelmich $
```

Test proceedings

- generate 0-z-crg file
- load test/real files
- FIRST: u,v maping ($z_a(u,v) \rightarrow z_b(u,v)$)
- SECOND: inertial x,y mapping ($z_a(x,y) \rightarrow z_b(x,y)$)
- display result

```
% DEFAULT SETTINGS
% clear enviroment
clear all;
close all;
```


Test1 (no additional parameter)


```
c = { 3 { 0 -0.2/3 } ... % klothoide
      ; 5 {-0.2 0.4/5 } ... % turning klothoide
      ; 8 { 0.4 0.4/8 } ... % circle
    };
```

```
dat1 = crg_gen_csb2crg0([], 16, 1, c);
dat2 = crg_read('demo1.crg');
```

```
data = crg_map_uv2uv(dat1, dat2); % u,v mapping
crg_show(data);
```


```
data = crg_map_xy2xy(dat1, dat2); % inertial mapping
crg_show(data);
```





<unknown CRG file name>

2011-06-08 11:18:04



<unknown CRG file name>

2011-06-08 11:18:05

CRC information

[illegible]





```
CRG comment data:

CRG minimal artificial road and flat surface
... curvature added
```

<unknown CRG file name>


CRG reference line map

2011-08-08 11:18:06




<unknown CRG file name>

2011-08-08 11:18:08



<unknown CRG file name>

2011-06-08 11:18:09



<unknown CRG file name>

2011-06-08 11:18:10

```
CRG comment data:

CRG minimal artificial road and flat surface
... curvature added
```

<unknown CRG file name>

7

Test2 (u-start/stop index)

```
c = { 3   { 0 -0.2/3 } ...   % klothoide
      ; 5   {-0.2  0.4/5 } ...   % turning klothoide
      ; 8   { 0.4  0.4/8 } ...   % circle
    };

dat1 = crg_gen_csb2crg0([], 16, 1, c);
dat2 = crg_read('demo3.crg');

data = crg_map_uv2uv(dat1, dat2, [200 1000]);      % u,v mapping
crg_show(data);

data = crg_map_xy2xy(dat1, dat2, [200 1000]);      % inertial mapping
crg_show(data);
```


Test3 (v-start/stop index)

Border Mode is default

```
c = { 3   { 0 -0.2/3 } ...   % klothoide
      ; 5   {-0.2  0.4/5 } ...   % turning klothoide
      ; 8   { 0.4  0.4/8 } ...   % circle
    };

dat1 = crg_gen_csb2crg0([], 16, 1, c);
dat2 = crg_read('demo1.crg');

data = crg_map_uv2uv(dat1, dat2, [], [70 110]);    % u,v mapping
crg_show(data);

data = crg_map_xy2xy(dat1, dat2, [], [20 75]);    % inertial mapping
crg_show(data);
```


Test4 (u/v-start/stop index)


```
c = { 3 { 0 -0.2/3 } ... % klothoide
      ; 5 {-0.2 0.4/5 } ... % turning klothoide
      ; 8 { 0.4 0.4/8 } ... % circle
    };
```


```
dat1 = crg_gen_csb2crg0([], 16, 1, c);
dat2 = crg_read('demo1.crg');
```

```
data = crg_map_uv2uv(dat1, dat2, [200 1000], [50 150]); % u,v mapping
crg_show(data);
```

```
data = crg_map_xy2xy(dat1, dat2, [50 150], [20 50]); % inertial mapping
crg_show(data);
```







```
CRG comment data:

CRG minimal artificial road and flat surface
... curvature added
```

<unknown CRG file name>

14

Test5 (add curved crg)


```
c = { 3 { 0 -0.2/3 } ... % klothoide
      ; 5 {-0.2 0.4/5 } ... % turning klothoide
      ; 8 { 0.4 0.4/8 } ... % circle
    };
```


```
dat1 = crg_gen_csb2crg0([], 16, 1, c);
```

```
dat2 = crg_read('demo7.crg');
```

```
data = crg_map_uv2uv(dat1, dat2); % u,v mapping
crg_show(data);
```

```
data = crg_map_xy2xy(dat1, dat2); % inertial mapping
crg_show(data);
```





CRG information

[illegible]





```
CRG comment data:

CRG minimal artificial road and flat surface
... curvature added
```

<unknown CRG file name>


CRG reference line map

2011-08-08 11:19:16



<unknown CRG file name>

2011-08-08 11:19:34



```
CRG minimal artificial road and flat surface
... curvature added
```

<unknown CRG file name>

19

Test6 (adding real dataset)


```
c = { 3 { 0 -0.2/3 } ... % klothoide
      ; 5 {-0.2 0.4/5 } ... % turning klothoide
      ; 8 { 0.4 0.4/8 } ... % circle
    };
```


```
dat1 = crg_gen_csb2crg0([], 16, 1, c);
dat2 = crg_read('../crg-bin/belgian_block.crg');
```

```
dat2.mods.rptx = 1;
dat2.mods.rpty = 1;
dat4 = crg_mods(dat2);
```

```
data = crg_map_uv2uv(dat1, dat4); % u,v mapping
crg_show(data);
```

```
data = crg_map_xy2xy(dat1, dat4); % inertial mapping
crg_show(data);
```





CBG information

[illegible]





CRG comment data:

CRG minimal artificial road and flat surface
... curvature added

<unknown CBG file name>


CRG reference line mark

2011-08-08 11:19:48



<unknown CRG file name>

2011-08-08 11:19:54



```
CRG comment data:

CRG minimal artificial road and flat surface
... curvature added
```

<unknown CRG file name>

24