

Student ID: 1111426

Student Name: 廖婧婷

**Definition**A graph  $G(V, E)$  consists of:

1.  $V$  = set of vertices (nodes)
2.  $E$  = set of edges connecting vertices

**Real-world Motivation: Google Maps**

Concept	Google Maps Analogy
Node (Vertex)	Intersection or landmark (e.g., Neili Station, Yuan Ze University)
Edge (Link)	Road connecting two intersections
Weight	Distance, travel time, or cost, user 可自行定義
Path	Sequence of connected roads from start to destination
Graph traversal / search	Finding all reachable locations or the best route
Cycle	Round trip that ends at the starting point
Directed edge	One-way street
Undirected edge	Two-way road

**Classification**

Type	Description	Example
Undirected Graph	Edges have no direction	Friendship network
Directed Graph (Digraph)	Edges have direction	Instagram "following"
Weighted Graph	Each edge has a cost	Google Maps distance
Unweighted Graph	All edges equal	Board game map
Cyclic Graph	Has loops	City ring road
Acyclic Graph	No loops	Family tree
Connected Graph	Every node reachable	Road network
Disconnected Graph	Some nodes isolated	Islands without bridge

**Graph Representation in Memory**1. Adjacency matrix $V \times V$  的 二維陣列表示

代表 node

	0	1	2	3
0	0	0	1	0
1	0	0	1	1
2	0	0	0	1
3	1	0	0	0

1: 有連, 有連接  
0: 無連接

$O(|V|^2)$

查詢:  $O(1)$ 

適用: Dense graph

空間效率: 較差, 即使很少, 仍需  $|V|^2$ 2. Adjacency List

使用 array 來 store 頂點, array 中的元素指向 link list, 像 hash table

$O(|V| + |E|)$  查詢: 慢, 需看整個 link list

適用: sparse graph

空間效率: good! 只 store real 連



## Graph Traversal

### 1. Graph vs. Tree

The Same: tree 是 graph 的一種

都由 nodes, edges 組成

都可使用 DFS, BFS

Difference:

tree 不包含 cycles, graph 可多個點 connect, tree 有 root node

邊的數量: tree:  $N$  個 nodes,  $N-1$  個邊; graph:  $0 \sim \frac{N(N-1)}{2}$


### 2. Depth-First Search (DFS)

用 stack 和 recursion 實現。

1. 從 start node 開始 (標記)
2. 訪問這個 node 第一個未標記的鄰居
3. 從新鄰居 node 重複 ②, 直到 '到達 leave 節點' ②. 所有鄰居皆標記
4. Back track 到前一個 node, check 是否有未標記鄰居

深度優先

應用: path finding, Topological sorting, cycle detection




### 3. Bread-First Search (BFS)

使用 Queue

1. start node 開始, 並標記後放入隊列中
2. 從隊列中取出一個 node
3. 訪問這個 node 所有未訪問的鄰居, 標記後放入隊列
4. 重複 ② ③

應用: 找最短 path, 連通分量的識別



by level  
去 search