

Your Piling Up! submission got 50.00 points. [Share](#)[Tweet](#)[Try the Next Challenge](#) | [Try a Random Challenge](#)

# Piling Up!

 by [sandyeeep](#)

Problem

Submissions

Leaderboard

Discussions

Editorial

There is a horizontal row of  $n$  cubes. The length of each cube is given. You need to create a new vertical pile of cubes. The new pile should follow these directions: if  $cube_i$  is on top of  $cube_j$  then  $sideLength_j \geq sideLength_i$ .

When stacking the cubes, you can only pick up either the leftmost or the rightmost cube each time. Print "Yes" if it is possible to stack the cubes. Otherwise, print "No". Do not print the quotation marks.

## Input Format

The first line contains a single integer  $T$ , the number of test cases.

For each test case, there are  $2$  lines.

The first line of each test case contains  $n$ , the number of cubes.

The second line contains  $n$  space separated integers, denoting the  $sideLengths$  of each cube in that order.

## Constraints

$$1 \leq T \leq 5$$

$$1 \leq n \leq 10^5$$

$$1 \leq sideLength < 2^{31}$$

## Output Format

For each test case, output a single line containing either "Yes" or "No" without the quotes.

## Sample Input

```
2
6
4 3 2 1 3 4
3
1 3 2
```

## Sample Output

```
Yes
No
```

## Explanation

In the first test case, pick in this order: **left - 4, right - 4, left - 3, right - 3, left - 2, right - 1.**

In the second test case, no order gives an appropriate arrangement of vertical cubes. **3** will always come after either **1** or **2**.

[f](#) [t](#) [in](#)Submissions: [7021](#)

Max Score: 50

Difficulty: Medium

Rate This Challenge:

[More](#)Current Buffer (saved locally, editable)  

Python 3



```
1 from collections import deque
2
3 def dq_pop_max(dq):
4     try:
5         if dq[0]>=dq[-1]:
6             return dq.popleft()
7         else:
8             return dq.pop()
9     except IndexError:
10        return None
11
12 def check_stack_dq(dq):
13     cur_value = pop_value = dq_pop_max(dq)
14     while(pop_value):
15         if cur_value>=pop_value:
16             cur_value, pop_value = pop_value, dq_pop_max(dq)
17         else:
18             return 'No'
19     return 'Yes'
20
21 testcases = int(input().strip())
22 dq_list = []
23 for i in range(testcases):
24     num = int(input().strip())
25     dq_list.append(deque([int(x) for x in input().strip().split(' ')]))
26
27 for dq in dq_list:
28     print(check_stack_dq(dq))
```

Line: 25 Col: 72

 [Upload Code as File](#) ☐ Test against custom input

Run Code

Submit Code

**Congrats, you solved this challenge!**Challenge your friends:   

✓ Test Case #0

✓ Test Case #1

✓ Test Case #2

✓ Test Case #3

✓ Test Case #4

You've earned 50.00 points.

[Next Challenge](#)[Contest Calendar](#) | [Blog](#) | [Scoring](#) | [Environment](#) | [FAQ](#) | [About Us](#) | [Support](#) | [Careers](#) | [Terms Of Service](#) | [Privacy Policy](#) | [Request a Feature](#)