

Assignment 2: Coding Basics

Jingxin Liang

OVERVIEW

This exercise accompanies the lessons/labs in Environmental Data Analytics on coding basics.

Directions

1. Rename this file `<FirstLast>_A02_CodingBasics.Rmd` (replacing `<FirstLast>` with your first and last name).
2. Change “Student Name” on line 3 (above) with your name.
3. Work through the steps, **creating code and output** that fulfill each instruction.
4. Be sure to **answer the questions** in this assignment document.
5. When you have completed the assignment, **Knit** the text and code into a single PDF file.
6. After Knitting, submit the completed exercise (PDF file) to Canvas.

Basics, Part 1

1. Generate a sequence of numbers from one to 55, increasing by fives. Assign this sequence a name.

```
Sequen_1to55 <- seq(from=1, to=55, by=5)
```

2. Compute the mean and median of this sequence.

```
Ave_seq <- mean(Sequen_1to55) Ave_seq
```

```
Median <- median(Sequen_1to55) Median
```

3. Ask R to determine whether the mean is greater than the median.

```
Median < Ave_seq
```

4. Insert comments in your code to describe what you are doing.

```
#1. Create a sequence of numbers from 1 to 55, increasing by 5  
Sequen_1to55 <- seq(from=1, to=55, by=5)
```

```
#2. Calculate the mean and median of the sequence  
Ave_seq <- mean(Sequen_1to55)  
Ave_seq
```

```
## [1] 26
```

```
Median <- median(Sequen_1to55)
Median
```

```
## [1] 26
```

```
#3.Compare whether the median is less than the mean (returns TRUE or FALSE)
Median < Ave_seq
```

```
## [1] FALSE
```

Basics, Part 2

5. Create three vectors, each with four components, consisting of (a) student names, (b) test scores, and (c) whether they are on scholarship or not (TRUE or FALSE).

```
#(a) student names, character vector students <- c("Michelle", "Isabella", "Bella", "Molly")
```

(b) test scores, numeric vector

```
scores <- c(85, 92, 88, 76)
```

(c) scholarship status, logical vector

```
scholarship<- c(FALSE, TRUE, TRUE, FALSE) scholarship
```

6. Label each vector with a comment on what type of vector it is.
7. Combine each of the vectors into a data frame. Assign the data frame an informative name.

```
student_data <- data.frame(students, scores, scholarship) student_data
```

8. Label the columns of your data frame with informative titles.

```
student_data <- data.frame(Name=students, Scores=scores, Scholarship=scholarship) student_data
```

```
#(a) student names, character vector
students <- c("Michelle", "Isabella", "Bella", "Molly")
```

```
# (b) test scores, numeric vector
scores <- c(85, 92, 88, 76)
```

```
# (c) scholarship status, logical vector
scholarship<- c(FALSE, TRUE, TRUE, FALSE)
scholarship
```

```
## [1] FALSE TRUE TRUE FALSE
```

```
student_data <- data.frame(students, scores, scholarship)
student_data
```

```
##   students scores scholarship
## 1 Michelle     85         FALSE
## 2 Isabella     92          TRUE
## 3   Bella     88          TRUE
## 4   Molly     76         FALSE
```

```
student_data <- data.frame(Name=students, Scores=scores, Scholarship=scholarship)
student_data
```

```
##      Name Scores Scholarship
## 1 Michelle     85         FALSE
## 2 Isabella     92          TRUE
## 3   Bella     88          TRUE
## 4   Molly     76         FALSE
```

9. QUESTION: How is this data frame different from a matrix?

Answer: Matrix can only have one data type while data frame can have multiple different data types.

10. Create a function with one input. In this function, use `if...else` to evaluate the value of the input: if it is greater than 50, print the word “Pass”; otherwise print the word “Fail”.

```
greater_than5_1 <- function(number) { if ( number > 50) { print("Pass")} else { print("Fail") } }
greater_than5_1(52.5)
```

11. Create a second function that does the exact same thing as the previous one but uses `ifelse()` instead of `if...else`.

```
greater_than5_2 <- function(number) { ifelse(number > 50, "Pass", "Fail")} greater_than5_2(52.5)
```

12. Run both functions using the value 52.5 as the input

13. Run both functions using the **vector** of student test scores you created as the input. (Only one will work properly...)

```
#greater_than5_1 <- function(number) { # if ( number > 50) { # print("Pass")} # else { # print("Fail")}}
#greater_than5_1(scores)
greater_than5_2 <- function(number) { ifelse(number > 50, "Pass", "Fail") } greater_than5_2(scores)
```

#10. Create a function using if...else

```
greater_than5_1 <- function(number) {
  if ( number > 50) {
    print("Pass")}
  else {
    print("Fail")}
}
greater_than5_1(52.5)
```

```
## [1] "Pass"
```

```
#11. Create a function using ifelse()
```

```
greater_than5_2 <- function(number) {  
  ifelse(number > 50, "Pass", "Fail")}
```

```
greater_than5_2(52.5)
```

```
## [1] "Pass"
```

```
#12a. Run the first function with the value 52.5
```

```
greater_than5_1(52.5)
```

```
## [1] "Pass"
```

```
#12b. Run the second function with the value 52.5
```

```
greater_than5_2(52.5)
```

```
## [1] "Pass"
```

```
#13a. Run the first function with the vector of test scores
```

```
#greater_than5_1 <- function(number) {  
#   if ( number > 50) {  
#     print("Pass")}  
#   else {  
#     print("Fail")}}
```

```
#greater_than5_1(scores)
```

```
#13b. Run the second function with the vector of test scores
```

```
greater_than5_2 <- function(number) {  
  ifelse(number > 50, "Pass", "Fail")  
}
```

```
greater_than5_2(scores)
```

```
## [1] "Pass" "Pass" "Pass" "Pass"
```

14. QUESTION: Which option of `if...else` vs. `ifelse` worked? Why? (Hint: search the web for “R vectorization”)

Answer: The `ifelse` worked, since “`if..else`” can only have one condition.

NOTE Before knitting, you’ll need to comment out the call to the function in Q13 that does not work. (A document can’t knit if the code it contains causes an error!)