

---

# Amazon DynamoDB

## Developer Guide

### API Version 2012-08-10



## Amazon DynamoDB: Developer Guide

Copyright © 2022 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

## Table of Contents

What is Amazon DynamoDB .....	1
High availability and durability .....	1
Getting started with DynamoDB .....	1
How it works .....	2
Core components .....	2
DynamoDB API .....	10
Supported data types and naming rules .....	13
Read consistency .....	17
Read/write capacity mode .....	17
Table classes .....	22
Partitions and data distribution .....	22
From SQL to NoSQL .....	25
Relational or NoSQL? .....	25
Characteristics of databases .....	27
Creating a table .....	29
Getting information about a table .....	30
Writing data to a table .....	32
Reading data from a table .....	34
Managing indexes .....	40
Modifying data in a table .....	44
Deleting data from a table .....	46
Removing a table .....	48
Additional Amazon DynamoDB resources .....	49
Blog posts, repositories, and guides .....	49
Data modeling and design pattern presentations .....	49
Training courses .....	49
Tools for coding and visualization .....	50
Setting up DynamoDB .....	51
Setting up DynamoDB local (downloadable version) .....	51
Deploying .....	51
Usage notes .....	55
Setting up DynamoDB (web service) .....	58
Signing up for AWS .....	58
Getting an AWS access key .....	58
Configuring your credentials .....	59
Accessing DynamoDB .....	60
Using the console .....	60
Using the AWS CLI .....	61
Downloading and configuring the AWS CLI .....	61
Using the AWS CLI with DynamoDB .....	61
Using the AWS CLI with downloadable DynamoDB .....	62
Using the API .....	63
Using the NoSQL workbench .....	63
IP address ranges .....	63
Getting started with DynamoDB .....	64
Basic concepts .....	64
Prerequisites .....	64
Step 1: Create a table .....	64
Step 2: Write data .....	68
Step 3: Read data .....	71
Step 4: Update data .....	73
Step 5: Query data .....	75
Step 6: Create a global secondary index .....	78
Step 7: Query the global secondary index .....	81

Step 8: (Optional) clean up .....	84
Next steps .....	84
Getting started with the AWS SDKs .....	85
Create a table .....	85
Create a DynamoDB table using an AWS SDK .....	85
Write an item .....	95
Write an item to a DynamoDB table using an AWS SDK .....	95
Read an item .....	105
Read an item from a DynamoDB table using an AWS SDK .....	105
Update an item .....	113
Update an item in a DynamoDB table using an AWS SDK .....	113
Delete an item .....	123
Delete an item in a DynamoDB table using an AWS SDK .....	123
Query a table .....	131
Query a DynamoDB table using an AWS SDK .....	132
Scan a table .....	143
Scan a DynamoDB table using an AWS SDK .....	132
Working with AWS SDKs .....	152
Programming with DynamoDB .....	153
Overview of AWS SDK support for DynamoDB .....	153
Programmatic interfaces .....	155
Low-level interfaces .....	156
Document interfaces .....	157
Object persistence interface .....	157
Low-level API .....	159
Request format .....	161
Response format .....	161
Data type descriptors .....	162
Numeric data .....	163
Binary data .....	163
Error handling .....	163
Error components .....	163
Transactional errors .....	164
Error messages and codes .....	164
Error handling in your application .....	167
Error retries and exponential backoff .....	168
Batch operations and error handling .....	168
Higher-level programming interfaces .....	169
Java: DynamoDBMapper .....	170
.NET: Document model .....	217
.NET: Object persistence model .....	240
Running the code examples .....	268
Load sample data .....	269
Java code examples .....	274
.NET code examples .....	276
Working with DynamoDB .....	279
Working with Tables .....	279
Basic Operations on Tables .....	279
Considerations when changing read/write Capacity Mode .....	285
Considerations when choosing a table class .....	285
Provisioned Capacity Tables .....	286
Item Sizes and Formats .....	290
Managing throughput capacity with Auto Scaling .....	291
Working with Global Tables .....	305
Tagging resources .....	329
Working with tables: Java .....	332
Working with tables: .NET .....	337

Working with read and write operations .....	344
DynamoDB API .....	344
PartiQL query language .....	466
Working with indexes .....	497
Global secondary indexes .....	500
Local Secondary Indexes .....	539
Working with transactions .....	577
How it works .....	577
Using IAM with transactions .....	583
Example code .....	585
Working with streams .....	588
Options .....	588
Working with Kinesis Data Streams .....	589
Working with DynamoDB Streams .....	598
Working with On-Demand backup and restore .....	629
Using AWS Backup .....	630
Using DynamoDB backups .....	636
Working with point-in-time recovery .....	649
How it works .....	649
Before you begin .....	651
Restoring a table to a point in time .....	651
In-memory acceleration with DAX .....	655
Use cases for DAX .....	656
DAX usage notes .....	656
How it works .....	657
How DAX processes requests .....	658
Item cache .....	659
Query cache .....	660
DAX cluster components .....	660
Nodes .....	660
Clusters .....	661
Regions and availability zones .....	661
Parameter groups .....	662
Security groups .....	662
Cluster ARN .....	662
Cluster endpoint .....	662
Node endpoints .....	663
Subnet groups .....	663
Events .....	663
Maintenance window .....	663
Creating a DAX cluster .....	664
Creating an IAM service role for DAX to access DynamoDB .....	664
Using the AWS CLI .....	666
Using the console .....	670
Consistency models .....	672
Consistency among DAX cluster nodes .....	673
DAX item cache behavior .....	673
DAX query cache behavior .....	675
Strongly consistent and transactional reads .....	676
Negative caching .....	676
Strategies for writes .....	676
Developing with the DAX client .....	679
Tutorial: Running a sample application .....	679
Modifying an existing application to use DAX .....	711
Managing DAX clusters .....	712
IAM permissions for managing a DAX cluster .....	712
Scaling a DAX cluster .....	714

Customizing DAX cluster settings .....	715
Configuring TTL settings .....	715
Tagging support for DAX .....	716
AWS CloudTrail integration .....	717
Deleting a DAX cluster .....	717
Monitoring DAX .....	718
Monitoring tools .....	718
Monitoring with CloudWatch .....	719
Logging DAX operations using AWS CloudTrail .....	733
DAX T3/T2 burstable instances .....	733
DAX T2 instance family .....	733
DAX T3 instance family .....	733
DAX access control .....	734
IAM service role for DAX .....	734
IAM policy to allow DAX cluster access .....	735
Case study: Accessing DynamoDB and DAX .....	736
Access to DynamoDB, but no access with DAX .....	737
Access to DynamoDB and to DAX .....	739
Access to DynamoDB via DAX, but no direct access to DynamoDB .....	742
DAX encryption at rest .....	744
Enabling encryption at rest using the AWS Management Console .....	745
DAX encryption in transit .....	746
Using service-linked roles for DAX .....	747
Service-linked role permissions for DAX .....	747
Creating a service-linked role for DAX .....	748
Editing a service-linked role for DAX .....	748
Deleting a service-linked role for DAX .....	748
Accessing DAX across AWS accounts .....	749
Set up IAM .....	750
Set up a VPC .....	751
Modify the DAX client to allow cross-account access .....	753
DAX cluster sizing guide .....	756
Overview .....	756
Estimating traffic .....	757
Load testing .....	757
API reference .....	758
NoSQL Workbench .....	759
Download .....	759
Data modeler .....	760
Creating a new model .....	760
Importing an existing model .....	766
Exporting a model .....	769
Editing an existing model .....	771
Data visualizer .....	773
Adding sample data .....	774
Importing from CSV .....	775
Facets .....	776
Aggregate view .....	780
Committing a data model .....	781
Operation builder .....	786
Exploring datasets .....	786
Building operations .....	790
Exporting to CSV .....	807
Sample data models .....	808
Employee data model .....	808
Discussion forum data model .....	808
Music library data model .....	809

Ski resort data model .....	809
Credit card offers data model .....	809
Bookmarks data model .....	810
Release history .....	810
Code examples .....	812
Actions .....	813
Create a table .....	813
Delete a table .....	823
Delete an item from a table .....	829
Get a batch of items .....	837
Get an item from a table .....	841
Get information about a table .....	848
List tables .....	853
Put an item in a table .....	859
Query a table .....	868
Run a PartiQL statement .....	880
Run batches of PartiQL statements .....	889
Scan a table .....	902
Update an item in a table .....	910
Write a batch of items .....	921
Scenarios .....	928
Accelerate reads with DAX .....	928
Get started using tables, items, and queries .....	934
Query a table by using batches of PartiQL statements .....	991
Query a table using PartiQL .....	1023
Cross-service examples .....	1050
Build an app to submit data to a DynamoDB table .....	1050
Create a REST API to track COVID-19 data .....	1051
Create a messenger application .....	1052
Create a web application to track DynamoDB data .....	1053
Create a websocket chat application .....	1054
Detect PPE in images .....	1055
Invoke a Lambda function from a browser .....	1056
Save EXIF and other image information .....	1056
Use API Gateway to invoke a Lambda function .....	1057
Use Step Functions to invoke Lambda functions .....	1058
Use scheduled events to invoke a Lambda function .....	1059
Security .....	1061
Data protection .....	1061
Encryption at rest .....	1062
Data protection in DAX .....	1069
Internetwork traffic privacy .....	1069
Identity and access management .....	1070
Identity and access management .....	1070
Identity and access management in DAX .....	1100
Compliance validation .....	1100
Resilience .....	1101
Infrastructure security .....	1101
Using VPC endpoints .....	1101
Configuration and vulnerability analysis .....	1107
Security best practices .....	1108
Preventative security best practices .....	1108
Detective security best practices .....	1109
Monitoring .....	1112
Logging and monitoring in DynamoDB .....	1112
Monitoring tools .....	1113
Monitoring with Amazon CloudWatch .....	1114

Logging DynamoDB operations by using AWS CloudTrail .....	1133
Logging and monitoring in DAX .....	1149
Contributor Insights .....	1149
How it works .....	1149
Getting started .....	1153
Using IAM .....	1157
Best practices .....	1162
NoSQL design .....	1163
NoSQL vs. RDBMS .....	1163
Two key concepts .....	1164
General approach .....	1164
Partition key design .....	1165
Burst capacity .....	1165
Adaptive capacity .....	1165
Distributing workloads .....	1167
Write sharding .....	1167
Uploading data efficiently .....	1168
Sort key design .....	1169
Version control .....	1170
Secondary indexes .....	1171
General guidelines .....	1171
Sparse indexes .....	1173
Aggregation .....	1174
GSI overloading .....	1175
GSI sharding .....	1176
Creating a replica .....	1177
Large items .....	1178
Compression .....	1178
Using Amazon S3 .....	1178
Time series data .....	1179
Design pattern for time series data .....	1179
Time series table examples .....	1179
Many-to-many relationships .....	1180
Adjacency lists .....	1180
Materialized graphs .....	1181
Hybrid DynamoDB–RDBMS .....	1184
Not migrating .....	1184
Hybrid system implementation .....	1185
Relational modeling .....	1185
First steps .....	1187
Example .....	1188
Querying and scanning .....	1191
Scan performance .....	1191
Avoid spikes .....	1191
Parallel scans .....	1194
Integrating with other AWS services .....	1196
Integrating with Amazon Cognito .....	1196
Integrating with Amazon Redshift .....	1198
Integrating with Amazon EMR .....	1199
Overview .....	1199
Tutorial: Working with Amazon DynamoDB and Apache Hive .....	1200
Creating an external table in Hive .....	1206
Processing HiveQL statements .....	1208
Querying data in DynamoDB .....	1209
Copying data to and from Amazon DynamoDB .....	1210
Performance tuning .....	1220
Integrating with S3 .....	1223

Import from Amazon S3 .....	1224
Export to Amazon S3 .....	1234
Quotas and limits .....	1242
Read/write capacity mode and throughput .....	1242
Capacity unit sizes (for provisioned tables) .....	1242
Request unit sizes (for on-demand tables) .....	1242
Throughput default quotas .....	1243
Increasing or decreasing throughput (for provisioned tables) .....	1243
Tables .....	1244
Table size .....	1244
Maximum number of tables per account per region .....	1244
Global tables .....	1245
Secondary indexes .....	1245
Secondary indexes per table .....	1245
Projected Secondary Index attributes per table .....	1245
Partition keys and sort keys .....	1246
Partition key length .....	1246
Partition key values .....	1246
Sort key length .....	1246
Sort key values .....	1246
Naming rules .....	1246
Table names and Secondary Index names .....	1246
Attribute names .....	1246
Data types .....	1247
String .....	1247
Number .....	1247
Binary .....	1247
Items .....	1247
Item size .....	1247
Item size for tables with Local Secondary Indexes .....	1248
Attributes .....	1248
Attribute name-value pairs per item .....	1248
Number of values in list, map, or set .....	1248
Attribute values .....	1248
Nested attribute depth .....	1248
Expression parameters .....	1248
Lengths .....	1248
Operators and operands .....	1248
Reserved words .....	1249
DynamoDB transactions .....	1249
DynamoDB Streams .....	1249
Simultaneous readers of a shard in DynamoDB Streams .....	1249
Maximum write capacity for a table with DynamoDB Streams enabled .....	1249
DynamoDB Accelerator (DAX) .....	1250
AWS region availability .....	1250
Nodes .....	1250
Parameter groups .....	1250
Subnet groups .....	1250
API-specific limits .....	1250
DynamoDB encryption at rest .....	1251
Table export to Amazon S3 .....	1252
API reference .....	1253
Appendix .....	1254
Troubleshooting SSL/TLS connection establishment issues .....	1254
Testing your application or service .....	1254
Testing your client browser .....	1255
Updating your software application client .....	1255

Updating your client browser .....	1255
Manually updating your certificate bundle .....	1255
Example tables and data .....	1256
Sample data files .....	1256
Creating example tables and uploading data .....	1265
Creating example tables and uploading data - Java .....	1265
Creating example tables and uploading data - .NET .....	1272
Example application using AWS SDK for Python (Boto3) .....	1281
Step 1: Deploy and test locally .....	1281
Step 2: Examine the data model and implementation details .....	1285
Step 3: Deploy in production .....	1293
Step 4: Clean up resources .....	1299
Integrating with AWS Data Pipeline .....	1300
Prerequisites to export and import data .....	1302
Exporting data from DynamoDB to Amazon S3 .....	1306
Importing data from Amazon S3 to DynamoDB .....	1307
Troubleshooting .....	1308
Predefined templates for AWS Data Pipeline and DynamoDB .....	1309
Amazon DynamoDB Storage Backend for Titan .....	1309
Reserved words in DynamoDB .....	1310
Legacy conditional parameters .....	1318
AttributesToGet .....	1319
AttributeUpdates .....	1320
ConditionalOperator .....	1322
Expected .....	1322
KeyConditions .....	1326
QueryFilter .....	1328
ScanFilter .....	1329
Writing conditions with legacy parameters .....	1330
Previous low-level API version (2011-12-05) .....	1336
Batch.GetItem .....	1336
BatchWriteItem .....	1341
CreateTable .....	1346
DeleteItem .....	1351
DeleteTable .....	1355
DescribeTables .....	1358
GetItem .....	1361
ListTables .....	1364
PutItem .....	1366
Query .....	1371
Scan .....	1380
UpdateItem .....	1390
UpdateTable .....	1396
AWS SDK for Java 1.x examples .....	1399
DAX and Java SDK v1 .....	1399
Modifying an existing SDK for Java 1.x application to use DAX .....	1408
Querying global secondary indexes with SDK for Java 1.x .....	1412
Document history .....	1415
Earlier updates .....	1422

# What is Amazon DynamoDB?

Welcome to the Amazon DynamoDB Developer Guide.

Amazon DynamoDB is a fully managed NoSQL database service that provides fast and predictable performance with seamless scalability. DynamoDB lets you offload the administrative burdens of operating and scaling a distributed database so that you don't have to worry about hardware provisioning, setup and configuration, replication, software patching, or cluster scaling. DynamoDB also offers encryption at rest, which eliminates the operational burden and complexity involved in protecting sensitive data. For more information, see [DynamoDB encryption at rest \(p. 1062\)](#).

With DynamoDB, you can create database tables that can store and retrieve any amount of data and serve any level of request traffic. You can scale up or scale down your tables' throughput capacity without downtime or performance degradation. You can use the AWS Management Console to monitor resource utilization and performance metrics.

DynamoDB provides on-demand backup capability. It allows you to create full backups of your tables for long-term retention and archival for regulatory compliance needs. For more information, see [Using On-Demand backup and restore for DynamoDB \(p. 629\)](#).

You can create on-demand backups and enable point-in-time recovery for your Amazon DynamoDB tables. Point-in-time recovery helps protect your tables from accidental write or delete operations. With point-in-time recovery, you can restore a table to any point in time during the last 35 days. For more information, see [Point-in-time recovery: How it works \(p. 649\)](#).

DynamoDB allows you to delete expired items from tables automatically to help you reduce storage usage and the cost of storing data that is no longer relevant. For more information, see [Expiring items by using DynamoDB Time to Live \(TTL\) \(p. 378\)](#).

## High availability and durability

DynamoDB automatically spreads the data and traffic for your tables over a sufficient number of servers to handle your throughput and storage requirements, while maintaining consistent and fast performance. All of your data is stored on solid-state disks (SSDs) and is automatically replicated across multiple Availability Zones in an AWS Region, providing built-in high availability and data durability. You can use global tables to keep DynamoDB tables in sync across AWS Regions. For more information, see [Global tables - multi-Region replication for DynamoDB \(p. 305\)](#).

## Getting started with DynamoDB

We recommend that you begin by reading the following sections:

- [Amazon DynamoDB: How it works \(p. 2\)](#)—To learn essential DynamoDB concepts.
- [Setting up DynamoDB \(p. 51\)](#)—To learn how to set up DynamoDB (the downloadable version or the web service).
- [Accessing DynamoDB \(p. 60\)](#)—To learn how to access DynamoDB using the console, AWS CLI, or API.

To get started quickly with DynamoDB, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

To learn more about application development, see the following:

- [Programming with DynamoDB and the AWS SDKs \(p. 153\)](#)
- [Working with tables, items, queries, scans, and indexes \(p. 279\)](#)

To quickly find recommendations for maximizing performance and minimizing throughput costs, see [Best practices for designing and architecting with DynamoDB \(p. 1162\)](#). To learn how to tag DynamoDB resources, see [Adding tags and labels to resources \(p. 329\)](#).

For best practices, how-to guides, and tools, see [Amazon DynamoDB resources](#).

You can use AWS Database Migration Service (AWS DMS) to migrate data from a relational database or MongoDB to a DynamoDB table. For more information, see the [AWS Database Migration Service User Guide](#).

To learn how to use MongoDB as a migration source, see [Using MongoDB as a source for AWS Database Migration Service](#). To learn how to use DynamoDB as a migration target, see [Using an Amazon DynamoDB database as a target for AWS Database Migration Service](#).

## Amazon DynamoDB: How it works

The following sections provide an overview of Amazon DynamoDB service components and how they interact.

After you read this introduction, try working through the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section, which walks you through the process of creating sample tables, uploading data, and performing some basic database operations.

For language-specific tutorials with sample code, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

### Topics

- [Core components of Amazon DynamoDB \(p. 2\)](#)
- [DynamoDB API \(p. 10\)](#)
- [Supported data types and naming rules in Amazon DynamoDB \(p. 13\)](#)
- [Read consistency \(p. 17\)](#)
- [Read/write capacity mode \(p. 17\)](#)
- [Table classes \(p. 22\)](#)
- [Partitions and data distribution \(p. 22\)](#)

## Core components of Amazon DynamoDB

In DynamoDB, tables, items, and attributes are the core components that you work with. A *table* is a collection of *items*, and each item is a collection of *attributes*. DynamoDB uses primary keys to uniquely identify each item in a table and secondary indexes to provide more querying flexibility. You can use DynamoDB Streams to capture data modification events in DynamoDB tables.

There are limits in DynamoDB. For more information, see [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#).

The following video will give you an introductory look at tables, items, and attributes.

[Tables, items, and attributes](#)

**Topics**

- [Tables, items, and attributes \(p. 3\)](#)
- [Primary key \(p. 6\)](#)
- [Secondary indexes \(p. 7\)](#)
- [DynamoDB Streams \(p. 9\)](#)

## Tables, items, and attributes

The following are the basic DynamoDB components:

- **Tables** – Similar to other database systems, DynamoDB stores data in tables. A *table* is a collection of data. For example, see the example table called *People* that you could use to store personal contact information about friends, family, or anyone else of interest. You could also have a *Cars* table to store information about vehicles that people drive.
- **Items** – Each table contains zero or more items. An *item* is a group of attributes that is uniquely identifiable among all of the other items. In a *People* table, each item represents a person. For a *Cars* table, each item represents one vehicle. Items in DynamoDB are similar in many ways to rows, records, or tuples in other database systems. In DynamoDB, there is no limit to the number of items you can store in a table.
- **Attributes** – Each item is composed of one or more attributes. An *attribute* is a fundamental data element, something that does not need to be broken down any further. For example, an item in a *People* table contains attributes called *PersonID*, *LastName*, *FirstName*, and so on. For a *Department* table, an item might have attributes such as *DepartmentID*, *Name*, *Manager*, and so on. Attributes in DynamoDB are similar in many ways to fields or columns in other database systems.

The following diagram shows a table named *People* with some example items and attributes.

## People

```
{  
    "PersonID": 101,  
    "LastName": "Smith",  
    "FirstName": "Fred",  
    "Phone": "555-4321"  
}
```

```
{  
    "PersonID": 102,  
    "LastName": "Jones",  
    "FirstName": "Mary",  
    "Address": {  
        "Street": "123 Main",  
        "City": "Anytown",  
        "State": "OH",  
        "ZIPCode": 12345  
    }  
}
```

```
{  
    "PersonID": 103,  
    "LastName": "Stephens",  
    "FirstName": "Howard",  
    "Address": {  
        "Street": "123 Main",  
        "City": "London",  
        "PostalCode": "ER3 5K8"  
    },  
    "FavoriteColor": "Blue"  
}
```

Note the following about the *People* table:

- Each item in the table has a unique identifier, or primary key, that distinguishes the item from all of the others in the table. In the *People* table, the primary key consists of one attribute (*PersonID*).
- Other than the primary key, the *People* table is schemaless, which means that neither the attributes nor their data types need to be defined beforehand. Each item can have its own distinct attributes.
- Most of the attributes are *scalar*, which means that they can have only one value. Strings and numbers are common examples of scalars.

- Some of the items have a nested attribute (*Address*). DynamoDB supports nested attributes up to 32 levels deep.

The following is another example table named *Music* that you could use to keep track of your music collection.

**Music**

<pre>{     "Artist": "No One You Know",     "SongTitle": "My Dog Spot",     "AlbumTitle": "Hey Now",     "Price": 1.98,     "Genre": "Country",     "CriticRating": 8.4 }</pre>
<pre>{     "Artist": "No One You Know",     "SongTitle": "Somewhere Down The Road",     "AlbumTitle": "Somewhat Famous",     "Genre": "Country",     "CriticRating": 8.4,     "Year": 1984 }</pre>
<pre>{     "Artist": "The Acme Band",     "SongTitle": "Still in Love",     "AlbumTitle": "The Buck Starts Here",     "Price": 2.47,     "Genre": "Rock",     "PromotionInfo": {         "RadioStationsPlaying": [             "KHCN",             "KQBX",             "WTNR",             "WJZH"         ],         "TourDates": {             "Seattle": "20150625",             "Cleveland": "20150630"         },         "Rotation": "Heavy"     } }</pre>
<pre>{     "Artist": "The Acme Band",     "SongTitle": "Look Out, World",     "AlbumTitle": "The Buck Starts Here",     "Price": 0.99,     "Genre": "Rock" }</pre>

Note the following about the *Music* table:

- The primary key for *Music* consists of two attributes (*Artist* and *SongTitle*). Each item in the table must have these two attributes. The combination of *Artist* and *SongTitle* distinguishes each item in the table from all of the others.

- Other than the primary key, the *Music* table is schemaless, which means that neither the attributes nor their data types need to be defined beforehand. Each item can have its own distinct attributes.
- One of the items has a nested attribute (*PromotionInfo*), which contains other nested attributes. DynamoDB supports nested attributes up to 32 levels deep.

For more information, see [Working with tables and data in DynamoDB \(p. 279\)](#).

## Primary key

When you create a table, in addition to the table name, you must specify the primary key of the table. The primary key uniquely identifies each item in the table, so that no two items can have the same key.

DynamoDB supports two different kinds of primary keys:

- **Partition key** – A simple primary key, composed of one attribute known as the *partition key*.

DynamoDB uses the partition key's value as input to an internal hash function. The output from the hash function determines the partition (physical storage internal to DynamoDB) in which the item will be stored.

In a table that has only a partition key, no two items can have the same partition key value.

The *People* table described in [Tables, items, and attributes \(p. 3\)](#) is an example of a table with a simple primary key (*PersonID*). You can access any item in the *People* table directly by providing the *PersonId* value for that item.

- **Partition key and sort key** – Referred to as a *composite primary key*, this type of key is composed of two attributes. The first attribute is the *partition key*, and the second attribute is the *sort key*.

DynamoDB uses the partition key value as input to an internal hash function. The output from the hash function determines the partition (physical storage internal to DynamoDB) in which the item will be stored. All items with the same partition key value are stored together, in sorted order by sort key value.

In a table that has a partition key and a sort key, it's possible for multiple items to have the same partition key value. However, those items must have different sort key values.

The *Music* table described in [Tables, items, and attributes \(p. 3\)](#) is an example of a table with a composite primary key (*Artist* and *SongTitle*). You can access any item in the *Music* table directly, if you provide the *Artist* and *SongTitle* values for that item.

A composite primary key gives you additional flexibility when querying data. For example, if you provide only the value for *Artist*, DynamoDB retrieves all of the songs by that artist. To retrieve only a subset of songs by a particular artist, you can provide a value for *Artist* along with a range of values for *SongTitle*.

### Note

The partition key of an item is also known as its *hash attribute*. The term *hash attribute* derives from the use of an internal hash function in DynamoDB that evenly distributes data items across partitions, based on their partition key values.

The sort key of an item is also known as its *range attribute*. The term *range attribute* derives from the way DynamoDB stores items with the same partition key physically close together, in sorted order by the sort key value.

Each primary key attribute must be a scalar (meaning that it can hold only a single value). The only data types allowed for primary key attributes are string, number, or binary. There are no such restrictions for other, non-key attributes.

## Secondary indexes

You can create one or more secondary indexes on a table. A *secondary index* lets you query the data in the table using an alternate key, in addition to queries against the primary key. DynamoDB doesn't require that you use indexes, but they give your applications more flexibility when querying your data. After you create a secondary index on a table, you can read data from the index in much the same way as you do from the table.


DynamoDB supports two kinds of indexes:

- Global secondary index – An index with a partition key and sort key that can be different from those on the table.
- Local secondary index – An index that has the same partition key as the table, but a different sort key.

Each table in DynamoDB has a quota of 20 global secondary indexes (default quota) and 5 local secondary indexes.

In the example *Music* table shown previously, you can query data items by *Artist* (partition key) or by *Artist* and *SongTitle* (partition key and sort key). What if you also wanted to query the data by *Genre* and *AlbumTitle*? To do this, you could create an index on *Genre* and *AlbumTitle*, and then query the index in much the same way as you'd query the *Music* table.

The following diagram shows the example *Music* table, with a new index called *GenreAlbumTitle*. In the index, *Genre* is the partition key and *AlbumTitle* is the sort key.



Note the following about the `GenreAlbumTitle` index:

- Every index belongs to a table, which is called the *base table* for the index. In the preceding example, `Music` is the base table for the `GenreAlbumTitle` index.
- DynamoDB maintains indexes automatically. When you add, update, or delete an item in the base table, DynamoDB adds, updates, or deletes the corresponding item in any indexes that belong to that table.
- When you create an index, you specify which attributes will be copied, or *projected*, from the base table to the index. At a minimum, DynamoDB projects the key attributes from the base table into the index. This is the case with `GenreAlbumTitle`, where only the key attributes from the `Music` table are projected into the index.

You can query the *GenreAlbumTitle* index to find all albums of a particular genre (for example, all *Rock* albums). You can also query the index to find all albums within a particular genre that have certain album titles (for example, all *Country* albums with titles that start with the letter H).

For more information, see [Improving data access with secondary indexes \(p. 497\)](#).

## DynamoDB Streams


DynamoDB Streams is an optional feature that captures data modification events in DynamoDB tables. The data about these events appear in the stream in near-real time, and in the order that the events occurred.

Each event is represented by a *stream record*. If you enable a stream on a table, DynamoDB Streams writes a stream record whenever one of the following events occurs:

- A new item is added to the table: The stream captures an image of the entire item, including all of its attributes.
- An item is updated: The stream captures the "before" and "after" image of any attributes that were modified in the item.
- An item is deleted from the table: The stream captures an image of the entire item before it was deleted.

Each stream record also contains the name of the table, the event timestamp, and other metadata. Stream records have a lifetime of 24 hours; after that, they are automatically removed from the stream.

You can use DynamoDB Streams together with AWS Lambda to create a *trigger*—code that runs automatically whenever an event of interest appears in a stream. For example, consider a *Customers* table that contains customer information for a company. Suppose that you want to send a "welcome" email to each new customer. You could enable a stream on that table, and then associate the stream with a Lambda function. The Lambda function would run whenever a new stream record appears, but only process new items added to the *Customers* table. For any item that has an `EmailAddress` attribute, the Lambda function would invoke Amazon Simple Email Service (Amazon SES) to send an email to that address.



#### Note

In this example, the last customer, Craig Roe, will not receive an email because he doesn't have an `EmailAddress`.

In addition to triggers, DynamoDB Streams enables powerful solutions such as data replication within and across AWS Regions, materialized views of data in DynamoDB tables, data analysis using Kinesis materialized views, and much more.

For more information, see [Change data capture for DynamoDB Streams \(p. 598\)](#).

## DynamoDB API

To work with Amazon DynamoDB, your application must use a few simple API operations. The following is a summary of these operations, organized by category.

### Topics

- [Control plane \(p. 10\)](#)
- [Data plane \(p. 11\)](#)
- [DynamoDB Streams \(p. 12\)](#)
- [Transactions \(p. 12\)](#)

## Control plane

*Control plane* operations let you create and manage DynamoDB tables. They also let you work with indexes, streams, and other objects that are dependent on tables.

- `CreateTable` – Creates a new table. Optionally, you can create one or more secondary indexes, and enable DynamoDB Streams for the table.

- `DescribeTable` – Returns information about a table, such as its primary key schema, throughput settings, and index information.
- `ListTables` – Returns the names of all of your tables in a list.
- `UpdateTable` – Modifies the settings of a table or its indexes, creates or removes new indexes on a table, or modifies DynamoDB Streams settings for a table.
- `DeleteTable` – Removes a table and all of its dependent objects from DynamoDB.

## Data plane

*Data plane* operations let you perform create, read, update, and delete (also called *CRUD*) actions on data in a table. Some of the data plane operations also let you read data from a secondary index.

You can use [PartiQL - a SQL-compatible query language for Amazon DynamoDB \(p. 466\)](#), to perform these CRUD operations or you can use DynamoDB's classic CRUD APIs that separates each operation into a distinct API call.

### PartiQL - A SQL-compatible query language

- `ExecuteStatement` – Reads multiple items from a table. You can also write or update a single item from a table. When writing or updating a single item, you must specify the primary key attributes.
- `BatchExecuteStatement` – Writes, updates or reads multiple items from a table. This is more efficient than `ExecuteStatement` because your application only needs a single network round trip to write or read the items.

## Classic APIs

### Creating data

- `PutItem` – Writes a single item to a table. You must specify the primary key attributes, but you don't have to specify other attributes.
- `BatchWriteItem` – Writes up to 25 items to a table. This is more efficient than calling `PutItem` multiple times because your application only needs a single network round trip to write the items. You can also use `BatchWriteItem` for deleting multiple items from one or more tables.

### Reading data

- `GetItem` – Retrieves a single item from a table. You must specify the primary key for the item that you want. You can retrieve the entire item, or just a subset of its attributes.
- `BatchGetItem` – Retrieves up to 100 items from one or more tables. This is more efficient than calling `GetItem` multiple times because your application only needs a single network round trip to read the items.
- `Query` – Retrieves all items that have a specific partition key. You must specify the partition key value. You can retrieve entire items, or just a subset of their attributes. Optionally, you can apply a condition to the sort key values so that you only retrieve a subset of the data that has the same partition key. You can use this operation on a table, provided that the table has both a partition key and a sort key. You can also use this operation on an index, provided that the index has both a partition key and a sort key.
- `Scan` – Retrieves all items in the specified table or index. You can retrieve entire items, or just a subset of their attributes. Optionally, you can apply a filtering condition to return only the values that you are interested in and discard the rest.

## Updating data

- `UpdateItem` – Modifies one or more attributes in an item. You must specify the primary key for the item that you want to modify. You can add new attributes and modify or remove existing attributes. You can also perform conditional updates, so that the update is only successful when a user-defined condition is met. Optionally, you can implement an atomic counter, which increments or decrements a numeric attribute without interfering with other write requests.

## Deleting data

- `DeleteItem` – Deletes a single item from a table. You must specify the primary key for the item that you want to delete.
- `BatchWriteItem` – Deletes up to 25 items from one or more tables. This is more efficient than calling `DeleteItem` multiple times because your application only needs a single network round trip to delete the items. You can also use `BatchWriteItem` for adding multiple items to one or more tables.

### Note

You can use `BatchWriteItem` to both create data and delete data.

## DynamoDB Streams

*DynamoDB Streams* operations let you enable or disable a stream on a table, and allow access to the data modification records contained in a stream.

- `ListStreams` – Returns a list of all your streams, or just the stream for a specific table.
- `DescribeStream` – Returns information about a stream, such as its Amazon Resource Name (ARN) and where your application can begin reading the first few stream records.
- `GetShardIterator` – Returns a *shard iterator*, which is a data structure that your application uses to retrieve the records from the stream.
- `GetRecords` – Retrieves one or more stream records, using a given shard iterator.

## Transactions

*Transactions* provide atomicity, consistency, isolation, and durability (ACID) enabling you to maintain data correctness in your applications more easily.

You can use [PartiQL - a SQL-compatible query language for Amazon DynamoDB \(p. 466\)](#), to perform transactional operations or you can use DynamoDB's classic CRUD APIs that separates each operation into a distinct API call.

## PartiQL - A SQL-compatible query language

- `ExecuteTransaction` – A batch operation that allows CRUD operations to multiple items both within and across tables with a guaranteed all-or-nothing result.

## Classic APIs

- `TransactWriteItems` – A batch operation that allows `Put`, `Update`, and `Delete` operations to multiple items both within and across tables with a guaranteed all-or-nothing result.
- `TransactGetItems` – A batch operation that allows `Get` operations to retrieve multiple items from one or more tables.

# Supported data types and naming rules in Amazon DynamoDB

This section describes the Amazon DynamoDB naming rules and the various data types that DynamoDB supports. There are limits that apply to data types. For more information, see [Data types \(p. 1247\)](#).

## Topics

- [Naming rules \(p. 13\)](#)
- [Data types \(p. 13\)](#)

## Naming rules

Tables, attributes, and other objects in DynamoDB must have names. Names should be meaningful and concise—for example, names such as *Products*, *Books*, and *Authors* are self-explanatory.

The following are the naming rules for DynamoDB:

- All names must be encoded using UTF-8, and are case-sensitive.
- Table names and index names must be between 3 and 255 characters long, and can contain only the following characters:
  - a–z
  - A–Z
  - 0–9
  - \_ (underscore)
  - – (dash)
  - . (dot)
- Attribute names must be at least one character long, but no greater than 64 KB long.

The following are the exceptions. These attribute names must be no greater than 255 characters long:

- Secondary index partition key names.
- Secondary index sort key names.
- The names of any user-specified projected attributes (applicable only to local secondary indexes).

## Reserved words and special characters

DynamoDB has a list of reserved words and special characters. For a complete list of reserved words in DynamoDB, see [Reserved words in DynamoDB \(p. 1310\)](#). Also, the following characters have special meaning in DynamoDB: # (hash) and : (colon).

Although DynamoDB allows you to use these reserved words and special characters for names, we recommend that you avoid doing so because you have to define placeholder variables whenever you use these names in an expression. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#).

## Data types

DynamoDB supports many different data types for attributes within a table. They can be categorized as follows:

- **Scalar Types** – A scalar type can represent exactly one value. The scalar types are number, string, binary, Boolean, and null.

- **Document Types** – A document type can represent a complex structure with nested attributes, such as you would find in a JSON document. The document types are list and map.
  - **Set Types** – A set type can represent multiple scalar values. The set types are string set, number set, and binary set.

When you create a table or a secondary index, you must specify the names and data types of each primary key attribute (partition key and sort key). Furthermore, each primary key attribute must be defined as type string, number, or binary.

DynamoDB is a NoSQL database and is *schemaless*. This means that, other than the primary key attributes, you don't have to define any attributes or data types when you create tables. By comparison, relational databases require you to define the names and data types of each column when you create a table.

The following are descriptions of each data type, along with examples in JSON format.

## Scalar types

The scalar types are number, string, binary, Boolean, and null.

## Number

Numbers can be positive, negative, or zero. Numbers can have up to 38 digits of precision. Exceeding this results in an exception.



In DynamoDB, numbers are represented as variable length. Leading and trailing zeroes are trimmed.

All numbers are sent across the network to DynamoDB as strings, to maximize compatibility across languages and libraries. However, DynamoDB treats them as number type attributes for mathematical operations.

## Note

If number precision is important, you should pass numbers to DynamoDB using strings that you convert from the number type.

You can use the number data type to represent a date or a timestamp. One way to do this is by using epoch time—the number of seconds since 00:00:00 UTC on 1 January 1970. For example, the epoch time 1437136300 represents 12:31:40 PM UTC on 17 July 2015.

For more information, see [http://en.wikipedia.org/wiki/Unix\\_time](http://en.wikipedia.org/wiki/Unix_time).

## String

Strings are Unicode with UTF-8 binary encoding. The minimum length of a string can be zero, if the attribute is not used as a key for an index or table, and is constrained by the maximum DynamoDB item size limit of 400 KB.

The following additional constraints apply to primary key attributes that are defined as type string:

- For a simple primary key, the maximum length of the first attribute value (the partition key) is 2048 bytes.
  - For a composite primary key, the maximum length of the second attribute value (the sort key) is 1024 bytes.

DynamoDB collates and compares strings using the bytes of the underlying UTF-8 string encoding. For example, "a" (0x61) is greater than "A" (0x41), and "ż" (0xC2BF) is greater than "z" (0x7A).

You can use the string data type to represent a date or a timestamp. One way to do this is by using ISO 8601 strings, as shown in these examples:

- 2016-02-15
- 2015-12-21T17:42:34Z
- 20150311T122706Z

For more information, see [http://en.wikipedia.org/wiki/ISO\\_8601](http://en.wikipedia.org/wiki/ISO_8601).

#### Note

Unlike conventional relational databases, DynamoDB does not natively support a date and time data type. It can be useful instead to store data and time data as a number data type, using Unix epoch time.

#### Binary

Binary type attributes can store any binary data, such as compressed text, encrypted data, or images. Whenever DynamoDB compares binary values, it treats each byte of the binary data as unsigned.

The length of a binary attribute can be zero, if the attribute is not used as a key for an index or table, and is constrained by the maximum DynamoDB item size limit of 400 KB.

If you define a primary key attribute as a binary type attribute, the following additional constraints apply:

- For a simple primary key, the maximum length of the first attribute value (the partition key) is 2048 bytes.
- For a composite primary key, the maximum length of the second attribute value (the sort key) is 1024 bytes.

Your applications must encode binary values in base64-encoded format before sending them to DynamoDB. Upon receipt of these values, DynamoDB decodes the data into an unsigned byte array and uses that as the length of the binary attribute.

The following example is a binary attribute, using base64-encoded text.

```
dGhpcyB0ZXh0IGlzIGJhc2U2NC1lbmNvZGVk
```

#### Boolean

A Boolean type attribute can store either `true` or `false`.

#### Null

Null represents an attribute with an unknown or undefined state.

#### Document types

The document types are list and map. These data types can be nested within each other, to represent complex data structures up to 32 levels deep.

There is no limit on the number of values in a list or a map, as long as the item containing the values fits within the DynamoDB item size limit (400 KB).

An attribute value can be an empty string or empty binary value if the attribute is not used for a table or index key. An attribute value cannot be an empty set (string set, number set, or binary set), however,

empty lists and maps are allowed. Empty string and binary values are allowed within lists and maps. For more information, see [Attributes \(p. 1248\)](#).

## List

A list type attribute can store an ordered collection of values. Lists are enclosed in square brackets: [ ... ]

A list is similar to a JSON array. There are no restrictions on the data types that can be stored in a list element, and the elements in a list element do not have to be of the same type.

The following example shows a list that contains two strings and a number.

```
FavoriteThings: ["Cookies", "Coffee", 3.14159]
```

### Note

DynamoDB lets you work with individual elements within lists, even if those elements are deeply nested. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

## Map

A map type attribute can store an unordered collection of name-value pairs. Maps are enclosed in curly braces: { ... }

A map is similar to a JSON object. There are no restrictions on the data types that can be stored in a map element, and the elements in a map do not have to be of the same type.

Maps are ideal for storing JSON documents in DynamoDB. The following example shows a map that contains a string, a number, and a nested list that contains another map.

```
{
    Day: "Monday",
    UnreadEmails: 42,
    ItemsOnMyDesk: [
        "Coffee Cup",
        "Telephone",
        {
            Pens: { Quantity : 3},
            Pencils: { Quantity : 2},
            Erasers: { Quantity : 1}
        }
    ]
}
```

### Note

DynamoDB lets you work with individual elements within maps, even if those elements are deeply nested. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

## Sets

DynamoDB supports types that represent sets of number, string, or binary values. All the elements within a set must be of the same type. For example, an attribute of type Number Set can only contain numbers; String Set can only contain strings; and so on.

There is no limit on the number of values in a set, as long as the item containing the values fits within the DynamoDB item size limit (400 KB).

Each value within a set must be unique. The order of the values within a set is not preserved. Therefore, your applications must not rely on any particular order of elements within the set. DynamoDB does not support empty sets, however, empty string and binary values are allowed within a set.

The following example shows a string set, a number set, and a binary set:

```
[ "Black", "Green", "Red"]  
[42.2, -19, 7.5, 3.14]  
[ "U3Vubnk=", "UmFpbnk=", "U25vd3k="]
```

## Read consistency

Amazon DynamoDB is available in multiple AWS Regions around the world. Each Region is independent and isolated from other AWS Regions. For example, if you have a table called *People* in the *us-east-2* Region and another table named *People* in the *us-west-2* Region, these are considered two entirely separate tables. For a list of all the AWS Regions in which DynamoDB is available, see [AWS Regions and Endpoints](#) in the *Amazon Web Services General Reference*.

Every AWS Region consists of multiple distinct locations called Availability Zones. Each Availability Zone is isolated from failures in other Availability Zones, and provides inexpensive, low-latency network connectivity to other Availability Zones in the same Region. This allows rapid replication of your data among multiple Availability Zones in a Region.

When your application writes data to a DynamoDB table and receives an HTTP 200 response (OK), the write has occurred and is durable. The data is eventually consistent across all storage locations, usually within one second or less.

DynamoDB supports *eventually consistent* and *strongly consistent* reads.

### Eventually Consistent Reads

When you read data from a DynamoDB table, the response might not reflect the results of a recently completed write operation. The response might include some stale data. If you repeat your read request after a short time, the response should return the latest data.

### Strongly Consistent Reads

When you request a strongly consistent read, DynamoDB returns a response with the most up-to-date data, reflecting the updates from all prior write operations that were successful. However, this consistency comes with some disadvantages:

- A strongly consistent read might not be available if there is a network delay or outage. In this case, DynamoDB may return a server error (HTTP 500).
- Strongly consistent reads may have higher latency than eventually consistent reads.
- Strongly consistent reads are not supported on global secondary indexes.
- Strongly consistent reads use more throughput capacity than eventually consistent reads. For details, see [Read/write capacity mode \(p. 17\)](#)

### Note

DynamoDB uses eventually consistent reads, unless you specify otherwise. Read operations (such as `GetItem`, `Query`, and `Scan`) provide a `ConsistentRead` parameter. If you set this parameter to true, DynamoDB uses strongly consistent reads during the operation.

## Read/write capacity mode

Amazon DynamoDB has two read/write capacity modes for processing reads and writes on your tables:

- On-demand
- Provisioned (default, free-tier eligible)

The read/write capacity mode controls how you are charged for read and write throughput and how you manage capacity. You can set the read/write capacity mode when creating a table or you can change it later.

Secondary indexes inherit the read/write capacity mode from the base table. For more information, see [Considerations when changing read/write Capacity Mode \(p. 285\)](#).

The following video will give you an introductory look at table capacity modes.

#### [Table capacity modes](#)

##### **Topics**

- [On-demand mode \(p. 18\)](#)
- [Provisioned mode \(p. 20\)](#)

## On-demand mode

Amazon DynamoDB on-demand is a flexible billing option capable of serving thousands of requests per second without capacity planning. DynamoDB on-demand offers pay-per-request pricing for read and write requests so that you pay only for what you use.

When you choose on-demand mode, DynamoDB instantly accommodates your workloads as they ramp up or down to any previously reached traffic level. If a workload's traffic level hits a new peak, DynamoDB adapts rapidly to accommodate the workload. Tables that use on-demand mode deliver the same single-digit millisecond latency, service-level agreement (SLA) commitment, and security that DynamoDB already offers. You can choose on-demand for both new and existing tables and you can continue using the existing DynamoDB APIs without changing code.

On-demand mode is a good option if any of the following are true:

- You create new tables with unknown workloads.
- You have unpredictable application traffic.
- You prefer the ease of paying for only what you use.

The request rate is only limited by the DynamoDB throughput default table quotas, but it can be raised upon request. For more information, see [Throughput default quotas \(p. 1243\)](#).

To get started with on-demand, you can create or update a table to use on-demand mode. For more information, see [Basic operations on DynamoDB tables \(p. 279\)](#).

You can switch between read/write capacity modes once every 24 hours. For issues you should consider when switching read/write capacity modes, see [Considerations when changing read/write Capacity Mode \(p. 285\)](#).

##### **Topics**

- [Read request units and write request units \(p. 19\)](#)
- [Peak traffic and scaling properties \(p. 19\)](#)
- [Initial throughput for on-demand capacity mode \(p. 19\)](#)
- [Table behavior while switching read/write capacity mode \(p. 20\)](#)

## Read request units and write request units

For on-demand mode tables, you don't need to specify how much read and write throughput you expect your application to perform. DynamoDB charges you for the reads and writes that your application performs on your tables in terms of read request units and write request units.

DynamoDB read requests can be either strongly consistent, eventually consistent, or transactional.

- A *strongly consistent* read request of up to 4 KB requires one read request unit.
- An *eventually consistent* read request of up to 4 KB requires one-half read request unit.
- A *transactional* read request of up to 4 KB requires two read request units.

If you need to read an item that is larger than 4 KB, DynamoDB needs additional read request units. The total number of read request units required depends on the item size, and whether you want an eventually consistent or strongly consistent read. For example, if your item size is 8 KB, you require 2 read request units to sustain one strongly consistent read, 1 read request unit if you choose eventually consistent reads, or 4 read request units for a transactional read request.

To learn more about DynamoDB read consistency models, see [Read consistency \(p. 17\)](#).

**Important**

If you perform a read operation on an item that *does not exist*, DynamoDB will still consume provisioned read throughput as outlined above.

One *write request unit* represents one write for an item up to 1 KB in size. If you need to write an item that is larger than 1 KB, DynamoDB needs to consume additional write request units. Transactional write requests require 2 write request units to perform one write for items up to 1 KB. The total number of write request units required depends on the item size. For example, if your item size is 2 KB, you require 2 write request units to sustain one write request or 4 write request units for a transactional write request.

For a list of AWS Regions where DynamoDB on-demand is available, see [Amazon DynamoDB Pricing](#).

## Peak traffic and scaling properties

DynamoDB tables using on-demand capacity mode automatically adapt to your application's traffic volume. On-demand capacity mode instantly accommodates up to double the previous peak traffic on a table. For example, if your application's traffic pattern varies between 25,000 and 50,000 strongly consistent reads per second where 50,000 reads per second is the previous traffic peak, on-demand capacity mode instantly accommodates sustained traffic of up to 100,000 reads per second. If your application sustains traffic of 100,000 reads per second, that peak becomes your new previous peak, enabling subsequent traffic to reach up to 200,000 reads per second.

If you need more than double your previous peak on table, DynamoDB automatically allocates more capacity as your traffic volume increases to help ensure that your workload does not experience throttling. However, throttling can occur if you exceed double your previous peak within 30 minutes. For example, if your application's traffic pattern varies between 25,000 and 50,000 strongly consistent reads per second where 50,000 reads per second is the previously reached traffic peak, DynamoDB recommends spacing your traffic growth over at least 30 minutes before driving more than 100,000 reads per second.

## Initial throughput for on-demand capacity mode

If you recently switched an existing table to on-demand capacity mode for the first time, or if you created a new table with on-demand capacity mode enabled, the table has the following previous peak settings, even though the table has not served traffic previously using on-demand capacity mode:

- **Newly created table with on-demand capacity mode:** The previous peak is 2,000 write request units or 6,000 read request units. You can drive up to double the previous peak immediately, which enables newly created on-demand tables to serve up to 4,000 write request units and 12,000 read request units.
- **Existing table switched to on-demand capacity mode:** The previous peak is half the maximum write capacity units and read capacity units provisioned since the table was created, or the settings for a newly created table with on-demand capacity mode, whichever is higher. In other words, your table will deliver at least as much throughput as it did prior to switching to on-demand capacity mode.

## Table behavior while switching read/write capacity mode

When you switch a table from provisioned capacity mode to on-demand capacity mode, DynamoDB makes several changes to the structure of your table and partitions. This process can take several minutes. During the switching period, your table delivers throughput that is consistent with the previously provisioned write capacity unit and read capacity unit amounts. When switching from on-demand capacity mode back to provisioned capacity mode, your table delivers throughput consistent with the previous peak reached when the table was set to on-demand capacity mode.

## Provisioned mode

If you choose provisioned mode, you specify the number of reads and writes per second that you require for your application. You can use auto scaling to adjust your table's provisioned capacity automatically in response to traffic changes. This helps you govern your DynamoDB use to stay at or below a defined request rate in order to obtain cost predictability.

Provisioned mode is a good option if any of the following are true:

- You have predictable application traffic.
- You run applications whose traffic is consistent or ramps gradually.
- You can forecast capacity requirements to control costs.

## Read capacity units and write capacity units

For provisioned mode tables, you specify throughput capacity in terms of read capacity units (RCUs) and write capacity units (WCUs):

- One *read capacity unit* represents one strongly consistent read per second, or two eventually consistent reads per second, for an item up to 4 KB in size. Transactional read requests require two read capacity units to perform one read per second for items up to 4 KB. If you need to read an item that is larger than 4 KB, DynamoDB must consume additional read capacity units. The total number of read capacity units required depends on the item size, and whether you want an eventually consistent or strongly consistent read. For example, if your item size is 8 KB, you require 2 read capacity units to sustain one strongly consistent read per second, 1 read capacity unit if you choose eventually consistent reads, or 4 read capacity units for a transactional read request. For more information, see [Capacity unit consumption for reads \(p. 287\)](#).

### Note

To learn more about DynamoDB read consistency models, see [Read consistency \(p. 17\)](#).

- One *write capacity unit* represents one write per second for an item up to 1 KB in size. If you need to write an item that is larger than 1 KB, DynamoDB must consume additional write capacity units. Transactional write requests require 2 write capacity units to perform one write per second for items up to 1 KB. The total number of write capacity units required depends on the item size. For example, if your item size is 2 KB, you require 2 write capacity units to sustain one write request per second or 4 write capacity units for a transactional write request. For more information, see [Capacity unit consumption for writes \(p. 288\)](#).

### Important

When calling `DescribeTable` on an on-demand table, read capacity units and write capacity units are set to 0.

If your application reads or writes larger items (up to the DynamoDB maximum item size of 400 KB), it will consume more capacity units.

For example, suppose that you create a provisioned table with 6 read capacity units and 6 write capacity units. With these settings, your application could do the following:

- Perform strongly consistent reads of up to 24 KB per second ( $4\text{ KB} \times 6$  read capacity units).
- Perform eventually consistent reads of up to 48 KB per second (twice as much read throughput).
- Perform transactional read requests of up to 12 KB per second.
- Write up to 6 KB per second ( $1\text{ KB} \times 6$  write capacity units).
- Perform transactional write requests of up to 3 KB per second.

For more information, see [Managing settings on DynamoDB provisioned capacity tables \(p. 286\)](#).

*Provisioned throughput* is the maximum amount of capacity that an application can consume from a table or index. If your application exceeds your provisioned throughput capacity on a table or index, it is subject to request throttling.

Throttling prevents your application from consuming too many capacity units.

When a request is throttled, it fails with an HTTP 400 code (Bad Request) and a `ProvisionedThroughputExceededException`. The AWS SDKs have built-in support for retrying throttled requests (see [Error retries and exponential backoff \(p. 168\)](#)), so you do not need to write this logic yourself.

You can use the AWS Management Console to monitor your provisioned and actual throughput, and to modify your throughput settings if necessary.

## DynamoDB auto scaling

DynamoDB auto scaling actively manages throughput capacity for tables and global secondary indexes. With auto scaling, you define a range (upper and lower limits) for read and write capacity units. You also define a target utilization percentage within that range. DynamoDB auto scaling seeks to maintain your target utilization, even as your application workload increases or decreases.

With DynamoDB auto scaling, a table or a global secondary index can increase its provisioned read and write capacity to handle sudden increases in traffic, without request throttling. When the workload decreases, DynamoDB auto scaling can decrease the throughput so that you don't pay for unused provisioned capacity.

### Note

If you use the AWS Management Console to create a table or a global secondary index, DynamoDB auto scaling is enabled by default.

You can manage auto scaling settings at any time by using the console, the AWS CLI, or one of the AWS SDKs.

For more information, see [Managing throughput capacity automatically with DynamoDB auto scaling \(p. 291\)](#).

## Reserved capacity

As a DynamoDB customer, you can purchase *reserved capacity* in advance for tables that use the DynamoDB Standard table class, as described at [Amazon DynamoDB Pricing](#). With reserved capacity, you pay a one-time upfront fee and commit to a minimum provisioned usage level over a period of time.

Your reserved capacity is billed at the hourly reserved capacity rate. By reserving your read and write capacity units ahead of time, you realize significant cost savings on your provisioned capacity costs. Any capacity that you provision in excess of your reserved capacity is billed at standard provisioned capacity rates.

Reserved capacity discounts are applied first to the account that purchased the reserved capacity. Any unused reserved capacity discount is then applied to other accounts in the same AWS organization as the purchasing account.

**Note**

Reserved capacity is not available for replicated write capacity units. Reserved capacity is also not available for tables using the DynamoDB Standard-IA table class or on-demand capacity mode.

To manage reserved capacity, go to the [DynamoDB console](#) and choose **Reserved Capacity**.

**Note**

You can prevent users from viewing or purchasing reserved capacity, while still allowing them to access the rest of the console. For more information, see "Grant Permissions to Prevent Purchasing of Reserved Capacity Offerings" in [Identity and access management in Amazon DynamoDB \(p. 1070\)](#).

For more information about specific pricing see [Amazon DynamoDB Pricing](#).

## Table classes

DynamoDB offers two table classes designed to help you optimize for cost. The DynamoDB Standard table class is the default, and is recommended for the vast majority of workloads. The DynamoDB Standard-Infrequent Access (DynamoDB Standard-IA) table class is optimized for tables where storage is the dominant cost. For example, tables that store infrequently accessed data, such as application logs, old social media posts, e-commerce order history, and past gaming achievements, are good candidates for the Standard-IA table class. See [Amazon DynamoDB Pricing](#) for pricing details.

Every DynamoDB table is associated with a table class (DynamoDB Standard by default). Each table class offers different pricing for data storage as well as for read and write requests. You can select the most cost-effective table class for your table based on its storage and throughput usage patterns.

The choice of a table class is not permanent—you can change this setting using the AWS Management Console, AWS CLI, or AWS SDK. DynamoDB also supports managing your table class using AWS CloudFormation for single-Region tables (tables that are not global tables). To learn more about selecting your table class, see [Considerations when choosing a table class \(p. 285\)](#).

## Partitions and data distribution

Amazon DynamoDB stores data in partitions. A *partition* is an allocation of storage for a table, backed by solid state drives (SSDs) and automatically replicated across multiple Availability Zones within an AWS Region. Partition management is handled entirely by DynamoDB—you never have to manage partitions yourself.

When you create a table, the initial status of the table is **CREATING**. During this phase, DynamoDB allocates sufficient partitions to the table so that it can handle your provisioned throughput requirements. You can begin writing and reading table data after the table status changes to **ACTIVE**.

DynamoDB allocates additional partitions to a table in the following situations:

- If you increase the table's provisioned throughput settings beyond what the existing partitions can support.
- If an existing partition fills to capacity and more storage space is required.

Partition management occurs automatically in the background and is transparent to your applications. Your table remains available throughout and fully supports your provisioned throughput requirements.

For more details, see [Partition key design \(p. 1165\)](#).

Global secondary indexes in DynamoDB are also composed of partitions. The data in a global secondary index is stored separately from the data in its base table, but index partitions behave in much the same way as table partitions.


## Data distribution: Partition key

If your table has a simple primary key (partition key only), DynamoDB stores and retrieves each item based on its partition key value.

To write an item to the table, DynamoDB uses the value of the partition key as input to an internal hash function. The output value from the hash function determines the partition in which the item will be stored.

To read an item from the table, you must specify the partition key value for the item. DynamoDB uses this value as input to its hash function, yielding the partition in which the item can be found.

The following diagram shows a table named *Pets*, which spans multiple partitions. The table's primary key is *AnimalType* (only this key attribute is shown). DynamoDB uses its hash function to determine where to store a new item, in this case based on the hash value of the string *Dog*. Note that the items are not stored in sorted order. Each item's location is determined by the hash value of its partition key.



### Note

DynamoDB is optimized for uniform distribution of items across a table's partitions, no matter how many partitions there may be. We recommend that you choose a partition key that can have a large number of distinct values relative to the number of items in the table.

## Data distribution: Partition key and sort key


If the table has a composite primary key (partition key and sort key), DynamoDB calculates the hash value of the partition key in the same way as described in [Data distribution: Partition key \(p. 23\)](#). However, it stores all the items with the same partition key value physically close together, ordered by sort key value.

To write an item to the table, DynamoDB calculates the hash value of the partition key to determine which partition should contain the item. In that partition, several items could have the same partition key value. So DynamoDB stores the item among the others with the same partition key, in ascending order by sort key.

To read an item from the table, you must specify its partition key value and sort key value. DynamoDB calculates the partition key's hash value, yielding the partition in which the item can be found.

You can read multiple items from the table in a single operation (Query) if the items you want have the same partition key value. DynamoDB returns all of the items with that partition key value. Optionally, you can apply a condition to the sort key so that it returns only the items within a certain range of values.

Suppose that the *Pets* table has a composite primary key consisting of *AnimalType* (partition key) and *Name* (sort key). The following diagram shows DynamoDB writing an item with a partition key value of *Dog* and a sort key value of *Fido*.



To read that same item from the *Pets* table, DynamoDB calculates the hash value of *Dog*, yielding the partition in which these items are stored. DynamoDB then scans the sort key attribute values until it finds *Fido*.

To read all of the items with an *AnimalType* of *Dog*, you can issue a `Query` operation without specifying a sort key condition. By default, the items are returned in the order that they are stored (that is, in ascending order by sort key). Optionally, you can request descending order instead.

To query only some of the *Dog* items, you can apply a condition to the sort key (for example, only the *Dog* items where *Name* begins with a letter that is within the range A through K).

**Note**

In a DynamoDB table, there is no upper limit on the number of distinct sort key values per partition key value. If you needed to store many billions of *Dog* items in the *Pets* table, DynamoDB would allocate enough storage to handle this requirement automatically.

## From SQL to NoSQL

If you are an application developer, you might have some experience using a relational database management system (RDBMS) and Structured Query Language (SQL). As you begin working with Amazon DynamoDB, you will encounter many similarities, but also many things that are different. *NoSQL* is a term used to describe nonrelational database systems that are highly available, scalable, and optimized for high performance. Instead of the relational model, NoSQL databases (like DynamoDB) use alternate models for data management, such as key-value pairs or document storage. For more information, see [What is NoSQL?](#).

Amazon DynamoDB supports [PartiQL](#), an open-source, SQL-compatible query language that makes it easy for you to efficiently query data, regardless of where or in what format it is stored. With PartiQL, you can easily process structured data from relational databases, semi-structured and nested data in open data formats, and even schema-less data in NoSQL or document databases that allow different attributes for different rows. For more information, see [PartiQL query language](#).

The following sections describe common database tasks, comparing and contrasting SQL statements with their equivalent DynamoDB operations.

**Note**

The SQL examples in this section are compatible with the MySQL RDBMS.

The DynamoDB examples in this section show the name of the DynamoDB operation, along with the parameters for that operation in JSON format. For code examples that use these operations, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

### Topics

- [Relational \(SQL\) or NoSQL? \(p. 25\)](#)
- [Characteristics of databases \(p. 27\)](#)
- [Creating a table \(p. 29\)](#)
- [Getting information about a table \(p. 30\)](#)
- [Writing data to a table \(p. 32\)](#)
- [Key differences when reading data from a table \(p. 34\)](#)
- [Managing indexes \(p. 40\)](#)
- [Modifying data in a table \(p. 44\)](#)
- [Deleting data from a table \(p. 46\)](#)
- [Removing a table \(p. 48\)](#)

## Relational (SQL) or NoSQL?

Today's applications have more demanding requirements than ever before. For example, an online game might start out with just a few users and a very small amount of data. However, if the game becomes successful, it can easily outstrip the resources of the underlying database management system. It is

common for web-based applications to have hundreds, thousands, or millions of concurrent users, with terabytes or more of new data generated per day. Databases for such applications must handle tens (or hundreds) of thousands of reads and writes per second.

Amazon DynamoDB is well-suited for these kinds of workloads. As a developer, you can start small and gradually increase your utilization as your application becomes more popular. DynamoDB scales seamlessly to handle very large amounts of data and very large numbers of users.

The following table shows some high-level differences between an RDBMS and DynamoDB.


Characteristic	Relational database management system (RDBMS)	Amazon DynamoDB
<b>Optimal Workloads</b>	Ad hoc queries; data warehousing; OLAP (online analytical processing).	Web-scale applications, including social networks, gaming, media sharing, and Internet of Things (IoT).
<b>Data Model</b>	The relational model requires a well-defined schema, where data is normalized into tables, rows, and columns. In addition, all of the relationships are defined among tables, columns, indexes, and other database elements.	DynamoDB is schemaless. Every table must have a primary key to uniquely identify each data item, but there are no similar constraints on other non-key attributes. DynamoDB can manage structured or semistructured data, including JSON documents.
<b>Data Access</b>	SQL is the standard for storing and retrieving data. Relational databases offer a rich set of tools for simplifying the development of database-driven applications, but all of these tools use SQL.	You can use the AWS Management Console, the AWS CLI, or NoSQL WorkBench to work with DynamoDB and perform ad hoc tasks. <a href="#">PartiQL</a> , a SQL-compatible query language, lets you select, insert, update, and delete data in DynamoDB. Applications can use the AWS software development kits (SDKs) to work with DynamoDB using object-based, document-centric, or low-level interfaces.
<b>Performance</b>	Relational databases are optimized for storage, so performance generally depends on the disk subsystem. Developers and database administrators must optimize queries, indexes, and table structures in order to achieve peak performance.	DynamoDB is optimized for compute, so performance is mainly a function of the underlying hardware and network latency. As a managed service, DynamoDB insulates you and your applications from these implementation details, so that you can focus on designing and building robust, high-performance applications.
<b>Scaling</b>	It is easiest to scale up with faster hardware. It is also possible for database tables to span across multiple hosts in	DynamoDB is designed to scale out using distributed clusters of hardware. This design allows increased throughput without

Characteristic	Relational database management system (RDBMS)	Amazon DynamoDB
	a distributed system, but this requires additional investment. Relational databases have maximum sizes for the number and size of files, which imposes upper limits on scalability.	increased latency. Customers specify their throughput requirements, and DynamoDB allocates sufficient resources to meet those requirements. There are no upper limits on the number of items per table, nor the total size of that table.

## Characteristics of databases

Before your application can access a database, it must be *authenticated* to ensure that the application is allowed to use the database. It must be *authorized* so that the application can perform only the actions for which it has permissions.

The following diagram shows a client's interaction with a relational database and with Amazon DynamoDB.



The following table has more details about client interaction tasks.

Characteristic	Relational database management system (RDBMS)	Amazon DynamoDB
<b>Tools for Accessing the Database</b>	Most relational databases provide a command line interface (CLI) so that you can	In most cases, you write application code. You can also use the AWS Management

Characteristic	Relational database management system (RDBMS)	Amazon DynamoDB
	enter ad hoc SQL statements and see the results immediately.	Console, the AWS Command Line Interface (AWS CLI), or NoSQL Workbench to send ad hoc requests to DynamoDB and view the results. <a href="#">PartiQL</a> , a SQL-compatible query language, lets you select, insert, update, and delete data in DynamoDB.
<b>Connecting to the Database</b>	An application program establishes and maintains a network connection with the database. When the application is finished, it terminates the connection.	DynamoDB is a web service, and interactions with it are stateless. Applications do not need to maintain persistent network connections. Instead, interaction with DynamoDB occurs using HTTP(S) requests and responses.
<b>Authentication</b>	An application cannot connect to the database until it is authenticated. The RDBMS can perform the authentication itself, or it can offload this task to the host operating system or a directory service.	Every request to DynamoDB must be accompanied by a cryptographic signature, which authenticates that particular request. The AWS SDKs provide all of the logic necessary for creating signatures and signing requests. For more information, see <a href="#">Signing AWS API requests</a> in the <a href="#">AWS General Reference</a> .
<b>Authorization</b>	Applications can perform only the actions for which they have been authorized. Database administrators or application owners can use the SQL GRANT and REVOKE statements to control access to database objects (such as tables), data (such as rows within a table), or the ability to issue certain SQL statements.	In DynamoDB, authorization is handled by AWS Identity and Access Management (IAM). You can write an IAM policy to grant permissions on a DynamoDB resource (such as a table), and then allow IAM users and roles to use that policy. IAM also features fine-grained access control for individual data items in DynamoDB tables. For more information, see <a href="#">Identity and access management in Amazon DynamoDB (p. 1070)</a> .
<b>Sending a Request</b>	The application issues a SQL statement for every database operation that it wants to perform. Upon receipt of the SQL statement, the RDBMS checks its syntax, creates a plan for performing the operation, and then runs the plan.	The application sends HTTP(S) requests to DynamoDB. The requests contain the name of the DynamoDB operation to perform, along with parameters. DynamoDB runs the request immediately.

Characteristic	Relational database management system (RDBMS)	Amazon DynamoDB
<b>Receiving a Response</b>	The RDBMS returns the results from the SQL statement. If there is an error, the RDBMS returns an error status and message.	DynamoDB returns an HTTP(S) response containing the results of the operation. If there is an error, DynamoDB returns an HTTP error status and messages.

## Creating a table

Tables are the fundamental data structures in relational databases and in Amazon DynamoDB. A relational database management system (RDBMS) requires you to define the table's schema when you create it. In contrast, DynamoDB tables are schemaless—other than the primary key, you do not need to define any extra attributes or data types when you create a table.

### Topics

- [SQL \(p. 29\)](#)
- [DynamoDB \(p. 29\)](#)

## SQL

Use the `CREATE TABLE` statement to create a table, as shown in the following example.

```
CREATE TABLE Music (
    Artist VARCHAR(20) NOT NULL,
    SongTitle VARCHAR(30) NOT NULL,
    AlbumTitle VARCHAR(25),
    Year INT,
    Price FLOAT,
    Genre VARCHAR(10),
    Tags TEXT,
    PRIMARY KEY(Artist, SongTitle)
);
```

The primary key for this table consists of *Artist* and *SongTitle*.

You must define all of the table's columns and data types, and the table's primary key. (You can use the `ALTER TABLE` statement to change these definitions later, if necessary.)

Many SQL implementations let you define storage specifications for your table, as part of the `CREATE TABLE` statement. Unless you indicate otherwise, the table is created with default storage settings. In a production environment, a database administrator can help determine the optimal storage parameters.

## DynamoDB

Use the `CreateTable` action to create a provisioned mode table, specifying parameters as shown following:

```
{
    TableName : "Music",
    KeySchema: [
        {
            AttributeName: "Artist",
            KeyType: "HASH"
        },
        {
            AttributeName: "SongTitle",
            KeyType: "RANGE"
        }
    ],
    AttributeDefinitions: [
        {
            AttributeName: "Artist",
            AttributeType: "S"
        },
        {
            AttributeName: "SongTitle",
            AttributeType: "S"
        }
    ],
    ProvisionedThroughput: {
        ReadCapacityUnits: 5,
        WriteCapacityUnits: 5
    }
}
```

```
        KeyType: "HASH", //Partition key
    },
    {
        AttributeName: "SongTitle",
        KeyType: "RANGE" //Sort key
    }
],
AttributeDefinitions: [
    {
        AttributeName: "Artist",
        AttributeType: "S"
    },
    {
        AttributeName: "SongTitle",
        AttributeType: "S"
    }
],
ProvisionedThroughput: {           // Only specified if using provisioned mode
    ReadCapacityUnits: 1,
    WriteCapacityUnits: 1
}
}
```

The primary key for this table consists of *Artist* (partition key) and *SongTitle* (sort key).

You must provide the following parameters to `CreateTable`:

- `TableName` – Name of the table.
- `KeySchema` – Attributes that are used for the primary key. For more information, see [Tables, items, and attributes \(p. 3\)](#) and [Primary key \(p. 6\)](#).
- `AttributeDefinitions` – Data types for the key schema attributes.
- `ProvisionedThroughput` (for provisioned tables) – Number of reads and writes per second that you need for this table. DynamoDB reserves sufficient storage and system resources so that your throughput requirements are always met. You can use the `UpdateTable` action to change these later, if necessary. You do not need to specify a table's storage requirements because storage allocation is managed entirely by DynamoDB.

**Note**

For code examples that use `CreateTable`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

## Getting information about a table

You can verify that a table has been created according to your specifications. In a relational database, all of the table's schema is shown. Amazon DynamoDB tables are schemaless, so only the primary key attributes are shown.

### Topics

- [SQL \(p. 30\)](#)
- [DynamoDB \(p. 31\)](#)

## SQL

Most relational database management systems (RDBMS) allow you to describe a table's structure—columns, data types, primary key definition, and so on. There is no standard way to do this in SQL.

However, many database systems provide a `DESCRIBE` command. The following is an example from MySQL.

```
DESCRIBE Music;
```

This returns the structure of your table, with all of the column names, data types, and sizes.

Field	Type	Null	Key	Default	Extra
Artist	varchar(20)	NO	PRI	NULL	
SongTitle	varchar(30)	NO	PRI	NULL	
AlbumTitle	varchar(25)	YES		NULL	
Year	int(11)	YES		NULL	
Price	float	YES		NULL	
Genre	varchar(10)	YES		NULL	
Tags	text	YES		NULL	

The primary key for this table consists of *Artist* and *SongTitle*.

## DynamoDB

DynamoDB has a `DescribeTable` action, which is similar. The only parameter is the table name.

```
{
    TableName : "Music"
}
```

The reply from `DescribeTable` looks like the following.

```
{
    "Table": {
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "TableName": "Music",
        "KeySchema": [
            {
                "AttributeName": "Artist",
                "KeyType": "HASH" //Partition key
            },
            {
                "AttributeName": "SongTitle",
                "KeyType": "RANGE" //Sort key
            }
        ],
        ...
    }
}
```

`DescribeTable` also returns information about indexes on the table, provisioned throughput settings, an approximate item count, and other metadata.

## Writing data to a table

Relational database tables contain *rows* of data. Rows are composed of *columns*. Amazon DynamoDB tables contain *items*. Items are composed of *attributes*.

This section describes how to write one row (or item) to a table.

### Topics

- [SQL \(p. 32\)](#)
- [DynamoDB \(p. 32\)](#)

## SQL

A table in a relational database is a two-dimensional data structure composed of rows and columns. Some database management systems also provide support for semistructured data, usually with native JSON or XML data types. However, the implementation details vary among vendors.

In SQL, you use the `INSERT` statement to add a row to a table.

```
INSERT INTO Music
    (Artist, SongTitle, AlbumTitle,
     Year, Price, Genre,
     Tags)
VALUES(
    'No One You Know', 'Call Me Today', 'Somewhat Famous',
    2015, 2.14, 'Country',
    '{"Composers": ["Smith", "Jones", "Davis"], "LengthInSeconds": 214}'
);
```

The primary key for this table consists of *Artist* and *SongTitle*. You must specify values for these columns.

### Note

This example uses the *Tags* column to store semistructured data about the songs in the *Music* table. The *Tags* column is defined as type TEXT, which can store up to 65,535 characters in MySQL.

## DynamoDB

In Amazon DynamoDB, you can use either the DynamoDB API, or [PartiQL](#), a SQL-compatible query language, to add an item to a table.

### DynamoDB API

With the DynamoDB API, you use the `PutItem` operation to add an item to a table.

```
{
  TableName: "Music",
  Item: {
    "Artist": "No One You Know",
    "SongTitle": "Call Me Today",
    "AlbumTitle": "Somewhat Famous",
    "Year": 2015,
    "Price": 2.14,
    "Genre": "Country",
    "Tags": {
      "Composers": [
        "Smith",
        "Jones",
        "Davis"
      ]
    }
  }
}
```

```
        "Jones",
        "Davis"
    ],
    "LengthInSeconds": 214
}
}
```

The primary key for this table consists of *Artist* and *SongTitle*. You must specify values for these attributes.

Here are some key things to know about this PutItem example:

- DynamoDB provides native support for documents, using JSON. This makes DynamoDB ideal for storing semistructured data, such as *Tags*. You can also retrieve and manipulate data from within JSON documents.
  - The *Music* table does not have any predefined attributes, other than the primary key (*Artist* and *SongTitle*).
  - Most SQL databases are transaction oriented. When you issue an `INSERT` statement, the data modifications are not permanent until you issue a `COMMIT` statement. With Amazon DynamoDB, the effects of a `PutItem` action are permanent when DynamoDB replies with an HTTP 200 status code (OK).

## Note

For code examples using `PutItem`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

The following are some other PutItem examples.

```
{  
    TableName: "Music",  
    Item: {  
        "Artist": "No One You Know",  
        "SongTitle": "My Dog Spot",  
        "AlbumTitle": "Hey Now",  
        "Price": 1.98,  
        "Genre": "Country",  
        "CriticRating": 8.4  
    }  
}
```

```
{  
    TableName: "Music",  
    Item: {  
        "Artist": "No One You Know",  
        "SongTitle": "Somewhere Down The Road",  
        "AlbumTitle": "Somewhat Famous",  
        "Genre": "Country",  
        "CriticRating": 8.4,  
        "Year": 1984  
    }  
}
```

```
{  
  TableName: "Music",  
  Item: {  
    "Artist": "The Acme Band",  
    "SongTitle": "Still In Love",  
    "AlbumTitle": "The Buck Starts Here",
```

```
"Price": 2.47,
"Genre": "Rock",
"PromotionInfo": {
    "RadioStationsPlaying": [
        "KHCR", "KBQX", "WTNR", "WJJH"
    ],
    "TourDates": {
        "Seattle": "20150625",
        "Cleveland": "20150630"
    },
    "Rotation": "Heavy"
}
}
```

```
{
    TableName: "Music",
    Item: {
        "Artist": "The Acme Band",
        "SongTitle": "Look Out, World",
        "AlbumTitle": "The Buck Starts Here",
        "Price": 0.99,
        "Genre": "Rock"
    }
}
```

**Note**

In addition to `PutItem`, DynamoDB supports a `BatchWriteItem` action for writing multiple items at the same time.

PartiQL for DynamoDB

With PartiQL, you use the `ExecuteStatement` operation to add an item to a table, using the PartiQL `Insert` statement.

```
INSERT into Music value {
    'Artist': 'No One You Know',
    'SongTitle': 'Call Me Today',
    'AlbumTitle': 'Somewhat Famous',
    'Year' : '2015',
    'Genre' : 'Acme'
}
```

The primary key for this table consists of `Artist` and `SongTitle`. You must specify values for these attributes.

**Note**

For code examples using `Insert` and `ExecuteStatement`, see [PartiQL insert statements for DynamoDB \(p. 481\)](#).

## Key differences when reading data from a table

With SQL, you use the `SELECT` statement to retrieve one or more rows from a table. You use the `WHERE` clause to determine the data that is returned to you.

Amazon DynamoDB provides the following operations for reading data:

- `ExecuteStatement` retrieves a single or multiple items from a table. `BatchExecuteStatement` retrieves multiple items from different tables in a single operation. Both of these operations use [PartiQL](#), a SQL-compatible query language.

- **GetItem** – Retrieves a single item from a table. This is the most efficient way to read a single item because it provides direct access to the physical location of the item. (DynamoDB also provides the `BatchGetItem` operation, allowing you to perform up to 100 `GetItem` calls in a single operation.)
- **Query** – Retrieves all of the items that have a specific partition key. Within those items, you can apply a condition to the sort key and retrieve only a subset of the data. `Query` provides quick, efficient access to the partitions where the data is stored. (For more information, see [Partitions and data distribution \(p. 22\)](#).)
- **Scan** – Retrieves all of the items in the specified table. (This operation should not be used with large tables because it can consume large amounts of system resources.)

#### Note

With a relational database, you can use the `SELECT` statement to join data from multiple tables and return the results. Joins are fundamental to the relational model. To ensure that joins run efficiently, the database and its applications should be performance-tuned on an ongoing basis. DynamoDB is a non-relational NoSQL database that does not support table joins. Instead, applications read data from one table at a time.

The following sections describe different use cases for reading data, and how to perform these tasks with a relational database and with DynamoDB.

#### Topics

- [Reading an item using its primary key \(p. 35\)](#)
- [Querying a table \(p. 37\)](#)
- [Scanning a table \(p. 39\)](#)

## Reading an item using its primary key

One common access pattern for databases is to read a single item from a table. You have to specify the primary key of the item you want.

#### Topics

- [SQL \(p. 35\)](#)
- [DynamoDB \(p. 36\)](#)

## SQL

In SQL, you use the `SELECT` statement to retrieve data from a table. You can request one or more columns in the result (or all of them, if you use the `*` operator). The `WHERE` clause determines which rows to return.

The following is a `SELECT` statement to retrieve a single row from the *Music* table. The `WHERE` clause specifies the primary key values.

```
SELECT *
FROM Music
WHERE Artist='No One You Know' AND SongTitle = 'Call Me Today'
```

You can modify this query to retrieve only a subset of the columns.

```
SELECT AlbumTitle, Year, Price
FROM Music
WHERE Artist='No One You Know' AND SongTitle = 'Call Me Today'
```

Note that the primary key for this table consists of *Artist* and *SongTitle*.

## DynamoDB

In Amazon DynamoDB, you can use either the DynamoDB API, or [PartiQL](#), a SQL-compatible query language, to read an item from a table.

### DynamoDB API

With the DynamoDB API, you use the `PutItem` operation to add an item to a table.

DynamoDB provides the `GetItem` action for retrieving an item by its primary key. `GetItem` is highly efficient because it provides direct access to the physical location of the item. (For more information, see [Partitions and data distribution \(p. 22\)](#).)

By default, `GetItem` returns the entire item with all of its attributes.

```
{  
    TableName: "Music",  
    Key: {  
        "Artist": "No One You Know",  
        "SongTitle": "Call Me Today"  
    }  
}
```

You can add a `ProjectionExpression` parameter to return only some of the attributes.

```
{  
    TableName: "Music",  
    Key: {  
        "Artist": "No One You Know",  
        "SongTitle": "Call Me Today"  
    },  
    "ProjectionExpression": "AlbumTitle, Year, Price"  
}
```

Note that the primary key for this table consists of *Artist* and *SongTitle*.

The DynamoDB `GetItem` action is very efficient: It uses the primary key values to determine the exact storage location of the item in question, and retrieves it directly from there. The SQL `SELECT` statement is similarly efficient, in the case of retrieving items by primary key values.

The SQL `SELECT` statement supports many kinds of queries and table scans. DynamoDB provides similar functionality with its `Query` and `Scan` actions, which are described in [Querying a table \(p. 37\)](#) and [Scanning a table \(p. 39\)](#).

The SQL `SELECT` statement can perform table joins, allowing you to retrieve data from multiple tables at the same time. Joins are most effective where the database tables are normalized and the relationships among the tables are clear. However, if you join too many tables in one `SELECT` statement application performance can be affected. You can work around such issues by using database replication, materialized views, or query rewrites.

DynamoDB is a nonrelational database and doesn't support table joins. If you are migrating an existing application from a relational database to DynamoDB, you need to denormalize your data model to eliminate the need for joins.

#### Note

For code examples that use `GetItem`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

### PartiQL for DynamoDB

With PartiQL, you use the `ExecuteStatement` operation to read an item from a table, using the PartiQL Select statement.

```
SELECT AlbumTitle, Year, Price
FROM Music
WHERE Artist='No One You Know' AND SongTitle = 'Call Me Today'
```

Note that the primary key for this table consists of `Artist` and `SongTitle`.

**Note**

The select PartiQL statement can also be used to Query or Scan a DynamoDB table

For code examples using `Select` and `ExecuteStatement`, see [PartiQL select statements for DynamoDB \(p. 474\)](#).

## Querying a table

Another common access pattern is reading multiple items from a table, based on your query criteria.

**Topics**

- [SQL \(p. 37\)](#)
- [DynamoDB \(p. 38\)](#)

## SQL

The SQL `SELECT` statement lets you query on key columns, non-key columns, or any combination. The `WHERE` clause determines which rows are returned, as shown in the following examples.

```
/* Return a single song, by primary key */

SELECT * FROM Music
WHERE Artist='No One You Know' AND SongTitle = 'Call Me Today';
```

```
/* Return all of the songs by an artist */

SELECT * FROM Music
WHERE Artist='No One You Know';
```

```
/* Return all of the songs by an artist, matching first part of title */

SELECT * FROM Music
WHERE Artist='No One You Know' AND SongTitle LIKE 'Call%';
```

```
/* Return all of the songs by an artist, with a particular word in the title...
...but only if the price is less than 1.00 */

SELECT * FROM Music
WHERE Artist='No One You Know' AND SongTitle LIKE '%Today%'
AND Price < 1.00;
```

Note that the primary key for this table consists of `Artist` and `SongTitle`.

## DynamoDB

In Amazon DynamoDB, you can use either the DynamoDB API, or [PartiQL](#), a SQL-compatible query language, to query an item from a table.

### DynamoDB API

With Amazon DynamoDB the `Query` action lets you retrieve data in a similar fashion. The `Query` action provides quick, efficient access to the physical locations where the data is stored. For more information, see [Partitions and data distribution \(p. 22\)](#).

You can use `Query` with any table that has a composite primary key (partition key and sort key). You must specify an equality condition for the partition key, and you can optionally provide another condition for the sort key.

The `KeyConditionExpression` parameter specifies the key values that you want to query. You can use an optional `FilterExpression` to remove certain items from the results before they are returned to you.

In DynamoDB, you must use `ExpressionAttributeValues` as placeholders in expression parameters (such as `KeyConditionExpression` and `FilterExpression`). This is analogous to the use of *bind variables* in relational databases, where you substitute the actual values into the `SELECT` statement at runtime.

Note that the primary key for this table consists of `Artist` and `SongTitle`.

The following are some DynamoDB `Query` examples.

```
// Return a single song, by primary key

{
    TableName: "Music",
    KeyConditionExpression: "Artist = :a and SongTitle = :t",
    ExpressionAttributeValues: {
        ":a": "No One You Know",
        ":t": "Call Me Today"
    }
}
```

```
// Return all of the songs by an artist

{
    TableName: "Music",
    KeyConditionExpression: "Artist = :a",
    ExpressionAttributeValues: {
        ":a": "No One You Know"
    }
}
```

```
// Return all of the songs by an artist, matching first part of title

{
    TableName: "Music",
    KeyConditionExpression: "Artist = :a and begins_with(SongTitle, :t)",
    ExpressionAttributeValues: {
        ":a": "No One You Know",
        ":t": "Call"
    }
}
```

**Note**

For code examples that use `Query`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

### PartiQL for DynamoDB

With PartiQL, you can perform a query by using the `ExecuteStatement` action and the `Select` statement on the partition key.

```
SELECT AlbumTitle, Year, Price
FROM Music
WHERE Artist='No One You Know'
```

Using the `SELECT` statement in this way returns all the songs associated with this particular `Artist`.

For code examples using `Select` and `ExecuteStatement`, see [PartiQL select statements for DynamoDB \(p. 474\)](#).

## Scanning a table

In SQL, a `SELECT` statement without a `WHERE` clause will return every row in a table. In Amazon DynamoDB, the `Scan` operation does the same thing. In both cases, you can retrieve all of the items or just some of them.

Whether you are using a SQL or a NoSQL database, scans should be used sparingly because they can consume large amounts of system resources. Sometimes a scan is appropriate (such as scanning a small table) or unavoidable (such as performing a bulk export of data). However, as a general rule, you should design your applications to avoid performing scans.

### Topics

- [SQL \(p. 39\)](#)
- [DynamoDB \(p. 39\)](#)

## SQL

In SQL, you can scan a table and retrieve all of its data by using a `SELECT` statement without specifying a `WHERE` clause. You can request one or more columns in the result. Or you can request all of them if you use the wildcard character (\*).

The following are examples of using a `SELECT` statement.

```
/* Return all of the data in the table */
SELECT * FROM Music;
```

```
/* Return all of the values for Artist and Title */
SELECT Artist, Title FROM Music;
```

## DynamoDB

In Amazon DynamoDB, you can use either the DynamoDB API, or [PartiQL](#), a SQL-compatible query language, to perform a scan on a table.

### DynamoDB API

With the DynamoDB API, you use the `Scan` operation to return one or more items and item attributes by accessing every item in a table or a secondary index.

```
// Return all of the data in the table
{
    TableName: "Music"
}
```

```
// Return all of the values for Artist and Title
{
    TableName: "Music",
    ProjectionExpression: "Artist, Title"
}
```

The `Scan` action also provides a `FilterExpression` parameter, which you can use to discard items that you do not want to appear in the results. A `FilterExpression` is applied after the scan is performed, but before the results are returned to you. (This is not recommended with large tables. You are still charged for the entire `Scan`, even if only a few matching items are returned.)

**Note**

For code examples that use `Scan`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

#### PartiQL for DynamoDB

With PartiQL, you perform a scan by using the `ExecuteStatement` operation to return all the contents for a table using the `Select` statement.

```
SELECT AlbumTitle, Year, Price
FROM Music
```

Note that this statement will return all items for in the `Music` table.

For code examples using `Select` and `ExecuteStatement`, see [PartiQL select statements for DynamoDB \(p. 474\)](#).

## Managing indexes

Indexes give you access to alternate query patterns, and can speed up queries. This section compares and contrasts index creation and usage in SQL and Amazon DynamoDB.

Whether you are using a relational database or DynamoDB, you should be judicious with index creation. Whenever a write occurs on a table, all of the table's indexes must be updated. In a write-heavy environment with large tables, this can consume large amounts of system resources. In a read-only or read-mostly environment, this is not as much of a concern. However, you should ensure that the indexes are actually being used by your application, and not simply taking up space.

**Topics**

- [Creating an index \(p. 40\)](#)
- [Querying and scanning an index \(p. 42\)](#)

## Creating an index

Compare the `CREATE INDEX` statement in SQL with the `UpdateTable` operation in Amazon DynamoDB.

**Topics**

- [SQL \(p. 41\)](#)

- [DynamoDB \(p. 41\)](#)

## SQL

In a relational database, an index is a data structure that lets you perform fast queries on different columns in a table. You can use the `CREATE INDEX` SQL statement to add an index to an existing table, specifying the columns to be indexed. After the index has been created, you can query the data in the table as usual, but now the database can use the index to quickly find the specified rows in the table instead of scanning the entire table.

After you create an index, the database maintains it for you. Whenever you modify data in the table, the index is automatically modified to reflect changes in the table.

In MySQL, you can create an index like the following.

```
CREATE INDEX GenreAndPriceIndex
ON Music (genre, price);
```

## DynamoDB

In DynamoDB, you can create and use a *secondary index* for similar purposes.

Indexes in DynamoDB are different from their relational counterparts. When you create a secondary index, you must specify its key attributes—a partition key and a sort key. After you create the secondary index, you can `Query` it or `Scan` it just as you would with a table. DynamoDB does not have a query optimizer, so a secondary index is only used when you `Query` it or `Scan` it.

DynamoDB supports two different kinds of indexes:

- Global secondary indexes – The primary key of the index can be any two attributes from its table.
- Local secondary indexes – The partition key of the index must be the same as the partition key of its table. However, the sort key can be any other attribute.

DynamoDB ensures that the data in a secondary index is eventually consistent with its table. You can request strongly consistent `Query` or `Scan` actions on a table or a local secondary index. However, global secondary indexes support only eventual consistency.

You can add a global secondary index to an existing table, using the `UpdateTable` action and specifying `GlobalSecondaryIndexUpdates`.

```
{
    TableName: "Music",
    AttributeDefinitions:[
        {AttributeName: "Genre", AttributeType: "S"},
        {AttributeName: "Price", AttributeType: "N"}
    ],
    GlobalSecondaryIndexUpdates: [
        {
            Create: {
                IndexName: "GenreAndPriceIndex",
                KeySchema: [
                    {AttributeName: "Genre", KeyType: "HASH"}, //Partition key
                    {AttributeName: "Price", KeyType: "RANGE"} //Sort key
                ],
                Projection: {
                    "ProjectionType": "ALL"
                },
                ProvisionedThroughput: { // Only specified
                    if using provisioned mode
                }
            }
        }
    ]
}
```

```
        "ReadCapacityUnits": 1, "WriteCapacityUnits": 1
    }
}
]
```

You must provide the following parameters to `UpdateTable`:

- `TableName` – The table that the index will be associated with.
- `AttributeDefinitions` – The data types for the key schema attributes of the index.
- `GlobalSecondaryIndexUpdates` – Details about the index you want to create:
  - `IndexName` – A name for the index.
  - `KeySchema` – The attributes that are used for the index's primary key.
  - `Projection` – Attributes from the table that are copied to the index. In this case, `ALL` means that all of the attributes are copied.
  - `ProvisionedThroughput` (for provisioned tables) – The number of reads and writes per second that you need for this index. (This is separate from the provisioned throughput settings of the table.)

Part of this operation involves backfilling data from the table into the new index. During backfilling, the table remains available. However, the index is not ready until its `Backfilling` attribute changes from true to false. You can use the `DescribeTable` action to view this attribute.

**Note**

For code examples that use `UpdateTable`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

## Querying and scanning an index

Compare querying and scanning an index using the `SELECT` statement in SQL with the `Query` and `Scan` operations in Amazon DynamoDB.

**Topics**

- [SQL \(p. 42\)](#)
- [DynamoDB \(p. 43\)](#)

### SQL

In a relational database, you do not work directly with indexes. Instead, you query tables by issuing `SELECT` statements, and the query optimizer can make use of any indexes.

A *query optimizer* is a relational database management system (RDBMS) component that evaluates the available indexes and determines whether they can be used to speed up a query. If the indexes can be used to speed up a query, the RDBMS accesses the index first and then uses it to locate the data in the table.

Here are some SQL statements that can use `GenreAndPriceIndex` to improve performance. We assume that the `Music` table has enough data in it that the query optimizer decides to use this index, rather than simply scanning the entire table.

```
/* All of the rock songs */

SELECT * FROM Music
WHERE Genre = 'Rock';
```

```
/* All of the cheap country songs */

SELECT Artist, SongTitle, Price FROM Music
WHERE Genre = 'Country' AND Price < 0.50;
```

## DynamoDB

In DynamoDB, you perform **Query** and **Scan** operations directly on the index, in the same way that you would on a table. You can use either the DynamoDB API, or [PartiQL](#), a SQL-compatible query language, to query or scan the index. You must specify both `TableName` and `IndexName`.

The following are some queries on `GenreAndPriceIndex` in DynamoDB. (The key schema for this index consists of `Genre` and `Price`.)

### DynamoDB API

```
// All of the rock songs

{
    TableName: "Music",
    IndexName: "GenreAndPriceIndex",
    KeyConditionExpression: "Genre = :genre",
    ExpressionAttributeValues: {
        ":genre": "Rock"
    },
};
```

This example uses a `ProjectionExpression` to indicate that you only want some of the attributes, rather than all of them, to appear in the results.

```
// All of the cheap country songs

{
    TableName: "Music",
    IndexName: "GenreAndPriceIndex",
    KeyConditionExpression: "Genre = :genre and Price < :price",
    ExpressionAttributeValues: {
        ":genre": "Country",
        ":price": 0.50
    },
    ProjectionExpression: "Artist, SongTitle, Price"
};
```

The following is a scan on `GenreAndPriceIndex`.

```
// Return all of the data in the index

{
    TableName: "Music",
    IndexName: "GenreAndPriceIndex"
}
```

### PartiQL for DynamoDB

With PartiQL, you use the PartiQL `Select` statement to perform queries and scans on the index.

```
// All of the rock songs

SELECT *
```

```
FROM Music.GenreAndPriceIndex
WHERE Genre = 'Rock'
```

```
// All of the cheap country songs

SELECT *
FROM Music.GenreAndPriceIndex
WHERE Genre = 'Rock' AND Price < 0.50
```

The following is a scan on *GenreAndPriceIndex*.

```
// Return all of the data in the index

SELECT *
FROM Music.GenreAndPriceIndex
```

**Note**

For code examples using `Select`, see [PartiQL select statements for DynamoDB \(p. 474\)](#).

## Modifying data in a table

The SQL language provides the `UPDATE` statement for modifying data. Amazon DynamoDB uses the `UpdateItem` operation to accomplish similar tasks.

**Topics**

- [SQL \(p. 44\)](#)
- [DynamoDB \(p. 44\)](#)

## SQL

In SQL, you use the `UPDATE` statement to modify one or more rows. The `SET` clause specifies new values for one or more columns, and the `WHERE` clause determines which rows are modified. The following is an example.

```
UPDATE Music
SET RecordLabel = 'Global Records'
WHERE Artist = 'No One You Know' AND SongTitle = 'Call Me Today';
```

If no rows match the `WHERE` clause, the `UPDATE` statement has no effect.

## DynamoDB

In DynamoDB, you can use either the classic API, or [PartiQL](#), a SQL-compatible query language to modify a single item. (If you want to modify multiple items, you must use multiple operations.)

### DynamoDB API

With the DynamoDB API, you use the `UpdateItem` action to modify a single item.

```
{
  TableName: "Music",
  Key: {
    "Artist": "No One You Know",
    "SongTitle": "Call Me Today"
```

```
        },
        UpdateExpression: "SET RecordLabel = :label",
        ExpressionAttributeValues: {
            ":label": "Global Records"
        }
    }
```

You must specify the `Key` attributes of the item to be modified and an `UpdateExpression` to specify attribute values. `UpdateItem` behaves like an "upsert" operation: The item is updated if it exists in the table, but if not, a new item is added (inserted).

`UpdateItem` supports *conditional writes*, where the operation succeeds only if a specific `ConditionExpression` evaluates to true. For example, the following `UpdateItem` action does not perform the update unless the price of the song is greater than or equal to 2.00.

```
{  
    TableName: "Music",  
    Key: {  
        "Artist": "No One You Know",  
        "SongTitle": "Call Me Today"  
    },  
    UpdateExpression: "SET RecordLabel = :label",  
    ConditionExpression: "Price >= :p",  
    ExpressionAttributeValues: {  
        ":label": "Global Records",  
        ":p": 2.00  
    }  
}
```

`UpdateItem` also supports *atomic counters*, or attributes of type `Number` that can be incremented or decremented. Atomic counters are similar in many ways to sequence generators, identity columns, or autoincrement fields in SQL databases.

The following is an example of an `UpdateItem` action to initialize a new attribute (`Plays`) to keep track of the number of times a song has been played.

```
{  
    TableName: "Music",  
    Key: {  
        "Artist": "No One You Know",  
        "SongTitle": "Call Me Today"  
    },  
    UpdateExpression: "SET Plays = :val",  
    ExpressionAttributeValues: {  
        ":val": 0  
    },  
    ReturnValues: "UPDATED_NEW"  
}
```

The `ReturnValues` parameter is set to `UPDATED_NEW`, which returns the new values of any attributes that were updated. In this case, it returns 0 (zero).

Whenever someone plays this song, we can use the following `UpdateItem` action to increment `Plays` by one.

```
{  
    TableName: "Music",  
    Key: {  
        "Artist": "No One You Know",  
        "SongTitle": "Call Me Today"  
    }  
}
```

```
    },
    UpdateExpression: "SET Plays = Plays + :incr",
    ExpressionAttributeValues: {
        ":incr": 1
    },
    ReturnValues: "UPDATED_NEW"
}
```

**Note**

For code examples that use `UpdateItem`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

### PartiQL for DynamoDB

With PartiQL, you use the `ExecuteStatement` operation to modify an item in a table, using the PartiQL `Update` statement.

The primary key for this table consists of `Artist` and `SongTitle`. You must specify values for these attributes.

```
UPDATE Music
SET RecordLabel ='Global Records'
WHERE Artist='No One You Know' AND SongTitle='Call Me Today'
```

You can also modify multiple fields at once, such as in the following example.

```
UPDATE Music
SET RecordLabel = 'Global Records'
SET AwardsWon = 10
WHERE Artist ='No One You Know' AND SongTitle='Call Me Today'
```

Update also supports *atomic counters*, or attributes of type `Number` that can be incremented or decremented. Atomic counters are similar in many ways to sequence generators, identity columns, or autoincrement fields in SQL databases.

The following is an example of an `Update` statement to initialize a new attribute (`Plays`) to keep track of the number of times a song has been played.

```
UPDATE Music
SET Plays = 0
WHERE Artist='No One You Know' AND SongTitle='Call Me Today'
```

Whenever someone plays this song, we can use the following `Update` statement to increment `Plays` by one.

```
UPDATE Music
SET Plays = Plays + 1
WHERE Artist='No One You Know' AND SongTitle='Call Me Today'
```

**Note**

For code examples using `Update` and `ExecuteStatement`, see [PartiQL update statements for DynamoDB \(p. 477\)](#).

## Deleting data from a table

In SQL, the `DELETE` statement removes one or more rows from a table. Amazon DynamoDB uses the `DeleteItem` operation to delete one item at a time.

## Topics

- [SQL \(p. 47\)](#)
- [DynamoDB \(p. 47\)](#)

## SQL

In SQL, you use the `DELETE` statement to delete one or more rows. The `WHERE` clause determines the rows that you want to modify. The following is an example.

```
DELETE FROM Music
WHERE Artist = 'The Acme Band' AND SongTitle = 'Look Out, World';
```

You can modify the `WHERE` clause to delete multiple rows. For example, you could delete all of the songs by a particular artist, as shown in the following example.

```
DELETE FROM Music WHERE Artist = 'The Acme Band'
```

### Note

If you omit the `WHERE` clause, the database attempts to delete all of the rows from the table.

## DynamoDB

In DynamoDB, you can use either the classic API, or [PartiQL](#), a SQL-compatible query language to delete a single item. (If you want to modify multiple items, you must use multiple operations.)

### DynamoDB API

With the DynamoDB API, you use the `DeleteItem` action to delete data from a table, one item at a time. You must specify the item's primary key values.

```
{
    TableName: "Music",
    Key: {
        Artist: "The Acme Band",
        SongTitle: "Look Out, World"
    }
}
```

### Note

In addition to `DeleteItem`, Amazon DynamoDB supports a `BatchWriteItem` action for deleting multiple items at the same time.

`DeleteItem` supports *conditional writes*, where the operation succeeds only if a specific `ConditionExpression` evaluates to true. For example, the following `DeleteItem` action deletes the item only if it has a `RecordLabel` attribute.

```
{
    TableName: "Music",
    Key: {
        Artist: "The Acme Band",
        SongTitle: "Look Out, World"
    },
    ConditionExpression: "attribute_exists(RecordLabel)"
}
```

**Note**

For code examples that use `DeleteItem`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

PartiQL for DynamoDB

With PartiQL, you use the `Delete` statement through the `ExecuteStatement` operation to delete data from a table, one item at a time. You must specify the item's primary key values.

The primary key for this table consists of `Artist` and `SongTitle`. You must specify values for these attributes.

```
DELETE FROM Music
WHERE Artist = 'Acme Band' AND SongTitle = 'PartiQL Rocks'
```

You can also specify additional conditions for the operation. The following `DELETE` operation only deletes the item if it has more than 11 `Awards`.

```
DELETE FROM Music
WHERE Artist = 'Acme Band' AND SongTitle = 'PartiQL Rocks' AND Awards > 11
```

**Note**

For code examples using `DELETE` and `ExecuteStatement`, see [PartiQL delete statements for DynamoDB \(p. 480\)](#).

## Removing a table

In SQL, you use the `DROP TABLE` statement to remove a table. In Amazon DynamoDB, you use the `DeleteTable` operation.

**Topics**

- [SQL \(p. 48\)](#)
- [DynamoDB \(p. 48\)](#)

## SQL

When you no longer need a table and want to discard it permanently, you use the `DROP TABLE` statement in SQL.

```
DROP TABLE Music;
```

After a table is dropped, it cannot be recovered. (Some relational databases do allow you to undo a `DROP TABLE` operation, but this is vendor-specific functionality and it is not widely implemented.)

## DynamoDB

DynamoDB has a similar action: `DeleteTable`. In the following example, the table is permanently deleted.

```
{
    TableName: "Music"
}
```

**Note**

For code examples that use `DeleteTable`, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

## Additional Amazon DynamoDB resources

**Topics**

- [Blog posts, repositories, and guides \(p. 49\)](#)
- [Data modeling and design pattern presentations \(p. 49\)](#)
- [Training courses \(p. 49\)](#)
- [Tools for coding and visualization \(p. 50\)](#)

### Blog posts, repositories, and guides

- AWS repository of [DynamoDB code examples](#) in various AWS SDK languages: [Node.js](#), [Java](#), [Python](#), [.Net](#), [Go](#), and [Rust](#).
- [The DynamoDB book](#) — A comprehensive guide from [Alex DeBrie](#) that teaches a strategy-driven approach to data modeling with DynamoDB.
- [DynamoDB guide](#) — An open guide from [Alex DeBrie](#) that walks through the basic concepts and advanced features of the DynamoDB NoSQL database.
- [How to switch from RDBMS to DynamoDB in 20 easy steps](#) — An irreverent list from [Jeremy Daly](#) of useful steps for learning data modeling.
- [DynamoDB JavaScript DocumentClient cheat sheet](#) — A cheat sheet to help you get started building applications with DynamoDB in a Node.js or JavaScript environment.

### Data modeling and design pattern presentations

- [AWS re:Invent 2019: Data modeling with DynamoDB](#)
  - A talk by [Alex DeBrie](#) that gets you started on the principles of DynamoDB data modeling.
- [AWS re:Invent 2020: Data modeling with DynamoDB part 1](#)
- [AWS re:Invent 2020: Data modeling with DynamoDB part 2](#)
- [AWS re:Invent 2017: Advanced design patterns](#)
- [AWS re:Invent 2018: Advanced design patterns](#)
- [AWS re:Invent 2019: Advanced design patterns](#)
  - Jeremy Daly shares his [12 key takeaways](#) from this session.
- [AWS re:Invent 2020: DynamoDB advanced design patterns part 1](#)
- [AWS re:Invent 2020: DynamoDB advanced design patterns part 2](#)
- [DynamoDB office hours on Twitch](#)

**Note**

Each session covers different use cases and examples.

### Training courses

- [Developing with Amazon DynamoDB](#) — Designed by AWS to take you from beginner to expert in developing real world applications with data modeling for Amazon DynamoDB.

- [DynamoDB deep-dive course](#) — A course from A Cloud Guru.
- [Amazon DynamoDB: Building NoSQL database-driven applications](#) — A course from the AWS Training and Certification team hosted on edX.
- [AWS DynamoDB — from beginner to pro](#) — A course from A Cloud Guru.

## Tools for coding and visualization

- [NoSQL workbench for Amazon DynamoDB](#) — A unified, visual tool that provides data modeling, data visualization, and query development features to help you design, create, query, and manage DynamoDB tables.
- [Dynobase](#) — A desktop tool that makes it easy to see and work with your DynamoDB tables, create app code, and edit records with real-time validation.
- [DynamoDB toolbox](#) — A project from Jeremy Daly that provides helpful utilities for working with data modeling and in JavaScript and Node.js.
- [DynamoDB streams processor](#) — A simple tool that makes working with [DynamoDB streams](#) super easy.

# Setting up DynamoDB

In addition to the Amazon DynamoDB web service, AWS provides a downloadable version of DynamoDB that you can run on your computer and is perfect for development and testing of your code. The downloadable version lets you write and test applications locally without accessing the DynamoDB web service.

The topics in this section describe how to set up DynamoDB (downloadable version) and the DynamoDB web service.

## Topics

- [Setting up DynamoDB local \(downloadable version\) \(p. 51\)](#)
- [Setting up DynamoDB \(web service\) \(p. 58\)](#)

## Setting up DynamoDB local (downloadable version)

With the downloadable version of Amazon DynamoDB, you can develop and test applications without accessing the DynamoDB web service. Instead, the database is self-contained on your computer. When you're ready to deploy your application in production, you remove the local endpoint in the code, and then it points to the DynamoDB web service.

Having this local version helps you save on throughput, data storage, and data transfer fees. In addition, you don't need an internet connection while you develop your application.

DynamoDB Local is available as a [download \(p. 51\)](#) (requires JRE), as an [Apache Maven dependency](#), or as a [Docker image](#).

If you prefer to use the Amazon DynamoDB web service instead, see [Setting up DynamoDB \(web service\) \(p. 58\)](#).

## Topics

- [Deploying DynamoDB locally on your computer \(p. 51\)](#)
- [DynamoDB local usage notes \(p. 55\)](#)

## Deploying DynamoDB locally on your computer

### Download locally

The downloadable version of Amazon DynamoDB is provided as an executable .jar file. The application runs on Windows, Linux, macOS, and other platforms that support Java.

Follow these steps to set up and run DynamoDB on your computer.

### To set up DynamoDB on your computer

1. Download DynamoDB for free from one of the following locations.

Region	Download Links	Checksums
Asia Pacific (Mumbai) Region	<a href="#">.tar.gz</a>   <a href="#">.zip</a>	<a href="#">.tar.gz.sha256</a>   <a href="#">.zip.sha256</a>
Asia Pacific (Singapore) Region	<a href="#">.tar.gz</a>   <a href="#">.zip</a>	<a href="#">.tar.gz.sha256</a>   <a href="#">.zip.sha256</a>
Asia Pacific (Tokyo) Region	<a href="#">.tar.gz</a>   <a href="#">.zip</a>	<a href="#">.tar.gz.sha256</a>   <a href="#">.zip.sha256</a>
Europe (Frankfurt) Region	<a href="#">.tar.gz</a>   <a href="#">.zip</a>	<a href="#">.tar.gz.sha256</a>   <a href="#">.zip.sha256</a>
South America (São Paulo) Region	<a href="#">.tar.gz</a>   <a href="#">.zip</a>	<a href="#">.tar.gz.sha256</a>   <a href="#">.zip.sha256</a>
US West (Oregon) Region	<a href="#">.tar.gz</a>   <a href="#">.zip</a>	<a href="#">.tar.gz.sha256</a>   <a href="#">.zip.sha256</a>

DynamoDB is also available as part of the AWS Toolkit for Eclipse. For more information, see [AWS Toolkit for Eclipse](#).

**Important**

To run DynamoDB on your computer, you must have the Java Runtime Environment (JRE) version 8.x or newer. The application doesn't run on earlier JRE versions.

2. After you download the archive, extract the contents and copy the extracted directory to a location of your choice.
3. To start DynamoDB on your computer, open a command prompt window, navigate to the directory where you extracted `DynamoDBLocal.jar`, and enter the following command.

```
java -Djava.library.path=./DynamoDBLocal_lib -jar DynamoDBLocal.jar -sharedDb
```

**Note**

If you're using Windows PowerShell, be sure to enclose the parameter name or the entire name and value like this:

```
java -D"java.library.path=./DynamoDBLocal_lib" -jar
DynamoDBLocal.jar
```

DynamoDB processes incoming requests until you stop it. To stop DynamoDB, press Ctrl +C at the command prompt.

DynamoDB uses port 8000 by default. If port 8000 is unavailable, this command throws an exception. For a complete list of DynamoDB runtime options, including `-port`, enter this command.

```
java -Djava.library.path=./DynamoDBLocal_lib -jar
DynamoDBLocal.jar -help
```

4. Before you can access DynamoDB programmatically or through the AWS Command Line Interface (AWS CLI), you must configure your credentials to enable authorization for your applications. Downloadable DynamoDB requires any credentials to work, as shown in the following example.

```
AWS Access Key ID: "fakeMyKeyId"
AWS Secret Access Key: "fakeSecretAccessKey"
```

You can use the `aws configure` command of the AWS CLI to set up credentials. For more information, see [Using the AWS CLI \(p. 61\)](#).

5. Start writing applications. To access DynamoDB running locally with the AWS CLI, use the `--endpoint-url` parameter. For example, use the following command to list DynamoDB tables.

```
aws dynamodb list-tables --endpoint-url http://localhost:8000
```

## Docker

The downloadable version of Amazon DynamoDB is available as a Docker image. For more information, see [dynamodb-local](#).

For an example of using DynamoDB local as part of a REST application built on the AWS Serverless Application Model (AWS SAM), see [SAM DynamoDB application for managing orders](#). This sample application demonstrates how to use DynamoDB local for testing.

If you want to run a multi-container application that also uses the DynamoDB local container, use Docker Compose to define and run all the services in your application, including DynamoDB local.

### To install and run DynamoDB local with Docker compose:

1. Download and install [Docker desktop](#).
2. Copy the following code to a file and save it as `docker-compose.yml`.

```
version: '3.8'
services:
  dynamodb-local:
    command: "-jar DynamoDBLocal.jar -sharedDb -dbPath ./data"
    image: "amazon/dynamodb-local:latest"
    container_name: dynamodb-local
    ports:
      - "8000:8000"
    volumes:
      - "./docker/dynamodb:/home/dynamodblocal/data"
    working_dir: /home/dynamodblocal
```

If you want your application and DynamoDB local to be in separate containers, use the following yaml file.

```
version: '3.8'
services:
  dynamodb-local:
    command: "-jar DynamoDBLocal.jar -sharedDb -dbPath ./data"
    image: "amazon/dynamodb-local:latest"
    container_name: dynamodb-local
    ports:
      - "8000:8000"
    volumes:
      - "./docker/dynamodb:/home/dynamodblocal/data"
    working_dir: /home/dynamodblocal
  app-node:
    depends_on:
      - dynamodb-local
    image: banst/awscli
    container_name: app-node
    ports:
      - "8080:8080"
    environment:
      AWS_ACCESS_KEY_ID: 'DUMMYIDEXAMPLE'
      AWS_SECRET_ACCESS_KEY: 'DUMMYEXAMPLEKEY'
    command:
      dynamodb describe-limits --endpoint-url http://dynamodb-local:8000 --region us-west-2
```

This docker-compose.yml script creates an app-node container and a dynamodb-local container. The script runs a command in the app-node container that uses the AWS CLI to connect to the dynamodb-local container and describes the account and table limits.

To use with your own application image, replace the `image` value in the example below with that of your application.

```
version: '3.8'
services:
  dynamodb-local:
    command: "-jar DynamoDBLocal.jar -sharedDb -dbPath ./data"
    image: "amazon/dynamodb-local:latest"
    container_name: dynamodb-local
    ports:
      - "8000:8000"
    volumes:
      - "./docker/dynamodb:/home/dynamodblocal/data"
    working_dir: /home/dynamodblocal
  app-node:
    image: location-of-your-dynamodb-demo-app:latest
    container_name: app-node
    ports:
      - "8080:8080"
    depends_on:
      - "dynamodb-local"
    links:
      - "dynamodb-local"
    environment:
      AWS_ACCESS_KEY_ID: 'DUMMYIDEXAMPLE'
      AWS_SECRET_ACCESS_KEY: 'DUMMYEXAMPLEKEY'
      REGION: 'eu-west-1'
```

### Note

The YAML scripts require that you specify an AWS access key and an AWS secret key, but they are not required to be valid AWS keys for you to access DynamoDB Local.

3. Run the following command-line command:

```
docker-compose up
```

## Apache Maven

Follow these steps to use Amazon DynamoDB in your application as a dependency.

### To deploy DynamoDB as an Apache Maven repository

1. Download and install Apache Maven. For more information, see [Downloading Apache Maven](#) and [Installing Apache Maven](#).
2. Add the DynamoDB Maven repository to your application's Project Object Model (POM) file.

```
<!--Dependency:-->
<dependencies>
  <dependency>
    <groupId>com.amazonaws</groupId>
    <artifactId>DynamoDBLocal</artifactId>
    <version>[1.12,2.0)</version>
  </dependency>
</dependencies>
<!--Custom repository:-->
```

```

<repositories>
  <repository>
    <id>dynamodb-local-oregon</id>
    <name>DynamoDB Local Release Repository</name>
    <url>https://s3-us-west-2.amazonaws.com/dynamodb-local/release</url>
  </repository>
</repositories>
```

### Note

You can also use one of the following repository URLs, depending on your AWS Region.

id	Repository URL
dynamodb-local-mumbai	<a href="https://s3.ap-south-1.amazonaws.com/dynamodb-local-mumbai/release">https://s3.ap-south-1.amazonaws.com/dynamodb-local-mumbai/release</a>
dynamodb-local-singapore	<a href="https://s3.ap-southeast-1.amazonaws.com/dynamodb-local-singapore/release">https://s3.ap-southeast-1.amazonaws.com/dynamodb-local-singapore/release</a>
dynamodb-local-tokyo	<a href="https://s3.ap-northeast-1.amazonaws.com/dynamodb-local-tokyo/release">https://s3.ap-northeast-1.amazonaws.com/dynamodb-local-tokyo/release</a>
dynamodb-local-frankfurt	<a href="https://s3.eu-central-1.amazonaws.com/dynamodb-local-frankfurt/release">https://s3.eu-central-1.amazonaws.com/dynamodb-local-frankfurt/release</a>
dynamodb-local-sao-paulo	<a href="https://s3.sa-east-1.amazonaws.com/dynamodb-local-sao-paulo/release">https://s3.sa-east-1.amazonaws.com/dynamodb-local-sao-paulo/release</a>

## DynamoDB local usage notes

Except for the endpoint, applications that run with the downloadable version of Amazon DynamoDB should also work with the DynamoDB web service. However, when using DynamoDB locally, you should be aware of the following:

- If you use the `-sharedDb` option, DynamoDB creates a single database file named *shared-local-instance.db*. Every program that connects to DynamoDB accesses this file. If you delete the file, you lose any data that you have stored in it.
- If you omit `-sharedDb`, the database file is named *myaccesskeyid\_region.db*, with the AWS access key ID and AWS Region as they appear in your application configuration. If you delete the file, you lose any data that you have stored in it.
- If you use the `-inMemory` option, DynamoDB doesn't write any database files at all. Instead, all data is written to memory, and the data is not saved when you terminate DynamoDB.
- If you use the `-optimizeDbBeforeStartup` option, you must also specify the `-dbPath` parameter so that DynamoDB can find its database file.
- The AWS SDKs for DynamoDB require that your application configuration specify an access key value and an AWS Region value. Unless you're using the `-sharedDb` or the `-inMemory` option, DynamoDB uses these values to name the local database file. These values don't have to be valid AWS values to run locally. However, you might find it convenient to use valid values so that you can run your code in the cloud later by changing the endpoint you're using.

### Topics

- [Command line options \(p. 56\)](#)

- [Setting the local endpoint \(p. 56\)](#)
- [Differences between downloadable DynamoDB and the DynamoDB web service \(p. 57\)](#)

## Command line options

You can use the following command line options with the downloadable version of DynamoDB:

- **-cors value** — Enables support for cross-origin resource sharing (CORS) for JavaScript. You must provide a comma-separated "allow" list of specific domains. The default setting for **-cors** is an asterisk (\*), which allows public access.
- **-dbPath value** — The directory where DynamoDB writes its database file. If you don't specify this option, the file is written to the current directory. You can't specify both **-dbPath** and **-inMemory** at once.
- **-delayTransientStatuses** — Causes DynamoDB to introduce delays for certain operations. DynamoDB (downloadable version) can perform some tasks almost instantaneously, such as create/update/delete operations on tables and indexes. However, the DynamoDB service requires more time for these tasks. Setting this parameter helps DynamoDB running on your computer simulate the behavior of the DynamoDB web service more closely. (Currently, this parameter introduces delays only for global secondary indexes that are in either *CREATING* or *DELETING* status.)
- **-help** — Prints a usage summary and options.
- **-inMemory** — DynamoDB runs in memory instead of using a database file. When you stop DynamoDB, none of the data is saved. You can't specify both **-dbPath** and **-inMemory** at once.
- **-optimizeDbBeforeStartup** — Optimizes the underlying database tables before starting DynamoDB on your computer. You also must specify **-dbPath** when you use this parameter.
- **-port value** — The port number that DynamoDB uses to communicate with your application. If you don't specify this option, the default port is 8000.

### Note

DynamoDB uses port 8000 by default. If port 8000 is unavailable, this command throws an exception. You can use the **-port** option to specify a different port number. For a complete list of DynamoDB runtime options, including **-port**, type this command:

```
java -Djava.library.path=./DynamoDBLocal_lib -jar DynamoDBLocal.jar -help
```

- **-sharedDb** — If you specify **-sharedDb**, DynamoDB uses a single database file instead of separate files for each credential and Region.

## Setting the local endpoint

By default, the AWS SDKs and tools use endpoints for the Amazon DynamoDB web service. To use the SDKs and tools with the downloadable version of DynamoDB, you must specify the local endpoint:

```
http://localhost:8000
```

### AWS Command Line Interface

You can use the AWS Command Line Interface (AWS CLI) to interact with downloadable DynamoDB. For example, you can use it to perform all the steps in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

To access DynamoDB running locally, use the **--endpoint-url** parameter. The following is an example of using the AWS CLI to list the tables in DynamoDB on your computer.

```
aws dynamodb list-tables --endpoint-url http://localhost:8000
```

**Note**

The AWS CLI can't use the downloadable version of DynamoDB as a default endpoint. Therefore, you must specify `--endpoint-url` with each AWS CLI command.

## AWS SDKs

The way you specify an endpoint depends on the programming language and AWS SDK you're using. The following sections describe how to do this:

- [Java: Setting the AWS Region and endpoint \(p. 275\)](#) (DynamoDB Local supports the AWS SDK for Java V1 and V2)
- [.NET: Setting the AWS Region and endpoint \(p. 278\)](#)

**Note**

For examples in other programming languages, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

## Differences between downloadable DynamoDB and the DynamoDB web service

The downloadable version of DynamoDB is intended for development and testing purposes only. By comparison, the DynamoDB web service is a managed service with scalability, availability, and durability features that make it ideal for production use.

The downloadable version of DynamoDB differs from the web service in the following ways:

- AWS Regions and distinct AWS accounts are not supported at the client level.
- Provisioned throughput settings are ignored in downloadable DynamoDB, even though the `CreateTable` operation requires them. For `CreateTable`, you can specify any numbers you want for provisioned read and write throughput, even though these numbers are not used. You can call `UpdateTable` as many times as you want per day. However, any changes to provisioned throughput values are ignored.
- Scan operations are performed sequentially. Parallel scans are not supported. The `Segment` and `TotalSegments` parameters of the `Scan` operation are ignored.
- The speed of read and write operations on table data is limited only by the speed of your computer. `CreateTable`, `UpdateTable`, and `DeleteTable` operations occur immediately, and table state is always ACTIVE. `UpdateTable` operations that change only the provisioned throughput settings on tables or global secondary indexes occur immediately. If an `UpdateTable` operation creates or deletes any global secondary indexes, then those indexes transition through normal states (such as CREATING and DELETING, respectively) before they become an ACTIVE state. The table remains ACTIVE during this time.
- Read operations are eventually consistent. However, due to the speed of DynamoDB running on your computer, most reads appear to be strongly consistent.
- Item collection metrics and item collection sizes are not tracked. In operation responses, nulls are returned instead of item collection metrics.
- In DynamoDB, there is a 1 MB limit on data returned per result set. Both the DynamoDB web service and the downloadable version enforce this limit. However, when querying an index, the DynamoDB service calculates only the size of the projected key and attributes. By contrast, the downloadable version of DynamoDB calculates the size of the entire item.
- If you're using DynamoDB Streams, the rate at which shards are created might differ. In the DynamoDB web service, shard-creation behavior is partially influenced by table partition activity. When you run DynamoDB locally, there is no table partitioning. In either case, shards are ephemeral, so your application should not be dependent on shard behavior.

- `TransactionConflictExceptions` are not thrown by downloadable DynamoDB for transactional APIs. We recommend that you use a Java mocking framework to simulate `TransactionConflictExceptions` in the DynamoDB handler to test how your application responds to conflicting transactions.
- In the DynamoDB web service, table names are case sensitive. A table named `Authors` and one named `authors` can both exist as separate tables. In the downloadable version, table names are case insensitive, and attempting to create these two tables would result in an error.

## Setting up DynamoDB (web service)

To use the Amazon DynamoDB web service:

1. [Sign up for AWS. \(p. 58\)](#)
2. [Get an AWS access key \(p. 58\)](#) (used to access DynamoDB programmatically).

**Note**

If you plan to interact with DynamoDB only through the AWS Management Console, you don't need an AWS access key, and you can skip ahead to [Using the console \(p. 60\)](#).

3. [Configure your credentials \(p. 59\)](#) (used to access DynamoDB programmatically).

## Signing up for AWS

To use the DynamoDB service, you must have an AWS account. If you don't already have an account, you are prompted to create one when you sign up. You're not charged for any AWS services that you sign up for unless you use them.

### To sign up for AWS

1. Open <https://portal.aws.amazon.com/billing/signup>.
2. Follow the online instructions.

Part of the sign-up procedure involves receiving a phone call and entering a verification code on the phone keypad.

## Getting an AWS access key

Before you can access DynamoDB programmatically or through the AWS Command Line Interface (AWS CLI), you must have an AWS access key. You don't need an access key if you plan to use the DynamoDB console only.

Access keys consist of an access key ID and secret access key, which are used to sign programmatic requests that you make to AWS. If you don't have access keys, you can create them from the AWS Management Console. As a best practice, do not use the AWS account root user access keys for any task where it's not required. Instead, [create a new administrator IAM user](#) with access keys for yourself.

The only time that you can view or download the secret access key is when you create the keys. You cannot recover them later. However, you can create new access keys at any time. You must also have permissions to perform the required IAM actions. For more information, see [Permissions required to access IAM resources](#) in the *IAM User Guide*.

### To create access keys for an IAM user

1. Sign in to the AWS Management Console and open the IAM console at <https://console.aws.amazon.com/iam/>.

2. In the navigation pane, choose **Users**.
  3. Choose the name of the user whose access keys you want to create, and then choose the **Security credentials** tab.
  4. In the **Access keys** section, choose **Create access key**.
  5. To view the new access key pair, choose **Show**. You will not have access to the secret access key again after this dialog box closes. Your credentials will look something like this:
    - Access key ID: AKIAIOSFODNN7EXAMPLE
    - Secret access key: wJalrXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY
  6. To download the key pair, choose **Download .csv file**. Store the keys in a secure location. You will not have access to the secret access key again after this dialog box closes.
- Keep the keys confidential in order to protect your AWS account and never email them. Do not share them outside your organization, even if an inquiry appears to come from AWS or Amazon.com. No one who legitimately represents Amazon will ever ask you for your secret key.
7. After you download the .csv file, choose **Close**. When you create an access key, the key pair is active by default, and you can use the pair right away.

#### Related topics

- [What is IAM?](#) in the *IAM User Guide*
- [AWS security credentials](#) in *AWS General Reference*

## Configuring your credentials

Before you can access DynamoDB programmatically or through the AWS CLI, you must configure your credentials to enable authorization for your applications.

There are several ways to do this. For example, you can manually create the credentials file to store your access key ID and secret access key. You also can use the `aws configure` command of the AWS CLI to automatically create the file. Alternatively, you can use environment variables. For more information about configuring your credentials, see the programming-specific AWS SDK developer guide.

To install and configure the AWS CLI, see [Using the AWS CLI \(p. 61\)](#).

# Accessing DynamoDB

You can access Amazon DynamoDB using the AWS Management Console, the AWS Command Line Interface (AWS CLI), or the DynamoDB API.

## Topics

- [Using the console \(p. 60\)](#)
- [Using the AWS CLI \(p. 61\)](#)
- [Using the API \(p. 63\)](#)
- [Using the NoSQL workbench for DynamoDB \(p. 63\)](#)
- [IP address ranges \(p. 63\)](#)

## Using the console

You can access the AWS Management Console for Amazon DynamoDB at <https://console.aws.amazon.com/dynamodb/home>.

You can use the console to do the following in DynamoDB:

- Monitor recent alerts, total capacity, service health, and the latest DynamoDB news on the DynamoDB dashboard.
- Create, update, and delete tables. The capacity calculator provides estimates of how many capacity units to request based on the usage information you provide.
- Manage streams.
- View, add, update, and delete items that are stored in tables. Manage Time to Live (TTL) to define when items in a table expire so that they can be automatically deleted from the database.
- Query and scan a table.
- Set up and view alarms to monitor your table's capacity usage. View your table's top monitoring metrics on real-time graphs from CloudWatch.
- Modify a table's provisioned capacity.
- Modify a table's table class.
- Create and delete global secondary indexes.
- Create triggers to connect DynamoDB streams to AWS Lambda functions.
- Apply tags to your resources to help organize and identify them.
- Purchase reserved capacity.

The console displays an introductory screen that prompts you to create your first table. To view your tables, in the navigation pane on the left side of the console, choose **Tables**.

Here's a high-level overview of the actions available per table within each navigation tab:

- **Overview** – View table details, including item count and metrics.
- **Indexes** – Manage global and local secondary indexes.
- **Monitor** – View alarms, CloudWatch Contributor Insights, and Cloudwatch metrics.
- **Global tables** – Manage table replicas.

- **Backups** – Manage point-in-time recovery and on-demand backups.
- **Exports and streams** – Export your table to Amazon S3 and manage DynamoDB Streams and Kinesis Data Streams.
- **Additional settings** – Manage read/write capacity, Time to Live settings, encryption, and tags.

## Using the AWS CLI

You can use the AWS Command Line Interface (AWS CLI) to control multiple AWS services from the command line and automate them through scripts. You can use the AWS CLI for ad hoc operations, such as creating a table. You can also use it to embed Amazon DynamoDB operations within utility scripts.

Before you can use the AWS CLI with DynamoDB, you must get an access key ID and secret access key. For more information, see [Getting an AWS access key \(p. 58\)](#).

For a complete listing of all the commands available for DynamoDB in the AWS CLI, see the [AWS CLI command reference](#).

### Topics

- [Downloading and configuring the AWS CLI \(p. 61\)](#)
- [Using the AWS CLI with DynamoDB \(p. 61\)](#)
- [Using the AWS CLI with downloadable DynamoDB \(p. 62\)](#)

## Downloading and configuring the AWS CLI

The AWS CLI is available at <http://aws.amazon.com/cli>. It runs on Windows, macOS, or Linux. After you download the AWS CLI, follow these steps to install and configure it:

1. Go to the [AWS Command Line Interface User Guide](#).
2. Follow the instructions for [Installing the AWS CLI](#) and [Configuring the AWS CLI](#).

## Using the AWS CLI with DynamoDB

The command line format consists of a DynamoDB operation name followed by the parameters for that operation. The AWS CLI supports a shorthand syntax for the parameter values, as well as JSON.

For example, the following command creates a table named *Music*. The partition key is *Artist*, and the sort key is *SongTitle*. (For easier readability, long commands in this section are broken into separate lines.)

```
aws dynamodb create-table \
    --table-name Music \
    --attribute-definitions \
        AttributeName=Artist,AttributeType=S \
        AttributeName=SongTitle,AttributeType=S \
    --key-schema AttributeName=Artist,KeyType=HASH AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=1,WriteCapacityUnits=1 \
    --table-class STANDARD
```

The following commands add new items to the table. These examples use a combination of shorthand syntax and JSON.

```
aws dynamodb put-item \
```

```
--table-name Music \
--item \
  '{"Artist": {"S": "No One You Know"}, "SongTitle": {"S": "Call Me Today"}, \
"AlbumTitle": {"S": "Somewhat Famous"} }' \
--return-consumed-capacity TOTAL

aws dynamodb put-item \
--table-name Music \
--item '{ \
  "Artist": {"S": "Acme Band"}, \
  "SongTitle": {"S": "Happy Day"}, \
  "AlbumTitle": {"S": "Songs About Life"} }' \
--return-consumed-capacity TOTAL
```

On the command line, it can be difficult to compose valid JSON. However, the AWS CLI can read JSON files. For example, consider the following JSON code snippet, which is stored in a file named *key-conditions.json*.

```
{
  "Artist": {
    "AttributeValueList": [
      {
        "S": "No One You Know"
      }
    ],
    "ComparisonOperator": "EQ"
  },
  "SongTitle": {
    "AttributeValueList": [
      {
        "S": "Call Me Today"
      }
    ],
    "ComparisonOperator": "EQ"
  }
}
```

You can now issue a `Query` request using the AWS CLI. In this example, the contents of the *key-conditions.json* file are used for the `--key-conditions` parameter.

```
aws dynamodb query --table-name Music --key-conditions file://key-conditions.json
```

## Using the AWS CLI with downloadable DynamoDB

The AWS CLI can also interact with DynamoDB (Downloadable Version) that runs on your computer. To enable this, add the following parameter to each command:

```
--endpoint-url http://localhost:8000
```

The following example uses the AWS CLI to list the tables in a local database.

```
aws dynamodb list-tables --endpoint-url http://localhost:8000
```

If DynamoDB is using a port number other than the default (8000), modify the `--endpoint-url` value accordingly.

### Note

The AWS CLI can't use the downloadable version of DynamoDB as a default endpoint. Therefore, you must specify `--endpoint-url` with each command.

## Using the API

You can use the AWS Management Console and the AWS Command Line Interface to work interactively with Amazon DynamoDB. However, to get the most out of DynamoDB, you can write application code using the AWS SDKs.

The AWS SDKs provide broad support for DynamoDB in [Java](#), [JavaScript in the browser](#), [.NET](#), [Node.js](#), [PHP](#), [Python](#), [Ruby](#), [C++](#), [Go](#), [Android](#), and [iOS](#). To get started quickly with these languages, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

Before you can use the AWS SDKs with DynamoDB, you must get an AWS access key ID and secret access key. For more information, see [Setting up DynamoDB \(web service\) \(p. 58\)](#).

For a high-level overview of DynamoDB application programming with the AWS SDKs, see [Programming with DynamoDB and the AWS SDKs \(p. 153\)](#).

## Using the NoSQL workbench for DynamoDB

You can also access DynamoDB, by [downloading](#) and using the [NoSQL Workbench for DynamoDB \(p. 759\)](#).

## IP address ranges

Amazon Web Services (AWS) publishes its current IP address ranges in JSON format. To view the current ranges, download [ip-ranges.json](#). For more information, see [AWS IP address ranges](#) in the AWS General Reference.

To find the IP address ranges that you can use to [access to DynamoDB tables and indexes](#), search the ip-ranges.json file for the following string: "service": "DYNAMODB".

**Note**

The IP address ranges do not apply to DynamoDB Streams or DynamoDB Accelerator (DAX).

# Getting started with DynamoDB

Use the hands-on tutorials in this section to help you get started and learn more about Amazon DynamoDB.

## Topics

- [Basic concepts in DynamoDB \(p. 64\)](#)
- [Prerequisites - getting started tutorial \(p. 64\)](#)
- [Step 1: Create a table \(p. 64\)](#)
- [Step 2: Write data to a table using the console or AWS CLI \(p. 68\)](#)
- [Step 3: Read data from a table \(p. 71\)](#)
- [Step 4: Update data in a table \(p. 73\)](#)
- [Step 5: Query data in a table \(p. 75\)](#)
- [Step 6: Create a global secondary index \(p. 78\)](#)
- [Step 7: Query the global secondary index \(p. 81\)](#)
- [Step 8: \(Optional\) clean up resources \(p. 84\)](#)
- [Getting started with DynamoDB: Next steps \(p. 84\)](#)

## Basic concepts in DynamoDB

Before you begin, you should familiarize yourself with the basic concepts in Amazon DynamoDB. For more information, see [DynamoDB core components](#).

Then continue on to [Prerequisites](#) to learn about setting up DynamoDB.

## Prerequisites - getting started tutorial

Before starting the Amazon DynamoDB tutorial, follow the steps in [Setting up DynamoDB](#). Then continue on to [Step 1: Create a table \(p. 64\)](#).

### Note

- If you plan to interact with DynamoDB only through the AWS Management Console, you don't need an AWS access key. Complete the steps in [Signing up for AWS](#), and then continue on to [Step 1: Create a table \(p. 64\)](#).
- If you don't want to sign up for a free tier account, you can set up [DynamoDB Local \(downloadable version\)](#). Then continue on to [Step 1: Create a table \(p. 64\)](#).

## Step 1: Create a table

In this step, you create a `Music` table in Amazon DynamoDB. The table has the following details:

- Partition key — **Artist**
- Sort key — **SongTitle**

For more information about table operations, see [Working with tables and data in DynamoDB \(p. 279\)](#).

**Note**

Before you begin, make sure that you followed the steps in [Prerequisites - getting started tutorial \(p. 64\)](#).

## AWS Management Console

To create a new **Music** table using the DynamoDB console:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Dashboard**.
3. On the right side of the console, choose **Create Table**.

### Create a table

Create an Amazon DynamoDB table for fast and predictable database performance at any scale.

[Learn more](#) 

**Create table**

4. Enter the table details as follows:
  - a. For the table name, enter **Music**.
  - b. For the partition key, enter **Artist**.
  - c. Enter **SongTitle** as the sort key.
  - d. Leave **Default settings** selected.
5. Choose **Create** to create the table.

## Create table

### Table details Info

DynamoDB is a schemaless database that requires only a table name and a primary key when you create the table.

#### Table name

This will be used to identify your table.

Music

Between 3 and 255 characters, containing only letters, numbers, underscores (\_), hyphens (-), and periods (.)

#### Partition key

The partition key is part of the table's primary key. It is a hash value that is used to retrieve items from your table and allocate data across hosts for scalability and availability.

Artist

String



1 to 255 characters and case sensitive.

#### Sort key - optional

You can use a sort key as the second part of a table's primary key. The sort key allows you to sort or search among all items sharing the same partition key.

SongTitle

String



1 to 255 characters and case sensitive.

### Settings

#### Default settings

The fastest way to create your table. You can modify these settings now or after your table has been created.

#### Customize settings

Use these advanced features to make DynamoDB work better for your needs.

### Default settings

#### Read/write capacity Info

Using provisioned capacity mode. Read and write capacity are set to 5 units each with auto scaling enabled.

#### Secondary indexes Info

No secondary indexes have been created. Queries will be run by using the table's partition key and sort key only.

#### Key management for encryption at rest Info

Using the AWS owned customer master key. This key is managed by DynamoDB at no extra cost.

### Tags

Tags are pairs of keys and optional values, that you can assign to AWS resources. You can use tags to control access to your resources or track your AWS spending.

No tags are associated with the resource.

Add new tag

You can add 50 more tags.

API Version 2012-08-10

66

Cancel

Create table

## AWS CLI

The following AWS CLI example creates a new Music table using `create-table`.

```
aws dynamodb create-table \
    --table-name Music \
    --attribute-definitions \
        AttributeName=Artist,AttributeType=S \
        AttributeName=SongTitle,AttributeType=S \
    --key-schema \
        AttributeName=Artist,KeyType=HASH \
        AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput \
        ReadCapacityUnits=5,WriteCapacityUnits=5 \
    --table-class STANDARD
```

Using `create-table` returns the following sample result.

```
{
    "TableDescription": {
        "TableArn": "arn:aws:dynamodb:us-west-2:522194210714:table/Music",
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "WriteCapacityUnits": 5,
            "ReadCapacityUnits": 5
        },
        "TableClassSummary": {
            "LastUpdateDateTime": 1558028402.69,
            "TableClass": "STANDARD"
        },
        "TableSizeBytes": 0,
        "TableName": "Music",
        "TableStatus": "CREATING",
        "TableId": "d04c7240-0e46-435d-b231-d54091fe1017",
        "KeySchema": [
            {
                "KeyType": "HASH",
                "AttributeName": "Artist"
            },
            {
                "KeyType": "RANGE",
                "AttributeName": "SongTitle"
            }
        ],
        "ItemCount": 0,
        "CreationDateTime": 1558028402.69
    }
}
```

Note that the value of the `TableStatus` field is set to `CREATING`.

To verify that DynamoDB has finished creating the `Music` table, use the `describe-table` command.

```
aws dynamodb describe-table --table-name Music | grep TableStatus
```

This command returns the following result. When DynamoDB finishes creating the table, the value of the TableStatus field is set to ACTIVE.

```
"TableStatus": "ACTIVE",
```

After creating the new table, proceed to [Step 2: Write data to a table using the console or AWS CLI \(p. 68\)](#).

## Step 2: Write data to a table using the console or AWS CLI

In this step, you insert several items into the `Music` table that you created in [Step 1: Create a table \(p. 64\)](#).

For more information about write operations, see [Writing an item \(p. 346\)](#).

### AWS Management Console

Follow these steps to write data to the `Music` table using the DynamoDB console.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. In the table list, choose the **Music** table.

The screenshot shows the AWS Management Console interface for DynamoDB. On the left, a sidebar titled 'DynamoDB' lists several options: Dashboard, Tables (which is selected and highlighted with a red oval), Items (New), PartiQL editor (New), Backups, Exports to S3 (New), and Reserved capacity. The main area is titled 'DynamoDB > Tables' and shows a table titled 'Tables (1)'. The table has columns: Name, Status, Partition key, and Sort key. A single row is listed for the 'Music' table, which is also circled in red. The status is 'Active' with a green checkmark, and the partition key and sort key are both 'Artist (String)' and 'SongTitle (String)' respectively.


4. Select **View Items**.

The screenshot shows the 'Music' table view. The title 'Music' is prominently displayed. Below it are two buttons: 'Actions ▾' and 'View items', where 'View items' is circled in red. A search bar labeled 'Find items' is also visible.

5. In the **Items** view, choose **Create item**.

The screenshot shows the 'Items returned (0)' view. It includes a search bar 'Find items', a 'Create item' button (which is circled in red), and standard pagination controls (previous, next, first, last).

6. Choose **Add new attribute**, and then choose **Number**. Name the field **Awards**.



7. Repeat this process to create an **AlbumTitle** of type **String**.
8. Enter the following values for your item:
  - a. For **Artist**, enter **No One You Know** as the value.
  - b. For **SongTitle**, enter **Call Me Today**.
  - c. For **AlbumTitle**, enter **Somewhat Famous**.
  - d. For **Awards**, enter **1**.
9. Choose **Create item**.

Create item

Attributes		Type
Attribute name	Value	
Artist - Partition key	No One You Know	String
SongTitle - Sort key	Call Me Today	String
Awards	1	Number
AlbumTitle	Somewhat Famous	String
<a href="#">Add new attribute ▾</a>		
		<a href="#">Cancel</a> <a href="#">Create item</a>

10. Repeat this process and create another item with the following values:
  - a. For **Artist**, enter **Acme Band**.
  - b. For **SongTitle** enter **Happy Day**.
  - c. For **AlbumTitle**, enter **Songs About Life**.
  - d. For **Awards**, enter **10**.
11. Do this one more time to create another item with the same **Artist** as the previous step, but different values for the other attributes:
  - a. For **Artist**, enter **Acme Band**.
  - b. For **SongTitle** enter **PartiQL Rocks**.
  - c. For **AlbumTitle**, enter **Another Album Title**.
  - d. For **Awards**, enter **8**.

## AWS CLI

The following AWS CLI example creates several new items in the **Music** table. You can do this either through the DynamoDB API or [PartiQL](#), a SQL-compatible query language for DynamoDB.

### DynamoDB API

```
aws dynamodb put-item \
--table-name Music \
--item \
'{"Artist": {"S": "No One You Know"}, "SongTitle": {"S": "Call Me Today"}, \
"AlbumTitle": {"S": "Somewhat Famous"}, "Awards": {"N": "1"}}'

aws dynamodb put-item \
--table-name Music \
--item \
'{"Artist": {"S": "No One You Know"}, "SongTitle": {"S": "Howdy"}, \
"AlbumTitle": {"S": "Somewhat Famous"}, "Awards": {"N": "2"}}'

aws dynamodb put-item \
--table-name Music \
--item \
'{"Artist": {"S": "Acme Band"}, "SongTitle": {"S": "Happy Day"}, "AlbumTitle": \
"S": "Songs About Life"}, "Awards": {"N": "10"} }'

aws dynamodb put-item \
```

```
--table-name Music \
--item \
  {"Artist": {"S": "Acme Band"}, "SongTitle": {"S": "PartiQL Rocks"}, \
"AlbumTitle": {"S": "Another Album Title"}, "Awards": {"N": "8"} }'
```

### PartiQL for DynamoDB

```
aws dynamodb execute-statement --statement "INSERT INTO Music \
    VALUE \
      {'Artist':'No One You Know','SongTitle':'Call Me Today',
'AlbumTitle':'Somewhat Famous', 'Awards':'1'}"

aws dynamodb execute-statement --statement "INSERT INTO Music \
    VALUE \
      {'Artist':'No One You Know','SongTitle':'Howdy', 'AlbumTitle':'Somewhat
Famous', 'Awards':'2'}"

aws dynamodb execute-statement --statement "INSERT INTO Music \
    VALUE \
      {'Artist':'Acme Band','SongTitle':'Happy Day', 'AlbumTitle':'Songs
About Life', 'Awards':'10'}"

aws dynamodb execute-statement --statement "INSERT INTO Music \
    VALUE \
      {'Artist':'Acme Band','SongTitle':'PartiQL Rocks',
'AlbumTitle':'Another Album Title', 'Awards':'8'}"
```

For more information about writing data with PartiQL, see [PartiQL insert statements](#).

For more information about supported data types in DynamoDB, see [Data types](#).

For more information about how to represent DynamoDB data types in JSON, see [Attribute values](#).

After writing data to your table, proceed to [Step 3: Read data from a table \(p. 71\)](#).

## Step 3: Read data from a table

In this step, you will read back an item that was created in [Step 2: Write data to a table using the console or AWS CLI \(p. 68\)](#). You can use the DynamoDB console or the AWS CLI to read an item from the **Music** table by specifying **Artist** and **SongTitle**.

For more information about read operations in DynamoDB, see [Reading an item \(p. 345\)](#).

### AWS Management Console

Follow these steps to read data from the **Music** table using the DynamoDB console.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Music** table from the table list.
4. Select the **View items**.
5. On the **Items** tab, view the list of items stored in the table, sorted by **Artist** and **SongTitle**. The first item in the list is the one with the **Artist Acme Band** and the **SongTitle Happy Day**.

DynamoDB > Items

**Items** Info Autopreview

> ▾ **Music** View table details

**Query** **Scan**

Table or index **Music**

Artist (Partition key)

SongTitle (Sort key)   Sort descending

▶ Filters

**Run** **Reset**

⌚ Completed Read capacity units consumed: 0.5

**Items returned (2)** Actions Create item

< 1 > ⟳ ✖

	Artist	SongTitle	AlbumTitle	Awards	
<input type="checkbox"/>	Acme Band	Happy Day	Songs Abou...	10	<span>⋮</span>
<input type="checkbox"/>	No One You...	Call Me Today	Somewhat ...	1	<span>⋮</span>

## AWS CLI

The following AWS CLI example reads an item from the `Music`. You can do this either through the DynamoDB API or [PartiQL](#), a SQL-compatible query language for DynamoDB.

### DynamoDB API

#### Note

The default behavior for DynamoDB is eventually consistent reads. The `consistent-read` parameter is used below to demonstrate strongly consistent reads.

```
aws dynamodb get-item --consistent-read \
--table-name Music \
--key '{ "Artist": {"S": "Acme Band"}, "SongTitle": {"S": "Happy Day"} }'
```

Using `get-item` returns the following sample result.

```
{  
    "Item": {  
        "AlbumTitle": {  
            "S": "Songs About Life"  
        },  
        "Awards": {  
            "N": "10"  
        },  
        "SongTitle": {  
            "S": "Happy Day"  
        },  
        "Artist": {  
            "S": "Acme Band"  
        }  
    }  
}
```

#### PartiQL for DynamoDB

```
aws dynamodb execute-statement --statement "SELECT * FROM Music \n  
WHERE Artist='Acme Band' AND  
SongTitle='Happy Day'"
```

Using the PartiQL Select statement returns the following sample result.

```
{  
    "Items": [  
        {  
            "AlbumTitle": {  
                "S": "Songs About Life"  
            },  
            "Awards": {  
                "S": "10"  
            },  
            "Artist": {  
                "S": "Acme Band"  
            },  
            "SongTitle": {  
                "S": "Happy Day"  
            }  
        }  
    ]  
}
```

For more information about reading data with PartiQL, see [PartiQL select statements](#).

To update the data in your table, proceed to [Step 4: Update data in a table \(p. 73\)](#).

## Step 4: Update data in a table

In this step, you update an item that you created in [Step 2: Write data to a table using the console or AWS CLI \(p. 68\)](#). You can use the DynamoDB console or the AWS CLI to update the `AlbumTitle` of an item in the `Music` table by specifying `Artist`, `SongTitle`, and the updated `AlbumTitle`.

For more information about write operations, see [Writing an item \(p. 346\)](#).

## AWS Management Console

You can use the DynamoDB console to update data in the **Music** table.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Music** table from the table list.
4. Choose **View items**.
5. Choose the item whose **Artist** value is **Acme Band** and **SongTitle** value is **Happy Day**.
6. Update the **AlbumTitle** value to **Updated Album Title**, and then choose **Save**.

The following image shows the updated item on the console.

The screenshot shows the AWS Management Console Item editor for the Music table. The 'Attributes' section displays four items:

Attribute name	Value	Type	Action
Artist - Partition key	Acme Band	String	New
SongTitle - Sort key	Happy Day	String	New
AlbumTitle	Updated Album Title	String	Remove
Awards	10	Number	Remove

At the bottom, there are 'Add new attribute' and 'Save changes' buttons.

## AWS CLI

The following AWS CLI example updates an item in the **Music** table. You can do this either through the DynamoDB API or [PartiQL](#), a SQL-compatible query language for DynamoDB.

### DynamoDB API

```
aws dynamodb update-item \  
  --table-name Music \  
  --key '{ "Artist": {"S": "Acme Band"}, "SongTitle": {"S": "Happy Day"} }' \  
  --update-expression "SET AlbumTitle = :newval" \  
  --expression-attribute-values '{":newval":{"S":"Updated Album Title"}}' \  
  --return-values ALL_NEW
```

Using `update-item` returns the following sample result because `return-values ALL_NEW` was specified.

```
{  
    "Attributes": {  
        "AlbumTitle": {  
            "S": "Updated Album Title"  
        },  
        "Awards": {  
            "N": "10"  
        },  
    },  
}
```

```
        "SongTitle": {  
            "S": "Happy Day"  
        },  
        "Artist": {  
            "S": "Acme Band"  
        }  
    }  
}
```

#### PartiQL for DynamoDB

```
aws dynamodb execute-statement --statement "UPDATE Music \  
SET AlbumTitle='Updated Album Title' \  
WHERE Artist='Acme Band' AND  
SongTitle='Happy Day' \  
RETURNING ALL NEW *"
```

Using the Update statement returns the following sample result because RETURNING ALL NEW \* was specified.

```
{  
    "Items": [  
        {  
            "AlbumTitle": {  
                "S": "Updated Album Title"  
            },  
            "Awards": {  
                "S": "10"  
            },  
            "Artist": {  
                "S": "Acme Band"  
            },  
            "SongTitle": {  
                "S": "Happy Day"  
            }  
        }  
    ]  
}
```

For more information about updating data with PartiQL, see [PartiQL update statements](#).

To query the data in the `Music` table, proceed to [Step 5: Query data in a table \(p. 75\)](#).

## Step 5: Query data in a table

In this step, you query the data that you wrote to the `Music` table in [the section called "Step 2: Write data" \(p. 68\)](#) by specifying `Artist`. This will display all songs that are associated with the partition key: `Artist`.

For more information about query operations, see [Query operations in DynamoDB \(p. 428\)](#).

### AWS Management Console

Follow these steps to use the DynamoDB console to query data in the `Music` table.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.

2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Music** table from the table list.
4. Choose **View items**.
5. Choose **Query**.
6. For **Partition key**, enter **Acme Band**, and then choose **Run**.

DynamoDB > Items

Items [Info](#) Autopreview [View table details](#)

> ▾ **Music**

[Query](#) [Scan](#)

Table or index [Music](#)

Artist (Partition key)

SongTitle (Sort key)

Equal to   Sort descending

▶ Filters

[Run](#) [Reset](#)

## AWS CLI

The following AWS CLI example queries an item in the `Music` table. You can do this either through the DynamoDB API or [PartiQL](#), a SQL-compatible query language for DynamoDB.

### DynamoDB API

You query an item through the DynamoDB API by using `query` and providing the partition key.

```
aws dynamodb query \
--table-name Music \
--key-condition-expression "Artist = :name" \
--expression-attribute-values '{":name":{"S":"Acme Band"}}'
```

Using `query` returns all the songs associated with this particular `Artist`.

```
{
  "Items": [
    {
      "AlbumTitle": {
        "S": "Updated Album Title"
      },
      "Awards": {
```

```
        "N": "10"
    },
    "Artist": {
        "S": "Acme Band"
    },
    "SongTitle": {
        "S": "Happy Day"
    }
},
{
    "AlbumTitle": {
        "S": "Another Album Title"
    },
    "Awards": {
        "N": "8"
    },
    "Artist": {
        "S": "Acme Band"
    },
    "SongTitle": {
        "S": "PartiQL Rocks"
    }
}
],
"Count": 2,
"ScannedCount": 2,
"ConsumedCapacity": null
}
```

### PartiQL for DynamoDB

You query an item through PartiQL by using the `Select` statement and providing the partition key.

```
aws dynamodb execute-statement --statement "SELECT * FROM Music  \
WHERE Artist='Acme Band'"
```

Using the `Select` statement in this way returns all the songs associated with this particular `Artist`.

```
{
    "Items": [
        {
            "AlbumTitle": {
                "S": "Updated Album Title"
            },
            "Awards": {
                "S": "10"
            },
            "Artist": {
                "S": "Acme Band"
            },
            "SongTitle": {
                "S": "Happy Day"
            }
        }
    ]
}
```

For more information about querying data with PartiQL, see [PartiQL select statements](#).

To create a global secondary index for your table, proceed to [Step 6: Create a global secondary index \(p. 78\)](#).

## Step 6: Create a global secondary index

In this step, you create a global secondary index for the **Music** table that you created in [Step 1: Create a table \(p. 64\)](#).

For more information about global secondary indexes, see [Using Global Secondary Indexes in DynamoDB \(p. 500\)](#).

### AWS Management Console

To use the Amazon DynamoDB console to create a global secondary index **AlbumTitle-index** for the **Music** table:

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Music** table from the table list.
4. Choose the **Indexes** tab for the Music table.
5. Choose **Create index**.



6. For the **Partition key**, enter **AlbumTitle**.
7. For **Index name**, enter **AlbumTitle-index**.
8. Leave the other settings on their default values and choose **Create index**.

DynamoDB > Tables > Music > Create index

## Create global secondary index [Info](#)

Global secondary indexes allow you to perform queries on attributes that are not part of a table's primary key. Note that global secondary index read and write capacity settings are separate from those of the table, and they will incur additional costs.

### Index details [Info](#)

#### Partition key

AlbumTitle

#### Data type

String

1 to 255 characters.

#### Sort key - optional

Enter the sort key name

#### Data type

String

1 to 255 characters.

#### Index name

AlbumTitle-index

Between 3 and 255 characters. Only A–Z, a–z, 0–9, underscore characters, hyphens, and periods allowed.

### Index capacity [Info](#)

#### Read capacity

##### Read capacity settings

- Copy from base table
- Customize settings

##### Auto scaling [Info](#)

Dynamically adjusts provisioned throughput capacity on your behalf in response to actual traffic patterns.

- On
- Off

##### Minimum capacity units

1

##### Maximum capacity units

10

##### Target utilization (%)

70

#### Write capacity

##### Write capacity settings

- Copy from base table
- Customize settings

##### Auto scaling [Info](#)

Dynamically adjusts provisioned throughput capacity on your behalf in response to actual traffic patterns.

- On
- Off

##### Minimum capacity units

1

##### Maximum capacity units

API Version 2012-08-10

##### Target utilization (%)

70

79

### Attribute projections [Info](#)

## AWS CLI

The following AWS CLI example creates a global secondary index `AlbumTitle-index` for the `Music` table using `update-table`.

```
aws dynamodb update-table \
    --table-name Music \
    --attribute-definitions AttributeName=AlbumTitle,AttributeType=S \
    --global-secondary-index-updates \
        "[{\\"Create\\":{\\\"IndexName\\\": \\"AlbumTitle-index\\\", \\\"KeySchema\\\": [{\\\"AttributeName\\\": \\\"AlbumTitle\\\", \\\"KeyType\\\": \\\"HASH\\\"}], \
            \\\"ProvisionedThroughput\\\": {\\\"ReadCapacityUnits\\\": 10, \\\"WriteCapacityUnits\\\": 5}, \
            \\\"Projection\\\":{\\\"ProjectionType\\\": \\\"ALL\\\"}}}]"
```

Using `update-table` returns the following sample result.

```
{
    "TableDescription": {
        "TableArn": "arn:aws:dynamodb:us-west-2:522194210714:table/Music",
        "AttributeDefinitions": [
            {
                "AttributeName": "AlbumTitle",
                "AttributeType": "S"
            },
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "GlobalSecondaryIndexes": [
            {
                "IndexSizeBytes": 0,
                "IndexName": "AlbumTitle-index",
                "Projection": {
                    "ProjectionType": "ALL"
                },
                "ProvisionedThroughput": {
                    "NumberOfDecreasesToday": 0,
                    "WriteCapacityUnits": 5,
                    "ReadCapacityUnits": 10
                },
                "IndexStatus": "CREATING",
                "Backfilling": false,
                "KeySchema": [
                    {
                        "KeyType": "HASH",
                        "AttributeName": "AlbumTitle"
                    }
                ],
                "IndexArn": "arn:aws:dynamodb:us-west-2:522194210714:table/Music/index/AlbumTitle-index",
                "ItemCount": 0
            }
        ],
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "WriteCapacityUnits": 5,
            "ReadCapacityUnits": 10
        }
    }
}
```

```
"TableSizeBytes": 0,  
"TableName": "Music",  
"TableStatus": "UPDATING",  
"TableId": "d04c7240-0e46-435d-b231-d54091fe1017",  
"KeySchema": [  
    {  
        "KeyType": "HASH",  
        "AttributeName": "Artist"  
    },  
    {  
        "KeyType": "RANGE",  
        "AttributeName": "SongTitle"  
    }  
,  
    "ItemCount": 0,  
    "CreationDateTime": 1558028402.69  
}  
}
```

Note that the value of the `IndexStatus` field is set to `CREATING`.

To verify that DynamoDB has finished creating the `AlbumTitle-index` global secondary index, use the `describe-table` command.

```
aws dynamodb describe-table --table-name Music | grep IndexStatus
```

This command returns the following result. The index is ready for use when the value of the `IndexStatus` field returned is set to `ACTIVE`.

```
"IndexStatus": "ACTIVE",
```

Next, you can query the global secondary index. For details, see [Step 7: Query the global secondary index \(p. 81\)](#).

## Step 7: Query the global secondary index

In this step, you query a global secondary index on the `Music` table using the Amazon DynamoDB console or the AWS CLI.


For more information about global secondary indexes, see [Using Global Secondary Indexes in DynamoDB \(p. 500\)](#).

### AWS Management Console

Follow these steps to use the DynamoDB console to query data through the `AlbumTitle-index` global secondary index.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Music** table from the table list.
4. Select the **View items**.
5. Choose **Query**.
6. In the drop-down list under **Query**, choose **AlbumTitle-index**.

For **AlbumTitle**, enter **Somewhat Famous**, and then choose **Run**.



## AWS CLI

The following AWS CLI example queries a global secondary index `AlbumTitle-index` on the `Music` table. You can do this either through the DynamoDB API or [PartiQL](#), a SQL-compatible query language for DynamoDB.

### DynamoDB API

You query the global secondary index through the DynamoDB API by using `query` and providing the index name.

```
aws dynamodb query \
    --table-name Music \
    --index-name AlbumTitle-index \
    --key-condition-expression "AlbumTitle = :name" \
    --expression-attribute-values '{":name":{"S":"Somewhat Famous"}}'
```

Using `query` returns the following sample result.

```
{
  "Items": [
    {
      "AlbumTitle": {
        "S": "Somewhat Famous"
      },
      "Awards": {
        "S": "1"
      },
      "Artist": {
        "S": "No One You Know"
      },
      "SongTitle": {
        "S": "Call Me Today"
      }
    },
    {
      "AlbumTitle": {
        "S": "Somewhat Famous"
      },
      "Awards": {
        "N": "2"
      },
    }
  ]
}
```

```

        "Artist": {
            "S": "No One You Know"
        },
        "SongTitle": {
            "S": "Howdy"
        }
    }
],
"Count": 2,
"ScannedCount": 2,
"ConsumedCapacity": null
}

```

### PartiQL for DynamoDB

You query the global secondary index through PartiQL by using the `Select` statement and providing the index name.

**Note**

You'll need to escape the double quotes around `Music` and `AlbumTitle-index` since you're doing this through the CLI.

```
aws dynamodb execute-statement --statement "SELECT * FROM \"Music\".\"AlbumTitle-index\"
WHERE AlbumTitle='Somewhat Famous'"
```

Using the `Select` statement in this way returns the following sample result.

```

{
    "Items": [
        {
            "AlbumTitle": {
                "S": "Somewhat Famous"
            },
            "Awards": {
                "S": "1"
            },
            "Artist": {
                "S": "No One You Know"
            },
            "SongTitle": {
                "S": "Call Me Today"
            }
        },
        {
            "AlbumTitle": {
                "S": "Somewhat Famous"
            },
            "Awards": {
                "S": "2"
            },
            "Artist": {
                "S": "No One You Know"
            },
            "SongTitle": {
                "S": "Howdy"
            }
        }
    ]
}

```

For more information about querying data with PartiQL, see [PartiQL select statements](#).

## Step 8: (Optional) clean up resources


If you no longer need the Amazon DynamoDB table that you created for the tutorial, you can delete it. This step helps ensure that you aren't charged for resources that you aren't using. You can use the DynamoDB console or the AWS CLI to delete the **Music** table that you created in [Step 1: Create a table \(p. 64\)](#).

For more information about table operations in DynamoDB, see [Working with tables and data in DynamoDB \(p. 279\)](#).

### AWS Management Console

To delete the **Music** table using the console:

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Music** table from the table list.
4. Choose the **Indexes** tab for the **Music** table.
5. Choose **Delete table**.



### AWS CLI

The following AWS CLI example deletes the **Music** table using `delete-table`.

```
aws dynamodb delete-table --table-name Music
```

## Getting started with DynamoDB: Next steps

For more information about using Amazon DynamoDB, see the following topics:

- [Working with tables and data in DynamoDB \(p. 279\)](#)
- [Working with items and attributes \(p. 344\)](#)
- [Query operations in DynamoDB \(p. 428\)](#)
- [Using Global Secondary Indexes in DynamoDB \(p. 500\)](#)
- [Working with transactions \(p. 577\)](#)
- [In-memory acceleration with DynamoDB Accelerator \(DAX\) \(p. 655\)](#)
- [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#)
- [Programming with DynamoDB and the AWS SDKs \(p. 153\)](#)

# Getting started with DynamoDB and AWS SDKs

This section contains hands-on tutorials to help you learn about Amazon DynamoDB. The code examples in these tutorials can run against either the downloadable version of DynamoDB or the DynamoDB web service.

## Topics

- [Create a DynamoDB table \(p. 85\)](#)
- [Write an item to a DynamoDB table \(p. 95\)](#)
- [Read an item from a DynamoDB table \(p. 105\)](#)
- [Update an item in a DynamoDB table \(p. 113\)](#)
- [Delete an item in a DynamoDB table \(p. 123\)](#)
- [Query a DynamoDB table \(p. 131\)](#)
- [Scan a DynamoDB table \(p. 143\)](#)
- [Using DynamoDB with an AWS SDK \(p. 152\)](#)

## Create a DynamoDB table

You can create a table using the AWS Management Console, the AWS CLI, or an AWS SDK. For more information on tables, see [Core components of Amazon DynamoDB \(p. 2\)](#).

### Create a DynamoDB table using an AWS SDK

The following code examples show how to create a DynamoDB table using an AWS SDK.

.NET

#### AWS SDK for .NET

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Creates a new Amazon DynamoDB table and then waits for the new
/// table to become active.
/// </summary>
/// <param name="client">An initialized Amazon DynamoDB client object.</
param>
/// <param name="tableName">The name of the table to create.</param>
/// <returns>A Boolean value indicating the success of the operation.</
returns>
```

```
public static async Task<bool> CreateMovieTableAsync(AmazonDynamoDBClient
client, string tableName)
{
    var response = await client.CreateTableAsync(new CreateTableRequest
    {
        TableName = tableName,
        AttributeDefinitions = new List<AttributeDefinition>()
        {
            new AttributeDefinition
            {
                AttributeName = "title",
                AttributeType = "S",
            },
            new AttributeDefinition
            {
                AttributeName = "year",
                AttributeType = "N",
            },
        },
        KeySchema = new List<KeySchemaElement>()
        {
            new KeySchemaElement
            {
                AttributeName = "year",
                KeyType = "HASH",
            },
            new KeySchemaElement
            {
                AttributeName = "title",
                KeyType = "RANGE",
            },
        },
        ProvisionedThroughput = new ProvisionedThroughput
        {
            ReadCapacityUnits = 5,
            WriteCapacityUnits = 5,
        },
    });
}

// Wait until the table is ACTIVE and then report success.
Console.WriteLine("Waiting for table to become active...");

var request = new DescribeTableRequest
{
    TableName = response.TableDescription.TableName,
};

TableStatus status;

int sleepDuration = 2000;

do
{
    System.Threading.Thread.Sleep(sleepDuration);

    var describeTableResponse = await
client.DescribeTableAsync(request);
    status = describeTableResponse.Table.TableStatus;

    Console.WriteLine(".");
}
while (status != "ACTIVE");

return status == TableStatus.ACTIVE;
}
```

- For API details, see [CreateTable in AWS SDK for .NET API Reference](#).

C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
if (!region.empty())
    clientConfig.region = region;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

std::cout << "Creating table " << table <<
    " with a simple primary key: \"Name\"" << std::endl;

Aws::DynamoDB::Model::CreateTableRequest req;

Aws::DynamoDB::Model::AttributeDefinition haskKey;
haskKey.SetAttributeName("Name");
haskKey.SetAttributeType(Aws::DynamoDB::Model::ScalarAttributeType::S);
req.AddAttributeDefinitions(haskKey);

Aws::DynamoDB::Model::KeySchemaElement keyselt;

keyselt.WithAttributeName("Name").WithKeyType(Aws::DynamoDB::Model::KeyType::HASH);
req.AddKeySchema(keyselt);

Aws::DynamoDB::Model::ProvisionedThroughput thruput;
thruput.WithReadCapacityUnits(5).WithWriteCapacityUnits(5);
req.SetProvisionedThroughput(thruput);
req.SetTableName(table);

const Aws::DynamoDB::Model::CreateTableOutcome& result =
dynamoClient.CreateTable(req);
if (result.IsSuccess())
{
    std::cout << "Table \""
result.GetResult().GetTableDescription().GetTableName() <<
        " created!" << std::endl;
}
else
{
    std::cout << "Failed to create table: " <<
result.GetError().GetMessage();
}
```

- For API details, see [CreateTable in AWS SDK for C++ API Reference](#).

Go

### SDK for Go V2

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// CreateMovieTable creates a DynamoDB table with a composite primary key defined
// as
// a string sort key named `title`, and a numeric partition key named `year`.
// This function uses NewTableExistsWaiter to wait for the table to be created by
// DynamoDB before it returns.
func (basics TableBasics) CreateMovieTable() (*types.TableDescription, error) {
    var tableDesc *types.TableDescription
    table, err := basics.DynamoDbClient.CreateTable(context.TODO(),
        &dynamodb.CreateTableInput{
            AttributeDefinitions: []types.AttributeDefinition{
                {AttributeName: aws.String("year")},
                {AttributeType: types.ScalarAttributeTypeN},
            },
            {AttributeName: aws.String("title")},
            {AttributeType: types.ScalarAttributeTypeS},
        },
        KeySchema: []types.KeySchemaElement{
            {AttributeName: aws.String("year")},
            {KeyType:      types.KeyTypeHash},
        },
        {AttributeName: aws.String("title")},
        {KeyType:      types.KeyTypeRange},
    },
    TableName: aws.String(basics.TableName),
    ProvisionedThroughput: &types.ProvisionedThroughput{
        ReadCapacityUnits: aws.Int64(10),
        WriteCapacityUnits: aws.Int64(10),
    },
})
if err != nil {
    log.Printf("Couldn't create table %v. Here's why: %v\n", basics.TableName, err)
} else {
    waiter := dynamodb.NewTableExistsWaiter(basics.DynamoDbClient)
    err = waiter.Wait(context.TODO(), &dynamodb.DescribeTableInput{
        TableName: aws.String(basics.TableName)},
        5*time.Minute)
    if err != nil {
        log.Printf("Wait for table exists failed. Here's why: %v\n", err)
    }
    tableDesc = table.TableDescription
}
return tableDesc, err
}
```

- For API details, see  [CreateTable in AWS SDK for Go API Reference](#).

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static String createTable(DynamoDbClient ddb, String tableName, String key) {
    DynamoDbWaiter dbWaiter = ddb.waiter();
    CreateTableRequest request = CreateTableRequest.builder()
        .attributeDefinitions(AttributeDefinition.builder()
            .attributeName(key)
            .attributeType(ScalarAttributeType.S)
            .build())
        .keySchema(KeySchemaElement.builder()
            .attributeName(key)
            .keyType(KeyType.HASH)
            .build())
        .provisionedThroughput(ProvisionedThroughput.builder()
            .readCapacityUnits(new Long(10))
            .writeCapacityUnits(new Long(10))
            .build())
        .tableName(tableName)
        .build());

    String newTable = "";
    try {
        CreateTableResponse response = ddb.createTable(request);
        DescribeTableRequest tableRequest = DescribeTableRequest.builder()
            .tableName(tableName)
            .build();

        // Wait until the Amazon DynamoDB table is created.
        WaiterResponse<DescribeTableResponse> waiterResponse =
        dbWaiter.waitUntilTableExists(tableRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        newTable = response.tableDescription().tableName();
        return newTable;
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return "";
}
```

- For API details, see [CreateTable in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon DynamoDB service client object.
const ddbClient = new DynamoDBClient({ region: REGION });
export { ddbClient };
```

Create the table.

```
// Import required AWS SDK clients and commands for Node.js
import { CreateTableCommand } from "@aws-sdk/client-dynamodb";
import { ddbClient } from "./libs/ddbClient.js";

// Set the parameters
export const params = {
    AttributeDefinitions: [
        {
            AttributeName: "Season", //ATTRIBUTE_NAME_1
            AttributeType: "N", //ATTRIBUTE_TYPE
        },
        {
            AttributeName: "Episode", //ATTRIBUTE_NAME_2
            AttributeType: "N", //ATTRIBUTE_TYPE
        },
    ],
    KeySchema: [
        {
            AttributeName: "Season", //ATTRIBUTE_NAME_1
            KeyType: "HASH",
        },
        {
            AttributeName: "Episode", //ATTRIBUTE_NAME_2
            KeyType: "RANGE",
        },
    ],
    ProvisionedThroughput: {
        ReadCapacityUnits: 1,
        WriteCapacityUnits: 1,
    },
    TableName: "TEST_TABLE", //TABLE_NAME
    StreamSpecification: {
        StreamEnabled: false,
    },
};

export const run = async () => {
    try {
        const data = await ddbClient.send(new CreateTableCommand(params));
        console.log("Table Created", data);
        return data;
    } catch (err) {
        console.log("Error", err);
    }
};
run();
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [CreateTable](#) in [AWS SDK for JavaScript API Reference](#).

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});
```

```

var params = {
    AttributeDefinitions: [
        {
            AttributeName: 'CUSTOMER_ID',
            AttributeType: 'N'
        },
        {
            AttributeName: 'CUSTOMER_NAME',
            AttributeType: 'S'
        }
    ],
    KeySchema: [
        {
            AttributeName: 'CUSTOMER_ID',
            KeyType: 'HASH'
        },
        {
            AttributeName: 'CUSTOMER_NAME',
            KeyType: 'RANGE'
        }
    ],
    ProvisionedThroughput: {
        ReadCapacityUnits: 1,
        WriteCapacityUnits: 1
    },
    TableName: 'CUSTOMER_LIST',
    StreamSpecification: {
        StreamEnabled: false
    }
};

// Call DynamoDB to create the table
ddb.createTable(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Table Created", data);
    }
});

```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [CreateTable in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

suspend fun createNewTable(tableNameVal: String, key: String): String? {

    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.S
    }
}

```

```

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef)
        keySchema = listOf(keySchemaVal)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        var tableArn: String
        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        tableArn = response.tableDescription!!.tableArn.toString()
        println("Table $tableArn is ready")
        return tableArn
    }
}

```

- For API details, see [CreateTable in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a table.

```

$tableName = "ddb_demo_table_$uuid";
$service->createTable(
    $tableName,
    [
        new DynamoDBAttribute('year', 'N', 'HASH'),
        new DynamoDBAttribute('title', 'S', 'RANGE')
    ]
);

public function createTable(string $tableName, array $attributes)
{
    $keySchema = [];
    $attributeDefinitions = [];
    foreach ($attributes as $attribute) {
        if (is_a($attribute, DynamoDBAttribute::class)) {
            $keySchema[] = ['AttributeName' => $attribute->AttributeName,
'KeyType' => $attribute->KeyType];
            $attributeDefinitions[] =
                ['AttributeName' => $attribute->AttributeName, 'AttributeType'
=> $attribute->AttributeType];
        }
    }
}

```

```

        }

        $this->dynamoDbClient->createTable([
            'TableName' => $tableName,
            'KeySchema' => $keySchema,
            'AttributeDefinitions' => $attributeDefinitions,
            'ProvisionedThroughput' => ['ReadCapacityUnits' => 10,
            'WriteCapacityUnits' => 10],
        ]);
    }
}

```

- For API details, see [CreateTable in AWS SDK for PHP API Reference](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a table for storing movie data.

```

class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def create_table(self, table_name):
        """
        Creates an Amazon DynamoDB table that can be used to store movie data.
        The table uses the release year of the movie as the partition key and the
        title as the sort key.

        :param table_name: The name of the table to create.
        :return: The newly created table.
        """
        try:
            self.table = self.dyn_resource.create_table(
                TableName=table_name,
                KeySchema=[
                    {'AttributeName': 'year', 'KeyType': 'HASH'}, # Partition key
                    {'AttributeName': 'title', 'KeyType': 'RANGE'} # Sort key
                ],
                AttributeDefinitions=[
                    {'AttributeName': 'year', 'AttributeType': 'N'},
                    {'AttributeName': 'title', 'AttributeType': 'S'}
                ],
                ProvisionedThroughput={'ReadCapacityUnits': 10,
                'WriteCapacityUnits': 10})
            self.table.wait_until_exists()
        except ClientError as err:
            logger.error(
                "Couldn't create table %s. Here's why: %s: %s",
                table_name,
                err.response['Error']['Code'],
                err.response['Error']['Message'])
            raise
        else:
            return self.table
}

```

- For API details, see [CreateTable in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Creates an Amazon DynamoDB table that can be used to store movie data.
# The table uses the release year of the movie as the partition key and the
# title as the sort key.
#
# @param table_name [String] The name of the table to create.
# @return [Aws::DynamoDB::Table] The newly created table.
def create_table(table_name)
  @table = @dynamo_resource.create_table(
    table_name: table_name,
    key_schema: [
      {attribute_name: "year", key_type: "HASH"}, # Partition key
      {attribute_name: "title", key_type: "RANGE"} # Sort key
    ],
    attribute_definitions: [
      {attribute_name: "year", attribute_type: "N"},
      {attribute_name: "title", attribute_type: "S"}
    ],
    provisioned_throughput: {read_capacity_units: 10, write_capacity_units: 10})
  @dynamo_resource.client.wait_until(:table_exists, table_name: table_name)
rescue Aws::Errors::ServiceError => e
  puts("Couldn't create table #{table_name}. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
else
  @table
end
```

- For API details, see [CreateTable in AWS SDK for Ruby API Reference](#).

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn create_table(client: &Client, table: &str, key: &str) -> Result<(), Error>
{
  let a_name: String = key.into();
  let table_name: String = table.into();

  let ad = AttributeDefinition::builder()
    .attribute_name(&a_name)
    .attribute_type(ScalarAttributeType::S)
    .build();
```

```
let ks = KeySchemaElement::builder()
    .attribute_name(&a_name)
    .key_type(KeyType::Hash)
    .build();

let pt = ProvisionedThroughput::builder()
    .read_capacity_units(10)
    .write_capacity_units(5)
    .build();

match client
    .create_table()
    .table_name(table_name)
    .key_schema(ks)
    .attribute_definitions(ad)
    .provisioned_throughput(pt)
    .send()
    .await
{
    Ok(_) => println!("Added table {} with key {}", table, key),
    Err(e) => {
        println!("Got an error creating table:");
        println!("{}: {}", e);
        process::exit(1);
    }
};

Ok(())
}
```

- For API details, see [CreateTable](#) in *AWS SDK for Rust API reference*.

For more DynamoDB examples, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

## Write an item to a DynamoDB table

You can write items to DynamoDB tables using the AWS Management Console, the AWS CLI, or an AWS SDK. For more information on items, see [Core components of Amazon DynamoDB \(p. 2\)](#).

### Write an item to a DynamoDB table using an AWS SDK

The following code examples show how to write an item to a DynamoDB table using an AWS SDK.

.NET

#### AWS SDK for .NET

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Adds a new item to the table.
```

```
/// </summary>
/// <param name="client">An initialized Amazon DynamoDB client object.</param>
/// <param name="newMovie">A Movie object containing information for
/// the movie to add to the table.</param>
/// <param name="tableName">The name of the table where the item will be
/// added.</param>
/// <returns>A Boolean value that indicates the results of adding the
/// item.</returns>
public static async Task<bool> PutItemAsync(AmazonDynamoDBClient client,
Movie newMovie, string tableName)
{
    var item = new Dictionary<string, AttributeValue>
    {
        ["title"] = new AttributeValue { S = newMovie.Title },
        ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
    };

    var request = new PutItemRequest
    {
        TableName = tableName,
        Item = item,
    };

    var response = await client.PutItemAsync(request);
    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [PutItem](#) in *AWS SDK for .NET API Reference*.

## C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

Aws::DynamoDB::Model::PutItemRequest putItemRequest;
putItemRequest.SetTableName(table);

Aws::DynamoDB::Model::AttributeValue av;
av.SetS(keyVal);

Aws::DynamoDB::Model::AttributeValue album;
album.SetS(AlbumTitleValue);

Aws::DynamoDB::Model::AttributeValue awards;
awards.SetS(AwardVal);

Aws::DynamoDB::Model::AttributeValue song;
song.SetS(SongTitleVal);

// Add all AttributeValue objects.
putItemRequest.AddItem(key, av);
putItemRequest.AddItem(albumTitle, album);
putItemRequest.AddItem(Awards, awards);
putItemRequest.AddItem(SongTitle, song);
```

```
const Aws::DynamoDB::Model::PutItemOutcome result =
dynamoClient.PutItem(putItemRequest);
if (!result.IsSuccess())
{
    std::cout << result.GetError().GetMessage() << std::endl;
    return 1;
}
std::cout << "Successfully added Item!" << std::endl;
```

- For API details, see [PutItem](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName      string
}

// AddMovie adds a movie to the DynamoDB table.
func (basics TableBasics) AddMovie(movie Movie) error {
    item, err := attributevalue.MarshalMap(movie)
    if err != nil {
        panic(err)
    }
    _, err = basics.DynamoDbClient.PutItem(context.TODO(), &dynamodb.PutItemInput{
        TableName: aws.String(basics.TableName), Item: item,
    })
    if err != nil {
        log.Printf("Couldn't add item to table. Here's why: %v\n", err)
    }
    return err
}
```

- For API details, see [PutItem](#) in *AWS SDK for Go API Reference*.

Java

## SDK for Java 2.x

### Tip

To learn how to set up and run this example, see [GitHub](#).

Puts an item into a table by using the enhanced client.

```
public static void putRecord(DynamoDbEnhancedClient enhancedClient) {
```

```
try {
    DynamoDbTable<Customer> custTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));

    // Create an Instant value.
    LocalDate localDate = LocalDate.parse("2020-04-07");
    LocalDateTime localDateTime = localDate.atStartOfDay();
    Instant instant = localDateTime.toInstant(ZoneOffset.UTC);

    // Populate the Table.
    Customer custRecord = new Customer();
    custRecord.setCustName("Tom red");
    custRecord.setId("id119");
    custRecord.setEmail("tred@noserver.com");
    custRecord.setRegistrationDate(instant) ;

    // Put the customer data into an Amazon DynamoDB table.
    custTable.putItem(custRecord);

} catch (DynamoDbException e) {
    System.err.println(e.getMessage());
    System.exit(1);
}
System.out.println("Customer data added to the table.");
}
```

- For API details, see [PutItem](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
```

```

    convertClassInstanceToMap: false, // false, by default.
};

const unmarshalOptions = {
  // Whether to return numbers as a string instead of converting them to native
  // JavaScript numbers.
  wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshalOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };

```

Put an item in a table using the DynamoDB document client.

```

import { PutCommand } from "@aws-sdk/lib-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

export const putItem = async () => {
  // Set the parameters.
  export const params = {
    TableName: "TABLE_NAME",
    Item: {
      primaryKey: "VALUE_1",
      sortKey: "VALUE_2",
    },
  };
  try {
    const data = await ddbDocClient.send(new PutCommand(params));
    console.log("Success - item added or updated", data);
  } catch (err) {
    console.log("Error", err.stack);
  }
};
putItem();

```

Put an item in a table using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];

export const run = async (tableName, movieTitle1, movieYear1) => {
  const params = {
    Statement: "INSERT INTO " + tableName + " value {'title':?:, 'year':?}",
    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
  };
  try {
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
    console.log("Success. Item added.");
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};

```

```
    }
};

run(tableName, movieTitle1, movieYear1);
```

Put items by batch in a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2
) => {
  const params = {
    Statements: [
      {
        Statement:
          "INSERT INTO " + tableName + " value {'title':?, 'year':?}",
        Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
      },
      {
        Statement:
          "INSERT INTO " + tableName + " value {'title':?, 'year':?}",
        Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
      },
    ],
  };
  try {
    const data = await ddbDocClient.send(
      new BatchExecuteStatementCommand(params)
    );
    console.log("Success. Items added.");
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);
```

- For API details, see [PutItem](#) in *AWS SDK for JavaScript API Reference*.

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Put an item in a table.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
```

```
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
    TableName: 'CUSTOMER_LIST',
    Item: {
        'CUSTOMER_ID' : {N: '001'},
        'CUSTOMER_NAME' : {S: 'Richard Roe'}
    }
};

// Call DynamoDB to add the item to the table
ddb.putItem(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Success", data);
    }
});
```

Put an item in a table using the DynamoDB document client.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
    TableName: 'TABLE',
    Item: {
        'HASHKEY': VALUE,
        'ATTRIBUTE_1': 'STRING_VALUE',
        'ATTRIBUTE_2': VALUE_2
    }
};

docClient.put(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Success", data);
    }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [PutItem](#) in [AWS SDK for JavaScript API Reference](#).

Kotlin

## SDK for Kotlin

### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun putItemInTable(  
    tableNameVal: String,  
    key: String,  
    keyVal: String,  
    albumTitle: String,  
    albumTitleValue: String,  
    awards: String,  
    awardVal: String,  
    songTitle: String,  
    songTitleVal: String  
) {  
    val itemValues = mutableMapOf<String, AttributeValue>()  
  
    // Add all content to the table.  
    itemValues[key] = AttributeValue.S(keyVal)  
    itemValues[songTitle] = AttributeValue.S(songTitleVal)  
    itemValues[albumTitle] = AttributeValue.S(albumTitleValue)  
    itemValues[awards] = AttributeValue.S(awardVal)  
  
    val request = PutItemRequest {  
        tableName = tableNameVal  
        item = itemValues  
    }  
  
    DynamoDbClient { region = "us-east-1" }.use { ddb ->  
        ddb.putItem(request)  
        println(" A new item was placed into $tableNameVal.")  
    }  
}
```

- For API details, see [PutItem](#) in *AWS SDK for Kotlin API reference*.

**PHP**

**SDK for PHP**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
echo "What's the name of the last movie you watched?\n";  
while (empty($movieName)) {  
    $movieName = testable_readline("Movie name: ");  
}  
echo "And what year was it released?\n";  
$movieYear = "year";  
while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {  
    $movieYear = testable_readline("Year released: ");  
}  
  
$service->putItem([  
    'Item' => [  
        'year' => [  
            'N' => "$movieYear",  
        ],  
        'title' => [  
            'S' => $movieName,  
        ]  
    ]  
]);
```

```
        ],
    ],
    'TableName' => $tableName,
]);

public function putItem(array $array)
{
    $this->dynamoDbClient->putItem($array);
}
```

- For API details, see [PutItem](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def add_movie(self, title, year, plot, rating):
        """
        Adds a movie to the table.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :param plot: The plot summary of the movie.
        :param rating: The quality rating of the movie.
        """
        try:
            self.table.put_item(
                Item={
                    'year': year,
                    'title': title,
                    'info': {'plot': plot, 'rating': Decimal(str(rating))})
        except ClientError as err:
            logger.error(
                "Couldn't add movie %s to table %s. Here's why: %s: %s",
                title, self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise
```

- For API details, see [PutItem](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Adds a movie to the table.  
#  
# @param title [String] The title of the movie.  
# @param year [Integer] The release year of the movie.  
# @param plot [String] The plot summary of the movie.  
# @param rating [Float] The quality rating of the movie.  
def add_movie(title:, year:, plot:, rating:)  
    @table.put_item(  
        item: {  
            "year" => year,  
            "title" => title,  
            "info" => {"plot" => plot, "rating" => rating}})  
rescue Aws::Errors::ServiceError => e  
    puts("Couldn't add movie #{title} to table #{@table.name}. Here's why:")  
    puts("\t#{e.code}: #{e.message}")  
    raise  
end
```

- For API details, see [PutItem](#) in *AWS SDK for Ruby API Reference*.

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn add_item(  
    client: &Client,  
    table: &str,  
    username: &str,  
    p_type: &str,  
    age: &str,  
    first: &str,  
    last: &str,  
) -> Result<(), Error> {  
    let user_av = AttributeValue::S(username.into());  
    let type_av = AttributeValue::S(p_type.into());  
    let age_av = AttributeValue::S(age.into());  
    let first_av = AttributeValue::S(first.into());  
    let last_av = AttributeValue::S(last.into());  
  
    let request = client  
        .put_item()  
        .table_name(table)  
        .item("username", user_av)  
        .item("account_type", type_av)  
        .item("age", age_av)  
        .item("first_name", first_av)  
        .item("last_name", last_av);  
  
    println!("Executing request [{:?:}] to add item...", request);  
  
    request.send().await?;  
  
    println!({  
        "Added user {}, {} {}, age {} as {} user",
```

```
        username, first, last, age, p_type
    );
    Ok(())
}
```

- For API details, see [PutItem](#) in *AWS SDK for Rust API reference*.

For more DynamoDB examples, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

## Read an item from a DynamoDB table

You can read items from DynamoDB tables using the AWS Management Console, the AWS CLI, or an AWS SDK. For more information on items, see [Core components of Amazon DynamoDB \(p. 2\)](#).

## Read an item from a DynamoDB table using an AWS SDK

The following code examples show how to read an item from a DynamoDB table using an AWS SDK.

C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);
Aws::DynamoDB::Model::GetItemRequest req;

// Set up the request.
req.SetTableName(table);
Aws::DynamoDB::Model::AttributeValue hashKey;
hashKey.SetS(keyval);
req.AddKey(key, hashKey);

// Retrieve the item's fields and values
const Aws::DynamoDB::Model::GetItemOutcome& result =
dynamoClient.GetItem(req);
if (result.IsSuccess())
{
    // Reference the retrieved fields/values.
    const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>& item
= result.GetResult().GetItem();
    if (item.size() > 0)
    {
        // Output each retrieved field and its value.
        for (const auto& i : item)
            std::cout << "Values: " << i.first << ":" << i.second.GetS()
<< std::endl;
    }
    else
    {
        std::cout << "No item found with the key " << key << std::endl;
    }
}
```

```
        }
    }
else
{
    std::cout << "Failed to get item: " << result.GetError().GetMessage();
}
```

- For API details, see [GetItem](#) in *AWS SDK for C++ API Reference*.

## Go

### SDK for Go V2

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// GetMovie gets movie data from the DynamoDB table by using the primary composite
// key
// made of title and year.
func (basics TableBasics) GetMovie(title string, year int) (Movie, error) {
    movie := Movie{Title: title, Year: year}
    response, err := basics.DynamoDbClient.GetItem(context.TODO(),
        &dynamodb.GetItemInput{
            Key: movie.GetKey(), TableName: aws.String(basics.TableName),
        })
    if err != nil {
        log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
    } else {
        err = attributevalue.UnmarshalMap(response.Item, &movie)
        if err != nil {
            log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
        }
    }
    return movie, err
}
```

- For API details, see [GetItem](#) in *AWS SDK for Go API Reference*.

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Gets an item from a table by using the `DynamoDbClient`.

```
public static int queryTable(DynamoDbClient ddb, String tableName, String partitionKeyName, String partitionKeyVal, String partitionAlias) {

    // Set up an alias for the partition key name in case it's a reserved word.
    HashMap<String, String> attrNameAlias = new HashMap<String, String>();
    attrNameAlias.put(partitionAlias, partitionKeyName);

    // Set up mapping of the partition name with the value.
    HashMap<String,AttributeValue> attrValues = new HashMap<>();

    attrValues.put(":" + partitionKeyName, AttributeValue.builder()
        .s(partitionKeyVal)
        .build());

    QueryRequest queryReq = QueryRequest.builder()
        .tableName(tableName)
        .keyConditionExpression(partitionAlias + " = :" + partitionKeyName)
        .expressionAttributeNames(attrNameAlias)
        .expressionAttributeValues(attrValues)
        .build();

    try {
        QueryResponse response = ddb.query(queryReq);
        return response.count();
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return -1;
}
```

- For API details, see [GetItem](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".
```

```
const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Get an item from a table.

```
import { GetCommand } from "@aws-sdk/lib-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

// Set the parameters.
export const params = {
    TableName: "TABLE_NAME",
    Key: {
        primaryKey: "VALUE_1",
        sortKey: "VALUE_2",
    },
};

export const getItem = async () => {
    try {
        const data = await ddbDocClient.send(new GetCommand(params));
        console.log("Success :", data.Item);
    } catch (err) {
        console.log("Error", err);
    }
};
getItem();
```

Get an item from a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient";

const tableName = process.argv[2];
const movieTitle1 = process.argv[3];

export const run = async (tableName, movieTitle1) => {
    const params = {
        Statement: "SELECT * FROM " + tableName + " where title=?",
        ExpressionAttributeValues: {
            ":t": movieTitle1,
        },
    };
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
    console.log(data.Items);
};
```

```
    Parameters: [{ S: movieTitle1 }],
);
try {
  const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
  for (let i = 0; i < data.Items.length; i++) {
    console.log(
      "Success. The query return the following data. Item " + i,
      data.Items[i].year,
      data.Items[i].title,
      data.Items[i].info
    );
  }
  return "Run successfully"; // For unit tests.
} catch (err) {
  console.error(err);
}
};

run(tableName, movieTitle1);
```

Get items by batch from a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2
) => {
  const params = {
    Statements: [
      {
        Statement: "SELECT * FROM " + tableName + " where title=? and year=?",
        Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
      },
      {
        Statement: "SELECT * FROM " + tableName + " where title=? and year=?",
        Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
      },
    ],
  };
  try {
    const data = await ddbDocClient.send(
      new BatchExecuteStatementCommand(params)
    );
    for (let i = 0; i < data.Responses.length; i++) {
      console.log(data.Responses[i].Item.year);
      console.log(data.Responses[i].Item.title);
    }
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
```

```
run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);
```

- For API details, see [GetItem](#) in *AWS SDK for JavaScript API Reference*.

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Get an item from a table.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
  TableName: 'TABLE',
  Key: {
    'KEY_NAME': {N: '001'}
  },
  ProjectionExpression: 'ATTRIBUTE_NAME'
};

// Call DynamoDB to read the item from the table
ddb.getItem(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

Get an item from a table using the DynamoDB document client.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
  TableName: 'EPISODES_TABLE',
  Key: {'KEY_NAME': VALUE}
};

docClient.get(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).

- For API details, see [GetItem](#) in *AWS SDK for JavaScript API Reference*.

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun getSpecificItem(tableNameVal: String, keyName: String, keyVal: String)
{
    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.S(keyVal)

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}
```

- For API details, see [GetItem](#) in *AWS SDK for Kotlin API reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
$movie = $service->getItemByKey($tableName, $key);
echo "\nThe movie {$movie['Item']['title'][ 'S']} was released in
{$movie['Item']['year'][ 'N']}.\n";

public function getItemByKey(string $tableName, array $key)
{
    return $this->dynamoDbClient->getItem([
        'Key' => $key['Item'],
        'TableName' => $tableName,
    ]);
}
```

- For API details, see [GetItem](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def get_movie(self, title, year):
        """
        Gets movie data from the table for a specific movie.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :return: The data about the requested movie.
        """
        try:
            response = self.table.get_item(Key={'year': year, 'title': title})
        except ClientError as err:
            logger.error(
                "Couldn't get movie %s from table %s. Here's why: %s: %s",
                title, self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise
        else:
            return response['Item']
```

- For API details, see [GetItem](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Gets movie data from the table for a specific movie.
#
# @param title [String] The title of the movie.
# @param year [Integer] The release year of the movie.
# @return [Hash] The data about the requested movie.
def get_movie(title, year)
    response = @table.get_item(key: {"year" => year, "title" => title})
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't get movie #{title} from table #{@table.name}. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        response.item
    end
```

- For API details, see [GetItem](#) in *AWS SDK for Ruby API Reference*.

For more DynamoDB examples, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

## Update an item in a DynamoDB table

You can update items from DynamoDB tables using the AWS Management Console, the AWS CLI, or an AWS SDK. For more information on items, see [Core components of Amazon DynamoDB \(p. 2\)](#).

### Update an item in a DynamoDB table using an AWS SDK

The following code examples show how to update an item in a DynamoDB table using an AWS SDK.

.NET

#### AWS SDK for .NET

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```
    /// <summary>
    /// Updates an existing item in the movies table.
    /// </summary>
    /// <param name="client">An initialized Amazon DynamoDB client object.</param>
    /// <param name="newMovie">A Movie object containing information for
    /// the movie to update.</param>
    /// <param name="newInfo">A MovieInfo object that contains the
    /// information that will be changed.</param>
    /// <param name="tableName">The name of the table that contains the
    /// movie.</param>
    /// <returns>A Boolean value that indicates the success of the operation.</returns>
    public static async Task<bool> UpdateItemAsync(
        AmazonDynamoDBClient client,
        Movie newMovie,
        MovieInfo newInfo,
        string tableName)
    {
        var key = new Dictionary<string, AttributeValue>
        {
            ["title"] = new AttributeValue { S = newMovie.Title },
            ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
        };
        var updates = new Dictionary<string, AttributeValueUpdate>
        {
            ["info.plot"] = new AttributeValueUpdate
            {
                Action = AttributeAction.PUT,
                Value = new AttributeValue { S = newInfo.Plot },
            },
            ["info.rating"] = new AttributeValueUpdate
            {
                Action = AttributeAction.PUT,
                Value = new AttributeValue { N = newInfo.Rank.ToString() },
            }
        };
        return await client.UpdateItemAsync(key, updates);
    }
}
```

```
        },
    };

    var request = new UpdateItemRequest
    {
        AttributeUpdates = updates,
        Key = key,
        TableName = tableName,
    };

    var response = await client.UpdateItemAsync(request);

    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [UpdateItem in AWS SDK for .NET API Reference](#).

## C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

// *** Define UpdateItem request arguments
// Define TableName argument.
Aws::DynamoDB::Model::UpdateItemRequest request;
request.SetTableName(tableName);

// Define KeyName argument.
Aws::DynamoDB::Model::AttributeValue attribValue;
attribValue.SetS(keyValue);
request.AddKey("id", attribValue);

// Construct the SET update expression argument.
Aws::String update_expression("SET #a = :valueA");
request.SetUpdateExpression(update_expression);

// Parse the attribute name and value. Syntax: "name=value".
auto parsed = Aws::Utils::StringUtils::Split(attributeNameAndValue, '=');

if (parsed.size() != 2)
{
    std::cout << "Invalid argument syntax: " << attributeNameAndValue <<
USAGE;
    return 1;
}

// Construct attribute name argument
// Note: Setting the ExpressionAttributeNames argument is required only
// when the name is a reserved word, such as "default". Otherwise, the
// name can be included in the update_expression, as in
// "SET MyAttributeName = :valueA"
Aws::Map< Aws::String, Aws::String> expressionAttributeNames;
expressionAttributeNames["#a"] = parsed[0];
request.SetExpressionAttributeNames(expressionAttributeNames);

// Construct attribute value argument.
```

```
Aws::DynamoDB::Model::AttributeValue attributeUpdatedValue;
attributeUpdatedValue.SetS(parsed[1]);
Aws::Map< Aws::String, Aws::DynamoDB::Model::AttributeValue>
expressionAttributeValues;
expressionAttributeValues[":valueA"] = attributeUpdatedValue;
request.SetExpressionAttributeValues(expressionAttributeValues);

// Update the item.
const Aws::DynamoDB::Model::UpdateItemOutcome& result =
dynamoClient.UpdateItem(request);
if (!result.IsSuccess())
{
    std::cout << result.GetError().GetMessage() << std::endl;
    return 1;
}
std::cout << "Item was updated" << std::endl;
```

- For API details, see [UpdateItem in AWS SDK for C++ API Reference](#).

## Go

### SDK for Go V2

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    dynamodb.Client
    TableName      string
}

// UpdateMovie updates the rating and plot of a movie that already exists in the
// DynamoDB table. This function uses the `expression` package to build the update
// expression.
func (basics TableBasics) UpdateMovie(movie Movie)
    (map[string]map[string]interface{}, error) {
    var err error
    var response *dynamodb.UpdateItemOutput
    var attributeMap map[string]map[string]interface{}
    update := expression.Set(expression.Name("info.rating"),
        expression.Value(movie.Info["rating"]))
    update.Set(expression.Name("info.plot"), expression.Value(movie.Info["plot"]))
    expr, err := expression.NewBuilder().WithUpdate(update).Build()
    if err != nil {
        log.Printf("Couldn't build expression for update. Here's why: %v\n", err)
    } else {
        response, err = basics.DynamoDbClient.UpdateItem(context.TODO(),
            &dynamodb.UpdateItemInput{
                TableName:          aws.String(basics.TableName),
                Key:               movie.GetKey(),
                ExpressionAttributeNames: expr.Names(),
                ExpressionAttributeValues: expr.Values(),
                UpdateExpression:   expr.Update(),
                ReturnValue:        types.ReturnValueUpdatedNew,
            })
    }
}
```

```
    if err != nil {
        log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
    } else {
        err = attributevalue.UnmarshalMap(response.Attributes, &attributeMap)
        if err != nil {
            log.Printf("Couldn't unmarshal update response. Here's why: %v\n", err)
        }
    }
    return attributeMap, err
}
```

- For API details, see [UpdateItem in AWS SDK for Go API Reference](#).

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Updates an item located in a table by using the enhanced client.

```
public static String modifyItem(DynamoDbEnhancedClient enhancedClient, String keyVal, String email) {

    try {

        DynamoDbTable<Customer> mappedTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));
        Key key = Key.builder()
            .partitionValue(keyVal)
            .build();

        // Get the item by using the key and update the email value.
        Customer customerRec = mappedTable.getItem(r->r.key(key));
        customerRec.setEmail(email);
        mappedTable.updateItem(customerRec);
        return customerRec.getEmail();

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return "";
}
```

- For API details, see [UpdateItem in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
```

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Update an item in a table using the DynamoDB document client.

```
import { UpdateCommand } from "@aws-sdk/lib-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

export const updateItem = async () => {
    // Set the parameters.
    const params = {
        TableName: "TABLE_NAME",
        Key: {
            title: "MOVIE_NAME",
            year: "MOVIE_YEAR",
        },
        ProjectionExpression: "#r",
        ExpressionAttributeNames: { "#r": "rank" },
        UpdateExpression: "set info.plot = :p, info.#r = :r",
        ExpressionAttributeValues: {
            ":p": "MOVIE_PLOT",
            ":r": "MOVIE_RANK",
        },
    };
    try {
        const data = await ddbDocClient.send(new UpdateCommand(params));
        console.log("Success - item added or updated", data);
        return data;
    }
}
```

```

    } catch (err) {
        console.log("Error", err);
    }
};

updateItem();

```

Update an item in a table using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const producer1 = process.argv[5];

export const run = async (tableName, movieYear1, movieTitle1, producer1) => {
    const params = {
        Statement:
            "UPDATE " + tableName + " SET Producer=? WHERE title=? AND year=?",
        Parameters: [{ S: producer1 }, { S: movieTitle1 }, { N: movieYear1 }],
    };
    try {
        const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
        console.log("Success. Item updated.");
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};
run(tableName, movieYear1, movieTitle1, producer1);

```

Update items by batch in a table using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[6];
const movieTitle2 = process.argv[7];
const producer1 = process.argv[5];
const producer2 = process.argv[8];

export const run = async (
    tableName,
    movieYear1,
    movieTitle1,
    movieYear2,
    movieTitle2,
    producer1,
    producer2
) => {
    const params = {
        Statements: [
            {
                Statement:

```

```

        "UPDATE " + tableName + " SET producer=? where title=? and year=?",
        Parameters: [{ S: producer1 }, { S: movieTitle1 }, { N: movieYear1 }],
    },
    {
        Statement:
        "UPDATE " + tableName + " SET producer=? where title=? and year=?",
        Parameters: [{ S: producer2 }, { S: movieTitle2 }, { N: movieYear2 }],
    },
],
);
try {
    const data = await ddbDocClient.send(
        new BatchExecuteStatementCommand(params)
    );
    console.log("Success. Items updated.");
    return "Run successfully"; // For unit tests.
} catch (err) {
    console.error(err);
}
};

run(
    tableName,
    movieYear1,
    movieTitle1,
    movieYear2,
    movieTitle2,
    producer1,
    producer2
);

```

- For API details, see [UpdateItem in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

suspend fun updateTableItem(
    tableNameVal: String,
    keyName: String,
    keyVal: String,
    name: String,
    updateVal: String
) {

    val itemKey = mutableMapOf<String, AttributeValue>()
    itemKey[keyName] = AttributeValue.S(keyVal)

    val updatedValues = mutableMapOf<String, AttributeValueUpdate>()
    updatedValues[name] = AttributeValueUpdate {
        value = AttributeValue.S(updateVal)
        action = AttributeAction.Put
    }

    val request = UpdateItemRequest {
        tableName = tableNameVal
    }
}

```

```
        key = itemKey
        attributeUpdates = updatedValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.updateItem(request)
        println("Item in $tableNameVal was updated")
    }
}
```

- For API details, see [UpdateItem in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
echo "What rating would you like to give {$movie['Item']['title']['S']}?\n";
$rating = 0;
while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 || $rating > 10) {
    $rating = testable_readline("Rating (1-10): ");
}
$service->updateItemAttributeByKey($tableName, $key, 'rating', 'N', $rating);

public function updateItemAttributeByKey(
    string $tableName,
    array $key,
    string $attributeName,
    string $attributeType,
    string $newValue
) {
    $this->dynamoDbClient->updateItem([
        'Key' => $key['Item'],
        'TableName' => $tableName,
        'UpdateExpression' => "set #NV=:NV",
        'ExpressionAttributeNames' => [
            '#NV' => $attributeName,
        ],
        'ExpressionAttributeValues' => [
            ':NV' => [
                $attributeType => $newValue
            ]
        ],
    ]);
}
```

- For API details, see [UpdateItem in AWS SDK for PHP API Reference](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Update an item by using an update expression.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def update_movie(self, title, year, rating, plot):
        """
        Updates rating and plot data for a movie in the table.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating: The updated rating to give the movie.
        :param plot: The updated plot summary to give the movie.
        :return: The fields that were updated, with their new values.
        """
        try:
            response = self.table.update_item(
                Key={'year': year, 'title': title},
                UpdateExpression="set info.rating=:r, info.plot=:p",
                ExpressionAttributeValues={
                    ':r': Decimal(str(rating)), ':p': plot},
                ReturnValues="UPDATED_NEW")
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title, self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise
        else:
            return response['Attributes']
```

Update an item by using an update expression that includes an arithmetic operation.

```
class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table

    def update_rating(self, title, year, rating_change):
        """
        Updates the quality rating of a movie in the table by using an arithmetic
        operation in the update expression. By specifying an arithmetic operation,
        you can adjust a value in a single request, rather than first getting its
        value and then setting its new value.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating_change: The amount to add to the current rating for the
        movie.
        :return: The updated rating.
        """
        try:
            response = self.table.update_item(
                Key={'year': year, 'title': title},
                UpdateExpression="set info.rating = info.rating + :val",
                ExpressionAttributeValues={':val': Decimal(str(rating_change))},
                ReturnValues="UPDATED_NEW")
        except ClientError as err:
```

```

    logger.error(
        "Couldn't update movie %s in table %s. Here's why: %s: %s",
        title, self.table.name,
        err.response['Error']['Code'], err.response['Error']['Message'])
    raise
else:
    return response['Attributes']

```

Update an item only when it meets certain conditions.

```

class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table

    def remove_actors(self, title, year, actor_threshold):
        """
        Removes an actor from a movie, but only when the number of actors is
        greater than a specified threshold. If the movie does not list more than the
        threshold, no actors are removed.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param actor_threshold: The threshold of actors to check.
        :return: The movie data after the update.
        """
        try:
            response = self.table.update_item(
                Key={'year': year, 'title': title},
                UpdateExpression="remove info.actors[0]",
                ConditionExpression="size(info.actors) > :num",
                ExpressionAttributeValues={':num': actor_threshold},
                ReturnValues="ALL_NEW")
        except ClientError as err:
            if err.response['Error']['Code'] == "ConditionalCheckFailedException":
                logger.warning(
                    "Didn't update %s because it has fewer than %s actors.",
                    title, actor_threshold + 1)
            else:
                logger.error(
                    "Couldn't update movie %s. Here's why: %s: %s", title,
                    err.response['Error']['Code'], err.response['Error']
                    ['Message'])
                raise
        else:
            return response['Attributes']

```

- For API details, see [UpdateItem in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

# Updates rating and plot data for a movie in the table.
#
# @param title [String] The title of the movie to update.

```

```
# @param year [Int] The release year of the movie to update.
# @param rating [Float] The updated rating to give the movie.
# @param plot [String] The updated plot summary to give the movie.
# @return [Hash] The fields that were updated, with their new values.
def update_movie(title:, year:, rating:, plot:)
    response = @table.update_item(
        key: {"year" => year, "title" => title},
        update_expression: "set info.rating=:r, info.plot=:p",
        expression_attribute_values: { ":r" => rating, ":p" => plot },
        return_values: "UPDATED_NEW")
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't update movie #{title} in table #{@table.name}. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        response.attributes
    end
```

- For API details, see [UpdateItem in AWS SDK for Ruby API Reference](#).

For more DynamoDB examples, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

## Delete an item in a DynamoDB table

You can delete items from DynamoDB tables using the AWS Management Console, the AWS CLI, or an AWS SDK. For more information on items, see [Core components of Amazon DynamoDB \(p. 2\)](#).

### Delete an item in a DynamoDB table using an AWS SDK

The following code examples show how to delete an item in a DynamoDB table using an AWS SDK.

.NET

#### AWS SDK for .NET

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Deletes a single item from a DynamoDB table.
/// </summary>
/// <param name="client">The initialized DynamoDB client object.</param>
/// <param name="tableName">The name of the table from which the item
/// will be deleted.</param>
/// <param name="movieToDelete">A movie object containing the title and
/// year of the movie to delete.</param>
/// <returns>A Boolean value indicating the success or failure of the
/// delete operation.</returns>
public static async Task<bool> DeleteItemAsync(
    AmazonDynamoDBClient client,
    string tableName,
    Movie movieToDelete)
{
    var key = new Dictionary<string, AttributeValue>
    {
```

```
[ "title" ] = new AttributeValue { S = movieToDelete.Title },
[ "year" ] = new AttributeValue { N =
movieToDelete.Year.ToString() },
};

var request = new DeleteItemRequest
{
    TableName = tableName,
    Key = key,
};

var response = await client.DeleteItemAsync(request);
return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [DeleteItem in AWS SDK for .NET API Reference](#).

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName      string
}

// DeleteMovie removes a movie from the DynamoDB table.
func (basics TableBasics) DeleteMovie(movie Movie) error {
    _, err := basics.DynamoDbClient.DeleteItem(context.TODO(),
        &dynamodb.DeleteItemInput{
            TableName: aws.String(basics.TableName), Key: movie.GetKey(),
        })
    if err != nil {
        log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title, err)
    }
    return err
}
```

- For API details, see [DeleteItem in AWS SDK for Go API Reference](#).

Java

## SDK for Java 2.x

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static void deleteDynamoDBItem(DynamoDbClient ddb, String tableName,
String key, String keyVal) {
    HashMap<String,AttributeValue> keyToGet = new HashMap<>();
    keyToGet.put(key, AttributeValue.builder()
        .s(keyVal)
        .build());

    DeleteItemRequest deleteReq = DeleteItemRequest.builder()
        .tableName(tableName)
        .key(keyToGet)
        .build();

    try {
        ddb.deleteItem(deleteReq);
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
}
```

- For API details, see [DeleteItem in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
};
```

```
    wrapNumbers: false, // false, by default.  
};  
  
const translateConfig = { marshallOptions, unmarshallOptions };  
  
// Create the DynamoDB document client.  
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);  
  
export { ddbDocClient };
```

Delete an item from a table using the DynamoDB document client.

```
import { DeleteCommand } from "@aws-sdk/lib-dynamodb";  
import { ddbDocClient } from "../libs/ddbDocClient.js";  
  
// Set the parameters.  
export const params = {  
  TableName: "TABLE_NAME",  
  Key: {  
    primaryKey: "VALUE_1",  
    sortKey: "VALUE_2",  
  },  
};  
  
export const deleteItem = async () => {  
  try {  
    const data = await ddbDocClient.send(new DeleteCommand(params));  
    console.log("Success - item deleted");  
  } catch (err) {  
    console.log("Error", err);  
  }  
};  
deleteItem();
```

Delete an item from a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.  
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";  
import { ddbDocClient } from "../libs/ddbDocClient.js";  
  
const tableName = process.argv[2];  
const movieYear1 = process.argv[3];  
const movieTitle1 = process.argv[4];  
  
export const run = async (tableName, movieYear1, movieTitle1) => {  
  const params = {  
    Statement: "DELETE FROM " + tableName + " where title=? and year=?",  
    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],  
  };  
  try {  
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));  
    console.log("Success. Item deleted.");  
    return "Run successfully"; // For unit tests.  
  } catch (err) {  
    console.error(err);  
  }  
};  
run(tableName, movieYear1, movieTitle1);
```

Delete an item from a table by batch using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2
) => {
  try {
    const params = {
      Statements: [
        {
          Statement: "DELETE FROM " + tableName + " where year=? and title=?",
          Parameters: [{ N: movieYear1 }, { S: movieTitle1 }],
        },
        {
          Statement: "DELETE FROM " + tableName + " where year=? and title=?",
          Parameters: [{ N: movieYear2 }, { S: movieTitle2 }],
        },
      ],
    };
    const data = await ddbDocClient.send(
      new BatchExecuteStatementCommand(params)
    );
    console.log("Success. Items deleted.", data);
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [DeleteItem in AWS SDK for JavaScript API Reference](#).

### SDK for JavaScript V2

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Delete an item from a table.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
  TableName: 'TABLE',
```

```
    Key: {
      'KEY_NAME': {N: 'VALUE'}
    }
};

// Call DynamoDB to delete the item from the table
ddb.deleteItem(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Delete an item from a table using the DynamoDB document client.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
  Key: {
    'HASH_KEY': VALUE
  },
  TableName: 'TABLE'
};

docClient.delete(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [DeleteItem in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun deleteDynamoDBItem(tableNameVal: String, keyName: String, keyVal: String) {

  val keyToGet = mutableMapOf<String, AttributeValue>()
  keyToGet[keyName] = AttributeValue.S(keyVal)
```

```
    val request = DeleteItemRequest {
        tableName = tableNameVal
        key = keyToGet
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteItem(request)
        println("Item with key matching $keyVal was deleted")
    }
}
```

- For API details, see [DeleteItem in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
$key = [
    'Item' => [
        'title' => [
            'S' => $movieName,
        ],
        'year' => [
            'N' => $movieYear,
        ],
    ],
];

$key = [
    'Item' => [
        'title' => [
            'S' => $movieName,
        ],
        'year' => [
            'N' => $movieYear,
        ],
    ],
];

$service->deleteItemByKey($tableName, $key);
echo "But, bad news, this was a trap. That movie has now been deleted
because of your rating...harsh.\n";

public function deleteItemByKey(string $tableName, array $key)
{
    $this->dynamoDbClient->deleteItem([
        'Key' => $key['Item'],
        'TableName' => $tableName,
    ]);
}
```

- For API details, see [DeleteItem in AWS SDK for PHP API Reference](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
```

```

:param dyn_resource: A Boto3 DynamoDB resource.
"""
self.dyn_resource = dyn_resource
self.table = None

def delete_movie(self, title, year):
    """
    Deletes a movie from the table.

    :param title: The title of the movie to delete.
    :param year: The release year of the movie to delete.
    """
try:
    self.table.delete_item(Key={'year': year, 'title': title})
except ClientError as err:
    logger.error(
        "Couldn't delete movie %s. Here's why: %s: %s",
        title,
        err.response['Error']['Code'],
        err.response['Error']['Message'])
    raise

```

You can specify a condition so that an item is deleted only when it meets certain criteria.

```

class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table

    def delete_underrated_movie(self, title, year, rating):
        """
        Deletes a movie only if it is rated below a specified value. By using a
        condition expression in a delete operation, you can specify that an item is
        deleted only when it meets certain criteria.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
        :param rating: The rating threshold to check before deleting the movie.
        """
try:
    self.table.delete_item(
        Key={'year': year, 'title': title},
        ConditionExpression="info.rating <= :val",
        ExpressionAttributeValues={":val": Decimal(str(rating))})
except ClientError as err:
    if err.response['Error']['Code'] == "ConditionalCheckFailedException":
        logger.warning(
            "Didn't delete %s because its rating is greater than %s.",
            title, rating)
    else:
        logger.error(
            "Couldn't delete movie %s. Here's why: %s: %s",
            title,
            err.response['Error']['Code'],
            err.response['Error']
            ['Message'])
    raise

```

- For API details, see [DeleteItem in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Deletes a movie from the table.  
#  
# @param title [String] The title of the movie to delete.  
# @param year [Integer] The release year of the movie to delete.  
def delete_movie(title, year)  
    @table.delete_item(key: {"year" => year, "title" => title})  
rescue Aws::Errors::ServiceError => e  
    puts("Couldn't delete movie #{title}. Here's why:")  
    puts("\t#{e.code}: #{e.message}")  
    raise  
end
```

- For API details, see [DeleteItem in AWS SDK for Ruby API Reference](#).

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn delete_item(client: &Client, table: &str, key: &str, value: &str) ->  
    Result<(), Error> {  
        match client  
            .delete_item()  
            .table_name(table)  
            .key(key, AttributeValue::S(value.into()))  
            .send()  
            .await  
        {  
            Ok(_) => println!("Deleted item from table"),  
            Err(e) => {  
                println!("Got an error deleting item from table:");  
                println!("{}: {}", "{}", e);  
                process::exit(1);  
            }  
        };  
        Ok(())  
    }
```

- For API details, see [DeleteItem in AWS SDK for Rust API reference](#).

For more DynamoDB examples, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

## Query a DynamoDB table

You can perform a query on a DynamoDB table using the AWS Management Console, the AWS CLI, or an AWS SDK. For more information on queries, see [Query operations in DynamoDB \(p. 428\)](#).

# Query a DynamoDB table using an AWS SDK

The following code examples show how to query a DynamoDB table using an AWS SDK.

.NET

## AWS SDK for .NET

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Queries the table for movies released in a particular year and
/// then displays the information for the movies returned.
/// </summary>
/// <param name="client">The initialized DynamoDB client object.</param>
/// <param name="tableName">The name of the table to query.</param>
/// <param name="year">The release year for which we want to
/// view movies.</param>
/// <returns>The number of movies that match the query.</returns>
public static async Task<int> QueryMoviesAsync(AmazonDynamoDBClient client,
string tableName, int year)
{
    var movieTable = Table.LoadTable(client, tableName);
    var filter = new QueryFilter("year", QueryOperator.Equal, year);

    Console.WriteLine("\nFind movies released in: {year}:");

    var config = new QueryOperationConfig()
    {
        Limit = 10, // 10 items per page.
        Select = SelectValues.SpecificAttributes,
        AttributesToGet = new List<string>
        {
            "title",
            "year",
        },
        ConsistentRead = true,
        Filter = filter,
    };

    // Value used to track how many movies match the
    // supplied criteria.
    var moviesFound = 0;

    Search search = movieTable.Query(config);
    do
    {
        var movieList = await search.GetNextSetAsync();
        moviesFound += movieList.Count;

        foreach (var movie in movieList)
        {
            DisplayDocument(movie);
        }
    }
    while (!search.IsDone);

    return moviesFound;
}
```

- For API details, see [Query](#) in *AWS SDK for .NET API Reference*.

C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;

Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);
Aws::DynamoDB::Model::QueryRequest req;

req.SetTableName(table);

// Set query key condition expression
req.SetKeyConditionExpression(partitionKeyAttributeName +
"= :valueToMatch");

// Set Expression AttributeValues
Aws::Map< Aws::String, Aws::DynamoDB::Model::AttributeValue>
attributeValues;
attributeValues.emplace(":valueToMatch", partitionKeyValue);

req.SetExpressionAttributeValues(attributeValues);

// Perform Query operation
const Aws::DynamoDB::Model::QueryOutcome& result = dynamoClient.Query(req);
if (result.IsSuccess())
{
    // Reference the retrieved items
    const Aws::Vector< Aws::Map< Aws::String,
Aws::DynamoDB::Model::AttributeValue>>& items = result.GetResult().GetItems();
    if(items.size() > 0)
    {
        std::cout << "Number of items retrieved from Query: " <<
items.size() << std::endl;
        //Iterate each item and print
        for(const auto &item: items)
        {
            std::cout <<
"*****" << std::endl;
            // Output each retrieved field and its value
            for (const auto& i : item)
                std::cout << i.first << ":" << i.second.GetS() << std::endl;
        }
    }
    else
    {
        std::cout << "No item found in table: " << table << std::endl;
    }
}
else
{
    std::cout << "Failed to Query items: " <<
result.GetError().GetMessage();
}
```

- For API details, see [Query](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// Query gets all movies in the DynamoDB table that were released in the specified
// year.
// The function uses the `expression` package to build the key condition expression
// that is used in the query.
func (basics TableBasics) Query(releaseYear int) ([]Movie, error) {
    var err error
    var response *dynamodb.QueryOutput
    var movies []Movie
    keyEx := expression.Key("year").Equal(expression.Value(releaseYear))
    expr, err := expression.NewBuilder().WithKeyCondition(keyEx).Build()
    if err != nil {
        log.Printf("Couldn't build expression for query. Here's why: %v\n", err)
    } else {
        response, err = basics.DynamoDbClient.Query(context.TODO(), &dynamodb.QueryInput{
            TableName:           aws.String(basics.TableName),
            ExpressionAttributeNames: expr.Names(),
            ExpressionAttributeValues: expr.Values(),
            KeyConditionExpression:   expr.KeyCondition(),
        })
        if err != nil {
            log.Printf("Couldn't query for movies released in %v. Here's why: %v\n",
                releaseYear, err)
        } else {
            err = attributevalue.UnmarshalListOfMaps(response.Items, &movies)
            if err != nil {
                log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
            }
        }
    }
    return movies, err
}
```

- For API details, see [Query in AWS SDK for Go API Reference](#).

Java

## SDK for Java 2.x

### Tip

To learn how to set up and run this example, see [GitHub](#).

Queries a table by using the enhanced client.

```

public static String queryTable(DynamoDbEnhancedClient enhancedClient) {

    try{
        DynamoDbTable<Customer> mappedTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));
        QueryConditional queryConditional =
QueryConditional.keyEqualTo(Key.builder()
            .partitionValue("id101")
            .build());

        // Get items in the table and write out the ID value.
        Iterator<Customer> results =
mappedTable.query(queryConditional).items().iterator();
        String result="";

        while (results.hasNext()) {
            Customer rec = results.next();
            result = rec.getId();
            System.out.println("The record id is "+result);
        }
        return result;
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return "";
}

```

Queries a table by using the enhanced client and a secondary index.

```

public static void queryIndex(DynamoDbClient ddb, String tableName) {

    try {
        // Create a DynamoDbEnhancedClient and use the DynamoDbClient object.
        DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
            .dynamoDbClient(ddb)
            .build();

        //Create a DynamoDbTable object based on Movies.
        DynamoDbTable<Movies> table = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
        String dateVal = "2013";

        DynamoDbIndex<Movies> secIndex = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class)).index("year-index");
        AttributeValue attVal = AttributeValue.builder()
            .n(dateVal)
            .build();

        // Create a QueryConditional object that's used in the query operation.
        QueryConditional queryConditional = QueryConditional
            .keyEqualTo(Key.builder().partitionValue(attVal)
            .build());

        // Get items in the table.
        SdkIterable<Page<Movies>> results =
secIndex.query(QueryEnhancedRequest.builder()
            .queryConditional(queryConditional)
            .limit(300)
            .build());
    }
}

```

```

        // Display the results.
        results.forEach(page -> {
            List<Movies> allMovies = page.items();
            for (Movies myMovies: allMovies) {
                System.out.println("The movie title is " + myMovies.getTitle()
+ ". The year is " + myMovies.getYear());
            }
        });

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
}

```

Queries a table by using the DynamoDbClient.

```

public static int queryTable(DynamoDbClient ddb, String tableName, String
partitionKeyName, String partitionKeyVal, String partitionAlias) {

    // Set up an alias for the partition key name in case it's a reserved word.
    HashMap<String, String> attrNameAlias = new HashMap<String, String>();
    attrNameAlias.put(partitionAlias, partitionKeyName);

    // Set up mapping of the partition name with the value.
    HashMap<String,AttributeValue> attrValues = new HashMap<>();

    attrValues.put(":+" + partitionKeyName, AttributeValue.builder()
        .s(partitionKeyVal)
        .build());

    QueryRequest queryReq = QueryRequest.builder()
        .tableName(tableName)
        .keyConditionExpression(partitionAlias + " = :" + partitionKeyName)
        .expressionAttributeNames(attrNameAlias)
        .expressionAttributeValues(attrValues)
        .build();

    try {
        QueryResponse response = ddb.query(queryReq);
        return response.count();
    }

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return -1;
}

```

Queries a table by using the DynamoDbClient and a secondary index.

```

public static void queryIndex(DynamoDbClient ddb, String tableName) {

    try {
        Map<String, String> expressionAttributesNames = new HashMap<>();
        expressionAttributesNames.put("#year", "year");
        Map<String,AttributeValue> expressionAttributeValues = new
        HashMap<>();
        expressionAttributeValues.put(":yearValue",
        AttributeValue.builder().n("2013").build());
    }
}

```

```
QueryRequest request = QueryRequest.builder()
    .tableName(tableName)
    .indexName("year-index")
    .keyConditionExpression("#year = :yearValue")
    .expressionAttributeNames(expressionAttributeNames)
    .expressionAttributeValues(expressionAttributeValues)
    .build();

System.out.println("== Movie Titles ==");
QueryResponse response = ddb.query(request);
response.items()
    .forEach(movie -> System.out.println(movie.get("title").s()));

} catch (DynamoDbException e) {
    System.err.println(e.getMessage());
    System.exit(1);
}
}
```

- For API details, see [Query](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon DynamoDB service client object.
const ddbClient = new DynamoDBClient({ region: REGION });
export { ddbClient };
```

Query the table.

```
// Import required AWS SDK clients and commands for Node.js
import { QueryCommand } from "@aws-sdk/client-dynamodb";
import { ddbClient } from "./libs/ddbClient.js";

// Set the parameters
export const params = {
    KeyConditionExpression: "Season = :s and Episode > :e",
    FilterExpression: "contains (Subtitle, :topic)",
    ExpressionAttributeValues: {
        ":s": { N: "1" },
        ":e": { N: "2" },
        ":topic": { S: "SubTitle" },
    },
    ProjectionExpression: "Episode, Title, Subtitle",
    TableName: "EPISODES_TABLE",
};

export const run = async () => {
    try {
        const data = await ddbClient.send(new QueryCommand(params));
```

```

        return data;
    data.Items.forEach(function (element, index, array) {
        console.log(element.Title.S + " (" + element.Subtitle.S + ")");
    });
} catch (err) {
    console.error(err);
}
};

run();

```

Create the client for the DynamoDB document client.

```

// Create service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient";

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the Dynamodb Document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };

```

Query the table using the DynamoDB document client.

```

import { QueryCommand } from "@aws-sdk/lib-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

// Set the parameters.
export const params = {
    ExpressionAttributeNames: { "#r": "rank", "#y": "year" },
    ProjectionExpression: "#r, #y, title",
    TableName: "TABLE_NAME",
    ExpressionAttributeValues: {
        ":t": "MOVIE_NAME",
        ":y": "MOVIE_YEAR",
        ":r": "MOVIE_RANK",
    },
    KeyConditionExpression: "title = :t and #y = :y",
    FilterExpression: "info.#r = :r",
};

export const queryTable = async () => {
    try {
        const data = await ddbDocClient.send(new QueryCommand(params));
        for (let i = 0; i < data.Items.length; i++) {
            console.log(

```

```
    "Success. Items with rank of " +
    "MOVIE_RANK" +
    " include\n" +
    "Year = " +
    data.Items[i].year +
    " Title = " +
    data.Items[i].title
  );
}
} catch (err) {
  console.log("Error", err);
}
};

queryTable();

```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [Query in AWS SDK for JavaScript API Reference](#).

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
  ExpressionAttributeValues: {
    ':s': 2,
    ':e': 9,
    ':topic': 'PHRASE'
  },
  KeyConditionExpression: 'Season = :s and Episode > :e',
  FilterExpression: 'contains (Subtitle, :topic)',
  TableName: 'EPISODES_TABLE'
};

docClient.query(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Items);
  }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [Query in AWS SDK for JavaScript API Reference](#).

## Kotlin

## SDK for Kotlin

### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun queryDynTable(  
    tableNameVal: String,  
    partitionKeyName: String,  
    partitionKeyVal: String,  
    partitionAlias: String  
) : Int {  
  
    val attrNameAlias = mutableMapOf<String, String>()  
    attrNameAlias[partitionAlias] = partitionKeyName  
  
    // Set up mapping of the partition name with the value.  
    val attrValues = mutableMapOf<String, AttributeValue>()  
    attrValues[":$partitionKeyName"] = AttributeValue.S(partitionKeyVal)  
  
    val request = QueryRequest {  
        tableName = tableNameVal  
        keyConditionExpression = "$partitionAlias = :$partitionKeyName"  
        expressionAttributeNames = attrNameAlias  
        this.expressionAttributeValues = attrValues  
    }  
  
    DynamoDbClient { region = "us-east-1" }.use { ddb ->  
        val response = ddb.query(request)  
        return response.count  
    }  
}
```

- For API details, see [Query](#) in *AWS SDK for Kotlin API reference*.

PHP

**SDK for PHP**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
$birthKey = [  
    'Key' => [  
        'year' => [  
            'N' => "$birthYear",  
        ],  
    ],  
];  
$result = $service->query($tableName, $birthKey);  
  
public function query(string $tableName, $key)  
{  
    $expressionAttributeValues = [];  
    $expressionAttributeNames = [];  
    $keyConditionExpression = "";  
    $index = 1;  
    foreach ($key as $name => $value) {  
        $keyConditionExpression .= "#" . array_key_first($value) . " = :v  
$index,";  
        $expressionAttributeNames["#" . array_key_first($value)] =  
        array_key_first($value);  
        $hold = array_pop($value);  
    }  
}
```

```

        $expressionAttributeValues[":v$index"] = [
            array_key_first($hold) => array_pop($hold),
        ];
    }
    $keyConditionExpression = substr($keyConditionExpression, 0, -1);
    $query = [
        'ExpressionAttributeValues' => $expressionAttributeValues,
        'ExpressionAttributeNames' => $expressionAttributeNames,
        'KeyConditionExpression' => $keyConditionExpression,
        'TableName' => $tableName,
    ];
    return $this->dynamoDbClient->query($query);
}

```

- For API details, see [Query](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Query items by using a key condition expression.

```

class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def query_movies(self, year):
        """
        Queries for movies that were released in the specified year.

        :param year: The year to query.
        :return: The list of movies that were released in the specified year.
        """
        try:
            response =
self.table.query(KeyConditionExpression=Key('year').eq(year))
        except ClientError as err:
            logger.error(
                "Couldn't query for movies released in %s. Here's why: %s: %s",
                year,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise
        else:
            return response['Items']

```

Query items and project them to return a subset of data.

```

class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table

    def query_and_project_movies(self, year, title_bounds):

```

```

"""
Query for movies that were released in a specified year and that have
titles
that start within a range of letters. A projection expression is used
to return a subset of data for each movie.

:param year: The release year to query.
:param title_bounds: The range of starting letters to query.
:return: The list of movies.
"""

try:
    response = self.table.query(
        ProjectionExpression="#yr, title, info.genres, info.actors[0]",
        ExpressionAttributeNames={"#yr": "year"},
        KeyConditionExpression=(
            Key('year').eq(year) &
            Key('title').between(title_bounds['first'],
        title_bounds['second'])))
    except ClientError as err:
        if err.response['Error']['Code'] == "ValidationException":
            logger.warning(
                "There's a validation error. Here's the message: %s: %s",
                err.response['Error']['Code'], err.response['Error']
            ['Message'])
        else:
            logger.error(
                "Couldn't query for movies. Here's why: %s: %s",
                err.response['Error']['Code'], err.response['Error']
            ['Message'])
            raise
    else:
        return response['Items']

```

- For API details, see [Query in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

# Queries for movies that were released in the specified year.
#
# @param year [Integer] The year to query.
# @return [Array] The list of movies that were released in the specified year.
def query_movies(year)
    response = @table.query(
        key_condition_expression: "#yr = :year",
        expression_attribute_names: {"#yr" => "year"},
        expression_attribute_values: {":year" => year})
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't query for movies released in #{year}. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        response.items
    end

```

- For API details, see [Query in AWS SDK for Ruby API Reference](#).

Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Find the movies made in the specified year.

```
fn movies_in_year(client: &Client, table_name: &str, year: u16) -> Query {
    client
        .query()
        .table_name(table_name)
        .key_condition_expression("#yr = :yyyy")
        .expression_attribute_names("#yr", "year")
        .expression_attribute_values(":yyyy", AttributeValue::N(year.to_string()))
}
```

- For API details, see [Query](#) in *AWS SDK for Rust API reference*.

For more DynamoDB examples, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

## Scan a DynamoDB table

You can perform a scan on a DynamoDB table using the AWS Management Console, the AWS CLI, or an AWS SDK. For more information on scans, see [Working with scans in DynamoDB \(p. 445\)](#).

## Scan a DynamoDB table using an AWS SDK

The following code examples show how to scan a DynamoDB table using an AWS SDK.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static async Task<int> ScanTableAsync(
    AmazonDynamoDBClient client,
    string tableName,
    int startYear,
    int endYear)
{
    var request = new ScanRequest
    {
        TableName = tableName,
        ExpressionAttributeNames = new Dictionary<string, string>
        {
            { "#yr", "year" },
        },
    };
}
```

```
ExpressionAttributeValues = new Dictionary<string, AttributeValue>
{
    { ":y_a", new AttributeValue { N = startYear.ToString() } },
    { ":y_z", new AttributeValue { N = endYear.ToString() } },
},
FilterExpression = "#yr between :y_a and :y_z",
ProjectionExpression = "#yr, title, info.actors[0], info.directors,
info.running_time_secs",
};

// Keep track of how many movies were found.
int foundCount = 0;

var response = new ScanResponse();
do
{
    response = await client.ScanAsync(request);
    foundCount += response.Items.Count;
    response.Items.ForEach(i => DisplayItem(i));
}
while (response.LastEvaluatedKey.Count > 1);
return foundCount;
}
```

- For API details, see [Scan](#) in *AWS SDK for .NET API Reference*.

## C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;

Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);
Aws::DynamoDB::Model::ScanRequest req;
req.SetTableName(table);

if (!projection.empty())
    req.SetProjectionExpression(projection);

// Perform scan on table
const Aws::DynamoDB::Model::ScanOutcome& result = dynamoClient.Scan(req);
if (result.IsSuccess())
{
    // Reference the retrieved items
    const Aws::Vector<Aws::Map<Aws::String,
Aws::DynamoDB::Model::AttributeValue>>& items = result.GetResult().GetItems();
    if(items.size() > 0)
    {
        std::cout << "Number of items retrieved from scan: " <<
items.size() << std::endl;
        //Iterate each item and print
        for(const auto &item: items)
        {
            std::cout <<
"*****" << std::endl;
            // Output each retrieved field and its value
            for (const auto& i : item)
                std::cout << i.first << ":" << i.second.GetS() << std::endl;
    }
}
```

```
        }
    }

    else
    {
        std::cout << "No item found in table: " << table << std::endl;
    }
else
{
    std::cout << "Failed to Scan items: " <<
result.GetError().GetMessage();
}
```

- For API details, see [Scan](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    dynamodb.Client
    TableName string
}

// Scan gets all movies in the DynamoDB table that were released in a range of
// years
// and projects them to return a reduced set of fields.
// The function uses the `expression` package to build the filter and projection
// expressions.
func (basics TableBasics) Scan(startYear int, endYear int) ([]Movie, error) {
    var movies []Movie
    var err error
    var response *dynamodb.ScanOutput
    filtEx := expression.Name("year").Between(expression.Value(startYear),
        expression.Value(endYear))
    projEx := expression.NamesList(
        expression.Name("year"), expression.Name("title"),
        expression.Name("info.rating"))
    expr, err :=
        expression.NewBuilder().WithFilter(filtEx).WithProjection(projEx).Build()
    if err != nil {
        log.Printf("Couldn't build expressions for scan. Here's why: %v\n", err)
    } else {
        response, err = basics.DynamoDbClient.Scan(context.TODO(), &dynamodb.ScanInput{
            TableName:           aws.String(basics.TableName),
            ExpressionAttributeNames: expr.Names(),
            ExpressionAttributeValues: expr.Values(),
            FilterExpression:      expr.Filter(),
            ProjectionExpression:  expr.Projection(),
        })
        if err != nil {
```

```
    log.Printf("Couldn't scan for movies released between %v and %v. Here's why: %v\n",
               startYear, endYear, err)
} else {
    err = attributevalue.UnmarshalListOfMaps(response.Items, &movies)
    if err != nil {
        log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
    }
}
return movies, err
}
```

- For API details, see [Scan in AWS SDK for Go API Reference](#).

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Scans an Amazon DynamoDB table by using the enhanced client.

```
public static void scan( DynamoDbEnhancedClient enhancedClient) {
    try{
        DynamoDbTable<Customer> custTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));
        Iterator<Customer> results = custTable.scan().items().iterator();
        while (results.hasNext()) {
            Customer rec = results.next();
            System.out.println("The record id is "+rec.getId());
            System.out.println("The name is " +rec.getCustName());
        }

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    System.out.println("Done");
}
```

- For API details, see [Scan in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
```

```
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Scan a table using the DynamoDB document client.

```
// Import required AWS SDK clients and commands for Node.js.
import { ddbDocClient } from "../libs/ddbDocClient.js";
import { ScanCommand } from "@aws-sdk/lib-dynamodb";
// Set the parameters.
export const params = {
    TableName: "TABLE_NAME",
    ProjectionExpression: "#r, #y, title",
    ExpressionAttributeNames: { "#r": "rank", "#y": "year" },
    FilterExpression: "title = :t and #y = :y and info.#r = :r",
    ExpressionAttributeValues: {
        ":r": "MOVIE_RANK",
        ":y": "MOVIE_YEAR",
        ":t": "MOVIE_NAME",
    },
};

export const scanTable = async () => {
    try {
        const data = await ddbDocClient.send(new ScanCommand(params));
        console.log("success", data.Items);
    } catch (err) {
        console.log("Error", err);
    }
};
scanTable();
```

- For API details, see [Scan in AWS SDK for JavaScript API Reference](#).

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js.
var AWS = require("aws-sdk");
// Set the AWS Region.
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object.
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

const params = {
    // Specify which items in the results are returned.
    FilterExpression: "Subtitle = :topic AND Season = :s AND Episode = :e",
    // Define the expression attribute value, which are substitutes for the values
    // you want to compare.
    ExpressionAttributeValues: {
        ":topic": {S: "SubTitle2"},
        ":s": {N: 1},
        ":e": {N: 2},
    },
    // Set the projection expression, which are the attributes that you want.
    ProjectionExpression: "Season, Episode, Title, Subtitle",
    TableName: "EPISODES_TABLE",
};

ddb.scan(params, function (err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Success", data);
        data.Items.forEach(function (element, index, array) {
            console.log(
                "printing",
                element.Title.S + " (" + element.Subtitle.S + ")"
            );
        });
    }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [Scan in AWS SDK for JavaScript API Reference](#).

## Kotlin

## SDK for Kotlin

### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun scanItems(tableNameVal: String) {

    val request = ScanRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.scan(request)
        response.items?.forEach { item ->
            item.keys.forEach { key ->
                println("The key name is $key\n")
                println("The value is ${item[key]}")
            }
        }
    }
}
```

- For API details, see [Scan in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
$yearsKey = [
    'Key' => [
        'year' => [
            'N' => [
                'minRange' => 1990,
                'maxRange' => 1999,
            ],
        ],
    ],
];
$filter = "year between 1990 and 1999";
echo "\nHere's a list of all the movies released in the 90s:\n";
$result = $service->scan($tableName, $yearsKey, $filter);
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    echo $movie['title'] . "\n";
}

public function scan(string $tableName, array $key, string $filters)
{
    $query = [
        'ExpressionAttributeNames' => ['#year' => 'year'],
        'ExpressionAttributeValues' => [
            ':min' => ['N' => '1990'],
            ':max' => ['N' => '1999'],
        ],
        'FilterExpression' => "#year between :min and :max",
        'TableName' => $tableName,
    ];
    return $this->dynamoDbClient->scan($query);
}
```

- For API details, see [Scan in AWS SDK for PHP API Reference](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def scan_movies(self, year_range):
        """
        Scans for movies that were released in a range of years.
        Uses a projection expression to return a subset of data for each movie.

        :param year_range: The range of years to retrieve.
        :return: The list of movies released in the specified years.
        """
        movies = []
        scan_kwargs = {
            'FilterExpression': Key('year').between(year_range['first'],
year_range['second']),
            'ProjectionExpression': "#yr, title, info.rating",
            'ExpressionAttributeNames': {"#yr": "year"}}
        try:
            done = False
            start_key = None
            while not done:
                if start_key:
                    scan_kwargs['ExclusiveStartKey'] = start_key
                response = self.table.scan(**scan_kwargs)
                movies.extend(response.get('Items', []))
                start_key = response.get('LastEvaluatedKey', None)
                done = start_key is None
        except ClientError as err:
            logger.error(
                "Couldn't scan for movies. Here's why: %s: %s",
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise

        return movies
```

- For API details, see [Scan in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Scans for movies that were released in a range of years.
# Uses a projection expression to return a subset of data for each movie.
#
```

```
# @param year_range [Hash] The range of years to retrieve.
# @return [Array] The list of movies released in the specified years.
def scan_movies(year_range)
    movies = []
    scan_hash = {
        filter_expression: "#yr between :start_yr and :end_yr",
        projection_expression: "#yr, title, info.rating",
        expression_attribute_names: {"#yr" => "year"},
        expression_attribute_values: {
            ":start_yr" => year_range[:start], ":end_yr" => year_range[:end]}
    }
    done = false
    start_key = nil
    until done
        scan_hash[:exclusive_start_key] = start_key unless start_key.nil?
        response = @table.scan(scan_hash)
        movies.concat(response.items) unless response.items.nil?
        start_key = response.last_evaluated_key
        done = start_key.nil?
    end
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't scan for movies. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        movies
    end
```

- For API details, see [Scan in AWS SDK for Ruby API Reference](#).

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn list_items(client: &Client, table: &str) -> Result<(), Error> {
    let items: Result<Vec<_>, _> = client
        .scan()
        .table_name(table)
        .into_paginator()
        .items()
        .send()
        .collect()
        .await;

    println!("Items in table:");
    for item in items? {
        println!("    {:?}", item);
    }

    Ok(())
}
```

- For API details, see [Scan in AWS SDK for Rust API reference](#).

For more DynamoDB examples, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

## Using DynamoDB with an AWS SDK

AWS software development kits (SDKs) are available for many popular programming languages. Each SDK provides an API, code examples, and documentation that make it easier for developers to build applications in their preferred language.

SDK documentation	Code examples
<a href="#">AWS SDK for C++</a>	<a href="#">AWS SDK for C++ code examples</a>
<a href="#">AWS SDK for Go</a>	<a href="#">AWS SDK for Go code examples</a>
<a href="#">AWS SDK for Java</a>	<a href="#">AWS SDK for Java code examples</a>
<a href="#">AWS SDK for JavaScript</a>	<a href="#">AWS SDK for JavaScript code examples</a>
<a href="#">AWS SDK for Kotlin</a>	<a href="#">AWS SDK for Kotlin code examples</a>
<a href="#">AWS SDK for .NET</a>	<a href="#">AWS SDK for .NET code examples</a>
<a href="#">AWS SDK for PHP</a>	<a href="#">AWS SDK for PHP code examples</a>
<a href="#">AWS SDK for Python (Boto3)</a>	<a href="#">AWS SDK for Python (Boto3) code examples</a>
<a href="#">AWS SDK for Ruby</a>	<a href="#">AWS SDK for Ruby code examples</a>
<a href="#">AWS SDK for Rust</a>	<a href="#">AWS SDK for Rust code examples</a>
<a href="#">AWS SDK for Swift</a>	<a href="#">AWS SDK for Swift code examples</a>

For examples specific to DynamoDB, see [Code examples for DynamoDB using AWS SDKs \(p. 812\)](#).

### Example availability

Can't find what you need? Request a code example by using the **Provide feedback** link at the bottom of this page.

# Programming with DynamoDB and the AWS SDKs

This section covers developer-related topics. If you want to run code examples instead, see [Running the code examples in this Developer Guide \(p. 268\)](#).

## Note


In December 2017, AWS began the process of migrating all Amazon DynamoDB endpoints to use secure certificates issued by Amazon Trust Services (ATS). For more information, see [Troubleshooting SSL/TLS connection establishment issues \(p. 1254\)](#).

## Topics

- [Overview of AWS SDK support for DynamoDB \(p. 153\)](#)
- [Programmatic interfaces \(p. 155\)](#)
- [DynamoDB low-level API \(p. 159\)](#)
- [Error handling with DynamoDB \(p. 163\)](#)
- [Higher-level programming interfaces for DynamoDB \(p. 169\)](#)
- [Running the code examples in this Developer Guide \(p. 268\)](#)

## Overview of AWS SDK support for DynamoDB

The following diagram provides a high-level overview of Amazon DynamoDB application programming using the AWS SDKs.



1. You write an application using an AWS SDK for your programming language.
2. Each AWS SDK provides one or more programmatic interfaces for working with DynamoDB. The specific interfaces available depend on which programming language and AWS SDK you use. Options include:
  - [Low-level interfaces \(p. 156\)](#)
  - [Document interfaces \(p. 157\)](#)
  - [Object persistence interface \(p. 157\)](#)
  - [High Level Interfaces \(p. 169\)](#)
3. The AWS SDK constructs HTTP(S) requests for use with the low-level DynamoDB API.
4. The AWS SDK sends the request to the DynamoDB endpoint.
5. DynamoDB runs the request. If the request is successful, DynamoDB returns an HTTP 200 response code (OK). If the request is unsuccessful, DynamoDB returns an HTTP error code and an error message.
6. The AWS SDK processes the response and propagates it back to your application.

Each of the AWS SDKs provides important services to your application, including the following:


- Formatting HTTP(S) requests and serializing request parameters.
- Generating a cryptographic signature for each request.
- Forwarding requests to a DynamoDB endpoint and receiving responses from DynamoDB.
- Extracting the results from those responses.
- Implementing basic retry logic in case of errors.

You do not need to write code for any of these tasks.

**Note**

For more information about AWS SDKs, including installation instructions and documentation, see [Tools for Amazon Web Services](#).

## Programmatic interfaces



Every [AWS SDK](#) provides one or more programmatic interfaces for working with Amazon DynamoDB. These interfaces range from simple low-level DynamoDB wrappers to object-oriented persistence layers. The available interfaces vary depending on the AWS SDK and programming language that you use.

The following section highlights some of the interfaces available, using the AWS SDK for Java as an example. (Not all interfaces are available in all AWS SDKs.)

**Topics**

- [Low-level interfaces \(p. 156\)](#)
- [Document interfaces \(p. 157\)](#)
- [Object persistence interface \(p. 157\)](#)

## Low-level interfaces

Every language-specific AWS SDK provides a low-level interface for Amazon DynamoDB, with methods that closely resemble low-level DynamoDB API requests.

In some cases, you will need to identify the data types of the attributes using [Data type descriptors \(p. 162\)](#), such as `S` for string or `N` for number.

**Note**

A low-level interface is available in every language-specific AWS SDK.

The following Java program uses the low-level interface of the AWS SDK for Java. The program issues a `GetItem` request for a song in the `Music` table and prints the year that the song was released.

The `com.amazonaws.services.dynamodbv2.AmazonDynamoDB` class implements the DynamoDB low-level interface.

```
package com.amazonaws.codesamples;

import java.util.HashMap;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
import com.amazonaws.services.dynamodbv2.model.GetItemRequest;
import com.amazonaws.services.dynamodbv2.model.GetItemResult;

public class MusicLowLevelDemo {

    public static void main(String[] args) {

        AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();

        HashMap<String, AttributeValue> key = new HashMap<String, AttributeValue>();
        key.put("Artist", new AttributeValue().withS("No One You Know"));
        key.put("SongTitle", new AttributeValue().withS("Call Me Today"));

        GetItemRequest request = new GetItemRequest()
            .withTableName("Music")
            .withKey(key);

        try {
            GetItemResult result = client.getItem(request);
            if (result && result.getItem() != null) {
                AttributeValue year = result.getItem().get("Year");
                System.out.println("The song was released in " + year.getN());
            } else {
                System.out.println("No matching song was found");
            }
        } catch (Exception e) {
            System.err.println("Unable to retrieve data: ");
            System.err.println(e.getMessage());
        }
    }
}
```

```
}
```

## Document interfaces

Many AWS SDKs provide a document interface, allowing you to perform data plane operations (create, read, update, delete) on tables and indexes. With a document interface, you do not need to specify [Data type descriptors \(p. 162\)](#). The data types are implied by the semantics of the data itself. These AWS SDKs also provide methods to easily convert JSON documents to and from native Amazon DynamoDB data types.

**Note**

Document interfaces are available in the AWS SDKs for [Java](#), [.NET](#), [Node.js](#), and [JavaScript in the browser](#).

The following Java program uses the document interface of the AWS SDK for Java. The program creates a `Table` object that represents the `Music` table, and then asks that object to use `GetItem` to retrieve a song. The program then prints the year that the song was released.

The `com.amazonaws.services.dynamodbv2.document.DynamoDB` class implements the `DynamoDB` document interface. Note how `DynamoDB` acts as a wrapper around the low-level client (`AmazonDynamoDB`).

```
package com.amazonaws.codesamples.gsg;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.GetItemOutcome;
import com.amazonaws.services.dynamodbv2.document.Table;

public class MusicDocumentDemo {

    public static void main(String[] args) {

        AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
        DynamoDB docClient = new DynamoDB(client);

        Table table = docClient.getTable("Music");
        GetItemOutcome outcome = table.getItemOutcome(
            "Artist", "No One You Know",
            "SongTitle", "Call Me Today");

        int year = outcome.getItem().getInt("Year");
        System.out.println("The song was released in " + year);

    }
}
```

## Object persistence interface

Some AWS SDKs provide an object persistence interface where you do not directly perform data plane operations. Instead, you create objects that represent items in Amazon DynamoDB tables and indexes, and interact only with those objects. This allows you to write object-centric code, rather than database-centric code.

**Note**

Object persistence interfaces are available in the AWS SDKs for Java and .NET. For more information, see [???](#) (p. 169) for DynamoDB.

The following Java program uses `DynamoDBMapper`, the object persistence interface of the AWS SDK for Java. The `MusicItem` class represents an item in the `Music` table.

```
package com.amazonaws.codesamples;

import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBAttribute;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBRangeKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;

@DynamoDBTable(tableName="Music")
public class MusicItem {
    private String artist;
    private String songTitle;
    private String albumTitle;
    private int year;

    @DynamoDBHashKey(attributeName="Artist")
    public String getArtist() { return artist; }
    public void setArtist(String artist) {this.artist = artist; }

    @DynamoDBRangeKey(attributeName="SongTitle")
    public String getSongTitle() { return songTitle; }
    public void setSongTitle(String songTitle) {this.songTitle = songTitle; }

    @DynamoDBAttribute(attributeName = "AlbumTitle")
    public String getAlbumTitle() { return albumTitle; }
    public void setAlbumTitle(String albumTitle) {this.albumTitle = albumTitle; }

    @DynamoDBAttribute(attributeName = "Year")
    public int getYear() { return year; }
    public void setYear(int year) { this.year = year; }
}
```

You can then instantiate a `MusicItem` object, and retrieve a song using the `load()` method of `DynamoDBMapper`. The program then prints the year that the song was released.

The `com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper` class implements the DynamoDB object persistence interface. Note how `DynamoDBMapper` acts as a wrapper around the low-level client (`AmazonDynamoDB`).

```
package com.amazonaws.codesamples;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;

public class MusicMapperDemo {

    public static void main(String[] args) {
        AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
        DynamoDBMapper mapper = new DynamoDBMapper(client);

        MusicItem keySchema = new MusicItem();
        keySchema.setArtist("No One You Know");
        keySchema.setSongTitle("Call Me Today");

        try {
            MusicItem result = mapper.load(keySchema);
            if (result != null) {
```


```
        System.out.println(
            "The song was released in "+ result.getYear());
    } else {
        System.out.println("No matching song was found");
    }
} catch (Exception e) {
    System.err.println("Unable to retrieve data: ");
    System.err.println(e.getMessage());
}

}
```

## DynamoDB low-level API

### Topics

- [Request format \(p. 161\)](#)
- [Response format \(p. 161\)](#)
- [Data type descriptors \(p. 162\)](#)
- [Numeric data \(p. 163\)](#)
- [Binary data \(p. 163\)](#)



The Amazon DynamoDB *low-level API* is the protocol-level interface for DynamoDB. At this level, every HTTP(S) request must be correctly formatted and carry a valid digital signature.

The AWS SDKs construct low-level DynamoDB API requests on your behalf and process the responses from DynamoDB. This lets you focus on your application logic, instead of low-level details. However, you can still benefit from a basic knowledge of how the low-level DynamoDB API works.

For more information about the low-level DynamoDB API, see [Amazon DynamoDB API Reference](#).

**Note**

DynamoDB Streams has its own low-level API, which is separate from that of DynamoDB and is fully supported by the AWS SDKs.

For more information, see [Change data capture for DynamoDB Streams \(p. 598\)](#). For the low-level DynamoDB Streams API, see the [Amazon DynamoDB Streams API Reference](#).

The low-level DynamoDB API uses JavaScript Object Notation (JSON) as a wire protocol format. JSON presents data in a hierarchy so that both data values and data structure are conveyed simultaneously. Name-value pairs are defined in the format `name : value`. The data hierarchy is defined by nested brackets of name-value pairs.

DynamoDB uses JSON only as a transport protocol, not as a storage format. The AWS SDKs use JSON to send data to DynamoDB, and DynamoDB responds with JSON. DynamoDB does not store data persistently in JSON format.

**Note**

For more information about JSON, see [Introducing JSON](#) on the [JSON.org](#) website.

## Request format

The DynamoDB low-level API accepts HTTP(S) POST requests as input. The AWS SDKs construct these requests for you.

Suppose that you have a table named `Pets`, with a key schema consisting of `AnimalType` (partition key) and `Name` (sort key). Both of these attributes are of type `string`. To retrieve an item from `Pets`, the AWS SDK constructs the following request.

```
POST / HTTP/1.1
Host: dynamodb.<region>.<domain>;
Accept-Encoding: identity
Content-Length: <PayloadSizeBytes>
User-Agent: <UserAgentString>
Content-Type: application/x-amz-json-1.0
Authorization: AWS4-HMAC-SHA256 Credential=<Credential>, SignedHeaders=<Headers>,
Signature=<Signature>
X-Amz-Date: <Date>
X-Amz-Target: DynamoDB_20120810.GetItem

{
    "TableName": "Pets",
    "Key": {
        "AnimalType": {"S": "Dog"},
        "Name": {"S": "Fido"}
    }
}
```

Note the following about this request:

- The `Authorization` header contains information required for DynamoDB to authenticate the request. For more information, see [Signing AWS API requests](#) and [Signature Version 4 signing process](#) in the [Amazon Web Services General Reference](#).
- The `X-Amz-Target` header contains the name of a DynamoDB operation: `GetItem`. (This is also accompanied by the low-level API version, in this case `20120810`.)
- The payload (body) of the request contains the parameters for the operation, in JSON format. For the `GetItem` operation, the parameters are `TableName` and `Key`.

## Response format

Upon receipt of the request, DynamoDB processes it and returns a response. For the request shown previously, the HTTP(S) response payload contains the results from the operation, as shown in the following example.

```
HTTP/1.1 200 OK
x-amzn-RequestId: <RequestId>
x-amz-crc32: <Checksum>
Content-Type: application/x-amz-json-1.0
Content-Length: <PayloadSizeBytes>
Date: <Date>
{
    "Item": {
        "Age": {"N": "8"},
        "Colors": {
```

```
"L": [
    {"S": "White"},
    {"S": "Brown"},
    {"S": "Black"}
]
},
"Name": {"S": "Fido"},
"Vaccinations": {
    "M": {
        "Rabies": {
            "L": [
                {"S": "2009-03-17"},
                {"S": "2011-09-21"},
                {"S": "2014-07-08"}
            ]
        },
        "Distemper": {"S": "2015-10-13"}
    }
},
"Breed": {"S": "Beagle"},
"AnimalType": {"S": "Dog"
}
```

At this point, the AWS SDK returns the response data to your application for further processing.

**Note**

If DynamoDB can't process a request, it returns an HTTP error code and message. The AWS SDK propagates these to your application in the form of exceptions. For more information, see [Error handling with DynamoDB \(p. 163\)](#).

## Data type descriptors

The low-level DynamoDB API protocol requires each attribute to be accompanied by a data type descriptor. *Data type descriptors* are tokens that tell DynamoDB how to interpret each attribute.

The examples in [Request format \(p. 161\)](#) and [Response format \(p. 161\)](#) show examples of how data type descriptors are used. The `GetItem` request specifies `S` for the `Pets` key schema attributes (`AnimalType` and `Name`), which are of type `string`. The `GetItem` response contains a `Pets` item with attributes of type `string` (`S`), `number` (`N`), `map` (`M`), and `list` (`L`).

The following is a complete list of DynamoDB data type descriptors:

- **S** – String
- **N** – Number
- **B** – Binary
- **BOOL** – Boolean
- **NULL** – Null
- **M** – Map
- **L** – List
- **SS** – String Set
- **NS** – Number Set
- **BS** – Binary Set

**Note**

For detailed descriptions of DynamoDB data types, see [Data types \(p. 13\)](#).

## Numeric data

Different programming languages offer different levels of support for JSON. In some cases, you might decide to use a third-party library for validating and parsing JSON documents.

Some third-party libraries build upon the JSON number type, providing their own types such as `int`, `long`, or `double`. However, the native number data type in DynamoDB does not map exactly to these other data types, so these type distinctions can cause conflicts. In addition, many JSON libraries do not handle fixed-precision numeric values, and they automatically infer a double data type for digit sequences that contain a decimal point.

To solve these problems, DynamoDB provides a single numeric type with no data loss. To avoid unwanted implicit conversions to a double value, DynamoDB uses strings for the data transfer of numeric values. This approach provides flexibility for updating attribute values while maintaining proper sorting semantics, such as putting the values "01", "2", and "03" in the proper sequence.

If number precision is important to your application, you should convert numeric values to strings before you pass them to DynamoDB.

## Binary data

DynamoDB supports binary attributes. However, JSON does not natively support encoding binary data. To send binary data in a request, you will need to encode it in base64 format. Upon receiving the request, DynamoDB decodes the base64 data back to binary.

The base64 encoding scheme used by DynamoDB is described at [RFC 4648](#) on the Internet Engineering Task Force (IETF) website.

# Error handling with DynamoDB

This section describes runtime errors and how to handle them. It also describes error messages and codes that are specific to Amazon DynamoDB.

### Topics

- [Error components \(p. 163\)](#)
- [Transactional errors \(p. 164\)](#)
- [Error messages and codes \(p. 164\)](#)
- [Error handling in your application \(p. 167\)](#)
- [Error retries and exponential backoff \(p. 168\)](#)
- [Batch operations and error handling \(p. 168\)](#)

## Error components

When your program sends a request, DynamoDB attempts to process it. If the request is successful, DynamoDB returns an HTTP success status code (`200 OK`), along with the results from the requested operation.

If the request is unsuccessful, DynamoDB returns an error. Each error has three components:

- An HTTP status code (such as `400`).
- An exception name (such as `ResourceNotFoundException`).
- An error message (such as `Requested resource not found: Table: tablename not found`).

The AWS SDKs take care of propagating errors to your application so that you can take appropriate action. For example, in a Java program, you can write `try-catch` logic to handle a `ResourceNotFoundException`.

If you are not using an AWS SDK, you need to parse the content of the low-level response from DynamoDB. The following is an example of such a response.

```
HTTP/1.1 400 Bad Request
x-amzn-RequestId: LDM6CJP8RMQ1FHKSC1RBVJFPNVV4KQNSO5AEMF66Q9ASUAAJG
Content-Type: application/x-amz-json-1.0
Content-Length: 240
Date: Thu, 15 Mar 2012 23:56:23 GMT

{"__type":"com.amazonaws.dynamodb.v20120810#ResourceNotFoundException",
"message":"Requested resource not found: Table: tablename not found"}
```

## Transactional errors

For information on transactional errors, please see [Transaction conflict handling in DynamoDB \(p. 581\)](#)

## Error messages and codes

The following is a list of exceptions returned by DynamoDB, grouped by HTTP status code. If *OK to retry?* is *Yes*, you can submit the same request again. If *OK to retry?* is *No*, you need to fix the problem on the client side before you submit a new request.

### HTTP status code 400

An HTTP 400 status code indicates a problem with your request, such as authentication failure, missing required parameters, or exceeding a table's provisioned throughput. You have to fix the issue in your application before submitting the request again.

#### AccessDeniedException

Message: *Access denied.*

The client did not correctly sign the request. If you are using an AWS SDK, requests are signed for you automatically; otherwise, go to the [Signature version 4 signing process](#) in the *AWS General Reference*.

OK to retry? No

#### ConditionalCheckFailedException

Message: *The conditional request failed.*

You specified a condition that evaluated to false. For example, you might have tried to perform a conditional update on an item, but the actual value of the attribute did not match the expected value in the condition.

OK to retry? No

#### IncompleteSignatureException

Message: *The request signature does not conform to AWS standards.*

The request signature did not include all of the required components. If you are using an AWS SDK, requests are signed for you automatically; otherwise, go to the [Signature Version 4 signing process](#) in the [AWS General Reference](#).

OK to retry? No

### **ItemCollectionSizeLimitExceededException**

Message: *Collection size exceeded.*

For a table with a local secondary index, a group of items with the same partition key value has exceeded the maximum size limit of 10 GB. For more information on item collections, see [Item collections in Local Secondary Indexes \(p. 548\)](#).

OK to retry? Yes

### **LimitExceededException**

Message: *Too many operations for a given subscriber.*

There are too many concurrent control plane operations. The cumulative number of tables and indexes in the CREATING, DELETING, or UPDATING state cannot exceed 500.

OK to retry? Yes

### **MissingAuthenticationTokenException**

Message: *Request must contain a valid (registered) AWS Access Key ID.*

The request did not include the required authorization header, or it was malformed. See [DynamoDB low-level API \(p. 159\)](#).

OK to retry? No

### **ProvisionedThroughputExceeded**

Message: *Throughput exceeds the current capacity of your table or index. DynamoDB is automatically scaling your table or index so please try again shortly. If exceptions persist, check if you have a hot key: Partition key design.*

Example: A sudden spike in reads has exceeded the configured read capacity for the table.

OK to retry? Yes

### **ProvisionedThroughputExceededException**

Message: *You exceeded your maximum allowed provisioned throughput for a table or for one or more global secondary indexes. To view performance metrics for provisioned throughput vs. consumed throughput, open the Amazon CloudWatch console.*

Example: Your request rate is too high. The AWS SDKs for DynamoDB automatically retry requests that receive this exception. Your request is eventually successful, unless your retry queue is too large to finish. Reduce the frequency of requests using [Error retries and exponential backoff \(p. 168\)](#).

OK to retry? Yes

### **RequestLimitExceeded**

Message: *Throughput exceeds the current throughput limit for your account. To request a limit increase, contact AWS Support at <https://aws.amazon.com/support>.*

Example: Rate of on-demand requests exceeds the allowed account throughput and the table cannot be scaled further.

OK to retry? Yes

### **ResourceInUseException**

Message: *The resource which you are attempting to change is in use.*

Example: You tried to re-create an existing table, or delete a table currently in the CREATING state.

OK to retry? No

### **ResourceNotFoundException**

Message: *Requested resource not found.*

Example: The table that is being requested does not exist, or is too early in the CREATING state.

OK to retry? No

### **ThrottlingException**

Message: *Rate of requests exceeds the allowed throughput.*

This exception is returned as an AmazonServiceException response with a THROTTLING\_EXCEPTION status code. This exception might be returned if you perform [control plane](#) API operations too rapidly.

For tables using on-demand mode, this exception might be returned for any [data plane](#) API operation if your request rate is too high. To learn more about on-demand scaling, see [Peak traffic and scaling properties](#)

OK to retry? Yes

### **UnrecognizedClientException**

Message: *The Access Key ID or security token is invalid.*

The request signature is incorrect. The most likely cause is an invalid AWS access key ID or secret key.

OK to retry? Yes

### **ValidationException**

Message: Varies, depending upon the specific error(s) encountered

This error can occur for several reasons, such as a required parameter that is missing, a value that is out of range, or mismatched data types. The error message contains details about the specific part of the request that caused the error.

OK to retry? No

## HTTP status code 5xx

An HTTP 5xx status code indicates a problem that must be resolved by AWS. This might be a transient error, in which case you can retry your request until it succeeds. Otherwise, go to the [AWS Service Health Dashboard](#) to see if there are any operational issues with the service.

### Internal Server Error (HTTP 500)

DynamoDB could not process your request.

OK to retry? Yes

#### Note

You might encounter internal server errors while working with items. These are expected during the lifetime of a table. Any failed requests can be retried immediately.

When you receive a status code 500 on a write operation, the operation may have succeeded or failed. If the write operation is a `TransactWriteItem` request, then it is OK to retry the operation. If the write operation is a single-item write request such as `PutItem`, `UpdateItem`, or `DeleteItem`, then your application should read the state of the item before retrying the operation, and/or use [Condition expressions \(p. 361\)](#) to ensure that the item remains in a correct state after retrying regardless of whether the prior operation succeeded or failed. If idempotency is a requirement for the write operation, please use [TransactWriteItem \(p. 578\)](#), which supports idempotent requests by automatically specifying a `ClientRequestToken` to disambiguate multiple attempts to perform the same action.

### Service Unavailable (HTTP 503)

DynamoDB is currently unavailable. (This should be a temporary state.)

OK to retry? Yes

## Error handling in your application

For your application to run smoothly, you need to add logic to catch and respond to errors. Typical approaches include using try-catch blocks or if-then statements.

The AWS SDKs perform their own retries and error checking. If you encounter an error while using one of the AWS SDKs, the error code and description can help you troubleshoot it.

You should also see a Request ID in the response. The Request ID can be helpful if you need to work with AWS Support to diagnose an issue.

The following Java code example tries to get an item from a DynamoDB table and performs rudimentary error handling. (In this case, it simply informs the user that the request failed.)

```
Table table = dynamoDB.getTable("Movies");

try {
    Item item = table.getItem("year", 1978, "title", "Superman");
    if (item != null) {
        System.out.println("Result: " + item);
    } else {
        //No such item exists in the table
        System.out.println("Item not found");
    }
} catch (AmazonServiceException ase) {
```

```
System.err.println("Could not complete operation");
System.err.println("Error Message: " + ase.getMessage());
System.err.println("HTTP Status: " + ase.getStatusCode());
System.err.println("AWS Error Code: " + ase.getErrorCode());
System.err.println("Error Type: " + ase.getErrorType());
System.err.println("Request ID: " + ase.getRequestId());

} catch (AmazonClientException ace) {
    System.err.println("Internal error occurred communicating with DynamoDB");
    System.out.println("Error Message: " + ace.getMessage());
}
```

In this code example, the try-catch construct handles two different kinds of exceptions:

- `AmazonServiceException`—Thrown if the client request was correctly transmitted to DynamoDB, but DynamoDB could not process the request and returned an error response instead.
- `AmazonClientException`—Thrown if the client could not get a response from a service, or if the client could not parse the response from a service.

## Error retries and exponential backoff

Numerous components on a network, such as DNS servers, switches, load balancers, and others, can generate errors anywhere in the life of a given request. The usual technique for dealing with these error responses in a networked environment is to implement retries in the client application. This technique increases the reliability of the application.

Each AWS SDK implements retry logic automatically. You can modify the retry parameters to your needs. For example, consider a Java application that requires a fail-fast strategy, with no retries allowed in case of an error. With the AWS SDK for Java, you could use the `ClientConfiguration` class and provide a `maxErrorRetry` value of 0 to turn off the retries. For more information, see the AWS SDK documentation for your programming language.

If you're not using an AWS SDK, you should retry original requests that receive server errors (5xx). However, client errors (4xx, other than a `ThrottlingException` or a `ProvisionedThroughputExceededException`) indicate that you need to revise the request itself to correct the problem before trying again.

In addition to simple retries, each AWS SDK implements an exponential backoff algorithm for better flow control. The concept behind exponential backoff is to use progressively longer waits between retries for consecutive error responses. For example, up to 50 milliseconds before the first retry, up to 100 milliseconds before the second, up to 200 milliseconds before third, and so on. However, after a minute, if the request has not succeeded, the problem might be the request size exceeding your provisioned throughput, and not the request rate. Set the maximum number of retries to stop around one minute. If the request is not successful, investigate your provisioned throughput options.

### Note

The AWS SDKs implement automatic retry logic and exponential backoff.

Most exponential backoff algorithms use jitter (randomized delay) to prevent successive collisions. Because you aren't trying to avoid such collisions in these cases, you do not need to use this random number. However, if you use concurrent clients, jitter can help your requests succeed faster. For more information, see the blog post about [Exponential backoff and jitter](#).

## Batch operations and error handling

The DynamoDB low-level API supports batch operations for reads and writes. `BatchGetItem` reads items from one or more tables, and `BatchWriteItem` puts or deletes items in one or more tables. These

batch operations are implemented as wrappers around other non-batch DynamoDB operations. In other words, `BatchGetItem` invokes `GetItem` once for each item in the batch. Similarly, `BatchWriteItem` invokes `DeleteItem` or `PutItem`, as appropriate, for each item in the batch.

A batch operation can tolerate the failure of individual requests in the batch. For example, consider a `BatchGetItem` request to read five items. Even if some of the underlying `GetItem` requests fail, this does not cause the entire `BatchGetItem` operation to fail. However, if all five read operations fail, then the entire `BatchGetItem` fails.

The batch operations return information about individual requests that fail so that you can diagnose the problem and retry the operation. For `BatchGetItem`, the tables and primary keys in question are returned in the `UnprocessedKeys` value of the response. For `BatchWriteItem`, similar information is returned in `UnprocessedItems`.

The most likely cause of a failed read or a failed write is *throttling*. For `BatchGetItem`, one or more of the tables in the batch request does not have enough provisioned read capacity to support the operation. For `BatchWriteItem`, one or more of the tables does not have enough provisioned write capacity.

If DynamoDB returns any unprocessed items, you should retry the batch operation on those items. However, we strongly recommend that you use an exponential backoff algorithm. If you retry the batch operation immediately, the underlying read or write requests can still fail due to throttling on the individual tables. If you delay the batch operation using exponential backoff, the individual requests in the batch are much more likely to succeed.

## Higher-level programming interfaces for DynamoDB

The AWS SDKs provide applications with low-level interfaces for working with Amazon DynamoDB. These client-side classes and methods correspond directly to the low-level DynamoDB API. However, many developers experience a sense of disconnect, or *impedance mismatch*, when they need to map complex data types to items in a database table. With a low-level database interface, developers must write methods for reading or writing object data to database tables, and vice versa. The amount of extra code required for each combination of object type and database table can seem overwhelming.

To simplify development, the AWS SDKs for Java and .NET provide additional interfaces with higher levels of abstraction. The higher-level interfaces for DynamoDB let you define the relationships between objects in your program and the database tables that store those objects' data. After you define this mapping, you call simple object methods such as `save`, `load`, or `delete`, and the underlying low-level DynamoDB operations are automatically invoked on your behalf. This allows you to write object-centric code, rather than database-centric code.

The higher-level programming interfaces for DynamoDB are available in the AWS SDKs for Java and .NET.

### Java

- [Java: DynamoDBMapper \(p. 170\)](#)

### .NET

- [.NET: Document model \(p. 217\)](#)
- [.NET: Object persistence model \(p. 240\)](#)

# Java: DynamoDBMapper

## Topics

- [Supported data types for DynamoDB Mapper for Java \(p. 172\)](#)
- [Java Annotations for DynamoDB \(p. 173\)](#)
- [DynamoDBMapper Class \(p. 177\)](#)
- [Optional configuration settings for DynamoDBMapper \(p. 185\)](#)
- [Example: CRUD operations \(p. 186\)](#)
- [Example: Batch write operations \(p. 188\)](#)
- [Example: Query and scan \(p. 195\)](#)
- [Example: Transaction operations \(p. 204\)](#)
- [Optimistic locking with version number \(p. 211\)](#)
- [Mapping arbitrary data \(p. 213\)](#)

The AWS SDK for Java provides a `DynamoDBMapper` class, allowing you to map your client-side classes to Amazon DynamoDB tables. To use `DynamoDBMapper`, you define the relationship between items in a DynamoDB table and their corresponding object instances in your code. The `DynamoDBMapper` class enables you to access your tables; perform various create, read, update, and delete (CRUD) operations; and run queries.

### Note

The `DynamoDBMapper` class does not allow you to create, update, or delete tables. To perform those tasks, use the low-level SDK for Java interface instead. For more information, see [Working with DynamoDB tables in Java \(p. 332\)](#).

The SDK for Java provides a set of annotation types so that you can map your classes to tables. For example, consider a `ProductCatalog` table that has `Id` as the partition key.

```
ProductCatalog(Id, ...)
```

You can map a class in your client application to the `ProductCatalog` table as shown in the following Java code. This code defines a plain old Java object (POJO) named `CatalogItem`, which uses annotations to map object fields to DynamoDB attribute names.

### Example

```
package com.amazonaws.codesamples;

import java.util.Set;

import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBAttribute;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBIgnore;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;

@DynamoDBTable(tableName="ProductCatalog")
public class CatalogItem {

    private Integer id;
    private String title;
    private String ISBN;
    private Set<String> bookAuthors;
    private String someProp;

    @DynamoDBHashKey(attributeName="Id")
    public Integer getId() { return id; }
```

```

public void setId(Integer id) {this.id = id; }

@DynamoDBAttribute(attributeName="Title")
public String getTitle() {return title; }
public void setTitle(String title) { this.title = title; }

@DynamoDBAttribute(attributeName="ISBN")
public String getISBN() { return ISBN; }
public void setISBN(String ISBN) { this.ISBN = ISBN; }

@DynamoDBAttribute(attributeName="Authors")
public Set<String> getBookAuthors() { return bookAuthors; }
public void setBookAuthors(Set<String> bookAuthors) { this.bookAuthors = bookAuthors; }

@DynamoDBIgnore
public String getSomeProp() { return someProp; }
public void setSomeProp(String someProp) { this.someProp = someProp; }
}

```

In the preceding code, the `@DynamoDBTable` annotation maps the `CatalogItem` class to the `ProductCatalog` table. You can store individual class instances as items in the table. In the class definition, the `@DynamoDBHashKey` annotation maps the `Id` property to the primary key.

By default, the class properties map to the same name attributes in the table. The properties `Title` and `ISBN` map to the same name attributes in the table.

The `@DynamoDBAttribute` annotation is optional when the name of the DynamoDB attribute matches the name of the property declared in the class. When they differ, use this annotation with the `attributeName` parameter to specify which DynamoDB attribute this property corresponds to.

In the preceding example, the `@DynamoDBAttribute` annotation is added to each property to ensure that the property names match exactly with the tables created in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#), and to be consistent with the attribute names used in other code examples in this guide.

Your class definition can have properties that don't map to any attributes in the table. You identify these properties by adding the `@DynamoDBIgnore` annotation. In the preceding example, the `SomeProp` property is marked with the `@DynamoDBIgnore` annotation. When you upload a `CatalogItem` instance to the table, your `DynamoDBMapper` instance does not include the `SomeProp` property. In addition, the mapper does not return this attribute when you retrieve an item from the table.

After you define your mapping class, you can use `DynamoDBMapper` methods to write an instance of that class to a corresponding item in the `Catalog` table. The following code example demonstrates this technique.

```

AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();

DynamoDBMapper mapper = new DynamoDBMapper(client);

CatalogItem item = new CatalogItem();
item.setId(102);
item.setTitle("Book 102 Title");
item.setISBN("222-222222222");
item.setBookAuthors(new HashSet<String>(Arrays.asList("Author 1", "Author 2")));
item.setSomeProp("Test");

mapper.save(item);

```

The following code example shows how to retrieve the item and access some of its attributes.

```
CatalogItem partitionKey = new CatalogItem();
```

```

partitionKey.setId(102);
DynamoDBQueryExpression<CatalogItem> queryExpression = new
DynamoDBQueryExpression<CatalogItem>()
    .withHashKeyValues(partitionKey);

List<CatalogItem> itemList = mapper.query(CatalogItem.class, queryExpression);

for (int i = 0; i < itemList.size(); i++) {
    System.out.println(itemList.get(i).getTitle());
    System.out.println(itemList.get(i).getBookAuthors());
}

```

DynamoDBMapper offers an intuitive, natural way of working with DynamoDB data within Java. It also provides several built-in features, such as optimistic locking, ACID transactions, autogenerated partition key and sort key values, and object versioning.

## Supported data types for DynamoDB Mapper for Java

This section describes the supported primitive Java data types, collections, and arbitrary data types in Amazon DynamoDB.

Amazon DynamoDB supports the following primitive Java data types and primitive wrapper classes.

- `String`
- `Boolean, boolean`
- `Byte, byte`
- `Date` (as [ISO\\_8601](#) millisecond-precision string, shifted to UTC)
- `Calendar` (as [ISO\\_8601](#) millisecond-precision string, shifted to UTC)
- `Long, long`
- `Integer, int`
- `Double, double`
- `Float, float`
- `BigDecimal`
- `BigInteger`

### Note

- For more information about DynamoDB naming rules and the various supported data types, see [Supported data types and naming rules in Amazon DynamoDB \(p. 13\)](#).
- Empty Binary values are supported by the DynamoDBMapper.
- Empty String values are supported by AWS SDK for Java 2.x.

In AWS SDK for Java 1.x, DynamoDBMapper supports reading of empty String attribute values, however, it will not write empty String attribute values because these attributes are dropped from the request.

DynamoDB supports the Java [Set](#), [List](#), and [Map](#) collection types. The following table summarizes how these Java types map to the DynamoDB types.

Java type	DynamoDB type
All number types	<code>N</code> (number type)

Java type	DynamoDB type
Strings	S (string type)
Boolean	BOOL (Boolean type), 0 or 1.
ByteBuffer	B (binary type)
Date	S (string type). The Date values are stored as ISO-8601 formatted strings.
<a href="#">Set</a> collection types	SS (string set) type, NS (number set) type, or BS (binary set) type.

The `DynamoDBTypeConverter` interface lets you map your own arbitrary data types to a data type that is natively supported by DynamoDB. For more information, see [Mapping arbitrary data \(p. 213\)](#).

## Java Annotations for DynamoDB

This section describes the annotations that are available for mapping your classes and properties to tables and attributes in Amazon DynamoDB.

For the corresponding Javadoc documentation, see [Annotation Types Summary](#) in the [AWS SDK for Java API Reference](#).

**Note**

In the following annotations, only `DynamoDBTable` and the `DynamoDBHashKey` are required.

**Topics**

- [DynamoDBAttribute \(p. 173\)](#)
- [DynamoDBAutoGeneratedKey \(p. 174\)](#)
- [DynamoDBDocument \(p. 174\)](#)
- [DynamoDBHashKey \(p. 175\)](#)
- [DynamoDBIgnore \(p. 176\)](#)
- [DynamoDBIndexHashKey \(p. 176\)](#)
- [DynamoDBIndexRangeKey \(p. 176\)](#)
- [DynamoDBRangeKey \(p. 176\)](#)
- [DynamoDBTable \(p. 177\)](#)
- [DynamoDBTypeConverted \(p. 177\)](#)
- [DynamoDBTyped \(p. 177\)](#)
- [DynamoDBVersionAttribute \(p. 177\)](#)

### DynamoDBAttribute

Maps a property to a table attribute. By default, each class property maps to an item attribute with the same name. However, if the names are not the same, you can use this annotation to map a property to the attribute. In the following Java snippet, the `DynamoDBAttribute` maps the `BookAuthors` property to the `Authors` attribute name in the table.

```
@DynamoDBAttribute(attributeName = "Authors")
public List<String> getBookAuthors() { return BookAuthors; }
public void setBookAuthors(List<String> BookAuthors) { this.BookAuthors = BookAuthors; }
```

The DynamoDBMapper uses `Authors` as the attribute name when saving the object to the table.

## DynamoDBAutoGeneratedKey

Marks a partition key or sort key property as being autogenerated. DynamoDBMapper generates a random [UUID](#) when saving these attributes. Only String properties can be marked as autogenerated keys.

The following example demonstrates using autogenerated keys.

```
@DynamoDBTable(tableName="AutoGeneratedKeysExample")
public class AutoGeneratedKeys {
    private String id;
    private String payload;

    @DynamoDBHashKey(attributeName = "Id")
    @DynamoDBAutoGeneratedKey
    public String getId() { return id; }
    public void setId(String id) { this.id = id; }

    @DynamoDBAttribute(attributeName="payload")
    public String getPayload() { return this.payload; }
    public void setPayload(String payload) { this.payload = payload; }

    public static void saveItem() {
        AutoGeneratedKeys obj = new AutoGeneratedKeys();
        obj.setPayload("abc123");

        // id field is null at this point
        DynamoDBMapper mapper = new DynamoDBMapper(dynamoDBClient);
        mapper.save(obj);

        System.out.println("Object was saved with id " + obj.getId());
    }
}
```

## DynamoDBDocument

Indicates that a class can be serialized as an Amazon DynamoDB document.

For example, suppose that you wanted to map a JSON document to a DynamoDB attribute of type Map (M). The following code example defines an item containing a nested attribute (`Pictures`) of type Map.

```
public class ProductCatalogItem {

    private Integer id; //partition key
    private Pictures pictures;
    /* ...other attributes omitted... */

    @DynamoDBHashKey(attributeName="Id")
    public Integer getId() { return id; }
    public void setId(Integer id) {this.id = id; }

    @DynamoDBAttribute(attributeName="Pictures")
    public Pictures getPictures() { return pictures; }
    public void setPictures(Pictures pictures) {this.pictures = pictures; }

    // Additional properties go here.

    @DynamoDBDocument
    public static class Pictures {
        private String frontView;
```

```

private String rearView;
private String sideView;

@DynamoDBAttribute(attributeName = "FrontView")
public String getFrontView() { return frontView; }
public void setFrontView(String frontView) { this.frontView = frontView; }

@DynamoDBAttribute(attributeName = "RearView")
public String getRearView() { return rearView; }
public void setRearView(String rearView) { this.rearView = rearView; }

@DynamoDBAttribute(attributeName = "SideView")
public String getSideView() { return sideView; }
public void setSideView(String sideView) { this.sideView = sideView; }

}
}

```

You could then save a new `ProductCatalog` item, with `Pictures`, as shown in the following example.

```

ProductCatalogItem item = new ProductCatalogItem();

Pictures pix = new Pictures();
pix.setFrontView("http://example.com/products/123_front.jpg");
pix.setRearView("http://example.com/products/123_rear.jpg");
pix.setSideView("http://example.com/products/123_left_side.jpg");
item.setPictures(pix);

item.setId(123);

mapper.save(item);

```

The resulting `ProductCatalog` item would look like the following (in JSON format).

```
{
  "Id" : 123
  "Pictures" : {
    "SideView" : "http://example.com/products/123_left_side.jpg",
    "RearView" : "http://example.com/products/123_rear.jpg",
    "FrontView" : "http://example.com/products/123_front.jpg"
  }
}
```

## DynamoDBHashKey

Maps a class property to the partition key of the table. The property must be one of the scalar string, number, or binary types. The property can't be a collection type.

Assume that you have a table, `ProductCatalog`, that has `Id` as the primary key. The following Java code defines a `CatalogItem` class and maps its `Id` property to the primary key of the `ProductCatalog` table using the `@DynamoDBHashKey` tag.

```

@DynamoDBTable(tableName="ProductCatalog")
public class CatalogItem {
    private Integer Id;
    @DynamoDBHashKey(attributeName="Id")
    public Integer getId() {
        return Id;
    }
    public void setId(Integer Id) {
        this.Id = Id;
    }
}

```

```

    }
    // Additional properties go here.
}

```

## DynamoDBIgnore

Indicates to the `DynamoDBMapper` instance that the associated property should be ignored. When saving data to the table, the `DynamoDBMapper` does not save this property to the table.

Applied to the getter method or the class field for a non-modeled property. If the annotation is applied directly to the class field, the corresponding getter and setter must be declared in the same class.

## DynamoDBIndexHashKey

Maps a class property to the partition key of a global secondary index. The property must be one of the scalar string, number, or binary types. The property can't be a collection type.

Use this annotation if you need to `Query` a global secondary index. You must specify the index name (`globalSecondaryIndexName`). If the name of the class property is different from the index partition key, you also must specify the name of that index attribute (`attributeName`).

## DynamoDBIndexRangeKey

Maps a class property to the sort key of a global secondary index or a local secondary index. The property must be one of the scalar string, number, or binary types. The property can't be a collection type.

Use this annotation if you need to `Query` a local secondary index or a global secondary index and want to refine your results using the index sort key. You must specify the index name (either `globalSecondaryIndexName` or `localSecondaryIndexName`). If the name of the class property is different from the index sort key, you must also specify the name of that index attribute (`attributeName`).

## DynamoDBRangeKey

Maps a class property to the sort key of the table. The property must be one of the scalar string, number, or binary types. It cannot be a collection type.

If the primary key is composite (partition key and sort key), you can use this tag to map your class field to the sort key. For example, assume that you have a `Reply` table that stores replies for forum threads. Each thread can have many replies. So the primary key of this table is both the `ThreadId` and `ReplyDateTime`. The `ThreadId` is the partition key, and `ReplyDateTime` is the sort key.

The following Java code defines a `Reply` class and maps it to the `Reply` table. It uses both the `@DynamoDBHashKey` and `@DynamoDBRangeKey` tags to identify class properties that map to the primary key.

```

@DynamoDBTable(tableName="Reply")
public class Reply {
    private Integer id;
    private String replyDateTime;

    @DynamoDBHashKey(attributeName="Id")
    public Integer getId() { return id; }
    public void setId(Integer id) { this.id = id; }

    @DynamoDBRangeKey(attributeName="ReplyDateTime")
    public String getReplyDateTime() { return replyDateTime; }
    public void setReplyDateTime(String replyDateTime) { this.replyDateTime =
        replyDateTime; }
}

```

```
// Additional properties go here.  
}
```

## DynamoDBTable

Identifies the target table in DynamoDB. For example, the following Java code defines a class `Developer` and maps it to the `People` table in DynamoDB.

```
@DynamoDBTable(tableName="People")  
public class Developer { ...}
```

The `@DynamoDBTable` annotation can be inherited. Any new class that inherits from the `Developer` class also maps to the `People` table. For example, assume that you create a `Lead` class that inherits from the `Developer` class. Because you mapped the `Developer` class to the `People` table, the `Lead` class objects are also stored in the same table.

The `@DynamoDBTable` can also be overridden. Any new class that inherits from the `Developer` class by default maps to the same `People` table. However, you can override this default mapping. For example, if you create a class that inherits from the `Developer` class, you can explicitly map it to another table by adding the `@DynamoDBTable` annotation as shown in the following Java code example.

```
@DynamoDBTable(tableName="Managers")  
public class Manager extends Developer { ...}
```

## DynamoDBTypeConverted

An annotation to mark a property as using a custom type converter. Can be annotated on a user-defined annotation to pass additional properties to the `DynamoDBTypeConverter`.

The `DynamoDBTypeConverter` interface lets you map your own arbitrary data types to a data type that is natively supported by DynamoDB. For more information, see [Mapping arbitrary data \(p. 213\)](#).

## DynamoDBTyped

An annotation to override the standard attribute type binding. Standard types do not require the annotation if applying the default attribute binding for that type.

## DynamoDBVersionAttribute

Identifies a class property for storing an optimistic locking version number. `DynamoDBMapper` assigns a version number to this property when it saves a new item, and increments it each time you update the item. Only number scalar types are supported. For more information about data types, see [Data types \(p. 13\)](#). For more information about versioning, see [Optimistic locking with version number \(p. 211\)](#).

# DynamoDBMapper Class

The `DynamoDBMapper` class is the entry point to Amazon DynamoDB. It provides access to a DynamoDB endpoint and enables you to access your data in various tables. It also enables you to perform various create, read, update, and delete (CRUD) operations on items, and run queries and scans against tables. This class provides the following methods for working with DynamoDB.

For the corresponding Javadoc documentation, see [DynamoDBMapper](#) in the [AWS SDK for Java API Reference](#).

## Topics

- [save \(p. 178\)](#)
- [load \(p. 178\)](#)
- [delete \(p. 179\)](#)
- [query \(p. 179\)](#)
- [queryPage \(p. 180\)](#)
- [scan \(p. 180\)](#)
- [scanPage \(p. 181\)](#)
- [parallelScan \(p. 181\)](#)
- [batchSave \(p. 182\)](#)
- [batchLoad \(p. 182\)](#)
- [batchDelete \(p. 182\)](#)
- [batchWrite \(p. 183\)](#)
- [transactionWrite \(p. 183\)](#)
- [transactionLoad \(p. 184\)](#)
- [count \(p. 184\)](#)
- [generateCreateTableRequest \(p. 184\)](#)
- [createS3Link \(p. 184\)](#)
- [getS3ClientCache \(p. 185\)](#)

## save

Saves the specified object to the table. The object that you want to save is the only required parameter for this method. You can provide optional configuration parameters using the `DynamoDBMapperConfig` object.

If an item that has the same primary key does not exist, this method creates a new item in the table. If an item that has the same primary key exists, it updates the existing item. If the partition key and sort key are of type `String` and are annotated with `@DynamoDBAutoGeneratedKey`, they are given a random universally unique identifier (UUID) if left uninitialized. Version fields that are annotated with `@DynamoDBVersionAttribute` are incremented by one. Additionally, if a version field is updated or a key generated, the object passed in is updated as a result of the operation.

By default, only attributes corresponding to mapped class properties are updated. Any additional existing attributes on an item are unaffected. However, if you specify `SaveBehavior.CLOBBER`, you can force the item to be completely overwritten.

```
mapper.save(obj, new DynamoDBMapperConfig(DynamoDBMapperConfig.SaveBehavior.CLOBBER));
```

If you have versioning enabled, the client-side and server-side item versions must match. However, the version does not need to match if the `SaveBehavior.CLOBBER` option is used. For more information about versioning, see [Optimistic locking with version number \(p. 211\)](#).

## load

Retrieves an item from a table. You must provide the primary key of the item that you want to retrieve. You can provide optional configuration parameters using the `DynamoDBMapperConfig` object. For example, you can optionally request strongly consistent reads to ensure that this method retrieves only the latest item values as shown in the following Java statement.

```
CatalogItem item = mapper.load(CatalogItem.class, item.getId());
```

```
new DynamoDBMapperConfig(DynamoDBMapperConfig.ConsistentReads.CONSISTENT));
```

By default, DynamoDB returns the item that has values that are eventually consistent. For information about the eventual consistency model of DynamoDB, see [Read consistency \(p. 17\)](#).

## delete

Deletes an item from the table. You must pass in an object instance of the mapped class.

If you have versioning enabled, the client-side and server-side item versions must match. However, the version does not need to match if the `SaveBehavior.CLOBBER` option is used. For more information about versioning, see [Optimistic locking with version number \(p. 211\)](#).

## query

Queries a table or a secondary index. You can query a table or an index only if it has a composite primary key (partition key and sort key). This method requires you to provide a partition key value and a query filter that is applied on the sort key. A filter expression includes a condition and a value.

Assume that you have a table, `Reply`, that stores forum thread replies. Each thread subject can have zero or more replies. The primary key of the `Reply` table consists of the `Id` and `ReplyDateTime` fields, where `Id` is the partition key and `ReplyDateTime` is the sort key of the primary key.

```
Reply ( Id, ReplyDateTime, ... )
```

Assume that you created a mapping between a `Reply` class and the corresponding `Reply` table in DynamoDB. The following Java code uses `DynamoDBMapper` to find all replies in the past two weeks for a specific thread subject.

### Example

```
String forumName = "&DDB;";
String forumSubject = "&DDB; Thread 1";
String partitionKey = forumName + "#" + forumSubject;

long twoWeeksAgoMilli = (new Date()).getTime() - (14L*24L*60L*60L*1000L);
Date twoWeeksAgo = new Date();
twoWeeksAgo.setTime(twoWeeksAgoMilli);
SimpleDateFormat df = new SimpleDateFormat("yyyy-MM-dd'T'HH:mm:ss.SSS'Z'");
String twoWeeksAgoStr = df.format(twoWeeksAgo);

Map<String, AttributeValue> eav = new HashMap<String, AttributeValue>();
eav.put(":v1", new AttributeValue().withS(partitionKey));
eav.put(":v2",new AttributeValue().withS(twoWeeksAgoStr.toString()));

DynamoDBQueryExpression<Reply> queryExpression = new DynamoDBQueryExpression<Reply>()
    .withKeyConditionExpression("Id = :v1 and ReplyDateTime > :v2")
    .withExpressionAttributeValues(eav);

List<Reply> latestReplies = mapper.query(Reply.class, queryExpression);
```

The query returns a collection of `Reply` objects.

By default, the `query` method returns a "lazy-loaded" collection. It initially returns only one page of results, and then makes a service call for the next page if needed. To obtain all the matching items, iterate over the `latestReplies` collection.

Note that calling the `size()` method on the collection will load every result in order to provide an accurate count. This can result in a lot of provisioned throughput being consumed, and on a very large table could even exhaust all the memory in your JVM.

To query an index, you must first model the index as a mapper class. Suppose that the `Reply` table has a global secondary index named `PostedBy-Message-Index`. The partition key for this index is `PostedBy`, and the sort key is `Message`. The class definition for an item in the index would look like the following.

```
@DynamoDBTable(tableName="Reply")
public class PostedByMessage {
    private String postedBy;
    private String message;

    @DynamoDBIndexHashKey(globalSecondaryIndexName = "PostedBy-Message-Index",
    attributeName = "PostedBy")
    public String getPostedBy() { return postedBy; }
    public void setPostedBy(String postedBy) { this.postedBy = postedBy; }

    @DynamoDBIndexRangeKey(globalSecondaryIndexName = "PostedBy-Message-Index",
    attributeName = "Message")
    public String getMessage() { return message; }
    public void setMessage(String message) { this.message = message; }

    // Additional properties go here.
}
```

The `@DynamoDBTable` annotation indicates that this index is associated with the `Reply` table. The `@DynamoDBIndexHashKey` annotation denotes the partition key (`PostedBy`) of the index, and `@DynamoDBIndexRangeKey` denotes the sort key (`Message`) of the index.

Now you can use `DynamoDBMapper` to query the index, retrieving a subset of messages that were posted by a particular user. You must specify `withIndexName` so that DynamoDB knows which index to query. The following code queries a global secondary index. Because global secondary indexes support eventually consistent reads but not strongly consistent reads, you must specify `withConsistentRead(false)`.

```
HashMap<String, AttributeValue> eav = new HashMap<String, AttributeValue>();
eav.put(":v1", new AttributeValue().withS("User A"));
eav.put(":v2", new AttributeValue().withS("DynamoDB"));

DynamoDBQueryExpression<PostedByMessage> queryExpression = new
DynamoDBQueryExpression<PostedByMessage>()
    .withIndexName("PostedBy-Message-Index")
    .withConsistentRead(false)
    .withKeyConditionExpression("PostedBy = :v1 and begins_with(Message, :v2)")
    .withExpressionAttributeValues(eav);

List<PostedByMessage> iList = mapper.query(PostedByMessage.class, queryExpression);
```

The query returns a collection of `PostedByMessage` objects.

## queryPage

Queries a table or secondary index and returns a single page of matching results. As with the `query` method, you must specify a partition key value and a query filter that is applied on the sort key attribute. However, `queryPage` returns only the first "page" of data, that is, the amount of data that fits in 1 MB.

## scan

Scans an entire table or a secondary index. You can optionally specify a `FilterExpression` to filter the result set.

Assume that you have a table, `Reply`, that stores forum thread replies. Each thread subject can have zero or more replies. The primary key of the `Reply` table consists of the `Id` and `ReplyDateTime` fields, where `Id` is the partition key and `ReplyDateTime` is the sort key of the primary key.

```
Reply ( Id, ReplyDateTime, ... )
```

If you mapped a Java class to the `Reply` table, you can use the `DynamoDBMapper` to scan the table. For example, the following Java code scans the entire `Reply` table, returning only the replies for a particular year.

### Example

```
HashMap<String,AttributeValue> eav = new HashMap<String,AttributeValue>();
eav.put(":v1", new AttributeValue().withS("2015"));

DynamoDBScanExpression scanExpression = new DynamoDBScanExpression()
    .withFilterExpression("begins_with(ReplyDateTime,:v1)")
    .withExpressionAttributeValues(eav);

List<Reply> replies = mapper.scan(Reply.class, scanExpression);
```

By default, the `scan` method returns a "lazy-loaded" collection. It initially returns only one page of results, and then makes a service call for the next page if needed. To obtain all the matching items, iterate over the `replies` collection.

Note that calling the `size()` method on the collection will load every result in order to provide an accurate count. This can result in a lot of provisioned throughput being consumed, and on a very large table could even exhaust all the memory in your JVM.

To scan an index, you must first model the index as a mapper class. Suppose that the `Reply` table has a global secondary index named `PostedBy-Message-Index`. The partition key for this index is `PostedBy`, and the sort key is `Message`. A mapper class for this index is shown in the [query \(p. 179\)](#) section. It uses the `@DynamoDBIndexHashKey` and `@DynamoDBIndexRangeKey` annotations to specify the index partition key and sort key.

The following code example scans `PostedBy-Message-Index`. It does not use a scan filter, so all of the items in the index are returned to you.

```
DynamoDBScanExpression scanExpression = new DynamoDBScanExpression()
    .withIndexName("PostedBy-Message-Index")
    .withConsistentRead(false);

List<PostedByMessage> iList = mapper.scan(PostedByMessage.class, scanExpression);
Iterator<PostedByMessage> indexItems = iList.iterator();
```

### scanPage

Scans a table or secondary index and returns a single page of matching results. As with the `scan` method, you can optionally specify a `FilterExpression` to filter the result set. However, `scanPage` only returns the first "page" of data, that is, the amount of data that fits within 1 MB.

### parallelScan

Performs a parallel scan of an entire table or secondary index. You specify a number of logical segments for the table, along with a scan expression to filter the results. The `parallelScan` divides the scan task among multiple workers, one for each logical segment; the workers process the data in parallel and return the results.

The following Java code example performs a parallel scan on the `Product` table.

```
int numberOfThreads = 4;
```

```
Map<String,AttributeValue> eav = new HashMap<String,AttributeValue>();
eav.put(":n", new AttributeValue().withN("100"));

DynamoDBScanExpression scanExpression = new DynamoDBScanExpression()
    .withFilterExpression("Price <= :n")
    .withExpressionAttributeValues(eav);

List<Product> scanResult = mapper.parallelScan(Product.class, scanExpression,
    numberOfThreads);
```

For a Java code example illustrating the usage of `parallelScan`, see [Example: Query and scan \(p. 195\)](#).

## batchSave

Saves objects to one or more tables using one or more calls to the `AmazonDynamoDB.batchWriteItem` method. This method does not provide transaction guarantees.

The following Java code saves two items (books) to the `ProductCatalog` table.

```
Book book1 = new Book();
book1.id = 901;
book1.productCategory = "Book";
book1.title = "Book 901 Title";

Book book2 = new Book();
book2.id = 902;
book2.productCategory = "Book";
book2.title = "Book 902 Title";

mapper.batchSave(Arrays.asList(book1, book2));
```

## batchLoad

Retrieves multiple items from one or more tables using their primary keys.

The following Java code retrieves two items from two different tables.

```
ArrayList<Object> itemsToGet = new ArrayList<Object>();

ForumItem forumItem = new ForumItem();
forumItem.setForumName("Amazon DynamoDB");
itemsToGet.add(forumItem);

ThreadItem threadItem = new ThreadItem();
threadItem.setForumName("Amazon DynamoDB");
threadItem.setSubject("Amazon DynamoDB thread 1 message text");
itemsToGet.add(threadItem);

Map<String, List<Object>> items = mapper.batchLoad(itemsToGet);
```

## batchDelete

Deletes objects from one or more tables using one or more calls to the `AmazonDynamoDB.batchWriteItem` method. This method does not provide transaction guarantees.

The following Java code deletes two items (books) from the `ProductCatalog` table.

```
Book book1 = mapper.load(Book.class, 901);
```

```
Book book2 = mapper.load(Book.class, 902);
mapper.batchDelete(Arrays.asList(book1, book2));
```

## batchWrite

Saves objects to and deletes objects from one or more tables using one or more calls to the `AmazonDynamoDB.batchWriteItem` method. This method does not provide transaction guarantees or support versioning (conditional puts or deletes).

The following Java code writes a new item to the `Forum` table, writes a new item to the `Thread` table, and deletes an item from the `ProductCatalog` table.

```
// Create a Forum item to save
Forum forumItem = new Forum();
forumItem.name = "Test BatchWrite Forum";

// Create a Thread item to save
Thread threadItem = new Thread();
threadItem.forumName = "AmazonDynamoDB";
threadItem.subject = "My sample question";

// Load a ProductCatalog item to delete
Book book3 = mapper.load(Book.class, 903);

List<Object> objectsToWrite = Arrays.asList(forumItem, threadItem);
List<Book> objectsToDelete = Arrays.asList(book3);

mapper.batchWrite(objectsToWrite, objectsToDelete);
```

## transactionWrite

Saves objects to and deletes objects from one or more tables using one call to the `AmazonDynamoDB.transactWriteItems` method.

For a list of transaction-specific exceptions, see [TransactWriteItems errors](#).

For more information about DynamoDB transactions and the provided atomicity, consistency, isolation, and durability (ACID) guarantees see [Amazon DynamoDB Transactions](#).

### Note

This method does not support the following:

- [DynamoDBMapperConfig.SaveBehavior](#).

The following Java code writes a new item to each of the `Forum` and `Thread` tables, transactionally.

```
Thread s3ForumThread = new Thread();
s3ForumThread.forumName = "S3 Forum";
s3ForumThread.subject = "Sample Subject 1";
s3ForumThread.message = "Sample Question 1";

Forum s3Forum = new Forum();
s3Forum.name = "S3 Forum";
s3Forum.category = "Amazon Web Services";
s3Forum.threads = 1;

TransactionWriteRequest transactionWriteRequest = new TransactionWriteRequest();
transactionWriteRequest.addPut(s3Forum);
transactionWriteRequest.addPut(s3ForumThread);
```

```
mapper.transactionWrite(transactionWriteRequest);
```

## transactionLoad

Loads objects from one or more tables using one call to the `AmazonDynamoDB.transactGetItems` method.

For a list of transaction-specific exceptions, see [TransactGetItems errors](#).

For more information about DynamoDB transactions and the provided atomicity, consistency, isolation, and durability (ACID) guarantees see [Amazon DynamoDB Transactions](#).

The following Java code loads one item from each of the `Forum` and `Thread` tables, transactionally.

```
Forum dynamodbForum = new Forum();
dynamodbForum.name = "DynamoDB Forum";
Thread dynamodbForumThread = new Thread();
dynamodbForumThread.forumName = "DynamoDB Forum";

TransactionLoadRequest transactionLoadRequest = new TransactionLoadRequest();
transactionLoadRequest.addLoad(dynamodbForum);
transactionLoadRequest.addLoad(dynamodbForumThread);
mapper.transactionLoad(transactionLoadRequest);
```

## count

Evaluates the specified scan expression and returns the count of matching items. No item data is returned.

## generateCreateTableRequest

Parses a POJO class that represents a DynamoDB table, and returns a `CreateTableRequest` for that table.

## createS3Link

Creates a link to an object in Amazon S3. You must specify a bucket name and a key name, which uniquely identifies the object in the bucket.

To use `createS3Link`, your mapper class must define getter and setter methods. The following code example illustrates this by adding a new attribute and getter/setter methods to the `CatalogItem` class.

```
@DynamoDBTable(tableName="ProductCatalog")
public class CatalogItem {

    ...

    public S3Link productImage;

    ...

    @DynamoDBAttribute(attributeName = "ProductImage")
    public S3Link getProductImage() {
        return productImage;
    }

    public void setProductImage(S3Link productImage) {
        this.productImage = productImage;
    }
}
```

```
...  
}
```

The following Java code defines a new item to be written to the `Product` table. The item includes a link to a product image; the image data is uploaded to Amazon S3.

```
CatalogItem item = new CatalogItem();  
  
item.id = 150;  
item.title = "Book 150 Title";  
  
String myS3Bucket = "myS3bucket";  
String myS3Key = "productImages/book_150_cover.jpg";  
item.setProductImage(mapper.createS3Link(myS3Bucket, myS3Key));  
  
item.getProductImage().uploadFrom(new File("/file/path/book_150_cover.jpg"));  
  
mapper.save(item);
```

The `S3Link` class provides many other methods for manipulating objects in Amazon S3. For more information, see the [Javadocs for `S3Link`](#).

## getS3ClientCache

Returns the underlying `S3ClientCache` for accessing Amazon S3. An `S3ClientCache` is a smart Map for `AmazonS3Client` objects. If you have multiple clients, an `S3ClientCache` can help you keep the clients organized by AWS Region, and can create new Amazon S3 clients on demand.

## Optional configuration settings for DynamoDBMapper

When you create an instance of `DynamoDBMapper`, it has certain default behaviors; you can override these defaults by using the `DynamoDBMapperConfig` class.

The following code snippet creates a `DynamoDBMapper` with custom settings:

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();  
  
DynamoDBMapperConfig mapperConfig = DynamoDBMapperConfig.builder()  
    .withSaveBehavior(DynamoDBMapperConfig.SaveBehavior.CLOBBER)  
    .withConsistentReads(DynamoDBMapperConfig.ConsistentReads.CONSISTENT)  
    .withTableNameOverride(null)  
  
    .withPaginationLoadingStrategy(DynamoDBMapperConfig.PaginationLoadingStrategy.EAGER_LOADING)  
    .build();  
  
DynamoDBMapper mapper = new DynamoDBMapper(client, mapperConfig);
```

For more information, see [DynamoDBMapperConfig](#) in the [AWS SDK for Java API Reference](#).

You can use the following arguments for an instance of `DynamoDBMapperConfig`:

- A `DynamoDBMapperConfig.ConsistentReads` enumeration value:
  - `EVENTUAL`—the mapper instance uses an eventually consistent read request.
  - `CONSISTENT`—the mapper instance uses a strongly consistent read request. You can use this optional setting with `load`, `query`, or `scan` operations. Strongly consistent reads have implications for performance and billing; see the [DynamoDB product detail page](#) for more information.

If you do not specify a read consistency setting for your mapper instance, the default is `EVENTUAL`.

- A `DynamoDBMapperConfig.PaginationLoadingStrategy` enumeration value—Controls how the mapper instance processes a paginated list of data, such as the results from a `query` or `scan`:
  - `LAZY_LOADING`—the mapper instance loads data when possible, and keeps all loaded results in memory.
  - `EAGER_LOADING`—the mapper instance loads the data as soon as the list is initialized.
  - `ITERATION_ONLY`—you can only use an `Iterator` to read from the list. During the iteration, the list will clear all the previous results before loading the next page, so that the list will keep at most one page of the loaded results in memory. This also means the list can only be iterated once. This strategy is recommended when handling large items, in order to reduce memory overhead.

If you do not specify a pagination loading strategy for your mapper instance, the default is `LAZY_LOADING`.

- A `DynamoDBMapperConfig.SaveBehavior` enumeration value - Specifies how the mapper instance should deal with attributes during save operations:
  - `UPDATE`—during a save operation, all modeled attributes are updated, and unmodeled attributes are unaffected. Primitive number types (`byte`, `int`, `long`) are set to 0. Object types are set to null.
  - `CLOBBER`—clears and replaces all attributes, included unmodeled ones, during a save operation. This is done by deleting the item and re-creating it. Versioned field constraints are also disregarded.

If you do not specify the save behavior for your mapper instance, the default is `UPDATE`.

**Note**

DynamoDBMapper transactional operations do not support `DynamoDBMapperConfig.SaveBehavior` enumeration.

- A `DynamoDBMapperConfig.TableNameOverride` object—Instructs the mapper instance to ignore the table name specified by a class's `DynamoDBTable` annotation, and instead use a different table name that you supply. This is useful when partitioning your data into multiple tables at runtime.

You can override the default configuration object for `DynamoDBMapper` per operation, as needed.

## Example: CRUD operations

The following Java code example declares a `CatalogItem` class that has `Id`, `Title`, `ISBN`, and `Authors` properties. It uses the annotations to map these properties to the `ProductCatalog` table in DynamoDB. The example then uses the `DynamoDBMapper` to save a book object, retrieve it, update it, and then delete the book item.

**Note**

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */
```

```
package com.amazonaws.codesamples.datamodeling;

import java.io.IOException;
import java.util.Arrays;
import java.util.HashSet;
import java.util.Set;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBAttribute;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapperConfig;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;

public class DynamoDBMapperCRUDExample {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();

    public static void main(String[] args) throws IOException {
        testCRUDOperations();
        System.out.println("Example complete!");
    }

    @DynamoDBTable(tableName = "ProductCatalog")
    public static class CatalogItem {
        private Integer id;
        private String title;
        private String ISBN;
        private Set<String> bookAuthors;

        // Partition key
        @DynamoDBHashKey(attributeName = "Id")
        public Integer getId() {
            return id;
        }

        public void setId(Integer id) {
            this.id = id;
        }

        @DynamoDBAttribute(attributeName = "Title")
        public String getTitle() {
            return title;
        }

        public void setTitle(String title) {
            this.title = title;
        }

        @DynamoDBAttribute(attributeName = "ISBN")
        public String getISBN() {
            return ISBN;
        }

        public void setISBN(String ISBN) {
            this.ISBN = ISBN;
        }

        @DynamoDBAttribute(attributeName = "Authors")
        public Set<String> getBookAuthors() {
            return bookAuthors;
        }

        public void setBookAuthors(Set<String> bookAuthors) {
            this.bookAuthors = bookAuthors;
        }
    }
}
```

```
}

@Override
public String toString() {
    return "Book [ISBN=" + ISBN + ", bookAuthors=" + bookAuthors + ", id=" + id +
", title=" + title + "]";
}
}

private static void testCRUDOperations() {

    CatalogItem item = new CatalogItem();
    item.setId(601);
    item.setTitle("Book 601");
    item.setISBN("611-1111111111");
    item.setBookAuthors(new HashSet<String>(Arrays.asList("Author1", "Author2")));

    // Save the item (book).
    DynamoDBMapper mapper = new DynamoDBMapper(client);
    mapper.save(item);

    // Retrieve the item.
    CatalogItem itemRetrieved = mapper.load(CatalogItem.class, 601);
    System.out.println("Item retrieved:");
    System.out.println(itemRetrieved);

    // Update the item.
    itemRetrieved.setISBN("622-2222222222");
    itemRetrieved.setBookAuthors(new HashSet<String>(Arrays.asList("Author1",
"Author3")));
    mapper.save(itemRetrieved);
    System.out.println("Item updated:");
    System.out.println(itemRetrieved);

    // Retrieve the updated item.
    DynamoDBMapperConfig config = DynamoDBMapperConfig.builder()
        .withConsistentReads(DynamoDBMapperConfig.ConsistentReads.CONSISTENT)
        .build();
    CatalogItem updatedItem = mapper.load(CatalogItem.class, 601, config);
    System.out.println("Retrieved the previously updated item:");
    System.out.println(updatedItem);

    // Delete the item.
    mapper.delete(updatedItem);

    // Try to retrieve deleted item.
    CatalogItem deletedItem = mapper.load(CatalogItem.class, updatedItem.getId(),
config);
    if (deletedItem == null) {
        System.out.println("Done - Sample item is deleted.");
    }
}
```

## Example: Batch write operations

The following Java code example declares Book, Forum, Thread, and Reply classes and maps them to the Amazon DynamoDB tables using the `DynamoDBMapper` class.

The code illustrates the following batch write operations:

- `batchSave` to put book items in the `ProductCatalog` table.
  - `batchDelete` to delete items from the `ProductCatalog` table.

- `batchWrite` to put and delete items from the `Forum` and the `Thread` tables.

For more information about the tables used in this example, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#). For step-by-step instructions for testing the following example, see [Java code examples \(p. 274\)](#).

## Example

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples.datamodeling;

import java.text.SimpleDateFormat;
import java.util.ArrayList;
import java.util.Arrays;
import java.util.HashSet;
import java.util.List;
import java.util.Set;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBAttribute;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapperConfig;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBRangeKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;

public class DynamoDBMapperBatchWriteExample {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static SimpleDateFormat dateFormatter = new SimpleDateFormat("yyyy-MM-
dd'T'HH:mm:ss.SSS'Z'");

    public static void main(String[] args) throws Exception {
        try {

            DynamoDBMapper mapper = new DynamoDBMapper(client);

            testBatchSave(mapper);
            testBatchDelete(mapper);
            testBatchWrite(mapper);

            System.out.println("Example complete!");

        }
        catch (Throwable t) {
            System.err.println("Error running the DynamoDBMapperBatchWriteExample: " + t);
            t.printStackTrace();
        }
    }
}
```

```

}

private static void testBatchSave(DynamoDBMapper mapper) {

    Book book1 = new Book();
    book1.id = 901;
    book1.inPublication = true;
    book1.ISBN = "902-11-11-1111";
    book1.pageCount = 100;
    book1.price = 10;
    book1.productCategory = "Book";
    book1.title = "My book created in batch write";

    Book book2 = new Book();
    book2.id = 902;
    book2.inPublication = true;
    book2.ISBN = "902-11-12-1111";
    book2.pageCount = 200;
    book2.price = 20;
    book2.productCategory = "Book";
    book2.title = "My second book created in batch write";

    Book book3 = new Book();
    book3.id = 903;
    book3.inPublication = false;
    book3.ISBN = "902-11-13-1111";
    book3.pageCount = 300;
    book3.price = 25;
    book3.productCategory = "Book";
    book3.title = "My third book created in batch write";

    System.out.println("Adding three books to ProductCatalog table.");
    mapper.batchSave(Arrays.asList(book1, book2, book3));
}

private static void testBatchDelete(DynamoDBMapper mapper) {

    Book book1 = mapper.load(Book.class, 901);
    Book book2 = mapper.load(Book.class, 902);
    System.out.println("Deleting two books from the ProductCatalog table.");
    mapper.batchDelete(Arrays.asList(book1, book2));
}

private static void testBatchWrite(DynamoDBMapper mapper) {

    // Create Forum item to save
    Forum forumItem = new Forum();
    forumItem.name = "Test BatchWrite Forum";
    forumItem.threads = 0;
    forumItem.category = "Amazon Web Services";

    // Create Thread item to save
    Thread threadItem = new Thread();
    threadItem.forumName = "AmazonDynamoDB";
    threadItem.subject = "My sample question";
    threadItem.message = "BatchWrite message";
    List<String> tags = new ArrayList<String>();
    tags.add("batch operations");
    tags.add("write");
    threadItem.tags = new HashSet<String>(tags);

    // Load ProductCatalog item to delete
    Book book3 = mapper.load(Book.class, 903);

    List<Object> objectsToWrite = Arrays.asList(forumItem, threadItem);
    List<Book> objectsToDelete = Arrays.asList(book3);
}

```

```
DynamoDBMapperConfig config = DynamoDBMapperConfig.builder()
    .withSaveBehavior(DynamoDBMapperConfig.SaveBehavior.CLOBBER)
    .build();

    mapper.batchWrite(objectsToWrite, objectsToDelete, config);
}

@DynamoDBTable(tableName = "ProductCatalog")
public static class Book {
    private int id;
    private String title;
    private String ISBN;
    private int price;
    private int pageCount;
    private String productCategory;
    private boolean inPublication;

    // Partition key
    @DynamoDBHashKey(attributeName = "Id")
    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    @DynamoDBAttribute(attributeName = "Title")
    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    @DynamoDBAttribute(attributeName = "ISBN")
    public String getISBN() {
        return ISBN;
    }

    public void setISBN(String ISBN) {
        this.ISBN = ISBN;
    }

    @DynamoDBAttribute(attributeName = "Price")
    public int getPrice() {
        return price;
    }

    public void setPrice(int price) {
        this.price = price;
    }

    @DynamoDBAttribute(attributeName = "PageCount")
    public int getPageCount() {
        return pageCount;
    }

    public void setPageCount(int pageCount) {
        this.pageCount = pageCount;
    }

    @DynamoDBAttribute(attributeName = "ProductCategory")
    public String getProductCategory() {
```

```

        return productCategory;
    }

    public void setProductCategory(String productCategory) {
        this.productCategory = productCategory;
    }

    @DynamoDBAttribute(attributeName = "InPublication")
    public boolean getInPublication() {
        return inPublication;
    }

    public void setInPublication(boolean inPublication) {
        this.inPublication = inPublication;
    }

    @Override
    public String toString() {
        return "Book [ISBN=" + ISBN + ", price=" + price + ", product category=" +
productCategory + ", id=" + id
        + ", title=" + title + "]";
    }

}

@dynamoDBTable(tableName = "Reply")
public static class Reply {
    private String id;
    private String replyDateTime;
    private String message;
    private String postedBy;

    // Partition key
    @DynamoDBHashKey(attributeName = "Id")
    public String getId() {
        return id;
    }

    public void setId(String id) {
        this.id = id;
    }

    // Sort key
    @DynamoDBRangeKey(attributeName = "ReplyDateTime")
    public String getReplyDateTime() {
        return replyDateTime;
    }

    public void setReplyDateTime(String replyDateTime) {
        this.replyDateTime = replyDateTime;
    }

    @DynamoDBAttribute(attributeName = "Message")
    public String getMessage() {
        return message;
    }

    public void setMessage(String message) {
        this.message = message;
    }

    @DynamoDBAttribute(attributeName = "PostedBy")
    public String getPostedBy() {
        return postedBy;
    }
}

```

```

        public void setPostedBy(String postedBy) {
            this.postedBy = postedBy;
        }
    }

    @DynamoDBTable(tableName = "Thread")
    public static class Thread {
        private String forumName;
        private String subject;
        private String message;
        private String lastPostedDateTime;
        private String lastPostedBy;
        private Set<String> tags;
        private int answered;
        private int views;
        private int replies;

        // Partition key
        @DynamoDBHashKey(attributeName = "ForumName")
        public String getForumName() {
            return forumName;
        }

        public void setForumName(String forumName) {
            this.forumName = forumName;
        }

        // Sort key
        @DynamoDBRangeKey(attributeName = "Subject")
        public String getSubject() {
            return subject;
        }

        public void setSubject(String subject) {
            this.subject = subject;
        }

        @DynamoDBAttribute(attributeName = "Message")
        public String getMessage() {
            return message;
        }

        public void setMessage(String message) {
            this.message = message;
        }

        @DynamoDBAttribute(attributeName = "LastPostedDateTime")
        public String getLastPostedDateTime() {
            return lastPostedDateTime;
        }

        public void setLastPostedDateTime(String lastPostedDateTime) {
            this.lastPostedDateTime = lastPostedDateTime;
        }

        @DynamoDBAttribute(attributeName = "LastPostedBy")
        public String getLastPostedBy() {
            return lastPostedBy;
        }

        public void setLastPostedBy(String lastPostedBy) {
            this.lastPostedBy = lastPostedBy;
        }

        @DynamoDBAttribute(attributeName = "Tags")
        public Set<String> getTags() {
    }
}

```

```
        return tags;
    }

    public void setTags(Set<String> tags) {
        this.tags = tags;
    }

    @DynamoDBAttribute(attributeName = "Answered")
    public int getAnswered() {
        return answered;
    }

    public void setAnswered(int answered) {
        this.answered = answered;
    }

    @DynamoDBAttribute(attributeName = "Views")
    public int getViews() {
        return views;
    }

    public void setViews(int views) {
        this.views = views;
    }

    @DynamoDBAttribute(attributeName = "Replies")
    public int getReplies() {
        return replies;
    }

    public void setReplies(int replies) {
        this.replies = replies;
    }

}

{@DynamoDBTable(tableName = "Forum")}
public static class Forum {
    private String name;
    private String category;
    private int threads;

    // Partition key
    @DynamoDBHashKey(attributeName = "Name")
    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    @DynamoDBAttribute(attributeName = "Category")
    public String getCategory() {
        return category;
    }

    public void setCategory(String category) {
        this.category = category;
    }

    @DynamoDBAttribute(attributeName = "Threads")
    public int getThreads() {
        return threads;
    }
}
```

```
    public void setThreads(int threads) {
        this.threads = threads;
    }
}
```

## Example: Query and scan

The Java example in this section defines the following classes and maps them to the tables in Amazon DynamoDB. For more information about creating sample tables, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

- The `Book` class maps to `ProductCatalog` table
- The `Forum`, `Thread`, and `Reply` classes map to tables of the same name.

The example then runs the following query and scan operations using a `DynamoDBMapper` instance.

- Get a book by `Id`.

The `ProductCatalog` table has `Id` as its primary key. It does not have a sort key as part of its primary key. Therefore, you cannot query the table. You can get an item using its `Id` value.

- Run the following queries against the `Reply` table.

The `Reply` table's primary key is composed of `Id` and `ReplyDateTime` attributes. `ReplyDateTime` is a sort key. Therefore, you can query this table.

- Find replies to a forum thread posted in the last 15 days.
- Find replies to a forum thread posted in a specific date range.
- Scan the `ProductCatalog` table to find books whose price is less than a specified value.

For performance reasons, you should use the query operation instead of the scan operation. However, there are times you might need to scan a table. Suppose that there was a data entry error and one of the book prices was set to less than 0. This example scans the `ProductCategory` table to find book items (`ProductCategory` is `book`) whose price is less than 0.

- Perform a parallel scan of the `ProductCatalog` table to find bicycles of a specific type.

### Note

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

### Example

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
```

```

/*
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples.datamodeling;

import java.text.SimpleDateFormat;
import java.util.Date;
import java.util.HashMap;
import java.util.List;
import java.util.Map;
import java.util.Set;
import java.util.TimeZone;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBAttribute;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBQueryExpression;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBRangeKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBScanExpression;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;

public class DynamoDBMapperQueryScanExample {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();

    public static void main(String[] args) throws Exception {
        try {

            DynamoDBMapper mapper = new DynamoDBMapper(client);

            // Get a book - Id=101
            GetBook(mapper, 101);
            // Sample forum and thread to test queries.
            String forumName = "Amazon DynamoDB";
            String threadSubject = "DynamoDB Thread 1";
            // Sample queries.
            FindRepliesInLast15Days(mapper, forumName, threadSubject);
            FindRepliesPostedWithinTimePeriod(mapper, forumName, threadSubject);

            // Scan a table and find book items priced less than specified
            // value.
            FindBooksPricedLessThanSpecifiedValue(mapper, "20");

            // Scan a table with multiple threads and find bicycle items with a
            // specified bicycle type
            int numberOfThreads = 16;
            FindBicyclesOfSpecificTypeWithMultipleThreads(mapper, numberOfThreads, "Road");

            System.out.println("Example complete!");

        }
        catch (Throwable t) {
            System.err.println("Error running the DynamoDBMapperQueryScanExample: " + t);
            t.printStackTrace();
        }
    }

    private static void GetBook(DynamoDBMapper mapper, int id) throws Exception {
        System.out.println("GetBook: Get book Id='101' ");
        System.out.println("Book table has no sort key. You can do GetItem, but not
Query.");
    }
}

```

```

        Book book = mapper.load(Book.class, id);
        System.out.format("Id = %s Title = %s, ISBN = %s %n", book.getId(),
book.getTitle(), book.getISBN());
    }

    private static void FindRepliesInLast15Days(DynamoDBMapper mapper, String forumName,
String threadSubject)
        throws Exception {
        System.out.println("FindRepliesInLast15Days: Replies within last 15 days.");

        String partitionKey = forumName + "#" + threadSubject;

        long twoWeeksAgoMilli = (new Date()).getTime() - (15L * 24L * 60L * 60L * 1000L);
        Date twoWeeksAgo = new Date();
        twoWeeksAgo.setTime(twoWeeksAgoMilli);
        SimpleDateFormat dateFormatter = new SimpleDateFormat("yyyy-MM-
dd'T'HH:mm:ss.SSS'Z'");
        dateFormatter.setTimeZone(TimeZone.getTimeZone("UTC"));
        String twoWeeksAgoStr = dateFormatter.format(twoWeeksAgo);

        Map<String, AttributeValue> eav = new HashMap<String, AttributeValue>();
        eav.put(":val1", new AttributeValue().withS(partitionKey));
        eav.put(":val2", new AttributeValue().withS(twoWeeksAgoStr.toString()));

        DynamoDBQueryExpression<Reply> queryExpression = new
DynamoDBQueryExpression<Reply>()
            .withKeyConditionExpression("Id = :val1 and ReplyDateTime
> :val2").withExpressionAttributeValues(eav);

        List<Reply> latestReplies = mapper.query(Reply.class, queryExpression);

        for (Reply reply : latestReplies) {
            System.out.format("Id=%s, Message=%s, PostedBy=%s %n, ReplyDateTime=%s %n",
reply.getId(),
                reply.getMessage(), reply.getPostedBy(), reply.getReplyDateTime());
        }
    }

    private static void FindRepliesPostedWithinTimePeriod(DynamoDBMapper mapper, String
forumName, String threadSubject)
        throws Exception {
        String partitionKey = forumName + "#" + threadSubject;

        System.out.println(
            "FindRepliesPostedWithinTimePeriod: Find replies for thread Message = 'DynamoDB
Thread 2' posted within a period.");
        long startDateMilli = (new Date()).getTime() - (14L * 24L * 60L * 60L * 1000L); // //
Two
                                                //
weeks
                                                //
ago.
        long endDateMilli = (new Date()).getTime() - (7L * 24L * 60L * 60L * 1000L); // One
                                                //
week
                                                //
ago.
        SimpleDateFormat dateFormatter = new SimpleDateFormat("yyyy-MM-
dd'T'HH:mm:ss.SSS'Z'");
        dateFormatter.setTimeZone(TimeZone.getTimeZone("UTC"));
        String startDate = dateFormatter.format(startDateMilli);
        String endDate = dateFormatter.format(endDateMilli);

        Map<String, AttributeValue> eav = new HashMap<String, AttributeValue>();
        eav.put(":val1", new AttributeValue().withS(partitionKey));
        eav.put(":val2", new AttributeValue().withS(startDate));
    }
}

```

```

        eav.put(":val3", new AttributeValue().withS(endDate));

        DynamoDBQueryExpression<Reply> queryExpression = new
DynamoDBQueryExpression<Reply>()
            .withKeyConditionExpression("Id = :val1 and ReplyDateTime between :val2
and :val3")
            .withExpressionAttributeValues(eav);

        List<Reply> betweenReplies = mapper.query(Reply.class, queryExpression);

        for (Reply reply : betweenReplies) {
            System.out.format("Id=%s, Message=%s, PostedBy=%s %n, PostedDateTime=%s %n",
reply.getId(),
                reply.getMessage(), reply.getPostedBy(), reply.getReplyDateTime());
        }
    }

    private static void FindBooksPricedLessThanSpecifiedValue(DynamoDBMapper mapper, String
value) throws Exception {

        System.out.println("FindBooksPricedLessThanSpecifiedValue: Scan ProductCatalog.");

        Map<String, AttributeValue> eav = new HashMap<String, AttributeValue>();
        eav.put(":val1", new AttributeValue().withN(value));
        eav.put(":val2", new AttributeValue().withS("Book"));

        DynamoDBScanExpression scanExpression = new DynamoDBScanExpression()
            .withFilterExpression("Price < :val1 and ProductCategory
= :val2").withExpressionAttributeValues(eav);

        List<Book> scanResult = mapper.scan(Book.class, scanExpression);

        for (Book book : scanResult) {
            System.out.println(book);
        }
    }

    private static void FindBicyclesOfSpecificTypeWithMultipleThreads(DynamoDBMapper
mapper, int numberOfThreads,
        String bicycleType) throws Exception {

        System.out.println("FindBicyclesOfSpecificTypeWithMultipleThreads: Scan
ProductCatalog With Multiple Threads.");
        Map<String, AttributeValue> eav = new HashMap<String, AttributeValue>();
        eav.put(":val1", new AttributeValue().withS("Bicycle"));
        eav.put(":val2", new AttributeValue().withS(bicycleType));

        DynamoDBScanExpression scanExpression = new DynamoDBScanExpression()
            .withFilterExpression("ProductCategory = :val1 and BicycleType
= :val2").withExpressionAttributeValues(eav);

        List<Bicycle> scanResult = mapper.parallelScan(Bicycle.class, scanExpression,
numberOfThreads);
        for (Bicycle bicycle : scanResult) {
            System.out.println(bicycle);
        }
    }

    @DynamoDBTable(tableName = "ProductCatalog")
public static class Book {
    private int id;
    private String title;
    private String ISBN;
    private int price;
    private int pageCount;
}

```

```
private String productCategory;
private boolean inPublication;

@DynamoDBHashKey(attributeName = "Id")
public int getId() {
    return id;
}

public void setId(int id) {
    this.id = id;
}

@DynamoDBAttribute(attributeName = "Title")
public String getTitle() {
    return title;
}

public void setTitle(String title) {
    this.title = title;
}

@DynamoDBAttribute(attributeName = "ISBN")
public String getISBN() {
    return ISBN;
}

public void setISBN(String ISBN) {
    this.ISBN = ISBN;
}

@DynamoDBAttribute(attributeName = "Price")
public int getPrice() {
    return price;
}

public void setPrice(int price) {
    this.price = price;
}

@DynamoDBAttribute(attributeName = "PageCount")
public int getPageCount() {
    return pageCount;
}

public void setPageCount(int pageCount) {
    this.pageCount = pageCount;
}

@DynamoDBAttribute(attributeName = "ProductCategory")
public String getProductCategory() {
    return productCategory;
}

public void setProductCategory(String productCategory) {
    this.productCategory = productCategory;
}

@DynamoDBAttribute(attributeName = "InPublication")
public boolean getInPublication() {
    return inPublication;
}

public void setInPublication(boolean inPublication) {
    this.inPublication = inPublication;
}
```

```
    @Override
    public String toString() {
        return "Book [ISBN=" + ISBN + ", price=" + price + ", product category=" +
productCategory + ", id=" + id
        + ", title=" + title + "]";
    }
}

@DynamoDBTable(tableName = "ProductCatalog")
public static class Bicycle {
    private int id;
    private String title;
    private String description;
    private String bicycleType;
    private String brand;
    private int price;
    private List<String> color;
    private String productCategory;

    @DynamoDBHashKey(attributeName = "Id")
    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    @DynamoDBAttribute(attributeName = "Title")
    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    @DynamoDBAttribute(attributeName = "Description")
    public String getDescription() {
        return description;
    }

    public void setDescription(String description) {
        this.description = description;
    }

    @DynamoDBAttribute(attributeName = "BicycleType")
    public String getBicycleType() {
        return bicycleType;
    }

    public void setBicycleType(String bicycleType) {
        this.bicycleType = bicycleType;
    }

    @DynamoDBAttribute(attributeName = "Brand")
    public String getBrand() {
        return brand;
    }

    public void setBrand(String brand) {
        this.brand = brand;
    }

    @DynamoDBAttribute(attributeName = "Price")
```

```

public int getPrice() {
    return price;
}

public void setPrice(int price) {
    this.price = price;
}

@DynamoDBAttribute(attributeName = "Color")
public List<String> getColor() {
    return color;
}

public void setColor(List<String> color) {
    this.color = color;
}

@DynamoDBAttribute(attributeName = "ProductCategory")
public String getProductCategory() {
    return productCategory;
}

public void setProductCategory(String productCategory) {
    this.productCategory = productCategory;
}

@Override
public String toString() {
    return "Bicycle [Type=" + bicycleType + ", color=" + color + ", price=" + price
+ ", product category="
        + productCategory + ", id=" + id + ", title=" + title + "]";
}
}

@DynamoDBTable(tableName = "Reply")
public static class Reply {
    private String id;
    private String replyDateTime;
    private String message;
    private String postedBy;

    // Partition key
    @DynamoDBHashKey(attributeName = "Id")
    public String getId() {
        return id;
    }

    public void setId(String id) {
        this.id = id;
    }

    // Range key
    @DynamoDBRangeKey(attributeName = "ReplyDateTime")
    public String getReplyDateTime() {
        return replyDateTime;
    }

    public void setReplyDateTime(String replyDateTime) {
        this.replyDateTime = replyDateTime;
    }

    @DynamoDBAttribute(attributeName = "Message")
    public String getMessage() {
        return message;
    }
}

```

```
public void setMessage(String message) {
    this.message = message;
}

@DynamoDBAttribute(attributeName = "PostedBy")
public String getPostedBy() {
    return postedBy;
}

public void setPostedBy(String postedBy) {
    this.postedBy = postedBy;
}
}

@DynamoDBTable(tableName = "Thread")
public static class Thread {
    private String forumName;
    private String subject;
    private String message;
    private String lastPostedDateTime;
    private String lastPostedBy;
    private Set<String> tags;
    private int answered;
    private int views;
    private int replies;

    // Partition key
    @DynamoDBHashKey(attributeName = "ForumName")
    public String getForumName() {
        return forumName;
    }

    public void setForumName(String forumName) {
        this.forumName = forumName;
    }

    // Range key
    @DynamoDBRangeKey(attributeName = "Subject")
    public String getSubject() {
        return subject;
    }

    public void setSubject(String subject) {
        this.subject = subject;
    }

    @DynamoDBAttribute(attributeName = "Message")
    public String getMessage() {
        return message;
    }

    public void setMessage(String message) {
        this.message = message;
    }

    @DynamoDBAttribute(attributeName = "LastPostedDateTime")
    public String getLastPostedDateTime() {
        return lastPostedDateTime;
    }

    public void setLastPostedDateTime(String lastPostedDateTime) {
        this.lastPostedDateTime = lastPostedDateTime;
    }

    @DynamoDBAttribute(attributeName = "LastPostedBy")
```

```
public String getLastPostedBy() {
    return lastPostedBy;
}

public void setLastPostedBy(String lastPostedBy) {
    this.lastPostedBy = lastPostedBy;
}

@DynamoDBAttribute(attributeName = "Tags")
public Set<String> getTags() {
    return tags;
}

public void setTags(Set<String> tags) {
    this.tags = tags;
}

@DynamoDBAttribute(attributeName = "Answered")
public int getAnswered() {
    return answered;
}

public void setAnswered(int answered) {
    this.answered = answered;
}

@DynamoDBAttribute(attributeName = "Views")
public int getViews() {
    return views;
}

public void setViews(int views) {
    this.views = views;
}

@DynamoDBAttribute(attributeName = "Replies")
public int getReplies() {
    return replies;
}

public void setReplies(int replies) {
    this.replies = replies;
}

}

@dynamoDBTable(tableName = "Forum")
public static class Forum {
    private String name;
    private String category;
    private int threads;

    @DynamoDBHashKey(attributeName = "Name")
    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    @DynamoDBAttribute(attributeName = "Category")
    public String getCategory() {
        return category;
    }
}
```

```

        public void setCategory(String category) {
            this.category = category;
        }

        @DynamoDBAttribute(attributeName = "Threads")
        public int getThreads() {
            return threads;
        }

        public void setThreads(int threads) {
            this.threads = threads;
        }
    }
}

```

## Example: Transaction operations

The following Java code example declares a `Forum` and a `Thread` class and maps them to the DynamoDB tables using the `DynamoDBMapper` class.

The code illustrates the following transactional operations:

- `transactionWrite` to add, update, and delete multiple items from one or more tables in one transaction.
- `transactionLoad` to retrieve multiple items from one or more tables in one transaction.

### Example

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

import java.io.IOException;
import java.util.Arrays;
import java.util.HashSet;
import java.util.Set;
import java.util.List;
import java.util.ArrayList;
import java.util.Map;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBAttribute;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapperConfig;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBRangeKey;
import com.amazonaws.services.dynamodbv2.datamodeling.TransactionWriteRequest;
import com.amazonaws.services.dynamodbv2.datamodeling.TransactionLoadRequest;
import com.amazonaws.services.dynamodbv2.model.TransactionCanceledException;

```

```

import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTransactionWriteExpression;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTransactionLoadExpression;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMappingException;
import com.amazonaws.services.dynamodbv2.model.ResourceNotFoundException;
import com.amazonaws.services.dynamodbv2.model.InternalServerErrorException;

public class DynamoDBMapperTransactionExample {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDBMapper mapper;

    public static void main(String[] args) throws Exception {
        try {

            mapper = new DynamoDBMapper(client);

            testPutAndUpdateInTransactionWrite();
            testPutWithConditionalUpdateInTransactionWrite();
            testPutWithConditionCheckInTransactionWrite();
            testMixedOperationsInTransactionWrite();
            testTransactionLoadWithSave();
            testTransactionLoadWithTransactionWrite();
            System.out.println("Example complete");

        }
        catch (Throwable t) {
            System.err.println("Error running the DynamoDBMapperTransactionWriteExample: "
+ t);
            t.printStackTrace();
        }
    }

    private static void testTransactionLoadWithSave() {
        // Create new Forum item for DynamoDB using save
        Forum dynamodbForum = new Forum();
        dynamodbForum.name = "DynamoDB Forum";
        dynamodbForum.category = "Amazon Web Services";
        dynamodbForum.threads = 0;
        mapper.save(dynamodbForum);

        // Add a thread to DynamoDB Forum
        Thread dynamodbForumThread = new Thread();
        dynamodbForumThread.forumName = "DynamoDB Forum";
        dynamodbForumThread.subject = "Sample Subject 1";
        dynamodbForumThread.message = "Sample Question 1";
        mapper.save(dynamodbForumThread);

        // Update DynamoDB Forum to reflect updated thread count
        dynamodbForum.threads = 1;
        mapper.save(dynamodbForum);

        // Read DynamoDB Forum item and Thread item at the same time in a serializable
manner
        TransactionLoadRequest transactionLoadRequest = new TransactionLoadRequest();

        // Read entire item for DynamoDB Forum
        transactionLoadRequest.addLoad(dynamodbForum);

        // Only read subject and message attributes from Thread item
        DynamoDBTransactionLoadExpression loadExpressionForThread = new
DynamoDBTransactionLoadExpression()

        .withProjectionExpression("Subject, Message");
        transactionLoadRequest.addLoad(dynamodbForumThread, loadExpressionForThread);
    }
}

```

```

// Loaded objects are guaranteed to be in same order as the order in which they are
// added to TransactionLoadRequest
List<Object> loadedObjects = executeTransactionLoad(transactionLoadRequest);
Forum loadedDynamoDBForum = (Forum) loadedObjects.get(0);
System.out.println("Forum: " + loadedDynamoDBForum.name);
System.out.println("Threads: " + loadedDynamoDBForum.threads);
Thread loadedDynamodbForumThread = (Thread) loadedObjects.get(1);
System.out.println("Subject: " + loadedDynamodbForumThread.subject);
System.out.println("Message: " + loadedDynamodbForumThread.message);
}

private static void testTransactionLoadWithTransactionWrite() {
    // Create new Forum item for DynamoDB using save
    Forum dynamodbForum = new Forum();
    dynamodbForum.name = "DynamoDB New Forum";
    dynamodbForum.category = "Amazon Web Services";
    dynamodbForum.threads = 0;
    mapper.save(dynamodbForum);

    // Update Forum item for DynamoDB and add a thread to DynamoDB Forum, in
    // an ACID manner using transactionWrite

    dynamodbForum.threads = 1;
    Thread dynamodbForumThread = new Thread();
    dynamodbForumThread.forumName = "DynamoDB New Forum";
    dynamodbForumThread.subject = "Sample Subject 2";
    dynamodbForumThread.message = "Sample Question 2";
    TransactionWriteRequest transactionWriteRequest = new TransactionWriteRequest();
    transactionWriteRequest.addPut(dynamodbForumThread);
    transactionWriteRequest.addUpdate(dynamodbForum);
    executeTransactionWrite(transactionWriteRequest);

    // Read DynamoDB Forum item and Thread item at the same time in a serializable
manner
    TransactionLoadRequest transactionLoadRequest = new TransactionLoadRequest();

    // Read entire item for DynamoDB Forum
    transactionLoadRequest.addLoad(dynamodbForum);

    // Only read subject and message attributes from Thread item
    DynamoDBTransactionLoadExpression loadExpressionForThread = new
DynamoDBTransactionLoadExpression()

    .withProjectionExpression("Subject, Message");
    transactionLoadRequest.addLoad(dynamodbForumThread, loadExpressionForThread);

    // Loaded objects are guaranteed to be in same order as the order in which they are
    // added to TransactionLoadRequest
    List<Object> loadedObjects = executeTransactionLoad(transactionLoadRequest);
    Forum loadedDynamoDBForum = (Forum) loadedObjects.get(0);
    System.out.println("Forum: " + loadedDynamoDBForum.name);
    System.out.println("Threads: " + loadedDynamoDBForum.threads);
    Thread loadedDynamodbForumThread = (Thread) loadedObjects.get(1);
    System.out.println("Subject: " + loadedDynamodbForumThread.subject);
    System.out.println("Message: " + loadedDynamodbForumThread.message);
}

private static void testPutAndUpdateInTransactionWrite() {
    // Create new Forum item for S3 using save
    Forum s3Forum = new Forum();
    s3Forum.name = "S3 Forum";
    s3Forum.category = "Core Amazon Web Services";
    s3Forum.threads = 0;
    mapper.save(s3Forum);
}

```

```

    // Update Forum item for S3 and Create new Forum item for DynamoDB using
transactionWrite
    s3Forum.category = "Amazon Web Services";
    Forum dynamodbForum = new Forum();
    dynamodbForum.name = "DynamoDB Forum";
    dynamodbForum.category = "Amazon Web Services";
    dynamodbForum.threads = 0;
    TransactionWriteRequest transactionWriteRequest = new TransactionWriteRequest();
    transactionWriteRequest.addUpdate(s3Forum);
    transactionWriteRequest.addPut(dynamodbForum);
    executeTransactionWrite(transactionWriteRequest);
}

private static void testPutWithConditionalUpdateInTransactionWrite() {
    // Create new Thread item for DynamoDB forum and update thread count in DynamoDB
forum
    // if the DynamoDB Forum exists
    Thread dynamodbForumThread = new Thread();
    dynamodbForumThread.forumName = "DynamoDB Forum";
    dynamodbForumThread.subject = "Sample Subject 1";
    dynamodbForumThread.message = "Sample Question 1";

    Forum dynamodbForum = new Forum();
    dynamodbForum.name = "DynamoDB Forum";
    dynamodbForum.category = "Amazon Web Services";
    dynamodbForum.threads = 1;

    DynamoDBTransactionWriteExpression transactionWriteExpression = new
DynamoDBTransactionWriteExpression()

    .withConditionExpression("attribute_exists(Category)");

    TransactionWriteRequest transactionWriteRequest = new TransactionWriteRequest();
    transactionWriteRequest.addPut(dynamodbForumThread);
    transactionWriteRequest.addUpdate(dynamodbForum, transactionWriteExpression);
    executeTransactionWrite(transactionWriteRequest);
}

private static void testPutWithConditionCheckInTransactionWrite() {
    // Create new Thread item for DynamoDB forum and update thread count in DynamoDB
forum if a thread already exists
    Thread dynamodbForumThread2 = new Thread();
    dynamodbForumThread2.forumName = "DynamoDB Forum";
    dynamodbForumThread2.subject = "Sample Subject 2";
    dynamodbForumThread2.message = "Sample Question 2";

    Thread dynamodbForumThread1 = new Thread();
    dynamodbForumThread1.forumName = "DynamoDB Forum";
    dynamodbForumThread1.subject = "Sample Subject 1";
    DynamoDBTransactionWriteExpression conditionExpressionForConditionCheck = new
DynamoDBTransactionWriteExpression()

    .withConditionExpression("attribute_exists(Subject)");

    Forum dynamodbForum = new Forum();
    dynamodbForum.name = "DynamoDB Forum";
    dynamodbForum.category = "Amazon Web Services";
    dynamodbForum.threads = 2;

    TransactionWriteRequest transactionWriteRequest = new TransactionWriteRequest();
    transactionWriteRequest.addPut(dynamodbForumThread2);
    transactionWriteRequest.addConditionCheck(dynamodbForumThread1,
conditionExpressionForConditionCheck);
    transactionWriteRequest.addUpdate(dynamodbForum);
    executeTransactionWrite(transactionWriteRequest);
}

```

```

private static void testMixedOperationsInTransactionWrite() {
    // Create new Thread item for S3 forum and delete "Sample Subject 1" Thread from
DynamoDB forum if
    // "Sample Subject 2" Thread exists in DynamoDB forum
    Thread s3ForumThread = new Thread();
    s3ForumThread.forumName = "S3 Forum";
    s3ForumThread.subject = "Sample Subject 1";
    s3ForumThread.message = "Sample Question 1";

    Forum s3Forum = new Forum();
    s3Forum.name = "S3 Forum";
    s3Forum.category = "Amazon Web Services";
    s3Forum.threads = 1;

    Thread dynamodbForumThread1 = new Thread();
    dynamodbForumThread1.forumName = "DynamoDB Forum";
    dynamodbForumThread1.subject = "Sample Subject 1";

    Thread dynamodbForumThread2 = new Thread();
    dynamodbForumThread2.forumName = "DynamoDB Forum";
    dynamodbForumThread2.subject = "Sample Subject 2";
    DynamoDBTransactionWriteExpression conditionExpressionForConditionCheck = new
DynamoDBTransactionWriteExpression()

    .withConditionExpression("attribute_exists(Subject)");

    Forum dynamodbForum = new Forum();
    dynamodbForum.name = "DynamoDB Forum";
    dynamodbForum.category = "Amazon Web Services";
    dynamodbForum.threads = 1;

    TransactionWriteRequest transactionWriteRequest = new TransactionWriteRequest();
    transactionWriteRequest.addPut(s3ForumThread);
    transactionWriteRequest.addUpdate(s3Forum);
    transactionWriteRequest.addDelete(dynamodbForumThread1);
    transactionWriteRequest.addConditionCheck(dynamodbForumThread2,
conditionExpressionForConditionCheck);
    transactionWriteRequest.addUpdate(dynamodbForum);
    executeTransactionWrite(transactionWriteRequest);
}

private static List<Object> executeTransactionLoad(TransactionLoadRequest
transactionLoadRequest) {
    List<Object> loadedObjects = new ArrayList<Object>();
    try {
        loadedObjects = mapper.transactionLoad(transactionLoadRequest);
    } catch (DynamoDBMappingException ddbme) {
        System.err.println("Client side error in Mapper, fix before retrying. Error: "
+ ddbme.getMessage());
    } catch (ResourceNotFoundException rnfe) {
        System.err.println("One of the tables was not found, verify table exists before
retrying. Error: " + rnfe.getMessage());
    } catch (InternalServerException ise) {
        System.err.println("Internal Server Error, generally safe to retry with back-
off. Error: " + ise.getMessage());
    } catch (TransactionCanceledException tce) {
        System.err.println("Transaction Canceled, implies a client issue, fix before
retrying. Error: " + tce.getMessage());
    } catch (Exception ex) {
        System.err.println("An exception occurred, investigate and configure retry
strategy. Error: " + ex.getMessage());
    }
    return loadedObjects;
}

```

```

    private static void executeTransactionWrite(TransactionWriteRequest transactionWriteRequest) {
        try {
            mapper.transactionWrite(transactionWriteRequest);
        } catch (DynamoDBMappingException ddbme) {
            System.err.println("Client side error in Mapper, fix before retrying. Error: " +
+ ddbme.getMessage());
        } catch (ResourceNotFoundException rnfe) {
            System.err.println("One of the tables was not found, verify table exists before
retrying. Error: " + rnfe.getMessage());
        } catch (InternalServerException ise) {
            System.err.println("Internal Server Error, generally safe to retry with back-
off. Error: " + ise.getMessage());
        } catch (TransactionCanceledException tce) {
            System.err.println("Transaction Canceled, implies a client issue, fix before
retrying. Error: " + tce.getMessage());
        } catch (Exception ex) {
            System.err.println("An exception occurred, investigate and configure retry
strategy. Error: " + ex.getMessage());
        }
    }

    @DynamoDBTable(tableName = "Thread")
    public static class Thread {
        private String forumName;
        private String subject;
        private String message;
        private String lastPostedDateTime;
        private String lastPostedBy;
        private Set<String> tags;
        private int answered;
        private int views;
        private int replies;

        // Partition key
        @DynamoDBHashKey(attributeName = "ForumName")
        public String getForumName() {
            return forumName;
        }

        public void setForumName(String forumName) {
            this.forumName = forumName;
        }

        // Sort key
        @DynamoDBRangeKey(attributeName = "Subject")
        public String getSubject() {
            return subject;
        }

        public void setSubject(String subject) {
            this.subject = subject;
        }

        @DynamoDBAttribute(attributeName = "Message")
        public String getMessage() {
            return message;
        }

        public void setMessage(String message) {
            this.message = message;
        }

        @DynamoDBAttribute(attributeName = "LastPostedDateTime")
        public String getLastPostedDateTime() {
            return lastPostedDateTime;
        }
    }
}

```

```

        }

    public void setLastPostedDateTime(String lastPostedDateTime) {
        this.lastPostedDateTime = lastPostedDateTime;
    }

    @DynamoDBAttribute(attributeName = "LastPostedBy")
    public String getLastPostedBy() {
        return lastPostedBy;
    }

    public void setLastPostedBy(String lastPostedBy) {
        this.lastPostedBy = lastPostedBy;
    }

    @DynamoDBAttribute(attributeName = "Tags")
    public Set<String> getTags() {
        return tags;
    }

    public void setTags(Set<String> tags) {
        this.tags = tags;
    }

    @DynamoDBAttribute(attributeName = "Answered")
    public int getAnswered() {
        return answered;
    }

    public void setAnswered(int answered) {
        this.answered = answered;
    }

    @DynamoDBAttribute(attributeName = "Views")
    public int getViews() {
        return views;
    }

    public void setViews(int views) {
        this.views = views;
    }

    @DynamoDBAttribute(attributeName = "Replies")
    public int getReplies() {
        return replies;
    }

    public void setReplies(int replies) {
        this.replies = replies;
    }

}

{@DynamoDBTable(tableName = "Forum")
public static class Forum {
    private String name;
    private String category;
    private int threads;

    // Partition key
    @DynamoDBHashKey(attributeName = "Name")
    public String getName() {
        return name;
    }

    public void setName(String name) {
}
}

```

```

        this.name = name;
    }

    @DynamoDBAttribute(attributeName = "Category")
    public String getCategory() {
        return category;
    }

    public void setCategory(String category) {
        this.category = category;
    }

    @DynamoDBAttribute(attributeName = "Threads")
    public int getThreads() {
        return threads;
    }

    public void setThreads(int threads) {
        this.threads = threads;
    }
}
}

```

## Optimistic locking with version number

*Optimistic locking* is a strategy to ensure that the client-side item that you are updating (or deleting) is the same as the item in Amazon DynamoDB. If you use this strategy, your database writes are protected from being overwritten by the writes of others, and vice versa.

With optimistic locking, each item has an attribute that acts as a version number. If you retrieve an item from a table, the application records the version number of that item. You can update the item, but only if the version number on the server side has not changed. If there is a version mismatch, it means that someone else has modified the item before you did. The update attempt fails, because you have a stale version of the item. If this happens, you simply try again by retrieving the item and then trying to update it. Optimistic locking prevents you from accidentally overwriting changes that were made by others. It also prevents others from accidentally overwriting your changes.

To support optimistic locking, the AWS SDK for Java provides the `@DynamoDBVersionAttribute` annotation. In the mapping class for your table, you designate one property to store the version number, and mark it using this annotation. When you save an object, the corresponding item in the DynamoDB table will have an attribute that stores the version number. The `DynamoDBMapper` assigns a version number when you first save the object, and it automatically increments the version number each time you update the item. Your update or delete requests succeed only if the client-side object version matches the corresponding version number of the item in the DynamoDB table.

`ConditionalCheckFailedException` is thrown if:

- You use optimistic locking with `@DynamoDBVersionAttribute` and the version value on the server is different from the value on the client side.
- You specify your own conditional constraints while saving data by using `DynamoDBMapper` with `DynamoDBSaveExpression` and these constraints failed.

### Note

- DynamoDB global tables use a “last writer wins” reconciliation between concurrent updates. If you use global tables, last writer policy wins. So in this case, the locking strategy does not work as expected.
- `DynamoDBMapper` transactional write operations do not support `@DynamoDBVersionAttribute` annotation and condition expressions within

the same API call. If an object within a transactional write is annotated with `@DynamoDBVersionAttribute` and also has a condition expression, then an `SdkClientException` will be thrown.

For example, the following Java code defines a `CatalogItem` class that has several properties. The `Version` property is tagged with the `@DynamoDBVersionAttribute` annotation.

### Example

```

@DynamoDBTable(tableName="ProductCatalog")
public class CatalogItem {

    private Integer id;
    private String title;
    private String ISBN;
    private Set<String> bookAuthors;
    private String someProp;
    private Long version;

    @DynamoDBHashKey(attributeName="Id")
    public Integer getId() { return id; }
    public void setId(Integer Id) { this.id = Id; }

    @DynamoDBAttribute(attributeName="Title")
    public String getTitle() { return title; }
    public void setTitle(String title) { this.title = title; }

    @DynamoDBAttribute(attributeName="ISBN")
    public String getISBN() { return ISBN; }
    public void setISBN(String ISBN) { this.ISBN = ISBN; }

    @DynamoDBAttribute(attributeName = "Authors")
    public Set<String> getBookAuthors() { return bookAuthors; }
    public void setBookAuthors(Set<String> bookAuthors) { this.bookAuthors = bookAuthors; }

    @DynamoDBIgnore
    public String getSomeProp() { return someProp; }
    public void setSomeProp(String someProp) { this.someProp = someProp; }

    @DynamoDBVersionAttribute
    public Long getVersion() { return version; }
    public void setVersion(Long version) { this.version = version; }
}

```

You can apply the `@DynamoDBVersionAttribute` annotation to nullable types provided by the primitive wrappers classes that provide a nullable type, such as `Long` and `Integer`.

Optimistic locking has the following impact on these `DynamoDBMapper` methods:

- **save** — For a new item, the `DynamoDBMapper` assigns an initial version number of 1. If you retrieve an item, update one or more of its properties, and attempt to save the changes, the `save` operation succeeds only if the version number on the client side and the server side match. The `DynamoDBMapper` increments the version number automatically.
- **delete** — The `delete` method takes an object as a parameter, and the `DynamoDBMapper` performs a version check before deleting the item. The version check can be disabled if `DynamoDBMapperConfig.SaveBehavior.CLOBBER` is specified in the request.

The internal implementation of optimistic locking within `DynamoDBMapper` uses conditional update and conditional delete support provided by DynamoDB.

- **transactionWrite** —

- Put — For a new item, the `DynamoDBMapper` assigns an initial version number of 1. If you retrieve an item, update one or more of its properties, and attempt to save the changes, the put operation succeeds only if the version number on the client side and the server side match. The `DynamoDBMapper` increments the version number automatically.
- Update — For a new item, the `DynamoDBMapper` assigns an initial version number of 1. If you retrieve an item, update one or more of its properties, and attempt to save the changes, the update operation succeeds only if the version number on the client side and the server side match. The `DynamoDBMapper` increments the version number automatically.
- Delete — The `DynamoDBMapper` performs a version check before deleting the item. The delete operation succeeds only if the version number on the client side and the server side match.
- ConditionCheck — The `@DynamoDBVersionAttribute` annotation is not supported for ConditionCheck operations. An `SdkClientException` will be thrown when a ConditionCheck item is annotated with `@DynamoDBVersionAttribute`.

## Disabling optimistic locking

To disable optimistic locking, you can change the `DynamoDBMapperConfig.SaveBehavior` enumeration value from `UPDATE` to `CLOBBER`. You can do this by creating a `DynamoDBMapperConfig` instance that skips version checking and use this instance for all your requests. For information about `DynamoDBMapperConfig.SaveBehavior` and other optional `DynamoDBMapper` parameters, see [Optional configuration settings for DynamoDBMapper \(p. 185\)](#).

You can also set locking behavior for a specific operation only. For example, the following Java snippet uses the `DynamoDBMapper` to save a catalog item. It specifies `DynamoDBMapperConfig.SaveBehavior` by adding the optional `DynamoDBMapperConfig` parameter to the `save` method.

### Note

The `transactionWrite` method does not support `DynamoDBMapperConfig.SaveBehavior` configuration. Disabling optimistic locking for `transactionWrite` is not supported.

### Example

```
DynamoDBMapper mapper = new DynamoDBMapper(client);

// Load a catalog item.
CatalogItem item = mapper.load(CatalogItem.class, 101);
item.setTitle("This is a new title for the item");
...
// Save the item.
mapper.save(item,
    new DynamoDBMapperConfig(
        DynamoDBMapperConfig.SaveBehavior.CLOBBER));
```

## Mapping arbitrary data

In addition to the supported Java types (see [Supported data types for DynamoDB Mapper for Java \(p. 172\)](#)), you can use types in your application for which there is no direct mapping to the Amazon DynamoDB types. To map these types, you must provide an implementation that converts your complex type to a DynamoDB supported type and vice versa, and annotate the complex type accessor method using the `@DynamoDBTypeConverted` annotation. The converter code transforms data when objects are saved or loaded. It is also used for all operations that consume complex types. Note that when comparing data during query and scan operations, the comparisons are made against the data stored in DynamoDB.

For example, consider the following `CatalogItem` class that defines a property, `Dimension`, that is of `DimensionType`. This property stores the item dimensions as height, width, and thickness. Assume that

you decide to store these item dimensions as a string (such as 8.5x11x.05) in DynamoDB. The following example provides converter code that converts the `DimensionType` object to a string and a string to the `DimensionType`.

### Note

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

### Example

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
package com.amazonaws.codesamples.datamodeling;  
  
import java.io.IOException;  
import java.util.Arrays;  
import java.util.HashSet;  
import java.util.Set;  
  
import com.amazonaws.regions.Regions;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;  
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBAttribute;  
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;  
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;  
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTypeConverted;  
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTypeConverter;  
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;  
  
public class DynamoDBMapperExample {  
  
    static AmazonDynamoDB client;  
  
    public static void main(String[] args) throws IOException {  
  
        // Set the AWS region you want to access.  
        Regions usWest2 = Regions.US_WEST_2;  
        client = AmazonDynamoDBClientBuilder.standard().withRegion(usWest2).build();  
  
        DimensionType dimType = new DimensionType();  
        dimType.setHeight("8.00");  
        dimType.setLength("11.0");  
        dimType.setThickness("1.0");  
  
        Book book = new Book();  
        book.setId(502);  
        book.setTitle("Book 502");  
        book.setISBN("555-5555555555");  
        book.setBookAuthors(new HashSet<String>(Arrays.asList("Author1", "Author2")));  
        book.setDimensions(dimType);
```

```

DynamoDBMapper mapper = new DynamoDBMapper(client);
mapper.save(book);

Book bookRetrieved = mapper.load(Book.class, 502);
System.out.println("Book info: " + "\n" + bookRetrieved);

bookRetrieved.getDimensions().setHeight("9.0");
bookRetrieved.getDimensions().setLength("12.0");
bookRetrieved.getDimensions().setThickness("2.0");

mapper.save(bookRetrieved);

bookRetrieved = mapper.load(Book.class, 502);
System.out.println("Updated book info: " + "\n" + bookRetrieved);
}

@DynamoDBTable(tableName = "ProductCatalog")
public static class Book {
    private int id;
    private String title;
    private String ISBN;
    private Set<String> bookAuthors;
    private DimensionType dimensionType;

    // Partition key
    @DynamoDBHashKey(attributeName = "Id")
    public int getId() {
        return id;
    }

    public void setId(int id) {
        this.id = id;
    }

    @DynamoDBAttribute(attributeName = "Title")
    public String getTitle() {
        return title;
    }

    public void setTitle(String title) {
        this.title = title;
    }

    @DynamoDBAttribute(attributeName = "ISBN")
    public String getISBN() {
        return ISBN;
    }

    public void setISBN(String ISBN) {
        this.ISBN = ISBN;
    }

    @DynamoDBAttribute(attributeName = "Authors")
    public Set<String> getBookAuthors() {
        return bookAuthors;
    }

    public void setBookAuthors(Set<String> bookAuthors) {
        this.bookAuthors = bookAuthors;
    }

    @DynamoDBTypeConverted(converter = DimensionTypeConverter.class)
    @DynamoDBAttribute(attributeName = "Dimensions")
    public DimensionType getDimensions() {
        return dimensionType;
    }
}

```

```

        }

    @DynamoDBAttribute(attributeName = "Dimensions")
    public void setDimensions(DimensionType dimensionType) {
        this.dimensionType = dimensionType;
    }

    @Override
    public String toString() {
        return "Book [ISBN=" + ISBN + ", bookAuthors=" + bookAuthors + ",
dimensionType= "
            + dimensionType.getHeight() + " X " + dimensionType.getLength() + " X " +
dimensionType.getThickness()
            + ", Id=" + id + ", Title=" + title + "]";
    }
}

static public class DimensionType {

    private String length;
    private String height;
    private String thickness;

    public String getLength() {
        return length;
    }

    public void setLength(String length) {
        this.length = length;
    }

    public String getHeight() {
        return height;
    }

    public void setHeight(String height) {
        this.height = height;
    }

    public String getThickness() {
        return thickness;
    }

    public void setThickness(String thickness) {
        this.thickness = thickness;
    }
}

// Converts the complex type DimensionType to a string and vice-versa.
static public class DimensionTypeConverter implements DynamoDBTypeConverter<String,
DimensionType> {

    @Override
    public String convert(DimensionType object) {
        DimensionType itemDimensions = (DimensionType) object;
        String dimension = null;
        try {
            if (itemDimensions != null) {
                dimension = String.format("%s x %s x %s", itemDimensions.getLength(),
itemDimensions.getHeight(),
                    itemDimensions.getThickness());
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

```

        return dimension;
    }

    @Override
    public DimensionType unconvert(String s) {

        DimensionType itemDimension = new DimensionType();
        try {
            if (s != null && s.length() != 0) {
                String[] data = s.split("x");
                itemDimension.setLength(data[0].trim());
                itemDimension.setHeight(data[1].trim());
                itemDimension.setThickness(data[2].trim());
            }
        }
        catch (Exception e) {
            e.printStackTrace();
        }

        return itemDimension;
    }
}

```

## .NET: Document model

### Topics

- [Operations not supported by the document model \(p. 217\)](#)
- [Supported data types \(p. 217\)](#)
- [Working with items in DynamoDB using the AWS SDK for .NET document model \(p. 219\)](#)
- [Getting an item - Table.GetItem \(p. 222\)](#)
- [Deleting an item - Table.DeleteItem \(p. 223\)](#)
- [Updating an item - Table.UpdateItem \(p. 224\)](#)
- [Batch write - putting and deleting multiple items \(p. 225\)](#)
- [Example: CRUD operations using the AWS SDK for .NET document model \(p. 227\)](#)
- [Example: Batch operations using the AWS SDK for .NET document model API \(p. 230\)](#)
- [Querying tables in DynamoDB using the AWS SDK for .NET document model \(p. 232\)](#)

The AWS SDK for .NET provides document model classes that wrap some of the low-level Amazon DynamoDB operations, further simplifying your coding. In the document model, the primary classes are `Table` and `Document`. The `Table` class provides data operation methods such as `PutItem`, `GetItem`, and `DeleteItem`. It also provides the `Query` and the `Scan` methods. The `Document` class represents a single item in a table.

The preceding document model classes are available in the `Amazon.DynamoDBv2.DocumentModel` namespace.

### Operations not supported by the document model

You can't use the document model classes to create, update, and delete tables. However, the document model does support most common data operations.

### Supported data types

The document model supports a set of primitive .NET data types and collections data types. The model supports the following primitive data types.

- `bool`
- `byte`
- `char`
- `DateTime`
- `decimal`
- `double`
- `float`
- `Guid`
- `Int16`
- `Int32`
- `Int64`
- `SByte`
- `string`
- `UInt16`
- `UInt32`
- `UInt64`

The following table summarizes the mapping of the preceding .NET types to the DynamoDB types.

.NET primitive type	DynamoDB type
All number types	<code>N</code> (number type)
All string types	<code>S</code> (string type)
<code>MemoryStream</code> , <code>byte[]</code>	<code>B</code> (binary type)
<code>bool</code>	<code>N</code> (number type). 0 represents false and 1 represents true.
<code>DateTime</code>	<code>S</code> (string type). The <code>DateTime</code> values are stored as ISO-8601 formatted strings.
<code>Guid</code>	<code>S</code> (string type).
Collection types ( <code>List</code> , <code>HashSet</code> , and array)	<code>BS</code> (binary set) type, <code>SS</code> (string set) type, and <code>NS</code> (number set) type

AWS SDK for .NET defines types for mapping DynamoDB's Boolean, null, list and map types to .NET document model API:

- Use `DynamoDBBool` for Boolean type.
- Use `DynamoDBNull` for null type.
- Use `DynamoDBList` for list type.
- Use `Document` for map type.

#### Note

- Empty binary values are supported.
- Reading of empty string values is supported. Empty string attribute values are supported within attribute values of string Set type while writing to DynamoDB. Empty string attribute

values of string type and empty string values contained within List or Map type are dropped from write requests

## Working with items in DynamoDB using the AWS SDK for .NET document model

### Topics

- [Putting an item - Table.PutItem method \(p. 220\)](#)
- [Specifying optional parameters \(p. 221\)](#)

To perform data operations using the document model, you must first call the `Table.LoadTable` method, which creates an instance of the `Table` class that represents a specific table. The following C# example creates a `Table` object that represents the `ProductCatalog` table in Amazon DynamoDB.

### Example

```
Table table = Table.LoadTable(client, "ProductCatalog");
```

#### Note

In general, you use the `LoadTable` method once at the beginning of your application because it makes a `DescribeTable` call that adds to the round trip to DynamoDB.

You can then use the `Table` object to perform various data operations. Each data operation has two types of overloads: One takes the minimum required parameters and the other takes optional, operation-specific configuration information. For example, to retrieve an item, you must provide the table's primary key value, in which case you can use the following `GetItem` overload.

### Example

```
// Get the item from a table that has a primary key that is composed of only a partition key.  
Table.GetItem(Primitive partitionKey);  
// Get the item from a table whose primary key is composed of both a partition key and sort key.  
Table.GetItem(Primitive partitionKey, Primitive sortKey);
```

You also can pass optional parameters to these methods. For example, the preceding `GetItem` returns the entire item including all its attributes. You can optionally specify a list of attributes to retrieve. In this case, you use the following `GetItem` overload that takes in the operation-specific configuration object parameter.

### Example

```
// Configuration object that specifies optional parameters.  
GetItemOperationConfig config = new GetItemOperationConfig()  
{  
    AttributesToGet = new List<string>() { "Id", "Title" },  
};  
// Pass in the configuration to the GetItem method.  
// 1. Table that has only a partition key as primary key.  
Table.GetItem(Primitive partitionKey, GetItemOperationConfig config);  
// 2. Table that has both a partition key and a sort key.  
Table.GetItem(Primitive partitionKey, Primitive sortKey, GetItemOperationConfig config);
```

You can use the configuration object to specify several optional parameters such as request a specific list of attributes or specify the page size (number of items per page). Each data operation method has its own configuration class. For example, you can use the `GetItemOperationConfig` class to provide options for the `GetItem` operation. You can use the `PutItemOperationConfig` class to provide optional parameters for the `PutItem` operation.

The following sections discuss each of the data operations that are supported by the `Table` class.

## Putting an item - `Table.PutItem` method

The `PutItem` method uploads the input `Document` instance to the table. If an item that has a primary key that is specified in the input `Document` exists in the table, the `PutItem` operation replaces the entire existing item. The new item is identical to the `Document` object that you provided to the `PutItem` method. If your original item had any extra attributes, they are no longer present in the new item.

The following are the steps to put a new item into a table using the AWS SDK for .NET document model.

1. Run the `Table.LoadTable` method that provides the table name in which you want to put an item.
2. Create a `Document` object that has a list of attribute names and their values.
3. Run `Table.PutItem` by providing the `Document` instance as a parameter.

The following C# code example demonstrates the preceding tasks. The example uploads an item to the `ProductCatalog` table.

### Example

```
Table table = Table.LoadTable(client, "ProductCatalog");

var book = new Document();
book["Id"] = 101;
book["Title"] = "Book 101 Title";
book["ISBN"] = "11-11-11-11";
book["Authors"] = new List<string> { "Author 1", "Author 2" };
book["InStock"] = new DynamoDBBool(true);
book["QuantityOnHand"] = new DynamoDBNull();

table.PutItem(book);
```

In the preceding example, the `Document` instance creates an item that has `Number`, `String`, `String Set`, `Boolean`, and `Null` attributes. (`Null` is used to indicate that the `QuantityOnHand` for this product is unknown.) For `Boolean` and `Null`, use the constructor methods `DynamoDBBool` and `DynamoDBNull`.

In DynamoDB, the `List` and `Map` data types can contain elements composed of other data types. Here is how to map these data types to the document model API:

- `List` — use the `DynamoDBList` constructor.
- `Map` — use the `Document` constructor.

You can modify the preceding example to add a `List` attribute to the item. To do this, use a `DynamoDBList` constructor, as shown in the following code example.

### Example

```
Table table = Table.LoadTable(client, "ProductCatalog");

var book = new Document();
book["Id"] = 101;
```

```

/*other attributes omitted for brevity...*/

var relatedItems = new DynamoDBList();
relatedItems.Add(341);
relatedItems.Add(472);
relatedItems.Add(649);
book.Add("RelatedItems", relatedItems);

table.PutItem(book);

```

To add a Map attribute to the book, you define another Document. The following code example illustrates how to do this.

### Example

```

Table table = Table.LoadTable(client, "ProductCatalog");

var book = new Document();
book["Id"] = 101;

/*other attributes omitted for brevity...*/

var pictures = new Document();
pictures.Add("FrontView", "http://example.com/products/101_front.jpg" );
pictures.Add("RearView", "http://example.com/products/101_rear.jpg" );

book.Add("Pictures", pictures);

table.PutItem(book);

```

These examples are based on the item shown in [Specifying item attributes when using expressions \(p. 354\)](#). The document model lets you create complex nested attributes, such as the `ProductReviews` attribute shown in the case study.

### Specifying optional parameters

You can configure optional parameters for the `PutItem` operation by adding the `PutItemOperationConfig` parameter. For a complete list of optional parameters, see [PutItem](#). The following C# code example puts an item in the `ProductCatalog` table. It specifies the following optional parameter:

- The `ConditionalExpression` parameter to make this a conditional put request. The example creates an expression that specifies the `ISBN` attribute must have a specific value that has to be present in the item that you are replacing.

### Example

```

Table table = Table.LoadTable(client, "ProductCatalog");

var book = new Document();
book["Id"] = 555;
book["Title"] = "Book 555 Title";
book["Price"] = "25.00";
book["ISBN"] = "55-55-55-55";
book["Name"] = "Item 1 updated";
book["Authors"] = new List<string> { "Author x", "Author y" };
book["InStock"] = new DynamoDBBool(true);
book["QuantityOnHand"] = new DynamoDBNull();

```

```
// Create a condition expression for the optional conditional put operation.
Expression expr = new Expression();
expr.ExpressionStatement = "ISBN = :val";
expr.ExpressionAttributeValues[":val"] = "55-55-55-55";

PutItemOperationConfig config = new PutItemOperationConfig()
{
    // Optional parameter.
    ConditionalExpression = expr
};

table.PutItem(book, config);
```

## Getting an item - Table.GetItem

The `GetItem` operation retrieves an item as a `Document` instance. You must provide the primary key of the item that you want to retrieve as shown in the following C# code example.

### Example

```
Table table = Table.LoadTable(client, "ProductCatalog");
Document document = table.GetItem(101); // Primary key 101.
```

The `GetItem` operation returns all the attributes of the item and performs an eventually consistent read (see [Read consistency \(p. 17\)](#)) by default.

## Specifying optional parameters

You can configure additional options for the `GetItem` operation by adding the `GetItemOperationConfig` parameter. For a complete list of optional parameters, see [GetItem](#). The following C# code example retrieves an item from the `ProductCatalog` table. It specifies the `GetItemOperationConfig` to provide the following optional parameters:

- The `AttributesToGet` parameter to retrieve only the specified attributes.
- The `ConsistentRead` parameter to request the latest values for all the specified attributes. To learn more about data consistency, see [Read consistency \(p. 17\)](#).

### Example

```
Table table = Table.LoadTable(client, "ProductCatalog");

GetItemOperationConfig config = new GetItemOperationConfig()
{
    AttributesToGet = new List<string>() { "Id", "Title", "Authors", "InStock",
    "QuantityOnHand" },
    ConsistentRead = true
};
Document doc = table.GetItem(101, config);
```

When you retrieve an item using the document model API, you can access individual elements within the `Document` object is returned, as shown in the following example.

### Example

```
int id = doc["Id"].AsInt();
string title = doc["Title"].AsString();
List<string> authors = doc["Authors"].AsListOfString();
bool inStock = doc["InStock"].AsBoolean();
```

```
DynamoDBNull quantityOnHand = doc["QuantityOnHand"].AsDynamoDBNull();
```

For attributes that are of type `List` or `Map`, here is how to map these attributes to the document model API:

- `List` — Use the `AsDynamoDBList` method.
- `Map` — Use the `AsDocument` method.

The following code example shows how to retrieve a `List` (`RelatedItems`) and a `Map` (`Pictures`) from the `Document` object:

#### Example

```
DynamoDBList relatedItems = doc["RelatedItems"].AsDynamoDBList();
Document pictures = doc["Pictures"].AsDocument();
```

## Deleting an item - Table.DeleteItem

The `DeleteItem` operation deletes an item from a table. You can pass the item's primary key as a parameter. Or, if you've already read an item and have the corresponding `Document` object, you can pass it as a parameter to the `DeleteItem` method, as shown in the following C# code example.

#### Example

```
Table table = Table.LoadTable(client, "ProductCatalog");

// Retrieve a book (a Document instance)
Document document = table.GetItem(111);

// 1) Delete using the Document instance.
table.DeleteItem(document);

// 2) Delete using the primary key.
int partitionKey = 222;
table.DeleteItem(partitionKey)
```

## Specifying optional parameters

You can configure additional options for the `Delete` operation by adding the `DeleteItemOperationConfig` parameter. For a complete list of optional parameters, see [DeleteTable](#). The following C# code example specifies the two following optional parameters:

- The `ConditionalExpression` parameter to ensure that the book item being deleted has a specific value for the `ISBN` attribute.
- The `ReturnValues` parameter to request that the `Delete` method return the item that it deleted.

#### Example

```
Table table = Table.LoadTable(client, "ProductCatalog");
int partitionKey = 111;

Expression expr = new Expression();
expr.ExpressionStatement = "ISBN = :val";
expr.ExpressionAttributeValues[":val"] = "11-11-11-11";
```

```
// Specify optional parameters for Delete operation.  
DeleteItemOperationConfig config = new DeleteItemOperationConfig  
{  
    ConditionalExpression = expr,  
    ReturnValues = ReturnValues.AllOldAttributes // This is the only supported value when  
    using the document model.  
};  
  
// Delete the book.  
Document d = table.DeleteItem(partitionKey, config);
```

## Updating an item - Table.UpdateItem

The `UpdateItem` operation updates an existing item if it is present. If the item that has the specified primary key is not found, the `UpdateItem` operation adds a new item.

You can use the `UpdateItem` operation to update existing attribute values, add new attributes to the existing collection, or delete attributes from the existing collection. You provide these updates by creating a `Document` instance that describes the updates that you want to perform.

The `UpdateItem` action uses the following guidelines:

- If the item does not exist, `UpdateItem` adds a new item using the primary key that is specified in the input.
- If the item exists, `UpdateItem` applies the updates as follows:
  - Replaces the existing attribute values with the values in the update.
  - If an attribute that you provide in the input does not exist, it adds a new attribute to the item.
  - If the input attribute value is null, it deletes the attributes, if it is present.

### Note

This midlevel `UpdateItem` operation does not support the `Add` action (see [UpdateItem](#)) that is supported by the underlying DynamoDB operation.

### Note

The `PutItem` operation ([Putting an item - Table.PutItem method \(p. 220\)](#)) can also perform an update. If you call `PutItem` to upload an item and the primary key exists, the `PutItem` operation replaces the entire item. If there are attributes in the existing item and those attributes are not specified on the `Document` that is being put, the `PutItem` operation deletes those attributes. However, `UpdateItem` only updates the specified input attributes. Any other existing attributes of that item remain unchanged.

The following are the steps to update an item using the AWS SDK for .NET document model:

1. Run the `Table.LoadTable` method by providing the name of the table in which you want to perform the update operation.
2. Create a `Document` instance by providing all the updates that you want to perform.

To delete an existing attribute, specify the attribute value as null.

3. Call the `Table.UpdateItem` method and provide the `Document` instance as an input parameter.

You must provide the primary key either in the `Document` instance or explicitly as a parameter.

The following C# code example demonstrates the preceding tasks. The code example updates an item in the `Book` table. The `UpdateItem` operation updates the existing `Authors` attribute, deletes the `PageCount` attribute, and adds a new `XYZ` attribute. The `Document` instance includes the primary key of the book to update.

## Example

```
Table table = Table.LoadTable(client, "ProductCatalog");

var book = new Document();

// Set the attributes that you wish to update.
book["Id"] = 111; // Primary key.
// Replace the authors attribute.
book["Authors"] = new List<string> { "Author x", "Author y" };
// Add a new attribute.
book["XYZ"] = 12345;
// Delete the existing PageCount attribute.
book["PageCount"] = null;

table.Update(book);
```

## Specifying optional parameters

You can configure additional options for the `UpdateItem` operation by adding the `UpdateItemOperationConfig` parameter. For a complete list of optional parameters, see [UpdateItem](#).

The following C# code example updates a book item price to 25. It specifies the two following optional parameters:

- The `ConditionalExpression` parameter that identifies the `Price` attribute with value 20 that you expect to be present.
- The `ReturnValues` parameter to request the `UpdateItem` operation to return the item that is updated.

## Example

```
Table table = Table.LoadTable(client, "ProductCatalog");
string partitionKey = "111";

var book = new Document();
book["Id"] = partitionKey;
book["Price"] = 25;

Expression expr = new Expression();
expr.ExpressionStatement = "Price = :val";
expr.ExpressionAttributeValues[":val"] = "20";

UpdateItemOperationConfig config = new UpdateItemOperationConfig()
{
    ConditionalExpression = expr,
    ReturnValues = ReturnValues.AllOldAttributes
};

Document d1 = table.Update(book, config);
```

## Batch write - putting and deleting multiple items

*Batch write* refers to putting and deleting multiple items in a batch. The operation enables you to put and delete multiple items from one or more tables in a single call. The following are the steps to put or delete multiple items from a table using the AWS SDK for .NET document model API.

1. Create a `Table` object by executing the `Table.LoadTable` method by providing the name of the table in which you want to perform the batch operation.

2. Run the `CreateBatchWrite` method on the table instance you created in the preceding step and create a `DocumentBatchWrite` object.
3. Use the `DocumentBatchWrite` object methods to specify the documents that you want to upload or delete.
4. Call the `DocumentBatchWrite.Execute` method to run the batch operation.

When using the document model API, you can specify any number of operations in a batch. However, DynamoDB limits the number of operations in a batch and the total size of the batch in a batch operation. For more information about the specific limits, see [BatchWriteItem](#). If the document model API detects that your batch write request exceeded the number of allowed write requests, or the HTTP payload size of a batch exceeded the limit allowed by `BatchWriteItem`, it breaks the batch into several smaller batches. Additionally, if a response to a batch write returns unprocessed items, the document model API automatically sends another batch request with those unprocessed items.

The following C# code example demonstrates the preceding steps. The example uses batch write operation to perform two writes; upload a book item and delete another book item.

```
Table productCatalog = Table.LoadTable(client, "ProductCatalog");
var batchWrite = productCatalog.CreateBatchWrite();

var book1 = new Document();
book1["Id"] = 902;
book1["Title"] = "My book1 in batch write using .NET document model";
book1["Price"] = 10;
book1["Authors"] = new List<string> { "Author 1", "Author 2", "Author 3" };
book1["InStock"] = new DynamoDBBool(true);
book1["QuantityOnHand"] = 5;

batchWrite.AddDocumentToPut(book1);
// specify delete item using overload that takes PK.
batchWrite.AddKeyToDelete(12345);

batchWrite.Execute();
```

For a working example, see [Example: Batch operations using the AWS SDK for .NET document model API \(p. 230\)](#).

You can use the `batchWrite` operation to perform put and delete operations on multiple tables. The following are the steps to put or delete multiple items from multiple tables using the AWS SDK for .NET document model.

1. You create a `DocumentBatchWrite` instance for each table in which you want to put or delete multiple items, as described in the preceding procedure.
2. Create an instance of the `MultiTableDocumentBatchWrite` and add the individual `DocumentBatchWrite` objects to it.
3. Run the `MultiTableDocumentBatchWrite.Execute` method.

The following C# code example demonstrates the preceding steps. The example uses the batch write operation to perform the following write operations:

- Put a new item in the `Forum` table item.
- Put an item in the `Thread` table and delete an item from the same table.

```
// 1. Specify item to add in the Forum table.
Table forum = Table.LoadTable(client, "Forum");
var forumBatchWrite = forum.CreateBatchWrite();

var forum1 = new Document();
forum1["Name"] = "Test BatchWrite Forum";
forum1["Threads"] = 0;
forumBatchWrite.AddDocumentToPut(forum1);

// 2a. Specify item to add in the Thread table.
Table thread = Table.LoadTable(client, "Thread");
var threadBatchWrite = thread.CreateBatchWrite();

var thread1 = new Document();
thread1["ForumName"] = "Amazon S3 forum";
thread1["Subject"] = "My sample question";
thread1["Message"] = "Message text";
thread1["KeywordTags"] = new List<string>{ "Amazon S3", "Bucket" };
threadBatchWrite.AddDocumentToPut(thread1);

// 2b. Specify item to delete from the Thread table.
threadBatchWrite.AddKeyToDelete("someForumName", "someSubject");

// 3. Create multi-table batch.
var superBatch = new MultiTableDocumentBatchWrite();
superBatch.AddBatch(forumBatchWrite);
superBatch.AddBatch(threadBatchWrite);

superBatch.Execute();
```

## Example: CRUD operations using the AWS SDK for .NET document model

The following C# code example performs the following actions:

- Creates a book item in the `ProductCatalog` table.
- Retrieves the book item.
- Updates the book item. The code example shows a normal update that adds new attributes and updates existing attributes. It also shows a conditional update that updates the book price only if the existing price value is as specified in the code.
- Deletes the book item.

For step-by-step instructions to test the following example, see [.NET code examples \(p. 276\)](#).

### Example

```
/** 
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
```

```

    * specific language governing permissions and limitations under the License.
*/
using System;
using System.Collections.Generic;
using System.Linq;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.DocumentModel;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
    class MidlevelItemCRUD
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();
        private static string tableName = "ProductCatalog";
        // The sample uses the following id PK value to add book item.
        private static int sampleBookId = 555;

        static void Main(string[] args)
        {
            try
            {
                Table productCatalog = Table.LoadTable(client, tableName);
                CreateBookItem(productCatalog);
                RetrieveBook(productCatalog);
                // Couple of sample updates.
                UpdateMultipleAttributes(productCatalog);
                UpdateBookPriceConditionally(productCatalog);

                // Delete.
                DeleteBook(productCatalog);
                Console.WriteLine("To continue, press Enter");
                Console.ReadLine();
            }
            catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
            catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
            catch (Exception e) { Console.WriteLine(e.Message); }
        }

        // Creates a sample book item.
        private static void CreateBookItem(Table productCatalog)
        {
            Console.WriteLine("\n*** Executing CreateBookItem() ***");
            var book = new Document();
            book["Id"] = sampleBookId;
            book["Title"] = "Book " + sampleBookId;
            book["Price"] = 19.99;
            book["ISBN"] = "111-111111111";
            book["Authors"] = new List<string> { "Author 1", "Author 2", "Author 3" };
            book["PageCount"] = 500;
            book["Dimensions"] = "8.5x11x.5";
            book["InPublication"] = new DynamoDBBool(true);
            book["InStock"] = new DynamoDBBool(false);
            book["QuantityOnHand"] = 0;

            productCatalog.PutItem(book);
        }

        private static void RetrieveBook(Table productCatalog)
        {
            Console.WriteLine("\n*** Executing RetrieveBook() ***");
            // Optional configuration.
            GetItemOperationConfig config = new GetItemOperationConfig
            {
                AttributesToGet = new List<string> { "Id", "ISBN", "Title", "Authors",
                "Price" },

```

```

        ConsistentRead = true
    };
    Document document = productCatalog.GetItem(sampleBookId, config);
    Console.WriteLine("RetrieveBook: Printing book retrieved...");
    PrintDocument(document);
}

private static void UpdateMultipleAttributes(Table productCatalog)
{
    Console.WriteLine("\n*** Executing UpdateMultipleAttributes() ***");
    Console.WriteLine("\nUpdating multiple attributes....");
    int partitionKey = sampleBookId;

    var book = new Document();
    book["Id"] = partitionKey;
    // List of attribute updates.
    // The following replaces the existing authors list.
    book["Authors"] = new List<string> { "Author x", "Author y" };
    book["newAttribute"] = "New Value";
    book["ISBN"] = null; // Remove it.

    // Optional parameters.
    UpdateItemOperationConfig config = new UpdateItemOperationConfig
    {
        // Get updated item in response.
        ReturnValue = ReturnValue.AllNewAttributes
    };
    Document updatedBook = productCatalog.UpdateItem(book, config);
    Console.WriteLine("UpdateMultipleAttributes: Printing item after updates ...");
    PrintDocument(updatedBook);
}

private static void UpdateBookPriceConditionally(Table productCatalog)
{
    Console.WriteLine("\n*** Executing UpdateBookPriceConditionally() ***");

    int partitionKey = sampleBookId;

    var book = new Document();
    book["Id"] = partitionKey;
    book["Price"] = 29.99;

    // For conditional price update, creating a condition expression.
    Expression expr = new Expression();
    expr.ExpressionStatement = "Price = :val";
    expr.ExpressionAttributeValues[":val"] = 19.00;

    // Optional parameters.
    UpdateItemOperationConfig config = new UpdateItemOperationConfig
    {
        ConditionalExpression = expr,
        ReturnValue = ReturnValue.AllNewAttributes
    };
    Document updatedBook = productCatalog.UpdateItem(book, config);
    Console.WriteLine("UpdateBookPriceConditionally: Printing item whose price was
conditionally updated");
    PrintDocument(updatedBook);
}

private static void DeleteBook(Table productCatalog)
{
    Console.WriteLine("\n*** Executing DeleteBook() ***");
    // Optional configuration.
    DeleteItemOperationConfig config = new DeleteItemOperationConfig
    {
        // Return the deleted item.
}

```

```

        ReturnValues = ReturnValues.AllOldAttributes
    };
    Document document = productCatalog.DeleteItem(sampleBookId, config);
    Console.WriteLine("DeleteBook: Printing deleted just deleted...");
    PrintDocument(document);
}

private static void PrintDocument(Document updatedDocument)
{
    foreach (var attribute in updatedDocument.GetAttributeNames())
    {
        string stringValue = null;
        var value = updatedDocument[attribute];
        if (value is Primitive)
            stringValue = value.AsPrimitive().Value.ToString();
        else if (value is PrimitiveList)
            stringValue = string.Join(", ", (from primitive
                                              in value.AsPrimitiveList().Entries
                                              select primitive.Value).ToArray());
        Console.WriteLine("{0} - {1}", attribute, stringValue);
    }
}
}

```

## Example: Batch operations using the AWS SDK for .NET document model API

Topics

- Example: Batch write using the AWS SDK for .NET document model (p. 230)

## Example: Batch write using the AWS SDK for .NET document model

The following C# code example illustrates single table and multi-table batch write operations. The example performs the following tasks:

- Illustrates a single table batch write. It adds two items to the `ProductCatalog` table.
  - Illustrates a multi-table batch write. It adds an item to both the `Forum` and `Thread` tables and deletes an item from the `Thread` table.

If you followed the steps in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#), you already have the ProductCatalog, Forum, and Thread tables created. You can also create these sample tables programmatically. For more information, see [Creating example tables and uploading data using the AWS SDK for .NET \(p. 1272\)](#). For step-by-step instructions for testing the following example, see [.NET code examples \(p. 276\)](#).

## Example

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 */
```

```

/*
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.DocumentModel;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
    class MidLevelBatchWriteItem
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();
        static void Main(string[] args)
        {
            try
            {
                SingleTableBatchWrite();
                MultiTableBatchWrite();
            }
            catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
            catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
            catch (Exception e) { Console.WriteLine(e.Message); }

            Console.WriteLine("To continue, press Enter");
            Console.ReadLine();
        }

        private static void SingleTableBatchWrite()
        {
            Table productCatalog = Table.LoadTable(client, "ProductCatalog");
            var batchWrite = productCatalog.CreateBatchWrite();

            var book1 = new Document();
            book1["Id"] = 902;
            book1["Title"] = "My book1 in batch write using .NET helper classes";
            book1["ISBN"] = "902-11-1111-1";
            book1["Price"] = 10;
            book1["ProductCategory"] = "Book";
            book1["Authors"] = new List<string> { "Author 1", "Author 2", "Author 3" };
            book1["Dimensions"] = "8.5x11x.5";
            book1["InStock"] = new DynamoDBBool(true);
            book1["QuantityOnHand"] = new DynamoDBNull(); //Quantity is unknown at this
time

            batchWrite.AddDocumentToPut(book1);
            // Specify delete item using overload that takes PK.
            batchWrite.AddKeyToDelete(12345);
            Console.WriteLine("Performing batch write in SingleTableBatchWrite()");
            batchWrite.Execute();
        }

        private static void MultiTableBatchWrite()
        {
            // 1. Specify item to add in the Forum table.
            Table forum = Table.LoadTable(client, "Forum");
            var forumBatchWrite = forum.CreateBatchWrite();

            var forum1 = new Document();
            forum1["Name"] = "Test BatchWrite Forum";
            forum1["Threads"] = 0;
            forumBatchWrite.AddDocumentToPut(forum1);
        }
    }
}

```

```

// 2a. Specify item to add in the Thread table.
Table thread = Table.LoadTable(client, "Thread");
var threadBatchWrite = thread.CreateBatchWrite();

var thread1 = new Document();
thread1["ForumName"] = "S3 forum";
thread1["Subject"] = "My sample question";
thread1["Message"] = "Message text";
thread1["KeywordTags"] = new List<string> { "S3", "Bucket" };
threadBatchWrite.AddDocumentToPut(thread1);

// 2b. Specify item to delete from the Thread table.
threadBatchWrite.AddKeyToDelete("someForumName", "someSubject");

// 3. Create multi-table batch.
var superBatch = new MultiTableDocumentBatchWrite();
superBatch.AddBatch(forumBatchWrite);
superBatch.AddBatch(threadBatchWrite);
Console.WriteLine("Performing batch write in MultiTableBatchWrite()");
superBatch.Execute();
}
}

```

## Querying tables in DynamoDB using the AWS SDK for .NET document model

## Topics

- `Table.Query` method in the AWS SDK for .NET (p. 232)
  - `Table.Scan` method in the AWS SDK for .NET (p. 237)

## Table.Query method in the AWS SDK for .NET

The `Query` method enables you to query your tables. You can only query the tables that have a composite primary key (partition key and sort key). If your table's primary key is made of only a partition key, then the `Query` operation is not supported. By default, `Query` internally performs queries that are eventually consistent. To learn about the consistency model, see [Read consistency \(p. 17\)](#).

The `Query` method provides two overloads. The minimum required parameters to the `Query` method are a partition key value and a sort key filter. You can use the following overload to provide these minimum required parameters.

## Example

```
Query(Primitive partitionKey, RangeFilter Filter);
```

For example, the following C# code queries for all forum replies that were posted in the last 15 days.

## Example

```
string tableName = "Reply";
Table table = Table.LoadTable(client, tableName);

DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
RangeFilter filter = new RangeFilter(QueryOperator.GreaterThan, twoWeeksAgoDate);
Search search = table.Query("DynamoDB Thread 2", filter);
```

This creates a `Search` object. You can now call the `Search.GetNextSet` method iteratively to retrieve one page of results at a time, as shown in the following C# code example. The code prints the attribute values for each item that the query returns.

### Example

```
List<Document> documentSet = new List<Document>();
do
{
    documentSet = search.GetNextSet();
    foreach (var document in documentSet)
        PrintDocument(document);
} while (!search.IsDone);

    private static void PrintDocument(Document document)
{
    Console.WriteLine();
    foreach (var attribute in document.GetAttributeNames())
    {
        string stringValue = null;
        var value = document[attribute];
        if (value is Primitive)
            stringValue = value.AsPrimitive().Value;
        else if (value is PrimitiveList)
            stringValue = string.Join(", ", (from primitive
                                              in value.AsPrimitiveList().Entries
                                              select primitive.Value).ToArray());
        Console.WriteLine("{0} - {1}", attribute, stringValue);
    }
}
```

### Specifying optional parameters

You can also specify optional parameters for `Query`, such as specifying a list of attributes to retrieve, strongly consistent reads, page size, and the number of items returned per page. For a complete list of parameters, see [Query](#). To specify optional parameters, you must use the following overload in which you provide the `QueryOperationConfig` object.

### Example

```
Query(QueryOperationConfig config);
```

Assume that you want to run the query in the preceding example (retrieve forum replies posted in the last 15 days). However, assume that you want to provide optional query parameters to retrieve only specific attributes and also request a strongly consistent read. The following C# code example constructs the request using the `QueryOperationConfig` object.

### Example

```
Table table = Table.LoadTable(client, "Reply");
DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
QueryOperationConfig config = new QueryOperationConfig()
{
    HashKey = "Dynamodb Thread 2", //Partition key
    AttributesToGet = new List<string>
    {
        "Subject", "ReplyDateTime", "PostedBy"
    },
    ConsistentRead = true,
    Filter = new RangeFilter(QueryOperator.GreaterThan, twoWeeksAgoDate)
};
```

```
Search search = table.Query(config);
```

### Example: Query using the Table.Query method

The following C# code example uses the `Table.Query` method to run the following sample queries.

- The following queries are run against the `Reply` table.
- Find forum thread replies that were posted in the last 15 days.

This query is run twice. In the first `Table.Query` call, the example provides only the required query parameters. In the second `Table.Query` call, you provide optional query parameters to request a strongly consistent read and a list of attributes to retrieve.

- Find forum thread replies posted during a period of time.

This query uses the `Between` query operator to find replies posted in between two dates.

- Get a product from the `ProductCatalog` table.

Because the `ProductCatalog` table has a primary key that is only a partition key, you can only get items; you cannot query the table. The example retrieves a specific product item using the item `Id`.

### Example

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
using System;  
using System.Collections.Generic;  
using System.Linq;  
using Amazon.DynamoDBv2;  
using Amazon.DynamoDBv2.DocumentModel;  
using Amazon.Runtime;  
using Amazon.SecurityToken;  
  
namespace com.amazonaws.codesamples  
{  
    class MidLevelQueryAndScan  
    {  
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();  
  
        static void Main(string[] args)  
        {  
            try  
            {  
                // Query examples.  
                Table replyTable = Table.LoadTable(client, "Reply");  
                string forumName = "Amazon DynamoDB";  
                string threadSubject = "DynamoDB Thread 2";  
                FindRepliesInLast15Days(replyTable, forumName, threadSubject);  
                FindRepliesInLast15DaysWithConfig(replyTable, forumName, threadSubject);  
            }  
        }  
    }  
}
```

```

        FindRepliesPostedWithinTimePeriod(replyTable, forumName, threadSubject);

        // Get Example.
        Table productCatalogTable = Table.LoadTable(client, "ProductCatalog");
        int productId = 101;
        GetProduct(productCatalogTable, productId);

        Console.WriteLine("To continue, press Enter");
        Console.ReadLine();
    }
    catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
    catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
    catch (Exception e) { Console.WriteLine(e.Message); }
}

private static void GetProduct(Table tableName, int productId)
{
    Console.WriteLine("**** Executing GetProduct() ****");
    Document productDocument = tableName.GetItem(productId);
    if (productDocument != null)
    {
        PrintDocument(productDocument);
    }
    else
    {
        Console.WriteLine("Error: product " + productId + " does not exist");
    }
}

private static void FindRepliesInLast15Days(Table table, string forumName, string
threadSubject)
{
    string Attribute = forumName + "#" + threadSubject;

    DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
    QueryFilter filter = new QueryFilter("Id", QueryOperator.Equal, partitionKey);
    filter.AddCondition("ReplyDateTime", QueryOperator.GreaterThan,
twoWeeksAgoDate);

    // Use Query overloads that takes the minimum required query parameters.
    Search search = table.Query(filter);

    List<Document> documentSet = new List<Document>();
    do
    {
        documentSet = search.GetNextSet();
        Console.WriteLine("\nFindRepliesInLast15Days: printing .....");
        foreach (var document in documentSet)
            PrintDocument(document);
    } while (!search.IsDone);
}

private static void FindRepliesPostedWithinTimePeriod(Table table, string
forumName, string threadSubject)
{
    DateTime startDate = DateTime.UtcNow.Subtract(new TimeSpan(21, 0, 0, 0));
    DateTime endDate = DateTime.UtcNow.Subtract(new TimeSpan(1, 0, 0, 0));

    QueryFilter filter = new QueryFilter("Id", QueryOperator.Equal, forumName + "#"
+ threadSubject);
    filter.AddCondition("ReplyDateTime", QueryOperator.Between, startDate,
endDate);

    QueryOperationConfig config = new QueryOperationConfig()
{
    Limit = 2, // 2 items/page.
}

```

```

        Select = SelectValues.SpecificAttributes,
        AttributesToGet = new List<string> { "Message",
                                              "ReplyDateTime",
                                              "PostedBy" },
        ConsistentRead = true,
        Filter = filter
    };

    Search search = table.Query(config);

    List<Document> documentList = new List<Document>();

    do
    {
        documentList = search.GetNextSet();
        Console.WriteLine("\nFindRepliesPostedWithinTimePeriod: printing replies
posted within dates: {0} and {1} ....", startDate, endDate);
        foreach (var document in documentList)
        {
            PrintDocument(document);
        }
    } while (!search.IsDone);
}

private static void FindRepliesInLast15DaysWithConfig(Table table, string
forumName, string threadName)
{
    DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
    QueryFilter filter = new QueryFilter("Id", QueryOperator.Equal, forumName + "#"
+ threadName);
    filter.AddCondition("ReplyDateTime", QueryOperator.GreaterThan,
twoWeeksAgoDate);
    // You are specifying optional parameters so use QueryOperationConfig.
    QueryOperationConfig config = new QueryOperationConfig()
    {
        Filter = filter,
        // Optional parameters.
        Select = SelectValues.SpecificAttributes,
        AttributesToGet = new List<string> { "Message", "ReplyDateTime",
                                              "PostedBy" },
        ConsistentRead = true
    };

    Search search = table.Query(config);

    List<Document> documentSet = new List<Document>();
    do
    {
        documentSet = search.GetNextSet();
        Console.WriteLine("\nFindRepliesInLast15DaysWithConfig:
printing ....");
        foreach (var document in documentSet)
            PrintDocument(document);
    } while (!search.IsDone);
}

private static void PrintDocument(Document document)
{
    // count++;
    Console.WriteLine();
    foreach (var attribute in document.GetAttributeNames())
    {
        string stringValue = null;
        var value = document[attribute];
        if (value is Primitive)
            stringValue = value.AsPrimitive().Value.ToString();
    }
}

```

```
        else if (value is PrimitiveList)
            stringValue = string.Join(",", (from primitive
                in value.AsPrimitiveList().Entries
                select primitive.Value).ToArray());
        Console.WriteLine("{0} - {1}", attribute, stringValue);
    }
}
```

## Table.Scan method in the AWS SDK for .NET

The `Scan` method performs a full table scan. It provides two overloads. The only parameter required by the `Scan` method is the scan filter, which you can provide using the following overload.

## Example

```
Scan(ScanFilter filter);
```

For example, assume that you maintain a table of forum threads tracking information such as thread subject (primary), the related message, forum ID to which the thread belongs, Tags, and other information. Assume that the subject is the primary key.

## Example

```
Thread(Subject, Message, ForumId, Tags, LastPostedDateTime, .... )
```

This is a simplified version of forums and threads that you see on AWS forums (see [Discussion forums](#)). The following C# code example queries all threads in a specific forum (ForumId = 101) that are tagged "sortkey". Because the ForumId is not a primary key, the example scans the table. The ScanFilter includes two conditions. The query returns all the threads that satisfy both of the conditions.

## Example

```
string tableName = "Thread";
Table ThreadTable = Table.LoadTable(client, tableName);

ScanFilter scanFilter = new ScanFilter();
scanFilter.AddCondition("ForumId", ScanOperator.Equal, 101);
scanFilter.AddCondition("Tags", ScanOperator.Contains, "sortkey");

Search search = ThreadTable.Scan(scanFilter);
```

## Specifying optional parameters

You also can specify optional parameters to `Scan`, such as a specific list of attributes to retrieve or whether to perform a strongly consistent read. To specify optional parameters, you must create a `ScanOperationConfig` object that includes both the required and optional parameters and use the following overload.

## Example

```
Scan(ScanOperationConfig config);
```

The following C# code example runs the same preceding query (find forum threads in which the ForumId is 101 and the Tag attribute contains the "sortkey" keyword). Assume that you want to add an optional parameter to retrieve only a specific attribute list. In this case, you must create a ScanOperationConfig object by providing all the parameters, required and optional parameters, as shown in the following code example.

## Example

```

string tableName = "Thread";
Table ThreadTable = Table.LoadTable(client, tableName);

ScanFilter scanFilter = new ScanFilter();
scanFilter.AddCondition("ForumId", ScanOperator.Equal, forumId);
scanFilter.AddCondition("Tags", ScanOperator.Contains, "sortkey");

ScanOperationConfig config = new ScanOperationConfig()
{
    AttributesToGet = new List<string> { "Subject", "Message" } ,
    Filter = scanFilter
};

Search search = ThreadTable.Scan(config);

```

### Example: Scan using the Table.Scan method

The Scan operation performs a full table scan making it a potentially expensive operation. You should use queries instead. However, there are times when you might need to run a scan against a table. For example, you might have a data entry error in the product pricing, and you must scan the table as shown in the following C# code example. The example scans the ProductCatalog table to find products for which the price value is less than 0. The example illustrates the use of the two Table.Scan overloads.

- Table.Scan that takes the ScanFilter object as a parameter.

You can pass the ScanFilter parameter when passing in only the required parameters.

- Table.Scan that takes the ScanOperationConfig object as a parameter.

You must use the ScanOperationConfig parameter if you want to pass any optional parameters to the Scan method.

## Example

```


/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using System.Linq;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.DocumentModel;

namespace com.amazonaws.codesamples
{
    class MidLevelScanOnly
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();


```

```

static void Main(string[] args)
{
    Table productCatalogTable = Table.LoadTable(client, "ProductCatalog");
    // Scan example.
    FindProductsWithNegativePrice(productCatalogTable);
    FindProductsWithNegativePriceWithConfig(productCatalogTable);

    Console.WriteLine("To continue, press Enter");
    Console.ReadLine();
}

private static void FindProductsWithNegativePrice(Table productCatalogTable)
{
    // Assume there is a price error. So we scan to find items priced < 0.
    ScanFilter scanFilter = new ScanFilter();
    scanFilter.AddCondition("Price", ScanOperator.LessThan, 0);

    Search search = productCatalogTable.Scan(scanFilter);

    List<Document> documentList = new List<Document>();
    do
    {
        documentList = search.GetNextSet();
        Console.WriteLine("\nFindProductsWithNegativePrice:");
printing .....
        foreach (var document in documentList)
            PrintDocument(document);
    } while (!search.IsDone);
}

private static void FindProductsWithNegativePriceWithConfig(Table
productCatalogTable)
{
    // Assume there is a price error. So we scan to find items priced < 0.
    ScanFilter scanFilter = new ScanFilter();
    scanFilter.AddCondition("Price", ScanOperator.LessThan, 0);

    ScanOperationConfig config = new ScanOperationConfig()
    {
        Filter = scanFilter,
        Select = SelectValues.SpecificAttributes,
        AttributesToGet = new List<string> { "Title", "Id" }
    };

    Search search = productCatalogTable.Scan(config);

    List<Document> documentList = new List<Document>();
    do
    {
        documentList = search.GetNextSet();
        Console.WriteLine("\nFindProductsWithNegativePriceWithConfig:");
printing .....
        foreach (var document in documentList)
            PrintDocument(document);
    } while (!search.IsDone);
}

private static void PrintDocument(Document document)
{
    // count++;
    Console.WriteLine();
    foreach (var attribute in document.GetAttributeNames())
    {
        string stringValue = null;
        var value = document[attribute];
        if (value is Primitive)

```

```
        stringValue = value.AsPrimitive().Value.ToString();
    else if (value is PrimitiveList)
        stringValue = string.Join(", ", (from primitive
            in value.AsPrimitiveList().Entries
            select primitive.Value).ToArray());
        Console.WriteLine("{0} - {1}", attribute, stringValue);
    }
}
}
```

## .NET: Object persistence model

### Topics

- [DynamoDB attributes \(p. 241\)](#)
- [DynamoDBContext class \(p. 243\)](#)
- [Supported data types \(p. 248\)](#)
- [Optimistic locking using a version number with DynamoDB using the AWS SDK for .NET object persistence model \(p. 249\)](#)
- [Mapping arbitrary data with DynamoDB using the AWS SDK for .NET object persistence model \(p. 251\)](#)
- [Batch operations using the AWS SDK for .NET object persistence model \(p. 254\)](#)
- [Example: CRUD operations using the AWS SDK for .NET object persistence model \(p. 257\)](#)
- [Example: Batch write operation using the AWS SDK for .NET object persistence model \(p. 259\)](#)
- [Example: Query and scan in DynamoDB using the AWS SDK for .NET object persistence model \(p. 263\)](#)

The AWS SDK for .NET provides an object persistence model that enables you to map your client-side classes to Amazon DynamoDB tables. Each object instance then maps to an item in the corresponding tables. To save your client-side objects to the tables, the object persistence model provides the `DynamoDBContext` class, an entry point to DynamoDB. This class provides you a connection to DynamoDB and enables you to access tables, perform various CRUD operations, and run queries.

The object persistence model provides a set of attributes to map client-side classes to tables, and properties/fields to table attributes.

#### Note

The object persistence model does not provide an API to create, update, or delete tables. It provides only data operations. You can use only the AWS SDK for .NET low-level API to create, update, and delete tables. For more information, see [Working with DynamoDB tables in .NET \(p. 337\)](#).

The following example shows how the object persistence model works. It starts with the `ProductCatalog` table. It has `Id` as the primary key.

```
ProductCatalog(Id, ...)
```

Suppose that you have a `Book` class with `Title`, `ISBN`, and `Authors` properties. You can map the `Book` class to the `ProductCatalog` table by adding the attributes defined by the object persistence model, as shown in the following C# code example.

#### Example

```
[DynamoDBTable("ProductCatalog")]
public class Book
{
```

```
[DynamoDBHashKey]  
public int Id { get; set; }  
  
public string Title { get; set; }  
public int ISBN { get; set; }  
  
[DynamoDBProperty("Authors")]  
public List<string> BookAuthors { get; set; }  
  
[DynamoDBIgnore]  
public string CoverPage { get; set; }  
}
```

In the preceding example, the `DynamoDBTable` attribute maps the `Book` class to the `ProductCatalog` table.

The object persistence model supports both the explicit and default mapping between class properties and table attributes.

- **Explicit mapping**—To map a property to a primary key, you must use the `DynamoDBHashKey` and `DynamoDBRangeKey` object persistence model attributes. Additionally, for the nonprimary key attributes, if a property name in your class and the corresponding table attribute to which you want to map it are not the same, you must define the mapping by explicitly adding the `DynamoDBProperty` attribute.

In the preceding example, the `Id` property maps to the primary key with the same name, and the `BookAuthors` property maps to the `Authors` attribute in the `ProductCatalog` table.

- **Default mapping**—By default, the object persistence model maps the class properties to the attributes with the same name in the table.

In the preceding example, the properties `Title` and `ISBN` map to the attributes with the same name in the `ProductCatalog` table.

You don't have to map every single class property. You identify these properties by adding the `DynamoDBIgnore` attribute. When you save a `Book` instance to the table, the `DynamoDBContext` does not include the `CoverPage` property. It also does not return this property when you retrieve the book instance.

You can map properties of .NET primitive types such as `int` and `string`. You also can map any arbitrary data types as long as you provide an appropriate converter to map the arbitrary data to one of the DynamoDB types. To learn about mapping arbitrary types, see [Mapping arbitrary data with DynamoDB using the AWS SDK for .NET object persistence model \(p. 251\)](#).

The object persistence model supports optimistic locking. During an update operation, this ensures that you have the latest copy of the item you are about to update. For more information, see [Optimistic locking using a version number with DynamoDB using the AWS SDK for .NET object persistence model \(p. 249\)](#).

## DynamoDB attributes

This section describes the attributes that the object persistence model offers so that you can map your classes and properties to DynamoDB tables and attributes.

### Note

In the following attributes, only `DynamoDBTable` and `DynamoDBHashKey` are required.

### DynamoDBGlobalSecondaryIndexHashKey

Maps a class property to the partition key of a global secondary index. Use this attribute if you need to query a global secondary index.

## DynamoDBGlobalSecondaryIndexRangeKey

Maps a class property to the sort key of a global secondary index. Use this attribute if you need to `Query` a global secondary index and want to refine your results using the index sort key.

## DynamoDBHashKey

Maps a class property to the partition key of the table's primary key. The primary key attributes cannot be a collection type.

The following C# code example maps the `Book` class to the `ProductCatalog` table, and the `Id` property to the table's primary key partition key.

```
[DynamoDBTable("ProductCatalog")]
public class Book {
    [DynamoDBHashKey]
    public int Id { get; set; }

    // Additional properties go here.
}
```

## DynamoDBIgnore

Indicates that the associated property should be ignored. If you don't want to save any of your class properties, you can add this attribute to instruct `DynamoDBContext` not to include this property when saving objects to the table.

## DynamoDBLocalSecondaryIndexRangeKey

Maps a class property to the sort key of a local secondary index. Use this attribute if you need to `Query` a local secondary index and want to refine your results using the index sort key.

## DynamoDBProperty

Maps a class property to a table attribute. If the class property maps to a table attribute of the same name, you don't need to specify this attribute. However, if the names are not the same, you can use this tag to provide the mapping. In the following C# statement, the `DynamoDBProperty` maps the `BookAuthors` property to the `Authors` attribute in the table.

```
[DynamoDBProperty("Authors")]
public List<string> BookAuthors { get; set; }
```

`DynamoDBContext` uses this mapping information to create the `Authors` attribute when saving object data to the corresponding table.

## DynamoDBRenamable

Specifies an alternative name for a class property. This is useful if you are writing a custom converter for mapping arbitrary data to a DynamoDB table where the name of a class property is different from a table attribute.

## DynamoDBRangeKey

Maps a class property to the sort key of the table's primary key. If the table has a composite primary key (partition key and sort key), you must specify both the `DynamoDBHashKey` and `DynamoDBRangeKey` attributes in your class mapping.

For example, the sample table `Reply` has a primary key made of the `Id` partition key and `Replenishment` sort key. The following C# code example maps the `Reply` class to the `Reply` table. The class definition also indicates that two of its properties map to the primary key.

For more information about sample tables, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

```
[DynamoDBTable("Reply")]
public class Reply {
    [DynamoDBHashKey]
    public int ThreadId { get; set; }
    [DynamoDBRangeKey]
    public string Replenishment { get; set; }
    // Additional properties go here.
}
```

## DynamoDBTable

Identifies the target table in DynamoDB to which the class maps. For example, the following C# code example maps the `Developer` class to the `People` table in DynamoDB.

```
[DynamoDBTable("People")]
public class Developer { ... }
```

This attribute can be inherited or overridden.

- The `DynamoDBTable` attribute can be inherited. In the preceding example, if you add a new class, `Lead`, that inherits from the `Developer` class, it also maps to the `People` table. Both the `Developer` and `Lead` objects are stored in the `People` table.
- The `DynamoDBTable` attribute can also be overridden. In the following C# code example, the `Manager` class inherits from the `Developer` class. However, the explicit addition of the `DynamoDBTable` attribute maps the class to another table (`Managers`).

```
[DynamoDBTable("Managers")]
public class Manager : Developer { ... }
```

You can add the optional parameter, `LowerCaseProperties`, to request DynamoDB to make the first letter of the property name lowercase when storing the objects to a table, as shown in the following C# example.

```
[DynamoDBTable("People", LowerCaseProperties=true)]
public class Developer {
    string DeveloperName;
    ...
}
```

When saving instances of the `Developer` class, `DynamoDBContext` saves the `DeveloperName` property as the `developerName`.

## DynamoDBVersion

Identifies a class property for storing the item version number. For more information about versioning, see [Optimistic locking using a version number with DynamoDB using the AWS SDK for .NET object persistence model \(p. 249\)](#).

## DynamoDBContext class

The `DynamoDBContext` class is the entry point to the Amazon DynamoDB database. It provides a connection to DynamoDB and enables you to access your data in various tables, perform various CRUD operations, and run queries. The `DynamoDBContext` class provides the following methods.

## CreateMultiTableBatchGet

Creates a `MultiTableBatchGet` object, composed of multiple individual `BatchGet` objects. Each of these `BatchGet` objects can be used for retrieving items from a single DynamoDB table.

To retrieve the items from tables, use the `ExecuteBatchGet` method, passing the `MultiTableBatchGet` object as a parameter.

## CreateMultiTableBatchWrite

Creates a `MultiTableBatchWrite` object, composed of multiple individual `BatchWrite` objects. Each of these `BatchWrite` objects can be used for writing or deleting items in a single DynamoDB table.

To write to tables, use the `ExecuteBatchWrite` method, passing the `MultiTableBatchWrite` object as a parameter.

## Createbatchget

Creates a `BatchGet` object that you can use to retrieve multiple items from a table. For more information, see [Batch get: Getting multiple items \(p. 256\)](#).

## Createbatchwrite

Creates a `BatchWrite` object that you can use to put multiple items into a table, or to delete multiple items from a table. For more information, see [Batch write: Putting and deleting multiple items \(p. 254\)](#).

## Delete

Deletes an item from the table. The method requires the primary key of the item you want to delete. You can provide either the primary key value or a client-side object containing a primary key value as a parameter to this method.

- If you specify a client-side object as a parameter and you have enabled optimistic locking, the delete succeeds only if the client-side and the server-side versions of the object match.
- If you specify only the primary key value as a parameter, the delete succeeds regardless of whether you have enabled optimistic locking or not.

### Note

To perform this operation in the background, use the `DeleteAsync` method instead.

## Dispose

Disposes of all managed and unmanaged resources.

## Executebatchget

Reads data from one or more tables, processing all of the `BatchGet` objects in a `MultiTableBatchGet`.

### Note

To perform this operation in the background, use the `ExecuteBatchGetAsync` method instead.

## Executebatchwrite

Writes or deletes data in one or more tables, processing all of the `BatchWrite` objects in a `MultiTableBatchWrite`.

**Note**

To perform this operation in the background, use the `ExecuteBatchWriteAsync` method instead.

## FromDocument

Given an instance of a `Document`, the `FromDocument` method returns an instance of a client-side class.

This is helpful if you want to use the document model classes along with the object persistence model to perform any data operations. For more information about the document model classes provided by the AWS SDK for .NET, see [.NET: Document model \(p. 217\)](#).

Suppose that you have a `Document` object named `doc`, that contains a representation of a `Forum` item. (To see how to construct this object, see the description for the `ToDocument` method later in this topic.) You can use `FromDocument` to retrieve the `Forum` item from the `Document`, as shown in the following C# code example.

### Example

```
forum101 = context.FromDocument<Forum>(101);
```

**Note**

If your `Document` object implements the `IEnumerable` interface, you can use the `FromDocuments` method instead. This allows you to iterate over all of the class instances in the `Document`.

## FromQuery

Runs a `Query` operation, with the query parameters defined in a `QueryOperationConfig` object.

**Note**

To perform this operation in the background, use the `FromQueryAsync` method instead.

## FromScan

Runs a `Scan` operation, with the scan parameters defined in a `ScanOperationConfig` object.

**Note**

To perform this operation in the background, use the `FromScanAsync` method instead.

## Gettargetable

Retrieves the target table for the specified type. This is useful if you are writing a custom converter for mapping arbitrary data to a DynamoDB table, and you need to determine which table is associated with a custom data type.

## Load

Retrieves an item from a table. The method requires only the primary key of the item you want to retrieve.

By default, DynamoDB returns the item with values that are eventually consistent. For information about the eventual consistency model, see [Read consistency \(p. 17\)](#).

**Note**

To perform this operation in the background, use the `LoadAsync` method instead.

## Query

Queries a table based on query parameters you provide.

You can query a table only if it has a composite primary key (partition key and sort key). When querying, you must specify a partition key and a condition that applies to the sort key.

Suppose that you have a client-side `Reply` class mapped to the `Reply` table in DynamoDB. The following C# code example queries the `Reply` table to find forum thread replies posted in the past 15 days. The `Reply` table has a primary key that has the `Id` partition key and the `ReplyDateTime` sort key. For more information about the `Reply` table, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

### Example

```
DynamoDBContext context = new DynamoDBContext(client);

string replyId = "DynamoDB#DynamoDB Thread 1"; //Partition key
DateTime twoWeeksAgoDate = DateTime.UtcNow.Subtract(new TimeSpan(14, 0, 0, 0)); // Date to
// compare.
IEnumerable<Reply> latestReplies = context.Query<Reply>(replyId, QueryOperator.GreaterThan,
twoWeeksAgoDate);
```

This returns a collection of `Reply` objects.

The `Query` method returns a "lazy-loaded" `IEnumerable` collection. It initially returns only one page of results, and then makes a service call for the next page if needed. To obtain all the matching items, you need to iterate only over the `IEnumerable`.

If your table has a simple primary key (partition key), you can't use the `Query` method. Instead, you can use the `Load` method and provide the partition key to retrieve the item.

#### Note

To perform this operation in the background, use the `QueryAsync` method instead.

## Save

Saves the specified object to the table. If the primary key specified in the input object doesn't exist in the table, the method adds a new item to the table. If the primary key exists, the method updates the existing item.

If you have optimistic locking configured, the update succeeds only if the client and the server-side versions of the item match. For more information, see [Optimistic locking using a version number with DynamoDB using the AWS SDK for .NET object persistence model \(p. 249\)](#).

#### Note

To perform this operation in the background, use the `SaveAsync` method instead.

## Scan

Performs an entire table scan.

You can filter scan results by specifying a scan condition. The condition can be evaluated on any attributes in the table. Suppose that you have a client-side class `Book` mapped to the `ProductCatalog` table in DynamoDB. The following C# example scans the table and returns only the book items priced less than 0.

### Example

```
IEnumerable<Book> itemsWithWrongPrice = context.Scan<Book>()
```

```
        new ScanCondition("Price", ScanOperator.LessThan, price),
        new ScanCondition("ProductCategory", ScanOperator.Equal, "Book")
    );
```

The `Scan` method returns a "lazy-loaded" `IEnumerable` collection. It initially returns only one page of results, and then makes a service call for the next page if needed. To obtain all the matching items, you only need to iterate over the `IEnumerable`.

For performance reasons, you should query your tables and avoid a table scan.

**Note**

To perform this operation in the background, use the `ScanAsync` method instead.

## ToDocument

Returns an instance of the `Document` document model class from your class instance.

This is helpful if you want to use the document model classes along with the object persistence model to perform any data operations. For more information about the document model classes provided by the AWS SDK for .NET, see [.NET: Document model \(p. 217\)](#).

Suppose that you have a client-side class mapped to the sample `Forum` table. You can then use a `DynamoDBContext` to get an item as a `Document` object from the `Forum` table, as shown in the following C# code example.

### Example

```
DynamoDBContext context = new DynamoDBContext(client);

Forum forum101 = context.Load<Forum>(101); // Retrieve a forum by primary key.
Document doc = context.ToDocument<Forum>(forum101);
```

## Specifying optional parameters for `DynamoDBContext`

When using the object persistence model, you can specify the following optional parameters for the `DynamoDBContext`.

- **ConsistentRead**—When retrieving data using the `Load`, `Query`, or `Scan` operations, you can add this optional parameter to request the latest values for the data.
- **IgnoreNullValues**—This parameter informs `DynamoDBContext` to ignore null values on attributes during a `Save` operation. If this parameter is false (or if it is not set), then a null value is interpreted as a directive to delete the specific attribute.
- **SkipVersionCheck**— This parameter informs `DynamoDBContext` not to compare versions when saving or deleting an item. For more information about versioning, see [Optimistic locking using a version number with DynamoDB using the AWS SDK for .NET object persistence model \(p. 249\)](#).
- **TableNamePrefix**— Prefixes all table names with a specific string. If this parameter is null (or if it is not set), then no prefix is used.

The following C# example creates a new `DynamoDBContext` by specifying two of the preceding optional parameters.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
...
DynamoDBContext context =
```

```
new DynamoDBContext(client, new DynamoDBContextConfig { ConsistentRead = true,
SkipVersionCheck = true});
```

DynamoDBContext includes these optional parameters with each request that you send using this context.

Instead of setting these parameters at the DynamoDBContext level, you can specify them for individual operations you run using DynamoDBContext, as shown in the following C# code example. The example loads a specific book item. The Load method of DynamoDBContext specifies the preceding optional parameters.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
...
DynamoDBContext context = new DynamoDBContext(client);
Book bookItem = context.Load<Book>(productId, new DynamoDBContextConfig{ ConsistentRead =
true, SkipVersionCheck = true });
```

In this case, DynamoDBContext includes these parameters only when sending the Get request.

## Supported data types

The object persistence model supports a set of primitive .NET data types, collections, and arbitrary data types. The model supports the following primitive data types.

- bool
- byte
- char
- DateTime
- decimal
- double
- float
- Int16
- Int32
- Int64
- SByte
- string
- UInt16
- UInt32
- UInt64

The object persistence model also supports the .NET collection types. DynamoDBContext is able to convert concrete collection types and simple Plain Old CLR Objects (POCOs).

The following table summarizes the mapping of the preceding .NET types to the DynamoDB types.

.NET primitive type	DynamoDB type
All number types	N (number type)
All string types	S (string type)

.NET primitive type	DynamoDB type
MemoryStream, byte[]	B (binary type)
bool	N (number type). 0 represents false and 1 represents true.
Collection types	BS (binary set) type, SS (string set) type, and NS (number set) type
DateTime	S (string type). The DateTime values are stored as ISO-8601 formatted strings.

The object persistence model also supports arbitrary data types. However, you must provide converter code to map the complex types to the DynamoDB types.

#### Note

- Empty binary values are supported.
- Reading of empty string values is supported. Empty string attribute values are supported within attribute values of string Set type while writing to DynamoDB. Empty string attribute values of string type and empty string values contained within List or Map type are dropped from write requests

## Optimistic locking using a version number with DynamoDB using the AWS SDK for .NET object persistence model

Optimistic locking support in the object persistence model ensures that the item version for your application is the same as the item version on the server side before updating or deleting the item. Suppose that you retrieve an item for update. However, before you send your updates back, some other application updates the same item. Now your application has a stale copy of the item. Without optimistic locking, any update you perform will overwrite the update made by the other application.

The optimistic locking feature of the object persistence model provides the `DynamoDBVersion` tag that you can use to enable optimistic locking. To use this feature, you add a property to your class for storing the version number. You add the `DynamoDBVersion` attribute to the property. When you first save the object, the `DynamoDBContext` assigns a version number and increments this value each time you update the item.

Your update or delete request succeeds only if the client-side object version matches the corresponding version number of the item on the server side. If your application has a stale copy, it must get the latest version from the server before it can update or delete that item.

The following C# code example defines a `Book` class with object persistence attributes mapping it to the `ProductCatalog` table. The `VersionNumber` property in the class decorated with the `DynamoDBVersion` attribute stores the version number value.

#### Example

```
[DynamoDBTable("ProductCatalog")]
public class Book
{
    [DynamoDBHashKey] //Partition key
    public int Id { get; set; }
    [DynamoDBProperty]
    public string Title { get; set; }
```

```
[DynamoDBProperty]
public string ISBN { get; set; }
[DynamoDBProperty("Authors")]
public List<string> BookAuthors { get; set; }
[DynamoDBVersion]
public int? VersionNumber { get; set; }
}
```

#### Note

You can apply the `DynamoDBVersion` attribute only to a nullable numeric primitive type (such as `int?`).

Optimistic locking has the following impact on `DynamoDBContext` operations:

- For a new item, `DynamoDBContext` assigns initial version number 0. If you retrieve an existing item, update one or more of its properties, and try to save the changes, the save operation succeeds only if the version number on the client side and the server side match. `DynamoDBContext` increments the version number. You don't need to set the version number.
- The `Delete` method provides overloads that can take either a primary key value or an object as parameter, as shown in the following C# code example.

#### Example

```
DynamoDBContext context = new DynamoDBContext(client);
...
// Load a book.
Book book = context.Load<ProductCatalog>(111);
// Do other operations.
// Delete 1 - Pass in the book object.
context.Delete<ProductCatalog>(book);

// Delete 2 - Pass in the Id (primary key)
context.Delete<ProductCatalog>(222);
```

If you provide an object as the parameter, the delete succeeds only if the object version matches the corresponding server-side item version. However, if you provide a primary key value as the parameter, `DynamoDBContext` is unaware of any version numbers, and it deletes the item without making the version check.

Note that the internal implementation of optimistic locking in the object persistence model code uses the conditional update and the conditional delete API actions in DynamoDB.

## Disabling optimistic locking

To disable optimistic locking, you use the `SkipVersionCheck` configuration property. You can set this property when creating `DynamoDBContext`. In this case, optimistic locking is disabled for any requests that you make using the context. For more information, see [Specifying optional parameters for DynamoDBContext \(p. 247\)](#).

Instead of setting the property at the context level, you can disable optimistic locking for a specific operation, as shown in the following C# code example. The example uses the context to delete a book item. The `Delete` method sets the optional `SkipVersionCheck` property to true, disabling version checking.

#### Example

```
DynamoDBContext context = new DynamoDBContext(client);
```

```
// Load a book.  
Book book = context.Load<ProductCatalog>(111);  
...  
// Delete the book.  
context.Delete<Book>(book, new DynamoDBContextConfig { SkipVersionCheck = true });
```

## Mapping arbitrary data with DynamoDB using the AWS SDK for .NET object persistence model

In addition to the supported .NET types (see [Supported data types \(p. 248\)](#)), you can use types in your application for which there is no direct mapping to the Amazon DynamoDB types. The object persistence model supports storing data of arbitrary types as long as you provide the converter to convert data from the arbitrary type to the DynamoDB type and vice versa. The converter code transforms data during both the saving and loading of the objects.

You can create any types on the client-side. However the data stored in the tables is one of the DynamoDB types, and during query and scan, any data comparisons made are against the data stored in DynamoDB.

The following C# code example defines a Book class with `Id`, `Title`, `ISBN`, and `Dimension` properties. The `Dimension` property is of the `DimensionType` that describes `Height`, `Width`, and `Thickness` properties. The example code provides the converter methods `ToEntry` and `FromEntry` to convert data between the `DimensionType` and the DynamoDB string types. For example, when saving a Book instance, the converter creates a book `Dimension` string such as "8.5x11x.05". When you retrieve a book, it converts the string to a `DimensionType` instance.

The example maps the `Book` type to the `ProductCatalog` table. It saves a sample `Book` instance, retrieves it, updates its dimensions, and saves the updated `Book` again.

For step-by-step instructions for testing the following example, see [.NET code examples \(p. 276\)](#).

### Example

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
using System;  
using System.Collections.Generic;  
using Amazon.DynamoDBv2;  
using Amazon.DynamoDBv2.DataModel;  
using Amazon.DynamoDBv2.DocumentModel;  
using Amazon.Runtime;  
using Amazon.SecurityToken;  
  
namespace com.amazonaws.codesamples  
{  
    class HighLevelMappingArbitraryData
```

```

{
    private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

    static void Main(string[] args)
    {
        try
        {
            DynamoDBContext context = new DynamoDBContext(client);

            // 1. Create a book.
            DimensionType myBookDimensions = new DimensionType()
            {
                Length = 8M,
                Height = 11M,
                Thickness = 0.5M
            };

            Book myBook = new Book
            {
                Id = 501,
                Title = "AWS SDK for .NET Object Persistence Model Handling Arbitrary
Data",
                ISBN = "999-9999999999",
                BookAuthors = new List<string> { "Author 1", "Author 2" },
                Dimensions = myBookDimensions
            };

            context.Save(myBook);

            // 2. Retrieve the book.
            Book bookRetrieved = context.Load<Book>(501);

            // 3. Update property (book dimensions).
            bookRetrieved.Dimensions.Height += 1;
            bookRetrieved.Dimensions.Length += 1;
            bookRetrieved.Dimensions.Thickness += 0.2M;
            // Update the book.
            context.Save(bookRetrieved);

            Console.WriteLine("To continue, press Enter");
            Console.ReadLine();
        }
        catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
        catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
        catch (Exception e) { Console.WriteLine(e.Message); }
    }
}

[DynamoDBTable("ProductCatalog")]
public class Book
{
    [DynamoDBHashKey] //Partition key
    public int Id
    {
        get; set;
    }
    [DynamoDBProperty]
    public string Title
    {
        get; set;
    }
    [DynamoDBProperty]
    public string ISBN
    {
        get; set;
    }
    // Multi-valued (set type) attribute.
}

```

```

[DynamoDBProperty("Authors")]
public List<string> BookAuthors
{
    get; set;
}
// Arbitrary type, with a converter to map it to DynamoDB type.
[DynamoDBProperty(typeof(DimensionTypeConverter))]
public DimensionType Dimensions
{
    get; set;
}

public class DimensionType
{
    public decimal Length
    {
        get; set;
    }
    public decimal Height
    {
        get; set;
    }
    public decimal Thickness
    {
        get; set;
    }
}

// Converts the complex type DimensionType to string and vice-versa.
public class DimensionTypeConverter : IPropertyConverter
{
    public DynamoDBEntry ToEntry(object value)
    {
        DimensionType bookDimensions = value as DimensionType;
        if (bookDimensions == null) throw new ArgumentOutOfRangeException();

        string data = string.Format("{1}{0}{2}{0}{3}", " x ",
                                     bookDimensions.Length, bookDimensions.Height,
                                     bookDimensions.Thickness);

        DynamoDBEntry entry = new Primitive
        {
            Value = data
        };
        return entry;
    }

    public object FromEntry(DynamoDBEntry entry)
    {
        Primitive primitive = entry as Primitive;
        if (primitive == null || !(primitive.Value is String) ||
string.IsNullOrEmpty((string)primitive.Value))
            throw new ArgumentOutOfRangeException();

        string[] data = ((string)(primitive.Value)).Split(new string[] { " x " },
StringSplitOptions.None);
        if (data.Length != 3) throw new ArgumentOutOfRangeException();

        DimensionType complexData = new DimensionType
        {
            Length = Convert.ToDecimal(data[0]),
            Height = Convert.ToDecimal(data[1]),
            Thickness = Convert.ToDecimal(data[2])
        };
        return complexData;
    }
}

```

```
    }
}
```

## Batch operations using the AWS SDK for .NET object persistence model

### Batch write: Putting and deleting multiple items

To put or delete multiple objects from a table in a single request, do the following:

- Run the `CreateBatchWrite` method of the `DynamoDBContext`, and create an instance of the `BatchWrite` class.
- Specify the items that you want to put or delete.
  - To put one or more items, use either the `AddPutItem` or the `AddPutItems` method.
  - To delete one or more items, you can specify either the primary key of the item or a client-side object that maps to the item that you want to delete. Use the `AddDeleteItem`, `AddDeleteItems`, and the `AddDeleteKey` methods to specify the list of items to delete.
- Call the `BatchWrite.Execute` method to put and delete all the specified items from the table.

#### Note

When using the object persistence model, you can specify any number of operations in a batch. However, note that Amazon DynamoDB limits the number of operations in a batch and the total size of the batch in a batch operation. For more information about the specific limits, see [BatchWriteItem](#). If the API detects that your batch write request exceeded the allowed number of write requests or exceeded the maximum allowed HTTP payload size, it breaks the batch into several smaller batches. Additionally, if a response to a batch write returns unprocessed items, the API automatically sends another batch request with those unprocessed items.

Suppose that you defined a C# class `Book` class that maps to the `ProductCatalog` table in DynamoDB. The following C# code example uses the `BatchWrite` object to upload two items and delete one item from the `ProductCatalog` table.

#### Example

```
DynamoDBContext context = new DynamoDBContext(client);
var bookBatch = context.CreateBatchWrite<Book>();

// 1. Specify two books to add.
Book book1 = new Book
{
    Id = 902,
    ISBN = "902-11-11-1111",
    ProductCategory = "Book",
    Title = "My book3 in batch write"
};
Book book2 = new Book
{
    Id = 903,
    ISBN = "903-11-11-1111",
    ProductCategory = "Book",
    Title = "My book4 in batch write"
};

bookBatch.AddPutItems(new List<Book> { book1, book2 });

bookBatch.DeleteItem("901-11-11-1111");
```

```
// 2. Specify one book to delete.  
bookBatch.AddDeleteKey(111);  
  
bookBatch.Execute();
```

To put or delete objects from multiple tables, do the following:

- Create one instance of the `BatchWrite` class for each type and specify the items you want to put or delete as described in the preceding section.
- Create an instance of `MultiTableBatchWrite` using one of the following methods:
  - Run the `Combine` method on one of the `BatchWrite` objects that you created in the preceding step.
  - Create an instance of the `MultiTableBatchWrite` type by providing a list of `BatchWrite` objects.
  - Run the `CreateMultiTableBatchWrite` method of `DynamoDBContext` and pass in your list of `BatchWrite` objects.
- Call the `Execute` method of `MultiTableBatchWrite`, which performs the specified put and delete operations on various tables.

Suppose that you defined `Forum` and `Thread` C# classes that map to the `Forum` and `Thread` tables in DynamoDB. Also, suppose that the `Thread` class has versioning enabled. Because versioning is not supported when using batch operations, you must explicitly disable versioning as shown in the following C# code example. The example uses the `MultiTableBatchWrite` object to perform a multi-table update.

### Example

```
DynamoDBContext context = new DynamoDBContext(client);  
// Create BatchWrite objects for each of the Forum and Thread classes.  
var forumBatch = context.CreateBatchWrite<Forum>();  
  
DynamoDBOperationConfig config = new DynamoDBOperationConfig();  
config.SkipVersionCheck = true;  
var threadBatch = context.CreateBatchWrite<Thread>(config);  
  
// 1. New Forum item.  
Forum newForum = new Forum  
{  
    Name = "Test BatchWrite Forum",  
    Threads = 0  
};  
forumBatch.AddPutItem(newForum);  
  
// 2. Specify a forum to delete by specifying its primary key.  
forumBatch.AddDeleteKey("Some forum");  
  
// 3. New Thread item.  
Thread newThread = new Thread  
{  
    ForumName = "Amazon S3 forum",  
    Subject = "My sample question",  
    KeywordTags = new List<string> { "Amazon S3", "Bucket" },  
    Message = "Message text"  
};  
  
threadBatch.AddPutItem(newThread);  
  
// Now run multi-table batch write.  
var superBatch = new MultiTableBatchWrite(forumBatch, threadBatch);
```

```
superBatch.Execute();
```

For a working example, see [Example: Batch write operation using the AWS SDK for .NET object persistence model \(p. 259\)](#).

#### Note

The DynamoDB batch API limits the number of writes in a batch and also limits the size of the batch. For more information, see [BatchWriteItem](#). When using the .NET object persistence model API, you can specify any number of operations. However, if either the number of operations in a batch or the size exceeds the limit, the .NET API breaks the batch write request into smaller batches and sends multiple batch write requests to DynamoDB.

## Batch get: Getting multiple items

To retrieve multiple items from a table in a single request, do the following:

- Create an instance of the `CreateBatchGet` class.
- Specify a list of primary keys to retrieve.
- Call the `Execute` method. The response returns the items in the `Results` property.

The following C# code example retrieves three items from the `ProductCatalog` table. The items in the result are not necessarily in the same order in which you specified the primary keys.

#### Example

```
DynamoDBContext context = new DynamoDBContext(client);
var bookBatch = context.CreateBatchGet<ProductCatalog>();
bookBatch.AddKey(101);
bookBatch.AddKey(102);
bookBatch.AddKey(103);
bookBatch.Execute();
// Process result.
Console.WriteLine(bookBatch.Results.Count);
Book book1 = bookBatch.Results[0];
Book book2 = bookBatch.Results[1];
Book book3 = bookBatch.Results[2];
```

To retrieve objects from multiple tables, do the following:

- For each type, create an instance of the `CreateBatchGet` type and provide the primary key values you want to retrieve from each table.
- Create an instance of the `MultiTableBatchGet` class using one of the following methods:
  - Run the `Combine` method on one of the `BatchGet` objects you created in the preceding step.
  - Create an instance of the `MultiBatchGet` type by providing a list of `BatchGet` objects.
  - Run the `CreateMultiTableBatchGet` method of `DynamoDBContext` and pass in your list of `BatchGet` objects.
- Call the `Execute` method of `MultiTableBatchGet`, which returns the typed results in the individual `BatchGet` objects.

The following C# code example retrieves multiple items from the `Order` and `OrderDetail` tables using the `CreateBatchGet` method.

#### Example

```
var orderBatch = context.CreateBatchGet<Order>();
```

```
orderBatch.AddKey(101);
orderBatch.AddKey(102);

var orderDetailBatch = context.CreateBatchGet<OrderDetail>();
orderDetailBatch.AddKey(101, "P1");
orderDetailBatch.AddKey(101, "P2");
orderDetailBatch.AddKey(102, "P3");
orderDetailBatch.AddKey(102, "P1");

var orderAndDetailSuperBatch = orderBatch.Combine(orderDetailBatch);
orderAndDetailSuperBatch.Execute();

Console.WriteLine(orderBatch.Results.Count);
Console.WriteLine(orderDetailBatch.Results.Count);

Order order1 = orderBatch.Results[0];
Order order2 = orderDetailBatch.Results[1];
OrderDetail orderDetail1 = orderDetailBatch.Results[0];
```

## Example: CRUD operations using the AWS SDK for .NET object persistence model

The following C# code example declares a `Book` class with `Id`, `Title`, `ISBN`, and `Authors` properties. The example uses object persistence attributes to map these properties to the `ProductCatalog` table in Amazon DynamoDB. The example then uses the `DynamoDBContext` to illustrate typical create, read, update, and delete (CRUD) operations. The example creates a sample `Book` instance and saves it to the `ProductCatalog` table. It then retrieves the book item and updates its `ISBN` and `Authors` properties. Note that the update replaces the existing authors list. Finally, the example deletes the book item.

For more information about the `ProductCatalog` table used in this example, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#). For step-by-step instructions to test the following example, see [.NET code examples \(p. 276\)](#).

### Note

The following example doesn't work with .NET core because it doesn't support synchronous methods. For more information, see [AWS asynchronous APIs for .NET](#).

### Example

```
/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.DataModel;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
```

```

class HighLevelItemCRUD
{
    private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

    static void Main(string[] args)
    {
        try
        {
            DynamoDBContext context = new DynamoDBContext(client);
            TestCRUDOperations(context);
            Console.WriteLine("To continue, press Enter");
            Console.ReadLine();
        }
        catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
        catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
        catch (Exception e) { Console.WriteLine(e.Message); }
    }

    private static void TestCRUDOperations(DynamoDBContext context)
    {
        int bookID = 1001; // Some unique value.
        Book myBook = new Book
        {
            Id = bookID,
            Title = "object persistence-AWS SDK for.NET SDK-Book 1001",
            ISBN = "111-111111001",
            BookAuthors = new List<string> { "Author 1", "Author 2" },
        };

        // Save the book.
        context.Save(myBook);
        // Retrieve the book.
        Book bookRetrieved = context.Load<Book>(bookID);

        // Update few properties.
        bookRetrieved.ISBN = "222-2222221001";
        bookRetrieved.BookAuthors = new List<string> { " Author 1", "Author x" }; // Replace existing authors list with this.
        context.Save(bookRetrieved);

        // Retrieve the updated book. This time add the optional ConsistentRead parameter using DynamoDBContextConfig object.
        Book updatedBook = context.Load<Book>(bookID, new DynamoDBContextConfig
        {
            ConsistentRead = true
        });

        // Delete the book.
        context.Delete<Book>(bookID);
        // Try to retrieve deleted book. It should return null.
        Book deletedBook = context.Load<Book>(bookID, new DynamoDBContextConfig
        {
            ConsistentRead = true
        });
        if (deletedBook == null)
            Console.WriteLine("Book is deleted");
    }

    [DynamoDBTable("ProductCatalog")]
    public class Book
    {
        [DynamoDBHashKey] //Partition key
        public int Id
        {
            get; set;
        }
    }
}

```

```

        }
        [DynamoDBProperty]
        public string Title
        {
            get; set;
        }
        [DynamoDBProperty]
        public string ISBN
        {
            get; set;
        }
        [DynamoDBProperty("Authors")] //String Set datatype
        public List<string> BookAuthors
        {
            get; set;
        }
    }
}

```

## Example: Batch write operation using the AWS SDK for .NET object persistence model

The following C# code example declares `Book`, `Forum`, `Thread`, and `Reply` classes and maps them to Amazon DynamoDB tables using the object persistence model attributes.

The example then uses the `DynamoDBContext` to illustrate the following batch write operations:

- `BatchWrite` object to put and delete book items from the `ProductCatalog` table.
- `MultiTableBatchWrite` object to put and delete items from the `Forum` and the `Thread` tables.

For more information about the tables used in this example, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#). For step-by-step instructions to test the following example, see [.NET code examples \(p. 276\)](#).

**Note**

The following example doesn't work with .NET core because it doesn't support synchronous methods. For more information, see [AWS asynchronous APIs for .NET](#).

### Example

```


/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.DataModel;
using Amazon.Runtime;
using Amazon.SecurityToken;


```

```

namespace com.amazonaws.codesamples
{
    class HighLevelBatchWriteItem
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
        {
            try
            {
                DynamoDBContext context = new DynamoDBContext(client);
                SingleTableBatchWrite(context);
                MultiTableBatchWrite(context);
            }
            catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
            catch (Exception e) { Console.WriteLine(e.Message); }

            Console.WriteLine("To continue, press Enter");
            Console.ReadLine();
        }

        private static void SingleTableBatchWrite(DynamoDBContext context)
        {
            Book book1 = new Book
            {
                Id = 902,
                InPublication = true,
                ISBN = "902-11-11-1111",
                PageCount = "100",
                Price = 10,
                ProductCategory = "Book",
                Title = "My book3 in batch write"
            };
            Book book2 = new Book
            {
                Id = 903,
                InPublication = true,
                ISBN = "903-11-11-1111",
                PageCount = "200",
                Price = 10,
                ProductCategory = "Book",
                Title = "My book4 in batch write"
            };

            var bookBatch = context.CreateBatchWrite<Book>();
            bookBatch.AddPutItems(new List<Book> { book1, book2 });

            Console.WriteLine("Performing batch write in SingleTableBatchWrite()");
            bookBatch.Execute();
        }

        private static void MultiTableBatchWrite(DynamoDBContext context)
        {
            // 1. New Forum item.
            Forum newForum = new Forum
            {
                Name = "Test BatchWrite Forum",
                Threads = 0
            };
            var forumBatch = context.CreateBatchWrite<Forum>();
            forumBatch.AddPutItem(newForum);

            // 2. New Thread item.
            Thread newThread = new Thread
            {

```

```

        ForumName = "S3 forum",
        Subject = "My sample question",
        KeywordTags = new List<string> { "S3", "Bucket" },
        Message = "Message text"
    };

    DynamoDBOperationConfig config = new DynamoDBOperationConfig();
    config.SkipVersionCheck = true;
    var threadBatch = context.CreateBatchWrite<Thread>(config);
    threadBatch.AddPutItem(newThread);
    threadBatch.AddDeleteKey("some partition key value", "some sort key value");

    var superBatch = new MultiTableBatchWrite(forumBatch, threadBatch);
    Console.WriteLine("Performing batch write in MultiTableBatchWrite().");
    superBatch.Execute();
}
}

[DynamoDBTable("Reply")]
public class Reply
{
    [DynamoDBHashKey] //Partition key
    public string Id
    {
        get; set;
    }

    [DynamoDBRangeKey] //Sort key
    public DateTime ReplyDateTime
    {
        get; set;
    }

    // Properties included implicitly.
    public string Message
    {
        get; set;
    }
    // Explicit property mapping with object persistence model attributes.
    [DynamoDBProperty("LastPostedBy")]
    public string PostedBy
    {
        get; set;
    }
    // Property to store version number for optimistic locking.
    [DynamoDBVersion]
    public int? Version
    {
        get; set;
    }
}

[DynamoDBTable("Thread")]
public class Thread
{
    // PK mapping.
    [DynamoDBHashKey]      //Partition key
    public string ForumName
    {
        get; set;
    }
    [DynamoDBRangeKey]      //Sort key
    public String Subject
    {
        get; set;
    }
}

```

```

// Implicit mapping.
public string Message
{
    get; set;
}
public string LastPostedBy
{
    get; set;
}
public int Views
{
    get; set;
}
public int Replies
{
    get; set;
}
public bool Answered
{
    get; set;
}
public DateTime LastPostedDateTime
{
    get; set;
}
// Explicit mapping (property and table attribute names are different.
[DynamoDBProperty("Tags")]
public List<string> KeywordTags
{
    get; set;
}
// Property to store version number for optimistic locking.
[DynamoDBVersion]
public int? Version
{
    get; set;
}

[DynamoDBTable("Forum")]
public class Forum
{
    [DynamoDBHashKey]          //Partition key
    public string Name
    {
        get; set;
    }
    // All the following properties are explicitly mapped,
    // only to show how to provide mapping.
    [DynamoDBProperty]
    public int Threads
    {
        get; set;
    }
    [DynamoDBProperty]
    public int Views
    {
        get; set;
    }
    [DynamoDBProperty]
    public string LastPostBy
    {
        get; set;
    }
    [DynamoDBProperty]
    public DateTime LastPostDateTime

```

```
        {
            get; set;
        }
        [DynamoDBProperty]
        public int Messages
        {
            get; set;
        }
    }

[DynamoDBTable("ProductCatalog")]
public class Book
{
    [DynamoDBHashKey] //Partition key
    public int Id
    {
        get; set;
    }
    public string Title
    {
        get; set;
    }
    public string ISBN
    {
        get; set;
    }
    public int Price
    {
        get; set;
    }
    public string PageCount
    {
        get; set;
    }
    public string ProductCategory
    {
        get; set;
    }
    public bool InPublication
    {
        get; set;
    }
}
```

## Example: Query and scan in DynamoDB using the AWS SDK for .NET object persistence model

The C# example in this section defines the following classes and maps them to the tables in DynamoDB. For more information about creating the tables used in this example, see [Creating tables and loading data for code examples in DynamoDB](#) (p. 269).

- The Book class maps to the ProductCatalog table.
  - The Forum, Thread, and Reply classes map to tables of the same name.

The example then runs the following query and scan operations using `DynamoDBContext`.

- Get a book by Id.

The `ProductCatalog` table has `Id` as its primary key. It does not have a sort key as part of its primary key. Therefore, you cannot query the table. You can get an item using its `Id` value.

- Run the following queries against the `Reply` table. (The `Reply` table's primary key is composed of `Id` and `ReplyDateTime` attributes. The `ReplyDateTime` is a sort key. Therefore, you can query this table.)
  - Find replies to a forum thread posted in the last 15 days.
  - Find replies to a forum thread posted in a specific date range.
- Scan the `ProductCatalog` table to find books whose price is less than zero.

For performance reasons, you should use a query operation instead of a scan operation. However, there are times you might need to scan a table. Suppose that there was a data entry error and one of the book prices is set to less than 0. This example scans the `ProductCategory` table to find book items (the `ProductCategory` is `book`) at price of less than 0.

For instructions about creating a working sample, see [.NET code examples \(p. 276\)](#).

**Note**

The following example does not work with .NET core because it does not support synchronous methods. For more information, see [AWS asynchronous APIs for .NET](#).

**Example**

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
using System;  
using System.Collections.Generic;  
using System.Configuration;  
using Amazon.DynamoDBv2;  
using Amazon.DynamoDBv2.DataModel;  
using Amazon.DynamoDBv2.DocumentModel;  
using Amazon.Runtime;  
  
namespace com.amazonaws.codesamples  
{  
    class HighLevelQueryAndScan  
    {  
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();  
  
        static void Main(string[] args)  
        {  
            try  
            {  
                DynamoDBContext context = new DynamoDBContext(client);  
                // Get an item.  
                GetBook(context, 101);  
  
                // Sample forum and thread to test queries.  
                string forumName = "Amazon DynamoDB";  
                string threadSubject = "DynamoDB Thread 1";  
                // Sample queries.  
                FindRepliesInLast15Days(context, forumName, threadSubject);  
                FindRepliesPostedWithinTimePeriod(context, forumName, threadSubject);  
            }  
        }  
    }  
}
```

```

        // Scan table.
        FindProductsPricedLessThanZero(context);
        Console.WriteLine("To continue, press Enter");
        Console.ReadLine();
    }
    catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
    catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
    catch (Exception e) { Console.WriteLine(e.Message); }
}

private static void GetBook(DynamoDBContext context, int productId)
{
    Book bookItem = context.Load<Book>(productId);

    Console.WriteLine("\nGetBook: Printing result.....");
    Console.WriteLine("Title: {0} \n No.Of threads:{1} \n No. of messages: {2}",
                    bookItem.Title, bookItem.ISBN, bookItem.PageCount);
}

private static void FindRepliesInLast15Days(DynamoDBContext context,
                                             string forumName,
                                             string threadSubject)
{
    string replyId = forumName + "#" + threadSubject;
    DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
    IEnumerable<Reply> latestReplies =
        context.Query<Reply>(replyId, QueryOperator.GreaterThan, twoWeeksAgoDate);
    Console.WriteLine("\nFindRepliesInLast15Days: Printing result.....");
    foreach (Reply r in latestReplies)
        Console.WriteLine("{0}\t{1}\t{2}\t{3}", r.Id, r.PostedBy, r.Message,
r.ReplyDateTime);
}

private static void FindRepliesPostedWithinTimePeriod(DynamoDBContext context,
                                                      string forumName,
                                                      string threadSubject)
{
    string forumId = forumName + "#" + threadSubject;
    Console.WriteLine("\nFindRepliesPostedWithinTimePeriod: Printing result.....");

    DateTime startDate = DateTime.UtcNow - TimeSpan.FromDays(30);
    DateTime endDate = DateTime.UtcNow - TimeSpan.FromDays(1);

    IEnumerable<Reply> repliesInAPeriod = context.Query<Reply>(forumId,
                                                               QueryOperator.Between,
                                                               startDate, endDate);
    foreach (Reply r in repliesInAPeriod)
        Console.WriteLine("{0}\t{1}\t{2}\t{3}", r.Id, r.PostedBy, r.Message,
r.ReplyDateTime);
}

private static void FindProductsPricedLessThanZero(DynamoDBContext context)
{
    int price = 0;
    IEnumerable<Book> itemsWithWrongPrice = context.Scan<Book>(
        new ScanCondition("Price", ScanOperator.LessThan, price),
        new ScanCondition("ProductCategory", ScanOperator.Equal, "Book")
    );
    Console.WriteLine("\nFindProductsPricedLessThanZero: Printing result.....");
    foreach (Book r in itemsWithWrongPrice)
        Console.WriteLine("{0}\t{1}\t{2}\t{3}", r.Id, r.Title, r.Price, r.ISBN);
}

[DynamoDBTable("Reply")]
public class Reply

```

```

{
    [DynamoDBHashKey] //Partition key
    public string Id
    {
        get; set;
    }

    [DynamoDBRangeKey] //Sort key
    public DateTime ReplyDateTime
    {
        get; set;
    }

    // Properties included implicitly.
    public string Message
    {
        get; set;
    }
    // Explicit property mapping with object persistence model attributes.
    [DynamoDBProperty("LastPostedBy")]
    public string PostedBy
    {
        get; set;
    }
    // Property to store version number for optimistic locking.
    [DynamoDBVersion]
    public int? Version
    {
        get; set;
    }
}

[DynamoDBTable("Thread")]
public class Thread
{
    // Partition key mapping.
    [DynamoDBHashKey] //Partition key
    public string ForumName
    {
        get; set;
    }
    [DynamoDBRangeKey] //Sort key
    public DateTime Subject
    {
        get; set;
    }
    // Implicit mapping.
    public string Message
    {
        get; set;
    }
    public string LastPostedBy
    {
        get; set;
    }
    public int Views
    {
        get; set;
    }
    public int Replies
    {
        get; set;
    }
    public bool Answered
    {
        get; set;
    }
}

```

```

        }
        public DateTime LastPostedDateTime
        {
            get; set;
        }
        // Explicit mapping (property and table attribute names are different).
        [DynamoDBProperty("Tags")]
        public List<string> KeywordTags
        {
            get; set;
        }
        // Property to store version number for optimistic locking.
        [DynamoDBVersion]
        public int? Version
        {
            get; set;
        }
    }

    [DynamoDBTable("Forum")]
    public class Forum
    {
        [DynamoDBHashKey]
        public string Name
        {
            get; set;
        }
        // All the following properties are explicitly mapped
        // to show how to provide mapping.
        [DynamoDBProperty]
        public int Threads
        {
            get; set;
        }
        [DynamoDBProperty]
        public int Views
        {
            get; set;
        }
        [DynamoDBProperty]
        public string LastPostBy
        {
            get; set;
        }
        [DynamoDBProperty]
        public DateTime LastPostDateTime
        {
            get; set;
        }
        [DynamoDBProperty]
        public int Messages
        {
            get; set;
        }
    }

    [DynamoDBTable("ProductCatalog")]
    public class Book
    {
        [DynamoDBHashKey] //Partition key
        public int Id
        {
            get; set;
        }
        public string Title
        {

```

```
        get; set;
    }
    public string ISBN
    {
        get; set;
    }
    public int Price
    {
        get; set;
    }
    public string PageCount
    {
        get; set;
    }
    public string ProductCategory
    {
        get; set;
    }
    public bool InPublication
    {
        get; set;
    }
}
```

## Running the code examples in this Developer Guide

The AWS SDKs provide broad support for Amazon DynamoDB in the following languages:

- [Java](#)
- [JavaScript in the browser](#)
- [.NET](#)
- [Node.js](#)
- [PHP](#)
- [Python](#)
- [Ruby](#)
- [C++](#)
- [Go](#)
- [Android](#)
- [iOS](#)

To get started quickly with these languages, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

The code examples in this developer guide provide more in-depth coverage of DynamoDB operations, using the following programming languages:

- [Java code examples \(p. 274\)](#)
- [.NET code examples \(p. 276\)](#)

Before you can begin with this exercise, you need to create an AWS account, get your access key and secret key, and set up the AWS Command Line Interface (AWS CLI) on your computer. For more information, see [Setting up DynamoDB \(web service\) \(p. 58\)](#).

**Note**

If you are using the downloadable version of DynamoDB, you need to use the AWS CLI to create the tables and sample data. You also need to specify the `--endpoint-url` parameter with each AWS CLI command. For more information, see [Setting the local endpoint \(p. 56\)](#).

## Creating tables and loading data for code examples in DynamoDB

In this tutorial, you use the AWS Management Console to create tables in Amazon DynamoDB. You then load data into these tables using the AWS Command Line Interface (AWS CLI).

These tables and their data are used as examples throughout this developer guide.

**Note**

If you are an application developer, we recommend that you also read [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#), which uses the downloadable version of DynamoDB. This lets you learn about the DynamoDB low-level API without having to pay any fees for throughput, storage, or data transfer.

### Topics

- [Step 1: Create example tables \(p. 269\)](#)
- [Step 2: Load data into tables \(p. 271\)](#)
- [Step 3: Query the data \(p. 272\)](#)
- [Step 4: \(Optional\) clean up \(p. 273\)](#)
- [Summary \(p. 274\)](#)

## Step 1: Create example tables

In this section, you use the AWS Management Console to create tables in Amazon DynamoDB for two simple use cases.

### Use case 1: Product catalog

Suppose that you want to store product information in DynamoDB. Each product has its own distinct attributes, so you need to store different information about each of these products.

You can create a `ProductCatalog` table, where each item is uniquely identified by a single, numeric attribute: `Id`.

Table name	Primary key
ProductCatalog	Partition key: <code>Id</code> (Number)

### Use case 2: Forum application

Suppose that you want to build an application for message boards or discussion forums. AWS [Discussion forums](#) represent one example of such an application. Customers can engage with the developer community, ask questions, or reply to other customers' posts. Each AWS service has a dedicated forum. Anyone can start a new discussion thread by posting a message in a forum. Each thread might receive any number of replies.

You can model this application by creating three tables: `Forum`, `Thread`, and `Reply`.

Table name	Primary key
<code>Forum</code>	Partition key: <code>Name</code> ( <code>String</code> )
<code>Thread</code>	Partition key: <code>ForumName</code> ( <code>String</code> ) Sort key: <code>Subject</code> ( <code>String</code> )
<code>Reply</code>	Partition key: <code>Id</code> ( <code>String</code> ) Sort key: <code>ReplyDateTime</code> ( <code>String</code> )

The `Reply` table has a global secondary index named `PostedBy-Message-Index`. This index facilitates queries on two non-key attributes of the `Reply` table.

Index name	Primary key
<code>PostedBy-Message-Index</code>	Partition key: <code>PostedBy</code> ( <code>String</code> ) Sort key: <code>Message</code> ( <code>String</code> )

## Create the ProductCatalog table

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. Choose **Create Table**.
3. In the **Create DynamoDB table** screen, do the following:
  - a. On the **Table** name box, enter `ProductCatalog`.
  - b. For the **Primary key**, in the **Partition key** box, enter `Id`. Set the data type to **Number**.
4. When the settings are as you want them, choose **Create**.

## Create the forum table

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. Choose **Create Table**.
3. In the **Create DynamoDB table** screen, do the following:
  - a. In the **Table** name box, enter `Forum`.
  - b. For the **Primary key**, in the **Partition key** box, enter `Name`. Set the data type to **String**.
4. When the settings are as you want them, choose **Create**.

## Create the thread table

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. Choose **Create Table**.
3. In the **Create DynamoDB table** screen, do the following:
  - a. In the **Table** name box, enter `Thread`.
  - b. For the **Primary key**, do the following:

- In the **Partition key** box, enter **ForumName**. Set the data type to **String**.
  - Choose **Add sort key**.
  - In the **Sort key** box, enter **Subject**. Set the data type to **String**.
4. When the settings are as you want them, choose **Create**.

## Create the reply table

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. Choose **Create Table**.
3. In the **Create DynamoDB table** screen, do the following:
  - a. In the **Table name** box, enter **Reply**.
  - b. For the **Primary key**, do the following:
    - In the **Partition key** box, enter **Id**. Set the data type to **String**.
    - Choose **Add sort key**.
    - In the **Sort key** box, enter **ReplyDateTime**. Set the data type to **String**.
  - c. In the **Table settings** section, clear **Use default settings**.
  - d. In the **Secondary indexes** section, choose **Add index**.
  - e. In the **Add index** window, do the following:
    - For the **Primary key**, do the following:
      - In the **Partition key** box, enter **PostedBy**. Set the data type to **String**.
      - Choose **Add sort key**.
      - In the **Sort key** box, enter **Message**. Set the data type to **String**.
    - In the **Index name** box, enter **PostedBy-Message-Index**.
    - Set the **Projected attributes** to **All**.
    - Choose **Add index**.
4. When the settings are as you want them, choose **Create**.

## Step 2: Load data into tables

In this step, you load sample data into the tables that you created. You could enter the data manually into the Amazon DynamoDB console. However, to save time, you use the AWS Command Line Interface (AWS CLI) instead.

### Note

If you have not yet set up the AWS CLI, see [Using the AWS CLI \(p. 61\)](#) for instructions.

You will download a .zip archive that contains JSON files with sample data for each table. For each file, you use the AWS CLI to load the data into DynamoDB. Each successful data load produces the following output.

```
{  
    "UnprocessedItems": {}  
}
```

## Download the sample data file archive

1. Download the sample data archive (`sampledata.zip`) using this link:

- [sampledata.zip](#)
2. Extract the .json data files from the archive.
  3. Copy the .json data files to your current directory.

## Load the sample data into DynamoDB tables

1. To load the `ProductCatalog` table with data, enter the following command.

```
aws dynamodb batch-write-item --request-items file://ProductCatalog.json
```

2. To load the `Forum` table with data, enter the following command.

```
aws dynamodb batch-write-item --request-items file://Forum.json
```

3. To load the `Thread` table with data, enter the following command.

```
aws dynamodb batch-write-item --request-items file://Thread.json
```

4. To load the `Reply` table with data, enter the following command.

```
aws dynamodb batch-write-item --request-items file://Reply.json
```

## Verify data load

You can use the AWS Management Console to verify the data that you loaded into the tables.

### To verify the data using the AWS Management Console

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, choose **Tables**.
3. In the list of tables, choose **ProductCatalog**.
4. Choose the **Items** tab to view the data that you loaded into the table.
5. To view an item in the table, choose its **Id**. (If you want, you can also edit the item.)
6. To return to the list of tables, choose **Cancel**.


Repeat this procedure for each of the other tables you created:

- `Forum`
- `Thread`
- `Reply`


## Step 3: Query the data

In this step, you try some simple queries against the tables that you created, using the Amazon DynamoDB console.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, choose **Tables**.
3. In the list of tables, choose **Reply**.
4. Choose the **Items** tab to view the data that you loaded into the table.
5. Choose the data filtering link, located just below the **Create item** button.



When you choose the link, the console reveals a data filtering pane.



6. In the data filtering pane, do the following:
  - a. Change the operation from **Scan** to **Query**.
  - b. For the **Partition key**, enter the value **Amazon DynamoDB#DynamoDB Thread 1**.
  - c. Choose **Start**. Only the items that match your query criteria are returned from the **Reply** table.
7. The **Reply** table has a global secondary index on the **PostedBy** and **Message** attributes. You can use the data filtering pane to query the index. Do the following:
  - a. Change the query source from the following:

[Table] Reply: Id, ReplyDateTime

To the following:

[Index] PostedBy-Message-Index: PostedBy, Message

- b. For the **Partition key**, enter the value **User A**.
- c. Choose **Start**. Only the items that match your query criteria are returned from **PostedBy-Message-Index**.

Take some time to explore your other tables using the DynamoDB console:

- ProductCatalog
- Forum
- Thread

## Step 4: (Optional) clean up

These sample tables are used throughout the *Amazon DynamoDB Developer Guide* to help illustrate table and item operations using the low-level API and various AWS SDKs. If you plan to read the rest of this guide, you might find the tables useful as a reference. However, if you don't want to keep these tables, you should delete them to avoid being charged for resources that you don't need.

### To delete the sample tables

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, choose **Tables**.
3. In the list of tables, choose **ProductCatalog**.
4. Choose **Delete Table**. You are asked to confirm your selection.

Repeat this procedure for each of the other tables you created:

- **Forum**
- **Thread**
- **Reply**

## Summary

In this exercise, you used the DynamoDB console to create several tables in DynamoDB. You then used the AWS CLI to load data into the tables, and performed some basic operations on the data using the console.

The console and the AWS CLI are helpful for getting started quickly. However, you probably want to learn more about how DynamoDB works, and how to write application programs with DynamoDB. The rest of this developer guide addresses those topics.

## Java code examples

### Topics

- [Java: Setting your AWS credentials \(p. 275\)](#)
- [Java: Setting the AWS Region and endpoint \(p. 275\)](#)

This Developer Guide contains Java code snippets and ready-to-run programs. You can find these code examples in the following sections:

- [Working with items and attributes \(p. 344\)](#)
- [Working with tables and data in DynamoDB \(p. 279\)](#)
- [Query operations in DynamoDB \(p. 428\)](#)
- [Working with scans in DynamoDB \(p. 445\)](#)
- [Improving data access with secondary indexes \(p. 497\)](#)
- [Java: DynamoDBMapper \(p. 170\)](#)
- [Change data capture for DynamoDB Streams \(p. 598\)](#)

You can get started quickly by using Eclipse with the [AWS Toolkit for Eclipse](#). In addition to a full-featured IDE, you also get the AWS SDK for Java with automatic updates, and preconfigured templates for building AWS applications.

### To run the Java code examples (using Eclipse)

1. Download and install the [Eclipse](#) IDE.
2. Download and install the [AWS Toolkit for Eclipse](#).
3. Start Eclipse, and on the **Eclipse** menu, choose **File, New, and then Other**.

4. In **Select a wizard**, choose **AWS**, choose **AWS Java Project**, and then choose **Next**.
5. In **Create an AWS Java**, do the following:
  - a. In **Project name**, enter a name for your project.
  - b. In **Select Account**, choose your credentials profile from the list.If this is your first time using the [AWS Toolkit for Eclipse](#), choose **Configure AWS Accounts** to set up your AWS credentials.
6. Choose **Finish** to create the project.
7. From the **Eclipse** menu, choose **File**, **New**, and then **Class**.
8. In **Java Class**, enter a name for your class in **Name** (use the same name as the code example that you want to run), and then choose **Finish** to create the class.
9. Copy the code example from the documentation page into the Eclipse editor.
10. To run the code, choose **Run** on the Eclipse menu.

The SDK for Java provides thread-safe clients for working with DynamoDB. As a best practice, your applications should create one client and reuse the client between threads.

For more information, see the [AWS SDK for Java](#).

**Note**

The code examples in this guide are intended for use with the latest version of the AWS SDK for Java.

If you are using the AWS Toolkit for Eclipse, you can configure automatic updates for the SDK for Java. To do this in Eclipse, go to **Preferences** and choose **AWS Toolkit**, **AWS SDK for Java**, **Download new SDKs automatically**.

## Java: Setting your AWS credentials

The SDK for Java requires that you provide AWS credentials to your application at runtime. The code examples in this guide assume that you are using an AWS credentials file, as described in [Set up your AWS credentials](#) in the *AWS SDK for Java Developer Guide*.

The following is an example of an AWS credentials file named `~/.aws/credentials`, where the tilde character (~) represents your home directory.

```
[default]
aws_access_key_id = AWS access key ID goes here
aws_secret_access_key = Secret key goes here
```

## Java: Setting the AWS Region and endpoint

By default, the code examples access DynamoDB in the US West (Oregon) Region. You can change the Region by modifying the `AmazonDynamoDB` properties.

The following code example instantiates a new `AmazonDynamoDB`.

```
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.regions.Regions;
...
// This client will default to US West (Oregon)
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard()
.withRegion(Regions.US_WEST_2)
.build();
```

You can use the `withRegion` method to run your code against DynamoDB in any Region where it is available. For a complete list, see [AWS regions and endpoints](#) in the *Amazon Web Services General Reference*.

If you want to run the code examples using DynamoDB locally on your computer, set the endpoint as follows.

## AWS SDK V1

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().withEndpointConfiguration(  
    new AwsClientBuilder.EndpointConfiguration("http://localhost:8000", "us-west-2"))  
.build();
```

## AWS SDK V2

```
DynamoDbClient client = DynamoDbClient.builder()  
.endpointOverride(URI.create("http://localhost:8000"))  
// The region is meaningless for local DynamoDb but required for client builder  
validation  
.region(Region.US_EAST_1)  
.credentialsProvider(StaticCredentialsProvider.create(  
    AwsBasicCredentials.create("dummy-key", "dummy-secret")))  
.build();
```

# .NET code examples

## Topics

- [.NET: Setting your AWS credentials \(p. 277\)](#)
- [.NET: Setting the AWS Region and endpoint \(p. 278\)](#)

This guide contains .NET code snippets and ready-to-run programs. You can find these code examples in the following sections:

- [Working with items and attributes \(p. 344\)](#)
- [Working with tables and data in DynamoDB \(p. 279\)](#)
- [Query operations in DynamoDB \(p. 428\)](#)
- [Working with scans in DynamoDB \(p. 445\)](#)
- [Improving data access with secondary indexes \(p. 497\)](#)
- [.NET: Document model \(p. 217\)](#)
- [.NET: Object persistence model \(p. 240\)](#)
- [Change data capture for DynamoDB Streams \(p. 598\)](#)

You can get started quickly by using the AWS SDK for .NET with the Toolkit for Visual Studio.

## To run the .NET code examples (using Visual Studio)

1. Download and install [Microsoft Visual Studio](#).
2. Download and install the [Toolkit for Visual Studio](#).
3. Start Visual Studio. Choose **File**, **New**, **Project**.
4. In **New Project**, choose **AWS Empty Project**, and then choose **OK**.
5. In **AWS Access Credentials**, choose **Use existing profile**, choose your credentials profile from the list, and then choose **OK**.

- If this is your first time using Toolkit for Visual Studio, choose **Use a new profile** to set up your AWS credentials.
6. In your Visual Studio project, choose the tab for your program's source code (`Program.cs`). Copy the code example from the documentation page into the Visual Studio editor, replacing any other code that you see in the editor.
  7. If you see error messages of the form The type or namespace name...could not be found, you need to install the AWS SDK assembly for DynamoDB as follows:
    - a. In Solution Explorer, open the context (right-click) menu for your project, and then choose **Manage NuGet Packages**.
    - b. In NuGet Package Manager, choose **Browse**.
    - c. In the search box, enter `AWSSDK.DynamoDBv2`, and wait for the search to complete.
    - d. Choose `AWSSDK.DynamoDBv2`, and then choose **Install**.
    - e. When the installation is complete, choose the **Program.cs** tab to return to your program.
  8. To run the code, choose **Start** in the Visual Studio toolbar.

The AWS SDK for .NET provides thread-safe clients for working with DynamoDB. As a best practice, your applications should create one client and reuse the client between threads.

For more information, see [AWS SDK for .NET](#).

**Note**

The code examples in this guide are intended for use with the latest version of the AWS SDK for .NET.

## .NET: Setting your AWS credentials

The AWS SDK for .NET requires that you provide AWS credentials to your application at runtime. The code examples in this guide assume that you are using the SDK Store to manage your AWS credentials file, as described in [Using the SDK store](#) in the *AWS SDK for .NET Developer Guide*.

The Toolkit for Visual Studio supports multiple sets of credentials from any number of accounts. Each set is referred to as a *profile*. Visual Studio adds entries to the project's `App.config` file so that your application can find the AWS credentials at runtime.

The following example shows the default `App.config` file that is generated when you create a new project using Toolkit for Visual Studio.

```
<?xml version="1.0" encoding="utf-8" ?>
<configuration>
    <appSettings>
        <add key="AWSProfileName" value="default"/>
        <add key="AWSRegion" value="us-west-2" />
    </appSettings>
</configuration>
```

At runtime, the program uses the `default` set of AWS credentials, as specified by the `AWSProfileName` entry. The AWS credentials themselves are kept in the SDK Store in encrypted form. The Toolkit for Visual Studio provides a graphical user interface for managing your credentials, all from within Visual Studio. For more information, see [Specifying credentials](#) in the *AWS Toolkit for Visual Studio User Guide*.

**Note**

By default, the code examples access DynamoDB in the US West (Oregon) Region. You can change the Region by modifying the `AWSRegion` entry in the `App.config` file. You can set `AWSRegion` to any Region where DynamoDB is available. For a complete list, see [AWS regions and endpoints](#) in the *Amazon Web Services General Reference*.

## .NET: Setting the AWS Region and endpoint

By default, the code examples access DynamoDB in the US West (Oregon) Region. You can change the Region by modifying the `AWSRegion` entry in the `App.config` file. Or, you can change the Region by modifying the `AmazonDynamoDBClient` properties.

The following code example instantiates a new `AmazonDynamoDBClient`. The client is modified so that the code runs against DynamoDB in a different Region.

```
AmazonDynamoDBConfig clientConfig = new AmazonDynamoDBConfig();
// This client will access the US East 1 region.
clientConfig.RegionEndpoint = RegionEndpoint.USEast1;
AmazonDynamoDBClient client = new AmazonDynamoDBClient(clientConfig);
```

For a complete list of Regions, see [AWS regions and endpoints](#) in the *Amazon Web Services General Reference*.

If you want to run the code examples using DynamoDB locally on your computer, set the endpoint as follows.

```
AmazonDynamoDBConfig clientConfig = new AmazonDynamoDBConfig();
// Set the endpoint URL
clientConfig.ServiceURL = "http://localhost:8000";
AmazonDynamoDBClient client = new AmazonDynamoDBClient(clientConfig);
```

# Working with tables, items, queries, scans, and indexes

This section provides details about working with tables, items, queries, and more in Amazon DynamoDB.

## Topics

- [Working with tables and data in DynamoDB \(p. 279\)](#)
- [Working with read and write operations \(p. 344\)](#)
- [Improving data access with secondary indexes \(p. 497\)](#)
- [Managing complex workflows with DynamoDB transactions \(p. 577\)](#)
- [Change data capture with Amazon DynamoDB \(p. 588\)](#)
- [Using On-Demand backup and restore for DynamoDB \(p. 629\)](#)
- [Point-in-time recovery for DynamoDB \(p. 649\)](#)

## Working with tables and data in DynamoDB

This section describes how to use the AWS Command Line Interface (AWS CLI) and the AWS SDKs to create, update, and delete tables in Amazon DynamoDB.

### Note

You can also perform these same tasks using the AWS Management Console. For more information, see [Using the console \(p. 60\)](#).

This section also provides more information about throughput capacity using DynamoDB auto scaling or manually setting provisioned throughput.

## Topics

- [Basic operations on DynamoDB tables \(p. 279\)](#)
- [Considerations when changing read/write Capacity Mode \(p. 285\)](#)
- [Considerations when choosing a table class \(p. 285\)](#)
- [Managing settings on DynamoDB provisioned capacity tables \(p. 286\)](#)
- [DynamoDB Item sizes and formats \(p. 290\)](#)
- [Managing throughput capacity automatically with DynamoDB auto scaling \(p. 291\)](#)
- [Global tables - multi-Region replication for DynamoDB \(p. 305\)](#)
- [Adding tags and labels to resources \(p. 329\)](#)
- [Working with DynamoDB tables in Java \(p. 332\)](#)
- [Working with DynamoDB tables in .NET \(p. 337\)](#)

## Basic operations on DynamoDB tables

Similar to other database systems, Amazon DynamoDB stores data in tables. You can manage your tables using a few basic operations.

## Topics

- [Creating a table \(p. 280\)](#)
- [Describing a table \(p. 283\)](#)

- [Updating a table \(p. 283\)](#)
- [Deleting a table \(p. 284\)](#)
- [Listing table names \(p. 284\)](#)
- [Describing provisioned throughput quotas \(p. 284\)](#)

## Creating a table

Use the `CreateTable` operation to create a table in Amazon DynamoDB. To create the table, you must provide the following information:

- **Table name.** The name must conform to the DynamoDB naming rules, and must be unique for the current AWS account and Region. For example, you could create a `People` table in US East (N. Virginia) and another `People` table in Europe (Ireland). However, these two tables would be entirely different from each other. For more information, see [Supported data types and naming rules in Amazon DynamoDB \(p. 13\)](#).
- **Primary key.** The primary key can consist of one attribute (partition key) or two attributes (partition key and sort key). You need to provide the attribute names, data types, and the role of each attribute: `HASH` (for a partition key) and `RANGE` (for a sort key). For more information, see [Primary key \(p. 6\)](#).
- **Throughput settings (for provisioned tables).** If using provisioned mode, you must specify the initial read and write throughput settings for the table. You can modify these settings later, or enable DynamoDB auto scaling to manage the settings for you. For more information, see [Managing settings on DynamoDB provisioned capacity tables \(p. 286\)](#) and [Managing throughput capacity automatically with DynamoDB auto scaling \(p. 291\)](#).

### Example 1: Create a provisioned table

The following AWS CLI example shows how to create a table (`Music`). The primary key consists of `Artist` (partition key) and `SongTitle` (sort key), each of which has a data type of `String`. The maximum throughput for this table is 10 read capacity units and 5 write capacity units.

```
aws dynamodb create-table \
    --table-name Music \
    --attribute-definitions \
        AttributeName=Artist,AttributeType=S \
        AttributeName=SongTitle,AttributeType=S \
    --key-schema \
        AttributeName=Artist,KeyType=HASH \
        AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput \
        ReadCapacityUnits=10,WriteCapacityUnits=5
```

The `CreateTable` operation returns metadata for the table, as shown following.

```
{
    "TableDescription": {
        "TableArn": "arn:aws:dynamodb:us-east-1:123456789012:table/Music",
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        ...
    }
}
```

```

    "ProvisionedThroughput": {
        "NumberOfDecreasesToday": 0,
        "WriteCapacityUnits": 5,
        "ReadCapacityUnits": 10
    },
    "TableSizeBytes": 0,
    "TableName": "Music",
    "TableStatus": "CREATING",
    "TableId": "12345678-0123-4567-a123-abcdefhijkl",
    "KeySchema": [
        {
            "KeyType": "HASH",
            "AttributeName": "Artist"
        },
        {
            "KeyType": "RANGE",
            "AttributeName": "SongTitle"
        }
    ],
    "ItemCount": 0,
    "CreationDateTime": 1542397215.37
}
}

```

The `TableStatus` element indicates the current state of the table (`CREATING`). It might take a while to create the table, depending on the values you specify for `ReadCapacityUnits` and `WriteCapacityUnits`. Larger values for these require DynamoDB to allocate more resources for the table.

## Example 2: Create an on-demand table

To create the same table `Music` using on-demand mode.

```

aws dynamodb create-table \
--table-name Music \
--attribute-definitions \
    AttributeName=Artist,AttributeType=S \
    AttributeName=SongTitle,AttributeType=S \
--key-schema \
    AttributeName=Artist,KeyType=HASH \
    AttributeName=SongTitle,KeyType=RANGE \
--billing-mode=PAY_PER_REQUEST

```

The `CreateTable` operation returns metadata for the table, as shown following.

```

{
    "TableDescription": {
        "TableArn": "arn:aws:dynamodb:us-east-1:123456789012:table/Music",
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "WriteCapacityUnits": 0,
            "ReadCapacityUnits": 0
        },
    }
}

```

```

    "TableSizeBytes": 0,
    "TableName": "Music",
    "BillingModeSummary": {
        "BillingMode": "PAY_PER_REQUEST"
    },
    "TableStatus": "CREATING",
    "TableId": "12345678-0123-4567-a123-abcdefghijkl",
    "KeySchema": [
        {
            "KeyType": "HASH",
            "AttributeName": "Artist"
        },
        {
            "KeyType": "RANGE",
            "AttributeName": "SongTitle"
        }
    ],
    "ItemCount": 0,
    "CreationDateTime": 1542397468.348
}
}

```

### **Important**

When calling `DescribeTable` on an on-demand table, read capacity units and write capacity units are set to 0.

## Example 3: Create a table using the DynamoDB standard-infrequent access table class

To create the same `Music` table using the DynamoDB Standard-Infrequent Access table class.

```

aws dynamodb create-table \
--table-name Music \
--attribute-definitions \
    AttributeName=Artist,AttributeType=S \
    AttributeName=SongTitle,AttributeType=S \
--key-schema \
    AttributeName=Artist,KeyType=HASH \
    AttributeName=SongTitle,KeyType=RANGE \
--provisioned-throughput \
    ReadCapacityUnits=10,WriteCapacityUnits=5 \
--table-class STANDARD_INFREQUENT_ACCESS

```

The `CreateTable` operation returns metadata for the table, as shown following.

```

{
    "TableDescription": {
        "TableArn": "arn:aws:dynamodb:us-east-1:123456789012:table/Music",
        "AttributeDefinitions": [
            {
                "AttributeName": "Artist",
                "AttributeType": "S"
            },
            {
                "AttributeName": "SongTitle",
                "AttributeType": "S"
            }
        ],
        "ProvisionedThroughput": {
            "NumberOfDecreasesToday": 0,
            "WriteCapacityUnits": 5,
            "ReadCapacityUnits": 10
        }
    }
}

```

```
        },
        "TableClassSummary": {
            "LastUpdateDateTime": 1542397215.37,
            "TableClass": "STANDARD_INFREQUENT_ACCESS"
        },
        "TableSizeBytes": 0,
        "TableName": "Music",
        "TableStatus": "CREATING",
        "TableId": "12345678-0123-4567-a123-abcdefhijkl",
        "KeySchema": [
            {
                "KeyType": "HASH",
                "AttributeName": "Artist"
            },
            {
                "KeyType": "RANGE",
                "AttributeName": "SongTitle"
            }
        ],
        "ItemCount": 0,
        "CreationDateTime": 1542397215.37
    }
}
```

## Describing a table

To view details about a table, use the `DescribeTable` operation. You must provide the table name. The output from `DescribeTable` is in the same format as that from `CreateTable`. It includes the timestamp when the table was created, its key schema, its provisioned throughput settings, its estimated size, and any secondary indexes that are present.

**Important**

When calling `DescribeTable` on an on-demand table, read capacity units and write capacity units are set to 0.

### Example

```
aws dynamodb describe-table --table-name Music
```

The table is ready for use when the `TableStatus` has changed from `CREATING` to `ACTIVE`.

**Note**

If you issue a `DescribeTable` request immediately after a `CreateTable` request, DynamoDB might return an error (`ResourceNotFoundException`). This is because `DescribeTable` uses an eventually consistent query, and the metadata for your table might not be available at that moment. Wait for a few seconds, and then try the `DescribeTable` request again.

For billing purposes, your DynamoDB storage costs include a per-item overhead of 100 bytes. (For more information, go to [DynamoDB Pricing](#).) This extra 100 bytes per item is not used in capacity unit calculations or by the `DescribeTable` operation.

## Updating a table

The `UpdateTable` operation allows you to do one of the following:

- Modify a table's provisioned throughput settings (for provisioned mode tables).
- Change the table's read/write capacity mode.
- Manipulate global secondary indexes on the table (see [Using Global Secondary Indexes in DynamoDB \(p. 500\)](#)).
- Enable or disable DynamoDB Streams on the table (see [Change data capture for DynamoDB Streams \(p. 598\)](#)).

### Example

The following AWS CLI example shows how to modify a table's provisioned throughput settings.

```
aws dynamodb update-table --table-name Music \
--provisioned-throughput ReadCapacityUnits=20,WriteCapacityUnits=10
```

#### Note

When you issue an `UpdateTable` request, the status of the table changes from `AVAILABLE` to `UPDATING`. The table remains fully available for use while it is `UPDATING`. When this process is completed, the table status changes from `UPDATING` to `AVAILABLE`.

### Example

The following AWS CLI example shows how to modify a table's read/write capacity mode to on-demand mode.

```
aws dynamodb update-table --table-name Music \
--billing-mode PAY_PER_REQUEST
```

## Deleting a table

You can remove an unused table with the `DeleteTable` operation. Deleting a table is an unrecoverable operation.

### Example

The following AWS CLI example shows how to delete a table.

```
aws dynamodb delete-table --table-name Music
```

When you issue a `DeleteTable` request, the table's status changes from `ACTIVE` to `DELETING`. It might take a while to delete the table, depending on the resources it uses (such as the data stored in the table, and any streams or indexes on the table).

When the `DeleteTable` operation concludes, the table no longer exists in DynamoDB.

## Listing table names

The `ListTables` operation returns the names of the DynamoDB tables for the current AWS account and Region.

### Example

The following AWS CLI example shows how to list the DynamoDB table names.

```
aws dynamodb list-tables
```

## Describing provisioned throughput quotas

The `DescribeLimits` operation returns the current read and write capacity quotas for the current AWS account and Region.

### Example

The following AWS CLI example shows how to describe the current provisioned throughput quotas.

```
aws dynamodb describe-limits
```

The output shows the upper quotas of read and write capacity units for the current AWS account and Region.

For more information about these quotas, and how to request quota increases, see [Throughput default quotas \(p. 1243\)](#).

## Considerations when changing read/write Capacity Mode

You can switch between read/write capacity modes once every 24 hours. Consider the following when updating your read/write capacity mode in Amazon DynamoDB.

### Managing capacity

When you update a table from provisioned to on-demand mode, you don't need to specify how much read and write throughput you expect your application to perform.

Consider the following when you update a table from on-demand to provisioned mode:

- If you're using the AWS Management Console, the console estimates initial provisioned capacity values based on the consumed read and write capacity of your table and global secondary indexes over the past 30 minutes. To override these recommended values, choose `Override recommended values`.
- If you're using the AWS CLI or AWS SDK, choose the right provisioned capacity settings of your table and global secondary indexes by using Amazon CloudWatch to look at your historical consumption (`ConsumedWriteCapacityUnits` and `ConsumedReadCapacityUnits` metrics) to determine the new throughput settings.

#### Note

If you're switching a global table to provisioned mode, look at the maximum consumption across all your regional replicas for base tables and global secondary indexes when determining the new throughput settings.

### Managing auto scaling

When you update a table from provisioned to on-demand mode:

- If you're using the console, all of your auto scaling settings (if any) will be deleted.
- If you're using the AWS CLI or AWS SDK, all of your auto scaling settings will be preserved. These settings can be applied when you update your table to provisioned billing mode again.

When you update a table from on-demand to provisioned mode:

- If you're using the console, DynamoDB recommends enabling auto scaling with the following defaults:
  - Target utilization: 70%
  - Minimum provisioned capacity: 5 units
  - Maximum provisioned capacity: The Region maximum
- If you're using the AWS CLI or SDK, your previous auto scaling settings (if any) are preserved.

## Considerations when choosing a table class

DynamoDB offers two table classes designed to help you optimize for cost. The DynamoDB Standard table class is the default, and is recommended for the vast majority of workloads. The DynamoDB Standard-Infrequent Access (DynamoDB Standard-IA) table class is optimized for tables where storage

is the dominant cost. For example, tables that store infrequently accessed data, such as application logs, old social media posts, e-commerce order history, and past gaming achievements, are good candidates for the Standard-IA table class.

Every DynamoDB table is associated with a table class. You can set your table class when creating your table (DynamoDB Standard by default) and update the table class of an existing table using the AWS Management Console, AWS CLI, or AWS SDK. DynamoDB also supports managing your table class using AWS CloudFormation for single-region tables (tables that are not global tables). Each table class offers different pricing for data storage as well as read and write requests. When choosing a table class for your table, keep the following in mind:

- The DynamoDB Standard table class offers lower throughput costs than DynamoDB Standard-IA and is the most cost-effective option for tables where throughput is the dominant cost.
- The DynamoDB Standard-IA table class offers lower storage costs than DynamoDB Standard, and is the most cost-effective option for tables where storage is the dominant cost. When storage exceeds 50% of the throughput (reads and writes) cost of a table using the DynamoDB Standard table class, the DynamoDB Standard-IA table class can help you reduce your total table cost.
- DynamoDB Standard-IA tables offer the same performance, durability, and availability as DynamoDB Standard tables.
- Switching between the DynamoDB Standard and DynamoDB Standard-IA table classes does not require changing your application code. You use the same DynamoDB APIs and service endpoints regardless of the table class your tables use.
- DynamoDB Standard-IA tables are compatible with all existing DynamoDB features such as auto scaling, on-demand mode, time-to-live (TTL), on-demand backups, point-in-time recovery (PITR), and global secondary indexes.

The most cost-effective table class for your table depends on your table's expected storage and throughput usage patterns. You can look at your table's historical storage and throughput cost and usage with AWS Cost and Usage Reports and the AWS Cost Explorer. Use this historical data to determine the most cost-effective table class for your table. To learn more about using AWS Cost and Usage Reports and the AWS Cost Explorer, see the [AWS Billing and Cost Management Documentation](#). See [Amazon DynamoDB Pricing](#) for details about table class pricing.

**Note**

A table class update is a background process. You can still access your table normally during a table class update. The time to update your table class depends on your table traffic, storage size, and other related variables. No more than two table class updates on your table are allowed in a 30-day trailing period.

## Managing settings on DynamoDB provisioned capacity tables

When you create a new provisioned table in Amazon DynamoDB, you must specify its *provisioned throughput capacity*. This is the amount of read and write activity that the table can support. DynamoDB uses this information to reserve sufficient system resources to meet your throughput requirements.

**Note**

You can create an on-demand mode table instead so that you don't have to manage any capacity settings for servers, storage, or throughput. DynamoDB instantly accommodates your workloads as they ramp up or down to any previously reached traffic level. If a workload's traffic level hits a new peak, DynamoDB adapts rapidly to accommodate the workload. For more information, see [On-demand mode \(p. 18\)](#).

You can optionally allow DynamoDB auto scaling to manage your table's throughput capacity. However, you still must provide initial settings for read and write capacity when you create the table. DynamoDB auto scaling uses these initial settings as a starting point, and then adjusts them dynamically in

response to your application's requirements. For more information, see [Managing throughput capacity automatically with DynamoDB auto scaling \(p. 291\)](#).

As your application data and access requirements change, you might need to adjust your table's throughput settings. If you're using DynamoDB auto scaling, the throughput settings are automatically adjusted in response to actual workloads. You can also use the `UpdateTable` operation to manually adjust your table's throughput capacity. You might decide to do this if you need to bulk-load data from an existing data store into your new DynamoDB table. You could create the table with a large write throughput setting and then reduce this setting after the bulk data load is complete.

You specify throughput requirements in terms of *capacity units*—the amount of data your application needs to read or write per second. You can modify these settings later, if needed, or enable DynamoDB auto scaling to modify them automatically.

### Topics

- [Read capacity units \(p. 287\)](#)
- [Write capacity units \(p. 288\)](#)
- [Request throttling and burst capacity \(p. 289\)](#)
- [Request throttling and adaptive capacity \(p. 289\)](#)
- [Choosing initial throughput settings \(p. 289\)](#)
- [Modifying throughput settings \(p. 290\)](#)

## Read capacity units

A *read capacity unit* represents one strongly consistent read per second, or two eventually consistent reads per second, for an item up to 4 KB in size.

### Note

To learn more about DynamoDB read consistency models, see [Read consistency \(p. 17\)](#).

For example, suppose that you create a table with 10 provisioned read capacity units. This allows you to perform 10 strongly consistent reads per second, or 20 eventually consistent reads per second, for items up to 4 KB.

Reading an item larger than 4 KB consumes more read capacity units. For example, a strongly consistent read of an item that is 8 KB ( $4\text{ KB} \times 2$ ) consumes 2 read capacity units. An eventually consistent read on that same item consumes only 1 read capacity unit.

Item sizes for reads are rounded up to the next 4 KB multiple. For example, reading a 3,500-byte item consumes the same throughput as reading a 4 KB item.

### Capacity unit consumption for reads

The following describes how DynamoDB read operations consume read capacity units:

- `GetItem`—Reads a single item from a table. To determine the number of capacity units that `GetItem` will consume, take the item size and round it up to the next 4 KB boundary. If you specified a strongly consistent read, this is the number of capacity units required. For an eventually consistent read (the default), divide this number by two.

For example, if you read an item that is 3.5 KB, DynamoDB rounds the item size to 4 KB. If you read an item of 10 KB, DynamoDB rounds the item size to 12 KB.

- `BatchGetItem`—Reads up to 100 items, from one or more tables. DynamoDB processes each item in the batch as an individual `GetItem` request, so DynamoDB first rounds up the size of each item to the next 4 KB boundary, and then calculates the total size. The result is not necessarily the same as the total size of all the items. For example, if `BatchGetItem` reads a 1.5 KB item and a 6.5 KB item, DynamoDB calculates the size as 12 KB ( $4\text{ KB} + 8\text{ KB}$ ), not 8 KB ( $1.5\text{ KB} + 6.5\text{ KB}$ ).

- **Query**—Reads multiple items that have the same partition key value. All items returned are treated as a single read operation, where DynamoDB computes the total size of all items and then rounds up to the next 4 KB boundary. For example, suppose your query returns 10 items whose combined size is 40.8 KB. DynamoDB rounds the item size for the operation to 44 KB. If a query returns 1500 items of 64 bytes each, the cumulative size is 96 KB.
- **Scan**—Reads all items in a table. DynamoDB considers the size of the items that are evaluated, not the size of the items returned by the scan.

If you perform a read operation on an item that does not exist, DynamoDB still consumes provisioned read throughput: A strongly consistent read request consumes one read capacity unit, while an eventually consistent read request consumes 0.5 of a read capacity unit.

For any operation that returns items, you can request a subset of attributes to retrieve. However, doing so has no impact on the item size calculations. In addition, `Query` and `Scan` can return item counts instead of attribute values. Getting the count of items uses the same quantity of read capacity units and is subject to the same item size calculations. This is because DynamoDB has to read each item in order to increment the count.

### Read operations and read consistency

The preceding calculations assume strongly consistent read requests. For an eventually consistent read request, the operation consumes only half the capacity units. For an eventually consistent read, if the total item size is 80 KB, the operation consumes only 10 capacity units.

## Write capacity units

A *write capacity unit* represents one write per second, for an item up to 1 KB in size.

For example, suppose that you create a table with 10 write capacity units. This allows you to perform 10 writes per second, for items up to 1 KB in size per second.

Item sizes for writes are rounded up to the next 1 KB multiple. For example, writing a 500-byte item consumes the same throughput as writing a 1 KB item.

### Capacity unit consumption for writes

The following describes how DynamoDB write operations consume write capacity units:

- `PutItem`—Writes a single item to a table. If an item with the same primary key exists in the table, the operation replaces the item. For calculating provisioned throughput consumption, the item size that matters is the larger of the two.
- `UpdateItem`—Modifies a single item in the table. DynamoDB considers the size of the item as it appears before and after the update. The provisioned throughput consumed reflects the larger of these item sizes. Even if you update just a subset of the item's attributes, `UpdateItem` will still consume the full amount of provisioned throughput (the larger of the "before" and "after" item sizes).
- `DeleteItem`—Removes a single item from a table. The provisioned throughput consumption is based on the size of the deleted item.
- `BatchWriteItem`—Writes up to 25 items to one or more tables. DynamoDB processes each item in the batch as an individual `PutItem` or `DeleteItem` request (updates are not supported). So DynamoDB first rounds up the size of each item to the next 1 KB boundary, and then calculates the total size. The result is not necessarily the same as the total size of all the items. For example, if `BatchWriteItem` writes a 500-byte item and a 3.5 KB item, DynamoDB calculates the size as 5 KB (1 KB + 4 KB), not 4 KB (500 bytes + 3.5 KB).

For `PutItem`, `UpdateItem`, and `DeleteItem` operations, DynamoDB rounds the item size up to the next 1 KB. For example, if you put or delete an item of 1.6 KB, DynamoDB rounds the item size up to 2 KB.

`PutItem`, `UpdateItem`, and `DeleteItem` allow *conditional writes*, where you specify an expression that must evaluate to true in order for the operation to succeed. If the expression evaluates to false, DynamoDB still consumes write capacity units from the table:

- For an existing item, the number of write capacity units consumed depends on the size of the new item. (For example, a failed conditional write of a 1 KB item would consume one write capacity unit. If the new item were twice that size, the failed conditional write would consume two write capacity units.)
- For a new item, DynamoDB consumes one write capacity unit.

## Request throttling and burst capacity

If your application performs reads or writes at a higher rate than your table can support, DynamoDB begins to *throttle* those requests. When DynamoDB throttles a read or write, it returns a `ProvisionedThroughputExceededException` to the caller. The application can then take appropriate action, such as waiting for a short interval before retrying the request.

### Note

We recommend that you use the AWS SDKs for software development. The AWS SDKs provide built-in support for retrying throttled requests; you do not need to write this logic yourself. For more information, see [Error retries and exponential backoff \(p. 168\)](#).

The DynamoDB console displays Amazon CloudWatch metrics for your tables, so you can monitor throttled read requests and write requests. If you encounter excessive throttling, you should consider increasing your table's provisioned throughput settings.

In some cases, DynamoDB uses *burst capacity* to accommodate reads or writes in excess of your table's throughput settings. With burst capacity, unexpected read or write requests can succeed where they otherwise would be throttled. For more information, see [Using burst capacity effectively \(p. 1165\)](#).

## Request throttling and adaptive capacity

DynamoDB automatically distributes your data across partitions, which are stored on multiple servers in the AWS Cloud (For more information, see [Partitions and data distribution \(p. 22\)](#)). It's not always possible to distribute read and write activity evenly all the time. When data access is imbalanced, a "hot" partition can receive such a higher volume of read and write traffic compared to other partitions. Adaptive capacity works by automatically increasing throughput capacity for partitions that receive more traffic. For more information, see [Understanding DynamoDB adaptive capacity \(p. 1165\)](#).

## Choosing initial throughput settings

Every application has different requirements for reading and writing from a database. When you are determining the initial throughput settings for a DynamoDB table, take the following inputs into consideration:

- **Item sizes.** Some items are small enough that they can be read or written using a single capacity unit. Larger items require multiple capacity units. By estimating the sizes of the items that will be in your table, you can specify accurate settings for your table's provisioned throughput.
- **Expected read and write request rates.** In addition to item size, you should estimate the number of reads and writes you need to perform per second.
- **Read consistency requirements.** Read capacity units are based on strongly consistent read operations, which consume twice as many database resources as eventually consistent reads. You should determine whether your application requires strongly consistent reads, or whether it can relax this requirement and perform eventually consistent reads instead. (Read operations in DynamoDB are eventually consistent, by default. You can request strongly consistent reads for these operations if necessary.)

For example, suppose that you want to read 80 items per second from a table. The items are 3 KB in size, and you want strongly consistent reads. For this scenario, each read requires one provisioned read capacity unit. To determine this number, you divide the item size of the operation by 4 KB, and then round up to the nearest whole number, as in this example:

- $3 \text{ KB} / 4 \text{ KB} = 0.75$ , or **1** read capacity unit

For this scenario, you have to set the table's provisioned read throughput to 80 read capacity units:

- 1 read capacity unit per item  $\times$  80 reads per second = **80** read capacity units

Now suppose that you want to write 100 items per second to your table, and that the items are 512 bytes in size. For this scenario, each write requires one provisioned write capacity unit. To determine this number, you divide the item size of the operation by 1 KB, and then round up to the nearest whole number:

- $512 \text{ bytes} / 1 \text{ KB} = 0.5$ , or **1**

For this scenario, you would want to set the table's provisioned write throughput to 100 write capacity units:

- 1 write capacity unit per item  $\times$  100 writes per second = **100** write capacity units

**Note**

For recommendations on provisioned throughput and related topics, see [Best practices for designing and using partition keys effectively \(p. 1165\)](#).

## Modifying throughput settings

If you have enabled DynamoDB auto scaling for a table, then its throughput capacity is dynamically adjusted in response to actual usage. No manual intervention is required.

You can modify your table's provisioned throughput settings using the AWS Management Console or the `UpdateTable` operation. For more information about throughput increases and decreases per day, see [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#).

## DynamoDB Item sizes and formats

DynamoDB tables are schemaless, except for the primary key, so the items in a table can all have different attributes, sizes, and data types.

The total size of an item is the sum of the lengths of its attribute names and values, plus any applicable overhead as described below. You can use the following guidelines to estimate attribute sizes:

- Strings are Unicode with UTF-8 binary encoding. The size of a string is  $(\text{length of attribute name}) + (\text{number of UTF-8-encoded bytes})$ .
- Numbers are variable length, with up to 38 significant digits. Leading and trailing zeroes are trimmed. The size of a number is approximately  $(\text{length of attribute name}) + (1 \text{ byte per two significant digits}) + (1 \text{ byte})$ .
- A binary value must be encoded in base64 format before it can be sent to DynamoDB, but the value's raw byte length is used for calculating size. The size of a binary attribute is  $(\text{length of attribute name}) + (\text{number of raw bytes})$ .
- The size of a null attribute or a Boolean attribute is  $(\text{length of attribute name}) + (1 \text{ byte})$ .

- An attribute of type `List` or `Map` requires 3 bytes of overhead, regardless of its contents. The size of a `List` or `Map` is  $(\text{length of attribute name}) + \text{sum}(\text{size of nested elements}) + (3 \text{ bytes})$ . The size of an empty `List` or `Map` is  $(\text{length of attribute name}) + (3 \text{ bytes})$ .

**Note**

We recommend that you choose shorter attribute names rather than long ones. This helps you reduce the amount of storage required, but also can lower the amount of RCU/WCUs you use.

For storage billing purposes, each item includes a per-item storage overhead that depends on the features you have enabled.

- All items in DynamoDB require 100 bytes of storage overhead for indexing.
- Some DynamoDB features (global tables, transactions, change data capture for Kinesis Data Streams with DynamoDB) require additional storage overhead to account for system-created attributes resulting from enabling those features. For example, global tables requires an additional 48 bytes of storage overhead.

## Managing throughput capacity automatically with DynamoDB auto scaling

Many database workloads are cyclical in nature or are difficult to predict in advance. For example, consider a social networking app where most of the users are active during daytime hours. The database must be able to handle the daytime activity, but there's no need for the same levels of throughput at night. Another example might be a new mobile gaming app that is experiencing rapid adoption. If the game becomes too popular, it could exceed the available database resources, resulting in slow performance and unhappy customers. These kinds of workloads often require manual intervention to scale database resources up or down in response to varying usage levels.

Amazon DynamoDB auto scaling uses the AWS Application Auto Scaling service to dynamically adjust provisioned throughput capacity on your behalf, in response to actual traffic patterns. This enables a table or a global secondary index to increase its provisioned read and write capacity to handle sudden increases in traffic, without throttling. When the workload decreases, Application Auto Scaling decreases the throughput so that you don't pay for unused provisioned capacity.

**Note**

If you use the AWS Management Console to create a table or a global secondary index, DynamoDB auto scaling is enabled by default. You can modify your auto scaling settings at any time. For more information, see [Using the AWS Management Console with DynamoDB auto scaling \(p. 294\)](#).

When you delete a table or global table replica, any associated scalable targets, scaling policies or CloudWatch alarms are not automatically deleted with it.

With Application Auto Scaling, you create a *scaling policy* for a table or a global secondary index. The scaling policy specifies whether you want to scale read capacity or write capacity (or both), and the minimum and maximum provisioned capacity unit settings for the table or index.

The scaling policy also contains a *target utilization*—the percentage of consumed provisioned throughput at a point in time. Application Auto Scaling uses a *target tracking* algorithm to adjust the provisioned throughput of the table (or index) upward or downward in response to actual workloads, so that the actual capacity utilization remains at or near your target utilization.

You can set the auto scaling target utilization values between 20 and 90 percent for your read and write capacity.

**Note**

In addition to tables, DynamoDB auto scaling also supports global secondary indexes. Every global secondary index has its own provisioned throughput capacity, separate from that of its


base table. When you create a scaling policy for a global secondary index, Application Auto Scaling adjusts the provisioned throughput settings for the index to ensure that its actual utilization stays at or near your desired utilization ratio.

## How DynamoDB auto scaling works

### Note

To get started quickly with DynamoDB auto scaling, see [Using the AWS Management Console with DynamoDB auto scaling \(p. 294\)](#).

The following diagram provides a high-level overview of how DynamoDB auto scaling manages throughput capacity for a table.



The following steps summarize the auto scaling process as shown in the previous diagram:

1. You create an Application Auto Scaling policy for your DynamoDB table.
2. DynamoDB publishes consumed capacity metrics to Amazon CloudWatch.
3. If the table's consumed capacity exceeds your target utilization (or falls below the target) for a specific length of time, Amazon CloudWatch triggers an alarm. You can view the alarm on the console and receive notifications using Amazon Simple Notification Service (Amazon SNS).
4. The CloudWatch alarm invokes Application Auto Scaling to evaluate your scaling policy.
5. Application Auto Scaling issues an `UpdateTable` request to adjust your table's provisioned throughput.
6. DynamoDB processes the `UpdateTable` request, dynamically increasing (or decreasing) the table's provisioned throughput capacity so that it approaches your target utilization.

To understand how DynamoDB auto scaling works, suppose that you have a table named `ProductCatalog`. The table is bulk-loaded with data infrequently, so it doesn't incur very much write activity. However, it does experience a high degree of read activity, which varies over time. By monitoring

the Amazon CloudWatch metrics for `ProductCatalog`, you determine that the table requires 1,200 read capacity units (to avoid DynamoDB throttling read requests when activity is at its peak). You also determine that `ProductCatalog` requires 150 read capacity units at a minimum, when read traffic is at its lowest point.

Within the range of 150 to 1,200 read capacity units, you decide that a target utilization of 70 percent would be appropriate for the `ProductCatalog` table. *Target utilization* is the ratio of consumed capacity units to provisioned capacity units, expressed as a percentage. Application Auto Scaling uses its target tracking algorithm to ensure that the provisioned read capacity of `ProductCatalog` is adjusted as required so that utilization remains at or near 70 percent.

**Note**

DynamoDB auto scaling modifies provisioned throughput settings only when the actual workload stays elevated (or depressed) for a sustained period of several minutes. The Application Auto Scaling target tracking algorithm seeks to keep the target utilization at or near your chosen value over the long term. Sudden, short-duration spikes of activity are accommodated by the table's built-in burst capacity. For more information, see [Using burst capacity effectively \(p. 1165\)](#).

To enable DynamoDB auto scaling for the `ProductCatalog` table, you create a scaling policy. This policy specifies the following:

- The table or global secondary index that you want to manage
- Which capacity type to manage (read capacity or write capacity)
- The upper and lower boundaries for the provisioned throughput settings
- Your target utilization

When you create a scaling policy, Application Auto Scaling creates a pair of Amazon CloudWatch alarms on your behalf. Each pair represents your upper and lower boundaries for provisioned throughput settings. These CloudWatch alarms are triggered when the table's actual utilization deviates from your target utilization for a sustained period of time.

When one of the CloudWatch alarms is triggered, Amazon SNS sends you a notification (if you have enabled it). The CloudWatch alarm then invokes Application Auto Scaling, which in turn notifies DynamoDB to adjust the `ProductCatalog` table's provisioned capacity upward or downward as appropriate.

## Usage notes

Before you begin using DynamoDB auto scaling, you should be aware of the following:

- DynamoDB auto scaling can increase read capacity or write capacity as often as necessary, in accordance with your auto scaling policy. All DynamoDB quotas remain in effect, as described in [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#).
- DynamoDB auto scaling doesn't prevent you from manually modifying provisioned throughput settings. These manual adjustments don't affect any existing CloudWatch alarms that are related to DynamoDB auto scaling.
- If you enable DynamoDB auto scaling for a table that has one or more global secondary indexes, we highly recommend that you also apply auto scaling uniformly to those indexes. You can do this by choosing **Apply same settings to global secondary indexes** in the AWS Management Console. For more information, see [Enabling DynamoDB auto scaling on existing tables \(p. 295\)](#).
- When you delete a table or global table replica, any associated scalable targets, scaling policies or CloudWatch alarms are not automatically deleted with it.
- When creating a GSI for an existing table, auto scaling is not enabled for the GSI. You will have to manually manage the capacity while the GSI is being built. Once the backfill on the GSI completes and it reaches active status, auto scaling will operate like normal.

## Using the AWS Management Console with DynamoDB auto scaling

When you use the AWS Management Console to create a new table, Amazon DynamoDB auto scaling is enabled for that table by default. You can also use the console to enable auto scaling for existing tables, modify auto scaling settings, or disable auto scaling.

### Note

For more advanced features like setting scale-in and scale-out cooldown times, use the AWS Command Line Interface (AWS CLI) to manage DynamoDB auto scaling. For more information, see [Using the AWS CLI to manage DynamoDB auto scaling \(p. 296\)](#).

### Topics

- [Before you begin: Granting user permissions for DynamoDB auto scaling \(p. 294\)](#)
- [Creating a new table with auto scaling enabled \(p. 294\)](#)
- [Enabling DynamoDB auto scaling on existing tables \(p. 295\)](#)
- [Viewing auto scaling activities on the console \(p. 296\)](#)
- [Modifying or disabling DynamoDB auto scaling settings \(p. 296\)](#)

### Before you begin: Granting user permissions for DynamoDB auto scaling

In AWS Identity and Access Management (IAM), the AWS managed policy `DynamoDBFullAccess` provides the required permissions for using the DynamoDB console. However, for DynamoDB auto scaling, IAM users require additional privileges.

### Important

`application-autoscaling:*` permissions are required to delete an auto scaling-enabled table. The AWS managed policy `DynamoDBFullAccess` includes such permissions.

To set up an IAM user for DynamoDB console access and DynamoDB auto scaling, add the following policy.

### To attach the `AmazonDynamoDBFullAccess` policy

1. Sign in to the AWS Management Console and open the IAM console at <https://console.aws.amazon.com/iam/>.
2. On the IAM console dashboard, choose **Users**, and then choose your IAM user from the list.
3. On the **Summary** page, choose **Add permissions**.
4. Choose **Attach existing policies directly**.
5. From the list of policies, choose `AmazonDynamoDBFullAccess`, and then choose **Next: Review**.
6. Choose **Add permissions**.

### Creating a new table with auto scaling enabled

### Note

DynamoDB auto scaling requires the presence of a service linked role (`AWSServiceRoleForApplicationAutoScaling_DynamoDBTable`) that performs auto scaling actions on your behalf. This role is created automatically for you. For more information, see [Service-linked roles for Application Auto Scaling](#) in the *Application Auto Scaling User Guide*.

### To create a new table with auto scaling enabled

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.

2. Choose **Create Table**.
3. On the **Create table** page, enter a **Table name** and primary key.
4. If **Default settings** is selected, the table will be created with auto scaling enabled.

Otherwise, for custom settings:

- a. Select **Customize settings**.
- b. In the **Read/write capacity settings** section, select **Provisioned** capacity mode and set **Auto scaling** to **On** for **Read capacity**, **Write capacity**, or both. For each of these, set your desired scaling policy for the table and, optionally, all global secondary indexes of the table.
  - **Minimum capacity units**—Enter your lower boundary for the auto scaling range.
  - **Maximum capacity units**—Enter your upper boundary for the auto scaling range.
  - **Target utilization**—Enter your target utilization percentage for the table.

#### Note

If you create a global secondary index for the new table, the index's capacity at time of creation will be the same as your base table's capacity. You can change the index's capacity in the table's settings after you create the table.

5. When the settings are as you want them, choose **Create table**. Your table is created with the auto scaling parameters.

## Enabling DynamoDB auto scaling on existing tables

#### Note

DynamoDB auto scaling requires the presence of a service linked role (`AWSServiceRoleForApplicationAutoScaling_DynamoDBTable`) that performs auto scaling actions on your behalf. This role is created automatically for you. For more information, see [Service-linked roles for Application Auto Scaling](#).

### To enable DynamoDB auto scaling for an existing table

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the table that you want to work with and select the **Additional settings** tab.
4. In the **Read/write capacity** section, select **Edit**.
5. In the **Capacity mode** section, select **Provisioned**.
6. In the **Table capacity** section, set **Auto scaling** to **On** for **Read capacity**, **Write capacity**, or both. For each of these, set your desired scaling policy for the table and, optionally, all global secondary indexes of the table.
  - **Minimum capacity units**—Enter your lower boundary for the auto scaling range.
  - **Maximum capacity units**—Enter your upper boundary for the auto scaling range.
  - **Target utilization**—Enter your target utilization percentage for the table.
  - **Use the same capacity read/write capacity settings for all global secondary indexes**—Choose whether global secondary indexes should use the same auto scaling policy as the base table.

#### Note

For best performance, we recommend that you enable **Use the same read/write capacity settings for all global secondary indexes**. This option allows DynamoDB auto scaling to uniformly scale all the global secondary indexes on the base table. This includes existing global secondary indexes, and any others that you create for this table in the future.

With this option enabled, you can't set a scaling policy on an individual global secondary index.

- When the settings are as you want them, choose **Save**.

## Viewing auto scaling activities on the console

As your application drives read and write traffic to your table, DynamoDB auto scaling dynamically modifies the table's throughput settings. Amazon CloudWatch keeps track of provisioned and consumed capacity, throttled events, latency, and other metrics for all of your DynamoDB tables and secondary indexes.

To view these metrics in the DynamoDB console, choose the table that you want to work with and select the **Monitor** tab. To create a customizable view of table metrics, select **View all in CloudWatch**.

For more information about CloudWatch monitoring in DynamoDB, see [Monitoring with Amazon CloudWatch \(p. 1114\)](#).

## Modifying or disabling DynamoDB auto scaling settings

You can use the AWS Management Console to modify your DynamoDB auto scaling settings. To do this, go to the **Additional settings** tab for your table, and select **Edit** in the **Read/write capacity** section. For more information about these settings, see [Enabling DynamoDB auto scaling on existing tables \(p. 295\)](#).

## Using the AWS CLI to manage DynamoDB auto scaling

Instead of using the AWS Management Console, you can use the AWS Command Line Interface (AWS CLI) to manage Amazon DynamoDB auto scaling. The tutorial in this section demonstrates how to install and configure the AWS CLI for managing DynamoDB auto scaling. In this tutorial, you do the following:

- Create a DynamoDB table named `TestTable`. The initial throughput settings are 5 read capacity units and 5 write capacity units.
- Create an Application Auto Scaling policy for `TestTable`. The policy seeks to maintain a 50 percent target ratio between consumed write capacity and provisioned write capacity. The range for this metric is between 5 and 10 write capacity units. (Application Auto Scaling is not allowed to adjust the throughput beyond this range.)
- Run a Python program to drive write traffic to `TestTable`. When the target ratio exceeds 50 percent for a sustained period of time, Application Auto Scaling notifies DynamoDB to adjust the throughput of `TestTable` upward to maintain the 50 percent target utilization.
- Verify that DynamoDB has successfully adjusted the provisioned write capacity for `TestTable`.

### Topics

- [Before you begin \(p. 296\)](#)
- [Step 1: Create a DynamoDB table \(p. 297\)](#)
- [Step 2: Register a scalable target \(p. 297\)](#)
- [Step 3: Create a scaling policy \(p. 298\)](#)
- [Step 4: Drive write traffic to TestTable \(p. 299\)](#)
- [Step 5: View Application Auto Scaling actions \(p. 300\)](#)
- [\(Optional\) Step 6: Clean up \(p. 300\)](#)

## Before you begin

Complete the following tasks before starting the tutorial.

## Install the AWS CLI

If you haven't already done so, you must install and configure the AWS CLI. To do this, follow these instructions in the *AWS Command Line Interface User Guide*:

- [Installing the AWS CLI](#)
- [Configuring the AWS CLI](#)

## Install Python

Part of this tutorial requires you to run a Python program (see [Step 4: Drive write traffic to TestTable \(p. 299\)](#)). If you don't already have it installed, you can [download Python](#).

## Step 1: Create a DynamoDB table

In this step, you use the AWS CLI to create `TestTable`. The primary key consists of `pk` (partition key) and `sk` (sort key). Both of these attributes are of type `Number`. The initial throughput settings are 5 read capacity units and 5 write capacity units.

1. Use the following AWS CLI command to create the table.

```
aws dynamodb create-table \  
    --table-name TestTable \  
    --attribute-definitions \  
        AttributeName=pk,AttributeType=N \  
        AttributeName=sk,AttributeType=N \  
    --key-schema \  
        AttributeName=pk,KeyType=HASH \  
        AttributeName=sk,KeyType=RANGE \  
    --provisioned-throughput ReadCapacityUnits=5,WriteCapacityUnits=5
```

2. To check the status of the table, use the following command.

```
aws dynamodb describe-table \  
    --table-name TestTable \  
    --query "Table.[TableName,TableStatus,ProvisionedThroughput]"
```

The table is ready for use when its status is `ACTIVE`.

## Step 2: Register a scalable target

Next you register the table's write capacity as a scalable target with Application Auto Scaling. This allows Application Auto Scaling to adjust the provisioned write capacity for `TestTable`, but only within the range of 5–10 capacity units.

### Note

DynamoDB auto scaling requires the presence of a service linked role (`AWSServiceRoleForApplicationAutoScaling_DynamoDBTable`) that performs auto scaling actions on your behalf. This role is created automatically for you. For more information, see [Service-linked roles for Application Auto Scaling](#) in the *Application Auto Scaling User Guide*.

1. Enter the following command to register the scalable target.

```
aws application-autoscaling register-scalable-target \  
    --service-namespace dynamodb \  
    --resource-id "table/TestTable" \  
    --scalable-dimension "dynamodb:table:WriteCapacityUnits" \  
    --min-capacity 5 \  
    --max-capacity 10
```

```
--max-capacity 10
```

2. To verify the registration, use the following command.

```
aws application-autoscaling describe-scalable-targets \
--service-namespace dynamodb \
--resource-id "table/TestTable"
```

**Note**

You can also register a scalable target against a global secondary index. For example, for a global secondary index ("test-index"), the resource ID and scalable dimension arguments are updated appropriately.

```
aws application-autoscaling register-scalable-target \
--service-namespace dynamodb \
--resource-id "table/TestTable/index/test-index" \
--scalable-dimension "dynamodb:index:WriteCapacityUnits" \
--min-capacity 5 \
--max-capacity 10
```

## Step 3: Create a scaling policy

In this step, you create a scaling policy for `TestTable`. The policy defines the details under which Application Auto Scaling can adjust your table's provisioned throughput, and what actions to take when it does so. You associate this policy with the scalable target that you defined in the previous step (write capacity units for the `TestTable` table).

The policy contains the following elements:

- `PredefinedMetricSpecification`—The metric that Application Auto Scaling is allowed to adjust. For DynamoDB, the following values are valid values for `PredefinedMetricType`:
  - `DynamoDBReadCapacityUtilization`
  - `DynamoDBWriteCapacityUtilization`
- `ScaleOutCooldown`—The minimum amount of time (in seconds) between each Application Auto Scaling event that increases provisioned throughput. This parameter allows Application Auto Scaling to continuously, but not aggressively, increase the throughput in response to real-world workloads. The default setting for `ScaleOutCooldown` is 0.
- `ScaleInCooldown`—The minimum amount of time (in seconds) between each Application Auto Scaling event that decreases provisioned throughput. This parameter allows Application Auto Scaling to decrease the throughput gradually and predictably. The default setting for `ScaleInCooldown` is 0.
- `TargetValue`—Application Auto Scaling ensures that the ratio of consumed capacity to provisioned capacity stays at or near this value. You define `TargetValue` as a percentage.

**Note**

To further understand how `TargetValue` works, suppose that you have a table with a provisioned throughput setting of 200 write capacity units. You decide to create a scaling policy for this table, with a `TargetValue` of 70 percent.

Now suppose that you begin driving write traffic to the table so that the actual write throughput is 150 capacity units. The consumed-to-provisioned ratio is now (150 / 200), or 75 percent. This ratio exceeds your target, so Application Auto Scaling increases the provisioned write capacity to 215 so that the ratio is (150 / 215), or 69.77 percent—as close to your `TargetValue` as possible, but not exceeding it.

For `TestTable`, you set `TargetValue` to 50 percent. Application Auto Scaling adjusts the table's provisioned throughput within the range of 5–10 capacity units (see [Step 2: Register a scalable](#)

[target \(p. 297\)](#)) so that the consumed-to-provisioned ratio remains at or near 50 percent. You set the values for `ScaleOutCooldown` and `ScaleInCooldown` to 60 seconds.

1. Create a file named `scaling-policy.json` with the following contents.

```
{
    "PredefinedMetricSpecification": {
        "PredefinedMetricType": "DynamoDBWriteCapacityUtilization"
    },
    "ScaleOutCooldown": 60,
    "ScaleInCooldown": 60,
    "TargetValue": 50.0
}
```

2. Use the following AWS CLI command to create the policy.

```
aws application-autoscaling put-scaling-policy \
--service-namespace dynamodb \
--resource-id "table/TestTable" \
--scalable-dimension "dynamodb:table:WriteCapacityUnits" \
--policy-name "MyScalingPolicy" \
--policy-type "TargetTrackingScaling" \
--target-tracking-scaling-policy-configuration file://scaling-policy.json
```

3. In the output, note that Application Auto Scaling has created two Amazon CloudWatch alarms—one each for the upper and lower boundary of the scaling target range.
4. Use the following AWS CLI command to view more details about the scaling policy.

```
aws application-autoscaling describe-scaling-policies \
--service-namespace dynamodb \
--resource-id "table/TestTable" \
--policy-name "MyScalingPolicy"
```

5. In the output, verify that the policy settings match your specifications from [Step 2: Register a scalable target \(p. 297\)](#) and [Step 3: Create a scaling policy \(p. 298\)](#).

## Step 4: Drive write traffic to TestTable

Now you can test your scaling policy by writing data to `TestTable`. To do this, you run a Python program.

1. Create a file named `bulk-load-test-table.py` with the following contents.

```
import boto3
dynamodb = boto3.resource('dynamodb')

table = dynamodb.Table("TestTable")

filler = "x" * 100000

i = 0
while (i < 10):
    j = 0
    while (j < 10):
        print (i, j)

        table.put_item(
            Item={
                'pk':i,
                'sk':j,
```

```
        'filler':{"S":filler}
    }
)
j += 1
i += 1
```

2. Enter the following command to run the program.

```
python bulk-load-test-table.py
```

The provisioned write capacity for `TestTable` is very low (5 write capacity units), so the program stalls occasionally due to write throttling. This is expected behavior.

Let the program continue running while you move on to the next step.

## Step 5: View Application Auto Scaling actions

In this step, you view the Application Auto Scaling actions that are initiated on your behalf. You also verify that Application Auto Scaling has updated the provisioned write capacity for `TestTable`.

1. Enter the following command to view the Application Auto Scaling actions.

```
aws application-autoscaling describe-scaling-activities \
--service-namespace dynamodb
```

Rerun this command occasionally, while the Python program is running. (It takes several minutes before your scaling policy is invoked.) You should eventually see the following output.

```
...
{
    "ScalableDimension": "dynamodb:table:WriteCapacityUnits",
    "Description": "Setting write capacity units to 10.",
    "ResourceId": "table/TestTable",
    "ActivityId": "0cc6fb03-2a7c-4b51-b67f-217224c6b656",
    "StartTime": 1489088210.175,
    "ServiceNamespace": "dynamodb",
    "EndTime": 1489088246.85,
    "Cause": "monitor alarm AutoScaling-table/TestTable-AlarmHigh-1bb3c8db-1b97-4353-
baf1-4def76f4e1b9 in state ALARM triggered policy MyScalingPolicy",
    "StatusMessage": "Successfully set write capacity units to 10. Change successfully
fulfilled by dynamodb.",
    "StatusCode": "Successful"
},
```

- This indicates that Application Auto Scaling has issued an `UpdateTable` request to DynamoDB.
2. Enter the following command to verify that DynamoDB increased the table's write capacity.

```
aws dynamodb describe-table \
--table-name TestTable \
--query "Table.[TableName,TableStatus,ProvisionedThroughput]"
```

The `WriteCapacityUnits` should have been scaled from 5 to 10.

## (Optional) Step 6: Clean up

In this tutorial, you created several resources. You can delete these resources if you no longer need them.

1. Delete the scaling policy for TestTable.

```
aws application-autoscaling delete-scaling-policy \
--service-namespace dynamodb \
--resource-id "table/TestTable" \
--scalable-dimension "dynamodb:table:WriteCapacityUnits" \
--policy-name "MyScalingPolicy"
```

2. Deregister the scalable target.

```
aws application-autoscaling deregister-scaling-target \
--service-namespace dynamodb \
--resource-id "table/TestTable" \
--scalable-dimension "dynamodb:table:WriteCapacityUnits"
```

3. Delete the TestTable table.

```
aws dynamodb delete-table --table-name TestTable
```

## Using the AWS SDK to configure Auto Scaling on Amazon DynamoDB tables

In addition to using the AWS Management Console and the AWS Command Line Interface (AWS CLI), you can write applications that interact with Amazon DynamoDB auto scaling. This section contains two Java programs that you can use to test this functionality:

- `EnableDynamoDBAutoscaling.java`
- `DisableDynamoDBAutoscaling.java`

### Enabling Application Auto Scaling for a table

The following program shows an example of setting up an auto scaling policy for a DynamoDB table (TestTable). It proceeds as follows:

- The program registers write capacity units as a scalable target for TestTable. The range for this metric is between 5 and 10 write capacity units.
- After the scalable target is created, the program builds a target tracking configuration. The policy seeks to maintain a 50 percent target ratio between consumed write capacity and provisioned write capacity.
- The program then creates the scaling policy, based on the target tracking configuration.

#### Note

When you manually remove a table or global table replica, you do not automatically remove any associated scalable targets, scaling policies, or CloudWatch alarms.

The program requires that you provide an Amazon Resource Name (ARN) for a valid Application Auto Scaling service linked role. (For example: `arn:aws:iam::122517410325:role/AWSServiceRoleForApplicationAutoScaling_DynamoDBTable`.) In the following program, replace `SERVICE_ROLE_ARN_Goes_Here` with the actual ARN.

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 */
```

```

/*
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
package com.amazonaws.codesamples.autoscaling;

import com.amazonaws.services.applicationautoscaling.AWSApplicationAutoScalingClient;
import
com.amazonaws.services.applicationautoscaling.AWSApplicationAutoScalingClientBuilder;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalableTargetsRequest;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalableTargetsResult;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalingPoliciesRequest;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalingPoliciesResult;
import com.amazonaws.services.applicationautoscaling.model.MetricType;
import com.amazonaws.services.applicationautoscaling.model.PolicyType;
import com.amazonaws.services.applicationautoscaling.model.PredefinedMetricSpecification;
import com.amazonaws.services.applicationautoscaling.model.PutScalingPolicyRequest;
import com.amazonaws.services.applicationautoscaling.model.RegisterScalableTargetRequest;
import com.amazonaws.services.applicationautoscaling.model.ScalableDimension;
import com.amazonaws.services.applicationautoscaling.model.ServiceNamespace;
import
com.amazonaws.services.applicationautoscaling.model.TargetTrackingScalingPolicyConfiguration;

public class EnableDynamoDBAutoscaling {

    static AWSApplicationAutoScalingClient aaClient = (AWSApplicationAutoScalingClient)
AWSApplicationAutoScalingClientBuilder.standard().build();

    public static void main(String args[]) {

        ServiceNamespace ns = ServiceNamespace.Dynamodb;
        ScalableDimension tableWCUs = ScalableDimension.DynamodbTableWriteCapacityUnits;
        String resourceID = "table/TestTable";

        // Define the scalable target
        RegisterScalableTargetRequest rstRequest = new RegisterScalableTargetRequest()
            .withServiceNamespace(ns)
            .withResourceId(resourceID)
            .withScalableDimension(tableWCUs)
            .withMinCapacity(5)
            .withMaxCapacity(10)
            .withRoleARN("SERVICE_ROLE_ARN_Goes_Here");

        try {
            aaClient.registerScalableTarget(rstRequest);
        } catch (Exception e) {
            System.err.println("Unable to register scalable target: ");
            System.err.println(e.getMessage());
        }

        // Verify that the target was created
        DescribeScalableTargetsRequest dscRequest = new DescribeScalableTargetsRequest()
            .withServiceNamespace(ns)
            .withScalableDimension(tableWCUs)
            .withResourceIds(resourceID);
        try {
            DescribeScalableTargetsResult dsaResult =
aaClient.describeScalableTargets(dscRequest);
            System.out.println("DescribeScalableTargets result: ");
            System.out.println(dsaResult);
        }
    }
}

```

```

        System.out.println();
    } catch (Exception e) {
        System.err.println("Unable to describe scalable target: ");
        System.err.println(e.getMessage());
    }

System.out.println();

// Configure a scaling policy
TargetTrackingScalingPolicyConfiguration targetTrackingScalingPolicyConfiguration =
new TargetTrackingScalingPolicyConfiguration()
.withPredefinedMetricSpecification(
    new PredefinedMetricSpecification()
    .withPredefinedMetricType(MetricType. DynamoDBWriteCapacityUtilization))
.withTargetValue(50.0)
.withScaleInCooldown(60)
.withScaleOutCooldown(60);

// Create the scaling policy, based on your configuration
PutScalingPolicyRequest pspRequest = new PutScalingPolicyRequest()
.withServiceNamespace(ns)
.withScalableDimension(tableWCUs)
.withResourceId(resourceID)
.withPolicyName("MyScalingPolicy")
.withPolicyType(PolicyType.TargetTrackingScaling)
.withTargetTrackingScalingPolicyConfiguration(targetTrackingScalingPolicyConfiguration);

try {
    aaClient.putScalingPolicy(pspRequest);
} catch (Exception e) {
    System.err.println("Unable to put scaling policy: ");
    System.err.println(e.getMessage());
}

// Verify that the scaling policy was created
DescribeScalingPoliciesRequest dspRequest = new DescribeScalingPoliciesRequest()
.withServiceNamespace(ns)
.withScalableDimension(tableWCUs)
.withResourceId(resourceID);

try {
    DescribeScalingPoliciesResult dspResult =
aaClient.describeScalingPolicies(dspRequest);
    System.out.println("DescribeScalingPolicies result: ");
    System.out.println(dspResult);
} catch (Exception e) {
    e.printStackTrace();
    System.err.println("Unable to describe scaling policy: ");
    System.err.println(e.getMessage());
}

}

```

## Disabling Application Auto Scaling for a table

The following program reverses the previous process. It removes the auto scaling policy and then deregisters the scalable target.

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 */
```

```

/*
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
package com.amazonaws.codesamples.autoscaling;

import com.amazonaws.services.applicationautoscaling.AWSApplicationAutoScalingClient;
import com.amazonaws.services.applicationautoscaling.model.DeleteScalingPolicyRequest;
import com.amazonaws.services.applicationautoscaling.model.DeregisterScalableTargetRequest;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalableTargetsRequest;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalableTargetsResult;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalingPoliciesRequest;
import com.amazonaws.services.applicationautoscaling.model.DescribeScalingPoliciesResult;
import com.amazonaws.services.applicationautoscaling.model.ScalableDimension;
import com.amazonaws.services.applicationautoscaling.model.ServiceNamespace;

public class DisableDynamoDBAutoscaling {

    static AWSApplicationAutoScalingClient aaClient = new
AWSApplicationAutoScalingClient();

    public static void main(String args[]) {

        ServiceNamespace ns = ServiceNamespace.Dynamodb;
        ScalableDimension tableWCUs = ScalableDimension.DynamodbTableWriteCapacityUnits;
        String resourceID = "table/TestTable";

        // Delete the scaling policy
        DeleteScalingPolicyRequest delSPRequest = new DeleteScalingPolicyRequest()
            .withServiceNamespace(ns)
            .withScalableDimension(tableWCUs)
            .withResourceId(resourceID)
            .withPolicyName("MyScalingPolicy");

        try {
            aaClient.deleteScalingPolicy(delSPRequest);
        } catch (Exception e) {
            System.err.println("Unable to delete scaling policy: ");
            System.err.println(e.getMessage());
        }

        // Verify that the scaling policy was deleted
        DescribeScalingPoliciesRequest descSPRequest = new DescribeScalingPoliciesRequest()
            .withServiceNamespace(ns)
            .withScalableDimension(tableWCUs)
            .withResourceId(resourceID);

        try {
            DescribeScalingPoliciesResult dspResult =
aaClient.describeScalingPolicies(descSPRequest);
            System.out.println("DescribeScalingPolicies result: ");
            System.out.println(dspResult);
        } catch (Exception e) {
            e.printStackTrace();
            System.err.println("Unable to describe scaling policy: ");
            System.err.println(e.getMessage());
        }

        System.out.println();
    }
}

```

```
// Remove the scalable target
DeregisterScalableTargetRequest delSTRequest = new DeregisterScalableTargetRequest()
    .withServiceNamespace(ns)
    .withScalableDimension(tableWCUs)
    .withResourceId(resourceID);

try {
    aaClient.deregisterScalableTarget(delSTRequest);
} catch (Exception e) {
    System.err.println("Unable to deregister scalable target: ");
    System.err.println(e.getMessage());
}

// Verify that the scalable target was removed
DescribeScalableTargetsRequest dscRequest = new DescribeScalableTargetsRequest()
    .withServiceNamespace(ns)
    .withScalableDimension(tableWCUs)
    .withResourceIds(resourceID);

try {
    DescribeScalableTargetsResult dsaResult =
aaClient.describeScalableTargets(dscRequest);
    System.out.println("DescribeScalableTargets result: ");
    System.out.println(dsaResult);
    System.out.println();
} catch (Exception e) {
    System.err.println("Unable to describe scalable target: ");
    System.err.println(e.getMessage());
}

}
```

## Global tables - multi-Region replication for DynamoDB

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\)](#) (p. 308) and [Version 2017.11.29](#) (p. 319). To find out which version you are using, see [Determining the version](#) (p. 307).

Amazon DynamoDB *global tables* provide a fully managed solution for deploying a multi-Region, multi-active database, without having to build and maintain your own replication solution. You can specify the AWS Regions where you want the tables to be available and DynamoDB will propagate ongoing data changes to all of them.

DynamoDB global tables are ideal for massively scaled applications with globally dispersed users. In such an environment, users expect very fast application performance. Global tables provide automatic multi-active replication to AWS Regions worldwide. They enable you to deliver low-latency data access to your users no matter where they are located.

The following video will give you an introductory look at global tables.

### Global tables for inter-Regional replication

#### Topics

- [Replicate data seamlessly across Regions with global tables](#) (p. 306)

- [Provide security and access for your global tables with AWS KMS \(p. 306\)](#)
- [Determining the global table version you are using \(p. 307\)](#)
- [Version 2019.11.21 \(Current\) \(p. 308\)](#)
- [Version 2017.11.29 \(p. 319\)](#)

## Replicate data seamlessly across Regions with global tables

Suppose you have a large customer base spread across three geographic areas—the US East Coast, the US West Coast, and Western Europe. These customers can update their profile information using your application. To satisfy this use case, you need to create three identical DynamoDB tables named `CustomerProfiles`, in three different AWS Regions where the customers are located. These three tables would be entirely separate from each other—changes to the data in one table would not be reflected in the others. Without a managed replication solution, you would have to write code to replicate the data changes. However, doing this would be a time-consuming and labor-intensive effort.

Instead of writing your own code, you could create a global table consisting of your three Region-specific `CustomerProfiles` tables. DynamoDB would then automatically replicate data changes among those tables so that changes to `CustomerProfiles` data in one Region would seamlessly propagate to the other Regions. In addition, if one of the AWS Regions were to become temporarily unavailable, your customers could still access the same `CustomerProfiles` data in the other Regions.

If the replicas in different regions have different access patterns, each replica can use a different table class to optimize cost and performance. For example, an infrequently accessed replica can use the DynamoDB Standard-Infrequent Access table class, while other replicas use the DynamoDB Standard table class for frequently-accessed data, where throughput is the dominant cost.

### Note

- Region support for global tables [Version 2017.11.29 \(p. 319\)](#) is limited to US East (N. Virginia), US East (Ohio), US West (N. California), US West (Oregon), Europe (Ireland), Europe (London), Europe (Frankfurt), Asia Pacific (Singapore), Asia Pacific (Sydney), Asia Pacific (Tokyo), and Asia Pacific (Seoul).
- Transactional operations provide atomicity, consistency, isolation, and durability (ACID) guarantees only within the region where the write is made originally. Transactions are not supported across regions in global tables. For example, if you have a global table with replicas in the US East (Ohio) and US West (Oregon) regions and perform a `TransactWriteItems` operation in the US East (N. Virginia) Region, you may observe partially completed transactions in US West (Oregon) Region as changes are replicated. Changes will only be replicated to other regions once they have been committed in the source region.
- If you [disable an AWS Region](#), DynamoDB will remove this replica from the replication group, 20 hours after detecting the AWS Region as inaccessible. The replica will not be deleted and replication will stop from and to this region.
- You must wait 24 hours from the time you add a read replica to successfully delete a source table. If you attempt to delete a table during the first 24 hours after adding a read replica, you will receive an error message stating: "Replica cannot be deleted because it has acted as a source region for new replicas being added in the table in the last 24 hours".

For information about the AWS Region availability and pricing, see [Amazon DynamoDB Pricing](#).

## Provide security and access for your global tables with AWS KMS

- You can perform AWS KMS operations on your global tables by using the `AWSServiceRoleForDynamoDBReplication` service-linked role against the [customer managed key](#) or the [AWS managed key](#) used to encrypt the replica.

- If the customer managed key used to encrypt a replica is inaccessible, DynamoDB will remove this replica from the replication group. The replica will not be deleted and replication will stop from and to this region, 20 hours after detecting the KMS key as inaccessible.
- If you want to disable your [customer managed key](#) that is used to encrypt a replica table, you must do so only if the key is no longer used to encrypt a replica table. After issuing a command to delete a replica table, you must wait for the delete operation to complete and for the global table to become Active before disabling the key. Not doing so could result in partial data replication from and to the replica table.
- If you want to modify or delete your IAM role policy for the replica table, you must do so when the replica table is in the Active state. If you don't do this, creating, updating, or deleting the replica table could fail.

**Note**

Customer Managed Key (CMK) is not supported in [Version 2017.11.29 \(p. 319\)](#). If you want to use a CMK in a DynamoDB Global Table, you need to upgrade the table to [Version 2019.11.21 \(Current\) \(p. 308\)](#) and then enable it.

## Determining the global table version you are using

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). We recommend using [Version 2019.11.21 \(Current\) \(p. 308\)](#) of global tables, which enables you to dynamically add new replica tables from a table populated with data. [Version 2019.11.21 \(Current\) \(p. 308\)](#) is more efficient and consumes less write capacity than [Version 2017.11.29 \(p. 319\)](#).

To find out which version of global tables you are using, do the following:

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/home>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the table you want to use.
4. Choose the **Global Tables** tab.
5. The **Global table version** displays the version of global tables in use.

 You are using global tables version 2019.11.21. If you need to use version 2017.11.29 instead, choose "Create version 2017.11.29 replica." You can create a version 2017.11.29 replica only if you have an empty table.

[Create a version 2017.11.29 replica.](#)

**Note**

- If you are using [Version 2019.11.21 \(Current\) \(p. 308\)](#) of global tables and you also use the [Time to Live](#) feature, DynamoDB replicates TTL deletes to all replica tables. The initial TTL delete does not consume write capacity in the region in which the TTL expiry occurs. However, the replicated TTL delete to the replica table(s) consumes a replicated write capacity unit when using provisioned capacity, or replicated write when using on-demand capacity mode, in each of the replica regions and applicable charges will apply.
- In [Version 2019.11.21 \(Current\) \(p. 308\)](#), when a TTL delete occurs it is replicated to all replica regions. These replicated writes do not contain `type` or `principalID` properties. This can make it difficult to distinguish a TTL delete from a user delete in the replicated tables.

## Version 2019.11.21 (Current)

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

### Topics

- [Global tables: How it works \(p. 308\)](#)
- [Best practices and requirements for managing global tables \(p. 309\)](#)
- [Tutorial: Creating a global table \(p. 310\)](#)
- [Monitoring global tables \(p. 314\)](#)
- [Using IAM with global tables \(p. 314\)](#)
- [Updating global tables to version 2019.11.21 \(current\) \(p. 317\)](#)

## Global tables: How it works

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

The following sections help you understand the concepts and behavior of global tables in Amazon DynamoDB.

### Global table concepts

A *global table* is a collection of one or more replica tables, all owned by a single AWS account.

A *replica table* (or *replica*, for short) is a single DynamoDB table that functions as a part of a global table. Each replica stores the same set of data items. Any given global table can only have one replica table per AWS Region. For more information about how to get started with global tables, see [Tutorial: Creating a global table \(p. 310\)](#).

When you create a DynamoDB global table, it consists of multiple replica tables (one per Region) that DynamoDB treats as a single unit. Every replica has the same table name and the same primary key schema. When an application writes data to a replica table in one Region, DynamoDB propagates the write to the other replica tables in the other AWS Regions automatically.

You can add replica tables to the global table so that it can be available in additional Regions.

### Consistency and conflict resolution

Any changes made to any item in any replica table are replicated to all the other replicas within the same global table. In a global table, a newly written item is usually propagated to all replica tables within a second.

With a global table, each replica table stores the same set of data items. DynamoDB does not support partial replication of only some of the items.

An application can read and write data to any replica table. If your application only uses eventually consistent reads and only issues reads against one AWS Region, it will work without any modification.

However, if your application requires strongly consistent reads, it must perform all of its strongly consistent reads and writes in the same Region. DynamoDB does not support strongly consistent reads across Regions. Therefore, if you write to one Region and read from another Region, the read response might include stale data that doesn't reflect the results of recently completed writes in the other Region.

If applications update the same item in different Regions at about the same time, conflicts can arise. To help ensure eventual consistency, DynamoDB global tables use a *last writer wins* reconciliation between concurrent updates, in which DynamoDB makes a best effort to determine the last writer. With this conflict resolution mechanism, all the replicas will agree on the latest update and converge toward a state in which they all have identical data.

### Availability and durability

If a single AWS Region becomes isolated or degraded, your application can redirect to a different Region and perform reads and writes against a different replica table. You can apply custom business logic to determine when to redirect requests to other Regions.

If a Region becomes isolated or degraded, DynamoDB keeps track of any writes that have been performed but have not yet been propagated to all of the replica tables. When the Region comes back online, DynamoDB resumes propagating any pending writes from that Region to the replica tables in other Regions. It also resumes propagating writes from other replica tables to the Region that is now back online.

## Best practices and requirements for managing global tables

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\)](#) (p. 308) and [Version 2017.11.29](#) (p. 319). To find out which version you are using, see [Determining the version](#) (p. 307).

Using Amazon DynamoDB global tables, you can replicate your table data across AWS Regions. It is important that the replica tables and secondary indexes in your global table have identical write capacity settings to ensure proper replication of data.

### Warning

The table name for Global Tables must be unique within your AWS account.

### Requirements for Managing Capacity

A global table must have throughput capacity configured one of two ways:

1. On-demand capacity mode, measured in replicated write request units (rWRUs)
2. Provisioned capacity mode with auto scaling, measured in replicated write capacity units (rWCUs)

Using provisioned capacity mode with auto scaling or on-demand capacity mode helps ensure a global table has sufficient capacity to perform replicated writes to all regions of the global table.

### Note

Switching from one table capacity mode to the other capacity mode in any Region switches the mode for all replicas.

### Replicas and Calculating Write Units

For planning, you should take the number of writes that one Region will perform and add that to the number of writes happening for each other Region. This is critical as every write that is performed in one Region must also be performed in every replica Region. If you do not have enough capacity to handle all of the writes, capacity exceptions will occur. In addition, inter-regional replication wait times will rise.

For example, suppose that you expect 5 writes per second to your replica table in Ohio, 10 writes per second to your replica table in N. Virginia, and 5 writes per second to your replica table in Ireland. In this case, you should expect to consume 20 rWCUs or rWRUs in each Region: Ohio, N. Virginia, and Ireland. In other words, you should expect to consume 60 rWCUs total across all three Regions.

For details about provisioned capacity with auto scaling and DynamoDB, see [Managing throughput capacity automatically with DynamoDB auto scaling \(p. 291\)](#).

**Note**

If a table is running in provisioned capacity mode with auto scaling, replicas in each Region may have different auto scaling configurations. It is best practice to set the same auto scaling policy in all Regions.

## Tutorial: Creating a global table

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

This section describes how to create a global table using the Amazon DynamoDB console or the AWS Command Line Interface (AWS CLI).

### Topics

- [Creating a global table \(console\) \(p. 310\)](#)
- [Creating a global table \(AWS CLI\) \(p. 311\)](#)
- [Creating a global table \(Java\) \(p. 312\)](#)

### Creating a global table (console)

Follow these steps to create a global table using the console. The following example creates a global table with replica tables in United States and Europe.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/home>. For this example, choose the US East (Ohio) Region.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose **Create Table**.
  - a. For **Table name**, enter **Music**.
  - b. For **Partition key** enter **Artist**. For **Sort key** enter **SongTitle**. (**Artist** and **SongTitle** should both be strings.)

To create the table, choose **Create table**. This table serves as the first replica table in a new global table. It is the prototype for other replica tables that you add later.

4. Choose the **Global Tables** tab, and then choose **Create replica**.
5. From the **Available replication Regions** dropdown, choose **US West (Oregon)**.

The console checks to ensure that a table with the same name doesn't exist in the selected Region. If a table with the same name does exist, you must delete the existing table before you can create a new replica table in that Region.

6. Choose **Create Replica**. This starts the table creation process in US West (Oregon);

The **Global Table** tab for the selected table (and for any other replica tables) shows that the table has been replicated in multiple Regions.

7. Now add another Region so that your global table is replicated and synchronized across the United States and Europe. To do this, repeat step 5, but this time, specify **Europe (Frankfurt)** instead of **US West (Oregon)**.
8. You should still be using the AWS Management Console in the US East (Ohio) Region. Select **Items** in the left navigation menu, select the **Music** table, then choose **Create Item**.
  - a. For **Artist**, enter **item\_1**.
  - b. For **SongTitle**, enter **Song Value 1**.
  - c. To write the item, choose **Create item**.
9. After a short time, the item is replicated across all three Regions of your global table. To verify this, in the console, on the Region selector in the upper-right corner, choose **Europe (Frankfurt)**. The Music table in Europe (Frankfurt) should contain the new item.
10. Repeat step 9 and choose **US West (Oregon)** to verify replication in that region.

### [Creating a global table \(AWS CLI\)](#)

Follow these steps to create a global table **Music** using the AWS CLI. The following example creates a global table, with replica tables in the United States and in Europe.

1. Create a new table (**Music**) in US East (Ohio), with DynamoDB Streams enabled (**NEW\_AND\_OLD\_IMAGES**).

```
aws dynamodb create-table \
    --table-name Music \
    --attribute-definitions \
        AttributeName=Artist,AttributeType=S \
        AttributeName=SongTitle,AttributeType=S \
    --key-schema \
        AttributeName=Artist,KeyType=HASH \
        AttributeName=SongTitle,KeyType=RANGE \
    --billing-mode PAY_PER_REQUEST \
    --stream-specification StreamEnabled=true,StreamViewType=NEW_AND_OLD_IMAGES \
    --region us-east-2
```

2. Create an identical **Music** table in US East (N. Virginia).

```
aws dynamodb update-table --table-name Music --cli-input-json \
'{
    "ReplicaUpdates": [
        {
            "Create": {
                "RegionName": "us-east-1"
            }
        }
    ]
}' \
--region=us-east-2
```

3. Repeat step 2 to create a table in Europe (Ireland) (eu-west-1).
4. You can view the list of replicas created using **describe-table**.

```
aws dynamodb describe-table --table-name Music --region us-east-2
```

5. To verify that replication is working, add a new item to the **Music** table in US East (Ohio).

```
aws dynamodb put-item \
```

```
--table-name Music \
--item '{"Artist": {"S":"item_1"}, "SongTitle": {"S":"Song Value 1"}}' \
--region us-east-2
```

6. Wait for a few seconds, and then check to see whether the item has been successfully replicated to US East (N. Virginia) and Europe (Ireland).

```
aws dynamodb get-item \
--table-name Music \
--key '{"Artist": {"S":"item_1"}, "SongTitle": {"S":"Song Value 1"}}' \
--region us-east-1
```

```
aws dynamodb get-item \
--table-name Music \
--key '{"Artist": {"S":"item_1"}, "SongTitle": {"S":"Song Value 1"}}' \
--region eu-west-1
```

7. Delete the replica table in Europe (Ireland) Region.

```
aws dynamodb update-table --table-name Music --cli-input-json \
'{
    "ReplicaUpdates": [
        {
            "Delete": {
                "RegionName": "eu-west-1"
            }
        }
    ]
}'
```

## Creating a global table (Java)

The following java code sample, create a `Music` table in Europe (Ireland) region then creates a replica in Asia Pacific (Seoul) region.

```
package com.amazonaws.codesamples.gtv2
import java.util.logging.Logger;
import com.amazonaws.auth.profile.ProfileCredentialsProvider;
import com.amazonaws.regions.Regions;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.model.AmazonDynamoDBException;
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;
import com.amazonaws.services.dynamodbv2.model.BillingMode;
import com.amazonaws.services.dynamodbv2.model.CreateReplicationGroupMemberAction;
import com.amazonaws.services.dynamodbv2.model.CreateTableRequest;
import com.amazonaws.services.dynamodbv2.model.DescribeTableRequest;
import com.amazonaws.services.dynamodbv2.model.GlobalSecondaryIndex;
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;
import com.amazonaws.services.dynamodbv2.model.KeyType;
import com.amazonaws.services.dynamodbv2.model.Projection;
import com.amazonaws.services.dynamodbv2.model.ProjectionType;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughputOverride;
import com.amazonaws.services.dynamodbv2.model.ReplicaGlobalSecondaryIndex;
import com.amazonaws.services.dynamodbv2.model.ReplicationGroupUpdate;
import com.amazonaws.services.dynamodbv2.model.ScalarAttributeType;
import com.amazonaws.services.dynamodbv2.model.StreamSpecification;
import com.amazonaws.services.dynamodbv2.model.StreamViewType;
import com.amazonaws.services.dynamodbv2.model.UpdateTableRequest;
```

```

import com.amazonaws.waiters.WaiterParameters;

public class App
{
    private final static Logger LOGGER = Logger.getLogger(Logger.GLOBAL_LOGGER_NAME);

    public static void main( String[] args )
    {

        String tableName = "Music";
        String indexName = "index1";

        Regions calledRegion = Regions.EU_WEST_1;
        Regions destRegion = Regions.AP_NORTHEAST_2;

        AmazonDynamoDB ddbClient = AmazonDynamoDBClientBuilder.standard()
            .withCredentials(new ProfileCredentialsProvider("default"))
            .withRegion(calledRegion)
            .build();

        LOGGER.info("Creating a regional table - TableName: " + tableName + ", IndexName: "
+ indexName + " ....");
        ddbClient.createTable(new CreateTableRequest()
            .withTableName(tableName)
            .withAttributeDefinitions(
                new AttributeDefinition()

            .withAttributeName("Artist").withAttributeType(ScalarAttributeType.S),
                new AttributeDefinition()

            .withAttributeName("SongTitle").withAttributeType(ScalarAttributeType.S))
            .withKeySchema(
                new
            KeySchemaElement().withAttributeName("Artist").withKeyType(KeyType.HASH),
                new
            KeySchemaElement().withAttributeName("SongTitle").withKeyType(KeyType.RANGE))
            .withBillingMode(BillingMode.PAY_PER_REQUEST)
            .withGlobalSecondaryIndexes(new GlobalSecondaryIndex()
                .withIndexName(indexName)
                .withKeySchema(new KeySchemaElement()
                    .withAttributeName("SongTitle")
                    .withKeyType(KeyType.HASH)))
            .withProjection(new
        Projection().withProjectionType(ProjectionType.ALL)))
            .withStreamSpecification(new StreamSpecification()
                .withStreamEnabled(true)
                .withStreamViewType(StreamViewType.NEW_AND_OLD_IMAGES)));
        }

        LOGGER.info("Waiting for ACTIVE table status ....");
        ddbClient.waiters().tableExists().run(new WaiterParameters<>(new
DescribeTableRequest(tableName)));

        LOGGER.info("Testing parameters for adding a new Replica in " + destRegion +
" ....");

        CreateReplicationGroupMemberAction createReplicaAction = new
CreateReplicationGroupMemberAction()
            .withRegionName(destRegion.getName())
            .withGlobalSecondaryIndexes(new ReplicaGlobalSecondaryIndex()
                .withIndexName(indexName)
                .withProvisionedThroughputOverride(new
ProvisionedThroughputOverride()
                    .withReadCapacityUnits(15L))));
    }
}

```

```
        ddbClient.updateTable(new UpdateTableRequest()
            .withTableName(tableName)
            .withReplicaUpdates(new ReplicationGroupUpdate()
                .withCreate(createReplicaAction.withKMSMasterKeyId(null))));

    }
}
```

## Monitoring global tables

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

You can use Amazon CloudWatch to monitor the behavior and performance of a global table. Amazon DynamoDB publishes `ReplicationLatency` metric for each replica in the global table.

- **ReplicationLatency**—The elapsed time between when an item is written to a replica table, and when that item appears in another replica in the global table. `ReplicationLatency` is expressed in milliseconds and is emitted for every source- and destination-Region pair.

During normal operation, `ReplicationLatency` should be fairly constant. An elevated value for `ReplicationLatency` could indicate that updates from one replica are not propagating to other replica tables in a timely manner. Over time, this could result in other replica tables *falling behind* because they no longer receive updates consistently. In this case, you should verify that the read capacity units (RCUs) and write capacity units (WCUs) are identical for each of the replica tables. In addition, when choosing WCU settings, follow the recommendations in [Requirements for Managing Capacity \(p. 309\)](#).

`ReplicationLatency` can increase if an AWS Region becomes degraded and you have a replica table in that Region. In this case, you can temporarily redirect your application's read and write activity to a different AWS Region.

For more information, see [DynamoDB Metrics and dimensions \(p. 1114\)](#).

## Using IAM with global tables

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

When you create a global table for the first time, Amazon DynamoDB automatically creates an AWS Identity and Access Management (IAM) service-linked role for you. This role is named `AWSServiceRoleForDynamoDBReplication`, and it allows DynamoDB to manage cross-Region replication for global tables on your behalf. Don't delete this service-linked role. If you do, all of your global tables will no longer function.

For more information about service-linked roles, see [Using service-linked roles](#) in the *IAM User Guide*.

To create replica tables in DynamoDB, you must have the following permissions in the source region.

- dynamodb:UpdateTable

To create replica tables in DynamoDB, you must have the following permissions in destination regions.

- dynamodb:CreateTable
  - dynamodb:CreateTableReplica
  - dynamodb:Scan
  - dynamodb:Query
  - dynamodb:UpdateItem
  - dynamodb:PutItem
  - dynamodb:GetItem
  - dynamodb:DeleteItem
  - dynamodb:BatchWriteItem

To delete replica tables in DynamoDB, you must have the following permissions in the destination regions.

- dynamodb:DeleteTable
  - dynamodb:DeleteTableReplica

To update replica auto-scaling policy through `UpdateTableReplicaAutoScaling`, you must have the following permissions in all Regions where table replicas exist

- application-autoscaling:DeleteScalingPolicy
  - application-autoscaling:DeleteScheduledAction
  - application-autoscaling:DeregisterScalableTarget
  - application-autoscaling:DescribeScalableTargets
  - application-autoscaling:DescribeScalingActivities
  - application-autoscaling:DescribeScalingPolicies
  - application-autoscaling:DescribeScheduledActions
  - application-autoscaling:PutScalingPolicy
  - application-autoscaling:PutScheduledAction
  - application-autoscaling:RegisterScalableTarget

To use `UpdateTimeToLive` you must have permission for `dynamodb:UpdateTimeToLive` in all Regions where table replicas exist.

## Example: Add replica

The following IAM policy grants permissions to allow you to add replicas to a global table.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "VisualEditor0",  
            "Effect": "Allow".
```

```

        "Action": [
            "dynamodb CreateTable",
            "dynamodb DescribeTable",
            "dynamodb UpdateTable",
            "dynamodb CreateTableReplica",
            "iam CreateServiceLinkedRole"
        ],
        "Resource": "*"
    }
]
}

```

### Example: Update AutoScaling policy

The following IAM policy grants permissions to allow you to update replica auto-scaling policy.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "VisualEditor0",
            "Effect": "Allow",
            "Action": [
                "application-autoscaling:RegisterScalableTarget",
                "application-autoscaling>DeleteScheduledAction",
                "application-autoscaling:DescribeScalableTargets",
                "application-autoscaling:DescribeScalingActivities",
                "application-autoscaling:DescribeScalingPolicies",
                "application-autoscaling:PutScalingPolicy",
                "application-autoscaling:DescribeScheduledActions",
                "application-autoscaling:DeleteScalingPolicy",
                "application-autoscaling:PutScheduledAction",
                "application-autoscaling:DeregisterScalableTarget"
            ],
            "Resource": "*"
        }
    ]
}

```

### Example: Allow replica creations for a specific table name and regions

The following IAM policy grants permissions to allow table and replica creation for `Customers` table with replicas in three Regions.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "VisualEditor0",
            "Effect": "Allow",
            "Action": [
                "dynamodb CreateTable",
                "dynamodb DescribeTable",
                "dynamodb UpdateTable"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-east-1:123456789012:table/Customers",
                "arn:aws:dynamodb:us-west-1:123456789012:table/Customers",
                "arn:aws:dynamodb:eu-east-2:123456789012:table/Customers"
            ]
        }
    ]
}

```

}

## Updating global tables to version 2019.11.21 (current)

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

This section describes how to update your global tables to *version 2019.11.21 (current)*.

### Topics

- [Before you begin \(p. 317\)](#)
- [Updating to version 2019.11.21 \(current\) \(p. 318\)](#)

### Before you begin

DynamoDB global tables version 2019.11.21 (current) introduces the following requirements:

- The [global secondary indexes](#) on the replica tables must be consistent across Regions.
- The [encryption](#) setting on the replica tables must be consistent across Regions.
- The [Time to live \(TTL\)](#) settings on the replica tables must be consistent across Regions. If TTL is enabled on a replica table, TTL deletes are replicated.
- DynamoDB auto scaling or [on-demand](#) capacity must be enabled for write capacity units across all replica tables.
- Global tables control plane operations (create, delete, update, and describe) APIs differ. For more information, see [Global tables: Multi-Region replication with DynamoDB](#).

DynamoDB global tables version 2019.11.21 (current) introduces the following changes in behavior:

- DynamoDB Streams publishes only one record (instead of two) for each write.
- For new inserts, `aws:rep:*` attributes in the item record are not added.
- For updates to items that contain `aws:rep:*` attributes, those attributes are not updated.
- DynamoDB mapper must not require the `aws:rep:*` attributes for this table.
- When updating from version 2017.11.29 to version 2019.11.21, you might see an increase in the [ReplicationLatency](#) metric. This is expected because version 2019.11.21 (current) captures the full end-to-end measurement of replication delay between global tables Regions. For more information, see the [ReplicationLatency](#) documentation for version [Version 2017.11.29](#) and [Version 2019.11.21 \(current\)](#).

### Required permissions

To update to version 2019.11.21 (current), you must have `dynamodb:UpdateGlobalTableVersion` permissions across replica Regions. These permissions are in addition to the permissions needed for accessing the DynamoDB console and viewing tables.

The following IAM policy grants permissions to update any global table to version 2019.11.21 (current).

```
{  
    "Version": "2012-10-17",  
    "Statement": [
```

```
{
    "Effect": "Allow",
    "Action": "dynamodb:UpdateGlobalTableVersion",
    "Resource": "*"
}
]
```

The following IAM policy grants permissions to update only the `Music` global table, with replicas in two Regions, to version 2019.11.21 (current).

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": "dynamodb:UpdateGlobalTableVersion",
            "Resource": [
                "arn:aws:dynamodb::123456789012:global-table/Music",
                "arn:aws:dynamodb:ap-southeast-1:123456789012:table/Music",
                "arn:aws:dynamodb:us-east-2:123456789012:table/Music"
            ]
        }
    ]
}
```

### [Update process overview](#)

During the update process, the state of your global table changes from **ACTIVE** to **UPDATING**.

The process takes several minutes, but it should finish in less than an hour. During the update process, your table remains available for read and write traffic. However, auto scaling does not alter the provisioned capacity on your table during the update. As such, before you begin the update, we recommend that you switch your table to [on-demand](#) capacity.

If you choose to use [provisioned](#) capacity with auto scaling during the update, you must increase the minimum read and write throughput on your policies to accommodate expected increases in traffic for the duration of the update.

When the update process is complete, your table status returns to **ACTIVE**. You can check the state of your table by using `DescribeTable`, or verify it using the **Tables** view on the DynamoDB console.

#### **Important**


- Updating from version 2017.11.29 to version 2019.11.21 (current) is a one-time action and cannot be reversed. Before proceeding with the update, ensure that you have performed all necessary testing. Allow up to 60 minutes before attempting to update a newly created global table.
- In version 2017.11.29 of global tables, DynamoDB performed a write operation to insert three attributes into the item record. These attributes (`aws:rep:*`) were used to enact replication and manage conflict resolution. In version 2019.11.21 (current) of global tables, replication activity is managed natively and is not exposed to users.
- Updating to version 2019.11.21 (current) is only available through the DynamoDB console.

### [Updating to version 2019.11.21 \(current\)](#)

Follow these steps to update your version of DynamoDB global tables using the AWS Management Console.

### To update global tables to version 2019.11.21

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/home>.
2. In the navigation pane on the left side of the console, choose **Tables**, and then select the global table that you want to update to 2019.11.21 (current).
3. Choose the **Global Tables** tab.
4. Choose **Update version**.



5. Read and agree to the new requirements, and then choose **Update version**.

**Important**

Updating from version 2017.11.29 to version 2019.11.21 (current) is a one-time action and cannot be reversed. Before starting the update, ensure that you have performed all necessary testing.

6. After the update process is complete, the global tables version that appears on the console changes to **2019.11.21**.

## Version 2017.11.29

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

### Topics

- [Global tables: How it works \(p. 319\)](#)
- [Best practices and requirements for managing global tables \(p. 321\)](#)
- [Creating a global table \(p. 323\)](#)
- [Monitoring global tables \(p. 326\)](#)
- [Using IAM with global tables \(p. 327\)](#)

## Global tables: How it works

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

The following sections help you understand the concepts and behavior of global tables in Amazon DynamoDB.

### Global table concepts

A *global table* is a collection of one or more replica tables, all owned by a single AWS account.

A *replica table* (or *replica*, for short) is a single DynamoDB table that functions as a part of a global table. Each replica stores the same set of data items. Any given global table can only have one replica table per AWS Region.

The following is a conceptual overview of how a global table is created.

1. Create an ordinary DynamoDB table, with DynamoDB Streams enabled, in an AWS Region.
2. Repeat step 1 for every other Region where you want to replicate your data.
3. Define a DynamoDB global table based on the tables that you have created.

The AWS Management Console automates these tasks, so you can create a global table more quickly and easily. For more information, see [Creating a global table \(p. 323\)](#).

The resulting DynamoDB global table consists of multiple replica tables, one per Region, that DynamoDB treats as a single unit. Every replica has the same table name and the same primary key schema. When an application writes data to a replica table in one Region, DynamoDB automatically propagates the write to the other replica tables in the other AWS Regions.

#### Important

To keep your table data in sync, global tables automatically create the following attributes for every item:

- `aws:rep:deleting`
- `aws:rep:updatetime`
- `aws:rep:updateregion`

Do not modify these attributes or create attributes with the same name.

You can add replica tables to the global table so that it can be available in additional Regions. (To do this, the global table must be empty. In other words, none of the replica tables can have any data in them.)

You can also remove a replica table from a global table. If you do this, the table is completely disassociated from the global table. This newly independent table no longer interacts with the global table, and data is no longer propagated to or from the global table.

#### Warning

Be aware that removing a replica is not an atomic process. To ensure consistent behavior and known state, you may want to consider diverting your application write traffic away from the replica to be removed ahead of time. After removing it, wait until all replica region endpoints show the replica as disassociated before making any further writes to it as its own isolated regional table.

### Consistency and conflict resolution

Any changes made to any item in any replica table are replicated to all the other replicas within the same global table. In a global table, a newly written item is usually propagated to all replica tables within seconds.

With a global table, each replica table stores the same set of data items. DynamoDB does not support partial replication of only some of the items.

An application can read and write data to any replica table. If your application only uses eventually consistent reads and only issues reads against one AWS Region, it will work without any modification. However, if your application requires strongly consistent reads, it must perform all of its strongly consistent reads and writes in the same Region. DynamoDB does not support strongly consistent reads across Regions. Therefore, if you write to one Region and read from another Region, the read response might include stale data that doesn't reflect the results of recently completed writes in the other Region.

Conflicts can arise if applications update the same item in different Regions at about the same time. To help ensure eventual consistency, DynamoDB global tables use a *last writer wins* reconciliation between concurrent updates, in which DynamoDB makes a best effort to determine the last writer. With this conflict resolution mechanism, all the replicas will agree on the latest update and converge toward a state in which they all have identical data.

### Availability and durability

If a single AWS Region becomes isolated or degraded, your application can redirect to a different Region and perform reads and writes against a different replica table. You can apply custom business logic to determine when to redirect requests to other Regions.

If a Region becomes isolated or degraded, DynamoDB keeps track of any writes that have been performed but have not yet been propagated to all of the replica tables. When the Region comes back online, DynamoDB resumes propagating any pending writes from that Region to the replica tables in other Regions. It also resumes propagating writes from other replica tables to the Region that is now back online.

## Best practices and requirements for managing global tables

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

Using Amazon DynamoDB global tables, you can replicate your table data across AWS Regions. It is important that the replica tables and secondary indexes in your global table have identical write capacity settings to ensure proper replication of data.

### Topics

- [Requirements for adding a new replica table \(p. 321\)](#)
- [Best practices and requirements for managing capacity \(p. 322\)](#)

### Requirements for adding a new replica table

If you want to add a new replica table to a global table, each of the following conditions must be true:

- The table must have the same partition key as all of the other replicas.
- The table must have the same write capacity management settings specified.
- The table must have the same name as all of the other replicas.
- The table must have DynamoDB Streams enabled, with the stream containing both the new and the old images of the item.
- None of the new or existing replica tables in the global table can contain any data.

If global secondary indexes are specified, the following conditions must also be met:

- The global secondary indexes must have the same name.

- The global secondary indexes must have the same partition key and sort key (if present).

**Important**

Write capacity settings should be set consistently across all of your global tables' replica tables and matching secondary indexes. To update write capacity settings for your global table, we strongly recommend using the DynamoDB console or the `UpdateGlobalTableSettings` API operation. `UpdateGlobalTableSettings` applies changes to write capacity settings to all replica tables and matching secondary indexes in a global table automatically. If you use the `UpdateTable`, `RegisterScalableTarget`, or `PutScalingPolicy` operations, you should apply the change to each replica table and matching secondary index individually. For more information, see [UpdateGlobalTableSettings](#) in the [Amazon DynamoDB API Reference](#).

We strongly recommend that you enable auto scaling to manage provisioned write capacity settings. If you prefer to manage write capacity settings manually, you should provision equal replicated write capacity units to all of your replica tables. Also provision equal replicated write capacity units to matching secondary indexes across your global table.

You must also have appropriate AWS Identity and Access Management (IAM) permissions. For more information, see [Using IAM with global tables \(p. 327\)](#).

### Best practices and requirements for managing capacity

Consider the following when managing capacity settings for replica tables in DynamoDB.

#### Using DynamoDB auto scaling

Using DynamoDB auto scaling is the recommended way to manage throughput capacity settings for replica tables that use the provisioned mode. DynamoDB auto scaling automatically adjusts read capacity units (RCUs) and write capacity units (WCUs) for each replica table based upon your actual application workload. For more information, see [Managing throughput capacity automatically with DynamoDB auto scaling \(p. 291\)](#).

If you create your replica tables using the AWS Management Console, auto scaling is enabled by default for each replica table, with default auto scaling settings for managing read capacity units and write capacity units.

Changes to auto scaling settings for a replica table or secondary index made through the DynamoDB console or using the `UpdateGlobalTableSettings` call are applied to all of the replica tables and matching secondary indexes in the global table automatically. These changes overwrite any existing auto scaling settings. This ensures that provisioned write capacity settings are consistent across the replica tables and secondary indexes in your global table. If you use the `UpdateTable`, `RegisterScalableTarget`, or `PutScalingPolicy` calls, you should apply the change to each replica table and matching secondary index individually.

**Note**

If auto scaling doesn't satisfy your application's capacity changes (unpredictable workload), or if you don't want to configure its settings (target settings for minimum, maximum, or utilization threshold), you can use on-demand mode to manage capacity for your global tables. For more information, see [On-demand mode \(p. 18\)](#).

If you enable on-demand mode on a global table, your consumption of replicated write request units (rWCUs) will be consistent with how rWCUs are provisioned. For example, if you perform 10 writes to a local table that is replicated in two additional Regions, you will consume 60 write request units ( $10 + 10 + 10 = 30; 30 \times 2 = 60$ ). The consumed 60 write request units include the extra write consumed by global tables Version 2017.11.29 to update the `aws:rep:deleting`, `aws:rep:updatetime`, and `aws:rep:updateregion` attributes.

#### Managing capacity manually

If you decide not to use DynamoDB auto scaling, you must manually set the read capacity and write capacity settings on each replica table and secondary index.

The provisioned replicated write capacity units (rWCUs) on every replica table should be set to the total number of rWCUs needed for application writes across all Regions multiplied by two. This accommodates application writes that occur in the local Region and replicated application writes coming from other Regions. For example, suppose that you expect 5 writes per second to your replica table in Ohio and 5 writes per second to your replica table in N. Virginia. In this case, you should provision 20 WCUs to each replica table ( $5 + 5 = 10; 10 \times 2 = 20$ ).

To update write capacity settings for your global table, we strongly recommend using the DynamoDB console or the `UpdateGlobalTableSettings` API operation. `UpdateGlobalTableSettings` applies changes to write capacity settings to all replica tables and matching secondary indexes in a global table automatically. If you use the `UpdateTable`, `RegisterScalableTarget`, or `PutScalingPolicy` operations, you should apply the change to each replica table and matching secondary index individually. For more information, see [Amazon DynamoDB API Reference](#).

**Note**

To update the settings (`UpdateGlobalTableSettings`) for a global table in DynamoDB, you must have the `dynamodb:UpdateGlobalTable`, `dynamodb:DescribeLimits`, `application-autoscaling:DeleteScalingPolicy`, and `application-autoscaling:DeregisterScalableTarget` permissions. For more information, see [Using IAM with global tables \(p. 327\)](#).

## Creating a global table

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

This section describes how to create a global table using the Amazon DynamoDB console or the AWS Command Line Interface (AWS CLI).

### Topics

- [Creating a global table \(console\) \(p. 323\)](#)
- [Creating a global table \(AWS CLI\) \(p. 324\)](#)

### Creating a global table (console)

Follow these steps to create a global table using the console. The following example creates a global table with replica tables in United States and Europe.


1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/home>. For this example, choose the us-east-2 (US East Ohio) Region.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose **Create Table**.

For **Table name**, enter **Music**.

For **Primary key** enter **Artist**. Choose **Add sort key**, and enter **SongTitle**. (**Artist** and **SongTitle** should both be strings.)

To create the table, choose **Create**. This table serves as the first replica table in a new global table. It is the prototype for other replica tables that you add later.

4. Choose the **Global Tables** tab, and then choose **Create a version 2017.11.29 replica**.



- From the **Available replication Regions** dropdown, choose **US West (Oregon)**.

The console checks to ensure that a table with the same name doesn't exist in the selected Region. If a table with the same name does exist, you must delete the existing table before you can create a new replica table in that Region.

- Choose **Create Replica**. This starts the table creation process in US West (Oregon);

The **Global Table** tab for the selected table (and for any other replica tables) shows that the table has been replicated in multiple Regions.

- Now add another Region so that your global table is replicated and synchronized across the United States and Europe. To do this, repeat step 5, but this time, specify **Europe (Frankfurt)** instead of **US West (Oregon)**.
- You should still be using the AWS Management Console in the US East (Ohio) Region. Select **Items** in the left navigation menu, select the **Music** table, then choose **Create Item**.
  - For **Artist**, enter **item\_1**.
  - For **SongTitle**, enter **Song Value 1**.
  - To write the item, choose **Create item**.
- After a short time, the item is replicated across all three Regions of your global table. To verify this, in the console, on the Region selector in the upper-right corner, choose **Europe (Frankfurt)**. The Music table in Europe (Frankfurt) should contain the new item.
- Repeat step 9 and choose **US West (Oregon)** to verify replication in that region.

### [Creating a global table \(AWS CLI\)](#)

Follow these steps to create a global table **Music** using the AWS CLI. The following example creates a global table, with replica tables in the United States and in Europe.

- Create a new table (**Music**) in US East (Ohio), with DynamoDB Streams enabled (**NEW\_AND\_OLD\_IMAGES**).

```
aws dynamodb create-table \
--table-name Music \
```

```
--attribute-definitions \
    AttributeName=Artist,AttributeType=S \
    AttributeName=SongTitle,AttributeType=S \
--key-schema \
    AttributeName=Artist,KeyType=HASH \
    AttributeName=SongTitle,KeyType=RANGE \
--provisioned-throughput \
    ReadCapacityUnits=10,WriteCapacityUnits=5 \
--stream-specification StreamEnabled=true,StreamViewType=NEW_AND_OLD_IMAGES \
--region us-east-2
```

2. Create an identical Music table in US East (N. Virginia).

```
aws dynamodb create-table \
--table-name Music \
--attribute-definitions \
    AttributeName=Artist,AttributeType=S \
    AttributeName=SongTitle,AttributeType=S \
--key-schema \
    AttributeName=Artist,KeyType=HASH \
    AttributeName=SongTitle,KeyType=RANGE \
--provisioned-throughput \
    ReadCapacityUnits=10,WriteCapacityUnits=5 \
--stream-specification StreamEnabled=true,StreamViewType=NEW_AND_OLD_IMAGES \
--region us-east-1
```

3. Create a global table (Music) consisting of replica tables in the us-east-2 and us-east-1 Regions.

```
aws dynamodb create-global-table \
--global-table-name Music \
--replication-group RegionName=us-east-2 RegionName=us-east-1 \
--region us-east-2
```

#### Note

The global table name (Music) must match the name of each of the replica tables (Music). For more information, see [Best practices and requirements for managing global tables \(p. 321\)](#).

4. Create another table in Europe (Ireland), with the same settings as those you created in step 1 and step 2.

```
aws dynamodb create-table \
--table-name Music \
--attribute-definitions \
    AttributeName=Artist,AttributeType=S \
    AttributeName=SongTitle,AttributeType=S \
--key-schema \
    AttributeName=Artist,KeyType=HASH \
    AttributeName=SongTitle,KeyType=RANGE \
--provisioned-throughput \
    ReadCapacityUnits=10,WriteCapacityUnits=5 \
--stream-specification StreamEnabled=true,StreamViewType=NEW_AND_OLD_IMAGES \
--region eu-west-1
```

After doing this step, add the new table to the Music global table.

```
aws dynamodb update-global-table \
--global-table-name Music \
--replica-updates 'Create={RegionName=eu-west-1}' \
--region us-east-2
```

5. To verify that replication is working, add a new item to the `Music` table in US East (Ohio).

```
aws dynamodb put-item \  
  --table-name Music \  
  --item '{"Artist": {"S":"item_1"}, "SongTitle": {"S":"Song Value 1"}}' \  
  --region us-east-2
```

6. Wait for a few seconds, and then check to see whether the item has been successfully replicated to US East (N. Virginia) and Europe (Ireland).

```
aws dynamodb get-item \  
  --table-name Music \  
  --key '{"Artist": {"S":"item_1"}, "SongTitle": {"S":"Song Value 1"}}' \  
  --region us-east-1
```

```
aws dynamodb get-item \  
  --table-name Music \  
  --key '{"Artist": {"S":"item_1"}, "SongTitle": {"S":"Song Value 1"}}' \  
  --region eu-west-1
```

## Monitoring global tables

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

You can use Amazon CloudWatch to monitor the behavior and performance of a global table. Amazon DynamoDB publishes `ReplicationLatency` and `PendingReplicationCount` metrics for each replica in the global table.

- **ReplicationLatency**—The elapsed time between when an updated item appears in the DynamoDB stream for one replica table, and when that item appears in another replica in the global table. `ReplicationLatency` is expressed in milliseconds and is emitted for every source- and destination-Region pair.

During normal operation, `ReplicationLatency` should be fairly constant. An elevated value for `ReplicationLatency` could indicate that updates from one replica are not propagating to other replica tables in a timely manner. Over time, this could result in other replica tables *falling behind* because they no longer receive updates consistently. In this case, you should verify that the read capacity units (RCUs) and write capacity units (WCUs) are identical for each of the replica tables. In addition, when choosing WCU settings, follow the recommendations in [Best practices and requirements for managing capacity \(p. 322\)](#).

`ReplicationLatency` can increase if an AWS Region becomes degraded and you have a replica table in that Region. In this case, you can temporarily redirect your application's read and write activity to a different AWS Region.

- **PendingReplicationCount**—The number of item updates that are written to one replica table, but that have not yet been written to another replica in the global table. `PendingReplicationCount` is expressed in number of items and is emitted for every source- and destination-Region pair.

During normal operation, `PendingReplicationCount` should be very low. If `PendingReplicationCount` increases for extended periods, investigate whether your replica tables' provisioned write capacity settings are sufficient for your current workload.

`PendingReplicationCount` can increase if an AWS Region becomes degraded and you have a replica table in that Region. In this case, you can temporarily redirect your application's read and write activity to a different AWS Region.

For more information, see [DynamoDB Metrics and dimensions \(p. 1114\)](#).

## Using IAM with global tables

There are two versions of DynamoDB global tables available: [Version 2019.11.21 \(Current\) \(p. 308\)](#) and [Version 2017.11.29 \(p. 319\)](#). To find out which version you are using, see [Determining the version \(p. 307\)](#).

When you create a global table for the first time, Amazon DynamoDB automatically creates an AWS Identity and Access Management (IAM) service-linked role for you. This role is named `AWSServiceRoleForDynamoDBReplication`, and it allows DynamoDB to manage cross-Region replication for global tables on your behalf. Don't delete this service-linked role. If you do, then all of your global tables will no longer function.

For more information about service-linked roles, see [Using service-linked roles](#) in the *IAM User Guide*.

To create and maintain global tables in DynamoDB, you must have the `dynamodb:CreateGlobalTable` permission to access each of the following:

- The replica table that you want to add.
- Each existing replica that's already part of the global table.
- The global table itself.

To update the settings (`UpdateGlobalTableSettings`) for a global table in DynamoDB, you must have the `dynamodb:UpdateGlobalTable`, `dynamodb:DescribeLimits`, `application-autoscaling:DeleteScalingPolicy`, and `application-autoscaling:DeregisterScalableTarget` permissions.

The `application-autoscaling:DeleteScalingPolicy` and `application-autoscaling:DeregisterScalableTarget` permissions are required when updating an existing scaling policy. This is so that the global tables service can remove the old scaling policy before attaching the new policy to the table or secondary index.

If you use an IAM policy to manage access to one replica table, you should apply an identical policy to all other replicas within that global table. This practice helps you maintain a consistent permissions model across all of the replica tables.

By using identical IAM policies on all replicas in a global table, you can also avoid granting unintended read and write access to your global table data. For example, consider a user who has access to only one replica in a global table. If that user can write to this replica, DynamoDB propagates the write to all of the other replica tables. In effect, the user can (indirectly) write to all of the other replicas in the global table. This scenario can be avoided by using consistent IAM policies on all of the replica tables.

### Example: Allow the `CreateGlobalTable` action

Before you can add a replica to a global table, you must have the `dynamodb:CreateGlobalTable` permission for the global table and for each of its replica tables.

The following IAM policy grants permissions to allow the `CreateGlobalTable` action on all tables.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": ["dynamodb:CreateGlobalTable"],
            "Resource": "*"
        }
    ]
}
```

**Example: Allow the `UpdateGlobalTable`, `DescribeLimits`, `application-autoscaling:DeleteScalingPolicy`, and `application-autoscaling:DeregisterScalableTarget` actions**

To update the settings (`UpdateGlobalTableSettings`) for a global table in DynamoDB, you must have the `dynamodb:UpdateGlobalTable`, `dynamodb:DescribeLimits`, `application-autoscaling:DeleteScalingPolicy`, and `application-autoscaling:DeregisterScalableTarget` permissions.

The following IAM policy grants permissions to allow the `UpdateGlobalTableSettings` action on all tables.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                "dynamodb:UpdateGlobalTable",
                "dynamodb:DescribeLimits",
                "application-autoscaling:DeleteScalingPolicy",
                "application-autoscaling:DeregisterScalableTarget"
            ],
            "Resource": "*"
        }
    ]
}
```

**Example: Allow the `CreateGlobalTable` action for a specific global table name with replicas allowed in certain regions only**

The following IAM policy grants permissions to allow the `CreateGlobalTable` action to create a global table named `Customers` with replicas in two Regions.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": "dynamodb:CreateGlobalTable",
            "Resource": [
                "arn:aws:dynamodb::123456789012:global-table/Customers",
                "arn:aws:dynamodb:us-east-1:123456789012:table/Customers",
                "arn:aws:dynamodb:us-west-1:123456789012:table/Customers"
            ]
        }
    ]
}
```

## Adding tags and labels to resources

You can label Amazon DynamoDB resources using *tags*. Tags let you categorize your resources in different ways, for example, by purpose, owner, environment, or other criteria. Tags can help you do the following:

- Quickly identify a resource based on the tags that you assigned to it.
- See AWS bills broken down by tags.

**Note**

Any local secondary indexes (LSI) and global secondary indexes (GSI) related to tagged tables are labeled with the same tags automatically. Currently, DynamoDB Streams usage cannot be tagged.

Tagging is supported by AWS services like Amazon EC2, Amazon S3, DynamoDB, and more. Efficient tagging can provide cost insights by enabling you to create reports across services that carry a specific tag.

To get started with tagging, do the following:

1. Understand [Tagging restrictions in DynamoDB \(p. 329\)](#).
2. Create tags by using [Tagging resources in DynamoDB \(p. 329\)](#).
3. Use [Cost allocation reports \(p. 332\)](#) to track your AWS costs per active tag.

Finally, it is good practice to follow optimal tagging strategies. For information, see [AWS tagging strategies](#).

## Tagging restrictions in DynamoDB

Each tag consists of a key and a value, both of which you define. The following restrictions apply:

- Each DynamoDB table can have only one tag with the same key. If you try to add an existing tag (same key), the existing tag value is updated to the new value.
- Tag keys and values are case sensitive.
- The maximum key length is 128 Unicode characters.
- The maximum value length is 256 Unicode characters.
- The allowed characters are letters, white space, and numbers, plus the following special characters: + - = . \_ : /
- The maximum number of tags per resource is 50.
- AWS-assigned tag names and values are automatically assigned the aws : prefix, which you can't assign. AWS-assigned tag names don't count toward the tag limit of 50. User-assigned tag names have the prefix user : in the cost allocation report.
- You can't backdate the application of a tag.

## Tagging resources in DynamoDB

You can use the Amazon DynamoDB console or the AWS Command Line Interface (AWS CLI) to add, list, edit, or delete tags. You can then activate these user-defined tags so that they appear on the AWS Billing and Cost Management console for cost allocation tracking. For more information, see [Cost allocation reports \(p. 332\)](#).

For bulk editing, you can also use Tag Editor on the AWS Management Console. For more information, see [Working with Tag Editor](#).

To use the DynamoDB API instead, see the following operations in the [Amazon DynamoDB API Reference](#):

- [TagResource](#)
- [UntagResource](#)
- [ListTagsOfResource](#)

## Topics

- [Setting permissions to filter by tags \(p. 330\)](#)
- [Adding tags to new or existing tables \(AWS Management Console\) \(p. 331\)](#)
- [Adding tags to new or existing tables \(AWS CLI\) \(p. 331\)](#)

## Setting permissions to filter by tags

To use tags to filter your table list in the DynamoDB console, make sure your IAM user's policies include access to the following operations:

- `tag:GetTagKeys`
- `tag:GetTagValues`

You can access these operations by attaching a new IAM policy to your IAM user by following the steps below.

1. Go to the [IAM console](#) with an Admin user.
2. Select "Policies" in the left navigation menu.
3. Select "Create policy."
4. Paste the following policy into the JSON editor.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "tag:GetTagKeys",  
                "tag:GetTagValues"  
            ],  
            "Resource": "*"  
        }  
    ]  
}
```

5. Complete the wizard and assign a name to the policy (for example, `TagKeysAndValuesReadAccess`).
6. Select "Users" in the left navigation menu.
7. From the list, select the user you normally use to access the DynamoDB console.
8. Select "Add permissions."
9. Select "Attach existing policies directly."
10. From the list, select the policy you created previously.
11. Complete the wizard.

## Adding tags to new or existing tables (AWS Management Console)

You can use the DynamoDB console to add tags to new tables when you create them, or to add, edit, or delete tags for existing tables.

### To tag resources on creation (console)

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, choose **Tables**, and then choose **Create table**.
3. On the **Create DynamoDB table** page, provide a name and primary key. In the **Tags** section, choose **Add new tag** and enter the tags that you want to use.

For information about tag structure, see [Tagging restrictions in DynamoDB \(p. 329\)](#).

For more information about creating tables, see [Basic operations on DynamoDB tables \(p. 279\)](#).

### To tag existing resources (console)

Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.

1. In the navigation pane, choose **Tables**.
2. Choose a table in the list, and then choose the **Additional settings** tab. You can add, edit, or delete your tags in the **Tags** section at the bottom of the page.

## Adding tags to new or existing tables (AWS CLI)

The following examples show how to use the AWS CLI to specify tags when you create tables and indexes, and to tag existing resources.

### To tag resources on creation (AWS CLI)

- The following example creates a new `Movies` table and adds the `Owner` tag with a value of `blueTeam`:

```
aws dynamodb create-table \
  --table-name Movies \
  --attribute-definitions AttributeName=Title,AttributeType=S \
  --key-schema AttributeName=Title,KeyType=HASH \
  --provisioned-throughput ReadCapacityUnits=5,WriteCapacityUnits=5 \
  --tags Key=Owner,Value=blueTeam
```

### To tag existing resources (AWS CLI)

- The following example adds the `Owner` tag with a value of `blueTeam` for the `Movies` table:

```
aws dynamodb tag-resource \
  --resource-arn arn:aws:dynamodb:us-east-1:123456789012:table/Movies \
  --tags Key=Owner,Value=blueTeam
```

### To list all tags for a table (AWS CLI)

- The following example lists all the tags that are associated with the `Movies` table:

```
aws dynamodb list-tags-of-resource \
--resource-arn arn:aws:dynamodb:us-east-1:123456789012:table/Movies
```

## Cost allocation reports

AWS uses tags to organize resource costs on your cost allocation report. AWS provides two types of cost allocation tags:

- An AWS-generated tag. AWS defines, creates, and applies this tag for you.
- User-defined tags. You define, create, and apply these tags.

You must activate both types of tags separately before they can appear in Cost Explorer or on a cost allocation report.

To activate AWS-generated tags:

1. Sign in to the AWS Management Console and open the Billing and Cost Management console at <https://console.aws.amazon.com/billing/home#/>.
2. In the navigation pane, choose **Cost Allocation Tags**.
3. Under **AWS-Generated Cost Allocation Tags**, choose **Activate**.

To activate user-defined tags:

1. Sign in to the AWS Management Console and open the Billing and Cost Management console at <https://console.aws.amazon.com/billing/home#/>.
2. In the navigation pane, choose **Cost Allocation Tags**.
3. Under **User-Defined Cost Allocation Tags**, choose **Activate**.

After you create and activate tags, AWS generates a cost allocation report with your usage and costs grouped by your active tags. The cost allocation report includes all of your AWS costs for each billing period. The report includes both tagged and untagged resources, so that you can clearly organize the charges for resources.

**Note**

Currently, any data transferred out from DynamoDB won't be broken down by tags on cost allocation reports.

For more information, see [Using cost allocation tags](#).

## Working with DynamoDB tables in Java

You can use the AWS SDK for Java to create, update, and delete Amazon DynamoDB tables, list all the tables in your account, or get information about a specific table.

**Topics**

- [Creating a table \(p. 333\)](#)
- [Updating a table \(p. 334\)](#)
- [Deleting a table \(p. 334\)](#)
- [Listing tables \(p. 335\)](#)
- [Example: Create, update, delete, and list tables using the AWS SDK for Java document API \(p. 335\)](#)

## Creating a table

To create a table, you must provide the table name, its primary key, and the provisioned throughput values. The following code snippet creates an example table that uses a numeric type attribute ID as its primary key.

### To create a table using the AWS SDK for Java API

1. Create an instance of the DynamoDB class.
2. Instantiate a `CreateTableRequest` to provide the request information.

You must provide the table name, attribute definitions, key schema, and provisioned throughput values.

3. Run the `createTable` method by providing the request object as a parameter.

The following code example demonstrates the preceding steps.

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

List<AttributeDefinition> attributeDefinitions= new ArrayList<AttributeDefinition>();
attributeDefinitions.add(new
    AttributeDefinition().withAttributeName("Id").withAttributeType("N"));

List<KeySchemaElement> keySchema = new ArrayList<KeySchemaElement>();
keySchema.add(new KeySchemaElement().withAttributeName("Id").withKeyType(KeyType.HASH));

CreateTableRequest request = new CreateTableRequest()
    .withTableName(tableName)
    .withKeySchema(keySchema)
    .withAttributeDefinitions(attributeDefinitions)
    .withProvisionedThroughput(new ProvisionedThroughput()
        .withReadCapacityUnits(5L)
        .withWriteCapacityUnits(6L));

Table table = dynamoDB.createTable(request);

table.waitForActive();
```

The table is not ready for use until DynamoDB creates it and sets its status to *ACTIVE*. The `createTable` request returns a `Table` object that you can use to obtain more information about the table.

### Example

```
TableDescription tableDescription =
    dynamoDB.getTable(tableName).describe();

System.out.printf("%s: %s \t ReadCapacityUnits: %d \t WriteCapacityUnits: %d",
    tableDescription.getTableStatus(),
    tableDescription.getTableName(),
    tableDescription.getProvisionedThroughput().getReadCapacityUnits(),
    tableDescription.getProvisionedThroughput().getWriteCapacityUnits());
```

You can call the `describe` method of the client to get table information at any time.

### Example

```
TableDescription tableDescription = dynamoDB.getTable(tableName).describe();
```

## Updating a table

You can update only the provisioned throughput values of an existing table. Depending on your application requirements, you might need to update these values.

### Note

For more information about throughput increases and decreases per day, see [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#).

### To update a table using the AWS SDK for Java API

1. Create an instance of the `Table` class.
2. Create an instance of the `ProvisionedThroughput` class to provide the new throughput values.
3. Run the `updateTable` method by providing the `ProvisionedThroughput` instance as a parameter.

The following code example demonstrates the preceding steps.

### Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("ProductCatalog");

ProvisionedThroughput provisionedThroughput = new ProvisionedThroughput()
    .withReadCapacityUnits(15L)
    .withWriteCapacityUnits(12L);

table.updateTable(provisionedThroughput);

table.waitForActive();
```

## Deleting a table

### To delete a table using the AWS SDK for Java API

1. Create an instance of the `Table` class.
2. Create an instance of the `DeleteTableRequest` class and provide the table name that you want to delete.
3. Run the `deleteTable` method by providing the `Table` instance as a parameter.

The following code example demonstrates the preceding steps.

### Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("ProductCatalog");

table.delete();

table.waitForDelete();
```

## Listing tables

To list tables in your account, create an instance of DynamoDB and run the `listTables` method. The [ListTables](#) operation requires no parameters.

### Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

TableCollection<ListTablesResult> tables = dynamoDB.listTables();
Iterator<Table> iterator = tables.iterator();

while (iterator.hasNext()) {
    Table table = iterator.next();
    System.out.println(table.getTableName());
}
```

## Example: Create, update, delete, and list tables using the AWS SDK for Java document API

The following code example uses the AWS SDK for Java Document API to create, update, and delete an Amazon DynamoDB table (`ExampleTable`). As part of the table update, it increases the provisioned throughput values. The example also lists all the tables in your account and gets the description of a specific table. For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

```
/** 
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples.document;

import java.util.ArrayList;
import java.util.Iterator;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Table;
import com.amazonaws.services.dynamodbv2.document.TableCollection;
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;
import com.amazonaws.services.dynamodbv2.model.CreateTableRequest;
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;
import com.amazonaws.services.dynamodbv2.model.KeyType;
import com.amazonaws.services.dynamodbv2.model.ListTablesResult;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;
import com.amazonaws.services.dynamodbv2.model.TableDescription;
```

```

public class DocumentAPITableExample {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDB dynamoDB = new DynamoDB(client);

    static String tableName = "ExampleTable";

    public static void main(String[] args) throws Exception {

        createExampleTable();
        listMyTables();
        getTableInformation();
        updateExampleTable();

        deleteExampleTable();
    }

    static void createExampleTable() {

        try {

            List<AttributeDefinition> attributeDefinitions = new
ArrayList<AttributeDefinition>();
            attributeDefinitions.add(new
AttributeDefinition().withAttributeName("Id").withAttributeType("N"));

            List<KeySchemaElement> keySchema = new ArrayList<KeySchemaElement>();
            keySchema.add(new
KeySchemaElement().withAttributeName("Id").withKeyType(KeyType.HASH)); // Partition

            // key

            CreateTableRequest request = new
CreateTableRequest().withTableName(tableName).withKeySchema(keySchema)
                .withAttributeDefinitions(attributeDefinitions).withProvisionedThroughput(
                    new
ProvisionedThroughput().withReadCapacityUnits(5L).withWriteCapacityUnits(6L));

            System.out.println("Issuing CreateTable request for " + tableName);
            Table table = dynamoDB.createTable(request);

            System.out.println("Waiting for " + tableName + " to be created...this may take
a while...");
            table.waitForActive();

            getTableInformation();

        }
        catch (Exception e) {
            System.err.println("CreateTable request failed for " + tableName);
            System.err.println(e.getMessage());
        }
    }

    static void listMyTables() {

        TableCollection<ListTablesResult> tables = dynamoDB.listTables();
        Iterator<Table> iterator = tables.iterator();

        System.out.println("Listing table names");

        while (iterator.hasNext()) {
            Table table = iterator.next();
            System.out.println(table.getTableName());
        }
    }
}

```

```

    }

    static void getTableInformation() {
        System.out.println("Describing " + tableName);

        TableDescription tableDescription = dynamoDB.getTable(tableName).describe();
        System.out.format(
            "Name: %s:\n" + "Status: %s \n" + "Provisioned Throughput (read capacity units/
sec): %d \n"
            + "Provisioned Throughput (write capacity units/sec): %d \n",
            tableDescription.getTableName(), tableDescription.getTableStatus(),
            tableDescription.getProvisionedThroughput().getReadCapacityUnits(),
            tableDescription.getProvisionedThroughput().getWriteCapacityUnits());
    }

    static void updateExampleTable() {
        Table table = dynamoDB.getTable(tableName);
        System.out.println("Modifying provisioned throughput for " + tableName);

        try {
            table.updateTable(new
                ProvisionedThroughput().withReadCapacityUnits(6L).withWriteCapacityUnits(7L));

            table.waitForActive();
        }
        catch (Exception e) {
            System.err.println("UpdateTable request failed for " + tableName);
            System.err.println(e.getMessage());
        }
    }

    static void deleteExampleTable() {
        Table table = dynamoDB.getTable(tableName);
        try {
            System.out.println("Issuing DeleteTable request for " + tableName);
            table.delete();

            System.out.println("Waiting for " + tableName + " to be deleted...this may take
a while...");

            table.waitForDelete();
        }
        catch (Exception e) {
            System.err.println("DeleteTable request failed for " + tableName);
            System.err.println(e.getMessage());
        }
    }
}

```

## Working with DynamoDB tables in .NET

You can use the AWS SDK for .NET to create, update, and delete tables, list all the tables in your account, or get information about a specific table.

The following are the common steps for Amazon DynamoDB table operations using the AWS SDK for .NET.

1. Create an instance of the `AmazonDynamoDBClient` class (the client).

2. Provide the required and optional parameters for the operation by creating the corresponding request objects.

For example, create a `CreateTableRequest` object to create a table and `UpdateTableRequest` object to update an existing table.

3. Run the appropriate method provided by the client that you created in the preceding step.

**Note**

The examples in this section don't work with .NET core because it doesn't support synchronous methods. For more information, see [AWS asynchronous APIs for .NET](#).

**Topics**

- [Creating a table \(p. 338\)](#)
- [Updating a table \(p. 339\)](#)
- [Deleting a table \(p. 340\)](#)
- [Listing tables \(p. 340\)](#)
- [Example: Create, update, delete, and list tables using the AWS SDK for .NET low-level API \(p. 341\)](#)

## Creating a table

To create a table, you must provide the table name, its primary key, and the provisioned throughput values.

### To create a table using the AWS SDK for .NET low-level API

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `CreateTableRequest` class to provide the request information.  
You must provide the table name, primary key, and the provisioned throughput values.
3. Run the `AmazonDynamoDBClient.CreateTable` method by providing the request object as a parameter.

The following C# example demonstrates the preceding steps. The sample creates a table (`ProductCatalog`) that uses `Id` as the primary key and set of provisioned throughput values. Depending on your application requirements, you can update the provisioned throughput values by using the `UpdateTable` API.

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new CreateTableRequest
{
    TableName = tableName,
    AttributeDefinitions = new List<AttributeDefinition>()
    {
        new AttributeDefinition
        {
            AttributeName = "Id",
            AttributeType = "N"
        }
    },
    KeySchema = new List<KeySchemaElement>()
    {
        new KeySchemaElement
        {
            AttributeName = "Id",
            KeyType = "HASH"
        }
    }
};
```

```
        KeyType = "HASH" //Partition key
    },
},
ProvisionedThroughput = new ProvisionedThroughput
{
    ReadCapacityUnits = 10,
    WriteCapacityUnits = 5
};
};

var response = client.CreateTable(request);
```

You must wait until DynamoDB creates the table and sets its status to `ACTIVE`. The `CreateTable` response includes the `TableDescription` property that provides the necessary table information.

### Example

```
var result = response.CreateTableResult;
var tableDescription = result.TableDescription;
Console.WriteLine("{1}: {0} \t ReadCapacityUnits: {2} \t WriteCapacityUnits: {3}",
    tableDescription.TableStatus,
    tableDescription.TableName,
    tableDescription.ProvisionedThroughput.ReadCapacityUnits,
    tableDescription.ProvisionedThroughput.WriteCapacityUnits);

string status = tableDescription.TableStatus;
Console.WriteLine(tableName + " - " + status);
```

You can also call the `DescribeTable` method of the client to get table information at any time.

### Example

```
var res = client.DescribeTable(new DescribeTableRequest{TableName = "ProductCatalog"});
```

## Updating a table

You can update only the provisioned throughput values of an existing table. Depending on your application requirements, you might need to update these values.

#### Note

You can increase throughput capacity as often as needed, and decrease it within certain constraints. For more information about throughput increases and decreases per day, see [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#).

### To update a table using the AWS SDK for .NET low-level API

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `UpdateTableRequest` class to provide the request information.  
You must provide the table name and the new provisioned throughput values.
3. Run the `AmazonDynamoDBClient.UpdateTable` method by providing the request object as a parameter.

The following C# example demonstrates the preceding steps.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
```

```
string tableName = "ExampleTable";

var request = new UpdateTableRequest()
{
    TableName = tableName,
    ProvisionedThroughput = new ProvisionedThroughput()
    {
        // Provide new values.
        ReadCapacityUnits = 20,
        WriteCapacityUnits = 10
    }
};
var response = client.UpdateTable(request);
```

## Deleting a table

Follow these steps to delete a table using the .NET low-level API.

### To delete a table using the AWS SDK for .NET low-level API

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `DeleteTableRequest` class, and provide the table name that you want to delete.
3. Run the `AmazonDynamoDBClient.DeleteTable` method by providing the request object as a parameter.

The following C# code example demonstrates the preceding steps.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ExampleTable";

var request = new DeleteTableRequest{ TableName = tableName };
var response = client.DeleteTable(request);
```

## Listing tables

To list tables in your account using the AWS SDK for .NET low-level API, create an instance of the `AmazonDynamoDBClient` and run the `ListTables` method.

The `ListTables` operation requires no parameters. However, you can specify optional parameters. For example, you can set the `Limit` parameter if you want to use paging to limit the number of table names per page. This requires you to create a `ListTablesRequest` object and provide optional parameters as shown in the following C# example. Along with the page size, the request sets the `ExclusiveStartTableName` parameter. Initially, `ExclusiveStartTableName` is null. However, after fetching the first page of results, to retrieve the next page of results, you must set this parameter value to the `LastEvaluatedTableName` property of the current result.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();

// Initial value for the first page of table names.
string lastEvaluatedTableName = null;
do
{
```

```
// Create a request object to specify optional parameters.
var request = new ListTablesRequest
{
    Limit = 10, // Page size.
    ExclusiveStartTableName = lastEvaluatedTableName
};

var response = client.ListTables(request);
ListTablesResult result = response.ListTablesResult;
foreach (string name in result.TableNames)
    Console.WriteLine(name);

lastEvaluatedTableName = result.LastEvaluatedTableName;

} while (lastEvaluatedTableName != null);
```

## Example: Create, update, delete, and list tables using the AWS SDK for .NET low-level API

The following C# example creates, updates, and deletes a table (`ExampleTable`). It also lists all the tables in your account and gets the description of a specific table. The table update increases the provisioned throughput values. For step-by-step instructions to test the following example, see [.NET code examples \(p. 276\)](#).

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
    class LowLevelTableExample
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();
        private static string tableName = "ExampleTable";

        static void Main(string[] args)
        {
            try
            {
                CreateExampleTable();
                ListMyTables();
                GetTableInformation();
                UpdateExampleTable();

                DeleteExampleTable();

                Console.WriteLine("To continue, press Enter");
            }
        }
    }
}
```

```

        Console.ReadLine();
    }
    catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
    catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
    catch (Exception e) { Console.WriteLine(e.Message); }
}

private static void CreateExampleTable()
{
    Console.WriteLine("\n*** Creating table ***");
    var request = new CreateTableRequest
    {
        AttributeDefinitions = new List<AttributeDefinition>()
    {
        new AttributeDefinition
        {
            AttributeName = "Id",
            AttributeType = "N"
        },
        new AttributeDefinition
        {
            AttributeName = "ReplyDateTime",
            AttributeType = "N"
        }
    },
    KeySchema = new List<KeySchemaElement>
    {
        new KeySchemaElement
        {
            AttributeName = "Id",
            KeyType = "HASH" //Partition key
        },
        new KeySchemaElement
        {
            AttributeName = "ReplyDateTime",
            KeyType = "RANGE" //Sort key
        }
    },
    ProvisionedThroughput = new ProvisionedThroughput
    {
        ReadCapacityUnits = 5,
        WriteCapacityUnits = 6
    },
    TableName = tableName
};

    var response = client.CreateTable(request);

    var tableDescription = response.TableDescription;
    Console.WriteLine("{1}: {0} \t ReadsPerSec: {2} \t WritesPerSec: {3}",
        tableDescription.TableStatus,
        tableDescription.TableName,
        tableDescription.ProvisionedThroughput.ReadCapacityUnits,
        tableDescription.ProvisionedThroughput.WriteCapacityUnits);

    string status = tableDescription.TableStatus;
    Console.WriteLine(tableName + " - " + status);

    WaitUntilTableReady(tableName);
}

private static void ListMyTables()
{
    Console.WriteLine("\n*** listing tables ***");
    string lastTableNameEvaluated = null;
    do

```

```

{
    var request = new ListTablesRequest
    {
        Limit = 2,
        ExclusiveStartTableName = lastTableNameEvaluated
    };

    var response = client.ListTables(request);
    foreach (string name in response.TableNames)
        Console.WriteLine(name);

    lastTableNameEvaluated = response.LastEvaluatedTableName;
} while (lastTableNameEvaluated != null);
}

private static void GetTableInformation()
{
    Console.WriteLine("\n*** Retrieving table information ***");
    var request = new DescribeTableRequest
    {
        TableName = tableName
    };

    var response = client.DescribeTable(request);

    TableDescription description = response.Table;
    Console.WriteLine("Name: {0}", description.TableName);
    Console.WriteLine("# of items: {0}", description.ItemCount);
    Console.WriteLine("Provision Throughput (reads/sec): {0}",
                      description.ProvisionedThroughput.ReadCapacityUnits);
    Console.WriteLine("Provision Throughput (writes/sec): {0}",
                      description.ProvisionedThroughput.WriteCapacityUnits);
}

private static void UpdateExampleTable()
{
    Console.WriteLine("\n*** Updating table ***");
    var request = new UpdateTableRequest()
    {
        TableName = tableName,
        ProvisionedThroughput = new ProvisionedThroughput()
        {
            ReadCapacityUnits = 6,
            WriteCapacityUnits = 7
        }
    };

    var response = client.UpdateTable(request);

    WaitUntilTableReady(tableName);
}

private static void DeleteExampleTable()
{
    Console.WriteLine("\n*** Deleting table ***");
    var request = new DeleteTableRequest
    {
        TableName = tableName
    };

    var response = client.DeleteTable(request);

    Console.WriteLine("Table is being deleted...");
}

private static void WaitUntilTableReady(string tableName)

```

```
{  
    string status = null;  
    // Let us wait until table is created. Call DescribeTable.  
    do  
    {  
        System.Threading.Thread.Sleep(5000); // Wait 5 seconds.  
        try  
        {  
            var res = client.DescribeTable(new DescribeTableRequest  
            {  
                TableName = tableName  
            });  
  
            Console.WriteLine("Table name: {0}, status: {1}",  
                res.Table.TableName,  
                res.Table.TableStatus);  
            status = res.Table.TableStatus;  
        }  
        catch (ResourceNotFoundException)  
        {  
            // DescribeTable is eventually consistent. So you might  
            // get resource not found. So we handle the potential exception.  
        }  
    } while (status != "ACTIVE");  
}  
}  
}
```

## Working with read and write operations

You can perform read and write operations with either the DynamoDB API or PartiQL for DynamoDB. These operations will allow you to interact with the items in your table to perform basic create, read, update, and delete (CRUD) functionality.

The following sections go more in depth on this topic.

### Topics

- [DynamoDB API \(p. 344\)](#)
- [PartiQL - a SQL-compatible query language for Amazon DynamoDB \(p. 466\)](#)

## DynamoDB API

### Topics

- [Working with items and attributes \(p. 344\)](#)
- [Item collections - how to model one-to-many relationships in DynamoDB \(p. 426\)](#)
- [Working with scans in DynamoDB \(p. 445\)](#)

## Working with items and attributes

In Amazon DynamoDB, an *item* is a collection of attributes. Each attribute has a name and a value. An attribute value can be a scalar, a set, or a document type. For more information, see [Amazon DynamoDB: How it works \(p. 2\)](#).

DynamoDB provides four operations for basic create, read, update, and delete (CRUD) functionality. All these operations are atomic.

- `PutItem` — Create an item.
- `GetItem` — Read an item.
- `UpdateItem` — Update an item.
- `DeleteItem` — Delete an item.

Each of these operations requires that you specify the primary key of the item that you want to work with. For example, to read an item using `GetItem`, you must specify the partition key and sort key (if applicable) for that item.

In addition to the four basic CRUD operations, DynamoDB also provides the following:

- `BatchGetItem` — Read up to 100 items from one or more tables.
- `BatchWriteItem` — Create or delete up to 25 items in one or more tables.

These batch operations combine multiple CRUD operations into a single request. In addition, the batch operations read and write items in parallel to minimize response latencies.

This section describes how to use these operations and includes related topics, such as conditional updates and atomic counters. This section also includes example code that uses the AWS SDKs.

### Topics

- [Reading an item \(p. 345\)](#)
- [Writing an item \(p. 346\)](#)
- [Return values \(p. 347\)](#)
- [Batch operations \(p. 348\)](#)
- [Atomic counters \(p. 350\)](#)
- [Conditional writes \(p. 350\)](#)
- [Using expressions in DynamoDB \(p. 354\)](#)
- [Expiring items by using DynamoDB Time to Live \(TTL\) \(p. 378\)](#)
- [Working with items: Java \(p. 383\)](#)
- [Working with items: .NET \(p. 403\)](#)

## Reading an item

To read an item from a DynamoDB table, use the `GetItem` operation. You must provide the name of the table, along with the primary key of the item you want.

### Example

The following AWS CLI example shows how to read an item from the `ProductCatalog` table.

```
aws dynamodb get-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"1"}}'
```

### Note

With `GetItem`, you must specify the *entire* primary key, not just part of it. For example, if a table has a composite primary key (partition key and sort key), you must supply a value for the partition key and a value for the sort key.

A `GetItem` request performs an eventually consistent read by default. You can use the `ConsistentRead` parameter to request a strongly consistent read instead. (This consumes additional read capacity units, but it returns the most up-to-date version of the item.)

`GetItem` returns all of the item's attributes. You can use a *projection expression* to return only some of the attributes. For more information, see [Projection expressions \(p. 357\)](#).

To return the number of read capacity units consumed by `GetItem`, set the `ReturnConsumedCapacity` parameter to `TOTAL`.

### Example

The following AWS Command Line Interface (AWS CLI) example shows some of the optional `GetItem` parameters.

```
aws dynamodb get-item \  
  --table-name ProductCatalog \  
  --key '{"Id":{"N":"1"}}' \  
  --consistent-read \  
  --projection-expression "Description, Price, RelatedItems" \  
  --return-consumed-capacity TOTAL
```

## Writing an item

To create, update, or delete an item in a DynamoDB table, use one of the following operations:

- `PutItem`
- `UpdateItem`
- `DeleteItem`

For each of these operations, you must specify the entire primary key, not just part of it. For example, if a table has a composite primary key (partition key and sort key), you must provide a value for the partition key and a value for the sort key.

To return the number of write capacity units consumed by any of these operations, set the `ReturnConsumedCapacity` parameter to one of the following:

- `TOTAL` — Returns the total number of write capacity units consumed.
- `INDEXES` — Returns the total number of write capacity units consumed, with subtotals for the table and any secondary indexes that were affected by the operation.
- `NONE` — No write capacity details are returned. (This is the default.)

### PutItem

`PutItem` creates a new item. If an item with the same key already exists in the table, it is replaced with the new item.

### Example

Write a new item to the `Thread` table. The primary key for `Thread` consists of `ForumName` (partition key) and `Subject` (sort key).

```
aws dynamodb put-item \  
  --table-name Thread \  
  --item file://item.json
```

The arguments for `--item` are stored in the `item.json` file.

```
{  
  "ForumName": {"S": "Amazon DynamoDB"},  
  "Subject": {"S": "New discussion thread"},
```

```

    "Message": {"S": "First post in this thread"},  

    "LastPostedBy": {"S": "fred@example.com"},  

    "LastPostDateTime": {"S": "201603190422"}  

}

```

## UpdateItem

If an item with the specified key does not exist, `UpdateItem` creates a new item. Otherwise, it modifies an existing item's attributes.

You use an *update expression* to specify the attributes that you want to modify and their new values. For more information, see [Update expressions \(p. 370\)](#).

Within the update expression, you use expression attribute values as placeholders for the actual values. For more information, see [Expression attribute values \(p. 360\)](#).

## Example

Modify various attributes in the `Thread` item. The optional `ReturnValues` parameter shows the item as it appears after the update. For more information, see [Return values \(p. 347\)](#).

```

aws dynamodb update-item \  

  --table-name Thread \  

  --key file://key.json \  

  --update-expression "SET Answered = :zero, Replies = :zero, LastPostedBy  

= :lastpostedby" \  

  --expression-attribute-values file://expression-attribute-values.json \  

  --return-values ALL_NEW

```

The arguments for `--key` are stored in the `key.json` file.

```
{
  "ForumName": {"S": "Amazon DynamoDB"},  

  "Subject": {"S": "New discussion thread"}
}
```

The arguments for `--expression-attribute-values` are stored in the `expression-attribute-values.json` file.

```
{
  ":zero": {"N": "0"},  

  ":lastpostedby": {"S": "barney@example.com"}
}
```

## DeleteItem

`DeleteItem` deletes the item with the specified key.

## Example

The following AWS CLI example shows how to delete the `Thread` item.

```

aws dynamodb delete-item \  

  --table-name Thread \  

  --key file://key.json

```

## Return values

In some cases, you might want DynamoDB to return certain attribute values as they appeared before or after you modified them. The `PutItem`, `UpdateItem`, and `DeleteItem` operations have

a `ReturnValues` parameter that you can use to return the attribute values before or after they are modified.

The default value for `ReturnValues` is `NONE`, meaning that DynamoDB does not return any information about attributes that were modified.

The following are the other valid settings for `ReturnValues`, organized by DynamoDB API operation.

### [PutItem](#)

- `ReturnValues: ALL_OLD`
  - If you overwrite an existing item, `ALL_OLD` returns the entire item as it appeared before the overwrite.
  - If you write a nonexistent item, `ALL_OLD` has no effect.

### [UpdateItem](#)

The most common usage for `UpdateItem` is to update an existing item. However, `UpdateItem` actually performs an *upsert*, meaning that it automatically creates the item if it doesn't already exist.

- `ReturnValues: ALL_OLD`
  - If you update an existing item, `ALL_OLD` returns the entire item as it appeared before the update.
  - If you update a nonexistent item (upsert), `ALL_OLD` has no effect.
- `ReturnValues: ALL_NEW`
  - If you update an existing item, `ALL_NEW` returns the entire item as it appeared after the update.
  - If you update a nonexistent item (upsert), `ALL_NEW` returns the entire item.
- `ReturnValues: UPDATED_OLD`
  - If you update an existing item, `UPDATED_OLD` returns only the updated attributes, as they appeared before the update.
  - If you update a nonexistent item (upsert), `UPDATED_OLD` has no effect.
- `ReturnValues: UPDATED_NEW`
  - If you update an existing item, `UPDATED_NEW` returns only the affected attributes, as they appeared after the update.
  - If you update a nonexistent item (upsert), `UPDATED_NEW` returns only the updated attributes, as they appear after the update.

### [DeleteItem](#)

- `ReturnValues: ALL_OLD`
  - If you delete an existing item, `ALL_OLD` returns the entire item as it appeared before you deleted it.
  - If you delete a nonexistent item, `ALL_OLD` doesn't return any data.

## Batch operations

For applications that need to read or write multiple items, DynamoDB provides the `BatchGetItem` and `BatchWriteItem` operations. Using these operations can reduce the number of network round trips from your application to DynamoDB. In addition, DynamoDB performs the individual read or write operations in parallel. Your applications benefit from this parallelism without having to manage concurrency or threading.

The batch operations are essentially wrappers around multiple read or write requests. For example, if a `BatchGetItem` request contains five items, DynamoDB performs five `GetItem` operations on your

behalf. Similarly, if a `BatchWriteItem` request contains two put requests and four delete requests, DynamoDB performs two `PutItem` and four `DeleteItem` requests.

In general, a batch operation does not fail unless *all* the requests in the batch fail. For example, suppose that you perform a `BatchGetItem` operation, but one of the individual `GetItem` requests in the batch fails. In this case, `BatchGetItem` returns the keys and data from the `GetItem` request that failed. The other `GetItem` requests in the batch are not affected.

### BatchGetItem

A single `BatchGetItem` operation can contain up to 100 individual `GetItem` requests and can retrieve up to 16 MB of data. In addition, a `BatchGetItem` operation can retrieve items from multiple tables.

#### Example

Retrieve two items from the `Thread` table, using a projection expression to return only some of the attributes.

```
aws dynamodb batch-get-item \
--request-items file://request-items.json
```

The arguments for `--request-items` are stored in the `request-items.json` file.

```
{
    "Thread": {
        "Keys": [
            {
                "ForumName": {"S": "Amazon DynamoDB"},
                "Subject": {"S": "DynamoDB Thread 1"}
            },
            {
                "ForumName": {"S": "Amazon S3"},
                "Subject": {"S": "S3 Thread 1"}
            }
        ],
        "ProjectionExpression": "ForumName, Subject, LastPostedDateTime, Replies"
    }
}
```

### BatchWriteItem

The `BatchWriteItem` operation can contain up to 25 individual `PutItem` and `DeleteItem` requests and can write up to 16 MB of data. (The maximum size of an individual item is 400 KB.) In addition, a `BatchWriteItem` operation can put or delete items in multiple tables.

#### Note

`BatchWriteItem` does not support `UpdateItem` requests.

#### Example

Write two items to the `ProductCatalog` table.

```
aws dynamodb batch-write-item \
--request-items file://request-items.json
```

The arguments for `--request-items` are stored in the `request-items.json` file.

```
{
    "ProductCatalog": [
        {

```

```

    "PutRequest": {
        "Item": {
            "Id": { "N": "601" },
            "Description": { "S": "Snowboard" },
            "QuantityOnHand": { "N": "5" },
            "Price": { "N": "100" }
        }
    }
},
{
    "PutRequest": {
        "Item": {
            "Id": { "N": "602" },
            "Description": { "S": "Snow shovel" }
        }
    }
}
]
}

```

## Atomic counters

You can use the `UpdateItem` operation to implement an *atomic counter*—a numeric attribute that is incremented, unconditionally, without interfering with other write requests. (All write requests are applied in the order in which they were received.) With an atomic counter, the updates are not idempotent. In other words, the numeric value increments each time you call `UpdateItem`.

You might use an atomic counter to track the number of visitors to a website. In this case, your application would increment a numeric value, regardless of its current value. If an `UpdateItem` operation fails, the application could simply retry the operation. This would risk updating the counter twice, but you could probably tolerate a slight overcounting or undercounting of website visitors.

An atomic counter would not be appropriate where overcounting or undercounting can't be tolerated (for example, in a banking application). In this case, it is safer to use a conditional update instead of an atomic counter.

For more information, see [Incrementing and decrementing numeric attributes \(p. 374\)](#).

### Example

The following AWS CLI example increments the `Price` of a product by 5. (Because `UpdateItem` is not idempotent, the `Price` increases every time you run this example.)

```

aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id": { "N": "601" }}' \
--update-expression "SET Price = Price + :incr" \
--expression-attribute-values '{":incr":{"N":"5"}}' \
--return-values UPDATED_NEW


```

## Conditional writes

By default, the DynamoDB write operations (`PutItem`, `UpdateItem`, `DeleteItem`) are *unconditional*: Each operation overwrites an existing item that has the specified primary key.

DynamoDB optionally supports conditional writes for these operations. A conditional write succeeds only if the item attributes meet one or more expected conditions. Otherwise, it returns an error. Conditional writes are helpful in many situations. For example, you might want a `PutItem` operation to succeed only if there is not already an item with the same primary key. Or you could prevent an `UpdateItem` operation from modifying an item if one of its attributes has a certain value.

Conditional writes are helpful in cases where multiple users attempt to modify the same item. Consider the following diagram, in which two users (Alice and Bob) are working with the same item from a DynamoDB table.



Suppose that Alice uses the AWS CLI to update the `Price` attribute to 8.

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"1"}}' \
--update-expression "SET Price = :newval" \
--expression-attribute-values file://expression-attribute-values.json
```

The arguments for `--expression-attribute-values` are stored in the file `expression-attribute-values.json`:

```
{
  ":newval":{"N":"8"}}
```

}


Now suppose that Bob issues a similar `UpdateItem` request later, but changes the `Price` to 12. For Bob, the `--expression-attribute-values` parameter looks like the following.

```
{  
    ":newval": {"N": "12"}  
}
```

Bob's request succeeds, but Alice's earlier update is lost.

To request a conditional `PutItem`, `DeleteItem`, or `UpdateItem`, you specify a condition expression. A *condition expression* is a string containing attribute names, conditional operators, and built-in functions. The entire expression must evaluate to true. Otherwise, the operation fails.

Now consider the following diagram, showing how conditional writes would prevent Alice's update from being overwritten.



Alice first tries to update `Price` to 8, but only if the current `Price` is 10.

```
aws dynamodb update-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"1"}}' \  
    --update-expression "SET Price = :newval" \  
    --condition-expression "Price = :currval" \  
    --expression-attribute-values file://expression-attribute-values.json
```

The arguments for `--expression-attribute-values` are stored in the `expression-attribute-values.json` file.

```
{  
    ":newval": {"N": "8"},  
    ":currval": {"N": "10"}  
}
```

Alice's update succeeds because the condition evaluates to true.

Next, Bob attempts to update the `Price` to 12, but only if the current `Price` is 10. For Bob, the `--expression-attribute-values` parameter looks like the following.

```
{  
    ":newval": {"N": "12"},  
    ":currval": {"N": "10"}  
}
```

Because Alice has previously changed the `Price` to 8, the condition expression evaluates to false, and Bob's update fails.

For more information, see [Condition expressions \(p. 361\)](#).

### Conditional write idempotence

Conditional writes can be *idempotent* if the conditional check is on the same attribute that is being updated. This means that DynamoDB performs a given write request only if certain attribute values in the item match what you expect them to be at the time of the request.

For example, suppose that you issue an `UpdateItem` request to increase the `Price` of an item by 3, but only if the `Price` is currently 20. After you send the request, but before you get the results back, a network error occurs, and you don't know whether the request was successful. Because this conditional write is idempotent, you can retry the same `UpdateItem` request, and DynamoDB updates the item only if the `Price` is currently 20.

### Capacity units consumed by conditional writes

If a `ConditionExpression` evaluates to false during a conditional write, DynamoDB still consumes write capacity from the table:

- If the item does not currently exist in the table, DynamoDB consumes one write capacity unit.
- If the item does exist, the number of write capacity units consumed depends on the size of the item. For example, a failed conditional write of a 1 KB item would consume one write capacity unit. If the item were twice that size, the failed conditional write would consume two write capacity units.

#### Note

Write operations consume *write* capacity units only. They never consume *read* capacity units.

A failed conditional write returns a `ConditionalCheckFailedException`. When this occurs, you don't receive any information in the response about the write capacity that was consumed. However, you

can view the `ConsumedWriteCapacityUnits` metric for the table in Amazon CloudWatch. For more information, see [DynamoDB metrics \(p. 1114\)](#) in [Logging and monitoring in DynamoDB \(p. 1112\)](#).

To return the number of write capacity units consumed during a conditional write, you use the `ReturnConsumedCapacity` parameter:

- `TOTAL` — Returns the total number of write capacity units consumed.
- `INDEXES` — Returns the total number of write capacity units consumed, with subtotals for the table and any secondary indexes that were affected by the operation.
- `NONE` — No write capacity details are returned. (This is the default.)

#### Note

Unlike a global secondary index, a local secondary index shares its provisioned throughput capacity with its table. Read and write activity on a local secondary index consumes provisioned throughput capacity from the table.

## Using expressions in DynamoDB

In Amazon DynamoDB, you use *expressions* to denote the attributes that you want to read from an item. You also use expressions when writing an item to indicate any conditions that must be met (also known as a conditional update), and to indicate how the attributes are to be updated. This section describes the basic expression grammar and the available kinds of expressions.

#### Note

For backward compatibility, DynamoDB also supports conditional parameters that do not use expressions. For more information, see [Legacy conditional parameters \(p. 1318\)](#).

New applications should use expressions rather than the legacy parameters.

#### Topics

- [Specifying item attributes when using expressions \(p. 354\)](#)
- [Projection expressions \(p. 357\)](#)
- [Expression attribute names in DynamoDB \(p. 358\)](#)
- [Expression attribute values \(p. 360\)](#)
- [Condition expressions \(p. 361\)](#)
- [Update expressions \(p. 370\)](#)

### Specifying item attributes when using expressions

This section describes how to refer to item attributes in an expression in Amazon DynamoDB. You can work with any attribute, even if it is deeply nested within multiple lists and maps.

#### Topics

- [Top-level attributes \(p. 355\)](#)
- [Nested attributes \(p. 356\)](#)
- [Document paths \(p. 356\)](#)

### A Sample Item: ProductCatalog

The following is a representation of an item in the `ProductCatalog` table. (This table is described in [Example tables and data \(p. 1256\)](#).)

```
{  
    "Id": 123,  
    "Title": "Bicycle 123",
```

```

    "Description": "123 description",
    "BicycleType": "Hybrid",
    "Brand": "Brand-Company C",
    "Price": 500,
    "Color": ["Red", "Black"],
    "ProductCategory": "Bicycle",
    "InStock": true,
    "QuantityOnHand": null,
    "RelatedItems": [
        341,
        472,
        649
    ],
    "Pictures": {
        "FrontView": "http://example.com/products/123_front.jpg",
        "RearView": "http://example.com/products/123_rear.jpg",
        "SideView": "http://example.com/products/123_left_side.jpg"
    },
    "ProductReviews": {
        "FiveStar": [
            "Excellent! Can't recommend it highly enough! Buy it!",
            "Do yourself a favor and buy this."
        ],
        "OneStar": [
            "Terrible product! Do not buy this."
        ],
        "Comment": "This product sells out quickly during the summer",
        "Safety.Warning": "Always wear a helmet"
    }
}

```

Note the following:

- The partition key value (`Id`) is 123. There is no sort key.
- Most of the attributes have scalar data types, such as `String`, `Number`, `Boolean`, and `Null`.
- One attribute (`Color`) is a `String Set`.
- The following attributes are document data types:
  - A list of `RelatedItems`. Each element is an `Id` for a related product.
  - A map of `Pictures`. Each element is a short description of a picture, along with a URL for the corresponding image file.
  - A map of `ProductReviews`. Each element represents a rating and a list of reviews corresponding to that rating. Initially, this map is populated with five-star and one-star reviews.

### Top-level attributes

An attribute is said to be *top level* if it is not embedded within another attribute. For the `ProductCatalog` item, the top-level attributes are as follows:

- `Id`
- `Title`
- `Description`
- `BicycleType`
- `Brand`
- `Price`
- `Color`
- `ProductCategory`
- `InStock`

- `QuantityOnHand`
- `RelatedItems`
- `Pictures`
- `ProductReviews`
- `Comment`
- `Safety.Warning`

All of these top-level attributes are scalars, except for `Color` (list), `RelatedItems` (list), `Pictures` (map), and `ProductReviews` (map).

### Nested attributes

An attribute is said to be *nested* if it is embedded within another attribute. To access a nested attribute, you use *dereference operators*:

- `[n]` — for list elements
- `.` (dot) — for map elements

### Accessing list elements

The dereference operator for a list element is `[N]`, where  $n$  is the element number. List elements are zero-based, so `[0]` represents the first element in the list, `[1]` represents the second, and so on. Here are some examples:

- `MyList[0]`
- `AnotherList[12]`
- `ThisList[5][11]`

The element `ThisList[5]` is itself a nested list. Therefore, `ThisList[5][11]` refers to the 12th element in that list.

The number within the square brackets must be a non-negative integer. Therefore, the following expressions are not valid:

- `MyList[-1]`
- `MyList[0.4]`

### Accessing map elements

The dereference operator for a map element is `.` (a dot). Use a dot as a separator between elements in a map:

- `MyMap.nestedField`
- `MyMap.nestedField.deeplyNestedField`

### Document paths

In an expression, you use a *document path* to tell DynamoDB where to find an attribute. For a top-level attribute, the document path is simply the attribute name. For a nested attribute, you construct the document path using dereference operators.

The following are some examples of document paths. (Refer to the item shown in [Specifying item attributes when using expressions \(p. 354\)](#).)

- A top-level scalar attribute.

`Description`

- A top-level list attribute. (This returns the entire list, not just some of the elements.)

`RelatedItems`

- The third element from the `RelatedItems` list. (Remember that list elements are zero-based.)

`RelatedItems[2]`

- The front-view picture of the product.

`Pictures.FrontView`

- All of the five-star reviews.

`ProductReviews.FiveStar`

- The first of the five-star reviews.

`ProductReviews.FiveStar[0]`

### Note

The maximum depth for a document path is 32. Therefore, the number of dereferences operators in a path cannot exceed this limit.

You can use any attribute name in a document path, provided that the first character is a-z or A-Z and the second character (if present) is a-z, A-Z, or 0-9. If an attribute name does not meet this requirement, you must define an expression attribute name as a placeholder. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#).

## Projection expressions

To read data from a table, you use operations such as `GetItem`, `Query`, or `Scan`. Amazon DynamoDB returns all the item attributes by default. To get only some, rather than all of the attributes, use a projection expression.

A *projection expression* is a string that identifies the attributes that you want. To retrieve a single attribute, specify its name. For multiple attributes, the names must be comma-separated.

The following are some examples of projection expressions, based on the `ProductCatalog` item from [Specifying item attributes when using expressions \(p. 354\)](#):

- A single top-level attribute.

`Title`

- Three top-level attributes. DynamoDB retrieves the entire `Color` set.

`Title, Price, Color`

- Four top-level attributes. DynamoDB returns the entire contents of `RelatedItems` and `ProductReviews`.

`Title, Description, RelatedItems, ProductReviews`

You can use any attribute name in a projection expression, provided that the first character is a-z or A-Z and the second character (if present) is a-z, A-Z, or 0-9. If an attribute name does not meet this requirement, you must define an expression attribute name as a placeholder. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#).

The following AWS CLI example shows how to use a projection expression with a `GetItem` operation. This projection expression retrieves a top-level scalar attribute (`Description`), the first element in a list (`RelatedItems[0]`), and a list nested within a map (`ProductReviews.FiveStar`).

```
aws dynamodb get-item \
--table-name ProductCatalog \
--key file://key.json \
--projection-expression "Description, RelatedItems[0], ProductReviews.FiveStar"
```

The arguments for `--key` are stored in the `key.json` file.

```
{  
    "Id": { "N": "123" }  
}
```

For programming language-specific code examples, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

### Expression attribute names in DynamoDB

An *expression attribute name* is a placeholder that you use in an Amazon DynamoDB expression as an alternative to an actual attribute name. An expression attribute name must begin with a pound sign (#), and be followed by one or more alphanumeric characters.

This section describes several situations in which you must use expression attribute names.

#### Note

The examples in this section use the AWS Command Line Interface (AWS CLI). For programming language-specific code examples, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

#### Topics

- [Reserved words \(p. 358\)](#)
- [Attribute names containing special characters \(p. 359\)](#)
- [Nested attributes \(p. 359\)](#)
- [Repeating attribute names \(p. 360\)](#)

#### Reserved words

Sometimes you might need to write an expression containing an attribute name that conflicts with a DynamoDB reserved word. (For a complete list of reserved words, see [Reserved words in DynamoDB \(p. 1310\)](#).)

For example, the following AWS CLI example would fail because `COMMENT` is a reserved word.

```
aws dynamodb get-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"123"}}' \
--projection-expression "Comment"
```

To work around this, you can replace `Comment` with an expression attribute name such as `#c`. The # (pound sign) is required and indicates that this is a placeholder for an attribute name. The AWS CLI example would now look like the following.

```
aws dynamodb get-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"123"}}' \
--projection-expression "#c" \
--expression-attribute-names '{"#c":"Comment"}'
```

**Note**

If an attribute name begins with a number, contains a space or contains a reserved word, you *must* use an expression attribute name to replace that attribute's name in the expression.

### Attribute names containing special characters

In an expression, a dot (".") is interpreted as a separator character in a document path. However, DynamoDB also allows you to use a dot character and other special characters, such as a hyphen ("-") as part of an attribute name. This can be ambiguous in some cases. To illustrate, suppose that you wanted to retrieve the Safety.Warning attribute from a ProductCatalog item (see [Specifying item attributes when using expressions \(p. 354\)](#)).

Suppose that you wanted to access Safety.Warning using a projection expression.

```
aws dynamodb get-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"123"}}' \  
    --projection-expression "Safety.Warning"
```

DynamoDB would return an empty result, rather than the expected string ("Always wear a helmet"). This is because DynamoDB interprets a dot in an expression as a document path separator. In this case, you must define an expression attribute name (such as #sw) as a substitute for Safety.Warning. You could then use the following projection expression.

```
aws dynamodb get-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"123"}}' \  
    --projection-expression "#sw" \  
    --expression-attribute-names '{"#sw":"Safety.Warning"}'
```

DynamoDB would then return the correct result.

**Note**

If an attribute name contains a dot (".") or a hyphen ("-"), you *must* use an expression attribute name to replace that attribute's name in the expression.

### Nested attributes

Suppose that you wanted to access the nested attribute ProductReviews.OneStar, using the following projection expression.

```
aws dynamodb get-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"123"}}' \  
    --projection-expression "ProductReviews.OneStar"
```

The result would contain all of the one-star product reviews, which is expected.

But what if you decided to use an expression attribute name instead? For example, what would happen if you were to define #pr1star as a substitute for ProductReviews.OneStar?

```
aws dynamodb get-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"123"}}' \  
    --projection-expression "#pr1star" \  
    --expression-attribute-names '{"#pr1star":"ProductReviews.OneStar"}'
```

DynamoDB would return an empty result instead of the expected map of one-star reviews. This is because DynamoDB interprets a dot in an expression attribute name as a character within an attribute's

name. When DynamoDB evaluates the expression attribute name `#pr1star`, it determines that `ProductReviews.OneStar` refers to a scalar attribute—which is not what was intended.

The correct approach would be to define an expression attribute name for each element in the document path:

- `#pr - ProductReviews`
- `#1star - OneStar`

You could then use `#pr.#1star` for the projection expression.

```
aws dynamodb get-item \
    --table-name ProductCatalog \
    --key '{"Id":{"N":"123"}}' \
    --projection-expression "#pr.#1star" \
    --expression-attribute-names '{"#pr":"ProductReviews", "#1star": "OneStar"}'
```

DynamoDB would then return the correct result.

### Repeating attribute names

Expression attribute names are helpful when you need to refer to the same attribute name repeatedly. For example, consider the following expression for retrieving some of the reviews from a `ProductCatalog` item.

```
aws dynamodb get-item \
    --table-name ProductCatalog \
    --key '{"Id":{"N":"123"}}' \
    --projection-expression "ProductReviews.FiveStar, ProductReviews.ThreeStar,
    ProductReviews.OneStar"
```

To make this more concise, you can replace `ProductReviews` with an expression attribute name such as `#pr`. The revised expression would now look like the following.

- `#pr.FiveStar, #pr.ThreeStar, #pr.OneStar`

```
aws dynamodb get-item \
    --table-name ProductCatalog \
    --key '{"Id":{"N":"123"}}' \
    --projection-expression "#pr.FiveStar, #pr.ThreeStar, #pr.OneStar" \
    --expression-attribute-names '{"#pr":"ProductReviews"}'
```

If you define an expression attribute name, you must use it consistently throughout the entire expression. Also, you cannot omit the `#` symbol.

### Expression attribute values

If you need to compare an attribute with a value, define an expression attribute value as a placeholder. *Expression attribute values* in Amazon DynamoDB are substitutes for the actual values that you want to compare—values that you might not know until runtime. An expression attribute value must begin with a colon (`:`) and be followed by one or more alphanumeric characters.

For example, suppose that you wanted to return all of the `ProductCatalog` items that are available in Black and cost 500 or less. You could use a `Scan` operation with a filter expression, as in this AWS Command Line Interface (AWS CLI) example.

```
aws dynamodb scan \
```

```
--table-name ProductCatalog \
--filter-expression "contains(Color, :c) and Price <= :p" \
--expression-attribute-values file://values.json
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
  ":c": { "S": "Black" },
  ":p": { "N": "500" }
}
```

**Note**

A Scan operation reads every item in a table. So you should avoid using Scan with large tables. The filter expression is applied to the Scan results, and items that don't match the filter expression are discarded.

If you define an expression attribute value, you must use it consistently throughout the entire expression. Also, you can't omit the `:` symbol.

Expression attribute values are used with key condition expressions, condition expressions, update expressions, and filter expressions.

**Note**

For programming language-specific code examples, see [Getting started with DynamoDB and AWS SDKs \(p. 85\)](#).

## Condition expressions

To manipulate data in an Amazon DynamoDB table, you use the `PutItem`, `UpdateItem`, and `DeleteItem` operations. (You can also use `BatchWriteItem` to perform multiple `PutItem` or `DeleteItem` operations in a single call.)

For these data manipulation operations, you can specify a *condition expression* to determine which items should be modified. If the condition expression evaluates to true, the operation succeeds; otherwise, the operation fails.

The following are some AWS Command Line Interface (AWS CLI) examples of using condition expressions. These examples are based on the `ProductCatalog` table, which was introduced in [Specifying item attributes when using expressions \(p. 354\)](#). The partition key for this table is `Id`; there is no sort key. The following `PutItem` operation creates a sample `ProductCatalog` item that the examples refer to.

```
aws dynamodb put-item \
  --table-name ProductCatalog \
  --item file://item.json
```

The arguments for `--item` are stored in the `item.json` file. (For simplicity, only a few item attributes are used.)

```
{
  "Id": { "N": "456" },
  "ProductCategory": { "S": "Sporting Goods" },
  "Price": { "N": "650" }
}
```

## Topics

- [Conditional put \(p. 362\)](#)
- [Conditional deletes \(p. 362\)](#)
- [Conditional updates \(p. 363\)](#)

- [Conditional expression examples \(p. 364\)](#)
- [Comparison operator and function reference \(p. 365\)](#)

## Conditional put

The `PutItem` operation overwrites an item with the same key (if it exists). If you want to avoid this, use a condition expression. This allows the write to proceed only if the item in question does not already have the same key.

```
aws dynamodb put-item \
  --table-name ProductCatalog \
  --item file://item.json \
  --condition-expression "attribute_not_exists(Id)"
```

If the condition expression evaluates to false, DynamoDB returns the following error message: The conditional request failed.

### Note

For more information about `attribute_not_exists` and other functions, see [Comparison operator and function reference \(p. 365\)](#).

## Conditional deletes

To perform a conditional delete, you use a `DeleteItem` operation with a condition expression. The condition expression must evaluate to true in order for the operation to succeed; otherwise, the operation fails.

Consider the item from [Condition expressions \(p. 361\)](#).

```
{  
  "Id": {  
    "N": "456"  
  },  
  "Price": {  
    "N": "650"  
  },  
  "ProductCategory": {  
    "S": "Sporting Goods"  
  }  
}
```

Suppose that you wanted to delete the item, but only under the following conditions:

- The `ProductCategory` is either "Sporting Goods" or "Gardening Supplies."
- The `Price` is between 500 and 600.

The following example tries to delete the item.

```
aws dynamodb delete-item \
  --table-name ProductCatalog \
  --key '{"Id":{"N":"456"}}' \
  --condition-expression "(ProductCategory IN (:cat1, :cat2)) and (Price between :lo  
and :hi)" \
  --expression-attribute-values file://values.json
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
```

```

":cat1": {"S": "Sporting Goods"},
":cat2": {"S": "Gardening Supplies"},
":lo": {"N": "500"},
":hi": {"N": "600"}
}

```

#### **Note**

In the condition expression, the `:` (colon character) indicates an *expression attribute value*—a placeholder for an actual value. For more information, see [Expression attribute values \(p. 360\)](#). For more information about `IN`, `AND`, and other keywords, see [Comparison operator and function reference \(p. 365\)](#).

In this example, the `ProductCategory` comparison evaluates to true, but the `Price` comparison evaluates to false. This causes the condition expression to evaluate to false and the `DeleteItem` operation to fail.

#### Conditional updates

To perform a conditional update, you use an `UpdateItem` operation with a condition expression. The condition expression must evaluate to true in order for the operation to succeed; otherwise, the operation fails.

#### **Note**

`UpdateItem` also supports *update expressions*, where you specify the modifications you want to make to an item. For more information, see [Update expressions \(p. 370\)](#).

Suppose that you started with the item shown in [Condition expressions \(p. 361\)](#).

```
{
    "Id": {"N": "456"},
    "Price": {"N": "650"},
    "ProductCategory": {"S": "Sporting Goods"}
}
```

The following example performs an `UpdateItem` operation. It tries to reduce the `Price` of a product by 75—but the condition expression prevents the update if the current `Price` is less than or equal to 500.

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id": {"N": "456"}}' \
--update-expression "SET Price = Price - :discount" \
--condition-expression "Price > :limit" \
--expression-attribute-values file://values.json
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
    ":discount": {"N": "75"},
    ":limit": {"N": "500"}
}
```

If the starting `Price` is 650, the `UpdateItem` operation reduces the `Price` to 575. If you run the `UpdateItem` operation again, the `Price` is reduced to 500. If you run it a third time, the condition expression evaluates to false, and the update fails.

#### **Note**

In the condition expression, the `:` (colon character) indicates an *expression attribute value*—a placeholder for an actual value. For more information, see [Expression attribute values \(p. 360\)](#). For more information about `>` and other operators, see [Comparison operator and function reference \(p. 365\)](#).

## Conditional expression examples

For more information about the functions used in the following examples, see [Comparison operator and function reference \(p. 365\)](#). If you want to know more about how to specify different attribute types in an expression, see [Specifying item attributes when using expressions \(p. 354\)](#).

### Checking for attributes in an item

You can check for the existence (or nonexistence) of any attribute. If the condition expression evaluates to true, the operation succeeds; otherwise, it fails.

The following example uses `attribute_not_exists` to delete a product only if it does not have a `Price` attribute.

```
aws dynamodb delete-item \
--table-name ProductCatalog \
--key '{"Id": {"N": "456"}}' \
--condition-expression "attribute_not_exists(Price)"
```

DynamoDB also provides an `attribute_exists` function. The following example deletes a product only if it has received poor reviews.

```
aws dynamodb delete-item \
--table-name ProductCatalog \
--key '{"Id": {"N": "456"}}' \
--condition-expression "attribute_exists(ProductReviews.OneStar)"
```

### Checking for attribute type

You can check the data type of an attribute value by using the `attribute_type` function. If the condition expression evaluates to true, the operation succeeds; otherwise, it fails.

The following example uses `attribute_type` to delete a product only if it has a `Color` attribute of type String Set.

```
aws dynamodb delete-item \
--table-name ProductCatalog \
--key '{"Id": {"N": "456"}}' \
--condition-expression "attribute_type(Color, :v_sub)" \
--expression-attribute-values file://expression-attribute-values.json
```

The arguments for `--expression-attribute-values` are stored in the `expression-attribute-values.json` file.

```
{
  ":v_sub": {"S": "SS"}
}
```

### Checking string starting value

You can check if a String attribute value begins with a particular substring by using the `begins_with` function. If the condition expression evaluates to true, the operation succeeds; otherwise, it fails.

The following example uses `begins_with` to delete a product only if the `FrontView` element of the `Pictures` map starts with a specific value.

```
aws dynamodb delete-item \
--table-name ProductCatalog \
--key '{"Id": {"N": "456"}}' \
--condition-expression "begins_with(Pictures.FrontView, :v_sub)" \
```

```
--expression-attribute-values file://expression-attribute-values.json
```

The arguments for `--expression-attribute-values` are stored in the `expression-attribute-values.json` file.

```
{  
    ":v_sub": {"S": "http://"}  
}
```

### Checking for an element in a set

You can check for an element in a set or look for a substring within a string by using the `contains` function. If the condition expression evaluates to true, the operation succeeds; otherwise, it fails.

The following example uses `contains` to delete a product only if the `Color` String Set has an element with a specific value.

```
aws dynamodb delete-item \  
    --table-name ProductCatalog \  
    --key '{"Id": {"N": "456"}}' \  
    --condition-expression "contains(Color, :v_sub)" \  
    --expression-attribute-values file://expression-attribute-values.json
```

The arguments for `--expression-attribute-values` are stored in the `expression-attribute-values.json` file.

```
{  
    ":v_sub": {"S": "Red"}  
}
```

### Checking the size of an attribute value

You can check for the size of an attribute value by using the `size` function. If the condition expression evaluates to true, the operation succeeds; otherwise, it fails.

The following example uses `size` to delete a product only if the size of the `VideoClip` Binary attribute is greater than 64000 bytes.

```
aws dynamodb delete-item \  
    --table-name ProductCatalog \  
    --key '{"Id": {"N": "456"}}' \  
    --condition-expression "size(VideoClip) > :v_sub" \  
    --expression-attribute-values file://expression-attribute-values.json
```

The arguments for `--expression-attribute-values` are stored in the `expression-attribute-values.json` file.

```
{  
    ":v_sub": {"N": "64000"}  
}
```

### Comparison operator and function reference

This section covers the built-in functions and keywords for writing filter expressions and condition expressions in Amazon DynamoDB.

#### Topics

- [Syntax for filter and condition expressions \(p. 366\)](#)

- [Making comparisons \(p. 366\)](#)
- [Functions \(p. 367\)](#)
- [Logical evaluations \(p. 369\)](#)
- [Parentheses \(p. 370\)](#)
- [Precedence in conditions \(p. 370\)](#)

### Syntax for filter and condition expressions

In the following syntax summary, an *operand* can be the following:

- A top-level attribute name, such as `Id`, `Title`, `Description`, or `ProductCategory`
- A document path that references a nested attribute

```
condition-expression ::=
    operand comparator operand
    | operand BETWEEN operand AND operand
    | operand IN ( operand (', ' operand (, ...) ))
    | function
    | condition AND condition
    | condition OR condition
    | NOT condition
    | ( condition )

comparator ::=
    =
    | <>
    | <
    | <=
    | >
    | >=

function ::=
    attribute_exists (path)
    | attribute_not_exists (path)
    | attribute_type (path, type)
    | begins_with (path, substr)
    | contains (path, operand)
    | size (path)
```

### Making comparisons

Use these comparators to compare an operand against a range of values or an enumerated list of values:

- $a = b$  — true if  $a$  is equal to  $b$
- $a <> b$  — true if  $a$  is not equal to  $b$
- $a < b$  — true if  $a$  is less than  $b$
- $a <= b$  — true if  $a$  is less than or equal to  $b$
- $a > b$  — true if  $a$  is greater than  $b$
- $a >= b$  — true if  $a$  is greater than or equal to  $b$

Use the `BETWEEN` and `IN` keywords to compare an operand against a range of values or an enumerated list of values:

- $a \text{ BETWEEN } b \text{ AND } c$  — true if  $a$  is greater than or equal to  $b$ , and less than or equal to  $c$ .
- $a \text{ IN } (b, c, d)$  — true if  $a$  is equal to any value in the list — for example, any of  $b$ ,  $c$  or  $d$ . The list can contain up to 100 values, separated by commas.

## Functions

Use the following functions to determine whether an attribute exists in an item, or to evaluate the value of an attribute. These function names are case sensitive. For a nested attribute, you must provide its full document path.

Function	Description
<code>attribute_exists (path)</code>	<p>True if the item contains the attribute specified by path.</p> <p>Example: Check whether an item in the <code>Product</code> table has a side view picture.</p> <ul style="list-style-type: none"> <li>• <code>attribute_exists (#Pictures.#SideView)</code></li> </ul>
<code>attribute_not_exists (path)</code>	<p>True if the attribute specified by path does not exist in the item.</p> <p>Example: Check whether an item has a <code>Manufacturer</code> attribute.</p> <ul style="list-style-type: none"> <li>• <code>attribute_not_exists (Manufacturer)</code></li> </ul>
<code>attribute_type (path, type)</code>	<p>True if the attribute at the specified path is of a particular data type. The type parameter must be one of the following:</p> <ul style="list-style-type: none"> <li>• S — String</li> <li>• SS — String Set</li> <li>• N — Number</li> <li>• NS — Number Set</li> <li>• B — Binary</li> <li>• BS — Binary Set</li> <li>• BOOL — Boolean</li> <li>• NULL — Null</li> <li>• L — List</li> <li>• M — Map</li> </ul> <p>You must use an expression attribute value for the type parameter.</p> <p>Example: Check whether the <code>QuantityOnHand</code> attribute is of type List. In this example, <code>:v_sub</code> is a placeholder for the string <code>L</code>.</p> <ul style="list-style-type: none"> <li>• <code>attribute_type (ProductReviews.FiveStar, :v_sub)</code></li> </ul> <p>You must use an expression attribute value for the type parameter.</p>
<code>begins_with (path, substr)</code>	True if the attribute specified by path begins with a particular substring.

Function	Description
	<p>Example: Check whether the first few characters of the front view picture URL are <code>http://</code>.</p> <ul style="list-style-type: none"> <li>• <code>begins_with (Pictures.FrontView, :v_sub)</code></li> </ul> <p>The expression attribute value <code>:v_sub</code> is a placeholder for <code>http://</code>.</p>
<code>contains (path, operand)</code>	<p>True if the attribute specified by path is one of the following:</p> <ul style="list-style-type: none"> <li>• A <code>String</code> that contains a particular substring.</li> <li>• A <code>Set</code> that contains a particular element within the set.</li> </ul> <p>The operand must be a <code>String</code> if the attribute specified by path is a <code>String</code>. If the attribute specified by path is a <code>Set</code>, the operand must be the set's element type.</p> <p>The path and the operand must be distinct; that is, <code>contains (a, a)</code> returns an error.</p> <p>Example: Check whether the <code>Brand</code> attribute contains the substring <code>Company</code>.</p> <ul style="list-style-type: none"> <li>• <code>contains (Brand, :v_sub)</code></li> </ul> <p>The expression attribute value <code>:v_sub</code> is a placeholder for <code>Company</code>.</p> <p>Example: Check whether the product is available in red.</p> <ul style="list-style-type: none"> <li>• <code>contains (Color, :v_sub)</code></li> </ul> <p>The expression attribute value <code>:v_sub</code> is a placeholder for <code>Red</code>.</p>

Function	Description
<code>size (path)</code>	<p>Returns a number representing an attribute's size. The following are valid data types for use with <code>size</code>.</p> <p>If the attribute is of type <code>String</code>, <code>size</code> returns the length of the string.</p> <p>Example: Check whether the string <code>Brand</code> is less than or equal to 20 characters. The expression attribute value <code>:v_sub</code> is a placeholder for 20.</p> <ul style="list-style-type: none"> <li>• <code>size (Brand) &lt;= :v_sub</code></li> </ul>
	<p>If the attribute is of type <code>Binary</code>, <code>size</code> returns the number of bytes in the attribute value.</p> <p>Example: Suppose that the <code>ProductCatalog</code> item has a binary attribute named <code>VideoClip</code>, which contains a short video of the product in use. The following expression checks whether <code>VideoClip</code> exceeds 64,000 bytes. The expression attribute value <code>:v_sub</code> is a placeholder for 64000.</p> <ul style="list-style-type: none"> <li>• <code>size(VideoClip) &gt; :v_sub</code></li> </ul>
	<p>If the attribute is a <code>Set</code> data type, <code>size</code> returns the number of elements in the set.</p> <p>Example: Check whether the product is available in more than one color. The expression attribute value <code>:v_sub</code> is a placeholder for 1.</p> <ul style="list-style-type: none"> <li>• <code>size (Color) &lt; :v_sub</code></li> </ul>
	<p>If the attribute is of type <code>List</code> or <code>Map</code>, <code>size</code> returns the number of child elements.</p> <p>Example: Check whether the number of <code>OneStar</code> reviews has exceeded a certain threshold. The expression attribute value <code>:v_sub</code> is a placeholder for 3.</p> <ul style="list-style-type: none"> <li>• <code>size(ProductReviews.OneStar) &gt; :v_sub</code></li> </ul>

### Logical evaluations

Use the `AND`, `OR`, and `NOT` keywords to perform logical evaluations. In the list following, `a` and `b` represent conditions to be evaluated.

- $a \text{ AND } b$  — true if  $a$  and  $b$  are both true.
- $a \text{ OR } b$  — true if either  $a$  or  $b$  (or both) are true.
- $\text{NOT } a$  — true if  $a$  is false; false if  $a$  is true.

### Parentheses

Use parentheses to change the precedence of a logical evaluation. For example, suppose that conditions  $a$  and  $b$  are true, and that condition  $c$  is false. The following expression evaluates to true:

- $a \text{ OR } b \text{ AND } c$

However, if you enclose a condition in parentheses, it is evaluated first. For example, the following evaluates to false:

- $(a \text{ OR } b) \text{ AND } c$

#### Note

You can nest parentheses in an expression. The innermost ones are evaluated first.

### Precedence in conditions

DynamoDB evaluates conditions from left to right using the following precedence rules:

- $= <> < <= > >=$
- IN
- BETWEEN
- attribute\_exists attribute\_not\_exists begins\_with contains
- Parentheses
- NOT
- AND
- OR

### Update expressions

To update an existing item in an Amazon DynamoDB table, you use the `UpdateItem` operation. You must provide the key of the item that you want to update. You must also provide an update expression, indicating the attributes that you want to modify and the values that you want to assign to them.

An *update expression* specifies how `UpdateItem` will modify the attributes of an item—for example, setting a scalar value or removing elements from a list or a map.

The following is a syntax summary for update expressions.

```
update-expression ::=  
  [ SET action [, action] ... ]  
  [ REMOVE action [, action] ... ]  
  [ ADD action [, action] ... ]  
  [ DELETE action [, action] ... ]
```

An update expression consists of one or more clauses. Each clause begins with a `SET`, `REMOVE`, `ADD`, or `DELETE` keyword. You can include any of these clauses in an update expression, in any order. However, each action keyword can appear only once.

Within each clause, there are one or more actions separated by commas. Each action represents a data modification.

The examples in this section are based on the `ProductCatalog` item shown in [Projection expressions \(p. 357\)](#).

### Topics

- [SET—modifying or adding item attributes \(p. 371\)](#)
- [REMOVE—deleting attributes from an item \(p. 375\)](#)
- [ADD—updating numbers and sets \(p. 376\)](#)
- [DELETE—removing elements from a set \(p. 377\)](#)

### [SET—modifying or adding item attributes](#)

Use the `SET` action in an update expression to add one or more attributes to an item. If any of these attributes already exists, they are overwritten by the new values.

You can also use `SET` to add or subtract from an attribute that is of type `Number`. To perform multiple `SET` actions, separate them with commas.

In the following syntax summary:

- The `path` element is the document path to the item.
- An `operand` element can be either a document path to an item or a function.

```
set-action ::=  
    path = value  
  
value ::=  
    operand  
    | operand '+' operand  
    | operand '-' operand  
  
operand ::=  
    path | function
```

The following `PutItem` operation creates a sample item that the examples refer to.

```
aws dynamodb put-item \  
  --table-name ProductCatalog \  
  --item file://item.json
```

The arguments for `--item` are stored in the `item.json` file. (For simplicity, only a few item attributes are used.)

```
{  
    "Id": {"N": "789"},  
    "ProductCategory": {"S": "Home Improvement"},  
    "Price": {"N": "52"},  
    "InStock": {"BOOL": true},  
    "Brand": {"S": "Acme"}  
}
```

### Topics

- [Modifying attributes \(p. 372\)](#)

- [Adding lists and maps \(p. 372\)](#)
- [Adding elements to a list \(p. 373\)](#)
- [Adding nested map attributes \(p. 373\)](#)
- [Incrementing and decrementing numeric attributes \(p. 374\)](#)
- [Appending elements to a list \(p. 374\)](#)
- [Preventing overwrites of an existing attribute \(p. 375\)](#)

## Modifying attributes

### Example

Update the `ProductCategory` and `Price` attributes.

```
aws dynamodb update-item \
    --table-name ProductCatalog \
    --key '{"Id":{"N":"789"}}' \
    --update-expression "SET ProductCategory = :c, Price = :p" \
    --expression-attribute-values file://values.json \
    --return-values ALL_NEW
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
    ":c": { "S": "Hardware" },
    ":p": { "N": "60" }
}
```

### Note

In the `UpdateItem` operation, `--return-values ALL_NEW` causes DynamoDB to return the item as it appears after the update.

## Adding lists and maps

### Example

Add a new list and a new map.

```
aws dynamodb update-item \
    --table-name ProductCatalog \
    --key '{"Id":{"N":"789"}}' \
    --update-expression "SET RelatedItems = :ri, ProductReviews = :pr" \
    --expression-attribute-values file://values.json \
    --return-values ALL_NEW
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
    ":ri": {
        "L": [
            { "S": "Hammer" }
        ]
    },
    ":pr": {
        "M": {
            "FiveStar": {
                "L": [

```

```
        { "S": "Best product ever!" }
    ]
}
}
```

## Adding elements to a list

### Example

Add a new attribute to the `RelatedItems` list. (Remember that list elements are zero-based, so [0] represents the first element in the list, [1] represents the second, and so on.)

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"789"}}' \
--update-expression "SET RelatedItems[1] = :ri" \
--expression-attribute-values file://values.json \
--return-values ALL_NEW
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
  ":ri": { "S": "Nails" }
}
```

### Note

When you use `SET` to update a list element, the contents of that element are replaced with the new data that you specify. If the element doesn't already exist, `SET` appends the new element at the end of the list.

If you add multiple elements in a single `SET` operation, the elements are sorted in order by element number.

## Adding nested map attributes

### Example

Add some nested map attributes.

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"789"}}' \
--update-expression "SET #pr.#5star[1] = :r5, #pr.#3star = :r3" \
--expression-attribute-names file://names.json \
--expression-attribute-values file://values.json \
--return-values ALL_NEW
```

The arguments for `--expression-attribute-names` are stored in the `names.json` file.

```
{
  "#pr": "ProductReviews",
  "#5star": "FiveStar",
  "#3star": "ThreeStar"
}
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
    ":r5": { "S": "Very happy with my purchase" },
    ":r3": {
        "L": [
            { "S": "Just OK - not that great" }
        ]
    }
}
```

### Incrementing and decrementing numeric attributes

You can add to or subtract from an existing numeric attribute. To do this, use the + (plus) and – (minus) operators.

#### Example

Decrease the Price of an item.

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"789"}}' \
--update-expression "SET Price = Price - :p" \
--expression-attribute-values '{":p": {"N":"15"}}' \
--return-values ALL_NEW
```

To increase the Price, you would use the + operator in the update expression.

#### Appending elements to a list

You can add elements to the end of a list. To do this, use SET with the list\_append function. (The function name is case sensitive.) The list\_append function is specific to the SET action and can only be used in an update expression. The syntax is as follows.

- `list_append (list1, list2)`

The function takes two lists as input and appends all elements from *list2* to *list1*.

#### Example

In [Adding elements to a list \(p. 373\)](#), you create the `RelatedItems` list and populate it with two elements: Hammer and Nails. Now you append two more elements to the end of `RelatedItems`.

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"789"}}' \
--update-expression "SET #ri = list_append(#ri, :vals)" \
--expression-attribute-names '{"#ri": "RelatedItems"}' \
--expression-attribute-values file://values.json \
--return-values ALL_NEW
```

The arguments for --expression-attribute-values are stored in the `values.json` file.

```
{
    ":vals": {
        "L": [
            { "S": "Screwdriver" },
            { "S": "Hacksaw" }
        ]
    }
}
```

```
}
```

Finally, you append one more element to the *beginning* of `RelatedItems`. To do this, swap the order of the `list_append` elements. (Remember that `list_append` takes two lists as input and appends the second list to the first.)

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"789"}}' \
--update-expression "SET #ri = list_append(:vals, #ri)" \
--expression-attribute-names '{"#ri": "RelatedItems"}' \
--expression-attribute-values '{":vals": {"L": [ { "S": "Chisel" } ]}}' \
--return-values ALL_NEW
```

The resulting `RelatedItems` attribute now contains five elements, in the following order: `Chisel`, `Hammer`, `Nails`, `Screwdriver`, `Hacksaw`.

### Preventing overwrites of an existing attribute

If you want to avoid overwriting an existing attribute, you can use `SET` with the `if_not_exists` function. (The function name is case sensitive.) The `if_not_exists` function is specific to the `SET` action and can only be used in an update expression. The syntax is as follows.

- `if_not_exists (path, value)`

If the item does not contain an attribute at the specified `path`, `if_not_exists` evaluates to `value`; otherwise, it evaluates to `path`.

### Example

Set the `Price` of an item, but only if the item does not already have a `Price` attribute. (If `Price` already exists, nothing happens.)

```
aws dynamodb update-item \
--table-name ProductCatalog \
--key '{"Id":{"N":"789"}}' \
--update-expression "SET Price = if_not_exists(Price, :p)" \
--expression-attribute-values '{":p": {"N": "100"}}' \
--return-values ALL_NEW
```

### REMOVE—deleting attributes from an item

Use the `REMOVE` action in an update expression to remove one or more attributes from an item in Amazon DynamoDB. To perform multiple `REMOVE` actions, separate them with commas.

The following is a syntax summary for `REMOVE` in an update expression. The only operand is the document path for the attribute that you want to remove.

```
remove-action ::=  
    path
```

### Example

Remove some attributes from an item. (If the attributes don't exist, nothing happens.)

```
aws dynamodb update-item \
```

```
--table-name ProductCatalog \
--key '{"Id":{"N":"789"}}' \
--update-expression "REMOVE Brand, InStock, QuantityOnHand" \
--return-values ALL_NEW
```

## Removing elements from a list

You can use REMOVE to delete individual elements from a list.

### Example

In [Appending elements to a list \(p. 374\)](#), you modify a list attribute (`RelatedItems`) so that it contained five elements:

- [0]—Chisel
- [1]—Hammer
- [2]—Nails
- [3]—Screwdriver
- [4]—Hacksaw

The following AWS Command Line Interface (AWS CLI) example deletes Hammer and Nails from the list.

```
aws dynamodb update-item \
  --table-name ProductCatalog \
  --key '{"Id":{"N":"789"}}' \
  --update-expression "REMOVE RelatedItems[1], RelatedItems[2]" \
  --return-values ALL_NEW
```

After Hammer and Nails are removed, the remaining elements are shifted. The list now contains the following:

- [0]—Chisel
- [1]—Screwdriver
- [2]—Hacksaw

## ADD—updating numbers and sets

### Note

In general, we recommend using SET rather than ADD.

Use the ADD action in an update expression to add a new attribute and its values to an item.

If the attribute already exists, the behavior of ADD depends on the attribute's data type:

- If the attribute is a number, and the value you are adding is also a number, the value is mathematically added to the existing attribute. (If the value is a negative number, it is subtracted from the existing attribute.)
- If the attribute is a set, and the value you are adding is also a set, the value is appended to the existing set.

### Note

The ADD action supports only number and set data types.

To perform multiple ADD actions, separate them with commas.

In the following syntax summary:

- The **path** element is the document path to an attribute. The attribute must be either a **Number** or a set data type.
- The **value** element is a number that you want to add to the attribute (for **Number** data types), or a set to append to the attribute (for set types).

```
add-action ::=  
    path value
```

### Adding a number

Assume that the **QuantityOnHand** attribute does not exist. The following AWS CLI example sets **QuantityOnHand** to 5.

```
aws dynamodb update-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"789"}}' \  
    --update-expression "ADD QuantityOnHand :q" \  
    --expression-attribute-values '{":q": {"N": "5"}}' \  
    --return-values ALL_NEW
```

Now that **QuantityOnHand** exists, you can rerun the example to increment **QuantityOnHand** by 5 each time.

### Adding elements to a set

Assume that the **Color** attribute does not exist. The following AWS CLI example sets **Color** to a string set with two elements.

```
aws dynamodb update-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"789"}}' \  
    --update-expression "ADD Color :c" \  
    --expression-attribute-values '{":c": {"SS":["Orange", "Purple"]}}' \  
    --return-values ALL_NEW
```

Now that **Color** exists, you can add more elements to it.

```
aws dynamodb update-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"789"}}' \  
    --update-expression "ADD Color :c" \  
    --expression-attribute-values '{":c": {"SS":["Yellow", "Green", "Blue"]}}' \  
    --return-values ALL_NEW
```

### DELETE—removing elements from a set

#### Important

The **DELETE** action supports only Set data types.

Use the **DELETE** action in an update expression to remove one or more elements from a set. To perform multiple **DELETE** actions, separate them with commas.

In the following syntax summary:

- The **path** element is the document path to an attribute. The attribute must be a set data type.

- The **subset** is one or more elements that you want to delete from **path**. You must specify **subset** as a set type.

```
delete-action ::=  
    path value
```

### Example

In [Adding elements to a set \(p. 377\)](#), you create the `Color` string set. This example removes some of the elements from that set.

```
aws dynamodb update-item \  
    --table-name ProductCatalog \  
    --key '{"Id":{"N":"789"}}' \  
    --update-expression "DELETE Color :p" \  
    --expression-attribute-values '{"": {"SS": ["Yellow", "Purple"]}}' \  
    --return-values ALL_NEW
```

## Expiring items by using DynamoDB Time to Live (TTL)

Amazon DynamoDB Time to Live (TTL) allows you to define a per-item timestamp to determine when an item is no longer needed. Shortly after the date and time of the specified timestamp, DynamoDB deletes the item from your table without consuming any write throughput. TTL is provided at no extra cost as a means to reduce stored data volumes by retaining only the items that remain current for your workload's needs.

TTL is useful if you store items that lose relevance after a specific time. The following are example TTL use cases:

- Remove user or sensor data after one year of inactivity in an application.
- Archive expired items to an Amazon S3 data lake via Amazon DynamoDB Streams and AWS Lambda.
- Retain sensitive data for a certain amount of time according to contractual or regulatory obligations.

For more information about TTL, see these topics:

- [Using Time to Live](#).
- [Time to Live: How It Works](#).
- [Enabling Time to Live](#).

### How it works: DynamoDB Time to Live (TTL)

When enabling TTL on a DynamoDB table, you must identify a specific attribute name that the service will look for when determining if an item is eligible for expiration. After you enable TTL on a table, a per-partition scanner background process automatically and continuously evaluates the expiry status of items in the table.

The scanner background process compares the current time, in [Unix epoch time format](#) in seconds, to the value stored in the user-defined attribute of an item. If the attribute is a `Number` data type, the attribute's value is a timestamp in [Unix epoch time format](#) in seconds, and the timestamp value is older than the current time but not five years older or more (in order to avoid a possible accidental deletion due to a malformed TTL value), then the item is set to expired. For specifics about formatting TTL attributes, see [Formatting an item's TTL attribute \(p. 380\)](#). A second background process scans for expired items and deletes them. Both processes take place automatically in the background, do not affect read or write traffic to the table, and do not have a monetary cost.

As items are deleted from the table, two background operations happen simultaneously:

- Items are removed from any local secondary index and global secondary index in the same way as a `DeleteItem` operation. This operation comes at no extra cost.
- A delete operation for each item enters the DynamoDB Stream, but is tagged as a system delete and not a regular delete. For more information about how to use this system delete, see [DynamoDB Streams and Time to Live](#).


### Important

- Depending on the size and activity level of a table, the actual delete operation of an expired item can vary. Because TTL is meant to be a background process, the nature of the capacity used to expire and delete items via TTL is variable (but free of charge). TTL typically deletes expired items within 48 hours of expiration.
- Items that have expired, but haven't yet been deleted by TTL, still appear in reads, queries, and scans. If you do not want expired items in the result set, you must filter them out. To do this, use a filter expression that returns only items where the Time to Live expiration value is greater than the current time in epoch format. For more information, see [Filter expressions for scan \(p. 446\)](#).
- Items that are past their expiration, but have not yet been deleted can still be updated, and successful updates to change or remove the expiration attribute will be honored.

You can monitor TTL rates on the CloudWatch metrics tab for a table, and see when and the rate at which items are deleted.

## Time to Live (TTL)

---



### Time to Live example

For example, consider a table named `SessionData` that tracks the session history of users. Each item in `SessionData` is identified by the partition key (`UserName`) and the sort key (`SessionId`). Additional

attributes like `UserName`, `SessionId`, `CreationTime`, and `ExpirationTime` track the session information. The `ExpirationTime` attribute is set as the TTL attribute on the table (not all of the attributes on each item are shown).

### SessionData

UserName	SessionId	CreationTime	ExpirationTime (TTL)	SessionInfo	...
user1	746865726527731571820360		1571827560	{JSON Document}	...
user2	6e6f7468696e671571820180		1571827380	{JSON Document}	...
user3	746f20736565201571820923		1571828123	{JSON Document}	...
user4	686572652121211571820683		1571827883	{JSON Document}	...
user5	6e6572642e2e2e1571820743		1571831543	{JSON Document}	...
...	...	...	...	...	...

In this example, each item has an `ExpirationTime` attribute value set when it is created. Consider the following table item.

### SessionData

UserName	SessionId	CreationTime	ExpirationTime (TTL)	SessionInfo	...
user1	746865726527731571820360		1571827560	{JSON Document}	...

In this example, the item `CreationTime` is set to Wednesday, October 23 08:46 AM UTC 2019, and the `ExpirationTime` is set 2 hours later at Wednesday, October 23 10:46 AM UTC 2019. The item expires when the current time, in epoch format, is greater than the time in the `ExpirationTime` attribute. In this case, the item with the key `{ Username: user1, SessionId: 74686572652773 }` expires 10:46 AM (1571827560).

### Using DynamoDB Time to Live (TTL)

When using TTL, most of the hard work is done behind the scenes by DynamoDB on your behalf. You should, though, be aware of a few considerations to help your implementation proceed smoothly.

#### Topics

- [Formatting an item's TTL attribute \(p. 380\)](#)
- [Usage notes \(p. 381\)](#)
- [Troubleshooting TTL \(p. 381\)](#)

#### [Formatting an item's TTL attribute](#)

When enabling TTL on a table, DynamoDB requires you to identify a specific attribute name that the service will look for when determining if an item is eligible for expiration. In addition, further

requirements ensure that the background TTL processes uses the value of the TTL attribute. If an item is to be eligible for expiration via TTL:

- The item must contain the attribute specified when TTL was enabled on the table. For example, if you specify for a table to use the attribute name `expdate` as the TTL attribute, but an item does not have an attribute with that name, the TTL process ignores the item.
- The TTL attribute's value must be a `Number` data type. For example, if you specify for a table to use the attribute name `expdate` as the TTL attribute, but the attribute on an item is a `String` data type, the TTL processes ignore the item.
- The TTL attribute's value must be a timestamp in [Unix epoch time format in seconds](#). If you use any other format, the TTL processes ignore the item. For example, if you set the value of the attribute to 1645119622, that is Thursday, February 17, 2022 17:40:22 (GMT), the item will be expired after that time. For help formatting your epoch timestamps, you can use third-party tools such as [Epoch Converter](#) to get a visual web form.
- The TTL attribute value must be a datetimestamp with an expiration of no more than five years in the past. For example, if you set the value of the attribute to 1171734022, that is February 17, 2007 17:40:22 (GMT) and older than five years. As a result, the TTL processes will not expire that item.

### Usage notes

When using TTL, consider the following:

- Enabling, disabling, or changing TTL settings on a table can take approximately one hour for the settings to propagate and to allow the execution of any further TTL related actions.
- You cannot reconfigure TTL to look for a different attribute. You must disable TTL, and then reenable TTL with the new attribute going forward.
- When you use AWS CloudFormation, you can enable TTL when creating a DynamoDB table. For more information, see the [AWS CloudFormation User Guide](#).
- You can use AWS Identity and Access Management (IAM) policies to prevent unauthorized updates to the TTL attribute on an item or the configuration of TTL. If you allow access to only specified actions in your existing IAM policies, ensure that your policies are updated to allow `dynamodb:UpdateTimeToLive` for roles that need to enable or disable TTL on tables. For more information, see [Using Identity-Based Policies \(IAM Policies\) for Amazon DynamoDB](#).
- Consider whether you need to do any post processing of deleted items via Amazon DynamoDB Streams, such as archiving items to an Amazon S3 data lake. The streams records of TTL deletes are marked as system deletes instead of normal deletes, and you can filter for system deletes by using an AWS Lambda function. For more information about the additions to the streams records, see [Amazon DynamoDB Streams and Time to Live](#).
- If data recovery is a concern, we recommend that you back up your tables.
  - For fully managed table backups, use DynamoDB [on-demand backups](#) or [continuous backups with point-in-time recovery](#).
  - For a 24-hour recovery window, you can use Amazon DynamoDB Streams. For more information, see [Amazon DynamoDB Streams and Time to Live](#).

### Troubleshooting TTL

If DynamoDB TTL is not working, check the following:

- Confirm that you have enabled TTL on the table, and the name of the attribute selected for TTL is set to what your code is writing into items. You can confirm this information on a table's *Overview* tab on the DynamoDB console.
- Look at Amazon CloudWatch metrics on the *Metrics* tab of the DynamoDB console to confirm that TTL is deleting items as you expect them to be deleted.

- Confirm that the TTL attribute value is properly formatted. For more information see, [Formatting an item's TTL attribute \(p. 380\)](#).

## Enabling Time to Live (TTL)

You can use the Amazon DynamoDB console or the AWS Command Line Interface (AWS CLI) to enable Time to Live. To use the API instead, see [Amazon DynamoDB API Reference](#).

### Topics

- [Enable Time to Live \(console\) \(p. 382\)](#)
- [Enable Time to Live \(AWS CLI\) \(p. 383\)](#)

### Enable Time to Live (console)

Follow these steps to enable Time to Live using the DynamoDB console:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. Choose **Tables**, and then choose the table that you want to modify.
3. In the **Additional settings** tab, in the **Time to Live (TTL)** section, choose **Enable**.



4. In the **Enable Time to Live (TTL)** page, enter the **TTL attribute name**.

The screenshot shows the 'TTL settings' section. It includes a 'TTL attribute name' input field containing 'ttl', with a note below it stating 'The name of the attribute that will be stored in the TTL timestamp.' and 'Between 1 and 255 characters.'

The screenshot shows the 'Preview' section. It includes a 'Simulated date and time' input field showing 'Epoch time value ▾' and '1629849640', with a note below it stating 'Specify the date and time to simulate which items would be expired.' and 'August 24, 2021, 17:00:40 (UTC-07:00)'. There is also a 'Run preview' button.

The screenshot shows a confirmation dialog box. It contains a note: 'Enabling TTL can take up to one hour to be applied across all partitions. You will not be able to make additional TTL changes until this update is complete.' At the bottom right are 'Cancel' and 'Enable TTL' buttons.

5. (Optional) To preview some of the items that will be deleted when TTL is enabled, choose **Run preview**.

**Warning**

This provides you with a sample list of items. It does not provide you with a complete list of items that will be deleted by TTL.

6. Choose **Enable TTL** to save the settings and enable TTL.

Now that TTL is enabled, the TTL attribute is marked **TTL** when you view items on the DynamoDB console. You can view the date and time that an item expires by hovering your pointer over the attribute.

### Enable Time to Live (AWS CLI)

1. Enable TTL on the **TTLEexample** table.

```
aws dynamodb update-time-to-live --table-name TTLEexample --time-to-live-specification "Enabled=true, AttributeName=ttl"
```

2. Describe TTL on the **TTLEexample** table.

```
aws dynamodb describe-time-to-live --table-name TTLEexample
{
    "TimeToLiveDescription": {
        "AttributeName": "ttl",
        "TimeToLiveStatus": "ENABLED"
    }
}
```

3. Add an item to the **TTLEexample** table with the Time to Live attribute set using the BASH shell and the AWS CLI.

```
EXP=`date -d '+5 days' +%%s`
aws dynamodb put-item --table-name "TTLEexample" --item '{"id": {"N": "1"}, "ttl": {"N": "'$EXP'"}}'
```

This example starts with the current date and adds 5 days to it to create an expiration time. Then, it converts the expiration time to epoch time format to finally add an item to the "TTLEexample" table.

**Note**

One way to set expiration values for Time to Live is to calculate the number of seconds to add to the expiration time. For example, 5 days is 432,000 seconds. However, it is often preferable to start with a date and work from there.

It is fairly simple to get the current time in epoch time format, as in the following examples.

- Linux Terminal: `date +%%s`
- Python: `import time; int(time.time())`
- Java: `System.currentTimeMillis() / 1000L`
- JavaScript: `Math.floor(Date.now() / 1000)`

### Working with items: Java

You can use the AWS SDK for Java Document API to perform typical create, read, update, and delete (CRUD) operations on Amazon DynamoDB items in a table.

### Note

The SDK for Java also provides an object persistence model, allowing you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code that you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

This section contains Java examples to perform several Java Document API item actions and several complete working examples.

### Topics

- [Putting an item \(p. 384\)](#)
- [Getting an item \(p. 387\)](#)
- [Batch write: Putting and deleting multiple items \(p. 388\)](#)
- [Batch get: Getting multiple items \(p. 389\)](#)
- [Updating an item \(p. 390\)](#)
- [Deleting an item \(p. 392\)](#)
- [Example: CRUD operations using the AWS SDK for Java document API \(p. 393\)](#)
- [Example: Batch operations using AWS SDK for Java document API \(p. 396\)](#)
- [Example: Handling binary type attributes using the AWS SDK for Java document API \(p. 400\)](#)

### [Putting an item](#)

The `putItem` method stores an item in a table. If the item exists, it replaces the entire item. Instead of replacing the entire item, if you want to update only specific attributes, you can use the `updateItem` method. For more information, see [Updating an item \(p. 390\)](#).

Follow these steps:

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `Table` class to represent the table you want to work with.
3. Create an instance of the `Item` class to represent the new item. You must specify the new item's primary key and its attributes.
4. Call the `putItem` method of the `Table` object, using the `Item` that you created in the preceding step.

The following Java code example demonstrates the preceding tasks. The code writes a new item to the `ProductCatalog` table.

### **Example**

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("ProductCatalog");

// Build a list of related items
List<Number> relatedItems = new ArrayList<Number>();
relatedItems.add(341);
relatedItems.add(472);
relatedItems.add(649);

//Build a map of product pictures
Map<String, String> pictures = new HashMap<String, String>();
pictures.put("FrontView", "http://example.com/products/123_front.jpg");
pictures.put("RearView", "http://example.com/products/123_rear.jpg");
pictures.put("SideView", "http://example.com/products/123_left_side.jpg");
```

```

//Build a map of product reviews
Map<String, List<String>> reviews = new HashMap<String, List<String>>();

List<String> fiveStarReviews = new ArrayList<String>();
fiveStarReviews.add("Excellent! Can't recommend it highly enough! Buy it!");
fiveStarReviews.add("Do yourself a favor and buy this");
reviews.put("FiveStar", fiveStarReviews);

List<String> oneStarReviews = new ArrayList<String>();
oneStarReviews.add("Terrible product! Do not buy this.");
reviews.put("OneStar", oneStarReviews);

// Build the item
Item item = new Item()
    .withPrimaryKey("Id", 123)
    .withString("Title", "Bicycle 123")
    .withString("Description", "123 description")
    .withString("BicycleType", "Hybrid")
    .withString("Brand", "Brand-Company C")
    .withNumber("Price", 500)
    .withStringSet("Color", new HashSet<String>(Arrays.asList("Red", "Black")))
    .withString("ProductCategory", "Bicycle")
    .withBoolean("InStock", true)
    .withNull("QuantityOnHand")
    .withList("RelatedItems", relatedItems)
    .withMap("Pictures", pictures)
    .withMap("Reviews", reviews);

// Write the item to the table
PutItemOutcome outcome = table.putItem(item);

```

In the preceding example, the item has attributes that are scalars (`String`, `Number`, `Boolean`, `Null`), sets (`String Set`), and document types (`List`, `Map`).

### Specifying optional parameters

Along with the required parameters, you can also specify optional parameters to the `putItem` method. For example, the following Java code example uses an optional parameter to specify a condition for uploading the item. If the condition you specify is not met, the AWS SDK for Java throws a `ConditionalCheckFailedException`. The code example specifies the following optional parameters in the `putItem` method:

- A `ConditionExpression` that defines the conditions for the request. The code defines the condition that the existing item with the same primary key is replaced only if it has an `ISBN` attribute that equals a specific value.
- A map for `ExpressionAttributeValues` that is used in the condition. In this case, there is only one substitution required: The placeholder `:val` in the condition expression is replaced at runtime with the actual `ISBN` value to be checked.

The following example adds a new book item using these optional parameters.

### Example

```

Item item = new Item()
    .withPrimaryKey("Id", 104)
    .withString("Title", "Book 104 Title")
    .withString("ISBN", "444-444444444")
    .withNumber("Price", 20)
    .withStringSet("Authors",
        new HashSet<String>(Arrays.asList("Author1", "Author2")));

```

```
Map<String, Object> expressionAttributeValues = new HashMap<String, Object>();
expressionAttributeValues.put(":val", "444-444444444");

PutItemOutcome outcome = table.putItem(
    item,
    "ISBN = :val", // ConditionExpression parameter
    null,           // ExpressionAttributeNames parameter - we're not using it for this
example
    expressionAttributeValues);
```

### PutItem and JSON documents

You can store a JSON document as an attribute in a DynamoDB table. To do this, use the `withJSON` method of `Item`. This method parses the JSON document and maps each element to a native DynamoDB data type.

Suppose that you wanted to store the following JSON document, containing vendors that can fulfill orders for a particular product.

### Example

```
{
    "V01": {
        "Name": "Acme Books",
        "Offices": [ "Seattle" ]
    },
    "V02": {
        "Name": "New Publishers, Inc.",
        "Offices": [ "London", "New York" ]
    },
    "V03": {
        "Name": "Better Buy Books",
        "Offices": [ "Tokyo", "Los Angeles", "Sydney" ]
    }
}
```

You can use the `withJSON` method to store this in the `ProductCatalog` table, in a Map attribute named `VendorInfo`. The following Java code example demonstrates how to do this.

```
// Convert the document into a String. Must escape all double-quotes.
String vendorDocument = "{"
+ "    \"V01\": {"
+ "        \"Name\": \"Acme Books\","
+ "        \"Offices\": [ \"Seattle\" ]"
+ "    },"
+ "    \"V02\": {"
+ "        \"Name\": \"New Publishers, Inc.\","
+ "        \"Offices\": [ \"London\", \"New York\" ]"
+ "    },"
+ "    \"V03\": {"
+ "        \"Name\": \"Better Buy Books\","
+ "        \"Offices\": [ \"Tokyo\", \"Los Angeles\", \"Sydney\" ]"
+ "    }"
+ "};"

Item item = new Item()
    .withPrimaryKey("Id", 210)
    .withString("Title", "Book 210 Title")
    .withString("ISBN", "210-2102102102")
    .withNumber("Price", 30)
    .withJSON("VendorInfo", vendorDocument);
```

```
PutItemOutcome outcome = table.putItem(item);
```

## Getting an item

To retrieve a single item, use the `getItem` method of a `Table` object. Follow these steps:

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `Table` class to represent the table you want to work with.
3. Call the `getItem` method of the `Table` instance. You must specify the primary key of the item that you want to retrieve.

The following Java code example demonstrates the preceding steps. The code gets the item that has the specified partition key.

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("ProductCatalog");

Item item = table.getItem("Id", 210);
```

## Specifying optional parameters

Along with the required parameters, you can also specify optional parameters for the `getItem` method. For example, the following Java code example uses an optional method to retrieve only a specific list of attributes and to specify strongly consistent reads. (To learn more about read consistency, see [Read consistency \(p. 17\)](#).)

You can use a `ProjectionExpression` to retrieve only specific attributes or elements, rather than an entire item. A `ProjectionExpression` can specify top-level or nested attributes using document paths. For more information, see [Projection expressions \(p. 357\)](#).

The parameters of the `getItem` method don't let you specify read consistency. However, you can create a `GetItemSpec`, which provides full access to all of the inputs to the low-level `GetItem` operation. The following code example creates a `GetItemSpec` and uses that spec as input to the `getItem` method.

## Example

```
GetItemSpec spec = new GetItemSpec()
    .withPrimaryKey("Id", 206)
    .withProjectionExpression("Id, Title, RelatedItems[0], Reviews.FiveStar")
    .withConsistentRead(true);

Item item = table.getItem(spec);

System.out.println(item.toJSONString());
```

To print an `Item` in a human-readable format, use the `toJSONPretty` method. The output from the previous example looks like the following.

```
{
    "RelatedItems" : [ 341 ],
    "Reviews" : {
        "FiveStar" : [ "Excellent! Can't recommend it highly enough! Buy it!", "Do yourself a favor and buy this" ]
    },
    "Id" : 123,
    "Title" : "20-Bicycle 123"
```

}

## GetItem and JSON documents

In the [PutItem and JSON documents \(p. 386\)](#) section, you store a JSON document in a Map attribute named `VendorInfo`. You can use the `getItem` method to retrieve the entire document in JSON format. Or you can use document path notation to retrieve only some of the elements in the document. The following Java code example demonstrates these techniques.

```
GetItemSpec spec = new GetItemSpec()
    .withPrimaryKey("Id", 210);

System.out.println("All vendor info:");
spec.withProjectionExpression("VendorInfo");
System.out.println(table.getItem(spec).toJSON());

System.out.println("A single vendor:");
spec.withProjectionExpression("VendorInfo.V03");
System.out.println(table.getItem(spec).toJSON());

System.out.println("First office location for this vendor:");
spec.withProjectionExpression("VendorInfo.V03.Offices[0]");
System.out.println(table.getItem(spec).toJSON());
```

The output from the previous example looks like the following.

```
All vendor info:
{"VendorInfo":{"V03":{"Name":"Better Buy Books","Offices":["Tokyo","Los
Angeles","Sydney"]}, "V02":{"Name":"New Publishers, Inc.", "Offices":["London","New
York"]}, "V01":{"Name":"Acme Books", "Offices":["Seattle"]}}}
A single vendor:
{"VendorInfo":{"V03":{"Name":"Better Buy Books","Offices":["Tokyo","Los
Angeles","Sydney"]}}}
First office location for a single vendor:
{"VendorInfo":{"V03":{"Offices":["Tokyo"]}}}
```

### Note

You can use the `toJSON` method to convert any item (or its attributes) to a JSON-formatted string. The following code retrieves several top-level and nested attributes and prints the results as JSON.

```
GetItemSpec spec = new GetItemSpec()
    .withPrimaryKey("Id", 210)
    .withProjectionExpression("VendorInfo.V01, Title, Price");

Item item = table.getItem(spec);
System.out.println(item.toJSON());
```

The output looks like the following.

```
{"VendorInfo":{"V01":{"Name":"Acme Books","Offices":
["Seattle"]}}, "Price":30, "Title":"Book 210 Title"}
```

## Batch write: Putting and deleting multiple items

*Batch write* refers to putting and deleting multiple items in a batch. The `batchWriteItem` method enables you to put and delete multiple items from one or more tables in a single call. The following are the steps to put or delete multiple items using the AWS SDK for Java Document API.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `TableWriteItems` class that describes all the put and delete operations for a table. If you want to write to multiple tables in a single batch write operation, you must create one `TableWriteItems` instance per table.
3. Call the `batchWriteItem` method by providing the `TableWriteItems` objects that you created in the preceding step.
4. Process the response. You should check if there were any unprocessed request items returned in the response. This could happen if you reach the provisioned throughput quota or some other transient error. Also, DynamoDB limits the request size and the number of operations you can specify in a request. If you exceed these limits, DynamoDB rejects the request. For more information, see [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#).

The following Java code example demonstrates the preceding steps. The example performs a `batchWriteItem` operation on two tables: `Forum` and `Thread`. The corresponding `TableWriteItems` objects define the following actions:

- Put an item in the `Forum` table.
- Put and delete an item in the `Thread` table.

The code then calls `batchWriteItem` to perform the operation.

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

TableWriteItems forumTableWriteItems = new TableWriteItems("Forum")
    .withItemsToPut(
        new Item()
            .withPrimaryKey("Name", "Amazon RDS")
            .withNumber("Threads", 0));

TableWriteItems threadTableWriteItems = new TableWriteItems("Thread")
    .withItemsToPut(
        new Item()
            .withPrimaryKey("ForumName", "Amazon RDS", "Subject", "Amazon RDS Thread 1")
            .withHashAndRangeKeysToDelete("ForumName", "Some partition key value", "Amazon S3",
                "Some sort key value"));

BatchWriteItemOutcome outcome = dynamoDB.batchWriteItem(forumTableWriteItems,
    threadTableWriteItems);

// Code for checking unprocessed items is omitted in this example
```

For a working example, see [Example: Batch write operation using the AWS SDK for Java document API \(p. 397\)](#).

### Batch get: Getting multiple items

The `batchGetItem` method enables you to retrieve multiple items from one or more tables. To retrieve a single item, you can use the `getItem` method.

Follow these steps:

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `TableKeysAndAttributes` class that describes a list of primary key values to retrieve from a table. If you want to read from multiple tables in a single batch get operation, you must create one `TableKeysAndAttributes` instance per table.

3. Call the `batchGetItem` method by providing the `TableKeysAndAttributes` objects that you created in the preceding step.

The following Java code example demonstrates the preceding steps. The example retrieves two items from the `Forum` table and three items from the `Thread` table.

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

    TableKeysAndAttributes forumTableKeysAndAttributes = new
    TableKeysAndAttributes(forumTableName);
    forumTableKeysAndAttributes.addHashOnlyPrimaryKeys("Name",
    "Amazon S3",
    "Amazon DynamoDB");

TableKeysAndAttributes threadTableKeysAndAttributes = new
    TableKeysAndAttributes(threadTableName);
threadTableKeysAndAttributes.addHashAndRangePrimaryKeys("ForumName", "Subject",
    "Amazon DynamoDB", "DynamoDB Thread 1",
    "Amazon DynamoDB", "DynamoDB Thread 2",
    "Amazon S3", "S3 Thread 1");

BatchGetItemOutcome outcome = dynamoDB.batchGetItem(
    forumTableKeysAndAttributes, threadTableKeysAndAttributes);

for (String tableName : outcome.getTableItems().keySet()) {
    System.out.println("Items in table " + tableName);
    List<Item> items = outcome.getTableItems().get(tableName);
    for (Item item : items) {
        System.out.println(item);
    }
}
```

### Specifying optional parameters

Along with the required parameters, you can also specify optional parameters when using `batchGetItem`. For example, you can provide a `ProjectionExpression` with each `TableKeysAndAttributes` you define. This allows you to specify the attributes that you want to retrieve from the table.

The following code example retrieves two items from the `Forum` table. The `withProjectionExpression` parameter specifies that only the `Threads` attribute is to be retrieved.

### Example

```
TableKeysAndAttributes forumTableKeysAndAttributes = new TableKeysAndAttributes("Forum")
    .withProjectionExpression("Threads");

forumTableKeysAndAttributes.addHashOnlyPrimaryKeys("Name",
    "Amazon S3",
    "Amazon DynamoDB");

BatchGetItemOutcome outcome = dynamoDB.batchGetItem(forumTableKeysAndAttributes);
```

### Updating an item

The `updateItem` method of a `Table` object can update existing attribute values, add new attributes, or delete attributes from an existing item.

The `updateItem` method behaves as follows:

- If an item does not exist (no item in the table with the specified primary key), `updateItem` adds a new item to the table.
- If an item exists, `updateItem` performs the update as specified by the `UpdateExpression` parameter.

#### **Note**

It is also possible to "update" an item using `putItem`. For example, if you call `putItem` to add an item to the table, but there is already an item with the specified primary key, `putItem` replaces the entire item. If there are attributes in the existing item that are not specified in the input, `putItem` removes those attributes from the item.

In general, we recommend that you use `updateItem` whenever you want to modify any item attributes. The `updateItem` method only modifies the item attributes that you specify in the input, and the other attributes in the item remain unchanged.

Follow these steps:

1. Create an instance of the `Table` class to represent the table that you want to work with.
2. Call the `updateTable` method of the `Table` instance. You must specify the primary key of the item that you want to retrieve, along with an `UpdateExpression` that describes the attributes to modify and how to modify them.

The following Java code example demonstrates the preceding tasks. The code updates a book item in the `ProductCatalog` table. It adds a new author to the set of `Authors` and deletes the existing `ISBN` attribute. It also reduces the price by one.

An `ExpressionAttributeValues` map is used in the `UpdateExpression`. The placeholders `:val1` and `:val2` are replaced at runtime with the actual values for `Authors` and `Price`.

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("ProductCatalog");

Map<String, String> expressionAttributeNames = new HashMap<String, String>();
expressionAttributeNames.put("#A", "Authors");
expressionAttributeNames.put("#P", "Price");
expressionAttributeNames.put("#I", "ISBN");

Map<String, Object> expressionAttributeValues = new HashMap<String, Object>();
expressionAttributeValues.put(":val1",
    new HashSet<String>(Arrays.asList("Author YY","Author ZZ")));
expressionAttributeValues.put(":val2", 1); //Price

UpdateItemOutcome outcome = table.updateItem(
    "Id", // key attribute name
    101, // key attribute value
    "add #A :val1 set #P = #P - :val2 remove #I", // UpdateExpression
    expressionAttributeNames,
    expressionAttributeValues);
```

#### [Specifying optional parameters](#)

Along with the required parameters, you can also specify optional parameters for the `updateItem` method, including a condition that must be met in order for the update to occur. If the condition you specify is not met, the AWS SDK for Java throws a `ConditionalCheckFailedException`. For example, the following Java code example conditionally updates a book item price to 25. It specifies a `ConditionExpression` stating that the price should be updated only if the existing price is 20.

## Example

```
Table table = dynamoDB.getTable("ProductCatalog");

Map<String, String> expressionAttributeNames = new HashMap<String, String>();
expressionAttributeNames.put("#P", "Price");

Map<String, Object> expressionAttributeValues = new HashMap<String, Object>();
expressionAttributeValues.put(":val1", 25); // update Price to 25...
expressionAttributeValues.put(":val2", 20); //...but only if existing Price is 20

UpdateItemOutcome outcome = table.updateItem(
    new PrimaryKey("Id",101),
    "set #P = :val1", // UpdateExpression
    "#P >= :val2", // ConditionExpression
    expressionAttributeNames,
    expressionAttributeValues);
```

## Atomic counter

You can use `updateItem` to implement an atomic counter, where you increment or decrement the value of an existing attribute without interfering with other write requests. To increment an atomic counter, use an `UpdateExpression` with a `set` action to add a numeric value to an existing attribute of type `Number`.

The following example demonstrates this, incrementing the `Quantity` attribute by one. It also demonstrates the use of the `ExpressionAttributeNames` parameter in an `UpdateExpression`.

```
Table table = dynamoDB.getTable("ProductCatalog");

Map<String, String> expressionAttributeNames = new HashMap<String, String>();
expressionAttributeNames.put("#p", "PageCount");

Map<String, Object> expressionAttributeValues = new HashMap<String, Object>();
expressionAttributeValues.put(":val", 1);

UpdateItemOutcome outcome = table.updateItem(
    "Id", 121,
    "set #p = #p + :val",
    expressionAttributeNames,
    expressionAttributeValues);
```

## Deleting an item

The `deleteItem` method deletes an item from a table. You must provide the primary key of the item that you want to delete.

Follow these steps:

1. Create an instance of the DynamoDB client.
2. Call the `deleteItem` method by providing the key of the item you want to delete.

The following Java example demonstrates these tasks.

## Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("ProductCatalog");
```

```
DeleteItemOutcome outcome = table.deleteItem("Id", 101);
```

## Specifying optional parameters

You can specify optional parameters for `deleteItem`. For example, the following Java code example specifies a `ConditionExpression`, stating that a book item in `ProductCatalog` can only be deleted if the book is no longer in publication (the `InPublication` attribute is false).

### Example

```
Map<String, Object> expressionAttributeValues = new HashMap<String, Object>();
expressionAttributeValues.put(":val", false);

DeleteItemOutcome outcome = table.deleteItem("Id", 103,
    "InPublication = :val",
    null, // ExpressionAttributeNames - not used in this example
    expressionAttributeValues);
```

## Example: CRUD operations using the AWS SDK for Java document API

The following code example illustrates CRUD operations on an Amazon DynamoDB item. The example creates an item, retrieves it, performs various updates, and finally deletes the item.

### Note

The SDK for Java also provides an object persistence model, enabling you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code that you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

### Note

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples.document;

import java.io.IOException;
import java.util.Arrays;
import java.util.HashMap;
import java.util.HashSet;
import java.util.Map;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.DeleteItemOutcome;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Item;
```

```

import com.amazonaws.services.dynamodbv2.document.Table;
import com.amazonaws.services.dynamodbv2.document.UpdateItemOutcome;
import com.amazonaws.services.dynamodbv2.document.spec.DeleteItemSpec;
import com.amazonaws.services.dynamodbv2.document.spec.UpdateItemSpec;
import com.amazonaws.services.dynamodbv2.document.utils.NameMap;
import com.amazonaws.services.dynamodbv2.document.utils.ValueMap;
import com.amazonaws.services.dynamodbv2.model.ReturnValue;

public class DocumentAPIItemCRUDExample {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDB dynamoDB = new DynamoDB(client);

    static String tableName = "ProductCatalog";

    public static void main(String[] args) throws IOException {

        createItems();

        retrieveItem();

        // Perform various updates.
        updateMultipleAttributes();
        updateAddNewAttribute();
        updateExistingAttributeConditionally();

        // Delete the item.
        deleteItem();

    }

    private static void createItems() {

        Table table = dynamoDB.getTable(tableName);
        try {

            Item item = new Item().withPrimaryKey("Id", 120).withString("Title", "Book 120
Title")
                .withString("ISBN", "120-1111111111")
                .withStringSet("Authors", new HashSet<String>(Arrays.asList("Author12",
"Author22")))
                .withNumber("Price", 20).withString("Dimensions",
"8.5x11.0x.75").withNumber("PageCount", 500)
                .withBoolean("InPublication", false).withString("ProductCategory", "Book");
            table.putItem(item);

            item = new Item().withPrimaryKey("Id", 121).withString("Title", "Book 121
Title")
                .withString("ISBN", "121-1111111111")
                .withStringSet("Authors", new HashSet<String>(Arrays.asList("Author21",
"Author 22")))
                .withNumber("Price", 20).withString("Dimensions",
"8.5x11.0x.75").withNumber("PageCount", 500)
                .withBoolean("InPublication", true).withString("ProductCategory", "Book");
            table.putItem(item);

        }
        catch (Exception e) {
            System.err.println("Create items failed.");
            System.err.println(e.getMessage());
        }
    }

    private static void retrieveItem() {
        Table table = dynamoDB.getTable(tableName);

```

```

try {

    Item item = table.getItem("Id", 120, "Id", ISBN, Title, Authors, null);

    System.out.println("Printing item after retrieving it....");
    System.out.println(item.toJSONString());

}
catch (Exception e) {
    System.err.println("GetItem failed.");
    System.err.println(e.getMessage());
}

}

private static void updateAddNewAttribute() {
    Table table = dynamoDB.getTable(tableName);

    try {

        UpdateItemSpec updateItemSpec = new UpdateItemSpec().withPrimaryKey("Id", 121)
            .withUpdateExpression("set #na = :val1").withNameMap(new
NameMap().with("#na", "NewAttribute"))
            .WithValueMap(new ValueMap().withString(":val1", "Some
value")).withReturnValues(ReturnValue.ALL_NEW);

        UpdateItemOutcome outcome = table.updateItem(updateItemSpec);

        // Check the response.
        System.out.println("Printing item after adding new attribute...");
        System.out.println(outcome.getItem().toJSONPretty());

    }
    catch (Exception e) {
        System.err.println("Failed to add new attribute in " + tableName);
        System.err.println(e.getMessage());
    }
}

private static void updateMultipleAttributes() {

    Table table = dynamoDB.getTable(tableName);

    try {

        UpdateItemSpec updateItemSpec = new UpdateItemSpec().withPrimaryKey("Id", 120)
            .withUpdateExpression("add #a :val1 set #na=:val2")
            .withNameMap(new NameMap().with("#a", "Authors").with("#na",
"NewAttribute"))
            .WithValueMap(
                new ValueMap().withStringSet(":val1", "Author YY", "Author
ZZ").withString(":val2", "someValue"))
            .withReturnValues(ReturnValue.ALL_NEW);

        UpdateItemOutcome outcome = table.updateItem(updateItemSpec);

        // Check the response.
        System.out.println("Printing item after multiple attribute update...");
        System.out.println(outcome.getItem().toJSONPretty());

    }
    catch (Exception e) {
        System.err.println("Failed to update multiple attributes in " + tableName);
        System.err.println(e.getMessage());
    }
}

```

```

        }

    }

    private static void updateExistingAttributeConditionally() {
        Table table = dynamoDB.getTable(tableName);

        try {

            // Specify the desired price (25.00) and also the condition (price =
            // 20.00)

            UpdateItemSpec updateItemSpec = new UpdateItemSpec().withPrimaryKey("Id", 120)
                .withReturnValues(ReturnValue.ALL_NEW).withUpdateExpression("set #p
= :val1")
                .withConditionExpression("#p = :val2").withNameMap(new NameMap().with("#p",
"Price"))
                .WithValueMap(new ValueMap().withNumber(":val1", 25).withNumber(":val2",
20));

            UpdateItemOutcome outcome = table.updateItem(updateItemSpec);

            // Check the response.
            System.out.println("Printing item after conditional update to new
attribute...");  

            System.out.println(outcome.getItem().toJSONPretty());
        }

        catch (Exception e) {
            System.err.println("Error updating item in " + tableName);
            System.err.println(e.getMessage());
        }
    }

    private static void deleteItem() {
        Table table = dynamoDB.getTable(tableName);

        try {

            DeleteItemSpec deleteItemSpec = new DeleteItemSpec().withPrimaryKey("Id", 120)
                .withConditionExpression("#ip = :val").withNameMap(new
NameMap().with("#ip", "InPublication"))
                .WithValueMap(new ValueMap().withBoolean(":val",
false)).withReturnValues(ReturnValue.ALL_OLD);

            DeleteItemOutcome outcome = table.deleteItem(deleteItemSpec);

            // Check the response.
            System.out.println("Printing item that was deleted...");  

            System.out.println(outcome.getItem().toJSONPretty());
        }

        catch (Exception e) {
            System.err.println("Error deleting item in " + tableName);
            System.err.println(e.getMessage());
        }
    }
}

```

### [Example: Batch operations using AWS SDK for Java document API](#)

This section provides examples of batch write and batch get operations in Amazon DynamoDB using the AWS SDK for Java Document API.

### Note

The SDK for Java also provides an object persistence model, enabling you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code that you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

### Topics

- [Example: Batch write operation using the AWS SDK for Java document API \(p. 397\)](#)
- [Example: Batch get operation using the AWS SDK for Java document API \(p. 399\)](#)

### [Example: Batch write operation using the AWS SDK for Java document API](#)

The following Java code example uses the `batchWriteItem` method to perform the following put and delete operations:

- Put one item in the `Forum` table.
- Put one item and delete one item from the `Thread` table.

You can specify any number of put and delete requests against one or more tables when creating your batch write request. However, `batchWriteItem` limits the size of a batch write request and the number of put and delete operations in a single batch write operation. If your request exceeds these limits, your request is rejected. If your table does not have sufficient provisioned throughput to serve this request, the unprocessed request items are returned in the response.

The following example checks the response to see if it has any unprocessed request items. If it does, it loops back and resends the `batchWriteItem` request with unprocessed items in the request. If you followed the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section, you should already have created the `Forum` and `Thread` tables. You can also create these tables and upload sample data programmatically. For more information, see [Creating example tables and uploading data using the AWS SDK for Java \(p. 1265\)](#).

For step-by-step instructions for testing the following sample, see [Java code examples \(p. 274\)](#).

### Example

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
  
package com.amazonaws.codesamples.document;  
  
import java.io.IOException;  
import java.util.Arrays;  
import java.util.HashSet;  
import java.util.List;  
import java.util.Map;  
  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
```

```

import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.BatchWriteItemOutcome;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Item;
import com.amazonaws.services.dynamodbv2.document.TableWriteItems;
import com.amazonaws.services.dynamodbv2.model.WriteRequest;

public class DocumentAPIBatchWrite {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDB dynamoDB = new DynamoDB(client);

    static String forumTableName = "Forum";
    static String threadTableName = "Thread";

    public static void main(String[] args) throws IOException {
        writeMultipleItemsBatchWrite();
    }

    private static void writeMultipleItemsBatchWrite() {
        try {
            // Add a new item to Forum
            TableWriteItems forumTableWriteItems = new TableWriteItems(forumTableName) // Forum
                .withItemsToPut(new Item().withPrimaryKey("Name", "Amazon RDS").withNumber("Threads", 0));

            // Add a new item, and delete an existing item, from Thread
            // This table has a partition key and range key, so need to specify
            // both of them
            TableWriteItems threadTableWriteItems = new TableWriteItems(threadTableName)
                .withItemsToPut(new Item().withPrimaryKey("ForumName", "Amazon RDS", "Subject", "Amazon RDS Thread 1")
                    .withString("Message", "ElasticCache Thread 1 message")
                    .withStringSet("Tags", new HashSet<String>(Arrays.asList("cache", "in-memory"))));
                .withHashAndRangeKeysToDelete("ForumName", "Subject", "Amazon S3", "S3 Thread 100");

            System.out.println("Making the request.");
            BatchWriteItemOutcome outcome = dynamoDB.batchWriteItem(forumTableWriteItems,
            threadTableWriteItems);

            do {
                // Check for unprocessed keys which could happen if you exceed
                // provisioned throughput

                Map<String, List<WriteRequest>> unprocessedItems =
                outcome.getUnprocessedItems();

                if (outcome.getUnprocessedItems().size() == 0) {
                    System.out.println("No unprocessed items found");
                }
                else {
                    System.out.println("Retrieving the unprocessed items");
                    outcome = dynamoDB.batchWriteItemUnprocessed(unprocessedItems);
                }
            } while (outcome.getUnprocessedItems().size() > 0);

        }
        catch (Exception e) {
    
```

```
        System.err.println("Failed to retrieve items: ");
        e.printStackTrace(System.err);
    }

}

}
```

### Example: Batch get operation using the AWS SDK for Java document API

The following Java code example uses the `batchGetItem` method to retrieve multiple items from the `Forum` and the `Thread` tables. The `BatchGetItemRequest` specifies the table names and a list of keys for each item to get. The example processes the response by printing the items retrieved.

#### Note

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

### Example

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples.document;

import java.io.IOException;
import java.util.List;
import java.util.Map;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.BatchGetItemOutcome;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Item;
import com.amazonaws.services.dynamodbv2.document.TableKeysAndAttributes;
import com.amazonaws.services.dynamodbv2.model.KeysAndAttributes;

public class DocumentAPIBatchGet {
    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDB dynamoDB = new DynamoDB(client);

    static String forumTableName = "Forum";
    static String threadTableName = "Thread";

    public static void main(String[] args) throws IOException {
        retrieveMultipleItemsBatchGet();
    }
}
```

```

private static void retrieveMultipleItemsBatchGet() {

    try {

        TableKeysAndAttributes forumTableKeysAndAttributes = new
TableKeysAndAttributes(forumTableName);
        // Add a partition key
        forumTableKeysAndAttributes.addHashOnlyPrimaryKeys("Name", "Amazon S3", "Amazon
DynamoDB");

        TableKeysAndAttributes threadTableKeysAndAttributes = new
TableKeysAndAttributes(threadTableName);
        // Add a partition key and a sort key
        threadTableKeysAndAttributes.addHashAndRangePrimaryKeys("ForumName", "Subject",
"Amazon DynamoDB",
        "DynamoDB Thread 1", "Amazon DynamoDB", "DynamoDB Thread 2", "Amazon S3",
"S3 Thread 1");

        System.out.println("Making the request.");

        BatchGetItemOutcome outcome =
dynamoDB.batchGetItem(forumTableKeysAndAttributes,
            threadTableKeysAndAttributes);

        Map<String, KeysAndAttributes> unprocessed = null;

        do {
            for (String tableName : outcome.getTableItems().keySet()) {
                System.out.println("Items in table " + tableName);
                List<Item> items = outcome.getTableItems().get(tableName);
                for (Item item : items) {
                    System.out.println(item.toJSONPretty());
                }
            }
            // Check for unprocessed keys which could happen if you exceed
            // provisioned
            // throughput or reach the limit on response size.
            unprocessed = outcome.getUnprocessedKeys();

            if (unprocessed.isEmpty()) {
                System.out.println("No unprocessed keys found");
            }
            else {
                System.out.println("Retrieving the unprocessed keys");
                outcome = dynamoDB.batchGetItemUnprocessed(unprocessed);
            }
        } while (!unprocessed.isEmpty());

    }
    catch (Exception e) {
        System.err.println("Failed to retrieve items.");
        System.err.println(e.getMessage());
    }
}
}

```

#### [Example: Handling binary type attributes using the AWS SDK for Java document API](#)

The following Java code example illustrates handling binary type attributes. The example adds an item to the Reply table. The item includes a binary type attribute (`ExtendedMessage`) that stores

compressed data. The example then retrieves the item and prints all the attribute values. For illustration, the example uses the `GZIPOutputStream` class to compress a sample stream and assign it to the `ExtendedMessage` attribute. When the binary attribute is retrieved, it is decompressed using the `GZIPInputStream` class.

**Note**

The SDK for Java also provides an object persistence model, enabling you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code that you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

If you followed the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section, you should already have created the `Reply` table. You can also create this table programmatically. For more information, see [Creating example tables and uploading data using the AWS SDK for Java \(p. 1265\)](#).

For step-by-step instructions for testing the following sample, see [Java code examples \(p. 274\)](#).

**Example**

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
  
package com.amazonaws.codesamples.document;  
  
import java.io.ByteArrayInputStream;  
import java.io.ByteArrayOutputStream;  
import java.io.IOException;  
import java.nio.ByteBuffer;  
import java.text.SimpleDateFormat;  
import java.util.Date;  
import java.util.TimeZone;  
import java.util.zip.GZIPInputStream;  
import java.util.zip.GZIPOutputStream;  
  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;  
import com.amazonaws.services.dynamodbv2.document.DynamoDB;  
import com.amazonaws.services.dynamodbv2.document.Item;  
import com.amazonaws.services.dynamodbv2.document.Table;  
import com.amazonaws.services.dynamodbv2.document.spec.GetItemSpec;  
  
public class DocumentAPIItemBinaryExample {  
  
    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();  
    static DynamoDB dynamoDB = new DynamoDB(client);  
  
    static String tableName = "Reply";  
    static SimpleDateFormat dateFormatter = new SimpleDateFormat("yyyy-MM-  
dd'T'HH:mm:ss.SSS'Z'");  
  
    public static void main(String[] args) throws IOException {  
        try {
```

```

        // Format the primary key values
        String threadId = "Amazon DynamoDB#DynamoDB Thread 2";

        dateFormatter.setTimeZone(TimeZone.getTimeZone("UTC"));
        String replyDateTime = dateFormatter.format(new Date());

        // Add a new reply with a binary attribute type
        createItem(threadId, replyDateTime);

        // Retrieve the reply with a binary attribute type
        retrieveItem(threadId, replyDateTime);

        // clean up by deleting the item
        deleteItem(threadId, replyDateTime);
    }
    catch (Exception e) {
        System.err.println("Error running the binary attribute type example: " + e);
        e.printStackTrace(System.err);
    }
}

public static void createItem(String threadId, String replyDateTime) throws IOException
{
    Table table = dynamoDB.getTable(tableName);

    // Craft a long message
    String messageInput = "Long message to be compressed in a lengthy forum reply";

    // Compress the long message
    ByteBuffer compressedMessage = compressString(messageInput.toString());

    table.putItem(new Item().withPrimaryKey("Id", threadId).withString("ReplyDateTime",
    replyDateTime)
        .withString("Message", "Long message follows").withBinary("ExtendedMessage",
    compressedMessage)
        .withString("PostedBy", "User A"));
}

public static void retrieveItem(String threadId, String replyDateTime) throws IOException
{
    Table table = dynamoDB.getTable(tableName);

    GetItemSpec spec = new GetItemSpec().withPrimaryKey("Id", threadId,
    "ReplyDateTime", replyDateTime)
        .withConsistentRead(true);

    Item item = table.getItem(spec);

    // Uncompress the reply message and print
    String uncompressed =
uncompressString(ByteBuffer.wrap(item.getBinary("ExtendedMessage")));

    System.out.println("Reply message:\n" + " Id: " + item.getString("Id") + "\n" +
    " ReplyDateTime: "
        + item.getString("ReplyDateTime") + "\n" + " PostedBy: " +
    item.getString("PostedBy") + "\n" + " Message: "
        + item.getString("Message") + "\n" + " ExtendedMessage (uncompressed): " +
    uncompressed + "\n");
}

public static void deleteItem(String threadId, String replyDateTime) {
    Table table = dynamoDB.getTable(tableName);
}

```

```

        table.deleteItem("Id", threadId, "ReplyDateTime", replyDateTime);
    }

    private static ByteBuffer compressString(String input) throws IOException {
        // Compress the UTF-8 encoded String into a byte[]
        ByteArrayOutputStream baos = new ByteArrayOutputStream();
        GZIPOutputStream os = new GZIPOutputStream(baos);
        os.write(input.getBytes("UTF-8"));
        os.close();
        baos.close();
        byte[] compressedBytes = baos.toByteArray();

        // The following code writes the compressed bytes to a ByteBuffer.
        // A simpler way to do this is by simply calling
        // ByteBuffer.wrap(compressedBytes);
        // However, the longer form below shows the importance of resetting the
        // position of the buffer
        // back to the beginning of the buffer if you are writing bytes directly
        // to it, since the SDK
        // will consider only the bytes after the current position when sending
        // data to DynamoDB.
        // Using the "wrap" method automatically resets the position to zero.
        ByteBuffer buffer = ByteBuffer.allocate(compressedBytes.length);
        buffer.put(compressedBytes, 0, compressedBytes.length);
        buffer.position(0); // Important: reset the position of the ByteBuffer
                           // to the beginning
        return buffer;
    }

    private static String uncompressString(ByteBuffer input) throws IOException {
        byte[] bytes = input.array();
        ByteArrayInputStream bais = new ByteArrayInputStream(bytes);
        ByteArrayOutputStream baos = new ByteArrayOutputStream();
        GZIPInputStream is = new GZIPInputStream(bais);

        int chunkSize = 1024;
        byte[] buffer = new byte[chunkSize];
        int length = 0;
        while ((length = is.read(buffer, 0, chunkSize)) != -1) {
            baos.write(buffer, 0, length);
        }

        String result = new String(baos.toByteArray(), "UTF-8");

        is.close();
        baos.close();
        bais.close();

        return result;
    }
}

```

## Working with items: .NET

You can use the AWS SDK for .NET low-level API to perform typical create, read, update, and delete (CRUD) operations on an item in a table. The following are the common steps that you follow to perform data CRUD operations using the .NET low-level API:

1. Create an instance of the `AmazonDynamoDBClient` class (the client).
2. Provide the operation-specific required parameters in a corresponding request object.

For example, use the `PutItemRequest` request object when uploading an item and use the `GetItemRequest` request object when retrieving an existing item.

- You can use the request object to provide both the required and optional parameters.
3. Run the appropriate method provided by the client by passing in the request object that you created in the preceding step.

The `AmazonDynamoDBClient` client provides `PutItem`, `GetItem`, `UpdateItem`, and `DeleteItem` methods for the CRUD operations.

## Topics

- [Putting an item \(p. 404\)](#)
- [Getting an item \(p. 405\)](#)
- [Updating an item \(p. 407\)](#)
- [Atomic counter \(p. 408\)](#)
- [Deleting an item \(p. 409\)](#)
- [Batch write: Putting and deleting multiple items \(p. 410\)](#)
- [Batch get: Getting multiple items \(p. 411\)](#)
- [Example: CRUD operations using the AWS SDK for .NET low-level API \(p. 414\)](#)
- [Example: Batch operations using the AWS SDK for .NET low-level API \(p. 418\)](#)
- [Example: Handling binary type attributes using the AWS SDK for .NET low-level API \(p. 424\)](#)

## Putting an item

The `PutItem` method uploads an item to a table. If the item exists, it replaces the entire item.

### Note

Instead of replacing the entire item, if you want to update only specific attributes, you can use the `UpdateItem` method. For more information, see [Updating an item \(p. 407\)](#).

The following are the steps to upload an item using the low-level .NET SDK API:

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Provide the required parameters by creating an instance of the `PutItemRequest` class.

To put an item, you must provide the table name and the item.
3. Run the `PutItem` method by providing the `PutItemRequest` object that you created in the preceding step.

The following C# example demonstrates the preceding steps. The example uploads an item to the `ProductCatalog` table.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new PutItemRequest
{
    TableName = tableName,
    Item = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue { N = "201" } },
        { "Title", new AttributeValue { S = "Book 201 Title" } },
        { "ISBN", new AttributeValue { S = "11-11-11-11" } },
    }
}
```

```

        { "Price", new AttributeValue { S = "20.00" }},
        {
            "Authors",
            new AttributeValue
            { SS = new List<string>{"Author1", "Author2"} }
        }
    };
client.PutItem(request);

```

In the preceding example, you upload a book item that has the `Id`, `Title`, `ISBN`, and `Authors` attributes. Note that `Id` is a numeric type attribute, and all other attributes are of the string type. `Authors` is a `String` set.

### Specifying optional parameters

You can also provide optional parameters using the `PutItemRequest` object as shown in the following C# example. The example specifies the following optional parameters:

- `ExpressionAttributeNames`, `ExpressionAttributeValues`, and `ConditionExpression` specify that the item can be replaced only if the existing item has the `ISBN` attribute with a specific value.
- `ReturnValues` parameter to request the old item in the response.

### Example

```

var request = new PutItemRequest
{
    TableName = tableName,
    Item = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue { N = "104" }},
        { "Title", new AttributeValue { S = "Book 104 Title" }},
        { "ISBN", new AttributeValue { S = "444-4444444444" }},
        { "Authors",
            new AttributeValue { SS = new List<string>{"Author3"} }
        },
        // Optional parameters.
        ExpressionAttributeNames = new Dictionary<string,string>()
        {
            {"#I", "ISBN"}
        },
        ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
        {
            {":isbn",new AttributeValue {S = "444-4444444444"}}
        },
        ConditionExpression = "#I = :isbn"
    };
    var response = client.PutItem(request);
}

```

For more information, see [PutItem](#).

### Getting an item

The `GetItem` method retrieves an item.

#### Note

To retrieve multiple items, you can use the `BatchGetItem` method. For more information, see [Batch get: Getting multiple items \(p. 411\)](#).

The following are the steps to retrieve an existing item using the low-level AWS SDK for .NET API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Provide the required parameters by creating an instance of the `GetItemRequest` class.  
To get an item, you must provide the table name and primary key of the item.
3. Run the `GetItem` method by providing the `GetItemRequest` object that you created in the preceding step.

The following C# example demonstrates the preceding steps. The example retrieves an item from the `ProductCatalog` table.

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new GetItemRequest
{
    TableName = tableName,
    Key = new Dictionary<string,AttributeValue>() { { "Id", new AttributeValue { N =
"202" } } },
};
var response = client.GetItem(request);

// Check the response.
var result = response.GetItemResult;
var attributeMap = result.Item; // Attribute list in the response.
```

### Specifying optional parameters

You can also provide optional parameters using the `GetItemRequest` object, as shown in the following C# example. The sample specifies the following optional parameters:

- `ProjectionExpression` parameter to specify the attributes to retrieve.
- `ConsistentRead` parameter to perform a strongly consistent read. To learn more read consistency, see [Read consistency \(p. 17\)](#).

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new GetItemRequest
{
    TableName = tableName,
    Key = new Dictionary<string,AttributeValue>() { { "Id", new AttributeValue { N =
"202" } } },
    // Optional parameters.
    ProjectionExpression = "Id, ISBN, Title, Authors",
    ConsistentRead = true
};

var response = client.GetItem(request);

// Check the response.
var result = response.GetItemResult;
var attributeMap = result.Item;
```

For more information, see [GetItem](#).

## Updating an item

The `UpdateItem` method updates an existing item if it is present. You can use the `UpdateItem` operation to update existing attribute values, add new attributes, or delete attributes from the existing collection. If the item that has the specified primary key is not found, it adds a new item.

The `UpdateItem` operation uses the following guidelines:

- If the item does not exist, `UpdateItem` adds a new item using the primary key that is specified in the input.
- If the item exists, `UpdateItem` applies the updates as follows:
  - Replaces the existing attribute values by the values in the update.
  - If the attribute that you provide in the input does not exist, it adds a new attribute to the item.
  - If the input attribute is null, it deletes the attribute, if it is present.
  - If you use `ADD` for the `Action`, you can add values to an existing set (string or number set), or mathematically add (use a positive number) or subtract (use a negative number) from the existing numeric attribute value.

### Note

The `PutItem` operation also can perform an update. For more information, see [Putting an item \(p. 404\)](#). For example, if you call `PutItem` to upload an item and the primary key exists, the `PutItem` operation replaces the entire item. If there are attributes in the existing item and those attributes are not specified in the input, the `PutItem` operation deletes those attributes. However, `UpdateItem` updates only the specified input attributes. Any other existing attributes of that item remain unchanged.

The following are the steps to update an existing item using the low-level .NET SDK API:

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Provide the required parameters by creating an instance of the `UpdateItemRequest` class.

This is the request object in which you describe all the updates, such as add attributes, update existing attributes, or delete attributes. To delete an existing attribute, specify the attribute name with null value.

3. Run the `UpdateItem` method by providing the `UpdateItemRequest` object that you created in the preceding step.

The following C# code example demonstrates the preceding steps. The example updates a book item in the `ProductCatalog` table. It adds a new author to the `Authors` collection, and deletes the existing `ISBN` attribute. It also reduces the price by one.

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new UpdateItemRequest
{
    TableName = tableName,
    Key = new Dictionary<string,AttributeValue>() { { "Id", new AttributeValue { N =
"202" } } },
    ExpressionAttributeNames = new Dictionary<string,string>()
    {
        { "#A", "Authors" },
        { "#P", "Price" },
        { "#NA", "NewAttribute" },
        { "#I", "ISBN" }
    }
}
```

```

},
ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
{
    {":auth",new AttributeValue { SS = {"Author YY","Author ZZ"}}},
    {":p",new AttributeValue {N = "1"}},
    {":newattr",new AttributeValue {S = "someValue"}},
},
// This expression does the following:
// 1) Adds two new authors to the list
// 2) Reduces the price
// 3) Adds a new attribute to the item
// 4) Removes the ISBN attribute from the item
UpdateExpression = "ADD #A :auth SET #P = #P - :p, #NA = :newattr REMOVE #I"
};
var response = client.UpdateItem(request);

```

## Specifying optional parameters

You can also provide optional parameters using the `UpdateItemRequest` object, as shown in the following C# example. It specifies the following optional parameters:

- `ExpressionAttributeValues` and `ConditionExpression` to specify that the price can be updated only if the existing price is 20.00.
- `ReturnValues` parameter to request the updated item in the response.

## Example

```

AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new UpdateItemRequest
{
    Key = new Dictionary<string,AttributeValue>() { { "Id", new AttributeValue { N = "202" } } },

    // Update price only if the current price is 20.00.
    ExpressionAttributeNames = new Dictionary<string,string>()
    {
        {"#P", "Price"}
    },
    ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
    {
        {":newprice",new AttributeValue {N = "22"}},
        {":currprice",new AttributeValue {N = "20"}}
    },
    UpdateExpression = "SET #P = :newprice",
    ConditionExpression = "#P = :currprice",
    TableName = tableName,
    ReturnValues = "ALL_NEW" // Return all the attributes of the updated item.
};

var response = client.UpdateItem(request);

```

For more information, see [UpdateItem](#).

## Atomic counter

You can use `updateItem` to implement an atomic counter, where you increment or decrement the value of an existing attribute without interfering with other write requests. To update an atomic counter, use

`updateItem` with an attribute of type `Number` in the `UpdateExpression` parameter, and `ADD` as the `Action`.

The following example demonstrates this, incrementing the `Quantity` attribute by one.

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new UpdateItemRequest
{
    Key = new Dictionary<string, AttributeValue>() { { "Id", new AttributeValue { N =
    "121" } } },
    ExpressionAttributeNames = new Dictionary<string, string>()
    {
        {"#Q", "Quantity"}
    },
    ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
    {
        {"::incr",new AttributeValue {N = "1"}}
    },
    UpdateExpression = "SET #Q = #Q + :incr",
    TableName = tableName
};

var response = client.UpdateItem(request);
```

## Deleting an item

The `DeleteItem` method deletes an item from a table.

The following are the steps to delete an item using the low-level .NET SDK API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Provide the required parameters by creating an instance of the `DeleteItemRequest` class.  
To delete an item, the table name and item's primary key are required.
3. Run the `DeleteItem` method by providing the `DeleteItemRequest` object that you created in the preceding step.

## Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "ProductCatalog";

var request = new DeleteItemRequest
{
    TableName = tableName,
    Key = new Dictionary<string,AttributeValue>() { { "Id", new AttributeValue { N =
    "201" } } },
};

var response = client.DeleteItem(request);
```

## Specifying optional parameters

You can also provide optional parameters using the `DeleteItemRequest` object as shown in the following C# code example. It specifies the following optional parameters:

- `ExpressionAttributeValues` and `ConditionExpression` to specify that the book item can be deleted only if it is no longer in publication (the `InPublication` attribute value is false).

- `ReturnValues` parameter to request the deleted item in the response.

### Example

```
var request = new DeleteItemRequest
{
    TableName = tableName,
    Key = new Dictionary<string,AttributeValue>() { { "Id", new AttributeValue { N =
"201" } } },

    // Optional parameters.
    ReturnValues = "ALL_OLD",
    ExpressionAttributeNames = new Dictionary<string, string>()
    {
        {"#IP", "InPublication"}
    },
    ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
    {
        {"<:inpub>", new AttributeValue {BOOL = false}}
    },
    ConditionExpression = "#IP = :inpub"
};

var response = client.DeleteItem(request);
```

For more information, see [DeleteItem](#).

### Batch write: Putting and deleting multiple items

*Batch write* refers to putting and deleting multiple items in a batch. The `BatchWriteItem` method enables you to put and delete multiple items from one or more tables in a single call. The following are the steps to retrieve multiple items using the low-level .NET SDK API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Describe all the put and delete operations by creating an instance of the `BatchWriteItemRequest` class.
3. Run the `BatchWriteItem` method by providing the `BatchWriteItemRequest` object that you created in the preceding step.
4. Process the response. You should check if there were any unprocessed request items returned in the response. This could happen if you reach the provisioned throughput quota or some other transient error. Also, DynamoDB limits the request size and the number of operations you can specify in a request. If you exceed these limits, DynamoDB rejects the request. For more information, see [BatchWriteItem](#).

The following C# code example demonstrates the preceding steps. The example creates a `BatchWriteItemRequest` to perform the following write operations:

- Put an item in `Forum` table.
- Put and delete an item from `Thread` table.

The code runs `BatchWriteItem` to perform a batch operation.

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();

string table1Name = "Forum";
string table2Name = "Thread";
```

```

var request = new BatchWriteItemRequest
{
    RequestItems = new Dictionary<string, List<WriteRequest>>
    {
        {
            table1Name, new List<WriteRequest>
            {
                new WriteRequest
                {
                    PutRequest = new PutRequest
                    {
                        Item = new Dictionary<string,AttributeValue>
                        {
                            { "Name", new AttributeValue { S = "Amazon S3 forum" } },
                            { "Threads", new AttributeValue { N = "0" } }
                        }
                    }
                }
            }
        },
        {
            table2Name, new List<WriteRequest>
            {
                new WriteRequest
                {
                    PutRequest = new PutRequest
                    {
                        Item = new Dictionary<string,AttributeValue>
                        {
                            { "ForumName", new AttributeValue { S = "Amazon S3 forum" } },
                            { "Subject", new AttributeValue { S = "My sample question" } },
                            { "Message", new AttributeValue { S = "Message Text." } },
                            { "KeywordTags", new AttributeValue { SS = new List<string> { "Amazon S3", "Bucket" } } }
                        }
                    }
                },
                new WriteRequest
                {
                    DeleteRequest = new DeleteRequest
                    {
                        Key = new Dictionary<string,AttributeValue>()
                        {
                            { "ForumName", new AttributeValue { S = "Some forum name" } },
                            { "Subject", new AttributeValue { S = "Some subject" } }
                        }
                    }
                }
            }
        }
    };
    response = client.BatchWriteItem(request);
}

```

For a working example, see [Example: Batch operations using the AWS SDK for .NET low-level API \(p. 418\)](#).

### Batch get: Getting multiple items

The `BatchGetItem` method enables you to retrieve multiple items from one or more tables.

#### Note

To retrieve a single item, you can use the `GetItem` method.

The following are the steps to retrieve multiple items using the low-level AWS SDK for .NET API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Provide the required parameters by creating an instance of the `BatchGetItemRequest` class.  
To retrieve multiple items, the table name and a list of primary key values are required.
3. Run the `BatchGetItem` method by providing the `BatchGetItemRequest` object that you created in the preceding step.
4. Process the response. You should check if there were any unprocessed keys, which could happen if you reach the provisioned throughput quota or some other transient error.

The following C# code example demonstrates the preceding steps. The example retrieves items from two tables, `Forum` and `Thread`. The request specifies two items in the `Forum` and three items in the `Thread` table. The response includes items from both of the tables. The code shows how you can process the response.

```

AmazonDynamoDBClient client = new AmazonDynamoDBClient();

string table1Name = "Forum";
string table2Name = "Thread";

var request = new BatchGetItemRequest
{
    RequestItems = new Dictionary<string, KeysAndAttributes>()
    {
        { table1Name,
            new KeysAndAttributes
            {
                Keys = new List<Dictionary<string, AttributeValue>>()
                {
                    new Dictionary<string, AttributeValue>()
                    {
                        { "Name", new AttributeValue { S = "DynamoDB" } },
                        new Dictionary<string, AttributeValue>()
                        {
                            { "Name", new AttributeValue { S = "Amazon S3" } }
                        }
                    }
                },
                {
                    table2Name,
                    new KeysAndAttributes
                    {
                        Keys = new List<Dictionary<string, AttributeValue>>()
                        {
                            new Dictionary<string, AttributeValue>()
                            {
                                { "ForumName", new AttributeValue { S = "DynamoDB" } },
                                { "Subject", new AttributeValue { S = "DynamoDB Thread 1" } }
                            },
                            new Dictionary<string, AttributeValue>()
                            {
                                { "ForumName", new AttributeValue { S = "DynamoDB" } },
                                { "Subject", new AttributeValue { S = "DynamoDB Thread 2" } }
                            },
                            new Dictionary<string, AttributeValue>()
                            {
                                { "ForumName", new AttributeValue { S = "Amazon S3" } },
                                { "Subject", new AttributeValue { S = "Amazon S3 Thread 1" } }
                            }
                        }
                    }
                }
            }
        }
    }
}

```

```

        }
    }

};

var response = client.BatchGetItem(request);

// Check the response.
var result = response.BatchGetItemResult;
var responses = result.Responses; // The attribute list in the response.

var table1Results = responses[table1Name];
Console.WriteLine("Items in table {0}" + table1Name);
foreach (var item1 in table1Results.Items)
{
    PrintItem(item1);
}

var table2Results = responses[table2Name];
Console.WriteLine("Items in table {1}" + table2Name);
foreach (var item2 in table2Results.Items)
{
    PrintItem(item2);
}
// Any unprocessed keys? could happen if you exceed ProvisionedThroughput or some other
// error.
Dictionary<string, KeysAndAttributes> unprocessedKeys = result.UnprocessedKeys;
foreach (KeyValuePair<string, KeysAndAttributes> pair in unprocessedKeys)
{
    Console.WriteLine(pair.Key, pair.Value);
}

```

## Specifying optional parameters

You can also provide optional parameters using the `BatchGetItemRequest` object as shown in the following C# code example. The example retrieves two items from the `Forum` table. It specifies the following optional parameter:

- `ProjectionExpression` parameter to specify the attributes to retrieve.

## Example

```

AmazonDynamoDBClient client = new AmazonDynamoDBClient();

string table1Name = "Forum";

var request = new BatchGetItemRequest
{
    RequestItems = new Dictionary<string, KeysAndAttributes>()
    {
        { table1Name,
            new KeysAndAttributes
            {
                Keys = new List<Dictionary<string, AttributeValue>>()
                {
                    new Dictionary<string, AttributeValue>()
                    {
                        { "Name", new AttributeValue { S = "DynamoDB" } }
                    },
                    new Dictionary<string, AttributeValue>()
                    {
                        { "Name", new AttributeValue { S = "Amazon S3" } }
                    }
                }
            }
        }
    }
}

```

```
        }
    },
    // Optional - name of an attribute to retrieve.
    ProjectionExpression = "Title"
}
};

var response = client.BatchGetItem(request);
```

For more information, see [BatchGetItem](#).

#### Example: CRUD operations using the AWS SDK for .NET low-level API

The following C# code example illustrates CRUD operations on an Amazon DynamoDB item. The example adds an item to the `ProductCatalog` table, retrieves it, performs various updates, and finally deletes the item. If you followed the steps in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#), you already have the `ProductCatalog` table created. You can also create these sample tables programmatically. For more information, see [Creating example tables and uploading data using the AWS SDK for .NET \(p. 1272\)](#).

For step-by-step instructions for testing the following sample, see [.NET code examples \(p. 276\)](#).

#### Example

```
/** 
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
*/
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;
using Amazon.SecurityToken;

namespace com.amazonaws.codesamples
{
    class LowLevelItemCRUDExample
    {
        private static string tableName = "ProductCatalog";
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
        {
            try
            {
                CreateItem();
                RetrieveItem();

                // Perform various updates.
                UpdateMultipleAttributes();
            }
        }
    }
}
```

```

        UpdateExistingAttributeConditionally();

        // Delete item.
        DeleteItem();
        Console.WriteLine("To continue, press Enter");
        Console.ReadLine();
    }
    catch (Exception e)
    {
        Console.WriteLine(e.Message);
        Console.WriteLine("To continue, press Enter");
        Console.ReadLine();
    }
}

private static void CreateItem()
{
    var request = new PutItemRequest
    {
        TableName = tableName,
        Item = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue {
            N = "1000"
        }},
        { "Title", new AttributeValue {
            S = "Book 201 Title"
        }},
        { "ISBN", new AttributeValue {
            S = "11-11-11-11"
        }},
        { "Authors", new AttributeValue {
            SS = new List<string>{"Author1", "Author2" }
        }},
        { "Price", new AttributeValue {
            N = "20.00"
        }},
        { "Dimensions", new AttributeValue {
            S = "8.5x11.0x.75"
        }},
        { "InPublication", new AttributeValue {
            BOOL = false
        } }
    };
    client.PutItem(request);
}

private static void RetrieveItem()
{
    var request = new GetItemRequest
    {
        TableName = tableName,
        Key = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue {
            N = "1000"
        } }
    },
    ProjectionExpression = "Id, ISBN, Title, Authors",
    ConsistentRead = true
};
    var response = client.GetItem(request);

    // Check the response.
    var attributeList = response.Item; // attribute list in the response.
}

```

```

        Console.WriteLine("\nPrinting item after retrieving it .....");
        PrintItem(attributeList);
    }

    private static void UpdateMultipleAttributes()
    {
        var request = new UpdateItemRequest
        {
            Key = new Dictionary<string, AttributeValue>()
        {
            { "Id", new AttributeValue {
                N = "1000"
            } }
        },
        // Perform the following updates:
        // 1) Add two new authors to the list
        // 1) Set a new attribute
        // 2) Remove the ISBN attribute
        ExpressionAttributeNames = new Dictionary<string, string>()
        {
            {"#A", "Authors"},
            {"#NA", "NewAttribute"},
            {"#I", "ISBN"}
        },
        ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
        {
            {"":auth",new AttributeValue {
                SS = {"Author YY", "Author ZZ"}
            }},
            {"":new",new AttributeValue {
                S = "New Value"
            }}
        },
        UpdateExpression = "ADD #A :auth SET #NA = :new REMOVE #I",
        TableName = tableName,
        ReturnValues = "ALL_NEW" // Give me all attributes of the updated item.
    };
    var response = client.UpdateItem(request);

    // Check the response.
    var attributeList = response.Attributes; // attribute list in the response.
                                                // print attributeList.
    Console.WriteLine("\nPrinting item after multiple attribute
update .....");
    PrintItem(attributeList);
}

private static void UpdateExistingAttributeConditionally()
{
    var request = new UpdateItemRequest
    {
        Key = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue {
            N = "1000"
        } }
    },
    ExpressionAttributeNames = new Dictionary<string, string>()
    {
        {"#P", "Price"}
    },
    ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
    {
        {"":newprice",new AttributeValue {
            S = "New Price"
        } }
    }
}

```

```

        N = "22.00"
    },
    {">:currprice",new AttributeValue {
        N = "20.00"
    }}
},
// This updates price only if current price is 20.00.
UpdateExpression = "SET #P = :newprice",
ConditionExpression = "#P = :currprice",

TableName = tableName,
ReturnValues = "ALL_NEW" // Give me all attributes of the updated item.
};

var response = client.UpdateItem(request);

// Check the response.
var attributeList = response.Attributes; // attribute list in the response.
Console.WriteLine("\nPrinting item after updating price value
conditionally .....");
PrintItem(attributeList);
}

private static void DeleteItem()
{
    var request = new DeleteItemRequest
    {
        TableName = tableName,
        Key = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue {
            N = "1000"
        } }
    },

    // Return the entire item as it appeared before the update.
    ReturnValues = "ALL_OLD",
    ExpressionAttributeNames = new Dictionary<string, string>()
    {
        {"#IP", "InPublication"}
    },
    ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
    {
        {">:inpub",new AttributeValue {
            BOOL = false
        }}
    },
    ConditionExpression = "#IP = :inpub"
};

var response = client.DeleteItem(request);

// Check the response.
var attributeList = response.Attributes; // Attribute list in the response.
// Print item.
Console.WriteLine("\nPrinting item that was just deleted .....");
PrintItem(attributeList);
}

private static void PrintItem(Dictionary<string, AttributeValue> attributeList)
{
    foreach (KeyValuePair<string, AttributeValue> kvp in attributeList)
    {
        string attributeName = kvp.Key;
        AttributeValue value = kvp.Value;

        Console.WriteLine(

```

```

        attributeName + " " +
        (value.S == null ? "" : "S=[ " + value.S + "]") +
        (value.N == null ? "" : "N=[ " + value.N + "]") +
        (value.SS == null ? "" : "SS=[ " + string.Join(", ", value.SS.ToArray()) +
        " ]") +
        (value.NS == null ? "" : "NS=[ " + string.Join(", ", value.NS.ToArray()) +
        " ]")
    );
}
Console.WriteLine("*****");
}
}

```

Example: Batch operations using the AWS SDK for .NET low-level API

## Topics

- Example: Batch write operation using the AWS SDK for .NET low-level API (p. 418)
  - Example: Batch get operation using the AWS SDK for .NET low-level API (p. 421)

This section provides examples of batch operations, *batch write* and *batch get*, that Amazon DynamoDB supports.

## Example: Batch write operation using the AWS SDK for .NET low-level API

The following C# code example uses the `BatchWriteItem` method to perform the following put and delete operations:

- Put one item in the `Forum` table.
  - Put one item and delete one item from the `Thread` table.

You can specify any number of put and delete requests against one or more tables when creating your batch write request. However, `DynamoDB BatchWriteItem` limits the size of a batch write request and the number of put and delete operations in a single batch write operation. For more information, see [BatchWriteItem](#). If your request exceeds these limits, your request is rejected. If your table does not have sufficient provisioned throughput to serve this request, the unprocessed request items are returned in the response.

The following example checks the response to see if it has any unprocessed request items. If it does, it loops back and resends the `BatchWriteItem` request with unprocessed items in the request. If you followed the steps in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#), you already have the `Forum` and `Thread` tables created. You can also create these sample tables and upload sample data programmatically. For more information, see [Creating example tables and uploading data using the AWS SDK for .NET \(p. 1272\)](#).

For step-by-step instructions for testing the following sample, see [.NET code examples](#) (p. 276).

## Example

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 */
```

```

* http://aws.amazon.com/apache2.0/
*
* This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
* CONDITIONS OF ANY KIND, either express or implied. See the License for the
* specific language governing permissions and limitations under the License.
*/
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
    class LowLevelBatchWrite
    {
        private static string tableName = "Forum";
        private static string table2Name = "Thread";
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
        {
            try
            {
                TestBatchWrite();
            }
            catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
            catch (Exception e) { Console.WriteLine(e.Message); }

            Console.WriteLine("To continue, press Enter");
            Console.ReadLine();
        }

        private static void TestBatchWrite()
        {
            var request = new BatchWriteItemRequest
            {
                ReturnConsumedCapacity = "TOTAL",
                RequestItems = new Dictionary<string, List<WriteRequest>>
            };
            {
                tableName, new List<WriteRequest>
                {
                    new WriteRequest
                    {
                        PutRequest = new PutRequest
                        {
                            Item = new Dictionary<string, AttributeValue>
                            {
                                { "Name", new AttributeValue { S = "S3 forum" } },
                                { "Threads", new AttributeValue { N = "0" } }
                            }
                        }
                    }
                }
            },
            {
                table2Name, new List<WriteRequest>
                {
                    new WriteRequest
                    {
                        PutRequest = new PutRequest

```

```

        {
            Item = new Dictionary<string, AttributeValue>
            {
                { "ForumName", new AttributeValue {
                    S = "S3 forum"
                } },
                { "Subject", new AttributeValue {
                    S = "My sample question"
                } },
                { "Message", new AttributeValue {
                    S = "Message Text."
                } },
                { "KeywordTags", new AttributeValue {
                    SS = new List<string> { "S3", "Bucket" }
                } }
            }
        }
    },
    new WriteRequest
    {
        // For the operation to delete an item, if you provide a
        // primary key value
        // that does not exist in the table, there is no error, it is
        just a no-op.
        DeleteRequest = new DeleteRequest
        {
            Key = new Dictionary<string, AttributeValue>()
            {
                { "ForumName", new AttributeValue {
                    S = "Some partition key value"
                } },
                { "Subject", new AttributeValue {
                    S = "Some sort key value"
                } }
            }
        }
    }
};

CallBatchWriteTillCompletion(request);
}

private static void CallBatchWriteTillCompletion(BatchWriteItemRequest request)
{
    BatchWriteItemResponse response;

    int callCount = 0;
    do
    {
        Console.WriteLine("Making request");
        response = client.BatchWriteItem(request);
        callCount++;

        // Check the response.

        var tableConsumedCapacities = response.ConsumedCapacity;
        var unprocessed = response.UnprocessedItems;

        Console.WriteLine("Per-table consumed capacity");
        foreach (var tableConsumedCapacity in tableConsumedCapacities)
        {
            Console.WriteLine("{0} - {1}", tableConsumedCapacity.TableName,
tableConsumedCapacity.CapacityUnits);
    }
}

```

```
        }

        Console.WriteLine("Unprocessed");
        foreach (var unp in unprocessed)
        {
            Console.WriteLine("{0} - {1}", unp.Key, unp.Value.Count);
        }
        Console.WriteLine();

        // For the next iteration, the request will have unprocessed items.
        request.RequestItems = unprocessed;
    } while (response.UnprocessedItems.Count > 0);

    Console.WriteLine("Total # of batch write API calls made: {0}", callCount);
}

}
```

Example: Batch get operation using the AWS SDK for .NET low-level API

The following C# code example uses the `BatchGetItem` method to retrieve multiple items from the `Forum` and the `Thread` tables in Amazon DynamoDB. The `BatchGetItemRequest` specifies the table names and a list of primary keys for each table. The example processes the response by printing the items retrieved.

If you followed the steps in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#), you already have these tables created with sample data. You can also create these sample tables and upload sample data programmatically. For more information, see [Creating example tables and uploading data using the AWS SDK for .NET \(p. 1272\)](#).

For step-by-step instructions for testing the following sample, see [.NET code examples \(p. 276\)](#).

## Example

```
/***
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
    class LowLevelBatchGet
    {
        private static string tableName = "Forum";
        private static string table2Name = "Thread";
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
```

```

    {
        try
        {
            RetrieveMultipleItemsBatchGet();

            Console.WriteLine("To continue, press Enter");
            Console.ReadLine();
        }
        catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
        catch (Exception e) { Console.WriteLine(e.Message); }
    }

    private static void RetrieveMultipleItemsBatchGet()
    {
        var request = new BatchGetItemRequest
        {
            RequestItems = new Dictionary<string, KeysAndAttributes>()
        };
        {
            table1Name,
            new KeysAndAttributes
            {
                Keys = new List<Dictionary<string, AttributeValue>>()
                {
                    new Dictionary<string, AttributeValue>()
                    {
                        { "Name", new AttributeValue {
                            S = "Amazon DynamoDB"
                        } },
                        new Dictionary<string, AttributeValue>()
                        {
                            { "Name", new AttributeValue {
                                S = "Amazon S3"
                            } }
                        }
                    }
                },
            },
            table2Name,
            new KeysAndAttributes
            {
                Keys = new List<Dictionary<string, AttributeValue>>()
                {
                    new Dictionary<string, AttributeValue>()
                    {
                        { "ForumName", new AttributeValue {
                            S = "Amazon DynamoDB"
                        } },
                        { "Subject", new AttributeValue {
                            S = "DynamoDB Thread 1"
                        } }
                    },
                    new Dictionary<string, AttributeValue>()
                    {
                        { "ForumName", new AttributeValue {
                            S = "Amazon DynamoDB"
                        } },
                        { "Subject", new AttributeValue {
                            S = "DynamoDB Thread 2"
                        } }
                    },
                    new Dictionary<string, AttributeValue>()
                    {
                        { "ForumName", new AttributeValue {
                            S = "Amazon S3"
                        } },
                    }
                }
            }
        };
    }
}

```

```

                { "Subject", new AttributeValue {
                    S = "S3 Thread 1"
                } }
            }
        }
    }
};

BatchGetItemResponse response;
do
{
    Console.WriteLine("Making request");
    response = client.BatchGetItem(request);

    // Check the response.
    var responses = response.Responses; // Attribute list in the response.

    foreach (var tableResponse in responses)
    {
        var tableResults = tableResponse.Value;
        Console.WriteLine("Items retrieved from table {0}", tableResponse.Key);
        foreach (var item1 in tableResults)
        {
            PrintItem(item1);
        }
    }

    // Any unprocessed keys? Could happen if you exceed ProvisionedThroughput
    or some other error.
    Dictionary<string, KeysAndAttributes> unprocessedKeys =
    response.UnprocessedKeys;
    foreach (var unprocessedTableKeys in unprocessedKeys)
    {
        // Print table name.
        Console.WriteLine(unprocessedTableKeys.Key);
        // Print unprocessed primary keys.
        foreach (var key in unprocessedTableKeys.Value.Keys)
        {
            PrintItem(key);
        }
    }

    request.RequestItems = unprocessedKeys;
} while (response.UnprocessedKeys.Count > 0);
}

private static void PrintItem(Dictionary<string, AttributeValue> attributeList)
{
    foreach (KeyValuePair<string, AttributeValue> kvp in attributeList)
    {
        string attributeName = kvp.Key;
        AttributeValue value = kvp.Value;

        Console.WriteLine(
            attributeName + " " +
            (value.S == null ? "" : "S=[ " + value.S + " ]") +
            (value.N == null ? "" : "N=[ " + value.N + " ]") +
            (value.SS == null ? "" : "SS=[ " + string.Join(",", value.SS.ToArray()) +
            " ]") +
            (value.NS == null ? "" : "NS=[ " + string.Join(",", value.NS.ToArray()) +
            " ]"));
    }
    Console.WriteLine("*****");
}

```

```
        }
    }
```

### Example: Handling binary type attributes using the AWS SDK for .NET low-level API

The following C# code example illustrates the handling of binary type attributes. The example adds an item to the Reply table. The item includes a binary type attribute (`ExtendedMessage`) that stores compressed data. The example then retrieves the item and prints all the attribute values. For illustration, the example uses the `GZipStream` class to compress a sample stream and assigns it to the `ExtendedMessage` attribute, and decompresses it when printing the attribute value.

If you followed the steps in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#), you already have the Reply table created. You can also create these sample tables programmatically. For more information, see [Creating example tables and uploading data using the AWS SDK for .NET \(p. 1272\)](#).

For step-by-step instructions for testing the following example, see [.NET code examples \(p. 276\)](#).

#### Example

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using System.IO;
using System.IO.Compression;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
    class LowLevelItemBinaryExample
    {
        private static string tableName = "Reply";
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
        {
            // Reply table primary key.
            string replyIdPartitionKey = "Amazon DynamoDB#DynamoDB Thread 1";
            string replyDateTimeSortKey = Convert.ToString(DateTime.UtcNow);

            try
            {
                CreateItem(replyIdPartitionKey, replyDateTimeSortKey);
                RetrieveItem(replyIdPartitionKey, replyDateTimeSortKey);
                // Delete item.
                DeleteItem(replyIdPartitionKey, replyDateTimeSortKey);
                Console.WriteLine("To continue, press Enter");
            }
        }

        private void CreateItem(string partitionKey, string sortKey)
        {
            var item = new Dictionary<string, AttributeValue>()
            {
                { "partitionKey", new AttributeValue { S = partitionKey } },
                { "sortKey", new AttributeValue { S = sortKey } },
                { "attribute1", new AttributeValue { B = Compress("Hello, world!") } },
                { "attribute2", new AttributeValue { N = "12345" } },
                { "attribute3", new AttributeValue { S = "A string value." } },
                { "attribute4", new AttributeValue { N = "12345" } },
                { "attribute5", new AttributeValue { B = Compress("A compressed binary value.") } }
            };
            var request = new PutItemRequest()
            {
                TableName = tableName,
                Item = item
            };
            client.PutItem(request);
        }

        private void RetrieveItem(string partitionKey, string sortKey)
        {
            var request = new GetItemRequest()
            {
                TableName = tableName,
                Key = new Dictionary<string, AttributeValue>()
                {
                    { "partitionKey", new AttributeValue { S = partitionKey } },
                    { "sortKey", new AttributeValue { S = sortKey } }
                }
            };
            var response = client.GetItem(request);
            var item = response.Item;
            if (item != null)
            {
                var attribute1 = item["attribute1"];
                var attribute2 = item["attribute2"];
                var attribute3 = item["attribute3"];
                var attribute4 = item["attribute4"];
                var attribute5 = item["attribute5"];
                Console.WriteLine("attribute1: " + attribute1.B);
                Console.WriteLine("attribute2: " + attribute2.N);
                Console.WriteLine("attribute3: " + attribute3.S);
                Console.WriteLine("attribute4: " + attribute4.N);
                Console.WriteLine("attribute5: " + attribute5.B);
            }
        }

        private void DeleteItem(string partitionKey, string sortKey)
        {
            var request = new DeleteItemRequest()
            {
                TableName = tableName,
                Key = new Dictionary<string, AttributeValue>()
                {
                    { "partitionKey", new AttributeValue { S = partitionKey } },
                    { "sortKey", new AttributeValue { S = sortKey } }
                }
            };
            client.DeleteItem(request);
        }

        private byte[] Compress(string value)
        {
            using (var ms = new MemoryStream())
            {
                using (var gs = new GZipStream(ms, CompressionLevel.Fastest))
                {
                    using (var sw = new StreamWriter(gs))
                    {
                        sw.Write(value);
                    }
                }
                return ms.ToArray();
            }
        }
    }
}
```

```

        Console.ReadLine();
    }
    catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }
    catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
    catch (Exception e) { Console.WriteLine(e.Message); }
}

private static void CreateItem(string partitionKey, string sortKey)
{
    MemoryStream compressedMessage = ToGzipMemoryStream("Some long extended message
to compress.");
    var request = new PutItemRequest
    {
        TableName = tableName,
        Item = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue {
            S = partitionKey
        }},
        { "ReplyDateTime", new AttributeValue {
            S = sortKey
        }},
        { "Subject", new AttributeValue {
            S = "Binary type "
        }},
        { "Message", new AttributeValue {
            S = "Some message about the binary type"
        }},
        { "ExtendedMessage", new AttributeValue {
            B = compressedMessage
        }}
    }
    };
    client.PutItem(request);
}

private static void RetrieveItem(string partitionKey, string sortKey)
{
    var request = new GetItemRequest
    {
        TableName = tableName,
        Key = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue {
            S = partitionKey
        }},
        { "ReplyDateTime", new AttributeValue {
            S = sortKey
        }}
    },
    ConsistentRead = true
};
    var response = client.GetItem(request);

    // Check the response.
    var attributeList = response.Item; // attribute list in the response.
    Console.WriteLine("\nPrinting item after retrieving it .....");

    PrintItem(attributeList);
}

private static void DeleteItem(string partitionKey, string sortKey)
{
    var request = new DeleteItemRequest
    {
        TableName = tableName,

```

```

        Key = new Dictionary<string, AttributeValue>()
    {
        { "Id", new AttributeValue {
            S = partitionKey
        } },
        { "ReplyDateTime", new AttributeValue {
            S = sortKey
        } }
    };
    var response = client.DeleteItem(request);
}

private static void PrintItem(Dictionary<string, AttributeValue> attributeList)
{
    foreach (KeyValuePair<string, AttributeValue> kvp in attributeList)
    {
        string attributeName = kvp.Key;
        AttributeValue value = kvp.Value;

        Console.WriteLine(
            attributeName + " " +
            (value.S == null ? "" : "S=[" + value.S + "])" +
            (value.N == null ? "" : "N=[" + value.N + "])" +
            (value.SS == null ? "" : "SS=[" + string.Join(",", value.SS.ToArray()) +
            "])" +
            (value.NS == null ? "" : "NS=[" + string.Join(",", value.NS.ToArray()) +
            "])" +
            (value.B == null ? "" : "B=[" + FromGzipMemoryStream(value.B) + "])");
        );
        Console.WriteLine("*****");
    }
}

private static MemoryStream ToGzipMemoryStream(string value)
{
    MemoryStream output = new MemoryStream();
    using (GZipStream zipStream = new GZipStream(output, CompressionMode.Compress,
true))
        using (StreamWriter writer = new StreamWriter(zipStream))
        {
            writer.Write(value);
        }
    return output;
}

private static string FromGzipMemoryStream(MemoryStream stream)
{
    using (GZipStream zipStream = new GZipStream(stream,
CompressionMode.Decompress))
        using (StreamReader reader = new StreamReader(zipStream))
        {
            return reader.ReadToEnd();
        }
}
}
}

```

## Item collections - how to model one-to-many relationships in DynamoDB

In DynamoDB, an *item collection* is a group of items that share the same partition key value, which means the items are related. Item collections are the primary mechanism to model one-to-many

relationships in DynamoDB. Item collections can only exist on tables or indexes configured to use a [composite primary key \(p. 6\)](#).

### Note

Item collections can exist either in a base table or a secondary index. For more information specifically about how item collections interact with indexes, see [Item collections in Local Secondary Indexes \(p. 548\)](#).

Consider the following table showing three different users and their in-game inventories:

Primary key		Attributes		
Partition key: PK	Sort key: SK			
account1234	inventory::armor	data		
	inventory::weapons	data		
	login-data	pw	state	last-login
		d1e8a70b5ccab1dc2f56bbf7e99f064a660c08e361a35751b9c483c88943d02	Active	1649276737
account1387	info	data		
	inventory::armor	data		
	login-data	pw	state	last-login
		k2g8jk0m5ppab1dc2f56bbf7e99f064a660c08e361a35751b9c464r23943d02	Banned	1649456737
account1138	info	data		
	inventory::armor	data		
	login-data	pw	state	last-login
		88a41a9a62b11ccc8c120861928765a3ea41deb9afe261d90f619473b89a2d2	Active	1427551696

For some items in each collection, the sort key is a concatenation made up of information used to group data, such as `inventory::armor`, `inventory::weapon` or `info`. Each item collection can have a different combination of these attributes as the sort key. User account1234 has an `inventory::weapons` item, while user account1387 does not (because they have not found any yet). User account1138 only uses two items for their sort key (since they have no inventory yet) while the other users use three.

DynamoDB lets you selectively retrieve items from these item collections to do the following:

- Retrieve all items from a particular user
- Retrieve only one item from a particular user
- Retrieve all the items of a specific type belonging to a particular user

## Speed up queries by organizing your data with item collections

In this example, each of the items in these three item collections represents a player and the data model we have chosen, based off the game's and player's access patterns. What data does the game need? When does it need it? How frequently does it need it? What's the cost of doing it this way? These data modeling decisions were made based off the answers to these questions.

In this game, there is a different page presented to the player for their inventory for weapons and another page for armor. When the player opens their inventory, weapons are shown first because we want that page to load extremely fast, while subsequent inventory pages can load after that. Since each of these item types can be quite large as the player acquires more in-game items, we decided that each inventory page would be its own item in the player's item collection in the database.

The following section talks more about how you can interact with item collections through the `Query` operation.

### Topics

- [Query operations in DynamoDB \(p. 428\)](#)

## Query operations in DynamoDB

The `Query` operation in Amazon DynamoDB finds items based on primary key values.

You must provide the name of the partition key attribute and a single value for that attribute. `Query` returns all items with that partition key value. Optionally, you can provide a sort key attribute and use a comparison operator to refine the search results.

For more information on how to use `Query`, such as the request syntax, response parameters, and additional examples, see [Query in the Amazon DynamoDB API Reference](#).

### Topics

- [Key condition expressions for query \(p. 428\)](#)
- [Filter expressions for query \(p. 430\)](#)
- [Limiting the number of items in the result set \(p. 431\)](#)
- [Paginating table query results \(p. 431\)](#)
- [Counting the items in the results \(p. 432\)](#)
- [Capacity units consumed by query \(p. 432\)](#)
- [Read consistency for query \(p. 433\)](#)
- [Querying tables and indexes: Java \(p. 433\)](#)
- [Querying tables and indexes: .NET \(p. 439\)](#)

### Key condition expressions for query

To specify the search criteria, you use a *key condition expression*—a string that determines the items to be read from the table or index.

You must specify the partition key name and value as an equality condition. You cannot use a non-key attribute in a Key Condition Expression.

You can optionally provide a second condition for the sort key (if present). The sort key condition must use one of the following comparison operators:

- `a = b` — true if the attribute `a` is equal to the value `b`
- `a < b` — true if `a` is less than `b`
- `a <= b` — true if `a` is less than or equal to `b`
- `a > b` — true if `a` is greater than `b`
- `a >= b` — true if `a` is greater than or equal to `b`
- `a BETWEEN b AND c` — true if `a` is greater than or equal to `b`, and less than or equal to `c`.

The following function is also supported:

- `begins_with (a, substr)`— true if the value of attribute `a` begins with a particular substring.

The following AWS Command Line Interface (AWS CLI) examples demonstrate the use of key condition expressions. These expressions use placeholders (such as `:name` and `:sub`) instead of actual values. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#) and [Expression attribute values \(p. 360\)](#).

## Example

Query the `Thread` table for a particular `ForumName` (partition key). All of the items with that `ForumName` value are read by the query because the sort key (`Subject`) is not included in `KeyConditionExpression`.

```
aws dynamodb query \  
    --table-name Thread \  
    --key-condition-expression "ForumName = :name" \  
    --expression-attribute-values '{":name": {"S": "Amazon DynamoDB"}}'
```

## Example

Query the `Thread` table for a particular `ForumName` (partition key), but this time return only the items with a given `Subject` (sort key).

```
aws dynamodb query \  
    --table-name Thread \  
    --key-condition-expression "ForumName = :name and Subject = :sub" \  
    --expression-attribute-values file://values.json
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{  
    ":name": {"S": "Amazon DynamoDB"},  
    ":sub": {"S": "DynamoDB Thread 1"}  
}
```

## Example

Query the `Reply` table for a particular `Id` (partition key), but return only those items whose `ReplyDateTime` (sort key) begins with certain characters.

```
aws dynamodb query \  
    --table-name Reply \  
    --key-condition-expression "Id = :id and begins_with(ReplyDateTime, :dt)" \  
    --expression-attribute-values file://values.json
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{  
    ":id": {"S": "Amazon DynamoDB#DynamoDB Thread 1"},  
    ":dt": {"S": "2015-09"}  
}
```

You can use any attribute name in a key condition expression, provided that the first character is a-z or A-Z and the rest of the characters (starting from the second character, if present) are a-z, A-Z, or 0-9. In addition, the attribute name must not be a DynamoDB reserved word. (For a complete list of these, see [Reserved words in DynamoDB \(p. 1310\)](#).) If an attribute name does not meet these requirements, you must define an expression attribute name as a placeholder. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#).

For items with a given partition key value, DynamoDB stores these items close together, in sorted order by sort key value. In a `Query` operation, DynamoDB retrieves the items in sorted order, and then processes the items using `KeyConditionExpression` and any `FilterExpression` that might be present. Only then are the `Query` results sent back to the client.

A `Query` operation always returns a result set. If no matching items are found, the result set is empty.

`Query` results are always sorted by the sort key value. If the data type of the sort key is `Number`, the results are returned in numeric order. Otherwise, the results are returned in order of UTF-8 bytes. By default, the sort order is ascending. To reverse the order, set the `ScanIndexForward` parameter to `false`.

A single `Query` operation can retrieve a maximum of 1 MB of data. This limit applies before any `FilterExpression` or `ProjectionExpression` is applied to the results. If `LastEvaluatedKey` is present in the response and is non-null, you must paginate the result set (see [Paginating table query results \(p. 431\)](#)).

### Filter expressions for query

If you need to further refine the `Query` results, you can optionally provide a filter expression. A *filter expression* determines which items within the `Query` results should be returned to you. All of the other results are discarded.

A filter expression is applied after a `Query` finishes, but before the results are returned. Therefore, a `Query` consumes the same amount of read capacity, regardless of whether a filter expression is present.

A `Query` operation can retrieve a maximum of 1 MB of data. This limit applies before the filter expression is evaluated.

A filter expression cannot contain partition key or sort key attributes. You need to specify those attributes in the key condition expression, not the filter expression.

The syntax for a filter expression is similar to that of a key condition expression. Filter expressions can use the same comparators, functions, and logical operators as a key condition expression. In addition, filter expressions can use the not-equals operator (`<>`), the OR operator, the `CONTAINS` operator, the `IN` operator, the `BEGINS_WITH` operator, the `BETWEEN` operator, the `EXISTS` operator, and the `SIZE` operator. For more information, see [Key condition expressions for query \(p. 428\)](#) and [Syntax for filter and condition expressions \(p. 366\)](#).

### Example

The following AWS CLI example queries the `Thread` table for a particular `ForumName` (partition key) and `Subject` (sort key). Of the items that are found, only the most popular discussion threads are returned—in other words, only those threads with more than a certain number of `Views`.

```
aws dynamodb query \
    --table-name Thread \
    --key-condition-expression "ForumName = :fn and Subject = :sub" \
    --filter-expression "#v >= :num" \
    --expression-attribute-names '{"#v": "Views"}' \
    --expression-attribute-values file:/values.json
```

The arguments for `--expression-attribute-values` are stored in the `values.json` file.

```
{
    ":fn": {"S": "Amazon DynamoDB"}, 
    ":sub": {"S": "DynamoDB Thread 1"}, 
    ":num": {"N": "3"}}
```

Note that `Views` is a reserved word in DynamoDB (see [Reserved words in DynamoDB \(p. 1310\)](#)), so this example uses `#v` as a placeholder. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#).

**Note**

A filter expression removes items from the `Query` result set. If possible, avoid using `Query` where you expect to retrieve a large number of items but also need to discard most of those items.

[Limiting the number of items in the result set](#)

The `Query` operation allows you to limit the number of items that it reads. To do this, set the `Limit` parameter to the maximum number of items that you want.

For example, suppose that you `Query` a table, with a `Limit` value of 6, and without a filter expression. The `Query` result contains the first six items from the table that match the key condition expression from the request.

Now suppose that you add a filter expression to the `Query`. In this case, DynamoDB reads up to six items, and then returns only those that match the filter expression. The final `Query` result contains six items or fewer, even if more items would have matched the filter expression if DynamoDB had kept reading more items.

[Paginating table query results](#)

DynamoDB *paginates* the results from `Query` operations. With pagination, the `Query` results are divided into "pages" of data that are 1 MB in size (or less). An application can process the first page of results, then the second page, and so on.

A single `Query` only returns a result set that fits within the 1 MB size limit. To determine whether there are more results, and to retrieve them one page at a time, applications should do the following:

1. Examine the low-level `Query` result:
  - If the result contains a `LastEvaluatedKey` element and it's non-null, proceed to step 2.
  - If there is *not* a `LastEvaluatedKey` in the result, there are no more items to be retrieved.
2. Construct a new `Query` request, with the same parameters as the previous one. However, this time, take the `LastEvaluatedKey` value from step 1 and use it as the `ExclusiveStartKey` parameter in the new `Query` request.
3. Run the new `Query` request.
4. Go to step 1.

In other words, the `LastEvaluatedKey` from a `Query` response should be used as the `ExclusiveStartKey` for the next `Query` request. If there is not a `LastEvaluatedKey` element in a `Query` response, then you have retrieved the final page of results. If `LastEvaluatedKey` is not empty, it does not necessarily mean that there is more data in the result set. The only way to know when you have reached the end of the result set is when `LastEvaluatedKey` is empty.

You can use the AWS CLI to view this behavior. The AWS CLI sends low-level `Query` requests to DynamoDB repeatedly, until `LastEvaluatedKey` is no longer present in the results. Consider the following AWS CLI example that retrieves movie titles from a particular year.

```
aws dynamodb query --table-name Movies \
--projection-expression "title" \
--key-condition-expression "#y = :yyyy" \
--expression-attribute-names '{"#y":"year"}' \
--expression-attribute-values '{":yyyy":{"N":"1993"}}' \
--page-size 5 \
--debug
```

Ordinarily, the AWS CLI handles pagination automatically. However, in this example, the AWS CLI `--page-size` parameter limits the number of items per page. The `--debug` parameter prints low-level information about requests and responses.

If you run the example, the first response from DynamoDB looks similar to the following.

```
2017-07-07 11:13:15,603 - MainThread - botocore.parsers - DEBUG - Response body:  
b'{"Count":5,"Items":[{"title":{"S":"A Bronx Tale"}},  
 {"title":{"S":"A Perfect World"}},{"title":{"S":"Addams Family Values"}},  
 {"title":{"S":"Alive"}},{"title":{"S":"Benny & Joon"}]},  
 "LastEvaluatedKey":{"year":{"N":"1993"},"title":{"S":"Benny & Joon"}},  
 "ScannedCount":5}'
```

The `LastEvaluatedKey` in the response indicates that not all of the items have been retrieved. The AWS CLI then issues another `Query` request to DynamoDB. This request and response pattern continues, until the final response.

```
2017-07-07 11:13:16,291 - MainThread - botocore.parsers - DEBUG - Response body:  
b'{"Count":1,"Items":[{"title":{"S":"What\\'s Eating Gilbert Grape"}]}],"ScannedCount":1}'
```

The absence of `LastEvaluatedKey` indicates that there are no more items to retrieve.

**Note**

The AWS SDKs handle the low-level DynamoDB responses (including the presence or absence of `LastEvaluatedKey`) and provide various abstractions for paginating `Query` results. For example, the SDK for Java document interface provides `java.util.Iterator` support so that you can walk through the results one at a time.

For code examples in various programming languages, see the [Amazon DynamoDB Getting Started Guide](#) and the AWS SDK documentation for your language.

You can also reduce page size by limiting the number of items in the result set, with the `Limit` parameter of the `Query` operation.

For more information about querying with DynamoDB, see [Query operations in DynamoDB \(p. 428\)](#).

### Counting the items in the results

In addition to the items that match your criteria, the `Query` response contains the following elements:

- `ScannedCount` — The number of items that matched the key condition expression *before* a filter expression (if present) was applied.
- `Count` — The number of items that remain *after* a filter expression (if present) was applied.

**Note**

If you don't use a filter expression, `ScannedCount` and `Count` have the same value.

If the size of the `Query` result set is larger than 1 MB, `ScannedCount` and `Count` represent only a partial count of the total items. You need to perform multiple `Query` operations to retrieve all the results (see [Paginating table query results \(p. 431\)](#)).

Each `Query` response contains the `ScannedCount` and `Count` for the items that were processed by that particular `Query` request. To obtain grand totals for all of the `Query` requests, you could keep a running tally of both `ScannedCount` and `Count`.

### Capacity units consumed by query

You can `Query` any table or secondary index, provided that it has a composite primary key (partition key and sort key). `Query` operations consume read capacity units, as follows.

If you <code>Query</code> a...	DynamoDB consumes read capacity units from...
Table	The table's provisioned read capacity.

If you query a...	DynamoDB consumes read capacity units from...
Global secondary index	The index's provisioned read capacity.
Local secondary index	The base table's provisioned read capacity.

By default, a `Query` operation does not return any data on how much read capacity it consumes. However, you can specify the `ReturnConsumedCapacity` parameter in a `Query` request to obtain this information. The following are the valid settings for `ReturnConsumedCapacity`:

- `NONE` — No consumed capacity data is returned. (This is the default.)
- `TOTAL` — The response includes the aggregate number of read capacity units consumed.
- `INDEXES` — The response shows the aggregate number of read capacity units consumed, together with the consumed capacity for each table and index that was accessed.

DynamoDB calculates the number of read capacity units consumed based on item size, not on the amount of data that is returned to an application. For this reason, the number of capacity units consumed is the same whether you request all of the attributes (the default behavior) or just some of them (using a projection expression). The number is also the same whether or not you use a filter expression.

### Read consistency for query

A `Query` operation performs eventually consistent reads, by default. This means that the `Query` results might not reflect changes due to recently completed `PutItem` or `UpdateItem` operations. For more information, see [Read consistency \(p. 17\)](#).

If you require strongly consistent reads, set the `ConsistentRead` parameter to `true` in the `Query` request.

### Querying tables and indexes: Java

The `Query` operation enables you to query a table or a secondary index in Amazon DynamoDB. You must provide a partition key value and an equality condition. If the table or index has a sort key, you can refine the results by providing a sort key value and a condition.

#### Note

The AWS SDK for Java also provides an object persistence model, enabling you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

The following are the steps to retrieve an item using the AWS SDK for Java Document API.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `Table` class to represent the table you want to work with.
3. Call the `query` method of the `Table` instance. You must specify the partition key value of the items that you want to retrieve, along with any optional query parameters.

The response includes an `ItemCollection` object that provides all items returned by the query.

The following Java code example demonstrates the preceding tasks. The example assumes that you have a `Reply` table that stores replies for forum threads. For more information, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

```
Reply ( Id, ReplyDateTime, ... )
```

Each forum thread has a unique ID and can have zero or more replies. Therefore, the `Id` attribute of the `Reply` table is composed of both the forum name and forum subject. `Id` (partition key) and `ReplyDateTime` (sort key) make up the composite primary key for the table.

The following query retrieves all replies for a specific thread subject. The query requires both the table name and the `Subject` value.

### Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard()
    .withRegion(Regions.US_WEST_2).build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("Reply");

QuerySpec spec = new QuerySpec()
    .withKeyConditionExpression("Id = :v_id")
    .WithValueMap(new ValueMap()
        .withString(":v_id", "Amazon DynamoDB#DynamoDB Thread 1"));

ItemCollection<QueryOutcome> items = table.query(spec);

Iterator<Item> iterator = items.iterator();
Item item = null;
while (iterator.hasNext()) {
    item = iterator.next();
    System.out.println(item.toJSONPretty());
}
```

### Specifying optional parameters

The `query` method supports several optional parameters. For example, you can optionally narrow the results from the preceding query to return replies in the past two weeks by specifying a condition. The condition is called a sort key condition, because DynamoDB evaluates the query condition that you specify against the sort key of the primary key. You can specify other optional parameters to retrieve only a specific list of attributes from items in the query result.

The following Java code example retrieves forum thread replies posted in the past 15 days. The example specifies optional parameters using the following:

- A `KeyConditionExpression` to retrieve the replies from a specific discussion forum (partition key) and, within that set of items, replies that were posted within the last 15 days (sort key).
- A `FilterExpression` to return only the replies from a specific user. The filter is applied after the query is processed, but before the results are returned to the user.
- A `ValueMap` to define the actual values for the `KeyConditionExpression` placeholders.
- A `ConsistentRead` setting of `true`, to request a strongly consistent read.

This example uses a `QuerySpec` object that gives access to all of the low-level `Query` input parameters.

### Example

```
Table table = dynamoDB.getTable("Reply");

long twoWeeksAgoMilli = (new Date()).getTime() - (15L*24L*60L*60L*1000L);
Date twoWeeksAgo = new Date();
twoWeeksAgo.setTime(twoWeeksAgoMilli);
SimpleDateFormat df = new SimpleDateFormat("yyyy-MM-dd'T'HH:mm:ss.SSS'Z'");
```

```

String twoWeeksAgoStr = df.format(twoWeeksAgo);

QuerySpec spec = new QuerySpec()
    .withKeyConditionExpression("Id = :v_id and ReplyDateTime > :v_reply_dt_tm")
    .withFilterExpression("PostedBy = :v_posted_by")
    .withValueMap(new ValueMap()
        .withString(":v_id", "Amazon DynamoDB#DynamoDB Thread 1")
        .withString(":v_reply_dt_tm", twoWeeksAgoStr)
        .withString(":v_posted_by", "User B"))
    .withConsistentRead(true);

ItemCollection<QueryOutcome> items = table.query(spec);

Iterator<Item> iterator = items.iterator();
while (iterator.hasNext()) {
    System.out.println(iterator.next().toJSONPretty());
}

```

You can also optionally limit the number of items per page by using the `withMaxPageSize` method. When you call the `query` method, you get an `ItemCollection` that contains the resulting items. You can then step through the results, processing one page at a time, until there are no more pages.

The following Java code example modifies the query specification shown previously. This time, the query spec uses the `withMaxPageSize` method. The `Page` class provides an iterator that allows the code to process the items on each page.

### Example

```

spec.withMaxPageSize(10);

ItemCollection<QueryOutcome> items = table.query(spec);

// Process each page of results
int pageNum = 0;
for (Page<Item, QueryOutcome> page : items.pages()) {

    System.out.println("\nPage: " + ++pageNum);

    // Process each item on the current page
    Iterator<Item> item = page.iterator();
    while (item.hasNext()) {
        System.out.println(item.next().toJSONPretty());
    }
}

```

### Example - query using Java

The following tables store information about a collection of forums. For more information, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

#### Note

The SDK for Java also provides an object persistence model, enabling you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

### Example

```

Forum ( Name, ... )
Thread ( ForumName, Subject, Message, LastPostedBy, LastPostDateTime, ... )

```

```
Reply ( Id, ReplyDateTime, Message, PostedBy, ...)
```

In this Java code example, you run variations of finding replies for a thread "DynamoDB Thread 1" in forum "DynamoDB".

- Find replies for a thread.
- Find replies for a thread, specifying a limit on the number of items per page of results. If the number of items in the result set exceeds the page size, you get only the first page of results. This coding pattern ensures that your code processes all the pages in the query result.
- Find replies in the last 15 days.
- Find replies in a specific date range.

The preceding two queries show how you can specify sort key conditions to narrow the query results and use other optional query parameters.

#### Note

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
  
package com.amazonaws.codesamples.document;  
  
import java.text.SimpleDateFormat;  
import java.util.Date;  
import java.util.Iterator;  
  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;  
import com.amazonaws.services.dynamodbv2.document.DynamoDB;  
import com.amazonaws.services.dynamodbv2.document.Item;  
import com.amazonaws.services.dynamodbv2.document.ItemCollection;  
import com.amazonaws.services.dynamodbv2.document.Page;  
import com.amazonaws.services.dynamodbv2.document.QueryOutcome;  
import com.amazonaws.services.dynamodbv2.document.Table;  
import com.amazonaws.services.dynamodbv2.document.spec.QuerySpec;  
import com.amazonaws.services.dynamodbv2.document.utils.ValueMap;  
  
public class DocumentAPIQuery {  
  
    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();  
    static DynamoDB dynamoDB = new DynamoDB(client);  
  
    static String tableName = "Reply";  
  
    public static void main(String[] args) throws Exception {
```

```

        String forumName = "Amazon DynamoDB";
        String threadSubject = "DynamoDB Thread 1";

        findRepliesForAThread(forumName, threadSubject);
        findRepliesForAThreadSpecifyOptionalLimit(forumName, threadSubject);
        findRepliesInLast15DaysWithConfig(forumName, threadSubject);
        findRepliesPostedWithinTimePeriod(forumName, threadSubject);
        findRepliesUsingAFilterExpression(forumName, threadSubject);
    }

    private static void findRepliesForAThread(String forumName, String threadSubject) {

        Table table = dynamoDB.getTable(tableName);

        String replyId = forumName + "#" + threadSubject;

        QuerySpec spec = new QuerySpec().withKeyConditionExpression("Id = :v_id")
            .WithValueMap(new ValueMap().withString(":v_id", replyId));

        ItemCollection<QueryOutcome> items = table.query(spec);

        System.out.println("\nfindRepliesForAThread results:");

        Iterator<Item> iterator = items.iterator();
        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }
    }

    private static void findRepliesForAThreadSpecifyOptionalLimit(String forumName, String
threadSubject) {

        Table table = dynamoDB.getTable(tableName);

        String replyId = forumName + "#" + threadSubject;

        QuerySpec spec = new QuerySpec().withKeyConditionExpression("Id = :v_id")
            .WithValueMap(new ValueMap().withString(":v_id", replyId)).withMaxPageSize(1);

        ItemCollection<QueryOutcome> items = table.query(spec);

        System.out.println("\nfindRepliesForAThreadSpecifyOptionalLimit results:");

        // Process each page of results
        int pageNum = 0;
        for (Page<Item, QueryOutcome> page : items.pages()) {

            System.out.println("\nPage: " + ++pageNum);

            // Process each item on the current page
            Iterator<Item> item = page.iterator();
            while (item.hasNext()) {
                System.out.println(item.next().toJSONPretty());
            }
        }
    }

    private static void findRepliesInLast15DaysWithConfig(String forumName, String
threadSubject) {

        Table table = dynamoDB.getTable(tableName);

        long twoWeeksAgoMilli = (new Date()).getTime() - (15L * 24L * 60L * 60L * 1000L);
        Date twoWeeksAgo = new Date();
    }
}

```

```

twoWeeksAgo.setTime(twoWeeksAgoMilli);
SimpleDateFormat df = new SimpleDateFormat("yyyy-MM-dd'T'HH:mm:ss.SSS'Z'");
String twoWeeksAgoStr = df.format(twoWeeksAgo);

String replyId = forumName + "#" + threadSubject;

QuerySpec spec = new QuerySpec().withProjectionExpression("Message, ReplyDateTime,
PostedBy")
    .withKeyConditionExpression("Id = :v_id and ReplyDateTime <= :v_reply_dt_tm")
    .withValueMap(new ValueMap().withString(":v_id",
replyId).withString(":v_reply_dt_tm", twoWeeksAgoStr));

ItemCollection<QueryOutcome> items = table.query(spec);

System.out.println("\nfindRepliesInLast15DaysWithConfig results:");
Iterator<Item> iterator = items.iterator();
while (iterator.hasNext()) {
    System.out.println(iterator.next().toJSONPretty());
}

}

private static void findRepliesPostedWithinTimePeriod(String forumName, String
threadSubject) {

    Table table = dynamoDB.getTable(tableName);

    long startDateMilli = (new Date()).getTime() - (15L * 24L * 60L * 60L * 1000L);
    long endDateMilli = (new Date()).getTime() - (5L * 24L * 60L * 60L * 1000L);
    java.text.SimpleDateFormat df = new java.text.SimpleDateFormat("yyyy-MM-
dd'T'HH:mm:ss.SSS'Z'");
    String startDate = df.format(startDateMilli);
    String endDate = df.format(endDateMilli);

    String replyId = forumName + "#" + threadSubject;

    QuerySpec spec = new QuerySpec().withProjectionExpression("Message, ReplyDateTime,
PostedBy")
        .withKeyConditionExpression("Id = :v_id and ReplyDateTime between :v_start_dt
and :v_end_dt")
        .withValueMap(new ValueMap().withString(":v_id",
replyId).withString(":v_start_dt", startDate)
            .withString(":v_end_dt", endDate));

    ItemCollection<QueryOutcome> items = table.query(spec);

    System.out.println("\nfindRepliesPostedWithinTimePeriod results:");
    Iterator<Item> iterator = items.iterator();
    while (iterator.hasNext()) {
        System.out.println(iterator.next().toJSONPretty());
    }
}

private static void findRepliesUsingAFilterExpression(String forumName, String
threadSubject) {

    Table table = dynamoDB.getTable(tableName);

    String replyId = forumName + "#" + threadSubject;

    QuerySpec spec = new QuerySpec().withProjectionExpression("Message, ReplyDateTime,
PostedBy")
        .withKeyConditionExpression("Id = :v_id").withFilterExpression("PostedBy
= :v_postedby")
        .withValueMap(new ValueMap().withString(":v_id",
replyId).withString(":v_postedby", "User B"));
}

```

```

        ItemCollection<QueryOutcome> items = table.query(spec);

        System.out.println("\nfindRepliesUsingAFilterExpression results:");
        Iterator<Item> iterator = items.iterator();
        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }
    }
}

```

## Querying tables and indexes: .NET

The `Query` operation enables you to query a table or a secondary index in Amazon DynamoDB. You must provide a partition key value and an equality condition. If the table or index has a sort key, you can refine the results by providing a sort key value and a condition.

The following are the steps to query a table using the low-level AWS SDK for .NET API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `QueryRequest` class and provide query operation parameters.
3. Run the `Query` method and provide the `QueryRequest` object that you created in the preceding step.

The response includes the `QueryResult` object that provides all items returned by the query.

The following C# code example demonstrates the preceding tasks. The code assumes that you have a `Reply` table that stores replies for forum threads. For more information, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

### Example

```
Reply Id, ReplyDateTime, ... )
```

Each forum thread has a unique ID and can have zero or more replies. Therefore, the primary key is composed of both the `Id` (partition key) and `ReplyDateTime` (sort key).

The following query retrieves all replies for a specific thread subject. The query requires both the table name and the `Subject` value.

### Example

```

AmazonDynamoDBClient client = new AmazonDynamoDBClient();

var request = new QueryRequest
{
    TableName = "Reply",
    KeyConditionExpression = "Id = :v_Id",
    ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
        {"":":v_Id", new AttributeValue { S = "Amazon DynamoDB#DynamoDB Thread 1" }}}
};

var response = client.Query(request);

foreach (Dictionary<string, AttributeValue> item in response.Items)
{
    // Process the result.
}

```

```
    PrintItem(item);
}
```

## Specifying optional parameters

The `Query` method supports several optional parameters. For example, you can optionally narrow the query result in the preceding query to return replies in the past two weeks by specifying a condition. The condition is called a *sort key condition*, because DynamoDB evaluates the query condition that you specify against the sort key of the primary key. You can specify other optional parameters to retrieve only a specific list of attributes from items in the query result. For more information, see [Query](#).

The following C# code example retrieves forum thread replies posted in the past 15 days. The example specifies the following optional parameters:

- A `KeyConditionExpression` to retrieve only the replies in the past 15 days.
- A `ProjectionExpression` parameter to specify a list of attributes to retrieve for items in the query result.
- A `ConsistentRead` parameter to perform a strongly consistent read.

## Example

```
DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
string twoWeeksAgoString = twoWeeksAgoDate.ToString(AWSSDKUtils.ISO8601DateFormat);

var request = new QueryRequest
{
    TableName = "Reply",
    KeyConditionExpression = "Id = :v_Id and ReplyDateTime > :v_twoWeeksAgo",
    ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
        {" :v_Id", new AttributeValue { S = "Amazon DynamoDB#DynamoDB Thread 2" }},
        {" :v_twoWeeksAgo", new AttributeValue { S = twoWeeksAgoString }}
    },
    ProjectionExpression = "Subject, ReplyDateTime, PostedBy",
    ConsistentRead = true
};

var response = client.Query(request);

foreach (Dictionary<string, AttributeValue> item in response.Items)
{
    // Process the result.
    PrintItem(item);
}
```

You can also optionally limit the page size, or the number of items per page, by adding the optional `Limit` parameter. Each time you run the `Query` method, you get one page of results that has the specified number of items. To fetch the next page, you run the `Query` method again by providing the primary key value of the last item in the previous page so that the method can return the next set of items. You provide this information in the request by setting the `ExclusiveStartKey` property. Initially, this property can be null. To retrieve subsequent pages, you must update this property value to the primary key of the last item in the preceding page.

The following C# example queries the `Reply` table. In the request, it specifies the `Limit` and `ExclusiveStartKey` optional parameters. The do/while loop continues to scan one page at time until the `LastEvaluatedKey` returns a null value.

## Example

```
Dictionary<string,AttributeValue> lastKeyEvaluated = null;

do
{
    var request = new QueryRequest
    {
        TableName = "Reply",
        KeyConditionExpression = "Id = :v_Id",
        ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
            {"v_Id", new AttributeValue { S = "Amazon DynamoDB#DynamoDB Thread 2" }}
        },

        // Optional parameters.
        Limit = 1,
        ExclusiveStartKey = lastKeyEvaluated
    };

    var response = client.Query(request);

    // Process the query result.
    foreach (Dictionary<string, AttributeValue> item in response.Items)
    {
        PrintItem(item);
    }

    lastKeyEvaluated = response.LastEvaluatedKey;
} while (lastKeyEvaluated != null && lastKeyEvaluated.Count != 0);
```

### Example - querying using the AWS SDK for .NET

The following tables store information about a collection of forums. For more information, see [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

#### Example

```
Forum ( Name, ... )
Thread ( ForumName, Subject, Message, LastPostedBy, LastPostDateTime, ... )
Reply ( Id, ReplyDateTime, Message, PostedBy, ... )
```

In this example, you run variations of "Find replies for a thread "DynamoDB Thread 1" in forum "DynamoDB".

- Find replies for a thread.
- Find replies for a thread. Specify the `Limit` query parameter to set page size.

This function illustrates the use of pagination to process multipage result. DynamoDB has a page size limit and if your result exceeds the page size, you get only the first page of results. This coding pattern ensures your code processes all the pages in the query result.

- Find replies in the last 15 days.
- Find replies in a specific date range.

The preceding two queries show how you can specify sort key conditions to narrow query results and use other optional query parameters.

For step-by-step instructions for testing the following example, see [.NET code examples \(p. 276\)](#).

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
*/
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;
using Amazon.Util;

namespace com.amazonaws.codesamples
{
    class LowLevelQuery
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
        {
            try
            {
                // Query a specific forum and thread.
                string forumName = "Amazon DynamoDB";
                string threadSubject = "DynamoDB Thread 1";

                FindRepliesForAThread(forumName, threadSubject);
                FindRepliesForAThreadSpecifyOptionalLimit(forumName, threadSubject);
                FindRepliesInLast15DaysWithConfig(forumName, threadSubject);
                FindRepliesPostedWithinTimePeriod(forumName, threadSubject);

                Console.WriteLine("Example complete. To continue, press Enter");
                Console.ReadLine();
            }
            catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message);
                Console.ReadLine(); }
            catch (AmazonServiceException e) { Console.WriteLine(e.Message);
                Console.ReadLine(); }
            catch (Exception e) { Console.WriteLine(e.Message); Console.ReadLine(); }
        }

        private static void FindRepliesPostedWithinTimePeriod(string forumName, string
threadSubject)
        {
            Console.WriteLine("**** Executing FindRepliesPostedWithinTimePeriod() ****");
            string replyId = forumName + "#" + threadSubject;
            // You must provide date value based on your test data.
            DateTime startDate = DateTime.UtcNow - TimeSpan.FromDays(21);
            string start = startDate.ToString(AWSSDKUtils.ISO8601DateFormat);

            // You provide date value based on your test data.
            DateTime endDate = DateTime.UtcNow - TimeSpan.FromDays(5);
            string end = endDate.ToString(AWSSDKUtils.ISO8601DateFormat);

            var request = new QueryRequest
            {
                TableName = "Reply",
                ReturnConsumedCapacity = "TOTAL",

```

```

        KeyConditionExpression = "Id = :v_replyId and ReplyDateTime
between :v_start and :v_end",
        ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
            {"":v_replyId", new AttributeValue {
                S = replyId
            }},
            {"":v_start", new AttributeValue {
                S = start
            }},
            {"":v_end", new AttributeValue {
                S = end
            }}
        }
    };

    var response = client.Query(request);

    Console.WriteLine("\nNo. of reads used (by query in
FindRepliesPostedWithinTimePeriod) {0}",
                    response.ConsumedCapacity.CapacityUnits);
    foreach (Dictionary<string, AttributeValue> item
             in response.Items)
    {
        PrintItem(item);
    }
    Console.WriteLine("To continue, press Enter");
    Console.ReadLine();
}

private static void FindRepliesInLast15DaysWithConfig(string forumName, string
threadSubject)
{
    Console.WriteLine("**** Executing FindRepliesInLast15DaysWithConfig() ****");
    string replyId = forumName + "#" + threadSubject;

    DateTime twoWeeksAgoDate = DateTime.UtcNow - TimeSpan.FromDays(15);
    string twoWeeksAgoString =
        twoWeeksAgoDate.ToString(AWSSDKUtils.ISO8601DateFormat);

    var request = new QueryRequest
    {
        TableName = "Reply",
        ReturnConsumedCapacity = "TOTAL",
        KeyConditionExpression = "Id = :v_replyId and ReplyDateTime > :v_interval",
        ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
            {"":v_replyId", new AttributeValue {
                S = replyId
            }},
            {"":v_interval", new AttributeValue {
                S = twoWeeksAgoString
            }}
        },
        // Optional parameter.
        ProjectionExpression = "Id, ReplyDateTime, PostedBy",
        // Optional parameter.
        ConsistentRead = true
    };

    var response = client.Query(request);

    Console.WriteLine("No. of reads used (by query in
FindRepliesInLast15DaysWithConfig) {0}",
                    response.ConsumedCapacity.CapacityUnits);
    foreach (Dictionary<string, AttributeValue> item
             in response.Items)
}

```

```

        {
            PrintItem(item);
        }
        Console.WriteLine("To continue, press Enter");
        Console.ReadLine();
    }

    private static void FindRepliesForAThreadSpecifyOptionalLimit(string forumName,
string threadSubject)
    {
        Console.WriteLine("**** Executing FindRepliesForAThreadSpecifyOptionalLimit()
****");
        string replyId = forumName + "#" + threadSubject;

        Dictionary<string, AttributeValue> lastKeyEvaluated = null;
        do
        {
            var request = new QueryRequest
            {
                TableName = "Reply",
                ReturnConsumedCapacity = "TOTAL",
                KeyConditionExpression = "Id = :v_replyId",
                ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
                    {"<:v_replyId", new AttributeValue {
                        S = replyId
                    }}
                },
                Limit = 2, // The Reply table has only a few sample items. So the page
size is smaller.
                ExclusiveStartKey = lastKeyEvaluated
            };

            var response = client.Query(request);

            Console.WriteLine("No. of reads used (by query in
FindRepliesForAThreadSpecifyLimit) {0}\n",
                response.ConsumedCapacity.CapacityUnits);
            foreach (Dictionary<string, AttributeValue> item
                in response.Items)
            {
                PrintItem(item);
            }
            lastKeyEvaluated = response.LastEvaluatedKey;
        } while (lastKeyEvaluated != null && lastKeyEvaluated.Count != 0);

        Console.WriteLine("To continue, press Enter");

        Console.ReadLine();
    }

    private static void FindRepliesForAThread(string forumName, string threadSubject)
    {
        Console.WriteLine("**** Executing FindRepliesForAThread() ****");
        string replyId = forumName + "#" + threadSubject;

        var request = new QueryRequest
        {
            TableName = "Reply",
            ReturnConsumedCapacity = "TOTAL",
            KeyConditionExpression = "Id = :v_replyId",
            ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
                {"<:v_replyId", new AttributeValue {
                    S = replyId
                }}
            }
        }
    }
}

```

```

    };

    var response = client.Query(request);
    Console.WriteLine("No. of reads used (by query in FindRepliesForAThread)
{0}\n",
                      response.ConsumedCapacity.CapacityUnits);
    foreach (Dictionary<string, AttributeValue> item in response.Items)
    {
        PrintItem(item);
    }
    Console.WriteLine("To continue, press Enter");
    Console.ReadLine();
}

private static void PrintItem(
    Dictionary<string, AttributeValue> attributeList)
{
    foreach (KeyValuePair<string, AttributeValue> kvp in attributeList)
    {
        string attributeName = kvp.Key;
        AttributeValue value = kvp.Value;

        Console.WriteLine(
            attributeName + " " +
            (value.S == null ? "" : "S=[ " + value.S + " ]") +
            (value.N == null ? "" : "N=[ " + value.N + " ]") +
            (value.SS == null ? "" : "SS=[ " + string.Join(",", value.SS.ToArray()) +
            " ]") +
            (value.NS == null ? "" : "NS=[ " + string.Join(",", value.NS.ToArray()) +
            " ]"));
    }
    Console.WriteLine("*****");
}
}

```

## Working with scans in DynamoDB

A Scan operation in Amazon DynamoDB reads every item in a table or a secondary index. By default, a Scan operation returns all of the data attributes for every item in the table or index. You can use the `ProjectionExpression` parameter so that Scan only returns some of the attributes, rather than all of them.

Scan always returns a result set. If no matching items are found, the result set is empty.

A single Scan request can retrieve a maximum of 1 MB of data. Optionally, DynamoDB can apply a filter expression to this data, narrowing the results before they are returned to the user.

## Topics

- Filter expressions for scan (p. 446)
  - Limiting the number of items in the result set (p. 446)
  - Paginating the results (p. 446)
  - Counting the items in the results (p. 448)
  - Capacity units consumed by scan (p. 448)
  - Read consistency for scan (p. 449)
  - Parallel scan (p. 449)
  - Scanning tables and indexes: Java (p. 451)

- Scanning tables and indexes: .NET (p. 458)

## Filter expressions for scan

If you need to further refine the Scan results, you can optionally provide a filter expression. A *filter expression* determines which items within the Scan results should be returned to you. All of the other results are discarded.

A filter expression is applied after a Scan finishes but before the results are returned. Therefore, a Scan consumes the same amount of read capacity, regardless of whether a filter expression is present.

A Scan operation can retrieve a maximum of 1 MB of data. This limit applies before the filter expression is evaluated.

With Scan, you can specify any attributes in a filter expression—including partition key and sort key attributes.

The syntax for a filter expression is identical to that of a condition expression. Filter expressions can use the same comparators, functions, and logical operators as a condition expression. For more information, [Condition expressions \(p. 361\)](#).

### Example

The following AWS Command Line Interface (AWS CLI) example scans the Thread table and returns only the items that were last posted to by a particular user.

```
aws dynamodb scan \  
  --table-name Thread \  
  --filter-expression "LastPostedBy = :name" \  
  --expression-attribute-values '{":name":{"S":"User A"}}'
```

## Limiting the number of items in the result set

The Scan operation enables you to limit the number of items that it returns in the result. To do this, set the Limit parameter to the maximum number of items that you want the Scan operation to return, prior to filter expression evaluation.

For example, suppose that you Scan a table with a Limit value of 6 and without a filter expression. The Scan result contains the first six items from the table.

Now suppose that you add a filter expression to the Scan. In this case, DynamoDB applies the filter expression to the six items that were returned, discarding those that do not match. The final Scan result contains six items or fewer, depending on the number of items that were filtered.

## Paginating the results

DynamoDB *paginates* the results from Scan operations. With pagination, the Scan results are divided into "pages" of data that are 1 MB in size (or less). An application can process the first page of results, then the second page, and so on.

A single Scan only returns a result set that fits within the 1 MB size limit.

To determine whether there are more results and to retrieve them one page at a time, applications should do the following:

1. Examine the low-level Scan result:

- If the result contains a `LastEvaluatedKey` element, proceed to step 2.
  - If there is *not* a `LastEvaluatedKey` in the result, then there are no more items to be retrieved.
2. Construct a new Scan request, with the same parameters as the previous one. However, this time, take the `LastEvaluatedKey` value from step 1 and use it as the `ExclusiveStartKey` parameter in the new Scan request.
  3. Run the new Scan request.
  4. Go to step 1.

In other words, the `LastEvaluatedKey` from a Scan response should be used as the `ExclusiveStartKey` for the next Scan request. If there is not a `LastEvaluatedKey` element in a Scan response, you have retrieved the final page of results. (The absence of `LastEvaluatedKey` is the only way to know that you have reached the end of the result set.)

You can use the AWS CLI to view this behavior. The AWS CLI sends low-level Scan requests to DynamoDB, repeatedly, until `LastEvaluatedKey` is no longer present in the results. Consider the following AWS CLI example that scans the entire `Movies` table but returns only the movies from a particular genre.

```
aws dynamodb scan \
    --table-name Movies \
    --projection-expression "title" \
    --filter-expression 'contains(info.genres,:gen)' \
    --expression-attribute-values '{":gen":{"S":"Sci-Fi"}}' \
    --page-size 100 \
    --debug
```

Ordinarily, the AWS CLI handles pagination automatically. However, in this example, the AWS CLI `--page-size` parameter limits the number of items per page. The `--debug` parameter prints low-level information about requests and responses.

**Note**

Your pagination results will also differ based on the input parameters you pass.

- Using `aws dynamodb scan --table-name Prices --max-items 1` returns a `NextToken`
- Using `aws dynamodb scan --table-name Prices --limit 1` returns a `LastEvaluatedKey`.

Also be aware that using `--starting-token` in particular requires the `NextToken` value.

If you run the example, the first response from DynamoDB looks similar to the following.

```
2017-07-07 12:19:14,389 - MainThread - botocore.parsers - DEBUG - Response body:
b'{"Count":7,"Items":[{"title":{"S":"Monster on the Campus"}}, {"title":{"S":"+1"}}, {"title":{"S":"100 Degrees Below Zero"}}, {"title":{"S":"About Time"}}, {"title":{"S":"After Earth"}}, {"title":{"S":"Age of Dinosaurs"}}, {"title":{"S":"Cloudy with a Chance of Meatballs 2"}}, "LastEvaluatedKey":{"year":{"N":"2013"}, "title":{"S":"Curse of Chucky"}}, "ScannedCount":100}'
```

The `LastEvaluatedKey` in the response indicates that not all of the items have been retrieved. The AWS CLI then issues another Scan request to DynamoDB. This request and response pattern continues, until the final response.

```
2017-07-07 12:19:17,830 - MainThread - botocore.parsers - DEBUG - Response body:
```

```
b'{"Count":1,"Items":[{"title":{"S":"WarGames"}}], "ScannedCount":6}'
```

The absence of `LastEvaluatedKey` indicates that there are no more items to retrieve.

**Note**

The AWS SDKs handle the low-level DynamoDB responses (including the presence or absence of `LastEvaluatedKey`) and provide various abstractions for paginating Scan results. For example, the SDK for Java document interface provides `java.util.Iterator` support so that you can walk through the results one at a time.

For code examples in various programming languages, see the [Amazon DynamoDB Getting Started Guide](#) and the AWS SDK documentation for your language.

## Counting the items in the results

In addition to the items that match your criteria, the Scan response contains the following elements:

- `ScannedCount` — The number of items evaluated, before any `ScanFilter` is applied. A high `ScannedCount` value with few, or no, `Count` results indicates an inefficient Scan operation. If you did not use a filter in the request, `ScannedCount` is the same as `Count`.
- `Count` — The number of items that remain, *after* a filter expression (if present) was applied.

**Note**

If you do not use a filter expression, `ScannedCount` and `Count` have the same value.

If the size of the Scan result set is larger than 1 MB, `ScannedCount` and `Count` represent only a partial count of the total items. You need to perform multiple Scan operations to retrieve all the results (see [Paginating the results \(p. 446\)](#)).

Each Scan response contains the `ScannedCount` and `Count` for the items that were processed by that particular Scan request. To get grand totals for all of the Scan requests, you could keep a running tally of both `ScannedCount` and `Count`.

## Capacity units consumed by scan

You can Scan any table or secondary index. Scan operations consume read capacity units, as follows.

If you Scan a...	DynamoDB consumes read capacity units from...
Table	The table's provisioned read capacity.
Global secondary index	The index's provisioned read capacity.
Local secondary index	The base table's provisioned read capacity.

By default, a Scan operation does not return any data on how much read capacity it consumes. However, you can specify the `ReturnConsumedCapacity` parameter in a Scan request to obtain this information. The following are the valid settings for `ReturnConsumedCapacity`:

- `NONE` — No consumed capacity data is returned. (This is the default.)
- `TOTAL` — The response includes the aggregate number of read capacity units consumed.
- `INDEXES` — The response shows the aggregate number of read capacity units consumed, together with the consumed capacity for each table and index that was accessed.

DynamoDB calculates the number of read capacity units consumed based on item size, not on the amount of data that is returned to an application. For this reason, the number of capacity units

consumed is the same whether you request all of the attributes (the default behavior) or just some of them (using a projection expression). The number is also the same whether or not you use a filter expression.

## Read consistency for scan

A Scan operation performs eventually consistent reads, by default. This means that the Scan results might not reflect changes due to recently completed PutItem or UpdateItem operations. For more information, see [Read consistency \(p. 17\)](#).

If you require strongly consistent reads, as of the time that the Scan begins, set the ConsistentRead parameter to true in the Scan request. This ensures that all of the write operations that completed before the Scan began are included in the Scan response.

Setting ConsistentRead to true can be useful in table backup or replication scenarios, in conjunction with [DynamoDB Streams](#). You first use Scan with ConsistentRead set to true to obtain a consistent copy of the data in the table. During the Scan, DynamoDB Streams records any additional write activity that occurs on the table. After the Scan is complete, you can apply the write activity from the stream to the table.

### Note

A Scan operation with ConsistentRead set to true consumes twice as many read capacity units as compared to leaving ConsistentRead at its default value (false).

## Parallel scan

By default, the Scan operation processes data sequentially. Amazon DynamoDB returns data to the application in 1 MB increments, and an application performs additional Scan operations to retrieve the next 1 MB of data.

The larger the table or index being scanned, the more time the Scan takes to complete. In addition, a sequential Scan might not always be able to fully use the provisioned read throughput capacity: Even though DynamoDB distributes a large table's data across multiple physical partitions, a Scan operation can only read one partition at a time. For this reason, the throughput of a Scan is constrained by the maximum throughput of a single partition.


To address these issues, the Scan operation can logically divide a table or secondary index into multiple *segments*, with multiple application workers scanning the segments in parallel. Each worker can be a thread (in programming languages that support multithreading) or an operating system process. To perform a parallel scan, each worker issues its own Scan request with the following parameters:

- Segment — A segment to be scanned by a particular worker. Each worker should use a different value for Segment.
- TotalSegments — The total number of segments for the parallel scan. This value must be the same as the number of workers that your application will use.

The following diagram shows how a multithreaded application performs a parallel Scan with three degrees of parallelism.

*S: Segment*  
*TS: TotalSegments*

*ESK: ExclusiveStartKey*  
*LEK: LastEvaluatedKey*



In this diagram, the application spawns three threads and assigns each thread a number. (Segments are zero-based, so the first number is always 0.) Each thread issues a `Scan` request, setting `Segment` to its designated number and setting `TotalSegments` to 3. Each thread scans its designated segment, retrieving data 1 MB at a time, and returns the data to the application's main thread.

The values for `Segment` and `TotalSegments` apply to individual `Scan` requests, and you can use different values at any time. You might need to experiment with these values, and the number of workers you use, until your application achieves its best performance.

#### Note

A parallel scan with a large number of workers can easily consume all of the provisioned throughput for the table or index being scanned. It is best to avoid such scans if the table or index is also incurring heavy read or write activity from other applications.

To control the amount of data returned per request, use the `Limit` parameter. This can help prevent situations where one worker consumes all of the provisioned throughput, at the expense of all other workers.

## Scanning tables and indexes: Java

The `Scan` operation reads all of the items in a table or index in Amazon DynamoDB.

The following are the steps to scan a table using the AWS SDK for Java Document API.

1. Create an instance of the `AmazonDynamoDB` class.
2. Create an instance of the `ScanRequest` class and provide scan parameter.  
The only required parameter is the table name.
3. Run the `scan` method and provide the `ScanRequest` object that you created in the preceding step.

The following `Reply` table stores replies for forum threads.

### Example

```
Reply ( Id, ReplyDateTime, Message, PostedBy )
```

The table maintains all the replies for various forum threads. Therefore, the primary key is composed of both the `Id` (partition key) and `ReplyDateTime` (sort key). The following Java code example scans the entire table. The `ScanRequest` instance specifies the name of the table to scan.

### Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();

ScanRequest scanRequest = new ScanRequest()
    .withTableName("Reply");

ScanResult result = client.scan(scanRequest);
for (Map<String, AttributeValue> item : result.getItems()){
    printItem(item);
}
```

### Specifying optional parameters

The `scan` method supports several optional parameters. For example, you can optionally use a filter expression to filter the scan result. In a filter expression, you can specify a condition and attribute names and values on which you want the condition evaluated. For more information, see [Scan](#).

The following Java example scans the `ProductCatalog` table to find items that are priced less than 0. The example specifies the following optional parameters:

- A filter expression to retrieve only the items priced less than 0 (error condition).
- A list of attributes to retrieve for items in the query results.

### Example

```
Map<String, AttributeValue> expressionAttributeValues =
    new HashMap<String, AttributeValue>();
```

```

expressionAttributeValues.put(":val", new AttributeValue().withN("0"));

ScanRequest scanRequest = new ScanRequest()
    .withTableName("ProductCatalog")
    .withFilterExpression("Price < :val")
    .withProjectionExpression("Id")
    .withExpressionAttributeValues(expressionAttributeValues);

ScanResult result = client.scan(scanRequest);
for (Map<String, AttributeValue> item : result.getItems()) {
    printItem(item);
}

```

You can also optionally limit the page size, or the number of items per page, by using the `withLimit` method of the scan request. Each time you run the `scan` method, you get one page of results that has the specified number of items. To fetch the next page, you run the `scan` method again by providing the primary key value of the last item in the previous page so that the `scan` method can return the next set of items. You provide this information in the request by using the `withExclusiveStartKey` method. Initially, the parameter of this method can be null. To retrieve subsequent pages, you must update this property value to the primary key of the last item in the preceding page.

The following Java code example scans the `ProductCatalog` table. In the request, the `withLimit` and `withExclusiveStartKey` methods are used. The do/while loop continues to scan one page at time until the `getLastEvaluatedKey` method of the result returns a value of null.

### Example

```

Map<String, AttributeValue> lastKeyEvaluated = null;
do {
    ScanRequest scanRequest = new ScanRequest()
        .withTableName("ProductCatalog")
        .withLimit(10)
        .withExclusiveStartKey(lastKeyEvaluated);

    ScanResult result = client.scan(scanRequest);
    for (Map<String, AttributeValue> item : result.getItems()){
        printItem(item);
    }
    lastKeyEvaluated = result.getLastEvaluatedKey();
} while (lastKeyEvaluated != null);

```

### Example - scan using Java

The following Java code example provides a working sample that scans the `ProductCatalog` table to find items that are priced less than 100.

#### Note

The SDK for Java also provides an object persistence model, enabling you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code that you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

#### Note

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.

```

```

/*
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples.document;

import java.util.HashMap;
import java.util.Iterator;
import java.util.Map;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Item;
import com.amazonaws.services.dynamodbv2.document.ItemCollection;
import com.amazonaws.services.dynamodbv2.document.ScanOutcome;
import com.amazonaws.services.dynamodbv2.document.Table;

public class DocumentAPIScan {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDB dynamoDB = new DynamoDB(client);
    static String tableName = "ProductCatalog";

    public static void main(String[] args) throws Exception {
        findProductsForPriceLessThanOneHundred();
    }

    private static void findProductsForPriceLessThanOneHundred() {
        Table table = dynamoDB.getTable(tableName);

        Map<String, Object> expressionAttributeValues = new HashMap<String, Object>();
        expressionAttributeValues.put(":pr", 100);

        ItemCollection<ScanOutcome> items = table.scan("Price < :pr", // FilterExpression
            "Id, Title, ProductCategory, Price", // ProjectionExpression
            null, // ExpressionAttributeNames - not used in this example
            expressionAttributeValues);

        System.out.println("Scan of " + tableName + " for items with a price less than
100.");
        Iterator<Item> iterator = items.iterator();
        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }
    }
}

```

### Example - parallel scan using Java

The following Java code example demonstrates a parallel scan. The program deletes and re-creates a table named ParallelScanTest, and then loads the table with data. When the data load is finished,

the program spawns multiple threads and issues parallel Scan requests. The program prints runtime statistics for each parallel request.

**Note**

The SDK for Java also provides an object persistence model, enabling you to map your client-side classes to DynamoDB tables. This approach can reduce the amount of code that you have to write. For more information, see [Java: DynamoDBMapper \(p. 170\)](#).

**Note**

This code example assumes that you have already loaded data into DynamoDB for your account by following the instructions in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section.

For step-by-step instructions to run the following example, see [Java code examples \(p. 274\)](#).

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
  
package com.amazonaws.codesamples.document;  
  
import java.util.ArrayList;  
import java.util.Arrays;  
import java.util.HashSet;  
import java.util.Iterator;  
import java.util.List;  
import java.util.concurrent.ExecutorService;  
import java.util.concurrent.Executors;  
import java.util.concurrent.TimeUnit;  
  
import com.amazonaws.AmazonServiceException;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;  
import com.amazonaws.services.dynamodbv2.document.DynamoDB;  
import com.amazonaws.services.dynamodbv2.document.Item;  
import com.amazonaws.services.dynamodbv2.document.ItemCollection;  
import com.amazonaws.services.dynamodbv2.document.ScanOutcome;  
import com.amazonaws.services.dynamodbv2.document.Table;  
import com.amazonaws.services.dynamodbv2.document.spec.ScanSpec;  
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;  
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;  
import com.amazonaws.services.dynamodbv2.model.KeyType;  
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;  
  
public class DocumentAPIParallelScan {  
  
    // total number of sample items  
    static int scanItemCount = 300;  
  
    // number of items each scan request should return  
    static int scanItemLimit = 10;  
  
    // number of logical segments for parallel scan  
    static int parallelScanThreads = 16;
```

```

// table that will be used for scanning
static String parallelScanTestTableName = "ParallelScanTest";

static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
static DynamoDB dynamoDB = new DynamoDB(client);

public static void main(String[] args) throws Exception {
    try {

        // Clean up the table
        deleteTable(parallelScanTestTableName);
        createTable(parallelScanTestTableName, 10L, 5L, "Id", "N");

        // Upload sample data for scan
        uploadSampleProducts(parallelScanTestTableName, scanItemCount);

        // Scan the table using multiple threads
        parallelScan(parallelScanTestTableName, scanItemLimit, parallelScanThreads);
    }
    catch (AmazonServiceException ase) {
        System.err.println(ase.getMessage());
    }
}

private static void parallelScan(String tableName, int itemLimit, int numberOfThreads)
{
    System.out.println(
        "Scanning " + tableName + " using " + numberOfThreads + " threads " + itemLimit
+ " items at a time");
    ExecutorService executor = Executors.newFixedThreadPool(numberOfThreads);

    // Divide DynamoDB table into logical segments
    // Create one task for scanning each segment
    // Each thread will be scanning one segment
    int totalSegments = numberOfThreads;
    for (int segment = 0; segment < totalSegments; segment++) {
        // Runnable task that will only scan one segment
        ScanSegmentTask task = new ScanSegmentTask(tableName, itemLimit, totalSegments,
segment);

        // Execute the task
        executor.execute(task);
    }

    shutDownExecutorService(executor);
}

// Runnable task for scanning a single segment of a DynamoDB table
private static class ScanSegmentTask implements Runnable {

    // DynamoDB table to scan
    private String tableName;

    // number of items each scan request should return
    private int itemLimit;

    // Total number of segments
    // Equals to total number of threads scanning the table in parallel
    private int totalSegments;

    // Segment that will be scanned with by this task
    private int segment;

    public ScanSegmentTask(String tableName, int itemLimit, int totalSegments, int
segment) {
        this.tableName = tableName;
}

```

```

        this.itemLimit = itemLimit;
        this.totalSegments = totalSegments;
        this.segment = segment;
    }

    @Override
    public void run() {
        System.out.println("Scanning " + tableName + " segment " + segment + " out of "
+ totalSegments
                + " segments " + itemLimit + " items at a time...");
        int totalScannedItemCount = 0;

        Table table = dynamoDB.getTable(tableName);

        try {
            ScanSpec spec = new
ScanSpec().withMaxResultSize(itemLimit).withTotalSegments(totalSegments)
                    .withSegment(segment);

            ItemCollection<ScanOutcome> items = table.scan(spec);
            Iterator<Item> iterator = items.iterator();

            Item currentItem = null;
            while (iterator.hasNext()) {
                totalScannedItemCount++;
                currentItem = iterator.next();
                System.out.println(currentItem.toString());
            }
        }
        catch (Exception e) {
            System.err.println(e.getMessage());
        }
        finally {
            System.out.println("Scanned " + totalScannedItemCount + " items from
segment " + segment + " out of "
                    + totalSegments + " of " + tableName);
        }
    }
}

private static void uploadSampleProducts(String tableName, int itemCount) {
    System.out.println("Adding " + itemCount + " sample items to " + tableName);
    for (int productIndex = 0; productIndex < itemCount; productIndex++) {
        uploadProduct(tableName, productIndex);
    }
}

private static void uploadProduct(String tableName, int productIndex) {

    Table table = dynamoDB.getTable(tableName);

    try {
        System.out.println("Processing record #" + productIndex);

        Item item = new Item().withPrimaryKey("Id", productIndex)
                .withString("Title", "Book " + productIndex + " Title").withString("ISBN",
"111-1111111111")
                .withStringSet("Authors", new
HashSet<String>(Arrays.asList("Author1"))).withNumber("Price", 2)
                .withString("Dimensions", "8.5 x 11.0 x 0.5").withNumber("PageCount", 500)
                .withBoolean("InPublication", true).withString("ProductCategory", "Book");
        table.putItem(item);

    }
    catch (Exception e) {

```

```

        System.err.println("Failed to create item " + productIndex + " in " +
tableName);
        System.err.println(e.getMessage());
    }

}

private static void deleteTable(String tableName) {
    try {

        Table table = dynamoDB.getTable(tableName);
        table.delete();
        System.out.println("Waiting for " + tableName + " to be deleted...this may take
a while...");
        table.waitForDelete();

    }
    catch (Exception e) {
        System.err.println("Failed to delete table " + tableName);
        e.printStackTrace(System.err);
    }
}

private static void createTable(String tableName, long readCapacityUnits, long
writeCapacityUnits,
String partitionKeyName, String partitionKeyType) {

    createTable(tableName, readCapacityUnits, writeCapacityUnits, partitionKeyName,
partitionKeyType, null, null);
}

private static void createTable(String tableName, long readCapacityUnits, long
writeCapacityUnits,
String partitionKeyName, String partitionKeyType, String sortKeyName, String
sortKeyType) {

    try {
        System.out.println("Creating table " + tableName);

        List<KeySchemaElement> keySchema = new ArrayList<KeySchemaElement>();
        keySchema.add(new
KeySchemaElement().withAttributeName(partitionKeyName).withKeyType(KeyType.HASH)); // /
Partition

        // key

        List<AttributeDefinition> attributeDefinitions = new
ArrayList<AttributeDefinition>();
        attributeDefinitions
            .add(new
AttributeDefinition().withAttributeName(partitionKeyName).withAttributeType(partitionKeyType));

        if (sortKeyName != null) {
            keySchema.add(new
KeySchemaElement().withAttributeName(sortKeyName).withKeyType(KeyType.RANGE)); // Sort

            // key
            attributeDefinitions
                .add(new
AttributeDefinition().withAttributeName(sortKeyName).withAttributeType(sortKeyType));
        }

        Table table = dynamoDB.createTable(tableName, keySchema, attributeDefinitions,
new ProvisionedThroughput()

        .withReadCapacityUnits(readCapacityUnits).withWriteCapacityUnits(writeCapacityUnits));
    }
}

```

```

        System.out.println("Waiting for " + tableName + " to be created...this may take
a while...");
        table.waitForActive();

    }
    catch (Exception e) {
        System.err.println("Failed to create table " + tableName);
        e.printStackTrace(System.err);
    }
}

private static void shutDownExecutorService(ExecutorService executor) {
    executor.shutdown();
    try {
        if (!executor.awaitTermination(10, TimeUnit.SECONDS)) {
            executor.shutdownNow();
        }
    }
    catch (InterruptedException e) {
        executor.shutdownNow();

        // Preserve interrupt status
        Thread.currentThread().interrupt();
    }
}
}

```

## Scanning tables and indexes: .NET

The `Scan` operation reads all of the items in a table or index in Amazon DynamoDB.

The following are the steps to scan a table using the AWS SDK for .NET low-level API:

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `ScanRequest` class and provide scan operation parameters.  
The only required parameter is the table name.
3. Run the `Scan` method and provide the `QueryRequest` object that you created in the preceding step.

The following `Reply` table stores replies for forum threads.

### Example

```
>Reply ( <emphasis role="underline">Id</emphasis>, <emphasis
role="underline">ReplyDateTime</emphasis>, Message, PostedBy )
```

The table maintains all the replies for various forum threads. Therefore, the primary key is composed of both the `Id` (partition key) and `ReplyDateTime` (sort key). The following C# code example scans the entire table. The `ScanRequest` instance specifies the name of the table to scan.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();

var request = new ScanRequest
{
```

```

        TableName = "Reply",
};

var response = client.Scan(request);
var result = response.ScanResult;

foreach (Dictionary<string, AttributeValue> item in response.ScanResult.Items)
{
    // Process the result.
    PrintItem(item);
}

```

### Specifying optional parameters

The `Scan` method supports several optional parameters. For example, you can optionally use a scan filter to filter the scan result. In a scan filter, you can specify a condition and an attribute name on which you want the condition evaluated. For more information, see [Scan](#).

The following C# code scans the `ProductCatalog` table to find items that are priced less than 0. The sample specifies the following optional parameters:

- A `FilterExpression` parameter to retrieve only the items priced less than 0 (error condition).
- A `ProjectionExpression` parameter to specify the attributes to retrieve for items in the query results.

The following C# example scans the `ProductCatalog` table to find all items priced less than 0.

### Example

```

var forumScanRequest = new ScanRequest
{
    TableName = "ProductCatalog",
    // Optional parameters.
    ExpressionAttributeValues = new Dictionary<string,AttributeValue> {
        {":val", new AttributeValue { N = "0" }}
    },
    FilterExpression = "Price < :val",
    ProjectionExpression = "Id"
};

```

You can also optionally limit the page size or the number of items per page, by adding the optional `Limit` parameter. Each time you run the `Scan` method, you get one page of results that has the specified number of items. To fetch the next page, you run the `Scan` method again by providing the primary key value of the last item in the previous page so that the `Scan` method can return the next set of items. You provide this information in the request by setting the `ExclusiveStartKey` property. Initially, this property can be null. To retrieve subsequent pages, you must update this property value to the primary key of the last item in the preceding page.

The following C# code example scans the `ProductCatalog` table. In the request, it specifies the `Limit` and `ExclusiveStartKey` optional parameters. The do/while loop continues to scan one page at time until the `LastEvaluatedKey` returns a null value.

### Example

```

Dictionary<string, AttributeValue> lastKeyEvaluated = null;
do
{
    var request = new ScanRequest

```

```

    {
        TableName = "ProductCatalog",
        Limit = 10,
        ExclusiveStartKey = lastKeyEvaluated
    };

    var response = client.Scan(request);

    foreach (Dictionary<string, AttributeValue> item
        in response.Items)
    {
        PrintItem(item);
    }
    lastKeyEvaluated = response.LastEvaluatedKey;

} while (lastKeyEvaluated != null && lastKeyEvaluated.Count != 0);

```

### Example - scan using .NET

The following C# code provides a working example that scans the `ProductCatalog` table to find items priced less than 0.

For step-by-step instructions for testing the following sample, see [.NET code examples \(p. 276\)](#).

```

/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;

namespace com.amazonaws.codesamples
{
    class LowLevelScan
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
        {
            try
            {
                FindProductsForPriceLessThanZero();

                Console.WriteLine("Example complete. To continue, press Enter");
                Console.ReadLine();
            }
            catch (Exception e)
            {
                Console.WriteLine(e.Message);
                Console.WriteLine("To continue, press Enter");
                Console.ReadLine();
            }
        }
    }
}

```

```

        }

    }

    private static void FindProductsForPriceLessThanZero()
    {
        Dictionary<string, AttributeValue> lastKeyEvaluated = null;
        do
        {
            var request = new ScanRequest
            {
                TableName = "ProductCatalog",
                Limit = 2,
                ExclusiveStartKey = lastKeyEvaluated,
                ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
                    {"<val", new AttributeValue {
                        N = "0"
                    }}
                },
                FilterExpression = "Price < :val",
                ProjectionExpression = "Id, Title, Price"
            };

            var response = client.Scan(request);

            foreach (Dictionary<string, AttributeValue> item
                     in response.Items)
            {
                Console.WriteLine("\nScanThreadTableUsePaging - printing.....");
                PrintItem(item);
            }
            lastKeyEvaluated = response.LastEvaluatedKey;
        } while (lastKeyEvaluated != null && lastKeyEvaluated.Count != 0);

        Console.WriteLine("To continue, press Enter");
        Console.ReadLine();
    }

    private static void PrintItem(
        Dictionary<string, AttributeValue> attributeList)
    {
        foreach (KeyValuePair<string, AttributeValue> kvp in attributeList)
        {
            string attributeName = kvp.Key;
            AttributeValue value = kvp.Value;

            Console.WriteLine(
                attributeName + " " +
                (value.S == null ? "" : "S=[[" + value.S + "]]") +
                (value.N == null ? "" : "N=[[" + value.N + "]]") +
                (value.SS == null ? "" : "SS=[[" + string.Join(",", value.SS.ToArray()) +
                "]]") +
                (value.NS == null ? "" : "NS=[[" + string.Join(",", value.NS.ToArray()) +
                "]]")
            );
        }
        Console.WriteLine("*****");
    }
}
}

```

### Example - parallel scan using .NET

The following C# code example demonstrates a parallel scan. The program deletes and then re-creates the `ProductCatalog` table and then loads the table with data. When the data load is finished, the

program spawns multiple threads and issues parallel Scan requests. Finally, the program prints a summary of runtime statistics.

For step-by-step instructions for testing the following sample, see [.NET code examples \(p. 276\)](#).

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
using System;  
using System.Collections.Generic;  
using System.Threading;  
using System.Threading.Tasks;  
using Amazon.DynamoDBv2;  
using Amazon.DynamoDBv2.Model;  
using Amazon.Runtime;  
  
namespace com.amazonaws.codesamples  
{  
    class LowLevelParallelScan  
    {  
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();  
        private static string tableName = "ProductCatalog";  
        private static int exampleItemCount = 100;  
        private static int scanItemLimit = 10;  
        private static int totalSegments = 5;  
  
        static void Main(string[] args)  
        {  
            try  
            {  
                DeleteExampleTable();  
                CreateExampleTable();  
                UploadExampleData();  
                ParallelScanExampleTable();  
            }  
            catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }  
            catch (AmazonServiceException e) { Console.WriteLine(e.Message); }  
            catch (Exception e) { Console.WriteLine(e.Message); }  
  
            Console.WriteLine("To continue, press Enter");  
            Console.ReadLine();  
        }  
  
        private static void ParallelScanExampleTable()  
        {  
            Console.WriteLine("\n*** Creating {0} Parallel Scan Tasks to scan {1}",  
totalSegments, tableName);  
            Task[] tasks = new Task[totalSegments];  
            for (int segment = 0; segment < totalSegments; segment++)  
            {  
                int tmpSegment = segment;  
                Task task = Task.Factory.StartNew(() =>  
                {
```

```

                ScanSegment(totalSegments, tmpSegment);
            });

            tasks[segment] = task;
        }

        Console.WriteLine("All scan tasks are created, waiting for them to complete.");
        Task.WaitAll(tasks);

        Console.WriteLine("All scan tasks are completed.");
    }

    private static void ScanSegment(int totalSegments, int segment)
    {
        Console.WriteLine("**** Starting to Scan Segment {0} of {1} out of {2} total
segments ***", segment, tableName, totalSegments);
        Dictionary<string, AttributeValue> lastEvaluatedKey = null;
        int totalScannedItemCount = 0;
        int totalScanRequestCount = 0;
        do
        {
            var request = new ScanRequest
            {
                TableName = tableName,
                Limit = scanItemLimit,
                ExclusiveStartKey = lastEvaluatedKey,
                Segment = segment,
                TotalSegments = totalSegments
            };

            var response = client.Scan(request);
            lastEvaluatedKey = response.LastEvaluatedKey;
            totalScanRequestCount++;
            totalScannedItemCount += response.ScannedCount;
            foreach (var item in response.Items)
            {
                Console.WriteLine("Segment: {0}, Scanned Item with Title: {1}",
segment, item["Title"].S);
            }
        } while (lastEvaluatedKey.Count != 0);

        Console.WriteLine("**** Completed Scan Segment {0} of {1}.
TotalScanRequestCount: {2}, TotalScannedItemCount: {3} ***", segment, tableName,
totalScanRequestCount, totalScannedItemCount);
    }

    private static void UploadExampleData()
    {
        Console.WriteLine("\n*** Uploading {0} Example Items to {1} Table***",
exampleItemCount, tableName);
        Console.Write("Uploading Items: ");
        for (int itemIndex = 0; itemIndex < exampleItemCount; itemIndex++)
        {
            Console.Write("{0}, ", itemIndex);
            CreateItem(itemIndex.ToString());
        }
        Console.WriteLine();
    }

    private static void CreateItem(string itemIndex)
    {
        var request = new PutItemRequest
        {
            TableName = tableName,
            Item = new Dictionary<string, AttributeValue>()
        }

```

```

        {
            "Id", new AttributeValue {
                N = itemIndex
            },
            "Title", new AttributeValue {
                S = "Book " + itemIndex + " Title"
            },
            "ISBN", new AttributeValue {
                S = "11-11-11-11"
            },
            "Authors", new AttributeValue {
                SS = new List<string>{"Author1", "Author2" }
            },
            "Price", new AttributeValue {
                N = "20.00"
            },
            "Dimensions", new AttributeValue {
                S = "8.5x11.0x.75"
            },
            "InPublication", new AttributeValue {
                BOOL = false
            }
        }
    );
    client.PutItem(request);
}

private static void CreateExampleTable()
{
    Console.WriteLine("\n*** Creating {0} Table ***", tableName);
    var request = new CreateTableRequest
    {
        AttributeDefinitions = new List<AttributeDefinition>()
    {
        new AttributeDefinition
        {
            AttributeName = "Id",
            AttributeType = "N"
        },
        KeySchema = new List<KeySchemaElement>
    {
        new KeySchemaElement
        {
            AttributeName = "Id",
            KeyType = "HASH" //Partition key
        }
    },
    ProvisionedThroughput = new ProvisionedThroughput
    {
        ReadCapacityUnits = 5,
        WriteCapacityUnits = 6
    },
    TableName = tableName
    };

    var response = client.CreateTable(request);

    var result = response;
    var tableDescription = result.TableDescription;
    Console.WriteLine("{1}: {0} \t ReadsPerSec: {2} \t WritesPerSec: {3}",
        tableDescription.TableStatus,
        tableDescription.TableName,
        tableDescription.ProvisionedThroughput.ReadCapacityUnits,
        tableDescription.ProvisionedThroughput.WriteCapacityUnits);

    string status = tableDescription.TableStatus;
}

```

```

        Console.WriteLine(tableName + " - " + status);

        WaitUntilTableReady(tableName);
    }

    private static void DeleteExampleTable()
    {
        try
        {
            Console.WriteLine("\n*** Deleting {0} Table ***", tableName);
            var request = new DeleteTableRequest
            {
                TableName = tableName
            };

            var response = client.DeleteTable(request);
            var result = response;
            Console.WriteLine("{0} is being deleted...", tableName);
            WaitUntilTableDeleted(tableName);
        }
        catch (ResourceNotFoundException)
        {
            Console.WriteLine("{0} Table delete failed: Table does not exist",
tableName);
        }
    }

    private static void WaitUntilTableReady(string tableName)
    {
        string status = null;
        // Let us wait until table is created. Call DescribeTable.
        do
        {
            System.Threading.Thread.Sleep(5000); // Wait 5 seconds.
            try
            {
                var res = client.DescribeTable(new DescribeTableRequest
                {
                    TableName = tableName
                });

                Console.WriteLine("Table name: {0}, status: {1}",
                    res.Table.TableName,
                    res.Table.TableStatus);
                status = res.Table.TableStatus;
            }
            catch (ResourceNotFoundException)
            {
                // DescribeTable is eventually consistent. So you might
                // get resource not found. So we handle the potential exception.
            }
        } while (status != "ACTIVE");
    }

    private static void WaitUntilTableDeleted(string tableName)
    {
        string status = null;
        // Let us wait until table is deleted. Call DescribeTable.
        do
        {
            System.Threading.Thread.Sleep(5000); // Wait 5 seconds.
            try
            {
                var res = client.DescribeTable(new DescribeTableRequest
                {
                    TableName = tableName
                });

```

```
        });

        Console.WriteLine("Table name: {0}, status: {1}",
            res.Table.TableName,
            res.Table.TableStatus);
        status = res.Table.TableStatus;
    }
    catch (ResourceNotFoundException)
    {
        Console.WriteLine("Table name: {0} is not found. It is deleted",
    tableName);
        return;
    }
} while (status == "DELETING");
}
}
```

## PartiQL - a SQL-compatible query language for Amazon DynamoDB

Amazon DynamoDB supports [PartiQL](#), a SQL-compatible query language, to select, insert, update, and delete data in Amazon DynamoDB. Using PartiQL, you can easily interact with DynamoDB tables and run ad hoc queries using the AWS Management Console, NoSQL Workbench, AWS Command Line Interface, and DynamoDB APIs for PartiQL.

PartiQL operations provide the same availability, latency, and performance as the other DynamoDB data plane operations.

The following sections describe the DynamoDB implementation of PartiQL.

### Topics

- [What is PartiQL? \(p. 466\)](#)
- [PartiQL in Amazon DynamoDB \(p. 466\)](#)
- [Getting started with PartiQL for DynamoDB \(p. 467\)](#)
- [PartiQL data types for DynamoDB \(p. 472\)](#)
- [PartiQL statements for DynamoDB \(p. 474\)](#)
- [Use PartiQL functions with amazon DynamoDB \(p. 482\)](#)
- [PartiQL arithmetic, comparison, and logical operators for DynamoDB \(p. 486\)](#)
- [Performing transactions with PartiQL for DynamoDB \(p. 487\)](#)
- [Running batch operations with PartiQL for DynamoDB \(p. 491\)](#)
- [IAM security policies with PartiQL for DynamoDB \(p. 494\)](#)

## What is PartiQL?

*PartiQL* provides SQL-compatible query access across multiple data stores containing structured data, semistructured data, and nested data. It is widely used within Amazon and is now available as part of many AWS services, including DynamoDB.

For the PartiQL specification and a tutorial on the core query language, see the [PartiQL documentation](#).

### Note

- Amazon DynamoDB supports a *subset* of the [PartiQL](#) query language.
- Amazon DynamoDB does not support the [Amazon ion](#) data format or Amazon Ion literals.

## PartiQL in Amazon DynamoDB

To run PartiQL queries in DynamoDB, you can use:

- The DynamoDB console
- The NoSQL Workbench
- The AWS Command Line Interface (AWS CLI)
- The DynamoDB APIs

For information about using these methods to access DynamoDB, see [Accessing DynamoDB](#).

## Getting started with PartiQL for DynamoDB


This section describes how to use PartiQL for DynamoDB from the Amazon DynamoDB console, the AWS Command Line Interface (AWS CLI), and DynamoDB APIs.

In the following examples, the DynamoDB table that is defined in the [Getting started with DynamoDB](#) tutorial is a pre-requisite.

For information about using the DynamoDB console, AWS Command Line Interface, or DynamoDB APIs to access DynamoDB, see [Accessing DynamoDB](#).

To download and use the [NoSQL workbench](#) to build [PartiQL for DynamoDB](#) statements choose **PartiQL operations** at the top right corner of the NoSQL Workbench for DynamoDB [Operation builder](#).

### Console



### Note

PartiQL for DynamoDB is only available in the new DynamoDB console. To use the new DynamoDB console, choose **Try the Preview of the new console** in the navigation pane on the left side of the console.

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **PartiQL editor**.
3. Choose the **Music** table.
4. Choose **Query table**. This action generates a query that will not result in a full table scan.

5. Replace `partitionKeyValue` with the string value `Acme Band`. Replace `sortKeyValue` with the string value `Happy Day`.
6. Choose the **Run** button.
7. You can view the results of the query by choosing the **Table view** or the **JSON view** buttons.

#### NoSQL workbench

The screenshot shows the NoSQL workbench interface with the following highlighted areas:

- 1**: A red box highlights the "PartiQL statement" radio button.
- 2**: A red box highlights the WHERE clause of the PartiQL SELECT statement.
- 3.a**: A red box highlights the "Optional request parameters" section.
- 3.b**: A red box highlights the "+ Add new parameter" button.
- 3.c**: A red box highlights the "Attribute value" field for the first parameter, which contains "Acme Band".
- 4**: A red box highlights the "Run" button.
- 5**: A red box highlights the "Generate code" button.
- 6**: A red box highlights the "Save operation" button.

1. Choose **PartiQL statement**.
2. Enter the following PartiQL **SELECT** statement

```
SELECT *
FROM Music
WHERE Artist=? and SongTitle=?
```

3. To specify a value for the `Artist` and `SongTitle` parameters:
    - a. Choose **Optional request parameters**.
    - b. Choose **Add new parameters**.
    - c. Choose the attribute type **string** and value `Acme Band`.
    - d. Repeat steps b and c, and choose type **string** and value `PartiQL Rocks`.
  4. If you want to generate code, choose **Generate code**.
- Select your desired language from the displayed tabs. You can now copy this code and use it in your application.
5. If you want the operation to be run immediately, choose **Run**.

## AWS CLI

1. Create an item in the `Music` table using the `INSERT` PartiQL statement.

```
aws dynamodb execute-statement --statement "INSERT INTO Music \
    VALUE \
        {'Artist':'Acme Band','SongTitle':'PartiQL Rocks'}"
```

2. Retrieve an item from the `Music` table using the `SELECT` PartiQL statement.

```
aws dynamodb execute-statement --statement "SELECT * FROM Music \
    WHERE Artist='Acme Band' AND
    SongTitle='PartiQL Rocks'"
```

3. Update an item in the `Music` table using the `UPDATE` PartiQL statement.

```
aws dynamodb execute-statement --statement "UPDATE Music \
    SET AwardsWon=1 \
    SET AwardDetail={'Grammys':[2020,
    2018]} \
    WHERE Artist='Acme Band' AND
    SongTitle='PartiQL Rocks'"
```

Add a list value for an item in the `Music` table.

```
aws dynamodb execute-statement --statement "UPDATE Music \
    SET AwardDetail.Grammys
    =list_append(AwardDetail.Grammys,[2016]) \
    WHERE Artist='Acme Band' AND
    SongTitle='PartiQL Rocks'"
```

Remove a list value for an item in the `Music` table.

```
aws dynamodb execute-statement --statement "UPDATE Music \
    REMOVE AwardDetail.Grammys[2] \
    WHERE Artist='Acme Band' AND
    SongTitle='PartiQL Rocks'"
```

Add a new map member for an item in the `Music` table.

```
aws dynamodb execute-statement --statement "UPDATE Music \
    SET AwardDetail.BillBoard=[2020] \
    WHERE Artist='Acme Band' AND
    SongTitle='PartiQL Rocks'"
```

Add a new string set attribute for an item in the `Music` table.

```
aws dynamodb execute-statement --statement "UPDATE Music \
    SET BandMembers =<<'member1',
    'member2'>> \
    WHERE Artist='Acme Band' AND
    SongTitle='PartiQL Rocks'"
```

Update a string set attribute for an item in the `Music` table.

```
aws dynamodb execute-statement --statement "UPDATE Music \
    SET BandMembers =<<'member1',
    'member2'>> \
    WHERE Artist='Acme Band' AND
    SongTitle='PartiQL Rocks'"
```

```

        SET BandMembers =set_add(BandMembers,
<<'newmember'>>) \
WHERE Artist='Acme Band' AND
SongTitle='PartiQL Rocks'"
```

4. Delete an item from the Music table using the DELETE PartiQL statement.

```

aws dynamodb execute-statement --statement "DELETE FROM Music \
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'"
```

#### Java

```

import java.util.ArrayList;
import java.util.List;

import com.amazonaws.AmazonClientException;
import com.amazonaws.AmazonServiceException;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
import com.amazonaws.services.dynamodbv2.model.ConditionalCheckFailedException;
import com.amazonaws.services.dynamodbv2.model.ExecuteStatementRequest;
import com.amazonaws.services.dynamodbv2.model.ExecuteStatementResult;
import com.amazonaws.services.dynamodbv2.model.InternalServerErrorException;
import com.amazonaws.services.dynamodbv2.model.ItemCollectionSizeLimitExceededException;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughputExceededException;
import com.amazonaws.services.dynamodbv2.model.RequestLimitExceededException;
import com.amazonaws.services.dynamodbv2.model.ResourceNotFoundException;
import com.amazonaws.services.dynamodbv2.model.TransactionConflictException;

public class DynamoDBPartiQGettingStarted {

    public static void main(String[] args) {
        // Create the DynamoDB Client with the region you want
        AmazonDynamoDB dynamoDB = createDynamoDbClient("us-west-1");

        try {
            // Create ExecuteStatementRequest
            ExecuteStatementRequest executeStatementRequest = new
ExecuteStatementRequest();
            List<AttributeValue> parameters= getPartiQLParameters();

            //Create an item in the Music table using the INSERT PartiQL statement
            processResults(executeStatementRequest(dynamoDB, "INSERT INTO Music value
{'Artist':?, 'SongTitle':?}");
            }

            //Retrieve an item from the Music table using the SELECT PartiQL statement.
            processResults(executeStatementRequest(dynamoDB, "SELECT * FROM Music
where Artist=? and SongTitle=?"));
            }

            //Update an item in the Music table using the UPDATE PartiQL statement.
            processResults(executeStatementRequest(dynamoDB, "UPDATE Music SET
AwardsWon=1 SET AwardDetail={'Grammys':[2020, 2018]} where Artist=? and SongTitle=?",
parameters));

            //Add a list value for an item in the Music table.
            processResults(executeStatementRequest(dynamoDB, "UPDATE Music SET
AwardDetail.Grammys =list_append(AwardDetail.Grammys,[2016]) where Artist=? and
SongTitle=?",
parameters));

            //Remove a list value for an item in the Music table.
            }
```

```

        processResults(executeStatementRequest(dynamoDB, "UPDATE Music REMOVE
AwardDetail.Grammys[2] where Artist=? and SongTitle=?", parameters));

        //Add a new map member for an item in the Music table.
        processResults(executeStatementRequest(dynamoDB, "UPDATE Music set
AwardDetail.BillBoard=[2020] where Artist=? and SongTitle=?", parameters));

        //Add a new string set attribute for an item in the Music table.
        processResults(executeStatementRequest(dynamoDB, "UPDATE Music SET
BandMembers =<<'member1', 'member2'>> where Artist=? and SongTitle=?",
parameters));

        //update a string set attribute for an item in the Music table.
        processResults(executeStatementRequest(dynamoDB, "UPDATE Music SET
BandMembers =set _add(BandMembers, <<'newmember'>>) where Artist=? and SongTitle=?",
parameters));

        //Retrieve an item from the Music table using the SELECT PartiQL statement.
        processResults(executeStatementRequest(dynamoDB, "SELECT * FROM Music
where Artist=? and SongTitle=?", parameters));

        //delete an item from the Music Table
        processResults(executeStatementRequest(dynamoDB, "DELETE FROM Music where
Artist=? and SongTitle=?", parameters));
    } catch (Exception e) {
        handleExecuteStatementErrors(e);
    }
}

private static AmazonDynamoDB createDynamoDbClient(String region) {
    return AmazonDynamoDBClientBuilder.standard().withRegion(region).build();
}

private static List<AttributeValue> getPartiQLParameters() {
    List<AttributeValue> parameters = new ArrayList<AttributeValue>();
    parameters.add(new AttributeValue("Acme Band"));
    parameters.add(new AttributeValue("PartiQL Rocks"));
    return parameters;
}

private static ExecuteStatementResult executeStatementRequest(AmazonDynamoDB
client, String statement, List<AttributeValue> parameters ) {
    ExecuteStatementRequest request = new ExecuteStatementRequest();
    request.setStatement(statement);
    request.setParameters(parameters);
    return client.executeStatement(request);
}

private static void processResults(ExecuteStatementResult executeStatementResult) {
    System.out.println("ExecuteStatement successful: "+
executeStatementResult.toString());
}

// Handles errors during ExecuteStatement execution. Use recommendations in error
messages below to add error handling specific to
// your application use-case.
private static void handleExecuteStatementErrors(Exception exception) {
    try {
        throw exception;
    } catch (ConditionalCheckFailedException ccfe) {
        System.out.println("Condition check specified in the operation failed,
review and update the condition " +
                           "check before retrying. Error: " +
ccfe.getErrorMessage());
    } catch (TransactionConflictException tce) {
}

```

```

        System.out.println("Operation was rejected because there is an ongoing
transaction for the item, generally " +
                           "safe to retry with exponential back-off. Error:
" + tce.getErrorMessage());
    } catch (ItemCollectionSizeLimitExceededException icslee) {
        System.out.println("An item collection is too large, you're using Local
Secondary Index and exceeded " +
                           "size limit of items per partition key. Consider
using Global Secondary Index instead. Error: " + icslee.getErrorMessage());
    } catch (Exception e) {
        handleCommonErrors(e);
    }
}

private static void handleCommonErrors(Exception exception) {
    try {
        throw exception;
    } catch (InternalServerErrorException isee) {
        System.out.println("Internal Server Error, generally safe to retry with
exponential back-off. Error: " + isee.getErrorMessage());
    } catch (RequestLimitExceededException rlee) {
        System.out.println("Throughput exceeds the current throughput limit for
your account, increase account level throughput before " +
                           "retrying. Error: " + rlee.getErrorMessage());
    } catch (ProvisionedThroughputExceededException ptee) {
        System.out.println("Request rate is too high. If you're using a custom
retry strategy make sure to retry with exponential back-off. " +
                           "Otherwise consider reducing frequency of
requests or increasing provisioned capacity for your table or secondary index. Error:
" +
                           ptee.getErrorMessage());
    } catch (ResourceNotFoundException rnfe) {
        System.out.println("One of the tables was not found, verify table exists
before retrying. Error: " + rnfe.getErrorMessage());
    } catch (AmazonServiceException ase) {
        System.out.println("An AmazonServiceException occurred, indicates that the
request was correctly transmitted to the DynamoDB " +
                           "service, but for some reason, the service was
not able to process it, and returned an error response instead. Investigate and " +
                           "configure retry strategy. Error type: " +
                           ase.getErrorType() + ". Error message: " + ase.getMessage());
    } catch (AmazonClientException ace) {
        System.out.println("An AmazonClientException occurred, indicates that the
client was unable to get a response from DynamoDB " +
                           "service, or the client was unable to parse the
response from the service. Investigate and configure retry strategy. " +
                           "Error: " + ace.getMessage());
    } catch (Exception e) {
        System.out.println("An exception occurred, investigate and configure retry
strategy. Error: " + e.getMessage());
    }
}
}

```

## PartiQL data types for DynamoDB

The following table lists the data types you can use with PartiQL for DynamoDB.

DynamoDB data type	PartiQL representation	Notes
Boolean	TRUE   FALSE	Not case sensitive.

DynamoDB data type	PartiQL representation	Notes
Binary	N/A	Only supported via code.
List	[ value1, value2,...]	There are no restrictions on the data types that can be stored in a List type, and the elements in a List do not have to be of the same type.
Map	{ 'name' : value }	There are no restrictions on the data types that can be stored in a Map type, and the elements in a Map do not have to be of the same type.
Null	NULL	Not case sensitive.
Number	1, 1.0, 1e0	Numbers can be positive, negative, or zero. Numbers can have up to 38 digits of precision.
Number Set	<>number1, number2>>	The elements in a number set must be of type Number.
String Set	<>'string1', 'string2'>>	The elements in a string set must be of type String.
String	'string value'	Single quotes must be used to specify String values.

## Examples

The following statement demonstrates how to insert the following data types: String, Number, Map, List, Number Set and String Set.

```
INSERT INTO TypesTable value {'primarykey':'1',
'NumberType':1,
'MapType' : {'entryname1': 'value', 'entryname2': 4},
'ListType': [1,'stringval'],
'NumberSetType':<<1,34,32,4.5>>,
'StringSetType':<<'stringval','stringval2'>>
}
```

The following statement demonstrates how to insert new elements into the Map, List, Number Set and String Set types and change the value of a Number type.

```
UPDATE TypesTable
SET NumberType=NumberType + 100
SET MapType.NewMapEntry=[2020, 'stringvalue', 2.4]
SET ListType = LIST_APPEND(ListType, [4, <<'string1', 'string2'>>])
SET NumberSetType= SET_ADD(NumberSetType, <<345, 48.4>>)
SET StringSetType = SET_ADD(StringSetType, <<'stringsetvalue1', 'stringsetvalue2'>>)
WHERE primarykey='1'
```

The following statement demonstrates how to remove elements from the Map, List, Number Set and String Set types and change the value of a Number type.

```
UPDATE TypesTable
SET NumberType=NumberType - 1
REMOVE ListType[1]
REMOVE MapType.NewMapEntry
SET NumberSetType = SET_DELETE( NumberSetType, <<345>>)
SET StringSetType = SET_DELETE( StringSetType, <<'stringsetvalue1'>>)
WHERE primarykey='1'
```

For more information, see [DynamoDB data types](#).

## PartiQL statements for DynamoDB

Amazon DynamoDB supports the following PartiQL statements.

### Note

DynamoDB does not support all PartiQL statements.

This reference provides basic syntax and usage examples of PartiQL statements that you manually run using the AWS CLI or APIs.

*Data manipulation language* (DML) is the set of PartiQL statements that you use to manage data in DynamoDB tables. You use DML statements to add, modify, or delete data in a table.

The following DML and query language statements are supported:

- [PartiQL select statements for DynamoDB \(p. 474\)](#)
- [PartiQL update statements for DynamoDB \(p. 477\)](#)
- [PartiQL insert statements for DynamoDB \(p. 481\)](#)
- [PartiQL delete statements for DynamoDB \(p. 480\)](#)

Performing transactions with [PartiQL for DynamoDB \(p. 487\)](#) and [Running batch operations with PartiQL for DynamoDB \(p. 491\)](#) are also supported by PartiQL for DynamoDB.

## PartiQL select statements for DynamoDB

Use the `SELECT` statement to retrieve data from a table in Amazon DynamoDB.

Using the `SELECT` statement can result in a full table scan if an equality condition with a partition key is not provided in the `WHERE` clause. A scan operation examines every item for the requested values and can use up the provisioned throughput for a large table or index in a single operation.

If you want to avoid full table scan in PartiQL, you can:

- Author your `SELECT` statements to not result in full table scans by making sure your [WHERE clause condition](#) is configured accordingly.
- Disable full table scans using the IAM policy specified at [Example: Allow select statements and deny full table scan statements in PartiQL for DynamoDB \(p. 496\)](#), in the DynamoDB developer guide.

For more information see [Best practices for querying and scanning data](#), in the DynamoDB developer guide.

### Topics

- [Syntax \(p. 475\)](#)
- [Parameters \(p. 475\)](#)
- [Examples \(p. 476\)](#)

## Syntax

```
SELECT expression [, ...]
FROM table[.index]
[ WHERE condition ] [ [ORDER BY key [DESC|ASC] , ...]
```

## Parameters

### *expression*

(Required) A projection formed from the \* wildcard or a projection list of one or more attribute names or document paths from the result set. An expression can consist of calls to [Use PartiQL functions with Amazon DynamoDB \(p. 482\)](#) or fields that are modified by [PartiQL arithmetic, comparison, and logical operators for DynamoDB \(p. 486\)](#).

### *table*

(Required) The table name to query.

### *index*

(Optional) The name of the index to query.

#### Note

You must add double quotation marks to the table name and index name when querying an index.

```
SELECT *
FROM "TableName"."IndexName"
```

### *condition*

(Optional) The selection criteria for the query.

#### Important

To ensure that a SELECT statement does not result in a full table scan, the WHERE clause condition must specify a partition key. Use the equality or IN operator.

For example, if you have an Orders table with an OrderID partition key and other non-key attributes, including an Address, the following statements would not result in a full table scan:

```
SELECT *
FROM "Orders"
WHERE OrderID = 100

SELECT *
FROM "Orders"
WHERE OrderID = 100 and Address='some address'

SELECT *
FROM "Orders"
WHERE OrderID = 100 or pk = 200

SELECT *
FROM "Orders"
WHERE OrderID IN [100, 300, 234]
```

The following SELECT statements, however, will result in a full table scan:

```
SELECT *
```

```

FROM "Orders"
WHERE OrderID > 1

SELECT *
FROM "Orders"
WHERE Address='some address'

SELECT *
FROM "Orders"
WHERE OrderID = 100 OR Address='some address'

```

### **key**

(Optional) A hash key or a sort key to use to order returned results. The default order is ascending (ASC) specify DESC if you want the results retuned in descending order.

### **Note**

If you omit the WHERE clause, then all of the items in the table are retrieved.

### **Examples**

The following query returns one item, if one exists, from the Orders table by specifying the partition key, OrderID, and using the equality operator.

```

SELECT OrderID, Total
FROM "Orders"
WHERE OrderID = 1

```

The following query returns all items in the Orders table that have a specific partition key, OrderID, values using the OR operator.

```

SELECT OrderID, Total
FROM "Orders"
WHERE OrderID = 1 OR OrderID = 2

```

The following query returns all items in the Orders table that have a specific partition key, OrderID, values using the IN operator. The returned results are in descending order, based on the OrderID key attribute value.

```

SELECT OrderID, Total
FROM "Orders"
WHERE OrderID IN [1, 2, 3] ORDER BY OrderID DESC

```

The following query shows a full table scan that returns all items from the Orders table that have a Total greater than 500, where Total is a non-key attribute.

```

SELECT OrderID, Total
FROM "Orders"
WHERE Total > 500

```

The following query shows a full table scan that returns all items from the Orders table within a specific Total order range, using the IN operator and a non-key attribute Total.

```

SELECT OrderID, Total
FROM "Orders"

```

```
WHERE Total IN [500, 600]
```

The following query shows a full table scan that returns all items from the `Orders` table within a specific `Total` order range, using the `BETWEEN` operator and a non-key attribute `Total`.

```
SELECT OrderID, Total
FROM "Orders"
WHERE Total BETWEEN 500 AND 600
```

The following query returns the first date a firestick device was used to watch by specifying the partition key `CustomerID` and sort key `MovieID` in the `WHERE` clause condition and using document paths in the `SELECT` clause.

```
SELECT Devices.FireStick.DateWatched[0]
FROM WatchList
WHERE CustomerID= 'C1' AND MovieID= 'M1'
```

The following query shows a full table scan that returns the list of items where a firestick device was first used after 12/12/19 using document paths in the `WHERE` clause condition.

```
SELECT Devices
FROM WatchList
WHERE Devices.FireStick.DateWatched[0] >= '12/12/19'
```

## PartiQL update statements for DynamoDB

Use the `UPDATE` statement to modify the value of one or more attributes within an item in an Amazon DynamoDB table.

### Note

You can only update one item at a time; you cannot issue a single DynamoDB PartiQL statement that updates multiple items. For information on updating multiple items, see [Performing transactions with PartiQL for DynamoDB \(p. 487\)](#) or [Running batch operations with PartiQL for DynamoDB \(p. 491\)](#).

### Topics

- [Syntax \(p. 477\)](#)
- [Parameters \(p. 477\)](#)
- [Return value \(p. 478\)](#)
- [Examples \(p. 478\)](#)

### Syntax

```
UPDATE table
[SET | REMOVE] path [= data] [...]
WHERE condition [RETURNING returnvalues]
<i></i><returnvalues> ::= [ALL OLD | MODIFIED OLD | ALL NEW | MODIFIED NEW] *
```

### Parameters

#### *table*

(Required) The table containing the data to be modified.

**path**

(Required) An attribute name or document path to be created or modified.

**data**

(Required) An attribute value or the result of an operation.

The supported operations to use with SET:

- LIST\_APPEND: adds a value to a list type.
- SET\_ADD: adds a value to a number or string set.
- SET\_DELETE: removes a value from a number or string set.

**condition**

(Required) The selection criteria for the item to be modified. This condition must resolve to a single primary key value.

**returnvalues**

(Optional) Use `returnvalues` if you want to get the item attributes as they appear before or after they are updated. The valid values are:

- ALL OLD \* - Returns all of the attributes of the item, as they appeared before the update operation.
- MODIFIED OLD \* - Returns only the updated attributes, as they appeared before the update operation.
- ALL NEW \* - Returns all of the attributes of the item, as they appear after the update operation.
- MODIFIED NEW \* - Returns only the updated attributes, as they appear after the `UpdateItem` operation.

**Return value**

This statement does not return a value unless `returnvalues` parameter is specified.

**Note**

If the WHERE clause of the UPDATE statement does not evaluate to true for any item in the DynamoDB table, `ConditionalCheckFailedException` is returned.

**Examples**

Update an attribute value in an existing item. If the attribute does not exist, it is created.

The following query updates an item in the "Music" table by adding an attribute of type number (`AwardsWon`) and an attribute of type map (`AwardDetail`).

```
UPDATE "Music"
SET AwardsWon=1
SET AwardDetail={'Grammys':[2020, 2018]}
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
```

You can add `RETURNING ALL OLD *` to return the attributes as they appeared before the `Update` operation.

```
UPDATE "Music"
SET AwardsWon=1
SET AwardDetail={'Grammys':[2020, 2018]}
```

```
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
RETURNING ALL OLD *
```

This returns the following:

```
{
  "Items": [
    {
      "Artist": {
        "S": "Acme Band"
      },
      "SongTitle": {
        "S": "PartiQL Rocks"
      }
    }
  ]
}
```

You can add RETURNING ALL NEW \* to return the attributes as they appeared after the Update operation.

```
UPDATE "Music"
SET AwardsWon=1
SET AwardDetail={'Grammys':[2020, 2018]}
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
RETURNING ALL NEW *
```

This returns the following:

```
{
  "Items": [
    {
      "AwardDetail": {
        "M": {
          "Grammys": {
            "L": [
              {
                "N": "2020"
              },
              {
                "N": "2018"
              }
            ]
          }
        },
        "AwardsWon": {
          "N": "1"
        }
      }
    ]
}
```

The following query updates an item in the "Music" table by appending to a list `AwardDetail.Grammys`.

```
UPDATE "Music"
SET AwardDetail.Grammys =list_append(AwardDetail.Grammys,[2016])
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
```

The following query updates an item in the "Music" table by removing from a list `AwardDetail.Grammys`.

```
UPDATE "Music"
REMOVE AwardDetail.Grammys[2]
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
```

The following query updates an item in the "Music" table by adding `BillBoard` to the map `AwardDetail`.

```
UPDATE "Music"
SET AwardDetail.BillBoard=[2020]
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
```

The following query updates an item in the "Music" table by adding the string set attribute `BandMembers`.

```
UPDATE "Music"
SET BandMembers =<<'member1', 'member2'>>
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
```

The following query updates an item in the "Music" table by adding `newbandmember` to the string set `BandMembers`.

```
UPDATE "Music"
SET BandMembers =set_add(BandMembers, <<'newbandmember'>>)
WHERE Artist='Acme Band' AND SongTitle='PartiQL Rocks'
```

## PartiQL delete statements for DynamoDB

Use the `DELETE` statement to delete an existing item from your Amazon DynamoDB table.

### Note

You can only delete one item at a time. You cannot issue a single DynamoDB PartiQL statement that deletes multiple items. For information on deleting multiple items, see [Performing transactions with PartiQL for DynamoDB \(p. 487\)](#) or [Running batch operations with PartiQL for DynamoDB \(p. 491\)](#).

### Topics

- [Syntax \(p. 480\)](#)
- [Parameters \(p. 480\)](#)
- [Return value \(p. 481\)](#)
- [Examples \(p. 481\)](#)

### Syntax

```
DELETE FROM table
WHERE condition [RETURNING returnvalues]
<returnvalues> ::= ALL OLD *
```

### Parameters

#### *table*

(Required) The DynamoDB table containing the item to be deleted.

**condition**

(Required) The selection criteria for the item to be deleted; this condition must resolve to a single primary key value.

**returnvalues**

(Optional) Use `returnvalues` if you want to get the item attributes as they appeared before they were deleted. The valid values are:

- `ALL OLD *` - The content of the old item is returned.

## Return value

This statement does not return a value unless `returnvalues` parameter is specified.

**Note**

If the DynamoDB table does not have any item with the same primary key as that of the item for which the `DELETE` is issued, `SUCCESS` is returned with 0 items deleted. If the table has an item with same primary key, but the condition in the `WHERE` clause of the `DELETE` statement evaluates to false, `ConditionalCheckFailedException` is returned.

## Examples

The following query deletes an item in the "Music" table.

```
DELETE FROM "Music" WHERE "Artist" = 'Acme Band' AND "SongTitle" = 'PartiQL Rocks'
```

You can add the parameter `RETURNING ALL OLD *` to return the data that was deleted.

```
DELETE FROM "Music" WHERE "Artist" = 'Acme Band' AND "SongTitle" = 'PartiQL Rocks'  
RETURNING ALL OLD *
```

The `Delete` statement now returns the following:

```
{  
  "Items": [  
    {  
      "Artist": {  
        "S": "Acme Band"  
      },  
      "SongTitle": {  
        "S": "PartiQL Rocks"  
      }  
    }  
  ]  
}
```

## PartiQL insert statements for DynamoDB

Use the `INSERT` statement to add an item to a table in Amazon DynamoDB.

**Note**

You can only insert one item at a time; you cannot issue a single DynamoDB PartiQL statement that inserts multiple items. For information on inserting multiple items, see [Performing transactions with PartiQL for DynamoDB \(p. 487\)](#) or [Running batch operations with PartiQL for DynamoDB \(p. 491\)](#).

## Topics

- [Syntax \(p. 482\)](#)
- [Parameters \(p. 482\)](#)
- [Return value \(p. 482\)](#)
- [Examples \(p. 482\)](#)

## Syntax

Insert a single item.

```
INSERT INTO table VALUE item
```

## Parameters

**table**

(Required) The table where you want to insert the data. The table must already exist.

**item**

(Required) A valid DynamoDB item represented as a [PartiQL tuple](#). You must specify only *one* item and each attribute name in the item is case-sensitive and can be denoted with *single* quotation marks (' . . . ') in PartiQL.

String values are also denoted with *single* quotation marks (' . . . ') in PartiQL.

## Return value

This statement does not return any values.

### Note

If the DynamoDB table already has an item with the same primary key as the primary key of the item being inserted, `DuplicateItemException` is returned.

## Examples

```
INSERT INTO "Music" value {'Artist' : 'Acme Band', 'SongTitle' : 'PartiQL Rocks'}
```

## Use PartiQL functions with amazon DynamoDB

PartiQL in Amazon DynamoDB supports the following built-in variants of SQL standard functions.

### Note

Any SQL functions that are not included in this list are not currently supported in DynamoDB.

## Aggregate functions

- [Using the SIZE function with PartiQL for amazon DynamoDB \(p. 485\)](#)

## Conditional functions

- [Using the EXISTS function with PartiQL for DynamoDB \(p. 483\)](#)
- [Using the ATTRIBUTE\\_TYPE function with PartiQL for DynamoDB \(p. 484\)](#)

- Using the `BEGINS_WITH` function with PartiQL for DynamoDB (p. 483)
- Using the `CONTAINS` function with PartiQL for DynamoDB (p. 485)
- Using the `MISSING` function with PartiQL for DynamoDB (p. 484)

## Using the `EXISTS` function with PartiQL for DynamoDB

You can use `EXISTS` to perform the same function as `ConditionCheck` does in the `TransactWriteItems` API. The `EXISTS` function can only be used in transactions.

Given a value, returns `TRUE` if the value is a non-empty collection. Otherwise, returns `FALSE`.

### Note

This function can only be used in transactional operations.

### Syntax

```
EXISTS ( statement )
```

### Arguments

#### *statement*

(Required) The `SELECT` statement that the function evaluates.

### Note

The `SELECT` statement must specify a full primary key and one other condition.

### Return type

`bool`

### Examples

```
EXISTS(
    SELECT * FROM "Music"
    WHERE "Artist" = 'Acme Band' AND "SongTitle" = 'PartiQL Rocks')
```

## Using the `BEGINS_WITH` function with PartiQL for DynamoDB

Returns `TRUE` if the attribute specified begins with a particular substring.

### Syntax

```
begins_with(path, value )
```

### Arguments

#### *path*

(Required) The attribute name or document path to use.

#### *value*

(Required) The string to search for.

## Return type

bool

## Examples

```
SELECT * FROM "Orders" WHERE "OrderID"=1 AND begins_with("Address", '7834 24th')
```

## Using the MISSING function with PartiQL for DynamoDB

Returns TRUE if the item does not contain the attribute specified. Only equality and inequality operators can be used with this function.

## Syntax

```
attributename IS | IS NOT MISSING
```

## Arguments

*attributename*

(Required) The attribute name to look for.

## Return type

bool

## Examples

```
SELECT * FROM Music WHERE "Awards" is MISSING
```

## Using the ATTRIBUTE\_TYPE function with PartiQL for DynamoDB

Returns TRUE if the attribute at the specified path is of a particular data type.

## Syntax

```
attribute_type( attributename, type )
```

## Arguments

*attributename*

(Required) The attribute name to use.

*type*

(Required) The attribute type to check for. For a list of valid values, see DynamoDB [attribute\\_type](#).

## Return type

bool

## Examples

```
SELECT * FROM "Music" WHERE attribute_type("Artist", 'S')
```

## Using the CONTAINS function with PartiQL for DynamoDB

Returns `TRUE` if the attribute specified by the path is one of the following:

- A String that contains a particular substring.
- A Set that contains a particular element within the set.

For more information, see the DynamoDB [contains](#) function.

### Syntax

```
contains( path, substring )
```

### Arguments

*path*

(Required) The attribute name or document path to use.

*substring*

(Required) The attribute substring or set member to check for. For more information, see the DynamoDB [contains](#) function.

### Return type

`bool`

## Examples

```
SELECT * FROM "Orders" WHERE "OrderID"=1 AND contains("Address", 'Kirkland')
```

## Using the SIZE function with PartiQL for amazon DynamoDB

Returns a number representing an attribute's size in bytes. The following are valid data types for use with size. For more information, see the DynamoDB [size](#) function.

### Syntax

```
size( path )
```

### Arguments

*path*

(Required) The attribute name or document path.

For supported types, see DynamoDB [size](#) function.

### Return type

int

### Examples

```
SELECT * FROM "Orders" WHERE "OrderID"=1 AND size("Image") >300
```

## PartiQL arithmetic, comparison, and logical operators for DynamoDB

PartiQL in Amazon DynamoDB supports the following [SQL standard operators](#).

#### Note

Any SQL operators that are not included in this list are not currently supported in DynamoDB.

### Arithmetic operators

Operator	Description
+	Add
-	Subtract

### Comparison operators

Operator	Description
=	Equal to
<>	Not Equal to
>	Greater than
<	Less than
>=	Greater than or equal to
<=	Less than or equal to

### Logical operators

Operator	Description
AND	TRUE if all the conditions separated by AND are TRUE
BETWEEN	TRUE if the operand is within the range of comparisons
IN	TRUE if the operand is equal to one of a list of expressions (at max 50 hash attribute values or at max 100 non-key attribute values)

Operator	Description
IS	TRUE if the operand is a given, PartiQL data type, including NULL or MISSING
NOT	Reverses the value of a given Boolean expression
OR	TRUE if any of the conditions separated by OR are TRUE

## Performing transactions with PartiQL for DynamoDB

This section describes how to use transactions with PartiQL for DynamoDB.

For more information on DynamoDB transactions, see [Managing complex workflows with DynamoDB transactions](#).

**Note**

The entire transaction must consist of either read statements or write statements. You can't mix both in one transaction. The EXISTS function is an exception. You can use it to check the condition of specific attributes of the item in a similar manner to ConditionCheck in the [TransactWriteItems](#) API operation.

**Topics**

- [Syntax \(p. 487\)](#)
- [Parameters \(p. 487\)](#)
- [Return values \(p. 488\)](#)
- [Examples \(p. 488\)](#)

## Syntax

```
[  
  {  
    "Statement": " statement ",  
    "Parameters": [  
      {  
        " parametertype " : " parametervalue "  
      }, ...]  
    ], ...  
]
```

## Parameters

***statement***

(Required) A PartiQL for DynamoDB supported statement.

**Note**

The entire transaction must consist of either read statements or write statements. You can't mix both in one transaction.

***parametertype***

(Optional) A DynamoDB type, if parameters were used when specifying the PartiQL statement.

***parametervalue***

(Optional) A parameter value if parameters were used when specifying the PartiQL statement.

## Return values

This statement doesn't return any values for Write operations (INSERT, UPDATE, or DELETE). However, it returns different values for Read operations (SELECT) based on the conditions specified in the WHERE clause.

### Note

If any of the singleton INSERT, UPDATE, or DELETE operations return an error, the transactions are canceled with the `TransactionCanceledException` exception, and the cancellation reason code includes the errors from the individual singleton operations.

## Examples

The following example runs multiple statements as a transaction.

### AWS CLI

1. Save the following JSON code to a file called `partiql.json`.

```
[  
  {  
    "Statement": "EXISTS(SELECT * FROM \"Music\" where Artist='No One You Know'  
    and SongTitle='Call Me Today' and Awards is MISSING)"  
  },  
  {  
    "Statement": "INSERT INTO Music value {'Artist':?:,'SongTitle':'?'},  
    "Parameters": [{"S": "Acme Band"}, {"S": "Best Song"}]  
  },  
  {  
    "Statement": "UPDATE \"Music\" SET AwardsWon=1 SET AwardDetail={'Grammys':  
    [2020, 2018]} where Artist='Acme Band' and SongTitle='PartiQL Rocks'"  
  }  
]
```

2. Run the following command in a command prompt.

```
aws dynamodb execute-transaction --transact-statements file://partiql.json
```

### Java

```
public class DynamoDBPartiqlTransaction {  
  
    public static void main(String[] args) {  
        // Create the DynamoDB Client with the region you want  
        AmazonDynamoDB dynamoDB = createDynamoDbClient("us-west-2");  
  
        try {  
            // Create ExecuteTransactionRequest  
            ExecuteTransactionRequest executeTransactionRequest =  
            createExecuteTransactionRequest();  
            ExecuteTransactionResult executeTransactionResult =  
            dynamoDB.executeTransaction(executeTransactionRequest);  
            System.out.println("ExecuteTransaction successful.");  
            // Handle executeTransactionResult  
  
        } catch (Exception e) {  
            handleExecuteTransactionErrors(e);  
        }  
    }  
}
```

```

private static AmazonDynamoDB createDynamoDbClient(String region) {
    return AmazonDynamoDBClientBuilder.standard().withRegion(region).build();
}

private static ExecuteTransactionRequest createExecuteTransactionRequest() {
    ExecuteTransactionRequest request = new ExecuteTransactionRequest();

    // Create statements
    List<ParameterizedStatement> statements = getPartiQLTransactionStatements();

    request.setTransactStatements(statements);
    return request;
}

private static List<ParameterizedStatement> getPartiQLTransactionStatements() {
    List<ParameterizedStatement> statements = new
    ArrayList<ParameterizedStatement>();

    statements.add(new ParameterizedStatement()
        .withStatement("EXISTS(SELECT * FROM "Music" where
Artist='No One You Know' and SongTitle='Call Me Today' and Awards is MISSING")));

    statements.add(new ParameterizedStatement()
        .withStatement("INSERT INTO "Music" value
{'Artist':'?', 'SongTitle':'?'})
        .withParameters(new AttributeValue("Acme Band"),new
AttributeValue("Best Song")));

    statements.add(new ParameterizedStatement()
        .withStatement("UPDATE "Music" SET AwardsWon=1 SET
AwardDetail={'Grammys':[2020, 2018]} where Artist='Acme Band' and SongTitle='PartiQL
Rocks'"));

    return statements;
}

// Handles errors during ExecuteTransaction execution. Use recommendations in error
messages below to add error handling specific to
// your application use-case.
private static void handleExecuteTransactionErrors(Exception exception) {
    try {
        throw exception;
    } catch (TransactionCanceledException tce) {
        System.out.println("Transaction Cancelled, implies a client issue, fix
before retrying. Error: " + tce.getErrorMessage());
    } catch (TransactionInProgressException tipe) {
        System.out.println("The transaction with the given request token is already
in progress, consider changing " +
            "retry strategy for this type of error. Error: " +
            tipe.getErrorMessage());
    } catch (IdempotentParameterMismatchException ipme) {
        System.out.println("Request rejected because it was retried with a
different payload but with a request token that was already used, " +
            "change request token for this payload to be accepted. Error: " +
            ipme.getErrorMessage());
    } catch (Exception e) {
        handleCommonErrors(e);
    }
}

private static void handleCommonErrors(Exception exception) {
    try {
        throw exception;
    } catch (InternalServerErrorException isee) {
        System.out.println("Internal Server Error, generally safe to retry with
exponential back-off. Error: " + isee.getErrorMessage());
}

```

```

        } catch (RequestLimitExceededException rlee) {
            System.out.println("Throughput exceeds the current throughput limit for
your account, increase account level throughput before " +
"retrying. Error: " + rlee.getErrorMessage());
        } catch (ProvisionedThroughputExceededException ptee) {
            System.out.println("Request rate is too high. If you're using a custom
retry strategy make sure to retry with exponential back-off. " +
"Otherwise consider reducing frequency of requests or increasing
provisioned capacity for your table or secondary index. Error: " +
ptee.getErrorMessage());
        } catch (ResourceNotFoundException rnfe) {
            System.out.println("One of the tables was not found, verify table exists
before retrying. Error: " + rnfe.getErrorMessage());
        } catch (AmazonServiceException ase) {
            System.out.println("An AmazonServiceException occurred, indicates that the
request was correctly transmitted to the DynamoDB " +
"service, but for some reason, the service was not able to process it,
and returned an error response instead. Investigate and " +
"configure retry strategy. Error type: " + ase.getErrorType() + ".
Error message: " + ase.getMessage());
        } catch (AmazonClientException ace) {
            System.out.println("An AmazonClientException occurred, indicates that the
client was unable to get a response from DynamoDB " +
"service, or the client was unable to parse the response from the
service. Investigate and configure retry strategy. " +
"Error: " + ace.getMessage());
        } catch (Exception e) {
            System.out.println("An exception occurred, investigate and configure retry
strategy. Error: " + e.getMessage());
        }
    }
}

```

The following example shows the different return values when DynamoDB reads items with different conditions specified in the WHERE clause.

#### AWS CLI

1. Save the following JSON code to a file called `partiql.json`.

```

[
    // Item exists and projected attribute exists
    {
        "Statement": "SELECT * FROM \"Music\" WHERE Artist='No One You Know' and
SongTitle='Call Me Today'"
    },
    // Item exists but projected attributes do not exist
    {
        "Statement": "SELECT non_existent_projected_attribute FROM \"Music\" WHERE
Artist='No One You Know' and SongTitle='Call Me Today'"
    },
    // Item does not exist
    {
        "Statement": "SELECT * FROM \"Music\" WHERE Artist='No One I Know' and
SongTitle='Call You Today'"
    }
]

```

2. following command in a command prompt.

```
aws dynamodb execute-transaction --transact-statements file://partiql.json
```

3. The following response is returned:

```
{
    "Responses": [
        // Item exists and projected attribute exists
        {
            "Item": {
                "Artist": {
                    "S": "No One You Know"
                },
                "SongTitle": {
                    "S": "Call Me Today"
                }
            }
        },
        // Item exists but projected attributes do not exist
        {
            "Item": {}
        },
        // Item does not exist
        {}
    ]
}
```

## Running batch operations with PartiQL for DynamoDB

This section describes how to use batch statements with PartiQL for DynamoDB.

### Note

- The entire batch must consist of either read statements or write statements; you cannot mix both in one batch.
- `BatchExecuteStatement` and `BatchWriteItem` can perform no more than 25 statements per batch.

### Topics

- [Syntax \(p. 491\)](#)
- [Parameters \(p. 491\)](#)
- [Examples \(p. 492\)](#)

## Syntax

```
[
    {
        "Statement": "statement ",
        "Parameters": [
            {
                "parametername": "parametertype : parametervalue "
            }, ...
        ]
    }, ...
]
```

## Parameters

### *statement*

(Required) A PartiQL for DynamoDB supported statement.

### Note

- The entire batch must consist of either read statements or write statements; you cannot mix both in one batch.
- `BatchExecuteStatement` and `BatchWriteItem` can perform no more than 25 statements per batch.

#### *parametertype*

(Optional) A DynamoDB type, if parameters were used when specifying the PartiQL statement.

#### *parametervalue*

(Optional) A parameter value if parameters were used when specifying the PartiQL statement.

## Examples

### AWS CLI

1. Save the following json to a file called `partiql.json`

```
[  
  {  
    "Statement": "INSERT INTO \"Music\" value {'Artist':'?', 'SongTitle':'?'}",  
    "Parameters": [{"S": "Acme Band"}, {"S": "Best Song"}]  
  },  
  {  
    "Statement": "UPDATE \"Music\" SET AwardsWon=1 SET AwardDetail={'Grammys':  
[2020, 2018]} where Artist='Acme Band' and SongTitle='PartiQL Rocks'"  
  }  
]
```

2. Run the following command in a command prompt.

```
aws dynamodb batch-execute-statement --statements file://partiql.json
```

### Java

```
public class DynamoDBPartiqlBatch {  
  
    public static void main(String[] args) {  
        // Create the DynamoDB Client with the region you want  
        AmazonDynamoDB dynamoDB = createDynamoDbClient("us-west-2");  
  
        try {  
            // Create BatchExecuteStatementRequest  
            BatchExecuteStatementRequest batchExecuteStatementRequest =  
createBatchExecuteStatementRequest();  
            BatchExecuteStatementResult batchExecuteStatementResult =  
dynamoDB.batchExecuteStatement(batchExecuteStatementRequest);  
            System.out.println("BatchExecuteStatement successful.");  
            // Handle batchExecuteStatementResult  
  
        } catch (Exception e) {  
            handleBatchExecuteStatementErrors(e);  
        }  
    }  
  
    private static AmazonDynamoDB createDynamoDbClient(String region) {
```

```

        return AmazonDynamoDBClientBuilder.standard().withRegion(region).build();
    }

    private static BatchExecuteStatementRequest createBatchExecuteStatementRequest() {
        BatchExecuteStatementRequest request = new BatchExecuteStatementRequest();

        // Create statements
        List<BatchStatementRequest> statements = getPartiQLBatchStatements();

        request.setStatements(statements);
        return request;
    }

    private static List<BatchStatementRequest> getPartiQLBatchStatements() {
        List<BatchStatementRequest> statements = new
        ArrayList<BatchStatementRequest>();

        statements.add(new BatchStatementRequest()
                        .withStatement("INSERT INTO "Music" value
{'Artist':'Acme Band','SongTitle':'PartiQL Rocks'}"));

        statements.add(new BatchStatementRequest()
                        .withStatement("UPDATE "Music" set
AwardDetail.BillBoard=[2020] where Artist='Acme Band' and SongTitle='PartiQL
Rocks'"));

        return statements;
    }

    // Handles errors during BatchExecuteStatement execution. Use recommendations in
    error messages below to add error handling specific to
    // your application use-case.
    private static void handleBatchExecuteStatementErrors(Exception exception) {
        try {
            throw exception;
        } catch (Exception e) {
            // There are no API specific errors to handle for BatchExecuteStatement,
            common DynamoDB API errors are handled below
            handleCommonErrors(e);
        }
    }

    private static void handleCommonErrors(Exception exception) {
        try {
            throw exception;
        } catch (InternalServerErrorException isee) {
            System.out.println("Internal Server Error, generally safe to retry with
            exponential back-off. Error: " + isee.getErrorMessage());
        } catch (RequestLimitExceededException rlee) {
            System.out.println("Throughput exceeds the current throughput limit for
            your account, increase account level throughput before " +
                "retrying. Error: " + rlee.getErrorMessage());
        } catch (ProvisionedThroughputExceededException ptee) {
            System.out.println("Request rate is too high. If you're using a custom
            retry strategy make sure to retry with exponential back-off. " +
                "Otherwise consider reducing frequency of requests or increasing
            provisioned capacity for your table or secondary index. Error: " +
                ptee.getErrorMessage());
        } catch (ResourceNotFoundException rnfe) {
            System.out.println("One of the tables was not found, verify table exists
            before retrying. Error: " + rnfe.getErrorMessage());
        } catch (AmazonServiceException ase) {
            System.out.println("An AmazonServiceException occurred, indicates that the
            request was correctly transmitted to the DynamoDB " +
                "service, but for some reason, the service was not able to process it,
            and returned an error response instead. Investigate and " +

```

```
        "configure retry strategy. Error type: " + ase.getErrorType() + ".  
Error message: " + ase.getErrorMessage());  
    } catch (AmazonClientException ace) {  
        System.out.println("An AmazonClientException occurred, indicates that the  
client was unable to get a response from DynamoDB " +  
                "service, or the client was unable to parse the response from the  
service. Investigate and configure retry strategy. "+  
                "Error: " + ace.getMessage());  
    } catch (Exception e) {  
        System.out.println("An exception occurred, investigate and configure retry  
strategy. Error: " + e.getMessage());  
    }  
}
```

## IAM security policies with PartiQL for DynamoDB

The following permissions are required:

- To read items using PartiQL for DynamoDB, you must have dynamodb:PartiQLSelect permission on the table or index.
  - To insert items using PartiQL for DynamoDB, you must have dynamodb:PartiQLInsert permission on the table or index.
  - To update items using PartiQL for DynamoDB, you must have dynamodb:PartiQLUpdate permission on the table or index.
  - To delete items using PartiQL for DynamoDB, you must have dynamodb:PartiQLDelete permission on the table or index.

Example: Allow all PartiQL for DynamoDB statements (Select/Insert/Update/Delete) on a table

The following IAM policy grants permissions to run all PartiQL for DynamoDB statements on a table.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                "dynamodb:PartiQLInsert",
                "dynamodb:PartiQLUpdate",
                "dynamodb:PartiQLDelete",
                "dynamodb:PartiQLSelect"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
            ]
        }
    ]
}
```

## Example: Allow PartiQL for DynamoDB select statements on a table

The following IAM policy grants permissions to run the `select` statement on a specific table.

{

```

    "Version":"2012-10-17",
    "Statement":[
        {
            "Effect":"Allow",
            "Action":[
                "dynamodb:PartiQLSelect"
            ],
            "Resource":[
                "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
            ]
        }
    ]
}

```

## Example: Allow PartiQL for DynamoDB insert statements on an index

The following IAM policy grants permissions to run the `insert` statement on a specific index.

```

{
    "Version":"2012-10-17",
    "Statement":[
        {
            "Effect":"Allow",
            "Action":[
                "dynamodb:PartiQLInsert"
            ],
            "Resource":[
                "arn:aws:dynamodb:us-west-2:123456789012:table/Music/index/index1"
            ]
        }
    ]
}

```

## Example: Allow PartiQL for DynamoDB transactional statements only on a table

The following IAM policy grants permissions to run only transactional statements on a specific table.

```

{
    "Version":"2012-10-17",
    "Statement":[
        {
            "Effect":"Allow",
            "Action":[
                "dynamodb:PartiQLInsert",
                "dynamodb:PartiQLUpdate",
                "dynamodb:PartiQLDelete",
                "dynamodb:PartiQLSelect"
            ],
            "Resource":[
                "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
            ],
            "Condition": {
                "StringEquals": {
                    "dynamodb:EnclosingOperation": [
                        "ExecuteTransaction"
                    ]
                }
            }
        }
    ]
}

```

## Example: Allow PartiQL for DynamoDB non-transactional reads and writes and block PartiQL transactional reads and writes transactional statements on a table.

The following IAM policy grants permissions to run PartiQL for DynamoDB non-transactional reads and writes while blocking PartiQL for DynamoDB transactional reads and writes.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Deny",
            "Action": [
                "dynamodb:PartiQLInsert",
                "dynamodb:PartiQLUpdate",
                "dynamodb:PartiQLDelete",
                "dynamodb:PartiQLSelect"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
            ],
            "Condition": {
                "StringEquals": {
                    "dynamodb:EnclosingOperation": [
                        "ExecuteTransaction"
                    ]
                }
            }
        },
        {
            "Effect": "Allow",
            "Action": [
                "dynamodb:PartiQLInsert",
                "dynamodb:PartiQLUpdate",
                "dynamodb:PartiQLDelete",
                "dynamodb:PartiQLSelect"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
            ]
        }
    ]
}
```

## Example: Allow select statements and deny full table scan statements in PartiQL for DynamoDB

The following IAM policy grants permissions to run the `select` statement on a specific table while blocking `select` statements that result in a full table scan.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Deny",
            "Action": [
                "dynamodb:PartiQLSelect"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/WatchList"
            ],

```

```
    "Condition": {
        "Bool": {
            "dynamodb:FullTableScan": [
                "true"
            ]
        }
    },
    {
        "Effect": "Allow",
        "Action": [
            "dynamodb:PartialUpdateItem"
        ],
        "Resource": [
            "arn:aws:dynamodb:us-west-2:123456789012:table/WatchList"
        ]
    }
}
```

## Improving data access with secondary indexes

### Topics

- [Using Global Secondary Indexes in DynamoDB \(p. 500\)](#)
- [Local Secondary Indexes \(p. 539\)](#)

Amazon DynamoDB provides fast access to items in a table by specifying primary key values. However, many applications might benefit from having one or more secondary (or alternate) keys available, to allow efficient access to data with attributes other than the primary key. To address this, you can create one or more secondary indexes on a table and issue `Query` or `Scan` requests against these indexes.

A *secondary index* is a data structure that contains a subset of attributes from a table, along with an alternate key to support `Query` operations. You can retrieve data from the index using a `Query`, in much the same way as you use `Query` with a table. A table can have multiple secondary indexes, which give your applications access to many different query patterns.

### Note

You can also `Scan` an index, in much the same way as you would `Scan` a table.

Every secondary index is associated with exactly one table, from which it obtains its data. This is called the *base table* for the index. When you create an index, you define an alternate key for the index (partition key and sort key). You also define the attributes that you want to be *projected*, or copied, from the base table into the index. DynamoDB copies these attributes into the index, along with the primary key attributes from the base table. You can then query or scan the index just as you would query or scan a table.

Every secondary index is automatically maintained by DynamoDB. When you add, modify, or delete items in the base table, any indexes on that table are also updated to reflect these changes.

DynamoDB supports two types of secondary indexes:

- **Global secondary index** — An index with a partition key and a sort key that can be different from those on the base table. A global secondary index is considered "global" because queries on the index can span all of the data in the base table, across all partitions. A global secondary index is stored in its own partition space away from the base table and scales separately from the base table.
- **Local secondary index** — An index that has the same partition key as the base table, but a different sort key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a base table partition that has the same partition key value.

You should consider your application's requirements when you determine which type of index to use. The following table shows the main differences between a global secondary index and a local secondary index.

Characteristic	Global secondary index	Local secondary index
<b>Key Schema</b>	The primary key of a global secondary index can be either simple (partition key) or composite (partition key and sort key).	The primary key of a local secondary index must be composite (partition key and sort key).
<b>Key Attributes</b>	The index partition key and sort key (if present) can be any base table attributes of type string, number, or binary.	The partition key of the index is the same attribute as the partition key of the base table. The sort key can be any base table attribute of type string, number, or binary.
<b>Size Restrictions Per Partition Key Value</b>	There are no size restrictions for global secondary indexes.	For each partition key value, the total size of all indexed items must be 10 GB or less.
<b>Online Index Operations</b>	Global secondary indexes can be created at the same time that you create a table. You can also add a new global secondary index to an existing table, or delete an existing global secondary index. For more information, see <a href="#">Managing Global Secondary Indexes (p. 508)</a> .	Local secondary indexes are created at the same time that you create a table. You cannot add a local secondary index to an existing table, nor can you delete any local secondary indexes that currently exist.
<b>Queries and Partitions</b>	A global secondary index lets you query over the entire table, across all partitions.	A local secondary index lets you query over a single partition, as specified by the partition key value in the query.
<b>Read Consistency</b>	Queries on global secondary indexes support eventual consistency only.	When you query a local secondary index, you can choose either eventual consistency or strong consistency.
<b>Provisioned Throughput Consumption</b>	Every global secondary index has its own provisioned throughput settings for read and write activity. Queries or scans on a global secondary index consume capacity units from the index, not from the base table. The same holds true for global secondary index updates due to table writes.	Queries or scans on a local secondary index consume read capacity units from the base table. When you write to a table, its local secondary indexes are also updated; these updates consume write capacity units from the base table.
<b>Projected Attributes</b>	With global secondary index queries or scans, you can only request the attributes that	If you query or scan a local secondary index, you can request attributes that are

Characteristic	Global secondary index	Local secondary index
	are projected into the index. DynamoDB does not fetch any attributes from the table.	not projected in to the index. DynamoDB automatically fetches those attributes from the table.

If you want to create more than one table with secondary indexes, you must do so sequentially. For example, you would create the first table and wait for it to become `ACTIVE`, create the next table and wait for it to become `ACTIVE`, and so on. If you try to concurrently create more than one table with a secondary index, DynamoDB returns a `LimitExceededException`.

For each secondary index, you must specify the following:

- The type of index to be created – either a global secondary index or a local secondary index.
- A name for the index. The naming rules for indexes are the same as those for tables, as listed in [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#). The name must be unique for the base table it is associated with, but you can use the same name for indexes that are associated with different base tables.
- The key schema for the index. Every attribute in the index key schema must be a top-level attribute of type `String`, `Number`, or `Binary`. Other data types, including documents and sets, are not allowed. Other requirements for the key schema depend on the type of index:
  - For a global secondary index, the partition key can be any scalar attribute of the base table. A sort key is optional, and it too can be any scalar attribute of the base table.
  - For a local secondary index, the partition key must be the same as the base table's partition key, and the sort key must be a non-key base table attribute.
- Additional attributes, if any, to project from the base table into the index. These attributes are in addition to the table's key attributes, which are automatically projected into every index. You can project attributes of any data type, including scalars, documents, and sets.
- The provisioned throughput settings for the index, if necessary:
  - For a global secondary index, you must specify read and write capacity unit settings. These provisioned throughput settings are independent of the base table's settings.
  - For a local secondary index, you do not need to specify read and write capacity unit settings. Any read and write operations on a local secondary index draw from the provisioned throughput settings of its base table.

For maximum query flexibility, you can create up to 20 global secondary indexes (default quota) and up to 5 local secondary indexes per table.

The quota of global secondary indexes per table is five for the following AWS Regions:

- AWS GovCloud (US-East)
- AWS GovCloud (US-West)
- Europe (Stockholm)

To get a detailed listing of secondary indexes on a table, use the `DescribeTable` operation. `DescribeTable` returns the name, storage size, and item counts for every secondary index on the table. These values are not updated in real time, but they are refreshed approximately every six hours.

You can access the data in a secondary index using either the `Query` or `Scan` operation. You must specify the name of the base table and the name of the index that you want to use, the attributes to be returned in the results, and any condition expressions or filters that you want to apply. DynamoDB can return the results in ascending or descending order.

When you delete a table, all of the indexes associated with that table are also deleted.

For best practices, see [Best practices for using secondary indexes in DynamoDB \(p. 1171\)](#).

## Using Global Secondary Indexes in DynamoDB

Some applications might need to perform many kinds of queries, using a variety of different attributes as query criteria. To support these requirements, you can create one or more *global secondary indexes* and issue `Query` requests against these indexes in Amazon DynamoDB.

### Topics

- [Scenario: Using a Global Secondary Index \(p. 500\)](#)
- [Attribute projections \(p. 503\)](#)
- [Reading data from a Global Secondary Index \(p. 504\)](#)
- [Data synchronization between tables and Global Secondary Indexes \(p. 505\)](#)
- [Table classes with Global Secondary Index \(p. 506\)](#)
- [Provisioned throughput considerations for Global Secondary Indexes \(p. 506\)](#)
- [Storage considerations for Global Secondary Indexes \(p. 507\)](#)
- [Managing Global Secondary Indexes \(p. 508\)](#)
- [Working with Global Secondary Indexes: Java \(p. 520\)](#)
- [Working with Global Secondary Indexes: .NET \(p. 527\)](#)
- [Working with Global Secondary Indexes: AWS CLI \(p. 538\)](#)

## Scenario: Using a Global Secondary Index

To illustrate, consider a table named `GameScores` that tracks users and scores for a mobile gaming application. Each item in `GameScores` is identified by a partition key (`UserId`) and a sort key (`GameTitle`). The following diagram shows how the items in the table would be organized. (Not all of the attributes are shown.)

GameScores

UserId	GameTitle	TopScore	TopScoreDateTime	Wins	Losses	
"101"	"Galaxy Invaders"	5842	"2015-09-15:17:24:31"	21	72	...
"101"	"Meteor Blasters"	1000	"2015-10-22:23:18:01"	12	3	...
"101"	"Starship X"	24	"2015-08-31:13:14:21"	4	9	...
"102"	"Alien Adventure"	192	"2015-07-12:11:07:56"	32	192	...
"102"	"Galaxy Invaders"	0	"2015-09-18:07:33:42"	0	5	...
"103"	"Attack Ships"	3	"2015-10-19:01:13:24"	1	8	...
"103"	"Galaxy Invaders"	2317	"2015-09-11:06:53:00"	40	3	...
"103"	"Meteor Blasters"	723	"2015-10-19:01:13:24"	22	12	...
"103"	"Starship X"	42	"2015-07-11:06:53:00"	4	19	...
...	...	...	...	...	...	...

Now suppose that you wanted to write a leaderboard application to display top scores for each game. A query that specified the key attributes (`UserId` and `GameTitle`) would be very efficient. However, if the application needed to retrieve data from `GameScores` based on `GameTitle` only, it would need to use a `Scan` operation. As more items are added to the table, scans of all the data would become slow and inefficient. This makes it difficult to answer questions such as the following:

- What is the top score ever recorded for the game Meteor Blasters?
- Which user had the highest score for Galaxy Invaders?
- What was the highest ratio of wins vs. losses?

To speed up queries on non-key attributes, you can create a global secondary index. A global secondary index contains a selection of attributes from the base table, but they are organized by a primary key that is different from that of the table. The index key does not need to have any of the key attributes from the table. It doesn't even need to have the same key schema as a table.

For example, you could create a global secondary index named `GameTitleIndex`, with a partition key of `GameTitle` and a sort key of `TopScore`. The base table's primary key attributes are always projected into an index, so the `UserId` attribute is also present. The following diagram shows what `GameTitleIndex` index would look like.

## *GameTitleIndex*

<i>GameTitle</i>	<i>TopScore</i>	<i>UserId</i>
“Alien Adventure”	192	“102”
“Attack Ships”	3	“103”
“Galaxy Invaders”	0	“102”
“Galaxy Invaders”	2317	“103”
“Galaxy Invaders”	5842	“101”
“Meteor Blasters”	723	“103”
“Meteor Blasters”	1000	“101”
“Starship X”	24	“101”
“Starship X”	42	“103”

\*\*\*                    \*\*\*                    \*\*\*

Now you can query `GameTitleIndex` and easily obtain the scores for Meteor Blasters. The results are ordered by the sort key values, `TopScore`. If you set the `ScanIndexForward` parameter to `false`, the results are returned in descending order, so the highest score is returned first.

Every global secondary index must have a partition key, and can have an optional sort key. The index key schema can be different from the base table schema. You could have a table with a simple primary key (partition key), and create a global secondary index with a composite primary key (partition key and sort key)—or vice versa. The index key attributes can consist of any top-level `String`, `Number`, or `Binary` attributes from the base table. Other scalar types, document types, and set types are not allowed.

You can project other base table attributes into the index if you want. When you query the index, DynamoDB can retrieve these projected attributes efficiently. However, global secondary index queries cannot fetch attributes from the base table. For example, if you query `GameTitleIndex` as shown in the previous diagram, the query could not access any non-key attributes other than `TopScore` (although the key attributes `GameTitle` and `UserId` would automatically be projected).

In a DynamoDB table, each key value must be unique. However, the key values in a global secondary index do not need to be unique. To illustrate, suppose that a game named Comet Quest is especially difficult, with many new users trying but failing to get a score above zero. The following is some data that could represent this.

UserId	GameTitle	TopScore
123	Comet Quest	0
201	Comet Quest	0
301	Comet Quest	0

When this data is added to the `GameScores` table, DynamoDB propagates it to `GameTitleIndex`. If we then query the index using `Comet Quest` for `GameTitle` and `0` for `TopScore`, the following data is returned.

GameTitle	TopScore	UserId
“Comet Quest”	0	“123”
“Comet Quest”	0	“201”
“Comet Quest”	0	“301”

Only the items with the specified key values appear in the response. Within that set of data, the items are in no particular order.

A global secondary index only tracks data items where its key attributes actually exist. For example, suppose that you added another new item to the `GameScores` table, but only provided the required primary key attributes.

UserId	GameTitle
400	Comet Quest

Because you didn't specify the `TopScore` attribute, DynamoDB would not propagate this item to `GameTitleIndex`. Thus, if you queried `GameScores` for all the Comet Quest items, you would get the following four items.

UserId	GameTitle	TopScore
“123”	“Comet Quest”	0
“201”	“Comet Quest”	0
“301”	“Comet Quest”	0
“400”	“Comet Quest”	

A similar query on GameTitleIndex would still return three items, rather than four. This is because the item with the nonexistent TopScore is not propagated to the index.

GameTitle	TopScore	UserId
“Comet Quest”	0	“123”
“Comet Quest”	0	“201”
“Comet Quest”	0	“301”

## Attribute projections

A *projection* is the set of attributes that is copied from a table into a secondary index. The partition key and sort key of the table are always projected into the index; you can project other attributes to support your application's query requirements. When you query an index, Amazon DynamoDB can access any attribute in the projection as if those attributes were in a table of their own.

When you create a secondary index, you need to specify the attributes that will be projected into the index. DynamoDB provides three different options for this:

- *KEYS\_ONLY* – Each item in the index consists only of the table partition key and sort key values, plus the index key values. The *KEYS\_ONLY* option results in the smallest possible secondary index.
- *INCLUDE* – In addition to the attributes described in *KEYS\_ONLY*, the secondary index will include other non-key attributes that you specify.
- *ALL* – The secondary index includes all of the attributes from the source table. Because all of the table data is duplicated in the index, an *ALL* projection results in the largest possible secondary index.

In the previous diagram, GameTitleIndex has only one projected attribute: UserId. So while an application can efficiently determine the UserId of the top scorers for each game using GameTitle and TopScore in queries, it can't efficiently determine the highest ratio of wins vs. losses for the top scorers. To do so, it would have to perform an additional query on the base table to fetch the wins and losses for each of the top scorers. A more efficient way to support queries on this data would be to project these attributes from the base table into the global secondary index, as shown in this diagram.

## *GameTitleIndex*

<i>GameTitle</i>	<i>TopScore</i>	<i>UserId</i>	<i>Wins</i>	<i>Losses</i>
“Alien Adventure”	192	“102”	32	192
“Attack Ships”	3	“103”	1	8
“Galaxy Invaders”	0	“102”	0	5
“Galaxy Invaders”	2317	“103”	40	3
“Galaxy Invaders”	5842	“101”	21	72
“Meteor Blasters”	723	“103”	22	12
“Meteor Blasters”	1000	“101”	12	3
“Starship X”	24	“101”	4	9
“Starship X”	42	“103”	4	19
...	...	...	...	...

Because the non-key attributes *Wins* and *Losses* are projected into the index, an application can determine the wins vs. losses ratio for any game, or for any combination of game and user ID.

When you choose the attributes to project into a global secondary index, you must consider the tradeoff between provisioned throughput costs and storage costs:

- If you need to access just a few attributes with the lowest possible latency, consider projecting only those attributes into a global secondary index. The smaller the index, the less that it costs to store it, and the less your write costs are.
- If your application frequently accesses some non-key attributes, you should consider projecting those attributes into a global secondary index. The additional storage costs for the global secondary index offset the cost of performing frequent table scans.
- If you need to access most of the non-key attributes on a frequent basis, you can project these attributes—or even the entire base table—into a global secondary index. This gives you maximum flexibility. However, your storage cost would increase, or even double.
- If your application needs to query a table infrequently, but must perform many writes or updates against the data in the table, consider projecting **KEYS\_ONLY**. The global secondary index would be of minimal size, but would still be available when needed for query activity.

## Reading data from a Global Secondary Index

You can retrieve items from a global secondary index using the `Query` and `Scan` operations. The `GetItem` and `BatchGetItem` operations can't be used on a global secondary index.

## Querying a Global Secondary Index

You can use the `Query` operation to access one or more items in a global secondary index. The query must specify the name of the base table and the name of the index that you want to use, the attributes to be returned in the query results, and any query conditions that you want to apply. DynamoDB can return the results in ascending or descending order.

Consider the following data returned from a `Query` that requests gaming data for a leaderboard application.

```
{  
    "TableName": "GameScores",  
    "IndexName": "GameTitleIndex",  
    "KeyConditionExpression": "GameTitle = :v_title",  
    "ExpressionAttributeValues": {  
        ":v_title": {"S": "Meteor Blasters"}  
    },  
    "ProjectionExpression": "UserId, TopScore",  
    "ScanIndexForward": false  
}
```

In this query:

- DynamoDB accesses `GameTitleIndex`, using the `GameTitle` partition key to locate the index items for Meteor Blasters. All of the index items with this key are stored adjacent to each other for rapid retrieval.
- Within this game, DynamoDB uses the index to access all of the user IDs and top scores for this game.
- The results are returned, sorted in descending order because the `ScanIndexForward` parameter is set to `false`.

## Scanning a Global Secondary Index

You can use the `Scan` operation to retrieve all of the data from a global secondary index. You must provide the base table name and the index name in the request. With a `Scan`, DynamoDB reads all of the data in the index and returns it to the application. You can also request that only some of the data be returned, and that the remaining data should be discarded. To do this, use the `FilterExpression` parameter of the `Scan` operation. For more information, see [Filter expressions for scan \(p. 446\)](#).

## Data synchronization between tables and Global Secondary Indexes

DynamoDB automatically synchronizes each global secondary index with its base table. When an application writes or deletes items in a table, any global secondary indexes on that table are updated asynchronously, using an eventually consistent model. Applications never write directly to an index. However, it is important that you understand the implications of how DynamoDB maintains these indexes.

Global secondary indexes inherit the read/write capacity mode from the base table. For more information, see [Considerations when changing read/write Capacity Mode \(p. 285\)](#).

When you create a global secondary index, you specify one or more index key attributes and their data types. This means that whenever you write an item to the base table, the data types for those attributes must match the index key schema's data types. In the case of `GameTitleIndex`, the `GameTitle` partition key in the index is defined as a `String` data type. The `TopScore` sort key in the index is of type `Number`. If you try to add an item to the `GameScores` table and specify a different data type for

either `GameTitle` or `TopScore`, DynamoDB returns a `ValidationException` because of the data type mismatch.

When you put or delete items in a table, the global secondary indexes on that table are updated in an eventually consistent fashion. Changes to the table data are propagated to the global secondary indexes within a fraction of a second, under normal conditions. However, in some unlikely failure scenarios, longer propagation delays might occur. Because of this, your applications need to anticipate and handle situations where a query on a global secondary index returns results that are not up to date.

If you write an item to a table, you don't have to specify the attributes for any global secondary index sort key. Using `GameTitleIndex` as an example, you would not need to specify a value for the `TopScore` attribute to write a new item to the `GameScores` table. In this case, DynamoDB does not write any data to the index for this particular item.

A table with many global secondary indexes incurs higher costs for write activity than tables with fewer indexes. For more information, see [Provisioned throughput considerations for Global Secondary Indexes \(p. 506\)](#).

## Table classes with Global Secondary Index

A global secondary index will always use the same table class as its base table. Any time a new global secondary index is added for a table, the new index will use the same table class as its base table. When a table's table class is updated, all associated global secondary indexes are updated as well.

## Provisioned throughput considerations for Global Secondary Indexes

When you create a global secondary index on a provisioned mode table, you must specify read and write capacity units for the expected workload on that index. The provisioned throughput settings of a global secondary index are separate from those of its base table. A `Query` operation on a global secondary index consumes read capacity units from the index, not the base table. When you put, update or delete items in a table, the global secondary indexes on that table are also updated. These index updates consume write capacity units from the index, not from the base table.

For example, if you `Query` a global secondary index and exceed its provisioned read capacity, your request will be throttled. If you perform heavy write activity on the table, but a global secondary index on that table has insufficient write capacity, the write activity on the table will be throttled.

### Note

To avoid potential throttling, the provisioned write capacity for a global secondary index should be equal or greater than the write capacity of the base table because new updates write to both the base table and global secondary index.

To view the provisioned throughput settings for a global secondary index, use the `DescribeTable` operation. Detailed information about all of the table's global secondary indexes is returned.

## Read capacity units

Global secondary indexes support eventually consistent reads, each of which consume one half of a read capacity unit. This means that a single global secondary index query can retrieve up to  $2 \times 4 \text{ KB} = 8 \text{ KB}$  per read capacity unit.

For global secondary index queries, DynamoDB calculates the provisioned read activity in the same way as it does for queries against tables. The only difference is that the calculation is based on the sizes of the index entries, rather than the size of the item in the base table. The number of read capacity units is the sum of all projected attribute sizes across all of the items returned. The result is then rounded up to

the next 4 KB boundary. For more information about how DynamoDB calculates provisioned throughput usage, see [Managing settings on DynamoDB provisioned capacity tables \(p. 286\)](#).

The maximum size of the results returned by a `Query` operation is 1 MB. This includes the sizes of all the attribute names and values across all of the items returned.

For example, consider a global secondary index where each item contains 2,000 bytes of data. Now suppose that you `Query` this index and that the query's `KeyConditionExpression` matches eight items. The total size of the matching items is  $2,000 \text{ bytes} \times 8 \text{ items} = 16,000 \text{ bytes}$ . This result is then rounded up to the nearest 4 KB boundary. Because global secondary index queries are eventually consistent, the total cost is  $0.5 \times (16 \text{ KB} / 4 \text{ KB})$ , or 2 read capacity units.

## Write capacity units

When an item in a table is added, updated, or deleted, and a global secondary index is affected by this, the global secondary index consumes provisioned write capacity units for the operation. The total provisioned throughput cost for a write consists of the sum of write capacity units consumed by writing to the base table and those consumed by updating the global secondary indexes. If a write to a table does not require a global secondary index update, no write capacity is consumed from the index.

For a table write to succeed, the provisioned throughput settings for the table and all of its global secondary indexes must have enough write capacity to accommodate the write. Otherwise, the write to the table is throttled.

The cost of writing an item to a global secondary index depends on several factors:

- If you write a new item to the table that defines an indexed attribute, or you update an existing item to define a previously undefined indexed attribute, one write operation is required to put the item into the index.
- If an update to the table changes the value of an indexed key attribute (from A to B), two writes are required, one to delete the previous item from the index and another write to put the new item into the index.
- If an item was present in the index, but a write to the table caused the indexed attribute to be deleted, one write is required to delete the old item projection from the index.
- If an item is not present in the index before or after the item is updated, there is no additional write cost for the index.
- If an update to the table only changes the value of projected attributes in the index key schema, but does not change the value of any indexed key attribute, one write is required to update the values of the projected attributes into the index.

All of these factors assume that the size of each item in the index is less than or equal to the 1 KB item size for calculating write capacity units. Larger index entries require additional write capacity units. You can minimize your write costs by considering which attributes your queries will need to return and projecting only those attributes into the index.

## Storage considerations for Global Secondary Indexes

When an application writes an item to a table, DynamoDB automatically copies the correct subset of attributes to any global secondary indexes in which those attributes should appear. Your AWS account is charged for storage of the item in the base table and also for storage of attributes in any global secondary indexes on that table.

The amount of space used by an index item is the sum of the following:

- The size in bytes of the base table primary key (partition key and sort key)
- The size in bytes of the index key attribute

- The size in bytes of the projected attributes (if any)
- 100 bytes of overhead per index item

To estimate the storage requirements for a global secondary index, you can estimate the average size of an item in the index and then multiply by the number of items in the base table that have the global secondary index key attributes.

If a table contains an item where a particular attribute is not defined, but that attribute is defined as an index partition key or sort key, DynamoDB doesn't write any data for that item to the index.

## Managing Global Secondary Indexes

This section describes how to create, modify, and delete global secondary indexes in Amazon DynamoDB.

### Topics

- [Creating a table with Global Secondary Indexes \(p. 508\)](#)
- [Describing the Global Secondary Indexes on a table \(p. 509\)](#)
- [Adding a Global Secondary Index to an existing table \(p. 509\)](#)
- [Deleting a Global Secondary Index \(p. 512\)](#)
- [Modifying a Global Secondary Index during creation \(p. 512\)](#)
- [Detecting and correcting index key violations \(p. 512\)](#)

## Creating a table with Global Secondary Indexes

To create a table with one or more global secondary indexes, use the `CreateTable` operation with the `GlobalSecondaryIndexes` parameter. For maximum query flexibility, you can create up to 20 global secondary indexes (default quota) per table.

You must specify one attribute to act as the index partition key. You can optionally specify another attribute for the index sort key. It is not necessary for either of these key attributes to be the same as a key attribute in the table. For example, in the `GameScores` table (see [Using Global Secondary Indexes in DynamoDB \(p. 500\)](#)), neither `TopScore` nor `TopScoreDateTime` are key attributes. You could create a global secondary index with a partition key of `TopScore` and a sort key of `TopScoreDateTime`. You might use such an index to determine whether there is a correlation between high scores and the time of day a game is played.

Each index key attribute must be a scalar of type `String`, `Number`, or `Binary`. (It cannot be a document or a set.) You can project attributes of any data type into a global secondary index. This includes scalars, documents, and sets. For a complete list of data types, see [Data types \(p. 13\)](#).

If using provisioned mode, you must provide `ProvisionedThroughput` settings for the index, consisting of `ReadCapacityUnits` and `WriteCapacityUnits`. These provisioned throughput settings are separate from those of the table, but behave in similar ways. For more information, see [Provisioned throughput considerations for Global Secondary Indexes \(p. 506\)](#).

Global secondary indexes inherit the read/write capacity mode from the base table. For more information, see [Considerations when changing read/write Capacity Mode \(p. 285\)](#).

### Note

Backfill operations and ongoing write operations share write throughput within the global secondary index. When creating a new GSI, it can be important to check if your choice of partition key is producing uneven or narrowed distribution of data or traffic across the new index's partition key values. If this occurs, you could be seeing backfill and write operations occurring at the same time and throttling writes to the base table. The service takes measures to

minimize the potential for this scenario, but has no insight into the shape of customer data with respect to the index partition key, the chosen projection, or the sparseness of the index primary key.

If you suspect that your new global secondary index might have narrow or skewed data or traffic distribution across partition key values, consider the following before adding new indexes to operationally important tables.

- It might be safest to add the index at a time when your application is driving the least amount of traffic.
- Consider enabling CloudWatch Contributor Insights on your base table and indexes. This will give you valuable insight into your traffic distribution.
- For provisioned capacity mode base tables and indexes, set the provisioned write capacity of your new index to at least double that of your base table. Watch `WriteThrottleEvents`, `ThrottledRequests`, `OnlineIndexPercentageProgress`, `OnlineIndexConsumedWriteCapacity` and `OnlineIndexThrottleEvents` CloudWatch metrics throughout the process. Adjust the provisioned write capacity as required to complete the backfill in a reasonable time without any significant throttling effects on your ongoing operations.
- Be prepared to cancel the index creation if you experience operational impact due to write throttling, and increasing the provisioned write capacity in your new GSI does not resolve it.

## Describing the Global Secondary Indexes on a table

To view the status of all the global secondary indexes on a table, use the `DescribeTable` operation. The `GlobalSecondaryIndexes` portion of the response shows all of the indexes on the table, along with the current status of each (`IndexStatus`).

The `IndexStatus` for a global secondary index will be one of the following:

- **CREATING** — The index is currently being created, and is not yet available for use.
- **ACTIVE** — The index is ready for use, and applications can perform `Query` operations on the index.
- **UPDATING** — The provisioned throughput settings of the index are being changed.
- **DELETING** — The index is currently being deleted, and can no longer be used.

When DynamoDB has finished building a global secondary index, the index status changes from `CREATING` to `ACTIVE`.

## Adding a Global Secondary Index to an existing table

To add a global secondary index to an existing table, use the `UpdateTable` operation with the `GlobalSecondaryIndexUpdates` parameter. You must provide the following:

- An index name. The name must be unique among all the indexes on the table.
- The key schema of the index. You must specify one attribute for the index partition key; you can optionally specify another attribute for the index sort key. It is not necessary for either of these key attributes to be the same as a key attribute in the table. The data types for each schema attribute must be scalar: `String`, `Number`, or `Binary`.
- The attributes to be projected from the table into the index:
  - **KEYS\_ONLY** — Each item in the index consists only of the table partition key and sort key values, plus the index key values.
  - **INCLUDE** — In addition to the attributes described in `KEYS_ONLY`, the secondary index includes other non-key attributes that you specify.
  - **ALL** — The index includes all of the attributes from the source table.

- The provisioned throughput settings for the index, consisting of `ReadCapacityUnits` and `WriteCapacityUnits`. These provisioned throughput settings are separate from those of the table.

You can only create one global secondary index per `UpdateTable` operation.

### Phases of index creation

When you add a new global secondary index to an existing table, the table continues to be available while the index is being built. However, the new index is not available for Query operations until its status changes from `CREATING` to `ACTIVE`.

#### Note

Global secondary index creation does not use Application Auto Scaling. Increasing the `MIN` Application Auto Scaling capacity will not decrease the creation time of the global secondary index.

Behind the scenes, DynamoDB builds the index in two phases:

#### Resource Allocation

DynamoDB allocates the compute and storage resources that are needed for building the index.

During the resource allocation phase, the `IndexStatus` attribute is `CREATING` and the `Backfilling` attribute is false. Use the `DescribeTable` operation to retrieve the status of a table and all of its secondary indexes.

While the index is in the resource allocation phase, you can't delete the index or delete its parent table. You also can't modify the provisioned throughput of the index or the table. You cannot add or delete other indexes on the table. However, you can modify the provisioned throughput of these other indexes.

#### Backfilling

For each item in the table, DynamoDB determines which set of attributes to write to the index based on its projection (`KEYS_ONLY`, `INCLUDE`, or `ALL`). It then writes these attributes to the index. During the backfill phase, DynamoDB tracks the items that are being added, deleted, or updated in the table. The attributes from these items are also added, deleted, or updated in the index as appropriate.

During the backfilling phase, the `IndexStatus` attribute is set to `CREATING`, and the `Backfilling` attribute is true. Use the `DescribeTable` operation to retrieve the status of a table and all of its secondary indexes.

While the index is backfilling, you cannot delete its parent table. However, you can still delete the index or modify the provisioned throughput of the table and any of its global secondary indexes.

#### Note

During the backfilling phase, some writes of violating items might succeed while others are rejected. After backfilling, all writes to items that violate the new index's key schema are rejected. We recommend that you run the Violation Detector tool after the backfill phase finishes to detect and resolve any key violations that might have occurred. For more information, see [Detecting and correcting index key violations \(p. 512\)](#).

While the resource allocation and backfilling phases are in progress, the index is in the `CREATING` state. During this time, DynamoDB performs read operations on the table. You are not charged for read operations from the base table to populate the global secondary index. However, you are charged for write operations to populate the newly created global secondary index.

When the index build is complete, its status changes to **ACTIVE**. You can't **Query** or **Scan** the index until it is **ACTIVE**.

**Note**

In some cases, DynamoDB can't write data from the table to the index because of index key violations. This can occur if:

- The data type of an attribute value does not match the data type of an index key schema data type.
- The size of an attribute exceeds the maximum length for an index key attribute.
- An index key attribute has an empty String or empty Binary attribute value.

Index key violations do not interfere with global secondary index creation. However, when the index becomes **ACTIVE**, the violating keys are not present in the index.

DynamoDB provides a standalone tool for finding and resolving these issues. For more information, see [Detecting and correcting index key violations \(p. 512\)](#).

### [Adding a Global Secondary Index to a large table](#)

The time required for building a global secondary index depends on several factors, such as the following:

- The size of the table
- The number of items in the table that qualify for inclusion in the index
- The number of attributes projected into the index
- The provisioned write capacity of the index
- Write activity on the main table during index builds

If you are adding a global secondary index to a very large table, it might take a long time for the creation process to complete. To monitor progress and determine whether the index has sufficient write capacity, consult the following Amazon CloudWatch metrics:

- `OnlineIndexPercentageProgress`
- `OnlineIndexConsumedWriteCapacity`
- `OnlineIndexThrottleEvents`

**Note**

For more information about CloudWatch metrics related to DynamoDB, see [DynamoDB metrics \(p. 1114\)](#).

If the provisioned write throughput setting on the index is too low, the index build will take longer to complete. To shorten the time it takes to build a new global secondary index, you can increase its provisioned write capacity temporarily.

**Note**

As a general rule, we recommend setting the provisioned write capacity of the index to 1.5 times the write capacity of the table. This is a good setting for many use cases. However, your actual requirements might be higher or lower.

While an index is being backfilled, DynamoDB uses internal system capacity to read from the table. This is to minimize the impact of the index creation and to assure that your table does not run out of read capacity.

However, it is possible that the volume of incoming write activity might exceed the provisioned write capacity of the index. This is a bottleneck scenario, in which the index creation takes more time because the write activity to the index is throttled. During the index build, we recommend that you monitor

the Amazon CloudWatch metrics for the index to determine whether its consumed write capacity is exceeding its provisioned capacity. In a bottleneck scenario, you should increase the provisioned write capacity on the index to avoid write throttling during the backfill phase.

After the index has been created, you should set its provisioned write capacity to reflect the normal usage of your application.

## Deleting a Global Secondary Index

If you no longer need a global secondary index, you can delete it using the `UpdateTable` operation.

You can delete only one global secondary index per `UpdateTable` operation.

While the global secondary index is being deleted, there is no effect on any read or write activity in the parent table. While the deletion is in progress, you can still modify the provisioned throughput on other indexes.

### Note

- When you delete a table using the `DeleteTable` action, all of the global secondary indexes on that table are also deleted.
- Your account will not be charged for the delete operation of the global secondary index.

## Modifying a Global Secondary Index during creation

While an index is being built, you can use the `DescribeTable` operation to determine what phase it is in. The description for the index includes a Boolean attribute, `Backfilling`, to indicate whether DynamoDB is currently loading the index with items from the table. If `Backfilling` is true, the resource allocation phase is complete and the index is now backfilling.

While the backfill is proceeding, you can update the provisioned throughput parameters for the index. You might decide to do this in order to speed up the index build: You can increase the write capacity of the index while it is being built, and then decrease it afterward. To modify the provisioned throughput settings of the index, use the `UpdateTable` operation. The index status changes to `UPDATING`, and `Backfilling` is true until the index is ready for use.

During the backfilling phase, you can delete the index that is being created. During this phase, you can't add or delete other indexes on the table.

### Note

For indexes that were created as part of a `CreateTable` operation, the `Backfilling` attribute does not appear in the `DescribeTable` output. For more information, see [Phases of index creation \(p. 510\)](#).

## Detecting and correcting index key violations

During the backfill phase of global secondary index creation, Amazon DynamoDB examines each item in the table to determine whether it is eligible for inclusion in the index. Some items might not be eligible because they would cause index key violations. In these cases, the items remain in the table, but the index doesn't have a corresponding entry for that item.

An *index key violation* occurs in the following situations:

- There is a data type mismatch between an attribute value and the index key schema data type. For example, suppose that one of the items in the `GameScores` table had a `TopScore` value of type `String`. If you added a global secondary index with a partition key of `TopScore`, of type `Number`, the item from the table would violate the index key.
- An attribute value from the table exceeds the maximum length for an index key attribute. The maximum length of a partition key is 2048 bytes, and the maximum length of a sort key is 1024 bytes.

If any of the corresponding attribute values in the table exceed these limits, the item from the table would violate the index key.

**Note**

If a String or Binary attribute value is set for an attribute that is used as an index key, then the attribute value must have a length greater than zero; otherwise, the item from the table would violate the index key.

This tool does not flag this index key violation, at this time.

If an index key violation occurs, the backfill phase continues without interruption. However, any violating items are not included in the index. After the backfill phase completes, all writes to items that violate the new index's key schema will be rejected.

To identify and fix attribute values in a table that violate an index key, use the Violation Detector tool. To run Violation Detector, you create a configuration file that specifies the name of a table to be scanned, the names and data types of the global secondary index partition key and sort key, and what actions to take if any index key violations are found. Violation Detector can run in one of two different modes:

- **Detection mode** — Detect index key violations. Use detection mode to report the items in the table that would cause key violations in a global secondary index. (You can optionally request that these violating table items be deleted immediately when they are found.) The output from detection mode is written to a file, which you can use for further analysis.
- **Correction mode** — Correct index key violations. In correction mode, Violation Detector reads an input file with the same format as the output file from detection mode. Correction mode reads the records from the input file and, for each record, it either deletes or updates the corresponding items in the table. (Note that if you choose to update the items, you must edit the input file and set appropriate values for these updates.)

## Downloading and running Violation Detector

Violation Detector is available as an executable Java Archive (.jar file), and runs on Windows, macOS, or Linux computers. Violation Detector requires Java 1.7 (or later) and Apache Maven.

- [Download violation detector from GitHub](#)

Follow the instructions in the `README.md` file to download and install Violation Detector using Maven.

To start Violation Detector, go to the directory where you have built `ViolationDetector.java` and enter the following command.

```
java -jar ViolationDetector.jar [options]
```

The Violation Detector command line accepts the following options:

- `-h | --help` — Prints a usage summary and options for Violation Detector.
- `-p | --configFilePath value` — The fully qualified name of a Violation Detector configuration file. For more information, see [The Violation Detector configuration file \(p. 514\)](#).
- `-t | --detect value` — Detect index key violations in the table, and write them to the Violation Detector output file. If the value of this parameter is set to `keep`, items with key violations are not modified. If the value is set to `delete`, items with key violations are deleted from the table.
- `-c | --correct value` — Read index key violations from an input file, and take corrective actions on the items in the table. If the value of this parameter is set to `update`, items with key violations are updated with new, non-violating values. If the value is set to `delete`, items with key violations are deleted from the table.

## The Violation Detector configuration file

At runtime, the Violation Detector tool requires a configuration file. The parameters in this file determine which DynamoDB resources that Violation Detector can access, and how much provisioned throughput it can consume. The following table describes these parameters.

Parameter name	Description	Required?
awsCredentialsFile	<p>The fully qualified name of a file containing your AWS credentials. The credentials file must be in the following format:</p> <pre>accessKey   = <i>access_key_id_goes_here</i> secretKey   = <i>secret_key_goes_here</i></pre>	Yes
dynamoDBRegion	The AWS Region in which the table resides. For example: us-west-2.	Yes
tableName	The name of the DynamoDB table to be scanned.	Yes
gsiHashKeyName	The name of the index partition key.	Yes
gsiHashKeyType	<p>The data type of the index partition key—String, Number, or Binary:</p> <p>S   N   B</p>	Yes
gsiRangeKeyName	The name of the index sort key. Do not specify this parameter if the index only has a simple primary key (partition key).	No
gsiRangeKeyType	<p>The data type of the index sort key—String, Number, or Binary:</p> <p>S   N   B</p> <p>Do not specify this parameter if the index only has a simple primary key (partition key).</p>	No
recordDetails	Whether to write the full details of index key violations to the output file. If set to true (the default), full information about the violating items is reported. If set to false, only the number of violations is reported.	No
recordGsiValueInViolationReport	Whether to write the values of the violating index keys to	No

Parameter name	Description	Required?
	<p>the output file. If set to <code>true</code> (default), the key values are reported. If set to <code>false</code>, the key values are not reported.</p>	
<code>detectionOutputPath</code>	<p>The full path of the Violation Detector output file. This parameter supports writing to a local directory or to Amazon Simple Storage Service (Amazon S3). The following are examples:</p> <pre><code>detectionOutputPath = //local/path/ filename.csv</code></pre> <pre><code>detectionOutputPath = s3://bucket/filename.csv</code></pre> <p>Information in the output file appears in comma-separated values (CSV) format. If you don't set <code>detectionOutputPath</code>, the output file is named <code>violation_detection.csv</code> and is written to your current working directory.</p>	No
<code>numOfSegments</code>	<p>The number of parallel scan segments to be used when Violation Detector scans the table. The default value is 1, meaning that the table is scanned in a sequential manner. If the value is 2 or higher, then Violation Detector divides the table into that many logical segments and an equal number of scan threads.</p> <p>The maximum setting for <code>numOfSegments</code> is 4096.</p> <p>For larger tables, a parallel scan is generally faster than a sequential scan. In addition, if the table is large enough to span multiple partitions, a parallel scan distributes its read activity evenly across multiple partitions.</p> <p>For more information about parallel scans in DynamoDB, see <a href="#">Parallel scan (p. 449)</a>.</p>	No

Parameter name	Description	Required?
<code>numOfViolations</code>	The upper limit of index key violations to write to the output file. If set to <code>-1</code> (the default), the entire table is scanned. If set to a positive integer, then Violation Detector stops after it encounters that number of violations.	No
<code>numOfRecords</code>	The number of items in the table to be scanned. If set to <code>-1</code> (the default), the entire table is scanned. If set to a positive integer, Violation Detector stops after it scans that many items in the table.	No
<code>readWriteIOPSPercent</code>	Regulates the percentage of provisioned read capacity units that are consumed during the table scan. Valid values range from <code>1</code> to <code>100</code> . The default value ( <code>25</code> ) means that Violation Detector will consume no more than <code>25%</code> of the table's provisioned read throughput.	No
<code>correctionInputPath</code>	<p>The full path of the Violation Detector correction input file. If you run Violation Detector in correction mode, the contents of this file are used to modify or delete data items in the table that violate the global secondary index.</p> <p>The format of the <code>correctionInputPath</code> file is the same as that of the <code>detectionOutputPath</code> file. This lets you process the output from detection mode as input in correction mode.</p>	No

Parameter name	Description	Required?
correctionOutputPath	<p>The full path of the Violation Detector correction output file. This file is created only if there are update errors.</p> <p>This parameter supports writing to a local directory or to Amazon S3. The following are examples:</p> <pre>correctionOutputPath = //local/path/ filename.csv</pre> <pre>correctionOutputPath = s3://bucket/filename.csv</pre> <p>Information in the output file appears in CSV format. If you don't set <code>correctionOutputPath</code>, the output file is named <code>violation_update_errors.csv</code> and is written to your current working directory.</p>	No

## Detection

To detect index key violations, use Violation Detector with the `--detect` command line option. To show how this option works, consider the `ProductCatalog` table shown in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#). The following is a list of items in the table. Only the primary key (`Id`) and the `Price` attribute are shown.

<b>Id (primary key)</b>	<b>Price</b>
101	5
102	20
103	200
201	100
202	200
203	300
204	400
205	500

All of the values for `Price` are of type `Number`. However, because DynamoDB is schemaless, it is possible to add an item with a non-numeric `Price`. For example, suppose that you add another item to the `ProductCatalog` table.

Id (primary key)	Price
999	"Hello"

The table now has a total of nine items.

Now you add a new global secondary index to the table: `PriceIndex`. The primary key for this index is a partition key, `Price`, which is of type `Number`. After the index has been built, it will contain eight items—but the `ProductCatalog` table has nine items. The reason for this discrepancy is that the value "Hello" is of type `String`, but `PriceIndex` has a primary key of type `Number`. The `String` value violates the global secondary index key, so it is not present in the index.

To use Violation Detector in this scenario, you first create a configuration file such as the following.

```
# Properties file for violation detection tool configuration.
# Parameters that are not specified will use default values.

awsCredentialsFile = /home/alice/credentials.txt
dynamoDBRegion = us-west-2
tableName = ProductCatalog
gsiHashKeyName = Price
gsiHashKeyType = N
recordDetails = true
recordGsiValueInViolationRecord = true
detectionOutputPath = ./gsi_violation_check.csv
correctionInputPath = ./gsi_violation_check.csv
numOfSegments = 1
readWriteIOPSPercent = 40
```

Next, you run Violation Detector as in the following example.

```
$ java -jar ViolationDetector.jar --configFilePath config.txt --detect keep

Violation detection started: sequential scan, Table name: ProductCatalog, GSI name:
PriceIndex
Progress: Items scanned in total: 9, Items scanned by this thread: 9, Violations
found by this thread: 1, Violations deleted by this thread: 0
Violation detection finished: Records scanned: 9, Violations found: 1, Violations deleted:
0, see results at: ./gsi_violation_check.csv
```

If the `recordDetails` config parameter is set to `true`, Violation Detector writes details of each violation to the output file, as in the following example.

```
Table Hash Key,GSI Hash Key Value,GSI Hash Key Violation Type,GSI Hash Key Violation
Description,GSI Hash Key Update Value(FOR USER),Delete Blank Attributes When Updating?(Y/
N)

999,"{""S"":""Hello""}",Type Violation,Expected: N Found: S,,
```

The output file is in CSV format. The first line in the file is a header, followed by one record per item that violates the index key. The fields of these violation records are as follows:

- **Table hash key** — The partition key value of the item in the table.
- **Table range key** — The sort key value of the item in the table.
- **GSI hash key value** — The partition key value of the global secondary index.

- **GSI hash key violation type** — Either Type Violation or Size Violation.
- **GSI hash key violation description** — The cause of the violation.
- **GSI hash key update Value(FOR USER)** — In correction mode, a new user-supplied value for the attribute.
- **GSI range key value** — The sort key value of the global secondary index.
- **GSI range key violation type** — Either Type Violation or Size Violation.
- **GSI range key violation description** — The cause of the violation.
- **GSI range key update Value(FOR USER)** — In correction mode, a new user-supplied value for the attribute.
- **Delete blank attribute when Updating(Y/N)** — In correction mode, determines whether to delete (Y) or keep (N) the violating item in the table—but only if either of the following fields are blank:
  - GSI Hash Key Update Value(FOR USER)
  - GSI Range Key Update Value(FOR USER)

If either of these fields are non-blank, then `Delete Blank Attribute When Updating(Y/N)` has no effect.

#### Note

The output format might vary, depending on the configuration file and command line options. For example, if the table has a simple primary key (without a sort key), no sort key fields will be present in the output. The violation records in the file might not be in sorted order.

#### Correction

To correct index key violations, use Violation Detector with the `--correct` command line option. In correction mode, Violation Detector reads the input file specified by the `correctionInputPath` parameter. This file has the same format as the `detectionOutputPath` file, so that you can use the output from detection as input for correction.

Violation Detector provides two different ways to correct index key violations:

- **Delete violations** — Delete the table items that have violating attribute values.
- **Update violations** — Update the table items, replacing the violating attributes with non-violating values.

In either case, you can use the output file from detection mode as input for correction mode.

Continuing with the `ProductCatalog` example, suppose that you want to delete the violating item from the table. To do this, you use the following command line.

```
$ java -jar ViolationDetector.jar --configFilePath config.txt --correct delete
```

At this point, you are asked to confirm whether you want to delete the violating items.

```
Are you sure to delete all violations on the table?y/n
y
Confirmed, will delete violations on the table...
Violation correction from file started: Reading records from file: ../
gsi_violation_check.csv, will delete these records from table.
Violation correction from file finished: Violations delete: 1, Violations Update: 0
```

Now both `ProductCatalog` and `PriceIndex` have the same number of items.

## Working with Global Secondary Indexes: Java

You can use the AWS SDK for Java Document API to create an Amazon DynamoDB table with one or more global secondary indexes, describe the indexes on the table, and perform queries using the indexes.

The following are the common steps for table operations.

1. Create an instance of the `DynamoDB` class.
2. Provide the required and optional parameters for the operation by creating the corresponding request objects.
3. Call the appropriate method provided by the client that you created in the preceding step.

### Topics

- [Create a table with a Global Secondary Index \(p. 520\)](#)
- [Describe a table with a Global Secondary Index \(p. 521\)](#)
- [Query a Global Secondary Index \(p. 522\)](#)
- [Example: Global Secondary Indexes using the AWS SDK for Java document API \(p. 523\)](#)

### Create a table with a Global Secondary Index

You can create global secondary indexes at the same time that you create a table. To do this, use `CreateTable` and provide your specifications for one or more global secondary indexes. The following Java code example creates a table to hold information about weather data. The partition key is `Location` and the sort key is `Date`. A global secondary index named `PrecipIndex` allows fast access to precipitation data for various locations.

The following are the steps to create a table with a global secondary index, using the DynamoDB document API.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `CreateTableRequest` class to provide the request information.

You must provide the table name, its primary key, and the provisioned throughput values. For the global secondary index, you must provide the index name, its provisioned throughput settings, the attribute definitions for the index sort key, the key schema for the index, and the attribute projection.

3. Call the `createTable` method by providing the request object as a parameter.

The following Java code example demonstrates the preceding steps. The code creates a table (`WeatherData`) with a global secondary index (`PrecipIndex`). The index partition key is `Date` and its sort key is `Precipitation`. All of the table attributes are projected into the index. Users can query this index to obtain weather data for a particular date, optionally sorting the data by precipitation amount.

Because `Precipitation` is not a key attribute for the table, it is not required. However, `WeatherData` items without `Precipitation` do not appear in `PrecipIndex`.

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

// Attribute definitions
ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<AttributeDefinition>();

attributeDefinitions.add(new AttributeDefinition()
    .withAttributeName("Location")
    .withAttributeType("S"));
```

```

attributeDefinitions.add(new AttributeDefinition()
    .withAttributeName("Date")
    .withAttributeType("S"));
attributeDefinitions.add(new AttributeDefinition()
    .withAttributeName("Precipitation")
    .withAttributeType("N"));

// Table key schema
ArrayList<KeySchemaElement> tableKeySchema = new ArrayList<KeySchemaElement>();
tableKeySchema.add(new KeySchemaElement()
    .withAttributeName("Location")
    .withKeyType(KeyType.HASH)); //Partition key
tableKeySchema.add(new KeySchemaElement()
    .withAttributeName("Date")
    .withKeyType(KeyType.RANGE)); //Sort key

// PrecipIndex
GlobalSecondaryIndex precipIndex = new GlobalSecondaryIndex()
    .withIndexName("PrecipIndex")
    .withProvisionedThroughput(new ProvisionedThroughput()
        .withReadCapacityUnits((long) 10)
        .withWriteCapacityUnits((long) 1))
    .withProjection(new Projection().withProjectionType(ProjectionType.ALL));

ArrayList<KeySchemaElement> indexKeySchema = new ArrayList<KeySchemaElement>();

indexKeySchema.add(new KeySchemaElement()
    .withAttributeName("Date")
    .withKeyType(KeyType.HASH)); //Partition key
indexKeySchema.add(new KeySchemaElement()
    .withAttributeName("Precipitation")
    .withKeyType(KeyType.RANGE)); //Sort key

precipIndex.setKeySchema(indexKeySchema);

CreateTableRequest createTableRequest = new CreateTableRequest()
    .withTableName("WeatherData")
    .withProvisionedThroughput(new ProvisionedThroughput()
        .withReadCapacityUnits((long) 5)
        .withWriteCapacityUnits((long) 1))
    .withAttributeDefinitions(attributeDefinitions)
    .withKeySchema(tableKeySchema)
    .withGlobalSecondaryIndexes(precipIndex);

Table table = dynamoDB.createTable(createTableRequest);
System.out.println(table.getDescription());

```

You must wait until DynamoDB creates the table and sets the table status to ACTIVE. After that, you can begin putting data items into the table.

## Describe a table with a Global Secondary Index

To get information about global secondary indexes on a table, use `DescribeTable`. For each index, you can access its name, key schema, and projected attributes.

The following are the steps to access global secondary index information a table.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `Table` class to represent the index you want to work with.
3. Call the `describe` method on the `Table` object.

The following Java code example demonstrates the preceding steps.

## Example

```

AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("WeatherData");
TableDescription tableDesc = table.describe();

Iterator<GlobalSecondaryIndexDescription> gsiIter =
    tableDesc.getGlobalSecondaryIndexes().iterator();
while (gsiIter.hasNext()) {
    GlobalSecondaryIndexDescription gsiDesc = gsiIter.next();
    System.out.println("Info for index "
        + gsiDesc.getIndexName() + ":");

    Iterator<KeySchemaElement> kseIter = gsiDesc.getKeySchema().iterator();
    while (kseIter.hasNext()) {
        KeySchemaElement kse = kseIter.next();
        System.out.printf("\t%s: %s\n", kse.getAttributeName(), kse.getKeyType());
    }
    Projection projection = gsiDesc.getProjection();
    System.out.println("\tThe projection type is: "
        + projection.getProjectionType());
    if (projection.getProjectionType().toString().equals("INCLUDE")) {
        System.out.println("\t\tThe non-key projected attributes are: "
            + projection.getNonKeyAttributes());
    }
}
}

```

## Query a Global Secondary Index

You can use `Query` on a global secondary index, in much the same way you `Query` a table. You need to specify the index name, the query criteria for the index partition key and sort key (if present), and the attributes that you want to return. In this example, the index is `PrecipIndex`, which has a partition key of `Date` and a sort key of `Precipitation`. The index query returns all of the weather data for a particular date, where the precipitation is greater than zero.

The following are the steps to query a global secondary index using the AWS SDK for Java Document API.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `Table` class to represent the index you want to work with.
3. Create an instance of the `Index` class for the index you want to query.
4. Call the `query` method on the `Index` object.

The attribute name `Date` is a DynamoDB reserved word. Therefore, you must use an expression attribute name as a placeholder in the `KeyConditionExpression`.

The following Java code example demonstrates the preceding steps.

## Example

```

AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

Table table = dynamoDB.getTable("WeatherData");
Index index = table.getIndex("PrecipIndex");

QuerySpec spec = new QuerySpec()

```

```

.withKeyConditionExpression("#d = :v_date and Precipitation = :v_precip")
.withNameMap(new NameMap()
    .with("#d", "Date"))
.writeValueMap(new ValueMap()
    .withString(":v_date", "2013-08-10")
    .withNumber(":v_precip", 0));

ItemCollection<QueryOutcome> items = index.query(spec);
Iterator<Item> iter = items.iterator();
while (iter.hasNext()) {
    System.out.println(iter.next().toJSONPretty());
}

```

## Example: Global Secondary Indexes using the AWS SDK for Java document API

The following Java code example shows how to work with global secondary indexes. The example creates a table named `Issues`, which might be used in a simple bug tracking system for software development. The partition key is `IssueId` and the sort key is `Title`. There are three global secondary indexes on this table:

- `CreateDateIndex` — The partition key is `CreateDate` and the sort key is `IssueId`. In addition to the table keys, the attributes `Description` and `Status` are projected into the index.
- `TitleIndex` — The partition key is `Title` and the sort key is `IssueId`. No attributes other than the table keys are projected into the index.
- `DueDateIndex` — The partition key is `DueDate`, and there is no sort key. All of the table attributes are projected into the index.

After the `Issues` table is created, the program loads the table with data representing software bug reports. It then queries the data using the global secondary indexes. Finally, the program deletes the `Issues` table.

For step-by-step instructions for testing the following example, see [Java code examples \(p. 274\)](#).

### Example

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples.document;

import java.util.ArrayList;
import java.util.Iterator;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Index;
import com.amazonaws.services.dynamodbv2.document.Item;
import com.amazonaws.services.dynamodbv2.document.ItemCollection;

```

```

import com.amazonaws.services.dynamodbv2.document.QueryOutcome;
import com.amazonaws.services.dynamodbv2.document.Table;
import com.amazonaws.services.dynamodbv2.document.spec.QuerySpec;
import com.amazonaws.services.dynamodbv2.document.utils.ValueMap;
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;
import com.amazonaws.services.dynamodbv2.model.CreateTableRequest;
import com.amazonaws.services.dynamodbv2.model.GlobalSecondaryIndex;
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;
import com.amazonaws.services.dynamodbv2.model.KeyType;
import com.amazonaws.services.dynamodbv2.model.Projection;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;

public class DocumentAPIGlobalSecondaryIndexExample {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDB dynamoDB = new DynamoDB(client);

    public static String tableName = "Issues";

    public static void main(String[] args) throws Exception {

        createTable();
        loadData();

        queryIndex("CreateDateIndex");
        queryIndex("TitleIndex");
        queryIndex("DueDateIndex");

        deleteTable(tableName);
    }

    public static void createTable() {

        // Attribute definitions
        ArrayList<AttributeDefinition> attributeDefinitions = new
        ArrayList<AttributeDefinition>();

        attributeDefinitions.add(new
        AttributeDefinition().withAttributeName("IssueId").withAttributeType("S"));
        attributeDefinitions.add(new
        AttributeDefinition().withAttributeName("Title").withAttributeType("S"));
        attributeDefinitions.add(new
        AttributeDefinition().withAttributeName("CreateDate").withAttributeType("S"));
        attributeDefinitions.add(new
        AttributeDefinition().withAttributeName("DueDate").withAttributeType("S"));

        // Key schema for table
        ArrayList<KeySchemaElement> tableKeySchema = new ArrayList<KeySchemaElement>();
        tableKeySchema.add(new
        KeySchemaElement().withAttributeName("IssueId").withKeyType(KeyType.HASH)); // Partition

        // key
        tableKeySchema.add(new
        KeySchemaElement().withAttributeName("Title").withKeyType(KeyType.RANGE)); // Sort

        // key

        // Initial provisioned throughput settings for the indexes
        ProvisionedThroughput ptIndex = new
        ProvisionedThroughput().withReadCapacityUnits(1L)
            .withWriteCapacityUnits(1L);

        // CreateDateIndex
        GlobalSecondaryIndex createDateIndex = new
        GlobalSecondaryIndex().withIndexName("CreateDateIndex")
    }
}

```

```

        .withProvisionedThroughput(ptIndex)
        .withKeySchema(new
KeySchemaElement().withAttributeName("CreateDate").withKeyType(KeyType.HASH), // Partition

            // key
            new
KeySchemaElement().withAttributeName("IssueId").withKeyType(KeyType.RANGE)) // Sort

        // key
        .withProjection(
            new
Projection().withProjectionType("INCLUDE").withNonKeyAttributes("Description", "Status"));

        // TitleIndex
        GlobalSecondaryIndex titleIndex = new
GlobalSecondaryIndex().withIndexName("TitleIndex")
            .withProvisionedThroughput(ptIndex)
            .withKeySchema(new
KeySchemaElement().withAttributeName("Title").withKeyType(KeyType.HASH), // Partition

            // key
            new
KeySchemaElement().withAttributeName("IssueId").withKeyType(KeyType.RANGE)) // Sort

        // key
        .withProjection(new Projection().withProjectionType("KEYS_ONLY"));

        // DueDateIndex
        GlobalSecondaryIndex dueDateIndex = new
GlobalSecondaryIndex().withIndexName("DueDateIndex")
            .withProvisionedThroughput(ptIndex)
            .withKeySchema(new
KeySchemaElement().withAttributeName("DueDate").withKeyType(KeyType.HASH)) // Partition

            // key
            .withProjection(new Projection().withProjectionType("ALL"));

        CreateTableRequest createTableRequest = new
CreateTableRequest().withTableName(tableName)
            .withProvisionedThroughput(
                new ProvisionedThroughput().withReadCapacityUnits((long)
1).withWriteCapacityUnits((long) 1))
            .withAttributeDefinitions(attributeDefinitions).withKeySchema(tableKeySchema)
            .withGlobalSecondaryIndexes(createDateIndex, titleIndex, dueDateIndex);

        System.out.println("Creating table " + tableName + "...");
        dynamoDB.createTable(createTableRequest);

        // Wait for table to become active
        System.out.println("Waiting for " + tableName + " to become ACTIVE...");
        try {
            Table table = dynamoDB.getTable(tableName);
            table.waitForActive();
        }
        catch (InterruptedException e) {
            e.printStackTrace();
        }
    }

    public static void queryIndex(String indexName) {

        Table table = dynamoDB.getTable(tableName);

        System.out.println("\n*****");
\n");
        System.out.print("Querying index " + indexName + "...");


```

```

        Index index = table.getIndex(indexName);

        ItemCollection<QueryOutcome> items = null;

        QuerySpec querySpec = new QuerySpec();

        if (indexName == "CreateDateIndex") {
            System.out.println("Issues filed on 2013-11-01");
            querySpec.withKeyConditionExpression("CreateDate = :v_date and
begins_with(IssueId, :v_issue)")
                .WithValueMap(new ValueMap().withString(":v_date",
"2013-11-01").withString(":v_issue", "A-"));
            items = index.query(querySpec);
        }
        else if (indexName == "TitleIndex") {
            System.out.println("Compilation errors");
            querySpec.withKeyConditionExpression("Title = :v_title and
begins_with(IssueId, :v_issue)")
                .WithValueMap(new ValueMap().withString(":v_title", "Compilation
error").withString(":v_issue", "A-"));
            items = index.query(querySpec);
        }
        else if (indexName == "DueDateIndex") {
            System.out.println("Items that are due on 2013-11-30");
            querySpec.withKeyConditionExpression("DueDate = :v_date")
                .WithValueMap(new ValueMap().withString(":v_date", "2013-11-30"));
            items = index.query(querySpec);
        }
        else {
            System.out.println("\nNo valid index name provided");
            return;
        }

        Iterator<Item> iterator = items.iterator();

        System.out.println("Query: printing results...");

        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }

    }

    public static void deleteTable(String tableName) {

        System.out.println("Deleting table " + tableName + "...");

        Table table = dynamoDB.getTable(tableName);
        table.delete();

        // Wait for table to be deleted
        System.out.println("Waiting for " + tableName + " to be deleted...");
        try {
            table.waitForDelete();
        }
        catch (InterruptedException e) {
            e.printStackTrace();
        }
    }

    public static void loadData() {

        System.out.println("Loading data into table " + tableName + "...");

        // IssueId, Title,

```

```

// Description,
// CreateDate, LastUpdateDate, DueDate,
// Priority, Status

    putItem("A-101", "Compilation error", "Can't compile Project X - bad version
number. What does this mean?", 
        "2013-11-01", "2013-11-02", "2013-11-10", 1, "Assigned");

    putItem("A-102", "Can't read data file", "The main data file is missing, or the
permissions are incorrect",
        "2013-11-01", "2013-11-04", "2013-11-30", 2, "In progress");

    putItem("A-103", "Test failure", "Functional test of Project X produces errors",
"2013-11-01", "2013-11-02",
        "2013-11-10", 1, "In progress");

    putItem("A-104", "Compilation error", "Variable 'messageCount' was not
initialized.", "2013-11-15",
        "2013-11-16", "2013-11-30", 3, "Assigned");

    putItem("A-105", "Network issue", "Can't ping IP address 127.0.0.1. Please fix
this.", "2013-11-15",
        "2013-11-16", "2013-11-19", 5, "Assigned");
}

public static void putItem(
    String issueId, String title, String description, String createDate, String
lastUpdateDate, String dueDate,
    Integer priority, String status) {

    Table table = dynamoDB.getTable(tableName);

    Item item = new Item().withPrimaryKey("IssueId", issueId).withString("Title",
title)
        .withString("Description", description).withString("CreateDate", createDate)
        .withString("LastUpdateDate", lastUpdateDate).withString("DueDate", dueDate)
        .withNumber("Priority", priority).withString("Status", status);

    table.putItem(item);
}
}

```

## Working with Global Secondary Indexes: .NET

You can use the AWS SDK for .NET low-level API to create an Amazon DynamoDB table with one or more global secondary indexes, describe the indexes on the table, and perform queries using the indexes. These operations map to the corresponding DynamoDB operations. For more information, see the [Amazon DynamoDB API Reference](#).

The following are the common steps for table operations using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Provide the required and optional parameters for the operation by creating the corresponding request objects.

For example, create a `CreateTableRequest` object to create a table and `QueryRequest` object to query a table or an index.

3. Run the appropriate method provided by the client that you created in the preceding step.

## Topics

- [Create a table with a Global Secondary Index \(p. 528\)](#)
- [Describe a table with a Global Secondary Index \(p. 529\)](#)
- [Query a Global Secondary Index \(p. 530\)](#)
- [Example: Global Secondary Indexes using the AWS SDK for .NET low-level API \(p. 531\)](#)

## Create a table with a Global Secondary Index

You can create global secondary indexes at the same time that you create a table. To do this, use `CreateTable` and provide your specifications for one or more global secondary indexes. The following C# code example creates a table to hold information about weather data. The partition key is `Location` and the sort key is `Date`. A global secondary index named `PrecipIndex` allows fast access to precipitation data for various locations.

The following are the steps to create a table with a global secondary index, using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `CreateTableRequest` class to provide the request information.

You must provide the table name, its primary key, and the provisioned throughput values. For the global secondary index, you must provide the index name, its provisioned throughput settings, the attribute definitions for the index sort key, the key schema for the index, and the attribute projection.

3. Run the `CreateTable` method by providing the request object as a parameter.

The following C# code example demonstrates the preceding steps. The code creates a table (`WeatherData`) with a global secondary index (`PrecipIndex`). The index partition key is `Date` and its sort key is `Precipitation`. All of the table attributes are projected into the index. Users can query this index to obtain weather data for a particular date, optionally sorting the data by precipitation amount.

Because `Precipitation` is not a key attribute for the table, it is not required. However, `WeatherData` items without `Precipitation` do not appear in `PrecipIndex`.

```

client = new AmazonDynamoDBClient();
string tableName = "WeatherData";

// Attribute definitions
var attributeDefinitions = new List<AttributeDefinition>()
{
    {new AttributeDefinition{
        AttributeName = "Location",
        AttributeType = "S"}},
    {new AttributeDefinition{
        AttributeName = "Date",
        AttributeType = "S"}},
    {new AttributeDefinition(){
        AttributeName = "Precipitation",
        AttributeType = "N"}}
};

// Table key schema
var tableKeySchema = new List<KeySchemaElement>()
{
    {new KeySchemaElement {
        AttributeName = "Location",
        KeyType = "HASH"}}, //Partition key
    {new KeySchemaElement {
        AttributeName = "Date",
        KeyType = "RANGE"}}, //Sort key
    {new KeySchemaElement {
        AttributeName = "Precipitation",
        KeyType = "RANGE"}}, //Index key
};

```

```

        {new KeySchemaElement {
            AttributeName = "Date",
            KeyType = "RANGE"} //Sort key
    }
};

// PrecipIndex
var precipIndex = new GlobalSecondaryIndex
{
    IndexName = "PrecipIndex",
    ProvisionedThroughput = new ProvisionedThroughput
    {
        ReadCapacityUnits = (long)10,
        WriteCapacityUnits = (long)1
    },
    Projection = new Projection { ProjectionType = "ALL" }
};

var indexKeySchema = new List<KeySchemaElement> {
    {new KeySchemaElement { AttributeName = "Date", KeyType = "HASH"}}, //Partition key
    {new KeySchemaElement{AttributeName = "Precipitation",KeyType = "RANGE"} } //Sort key
};

precipIndex.KeySchema = indexKeySchema;

CreateTableRequest createTableRequest = new CreateTableRequest
{
    TableName = tableName,
    ProvisionedThroughput = new ProvisionedThroughput
    {
        ReadCapacityUnits = (long)5,
        WriteCapacityUnits = (long)1
    },
    AttributeDefinitions = attributeDefinitions,
    KeySchema = tableKeySchema,
    GlobalSecondaryIndexes = { precipIndex }
};

CreateTableResponse response = client.CreateTable(createTableRequest);
Console.WriteLine(response.CreateTableResult.TableDescription.TableName);
Console.WriteLine(response.CreateTableResult.TableDescription.TableStatus);

```

You must wait until DynamoDB creates the table and sets the table status to ACTIVE. After that, you can begin putting data items into the table.

## Describe a table with a Global Secondary Index

To get information about global secondary indexes on a table, use `DescribeTable`. For each index, you can access its name, key schema, and projected attributes.

The following are the steps to access global secondary index information for a table using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Run the `describeTable` method by providing the request object as a parameter.

Create an instance of the `DescribeTableRequest` class to provide the request information. You must provide the table name.

3.

The following C# code example demonstrates the preceding steps.

### Example

```

client = new AmazonDynamoDBClient();
string tableName = "WeatherData";

DescribeTableResponse response = client.DescribeTable(new DescribeTableRequest { TableName
= tableName });

List<GlobalSecondaryIndexDescription> globalSecondaryIndexes =
response.DescribeTableResult.Table.GlobalSecondaryIndexes;

// This code snippet will work for multiple indexes, even though
// there is only one index in this example.

foreach (GlobalSecondaryIndexDescription gsiDescription in globalSecondaryIndexes) {
    Console.WriteLine("Info for index " + gsiDescription.IndexName + ":");

    foreach (KeySchemaElement kse in gsiDescription.KeySchema) {
        Console.WriteLine("\t" + kse.AttributeName + ": key type is " + kse.KeyType);
    }

    Projection projection = gsiDescription.Projection;
    Console.WriteLine("\tThe projection type is: " + projection.ProjectionType);

    if (projection.ProjectionType.ToString().Equals("INCLUDE")) {
        Console.WriteLine("\t\tThe non-key projected attributes are: "
+ projection.NonKeyAttributes);
    }
}

```

## Query a Global Secondary Index

You can use `Query` on a global secondary index, in much the same way you `Query` a table. You need to specify the index name, the query criteria for the index partition key and sort key (if present), and the attributes that you want to return. In this example, the index is `PrecipIndex`, which has a partition key of `Date` and a sort key of `Precipitation`. The index query returns all of the weather data for a particular date, where the precipitation is greater than zero.

The following are the steps to query a global secondary index using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `QueryRequest` class to provide the request information.
3. Run the `query` method by providing the request object as a parameter.

The attribute name `Date` is a DynamoDB reserved word. Therefore, you must use an expression attribute name as a placeholder in the `KeyConditionExpression`.

The following C# code example demonstrates the preceding steps.

### Example

```

client = new AmazonDynamoDBClient();

QueryRequest queryRequest = new QueryRequest
{
    TableName = "WeatherData",
    IndexName = "PrecipIndex",
    KeyConditionExpression = "#dt = :v_date and Precipitation > :v_precip",
    ExpressionAttributeNames = new Dictionary<String, String> {

```

```

        {"#dt", "Date"}
    },
    ExpressionAttributeValues = new Dictionary<string, AttributeValue> {
        {"<:v_date", new AttributeValue { S = "2013-08-01" }},
        {"<:v_precip", new AttributeValue { N = "0" }}
    },
    ScanIndexForward = true
};

var result = client.Query(queryRequest);

var items = result.Items;
foreach (var currentItem in items)
{
    foreach (string attr in currentItem.Keys)
    {
        Console.Write(attr + "----> ");
        if (attr == "Precipitation")
        {
            Console.WriteLine(currentItem[attr].N);
        }
        else
        {
            Console.WriteLine(currentItem[attr].S);
        }
    }
    Console.WriteLine();
}

```

## Example: Global Secondary Indexes using the AWS SDK for .NET low-level API

The following C# code example shows how to work with global secondary indexes. The example creates a table named `Issues`, which might be used in a simple bug tracking system for software development. The partition key is `IssueId` and the sort key is `Title`. There are three global secondary indexes on this table:

- `CreateDateIndex` — The partition key is `CreateDate` and the sort key is `IssueId`. In addition to the table keys, the attributes `Description` and `Status` are projected into the index.
- `TitleIndex` — The partition key is `Title` and the sort key is `IssueId`. No attributes other than the table keys are projected into the index.
- `DueDateIndex` — The partition key is `DueDate`, and there is no sort key. All of the table attributes are projected into the index.

After the `Issues` table is created, the program loads the table with data representing software bug reports. It then queries the data using the global secondary indexes. Finally, the program deletes the `Issues` table.

For step-by-step instructions for testing the following sample, see [.NET code examples \(p. 276\)](#).

### Example

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 */

```

```

 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
using System;
using System.Collections.Generic;
using System.Linq;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.DataModel;
using Amazon.DynamoDBv2.DocumentModel;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;
using Amazon.SecurityToken;

namespace com.amazonaws.codesamples
{
    class LowLevelGlobalSecondaryIndexExample
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();
        public static String tableName = "Issues";

        public static void Main(string[] args)
        {
            CreateTable();
            LoadData();

            QueryIndex("CreateDateIndex");
            QueryIndex("TitleIndex");
            QueryIndex("DueDateIndex");

            DeleteTable(tableName);

            Console.WriteLine("To continue, press enter");
            Console.Read();
        }

        private static void CreateTable()
        {
            // Attribute definitions
            var attributeDefinitions = new List<AttributeDefinition>()
            {
                {new AttributeDefinition {
                    AttributeName = "IssueId", AttributeType = "S"
                }},
                {new AttributeDefinition {
                    AttributeName = "Title", AttributeType = "S"
                }},
                {new AttributeDefinition {
                    AttributeName = "CreateDate", AttributeType = "S"
                }},
                {new AttributeDefinition {
                    AttributeName = "DueDate", AttributeType = "S"
                }}
            };

            // Key schema for table
            var tableKeySchema = new List<KeySchemaElement>() {
            {
                new KeySchemaElement {
                    AttributeName= "IssueId",
                    KeyType = "HASH" //Partition key
                }
            },
            {

```

```

        new KeySchemaElement {
            AttributeName = "Title",
            KeyType = "RANGE" //Sort key
        }
    }
};

// Initial provisioned throughput settings for the indexes
var ptIndex = new ProvisionedThroughput
{
    ReadCapacityUnits = 1L,
    WriteCapacityUnits = 1L
};

// CreateDateIndex
var createDateIndex = new GlobalSecondaryIndex()
{
    IndexName = "CreateDateIndex",
    ProvisionedThroughput = ptIndex,
    KeySchema = [
        new KeySchemaElement {
            AttributeName = "CreateDate", KeyType = "HASH" //Partition key
        },
        new KeySchemaElement {
            AttributeName = "IssueId", KeyType = "RANGE" //Sort key
        }
    ],
    Projection = new Projection
    {
        ProjectionType = "INCLUDE",
        NonKeyAttributes = [
            "Description", "Status"
        ]
    }
};

// TitleIndex
var titleIndex = new GlobalSecondaryIndex()
{
    IndexName = "TitleIndex",
    ProvisionedThroughput = ptIndex,
    KeySchema = [
        new KeySchemaElement {
            AttributeName = "Title", KeyType = "HASH" //Partition key
        },
        new KeySchemaElement {
            AttributeName = "IssueId", KeyType = "RANGE" //Sort key
        }
    ],
    Projection = new Projection
    {
        ProjectionType = "KEYS_ONLY"
    }
};

// DueDateIndex
var dueDateIndex = new GlobalSecondaryIndex()
{
    IndexName = "DueDateIndex",
    ProvisionedThroughput = ptIndex,
    KeySchema = [
        new KeySchemaElement {
            AttributeName = "DueDate",
            KeyType = "HASH" //Partition key
        }
    ],
}
;
```

```

        Projection = new Projection
        {
            ProjectionType = "ALL"
        };
    }

    var createTableRequest = new CreateTableRequest
    {
        TableName = tableName,
        ProvisionedThroughput = new ProvisionedThroughput
        {
            ReadCapacityUnits = (long)1,
            WriteCapacityUnits = (long)1
        },
        AttributeDefinitions = attributeDefinitions,
        KeySchema = tableKeySchema,
        GlobalSecondaryIndexes = {
            createDateIndex, titleIndex, dueDateIndex
        }
    };

    Console.WriteLine("Creating table " + tableName + "...");
    client.CreateTable(createTableRequest);

    WaitUntilTableReady(tableName);
}

private static void LoadData()
{
    Console.WriteLine("Loading data into table " + tableName + "...");

    // IssueId, Title,
    // Description,
    // CreateDate, LastUpdateDate, DueDate,
    // Priority, Status

    putItem("A-101", "Compilation error",
        "Can't compile Project X - bad version number. What does this mean?",
        "2013-11-01", "2013-11-02", "2013-11-10",
        1, "Assigned");

    putItem("A-102", "Can't read data file",
        "The main data file is missing, or the permissions are incorrect",
        "2013-11-01", "2013-11-04", "2013-11-30",
        2, "In progress");

    putItem("A-103", "Test failure",
        "Functional test of Project X produces errors",
        "2013-11-01", "2013-11-02", "2013-11-10",
        1, "In progress");

    putItem("A-104", "Compilation error",
        "Variable 'messageCount' was not initialized.",
        "2013-11-15", "2013-11-16", "2013-11-30",
        3, "Assigned");

    putItem("A-105", "Network issue",
        "Can't ping IP address 127.0.0.1. Please fix this.",
        "2013-11-15", "2013-11-16", "2013-11-19",
        5, "Assigned");
}

private static void putItem(
    String issueId, String title,

```

```

        String description,
        String createDate, String lastUpdateDate, String dueDate,
        Int32 priority, String status)
    {
        Dictionary<String, AttributeValue> item = new Dictionary<string,
AttributeValue>();

        item.Add("IssueId", new AttributeValue
        {
            S = issueId
        });
        item.Add("Title", new AttributeValue
        {
            S = title
        });
        item.Add("Description", new AttributeValue
        {
            S = description
        });
        item.Add("CreateDate", new AttributeValue
        {
            S = createDate
        });
        item.Add("LastUpdateDate", new AttributeValue
        {
            S = lastUpdateDate
        });
        item.Add("DueDate", new AttributeValue
        {
            S = dueDate
        });
        item.Add("Priority", new AttributeValue
        {
            N = priority.ToString()
        });
        item.Add("Status", new AttributeValue
        {
            S = status
        });

        try
        {
            client.PutItem(new PutItemRequest
            {
                TableName = tableName,
                Item = item
            });
        }
        catch (Exception e)
        {
            Console.WriteLine(e.ToString());
        }
    }

    private static void QueryIndex(string indexName)
    {
        Console.WriteLine
        ("*****\nQuerying index " + indexName + "...");

        QueryRequest queryRequest = new QueryRequest
        {
            TableName = tableName,
            IndexName = indexName,
            ScanIndexForward = true
        };
    }
}

```

```

        String keyConditionExpression;
        Dictionary<string, AttributeValue> expressionAttributeValues = new
Dictionary<string, AttributeValue>();

        if (indexName == "CreateDateIndex")
{
    Console.WriteLine("Issues filed on 2013-11-01\n");

    keyConditionExpression = "CreateDate = :v_date and
begins_with(IssueId, :v_issue)";
    expressionAttributeValues.Add(":v_date", new AttributeValue
{
        S = "2013-11-01"
});
    expressionAttributeValues.Add(":v_issue", new AttributeValue
{
        S = "A-"
});
}
else if (indexName == "TitleIndex")
{
    Console.WriteLine("Compilation errors\n");

    keyConditionExpression = "Title = :v_title and
begins_with(IssueId, :v_issue)";
    expressionAttributeValues.Add(":v_title", new AttributeValue
{
        S = "Compilation error"
});
    expressionAttributeValues.Add(":v_issue", new AttributeValue
{
        S = "A-"
});

    // Select
    queryRequest.Select = "ALL_PROJECTED_ATTRIBUTES";
}
else if (indexName == "DueDateIndex")
{
    Console.WriteLine("Items that are due on 2013-11-30\n");

    keyConditionExpression = "DueDate = :v_date";
    expressionAttributeValues.Add(":v_date", new AttributeValue
{
        S = "2013-11-30"
});

    // Select
    queryRequest.Select = "ALL_PROJECTED_ATTRIBUTES";
}
else
{
    Console.WriteLine("\nNo valid index name provided");
    return;
}

queryRequest.KeyConditionExpression = keyConditionExpression;
queryRequest.ExpressionAttributeValues = expressionAttributeValues;

var result = client.Query(queryRequest);
var items = result.Items;
foreach (var currentItem in items)
{
    foreach (string attr in currentItem.Keys)

```

```

        {
            if (attr == "Priority")
            {
                Console.WriteLine(attr + "----> " + currentItem[attr].N);
            }
            else
            {
                Console.WriteLine(attr + "----> " + currentItem[attr].S);
            }
        }
        Console.WriteLine();
    }
}

private static void DeleteTable(string tableName)
{
    Console.WriteLine("Deleting table " + tableName + "...");
    client.DeleteTable(new DeleteTableRequest
    {
        TableName = tableName
    });
    WaitForTableToDelete(tableName);
}

private static void WaitUntilTableReady(string tableName)
{
    string status = null;
    // Let us wait until table is created. Call DescribeTable.
    do
    {
        System.Threading.Thread.Sleep(5000); // Wait 5 seconds.
        try
        {
            var res = client.DescribeTable(new DescribeTableRequest
            {
                TableName = tableName
            });

            Console.WriteLine("Table name: {0}, status: {1}",
                res.Table.TableName,
                res.Table.TableStatus);
            status = res.Table.TableStatus;
        }
        catch (ResourceNotFoundException)
        {
            // DescribeTable is eventually consistent. So you might
            // get resource not found. So we handle the potential exception.
        }
    } while (status != "ACTIVE");
}

private static void WaitForTableToDelete(string tableName)
{
    bool tablePresent = true;

    while (tablePresent)
    {
        System.Threading.Thread.Sleep(5000); // Wait 5 seconds.
        try
        {
            var res = client.DescribeTable(new DescribeTableRequest
            {
                TableName = tableName
            });

            Console.WriteLine("Table name: {0}, status: {1}",
                res.Table.TableName,
                res.Table.TableStatus);
        }
        catch (ResourceNotFoundException)
        {
            // DescribeTable is eventually consistent. So you might
            // get resource not found. So we handle the potential exception.
        }
    }
}

```

```
        res.Table.TableName,
        res.Table.TableStatus);
    }
    catch (ResourceNotFoundException)
    {
        tablePresent = false;
    }
}
}
```

## Working with Global Secondary Indexes: AWS CLI

You can use the AWS CLI to create an Amazon DynamoDB table with one or more global secondary indexes, describe the indexes on the table, and perform queries using the indexes.

### Topics

- [Create a table with a Global Secondary Index \(p. 538\)](#)
- [Add a Global Secondary Index to an existing table \(p. 539\)](#)
- [Describe a table with a Global Secondary Index \(p. 539\)](#)
- [Query a Global Secondary Index \(p. 539\)](#)

### Create a table with a Global Secondary Index

Global secondary indexes may be created at the same time you create a table. To do this, use the `--create-table` parameter and provide your specifications for one or more global secondary indexes. The following example creates a table named `GameScores` with a global secondary index called `GameTitleIndex`. The base table has a partition key of `UserId` and a sort key of `GameTitle`, allowing you to find an individual user's best score for a specific game efficiently, whereas the GSI has a partition key of `GameTitle` and a sort key of `TopScore`, allowing you to quickly find the overall highest score for a particular game.

```
aws dynamodb create-table \
--table-name GameScores \
--attribute-definitions AttributeName=UserId,AttributeType=S \
    AttributeName=GameTitle,AttributeType=S \
    AttributeName=TopScore,AttributeType=N \
--key-schema AttributeName=UserId,KeyType=HASH \
    AttributeName=GameTitle,KeyType=RANGE \
--provisioned-throughput ReadCapacityUnits=10,WriteCapacityUnits=5 \
--global-secondary-indexes \
"[
{
    \"IndexName\": \"GameTitleIndex\",
    \"KeySchema\": [{\"AttributeName\":\"GameTitle\", \"KeyType\":\"HASH\"},
                  {"AttributeName":"TopScore", "KeyType": "RANGE"}],
    \"Projection\":{
        \"ProjectionType\":\"INCLUDE\",
        \"NonKeyAttributes\":[\"UserId\"]
    },
    \"ProvisionedThroughput\": {
        \"ReadCapacityUnits\": 10,
        \"WriteCapacityUnits\": 5
    }
}
]"
```

You must wait until DynamoDB creates the table and sets the table status to **ACTIVE**. After that, you can begin putting data items into the table. You can use [describe-table](#) to determine the status of the table creation.

## Add a Global Secondary Index to an existing table

Global secondary indexes may also be added or modified after table creation. To do this, use the `update-table` parameter and provide your specifications for one or more global secondary indexes. The following example uses the same schema as the previous example, but assumes that the table has already been created and we're adding the GSI later.

```
aws dynamodb update-table \
--table-name GameScores \
--attribute-definitions AttributeName=TopScore,AttributeType=N \
--global-secondary-index-updates \
"[
{
    \"Create\": {
        \"IndexName\": \"GameTitleIndex\",
        \"KeySchema\": [ {\"AttributeName\":\"GameTitle\", \"KeyType\":\"HASH\"},
                      {\"AttributeName\":\"TopScore\", \"KeyType\":\"RANGE\"} ],
        \"Projection\":{
            \"ProjectionType\":\"INCLUDE\",
            \"NonKeyAttributes\":[ \"UserId\" ]
        }
    }
}]"
```

## Describe a table with a Global Secondary Index

To get information about local secondary indexes on a table, use the `describe-table` parameter. For each index, you can access its name, key schema, and projected attributes.

```
aws dynamodb describe-table --table-name GameScores
```

## Query a Global Secondary Index

You can use the `query` operation on a global secondary index in much the same way that you query a table. You must specify the index name, the query criteria for the index sort key, and the attributes that you want to return. In this example, the index is `GameTitleIndex` and the index sort key is `GameTitle`.

The only attributes returned are those that have been projected into the index. You could modify this query to select non-key attributes too, but this would require table fetch activity that is relatively expensive. For more information about table fetches, see [Attribute projections \(p. 503\)](#).

```
aws dynamodb query \
--index-name GameTitleIndex \
--key-condition-expression "GameTitle = :v_game" \
--expression-attribute-values '{":v_game":{"S":"Alien Adventure"} }'
```

## Local Secondary Indexes

Some applications only need to query data using the base table's primary key. However, there might be situations where an alternative sort key would be helpful. To give your application a choice of sort keys, you can create one or more local secondary indexes on an Amazon DynamoDB table and issue `Query` or `Scan` requests against these indexes.

### Topics

- [Scenario: Using a Local Secondary Index \(p. 540\)](#)
- [Attribute projections \(p. 542\)](#)
- [Creating a Local Secondary Index \(p. 544\)](#)
- [Reading data from a Local Secondary Index \(p. 544\)](#)
- [Item writes and Local Secondary Indexes \(p. 545\)](#)
- [Provisioned throughput considerations for Local Secondary Indexes \(p. 546\)](#)
- [Storage considerations for Local Secondary Indexes \(p. 547\)](#)
- [Item collections in Local Secondary Indexes \(p. 548\)](#)
- [Working with Local Secondary Indexes: Java \(p. 551\)](#)
- [Working with Local Secondary Indexes: .NET \(p. 560\)](#)
- [Working with Local Secondary Indexes: AWS CLI \(p. 575\)](#)

## Scenario: Using a Local Secondary Index

As an example, consider the `Thread` table that is defined in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#). This table is useful for an application such as the [AWS discussion forums](#). The following diagram shows how the items in the table would be organized. (Not all of the attributes are shown.)

Thread				
ForumName	Subject	LastPostDateTime	Replies	
"S3"	"aaa"	"2015-03-15:17:24:31"	12	...
"S3"	"bbb"	"2015-01-22:23:18:01"	3	...
"S3"	"ccc"	"2015-02-31:13:14:21"	4	...
"S3"	"ddd"	"2015-01-03:09:21:11"	9	...
"EC2"	"yyy"	"2015-02-12:11:07:56"	18	...
"EC2"	"zzz"	"2015-01-18:07:33:42"	0	...
"RDS"	"rrr"	"2015-01-19:01:13:24"	3	...
"RDS"	"sss"	"2015-03-11:06:53:00"	11	...
"RDS"	"ttt"	"2015-10-22:12:19:44"	5	...
***	***	***	***	***

DynamoDB stores all of the items with the same partition key value contiguously. In this example, given a particular `ForumName`, a `Query` operation could immediately locate all of the threads for that forum. Within a group of items with the same partition key value, the items are sorted by sort key value. If the sort key (`Subject`) is also provided in the query, DynamoDB can narrow down the results that are returned—for example, returning all of the threads in the "S3" forum that have a `Subject` beginning with the letter "a".

Some requests might require more complex data access patterns. For example:

- Which forum threads get the most views and replies?
- Which thread in a particular forum has the largest number of messages?
- How many threads were posted in a particular forum within a particular time period?

To answer these questions, the `Query` action would not be sufficient. Instead, you would have to `Scan` the entire table. For a table with millions of items, this would consume a large amount of provisioned read throughput and take a long time to complete.

However, you can specify one or more local secondary indexes on non-key attributes, such as `Replies` or `LastPostDateTime`.

A *local secondary index* maintains an alternate sort key for a given partition key value. A local secondary index also contains a copy of some or all of the attributes from its base table. You specify which attributes are projected into the local secondary index when you create the table. The data in a local secondary index is organized by the same partition key as the base table, but with a different sort key. This lets you access data items efficiently across this different dimension. For greater query or scan flexibility, you can create up to five local secondary indexes per table.

Suppose that an application needs to find all of the threads that have been posted within the last three months in a particular forum. Without a local secondary index, the application would have to `Scan` the entire `Thread` table and discard any posts that were not within the specified time frame. With a local secondary index, a `Query` operation could use `LastPostDateTime` as a sort key and find the data quickly.

The following diagram shows a local secondary index named `LastPostIndex`. Note that the partition key is the same as that of the `Thread` table, but the sort key is `LastPostDateTime`.

## *LastPostIndex*

<i>ForumName</i>	<i>LastPostDateTime</i>	<i>Subject</i>
“S3”	“2015-01-03:09:21:11”	“ddd”
“S3”	“2015-01-22:23:18:01”	“bbb”
“S3”	“2015-02-31:13:14:21”	“ccc”
“S3”	“2015-03-15:17:24:31”	“aaa”
“EC2”	“2015-01-18:07:33:42”	“zzz”
“EC2”	“2015-02-12:11:07:56”	“yyy”
“RDS”	“2015-01-19:01:13:24”	“rr”
“RDS”	“2015-02-22:12:19:44”	“ttt”
“RDS”	“2015-03-11:06:53:00”	“sss”
***	***	***

Every local secondary index must meet the following conditions:

- The partition key is the same as that of its base table.
- The sort key consists of exactly one scalar attribute.

- The sort key of the base table is projected into the index, where it acts as a non-key attribute.

In this example, the partition key is `ForumName` and the sort key of the local secondary index is `LastPostDateTime`. In addition, the sort key value from the base table (in this example, `Subject`) is projected into the index, but it is not a part of the index key. If an application needs a list that is based on `ForumName` and `LastPostDateTime`, it can issue a `Query` request against `LastPostIndex`. The query results are sorted by `LastPostDateTime`, and can be returned in ascending or descending order. The query can also apply key conditions, such as returning only items that have a `LastPostDateTime` within a particular time span.

Every local secondary index automatically contains the partition and sort keys from its base table; you can optionally project non-key attributes into the index. When you query the index, DynamoDB can retrieve these projected attributes efficiently. When you query a local secondary index, the query can also retrieve attributes that are *not* projected into the index. DynamoDB automatically fetches these attributes from the base table, but at a greater latency and with higher provisioned throughput costs.

For any local secondary index, you can store up to 10 GB of data per distinct partition key value. This figure includes all of the items in the base table, plus all of the items in the indexes, that have the same partition key value. For more information, see [Item collections in Local Secondary Indexes \(p. 548\)](#).

## Attribute projections

With `LastPostIndex`, an application could use `ForumName` and `LastPostDateTime` as query criteria. However, to retrieve any additional attributes, DynamoDB must perform additional read operations against the `Thread` table. These extra reads are known as *fetches*, and they can increase the total amount of provisioned throughput required for a query.

Suppose that you wanted to populate a webpage with a list of all the threads in "S3" and the number of replies for each thread, sorted by the last reply date/time beginning with the most recent reply. To populate this list, you would need the following attributes:

- `Subject`
- `Replies`
- `LastPostDateTime`

The most efficient way to query this data and to avoid fetch operations would be to project the `Replies` attribute from the table into the local secondary index, as shown in this diagram.

## LastPostIndex

ForumName	LastPostDateTime	Subject	Replies
"S3"	"2015-01-03:09:21:11"	"ddd"	9
	"2015-01-22:23:18:01"	"bbb"	3
	"2015-02-31:13:14:21"	"ccc"	4
	"2015-03-15:17:24:31"	"aaa"	12
"EC2"	"2015-01-18:07:33:42"	"zzz"	0
	"2015-02-12:11:07:56"	"yyy"	18
"RDS"	"2015-01-19:01:13:24"	"rrr"	3
	"2015-02-22:12:19:44"	"ttt"	5
	"2015-03-11:06:53:00"	"sss"	11
...	...	...	...

A *projection* is the set of attributes that is copied from a table into a secondary index. The partition key and sort key of the table are always projected into the index; you can project other attributes to support your application's query requirements. When you query an index, Amazon DynamoDB can access any attribute in the projection as if those attributes were in a table of their own.

When you create a secondary index, you need to specify the attributes that will be projected into the index. DynamoDB provides three different options for this:

- **KEYS\_ONLY** – Each item in the index consists only of the table partition key and sort key values, plus the index key values. The **KEYS\_ONLY** option results in the smallest possible secondary index.
- **INCLUDE** – In addition to the attributes described in **KEYS\_ONLY**, the secondary index will include other non-key attributes that you specify.
- **ALL** – The secondary index includes all of the attributes from the source table. Because all of the table data is duplicated in the index, an **ALL** projection results in the largest possible secondary index.

In the previous diagram, the non-key attribute **Replies** is projected into **LastPostIndex**. An application can query **LastPostIndex** instead of the full **Thread** table to populate a webpage with **Subject**, **Replies**, and **LastPostDateTime**. If any other non-key attributes are requested, DynamoDB would need to fetch those attributes from the **Thread** table.

From an application's point of view, fetching additional attributes from the base table is automatic and transparent, so there is no need to rewrite any application logic. However, such fetching can greatly reduce the performance advantage of using a local secondary index.

When you choose the attributes to project into a local secondary index, you must consider the tradeoff between provisioned throughput costs and storage costs:

- If you need to access just a few attributes with the lowest possible latency, consider projecting only those attributes into a local secondary index. The smaller the index, the less that it costs to store it, and the less your write costs are. If there are attributes that you occasionally need to fetch, the cost for provisioned throughput may well outweigh the longer-term cost of storing those attributes.
- If your application frequently accesses some non-key attributes, you should consider projecting those attributes into a local secondary index. The additional storage costs for the local secondary index offset the cost of performing frequent table scans.
- If you need to access most of the non-key attributes on a frequent basis, you can project these attributes—or even the entire base table—into a local secondary index. This gives you maximum flexibility and lowest provisioned throughput consumption, because no fetching would be required. However, your storage cost would increase, or even double if you are projecting all attributes.
- If your application needs to query a table infrequently, but must perform many writes or updates against the data in the table, consider projecting *KEYS\_ONLY*. The local secondary index would be of minimal size, but would still be available when needed for query activity.

## Creating a Local Secondary Index

To create one or more local secondary indexes on a table, use the `LocalSecondaryIndexes` parameter of the `CreateTable` operation. Local secondary indexes on a table are created when the table is created. When you delete a table, any local secondary indexes on that table are also deleted.

You must specify one non-key attribute to act as the sort key of the local secondary index. The attribute that you choose must be a scalar `String`, `Number`, or `Binary`. Other scalar types, document types, and set types are not allowed. For a complete list of data types, see [Data types \(p. 13\)](#).

### Important

For tables with local secondary indexes, there is a 10 GB size limit per partition key value. A table with local secondary indexes can store any number of items, as long as the total size for any one partition key value does not exceed 10 GB. For more information, see [Item collection size limit \(p. 550\)](#).

You can project attributes of any data type into a local secondary index. This includes scalars, documents, and sets. For a complete list of data types, see [Data types \(p. 13\)](#).

## Reading data from a Local Secondary Index

You can retrieve items from a local secondary index using the `Query` and `Scan` operations. The `GetItem` and `BatchGetItem` operations can't be used on a local secondary index.

### Querying a Local Secondary Index

In a DynamoDB table, the combined partition key value and sort key value for each item must be unique. However, in a local secondary index, the sort key value does not need to be unique for a given partition key value. If there are multiple items in the local secondary index that have the same sort key value, a `Query` operation returns all of the items that have the same partition key value. In the response, the matching items are not returned in any particular order.

You can query a local secondary index using either eventually consistent or strongly consistent reads. To specify which type of consistency you want, use the `ConsistentRead` parameter of the `Query` operation. A strongly consistent read from a local secondary index always returns the latest updated values. If the query needs to fetch additional attributes from the base table, those attributes will be consistent with respect to the index.

## Example

Consider the following data returned from a `Query` that requests data from the discussion threads in a particular forum.

```
{  
    "TableName": "Thread",  
    "IndexName": "LastPostIndex",  
    "ConsistentRead": false,  
    "ProjectionExpression": "Subject, LastPostDateTime, Replies, Tags",  
    "KeyConditionExpression":  
        "ForumName = :v_forum and LastPostDateTime between :v_start and :v_end",  
    "ExpressionAttributeValues": {  
        ":v_start": {"S": "2015-08-31T00:00:00.000Z"},  
        ":v_end": {"S": "2015-11-31T00:00:00.000Z"},  
        ":v_forum": {"S": "EC2"}  
    }  
}
```

In this query:

- DynamoDB accesses `LastPostIndex`, using the `ForumName` partition key to locate the index items for "EC2". All of the index items with this key are stored adjacent to each other for rapid retrieval.
- Within this forum, DynamoDB uses the index to look up the keys that match the specified `LastPostDateTime` condition.
- Because the `Replies` attribute is projected into the index, DynamoDB can retrieve this attribute without consuming any additional provisioned throughput.
- The `Tags` attribute is not projected into the index, so DynamoDB must access the `Thread` table and fetch this attribute.
- The results are returned, sorted by `LastPostDateTime`. The index entries are sorted by partition key value and then by sort key value, and `Query` returns them in the order they are stored. (You can use the `ScanIndexForward` parameter to return the results in descending order.)

Because the `Tags` attribute is not projected into the local secondary index, DynamoDB must consume additional read capacity units to fetch this attribute from the base table. If you need to run this query often, you should project `Tags` into `LastPostIndex` to avoid fetching from the base table. However, if you needed to access `Tags` only occasionally, the additional storage cost for projecting `Tags` into the index might not be worthwhile.

## Scanning a Local Secondary Index

You can use `Scan` to retrieve all of the data from a local secondary index. You must provide the base table name and the index name in the request. With a `Scan`, DynamoDB reads all of the data in the index and returns it to the application. You can also request that only some of the data be returned, and that the remaining data should be discarded. To do this, use the `FilterExpression` parameter of the `Scan` API. For more information, see [Filter expressions for scan \(p. 446\)](#).

## Item writes and Local Secondary Indexes

DynamoDB automatically keeps all local secondary indexes synchronized with their respective base tables. Applications never write directly to an index. However, it is important that you understand the implications of how DynamoDB maintains these indexes.

When you create a local secondary index, you specify an attribute to serve as the sort key for the index. You also specify a data type for that attribute. This means that whenever you write an item to the base table, if the item defines an index key attribute, its type must match the index key schema's data type. In the case of `LastPostIndex`, the `LastPostDateTime` sort key in the index is defined as a `String` data type. If you try to add an item to the `Thread` table and specify a different data type for

If you specify a `LastPostDateTime` (such as `Number`), DynamoDB returns a `ValidationException` because of the data type mismatch.

There is no requirement for a one-to-one relationship between the items in a base table and the items in a local secondary index. In fact, this behavior can be advantageous for many applications.

A table with many local secondary indexes incurs higher costs for write activity than tables with fewer indexes. For more information, see [Provisioned throughput considerations for Local Secondary Indexes \(p. 546\)](#).

**Important**

For tables with local secondary indexes, there is a 10 GB size limit per partition key value. A table with local secondary indexes can store any number of items, as long as the total size for any one partition key value does not exceed 10 GB. For more information, see [Item collection size limit \(p. 550\)](#).

## Provisioned throughput considerations for Local Secondary Indexes

When you create a table in DynamoDB, you provision read and write capacity units for the table's expected workload. That workload includes read and write activity on the table's local secondary indexes.

To view the current rates for provisioned throughput capacity, see [Amazon DynamoDB pricing](#).

### Read capacity units

When you query a local secondary index, the number of read capacity units consumed depends on how the data is accessed.

As with table queries, an index query can use either eventually consistent or strongly consistent reads depending on the value of `ConsistentRead`. One strongly consistent read consumes one read capacity unit; an eventually consistent read consumes only half of that. Thus, by choosing eventually consistent reads, you can reduce your read capacity unit charges.

For index queries that request only index keys and projected attributes, DynamoDB calculates the provisioned read activity in the same way as it does for queries against tables. The only difference is that the calculation is based on the sizes of the index entries, rather than the size of the item in the base table. The number of read capacity units is the sum of all projected attribute sizes across all of the items returned; the result is then rounded up to the next 4 KB boundary. For more information about how DynamoDB calculates provisioned throughput usage, see [Managing settings on DynamoDB provisioned capacity tables \(p. 286\)](#).

For index queries that read attributes that are not projected into the local secondary index, DynamoDB needs to fetch those attributes from the base table, in addition to reading the projected attributes from the index. These fetches occur when you include any non-projected attributes in the `Select` or `ProjectionExpression` parameters of the `Query` operation. Fetching causes additional latency in query responses, and it also incurs a higher provisioned throughput cost: In addition to the reads from the local secondary index described previously, you are charged for read capacity units for every base table item fetched. This charge is for reading each entire item from the table, not just the requested attributes.

The maximum size of the results returned by a `Query` operation is 1 MB. This includes the sizes of all the attribute names and values across all of the items returned. However, if a `Query` against a local secondary index causes DynamoDB to fetch item attributes from the base table, the maximum size of the data in the results might be lower. In this case, the result size is the sum of:

- The size of the matching items in the index, rounded up to the next 4 KB.
- The size of each matching item in the base table, with each item individually rounded up to the next 4 KB.

Using this formula, the maximum size of the results returned by a Query operation is still 1 MB.

For example, consider a table where the size of each item is 300 bytes. There is a local secondary index on that table, but only 200 bytes of each item is projected into the index. Now suppose that you `Query` this index, that the query requires table fetches for each item, and that the query returns 4 items. DynamoDB sums up the following:

- The size of the matching items in the index:  $200 \text{ bytes} \times 4 \text{ items} = 800 \text{ bytes}$ ; this is then rounded up to 4 KB.
- The size of each matching item in the base table:  $(300 \text{ bytes, rounded up to 4 KB}) \times 4 \text{ items} = 16 \text{ KB}$ .

The total size of the data in the result is therefore 20 KB.

## Write capacity units

When an item in a table is added, updated, or deleted, updating the local secondary indexes consumes provisioned write capacity units for the table. The total provisioned throughput cost for a write is the sum of write capacity units consumed by writing to the table and those consumed by updating the local secondary indexes.

The cost of writing an item to a local secondary index depends on several factors:

- If you write a new item to the table that defines an indexed attribute, or you update an existing item to define a previously undefined indexed attribute, one write operation is required to put the item into the index.
- If an update to the table changes the value of an indexed key attribute (from A to B), two writes are required: one to delete the previous item from the index and another write to put the new item into the index.
- If an item was present in the index, but a write to the table caused the indexed attribute to be deleted, one write is required to delete the old item projection from the index.
- If an item is not present in the index before or after the item is updated, there is no additional write cost for the index.

All of these factors assume that the size of each item in the index is less than or equal to the 1 KB item size for calculating write capacity units. Larger index entries require additional write capacity units. You can minimize your write costs by considering which attributes your queries need to return and projecting only those attributes into the index.

## Storage considerations for Local Secondary Indexes

When an application writes an item to a table, DynamoDB automatically copies the correct subset of attributes to any local secondary indexes in which those attributes should appear. Your AWS account is charged for storage of the item in the base table and also for storage of attributes in any local secondary indexes on that table.

The amount of space used by an index item is the sum of the following:

- The size in bytes of the base table primary key (partition key and sort key)
- The size in bytes of the index key attribute
- The size in bytes of the projected attributes (if any)
- 100 bytes of overhead per index item

To estimate the storage requirements for a local secondary index, you can estimate the average size of an item in the index and then multiply by the number of items in the base table.

If a table contains an item where a particular attribute is not defined, but that attribute is defined as an index sort key, then DynamoDB does not write any data for that item to the index.


## Item collections in Local Secondary Indexes

### Note

This section pertains only to tables that have local secondary indexes.

In DynamoDB, an *item collection* is any group of items that have the same partition key value in a table and all of its local secondary indexes. In the examples used throughout this section, the partition key for the `Thread` table is `ForumName`, and the partition key for `LastPostIndex` is also `ForumName`. All the table and index items with the same `ForumName` are part of the same item collection. For example, in the `Thread` table and the `LastPostIndex` local secondary index, there is an item collection for forum `EC2` and a different item collection for forum `RDS`.

The following diagram shows the item collection for forum `S3`.



In this diagram, the item collection consists of all the items in `Thread` and `LastPostIndex` where the `ForumName` partition key value is "S3". If there were other local secondary indexes on the table, any items in those indexes with `ForumName` equal to "S3" would also be part of the item collection.

You can use any of the following operations in DynamoDB to return information about item collections:

- `BatchWriteItem`

- `DeleteItem`
- `PutItem`
- `UpdateItem`
- `TransactWriteItems`

Each of these operations supports the `ReturnItemCollectionMetrics` parameter. When you set this parameter to `SIZE`, you can view information about the size of each item collection in the index.

### Example

The following is an example from the output of an `UpdateItem` operation on the `Thread` table, with `ReturnItemCollectionMetrics` set to `SIZE`. The item that was updated had a `ForumName` value of "EC2", so the output includes information about that item collection.

```
{  
    ItemCollectionMetrics: {  
        ItemCollectionKey: {  
            ForumName: "EC2"  
        },  
        SizeEstimateRangeGB: [0.0, 1.0]  
    }  
}
```

The `SizeEstimateRangeGB` object shows that the size of this item collection is between 0 and 1 GB. DynamoDB periodically updates this size estimate, so the numbers might be different next time the item is modified.

### Item collection size limit

The maximum size of any item collection is 10 GB. This limit does not apply to tables without local secondary indexes. Only tables that have one or more local secondary indexes are affected.

If an item collection exceeds the 10 GB limit, DynamoDB returns an `ItemCollectionSizeLimitExceededException`, and you won't be able to add more items to the item collection or increase the sizes of items that are in the item collection. (Read and write operations that shrink the size of the item collection are still allowed.) You can still add items to other item collections.

To reduce the size of an item collection, you can do one of the following:

- Delete any unnecessary items with the partition key value in question. When you delete these items from the base table, DynamoDB also removes any index entries that have the same partition key value.
- Update the items by removing attributes or by reducing the size of the attributes. If these attributes are projected into any local secondary indexes, DynamoDB also reduces the size of the corresponding index entries.
- Create a new table with the same partition key and sort key, and then move items from the old table to the new table. This might be a good approach if a table has historical data that is infrequently accessed. You might also consider archiving this historical data to Amazon Simple Storage Service (Amazon S3).

When the total size of the item collection drops below 10 GB, you can once again add items with the same partition key value.

We recommend as a best practice that you instrument your application to monitor the sizes of your item collections. One way to do so is to set the `ReturnItemCollectionMetrics` parameter to

`SIZE` whenever you use `BatchWriteItem`, `DeleteItem`, `PutItem`, or `UpdateItem`. Your application should examine the `ReturnItemCollectionMetrics` object in the output and log an error message whenever an item collection exceeds a user-defined limit (8 GB, for example). Setting a limit that is less than 10 GB would provide an early warning system so you know that an item collection is approaching the limit in time to do something about it.

## Item collections and partitions

The table and index data for each item collection is stored in a single partition. Referring to the `Thread` table example, all of the base table and index items with the same `ForumName` attribute would be stored in the same partition. The "S3" item collection would be stored on one partition, "EC2" in another partition, and "RDS" in a third partition.

You should design your applications so that table data is evenly distributed across distinct partition key values. For tables with local secondary indexes, your applications should not create "hot spots" of read and write activity within a single item collection on a single partition.

## Working with Local Secondary Indexes: Java

You can use the AWS SDK for Java Document API to create an Amazon DynamoDB table with one or more local secondary indexes, describe the indexes on the table, and perform queries using the indexes.

The following are the common steps for table operations using the AWS SDK for Java Document API.

1. Create an instance of the `DynamoDB` class.
2. Provide the required and optional parameters for the operation by creating the corresponding request objects.
3. Call the appropriate method provided by the client that you created in the preceding step.

### Topics

- [Create a table with a Local Secondary Index \(p. 551\)](#)
- [Describe a table with a Local Secondary Index \(p. 553\)](#)
- [Query a Local Secondary Index \(p. 553\)](#)
- [Example: Local Secondary Indexes using the Java document API \(p. 554\)](#)

## Create a table with a Local Secondary Index

Local secondary indexes must be created at the same time you create a table. To do this, use the `createTable` method and provide your specifications for one or more local secondary indexes. The following Java code example creates a table to hold information about songs in a music collection. The partition key is `Artist` and the sort key is `SongTitle`. A secondary index, `AlbumTitleIndex`, facilitates queries by album title.

The following are the steps to create a table with a local secondary index, using the DynamoDB document API.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `CreateTableRequest` class to provide the request information.

You must provide the table name, its primary key, and the provisioned throughput values. For the local secondary index, you must provide the index name, the name and data type for the index sort key, the key schema for the index, and the attribute projection.

3. Call the `createTable` method by providing the request object as a parameter.

The following Java code example demonstrates the preceding steps. The code creates a table (`Music`) with a secondary index on the `AlbumTitle` attribute. The table partition key and sort key, plus the index sort key, are the only attributes projected into the index.

```

AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

String tableName = "Music";

CreateTableRequest createTableRequest = new CreateTableRequest().withTableName(tableName);

//ProvisionedThroughput
createTableRequest.setProvisionedThroughput(new
    ProvisionedThroughput().withReadCapacityUnits((long)5).withWriteCapacityUnits((long)5));

//AttributeDefinitions
ArrayList<AttributeDefinition> attributeDefinitions= new ArrayList<AttributeDefinition>();
attributeDefinitions.add(new
    AttributeDefinition().withAttributeName("Artist").withAttributeType("S"));
attributeDefinitions.add(new
    AttributeDefinition().withAttributeName("SongTitle").withAttributeType("S"));
attributeDefinitions.add(new
    AttributeDefinition().withAttributeName("AlbumTitle").withAttributeType("S"));

createTableRequest.setAttributeDefinitions(attributeDefinitions);

//KeySchema
ArrayList<KeySchemaElement> tableKeySchema = new ArrayList<KeySchemaElement>();
tableKeySchema.add(new
    KeySchemaElement().withAttributeName("Artist").withKeyType(KeyType.HASH)); //Partition
key
tableKeySchema.add(new
    KeySchemaElement().withAttributeName("SongTitle").withKeyType(KeyType.RANGE)); //Sort key

createTableRequest.setKeySchema(tableKeySchema);

ArrayList<KeySchemaElement> indexKeySchema = new ArrayList<KeySchemaElement>();
indexKeySchema.add(new
    KeySchemaElement().withAttributeName("Artist").withKeyType(KeyType.HASH)); //Partition
key
indexKeySchema.add(new
    KeySchemaElement().withAttributeName("AlbumTitle").withKeyType(KeyType.RANGE)); //Sort
key

Projection projection = new Projection().withProjectionType(ProjectionType.INCLUDE);
ArrayList<String> nonKeyAttributes = new ArrayList<String>();
nonKeyAttributes.add("Genre");
nonKeyAttributes.add("Year");
projection.setNonKeyAttributes(nonKeyAttributes);

LocalSecondaryIndex localSecondaryIndex = new LocalSecondaryIndex()
    .withIndexName("AlbumTitleIndex").withKeySchema(indexKeySchema).withProjection(projection);

ArrayList<LocalSecondaryIndex> localSecondaryIndexes = new
    ArrayList<LocalSecondaryIndex>();
localSecondaryIndexes.add(localSecondaryIndex);
createTableRequest.setLocalSecondaryIndexes(localSecondaryIndexes);

Table table = dynamoDB.createTable(createTableRequest);
System.out.println(table.getDescription());

```

You must wait until DynamoDB creates the table and sets the table status to ACTIVE. After that, you can begin putting data items into the table.

## Describe a table with a Local Secondary Index

To get information about local secondary indexes on a table, use the `describeTable` method. For each index, you can access its name, key schema, and projected attributes.

The following are the steps to access local secondary index information a table using the AWS SDK for Java Document API.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `Table` class. You must provide the table name.
3. Call the `describeTable` method on the `Table` object.

The following Java code example demonstrates the preceding steps.

### Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

String tableName = "Music";

Table table = dynamoDB.getTable(tableName);

TableDescription tableDescription = table.describe();

List<LocalSecondaryIndexDescription> localSecondaryIndexes
    = tableDescription.getLocalSecondaryIndexes();

// This code snippet will work for multiple indexes, even though
// there is only one index in this example.

Iterator<LocalSecondaryIndexDescription> lsiIter = localSecondaryIndexes.iterator();
while (lsiIter.hasNext()) {

    LocalSecondaryIndexDescription lsiDescription = lsiIter.next();
    System.out.println("Info for index " + lsiDescription.getIndexName() + ":");
    Iterator<KeySchemaElement> kseIter = lsiDescription.getKeySchema().iterator();
    while (kseIter.hasNext()) {
        KeySchemaElement kse = kseIter.next();
        System.out.printf("\t%s: %s\n", kse.getAttributeName(), kse.getKeyType());
    }
    Projection projection = lsiDescription.getProjection();
    System.out.println("\tThe projection type is: " + projection.getProjectionType());
    if (projection.getProjectionType().toString().equals("INCLUDE")) {
        System.out.println("\t\tThe non-key projected attributes are: " +
            projection.getNonKeyAttributes());
    }
}
```

## Query a Local Secondary Index

You can use the `Query` operation on a local secondary index in much the same way that you `Query` a table. You must specify the index name, the query criteria for the index sort key, and the attributes that you want to return. In this example, the index is `AlbumTitleIndex` and the index sort key is `AlbumTitle`.

The only attributes returned are those that have been projected into the index. You could modify this query to select non-key attributes too, but this would require table fetch activity that is relatively expensive. For more information about table fetches, see [Attribute projections \(p. 542\)](#).

The following are the steps to query a local secondary index using the AWS SDK for Java Document API.

1. Create an instance of the `DynamoDB` class.
2. Create an instance of the `Table` class. You must provide the table name.
3. Create an instance of the `Index` class. You must provide the index name.
4. Call the `query` method of the `Index` class.

The following Java code example demonstrates the preceding steps.

### Example

```
AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
DynamoDB dynamoDB = new DynamoDB(client);

String tableName = "Music";

Table table = dynamoDB.getTable(tableName);
Index index = table.getIndex("AlbumTitleIndex");

QuerySpec spec = new QuerySpec()
    .withKeyConditionExpression("Artist = :v_artist and AlbumTitle = :v_title")
    .WithValueMap(new ValueMap()
        .withString(":v_artist", "Acme Band")
        .withString(":v_title", "Songs About Life"));

ItemCollection<QueryOutcome> items = index.query(spec);

Iterator<Item> itemsIter = items.iterator();

while (itemsIter.hasNext()) {
    Item item = itemsIter.next();
    System.out.println(item.toJSONPretty());
}
```

### Example: Local Secondary Indexes using the Java document API

The following Java code example shows how to work with local secondary indexes in Amazon DynamoDB. The example creates a table named `CustomerOrders` with a partition key of `CustomerId` and a sort key of `OrderId`. There are two local secondary indexes on this table:

- `OrderCreationDateIndex` — The sort key is `OrderCreationDate`, and the following attributes are projected into the index:
  - `ProductCategory`
  - `ProductName`
  - `OrderStatus`
  - `ShipmentTrackingId`
- `IsOpenIndex` — The sort key is `IsOpen`, and all of the table attributes are projected into the index.

After the `CustomerOrders` table is created, the program loads the table with data representing customer orders. It then queries the data using the local secondary indexes. Finally, the program deletes the `CustomerOrders` table.

For step-by-step instructions for testing the following sample, see [Java code examples \(p. 274\)](#).

### Example

```
/***
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
```

```
* This file is licensed under the Apache License, Version 2.0 (the "License").  
* You may not use this file except in compliance with the License. A copy of  
* the License is located at  
*  
* http://aws.amazon.com/apache2.0/  
*  
* This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
* CONDITIONS OF ANY KIND, either express or implied. See the License for the  
* specific language governing permissions and limitations under the License.  
*/  
  
package com.amazonaws.codesamples.document;  
  
import java.util.ArrayList;  
import java.util.Iterator;  
  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;  
import com.amazonaws.services.dynamodbv2.document.DynamoDB;  
import com.amazonaws.services.dynamodbv2.document.Index;  
import com.amazonaws.services.dynamodbv2.document.Item;  
import com.amazonaws.services.dynamodbv2.document.ItemCollection;  
import com.amazonaws.services.dynamodbv2.document.PutItemOutcome;  
import com.amazonaws.services.dynamodbv2.document.QueryOutcome;  
import com.amazonaws.services.dynamodbv2.document.Table;  
import com.amazonaws.services.dynamodbv2.document.spec.QuerySpec;  
import com.amazonaws.services.dynamodbv2.document.utils.ValueMap;  
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;  
import com.amazonaws.services.dynamodbv2.model.CreateTableRequest;  
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;  
import com.amazonaws.services.dynamodbv2.model.KeyType;  
import com.amazonaws.services.dynamodbv2.model.LocalSecondaryIndex;  
import com.amazonaws.services.dynamodbv2.model.Projection;  
import com.amazonaws.services.dynamodbv2.model.ProjectionType;  
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;  
import com.amazonaws.services.dynamodbv2.model.ReturnConsumedCapacity;  
import com.amazonaws.services.dynamodbv2.model.Select;  
  
public class DocumentAPILocalSecondaryIndexExample {  
  
    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();  
    static DynamoDB dynamoDB = new DynamoDB(client);  
  
    public static String tableName = "CustomerOrders";  
  
    public static void main(String[] args) throws Exception {  
  
        createTable();  
        loadData();  
  
        query(null);  
        query("IsOpenIndex");  
        query("OrderCreationDateIndex");  
  
        deleteTable(tableName);  
    }  
  
    public static void createTable() {  
  
        CreateTableRequest createTableRequest = new  
CreateTableRequest().withTableName(tableName)  
            .withProvisionedThroughput(  
                new ProvisionedThroughput().withReadCapacityUnits((long)  
1).withWriteCapacityUnits((long) 1));  
    }  
}
```

```

        // Attribute definitions for table partition and sort keys
        ArrayList<AttributeDefinition> attributeDefinitions = new
        ArrayList<AttributeDefinition>();
        attributeDefinitions.add(new
        AttributeDefinition().withAttributeName("CustomerId").withAttributeType("S"));
        attributeDefinitions.add(new
        AttributeDefinition().withAttributeName("OrderId").withAttributeType("N"));

        // Attribute definition for index primary key attributes
        attributeDefinitions
            .add(new
        AttributeDefinition().withAttributeName("OrderCreationDate").withAttributeType("N"));
        attributeDefinitions.add(new
        AttributeDefinition().withAttributeName("IsOpen").withAttributeType("N"));

        createTableRequest.setAttributeDefinitions(attributeDefinitions);

        // Key schema for table
        ArrayList<KeySchemaElement> tableKeySchema = new ArrayList<KeySchemaElement>();
        tableKeySchema.add(new
        KeySchemaElement().withAttributeName("CustomerId").withKeyType(KeyType.HASH)); // Partition

        // key
        tableKeySchema.add(new
        KeySchemaElement().withAttributeName("OrderId").withKeyType(KeyType.RANGE)); // Sort

        // key

        createTableRequest.setKeySchema(tableKeySchema);

        ArrayList<LocalSecondaryIndex> localSecondaryIndexes = new
        ArrayList<LocalSecondaryIndex>();

        // OrderCreationDateIndex
        LocalSecondaryIndex orderCreationDateIndex = new
        LocalSecondaryIndex().withIndexName("OrderCreationDateIndex");

        // Key schema for OrderCreationDateIndex
        ArrayList<KeySchemaElement> indexKeySchema = new ArrayList<KeySchemaElement>();
        indexKeySchema.add(new
        KeySchemaElement().withAttributeName("CustomerId").withKeyType(KeyType.HASH)); // Partition

        // key
        indexKeySchema.add(new
        KeySchemaElement().withAttributeName("OrderCreationDate").withKeyType(KeyType.RANGE)); // Sort

        // key

        orderCreationDateIndex.setKeySchema(indexKeySchema);

        // Projection (with list of projected attributes) for
        // OrderCreationDateIndex
        Projection projection = new
        Projection().withProjectionType(ProjectionType.INCLUDE);
        ArrayList<String> nonKeyAttributes = new ArrayList<String>();
        nonKeyAttributes.add("ProductCategory");
        nonKeyAttributes.add("ProductName");
        projection.setNonKeyAttributes(nonKeyAttributes);

        orderCreationDateIndex.setProjection(projection);

        localSecondaryIndexes.add(orderCreationDateIndex);
    
```

```

    // IsOpenIndex
    LocalSecondaryIndex isOpenIndex = new
    LocalSecondaryIndex().withIndexName("IsOpenIndex");

    // Key schema for IsOpenIndex
    indexKeySchema = new ArrayList<KeySchemaElement>();
    indexKeySchema.add(new
    KeySchemaElement().withAttributeName("CustomerId").withKeyType(KeyType.HASH)); // Partition

    // key
    indexKeySchema.add(new
    KeySchemaElement().withAttributeName("IsOpen").withKeyType(KeyType.RANGE)); // Sort

    // key

    // Projection (all attributes) for IsOpenIndex
    projection = new Projection().withProjectionType(ProjectionType.ALL);

    isOpenIndex.setKeySchema(indexKeySchema);
    isOpenIndex.setProjection(projection);

    localSecondaryIndexes.add(isOpenIndex);

    // Add index definitions to CreateTable request
    createTableRequest.setLocalSecondaryIndexes(localSecondaryIndexes);

    System.out.println("Creating table " + tableName + "...");
    System.out.println(dynamoDB.createTable(createTableRequest));

    // Wait for table to become active
    System.out.println("Waiting for " + tableName + " to become ACTIVE...");
    try {
        Table table = dynamoDB.getTable(tableName);
        table.waitForActive();
    }
    catch (InterruptedException e) {
        e.printStackTrace();
    }
}

public static void query(String indexName) {

    Table table = dynamoDB.getTable(tableName);

    System.out.println("\n*****\n");
    System.out.println("Querying table " + tableName + "...");

    QuerySpec querySpec = new
    QuerySpec().withConsistentRead(true).withScanIndexForward(true)
        .withReturnConsumedCapacity(ReturnConsumedCapacity.TOTAL);

    if (indexName == "IsOpenIndex") {

        System.out.println("\nUsing index: '" + indexName + "' : Bob's orders that are
open.");
        System.out.println("Only a user-specified list of attributes are returned\n");
        Index index = table.getIndex(indexName);

        querySpec.withKeyConditionExpression("CustomerId = :v_custid and IsOpen
= :v_isopen")
            .withValueMap(new ValueMap().withString(":v_custid",
"bob@example.com").withNumber(":v_isopen", 1));
    }
}

```

```

        querySpec.withProjectionExpression("OrderCreationDate, ProductCategory,
ProductName, OrderStatus");

        ItemCollection<QueryOutcome> items = index.query(querySpec);
        Iterator<Item> iterator = items.iterator();

        System.out.println("Query: printing results...");

        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }

    }
    else if (indexName == "OrderCreationDateIndex") {
        System.out.println("\nUsing index: '" + indexName + "' : Bob's orders that were
placed after 01/31/2015.");
        System.out.println("Only the projected attributes are returned\n");
        Index index = table.getIndex(indexName);

        querySpec.withKeyConditionExpression("CustomerId = :v_custid and
OrderCreationDate >= :v_orddate")
            .withValueMap(
                new ValueMap().withString(":v_custid",
"bob@example.com").withNumber(":v_orddate", 20150131));

        querySpec.withSelect(Select.ALL_PROJECTED_ATTRIBUTES);

        ItemCollection<QueryOutcome> items = index.query(querySpec);
        Iterator<Item> iterator = items.iterator();

        System.out.println("Query: printing results...");

        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }

    }
    else {
        System.out.println("\nNo index: All of Bob's orders, by OrderId:\n");

        querySpec.withKeyConditionExpression("CustomerId = :v_custid")
            .withValueMap(new ValueMap().withString(":v_custid", "bob@example.com"));

        ItemCollection<QueryOutcome> items = table.query(querySpec);
        Iterator<Item> iterator = items.iterator();

        System.out.println("Query: printing results...");

        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }

    }
}

public static void deleteTable(String tableName) {

    Table table = dynamoDB.getTable(tableName);
    System.out.println("Deleting table " + tableName + "...");
    table.delete();

    // Wait for table to be deleted
    System.out.println("Waiting for " + tableName + " to be deleted...");
    try {
        table.waitForDelete();
    }
}

```

```

        }
    catch (InterruptedException e) {
        e.printStackTrace();
    }
}

public static void loadData() {

    Table table = dynamoDB.getTable(tableName);

    System.out.println("Loading data into table " + tableName + "...");

    Item item = new Item().withPrimaryKey("CustomerId",
"alice@example.com").withNumber("OrderId", 1)
    .withNumber("IsOpen", 1).withNumber("OrderCreationDate",
20150101).withString("ProductCategory", "Book")
    .withString("ProductName", "The Great Outdoors").withString("OrderStatus",
"PACKING ITEMS");
    // no ShipmentTrackingId attribute

    PutItemOutcome putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"alice@example.com").withNumber("OrderId", 2)
    .withNumber("IsOpen", 1).withNumber("OrderCreationDate",
20150221).withString("ProductCategory", "Bike")
    .withString("ProductName", "Super Mountain").withString("OrderStatus", "ORDER RECEIVED");
    // no ShipmentTrackingId attribute

    putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"alice@example.com").withNumber("OrderId", 3)
    // no IsOpen attribute
    .withNumber("OrderCreationDate", 20150304).withString("ProductCategory",
"Music")
    .withString("ProductName", "A Quiet Interlude").withString("OrderStatus", "IN TRANSIT")
    .withString("ShipmentTrackingId", "176493");

    putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"bob@example.com").withNumber("OrderId", 1)
    // no IsOpen attribute
    .withNumber("OrderCreationDate", 20150111).withString("ProductCategory",
"Movie")
    .withString("ProductName", "Calm Before The Storm").withString("OrderStatus",
"SHIPPING DELAY")
    .withString("ShipmentTrackingId", "859323");

    putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"bob@example.com").withNumber("OrderId", 2)
    // no IsOpen attribute
    .withNumber("OrderCreationDate", 20150124).withString("ProductCategory",
"Music")
    .withString("ProductName", "E-Z Listening").withString("OrderStatus",
"DELIVERED")
    .withString("ShipmentTrackingId", "756943");

    putItemOutcome = table.putItem(item);
}

```

```
        item = new Item().withPrimaryKey("CustomerId",
"bob@example.com").withNumber("OrderId", 3)
        // no IsOpen attribute
        .withNumber("OrderCreationDate", 20150221).withString("ProductCategory",
"Music")
        .withString("ProductName", "Symphony 9").withString("OrderStatus", "DELIVERED")
        .withString("ShipmentTrackingId", "645193");

    putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"bob@example.com").withNumber("OrderId", 4)
        .withNumber("IsOpen", 1).withNumber("OrderCreationDate",
20150222).withString("ProductCategory", "Hardware")
        .withString("ProductName", "Extra Heavy Hammer").withString("OrderStatus",
"PACKING ITEMS");
        // no ShipmentTrackingId attribute

    putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"bob@example.com").withNumber("OrderId", 5)
        /* no IsOpen attribute */
        .withNumber("OrderCreationDate", 20150309).withString("ProductCategory",
"Book")
        .withString("ProductName", "How To Cook").withString("OrderStatus", "IN
TRANSIT")
        .withString("ShipmentTrackingId", "440185");

    putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"bob@example.com").withNumber("OrderId", 6)
        // no IsOpen attribute
        .withNumber("OrderCreationDate", 20150318).withString("ProductCategory",
"Luggage")
        .withString("ProductName", "Really Big Suitcase").withString("OrderStatus",
"DELIVERED")
        .withString("ShipmentTrackingId", "893927");

    putItemOutcome = table.putItem(item);

    item = new Item().withPrimaryKey("CustomerId",
"bob@example.com").withNumber("OrderId", 7)
        /* no IsOpen attribute */
        .withNumber("OrderCreationDate", 20150324).withString("ProductCategory",
"Golf")
        .withString("ProductName", "PGA Pro II").withString("OrderStatus", "OUT FOR
DELIVERY")
        .withString("ShipmentTrackingId", "383283");

    putItemOutcome = table.putItem(item);
    assert putItemOutcome != null;
}

}
```

## Working with Local Secondary Indexes: .NET

### Topics

- [Create a table with a Local Secondary Index \(p. 561\)](#)
- [Describe a table with a Local Secondary Index \(p. 563\)](#)

- [Query a Local Secondary Index \(p. 563\)](#)
- [Example: Local Secondary Indexes using the AWS SDK for .NET low-level API \(p. 564\)](#)

You can use the AWS SDK for .NET low-level API to create an Amazon DynamoDB table with one or more local secondary indexes, describe the indexes on the table, and perform queries using the indexes. These operations map to the corresponding low-level DynamoDB API actions. For more information, see [.NET code examples \(p. 276\)](#).

The following are the common steps for table operations using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Provide the required and optional parameters for the operation by creating the corresponding request objects.

For example, create a `CreateTableRequest` object to create a table and an `QueryRequest` object to query a table or an index.

3. Run the appropriate method provided by the client that you created in the preceding step.

## Create a table with a Local Secondary Index

Local secondary indexes must be created at the same time that you create a table. To do this, use `CreateTable` and provide your specifications for one or more local secondary indexes. The following C# code example creates a table to hold information about songs in a music collection. The partition key is `Artist` and the sort key is `SongTitle`. A secondary index, `AlbumTitleIndex`, facilitates queries by album title.

The following are the steps to create a table with a local secondary index, using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `CreateTableRequest` class to provide the request information.

You must provide the table name, its primary key, and the provisioned throughput values. For the local secondary index, you must provide the index name, the name and data type of the index sort key, the key schema for the index, and the attribute projection.

3. Run the `CreateTable` method by providing the request object as a parameter.

The following C# code example demonstrates the preceding steps. The code creates a table (`Music`) with a secondary index on the `AlbumTitle` attribute. The table partition key and sort key, plus the index sort key, are the only attributes projected into the index.

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "Music";

CreateTableRequest createTableRequest = new CreateTableRequest()
{
    TableName = tableName
};

//ProvisionedThroughput
createTableRequest.ProvisionedThroughput = new ProvisionedThroughput()
{
    ReadCapacityUnits = (long)5,
    WriteCapacityUnits = (long)5
};

//AttributeDefinitions
```

```

List<AttributeDefinition> attributeDefinitions = new List<AttributeDefinition>();

attributeDefinitions.Add(new AttributeDefinition()
{
    AttributeName = "Artist",
    AttributeType = "S"
});

attributeDefinitions.Add(new AttributeDefinition()
{
    AttributeName = "SongTitle",
    AttributeType = "S"
});

attributeDefinitions.Add(new AttributeDefinition()
{
    AttributeName = "AlbumTitle",
    AttributeType = "S"
});

createTableRequest.AttributeDefinitions = attributeDefinitions;

//KeySchema
List<KeySchemaElement> tableKeySchema = new List<KeySchemaElement>();

tableKeySchema.Add(new KeySchemaElement() { AttributeName = "Artist", KeyType = "HASH" });
    //Partition key
tableKeySchema.Add(new KeySchemaElement() { AttributeName = "SongTitle", KeyType =
    "RANGE" }); //Sort key

createTableRequest.KeySchema = tableKeySchema;

List<KeySchemaElement> indexKeySchema = new List<KeySchemaElement>();
indexKeySchema.Add(new KeySchemaElement() { AttributeName = "Artist", KeyType = "HASH" });
    //Partition key
indexKeySchema.Add(new KeySchemaElement() { AttributeName = "AlbumTitle", KeyType =
    "RANGE" }); //Sort key

Projection projection = new Projection() { ProjectionType = "INCLUDE" };

List<string> nonKeyAttributes = new List<string>();
nonKeyAttributes.Add("Genre");
nonKeyAttributes.Add("Year");
projection.NonKeyAttributes = nonKeyAttributes;

LocalSecondaryIndex localSecondaryIndex = new LocalSecondaryIndex()
{
    IndexName = "AlbumTitleIndex",
    KeySchema = indexKeySchema,
    Projection = projection
};

List<LocalSecondaryIndex> localSecondaryIndexes = new List<LocalSecondaryIndex>();
localSecondaryIndexes.Add(localSecondaryIndex);
createTableRequest.LocalSecondaryIndexes = localSecondaryIndexes;

CreateTableResponse result = client.CreateTable(createTableRequest);
Console.WriteLine(result.CreateTableResult.TableDescription.TableName);
Console.WriteLine(result.CreateTableResult.TableDescription.TableStatus);

```

You must wait until DynamoDB creates the table and sets the table status to ACTIVE. After that, you can begin putting data items into the table.

## Describe a table with a Local Secondary Index

To get information about local secondary indexes on a table, use the `DescribeTable` API. For each index, you can access its name, key schema, and projected attributes.

The following are the steps to access local secondary index information a table using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `DescribeTableRequest` class to provide the request information. You must provide the table name.
3. Run the `describeTable` method by providing the request object as a parameter.
- 4.

The following C# code example demonstrates the preceding steps.

### Example

```
AmazonDynamoDBClient client = new AmazonDynamoDBClient();
string tableName = "Music";

DescribeTableResponse response = client.DescribeTable(new DescribeTableRequest()
{ TableName = tableName });
List<LocalSecondaryIndexDescription> localSecondaryIndexes =
    response.DescribeTableResult.Table.LocalSecondaryIndexes;

// This code snippet will work for multiple indexes, even though
// there is only one index in this example.
foreach (LocalSecondaryIndexDescription lsiDescription in localSecondaryIndexes)
{
    Console.WriteLine("Info for index " + lsiDescription.IndexName + ":");

    foreach (KeySchemaElement kse in lsiDescription.KeySchema)
    {
        Console.WriteLine("\t" + kse.AttributeName + ": key type is " + kse.KeyType);
    }

    Projection projection = lsiDescription.Projection;

    Console.WriteLine("\tThe projection type is: " + projection.ProjectionType);

    if (projection.ProjectionType.ToString().Equals("INCLUDE"))
    {
        Console.WriteLine("\t\tThe non-key projected attributes are:");

        foreach (String s in projection.NonKeyAttributes)
        {
            Console.WriteLine("\t\t\t" + s);
        }
    }
}
```

## Query a Local Secondary Index

You can use `Query` on a local secondary index in much the same way you `Query` a table. You must specify the index name, the query criteria for the index sort key, and the attributes that you want to return. In this example, the index is `AlbumTitleIndex`, and the index sort key is `AlbumTitle`.

The only attributes returned are those that have been projected into the index. You could modify this query to select non-key attributes too, but this would require table fetch activity that is relatively expensive. For more information about table fetches, see [Attribute projections \(p. 542\)](#)

The following are the steps to query a local secondary index using the .NET low-level API.

1. Create an instance of the `AmazonDynamoDBClient` class.
2. Create an instance of the `QueryRequest` class to provide the request information.
3. Run the `query` method by providing the request object as a parameter.

The following C# code example demonstrates the preceding steps.

### Example

```
QueryRequest queryRequest = new QueryRequest
{
    TableName = "Music",
    IndexName = "AlbumTitleIndex",
    Select = "ALL_ATTRIBUTES",
    ScanIndexForward = true,
    KeyConditionExpression = "Artist = :v_artist and AlbumTitle = :v_title",
    ExpressionAttributeValues = new Dictionary<string, AttributeValue>()
    {
        {":v_artist", new AttributeValue {S = "Acme Band"}},
        {":v_title", new AttributeValue {S = "Songs About Life"}}
    },
};

QueryResponse response = client.Query(queryRequest);

foreach (var attribs in response.Items)
{
    foreach (var attrib in attribs)
    {
        Console.WriteLine(attrib.Key + " ---> " + attrib.Value.S);
    }
    Console.WriteLine();
}
```

### Example: Local Secondary Indexes using the AWS SDK for .NET low-level API

The following C# code example shows how to work with local secondary indexes in Amazon DynamoDB. The example creates a table named `CustomerOrders` with a partition key of `CustomerId` and a sort key of `OrderId`. There are two local secondary indexes on this table:

- `OrderCreationDateIndex` — The sort key is `OrderCreationDate`, and the following attributes are projected into the index:
  - `ProductCategory`
  - `ProductName`
  - `OrderStatus`
  - `ShipmentTrackingId`
- `IsOpenIndex` — The sort key is `IsOpen`, and all of the table attributes are projected into the index.

After the `CustomerOrders` table is created, the program loads the table with data representing customer orders. It then queries the data using the local secondary indexes. Finally, the program deletes the `CustomerOrders` table.

For step-by-step instructions for testing the following example, see [.NET code examples \(p. 276\)](#).

## Example

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
using System;  
using System.Collections.Generic;  
using System.Linq;  
using Amazon.DynamoDBv2;  
using Amazon.DynamoDBv2.DataModel;  
using Amazon.DynamoDBv2.DocumentModel;  
using Amazon.DynamoDBv2.Model;  
using Amazon.Runtime;  
using Amazon.SecurityToken;  
  
namespace com.amazonaws.codesamples  
{  
    class LowLevelLocalSecondaryIndexExample  
    {  
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();  
        private static string tableName = "CustomerOrders";  
  
        static void Main(string[] args)  
        {  
            try  
            {  
                CreateTable();  
                LoadData();  
  
                Query(null);  
                Query("IsOpenIndex");  
                Query("OrderCreationDateIndex");  
  
                DeleteTable(tableName);  
  
                Console.WriteLine("To continue, press Enter");  
                Console.ReadLine();  
            }  
            catch (AmazonDynamoDBException e) { Console.WriteLine(e.Message); }  
            catch (AmazonServiceException e) { Console.WriteLine(e.Message); }  
            catch (Exception e) { Console.WriteLine(e.Message); }  
        }  
  
        private static void CreateTable()  
        {  
            var createTableRequest =  
                new CreateTableRequest()  
            {  
                TableName = tableName,  
                ProvisionedThroughput =  
                    new ProvisionedThroughput()  
                {  
                   
```

```

        ReadCapacityUnits = (long)1,
        WriteCapacityUnits = (long)1
    }
};

var attributeDefinitions = new List<AttributeDefinition>()
{
    // Attribute definitions for table primary key
    { new AttributeDefinition() {
        AttributeName = "CustomerId", AttributeType = "S"
    } },
    { new AttributeDefinition() {
        AttributeName = "OrderId", AttributeType = "N"
    } },
    // Attribute definitions for index primary key
    { new AttributeDefinition() {
        AttributeName = "OrderCreationDate", AttributeType = "N"
    } },
    { new AttributeDefinition() {
        AttributeName = "IsOpen", AttributeType = "N"
    } }
};

createTableRequest.AttributeDefinitions = attributeDefinitions;

// Key schema for table
var tableKeySchema = new List<KeySchemaElement>()
{
    { new KeySchemaElement() {
        AttributeName = "CustomerId", KeyType = "HASH"                                //Partition key
    } },
    { new KeySchemaElement() {
        AttributeName = "OrderId", KeyType = "RANGE"                                //Sort key
    } }
};

createTableRequest.KeySchema = tableKeySchema;

var localSecondaryIndexes = new List<LocalSecondaryIndex>();

// OrderCreationDateIndex
LocalSecondaryIndex orderCreationDateIndex = new LocalSecondaryIndex()
{
    IndexName = "OrderCreationDateIndex"
};

// Key schema for OrderCreationDateIndex
var indexKeySchema = new List<KeySchemaElement>()
{
    { new KeySchemaElement() {
        AttributeName = "CustomerId", KeyType = "HASH"                                //Partition key
    } },
    { new KeySchemaElement() {
        AttributeName = "OrderCreationDate", KeyType = "RANGE"                            //Sort key
    } }
};

orderCreationDateIndex.KeySchema = indexKeySchema;

// Projection (with list of projected attributes) for
// OrderCreationDateIndex
var projection = new Projection()
{
    ProjectionType = "INCLUDE"
};

```

```

        var nonKeyAttributes = new List<string>()
    {
        "ProductCategory",
        "ProductName"
    };
    projection.NonKeyAttributes = nonKeyAttributes;
    orderCreationDateIndex.Projection = projection;
    localSecondaryIndexes.Add(orderCreationDateIndex);

    // IsOpenIndex
    LocalSecondaryIndex isOpenIndex
        = new LocalSecondaryIndex()
    {
        IndexName = "IsOpenIndex"
    };

    // Key schema for IsOpenIndex
    indexKeySchema = new List<KeySchemaElement>()
    {
        { new KeySchemaElement() {
            AttributeName = "CustomerId", KeyType = "HASH"
        } },
        { new KeySchemaElement() {
            AttributeName = "IsOpen", KeyType = "RANGE"
        } } //Partition key
    };
    // Sort key

    // Projection (all attributes) for IsOpenIndex
    projection = new Projection()
    {
        ProjectionType = "ALL"
    };

    isOpenIndex.KeySchema = indexKeySchema;
    isOpenIndex.Projection = projection;

    localSecondaryIndexes.Add(isOpenIndex);

    // Add index definitions to CreateTable request
    createTableRequest.LocalSecondaryIndexes = localSecondaryIndexes;

    Console.WriteLine("Creating table " + tableName + "...");
    Client.CreateTable(createTableRequest);
    WaitUntilTableReady(tableName);
}

public static void Query(string indexName)
{
    Console.WriteLine("\n*****\n");
    Console.WriteLine("Querying table " + tableName + "...");

    QueryRequest queryRequest = new QueryRequest()
    {
        TableName = tableName,
        ConsistentRead = true,
        ScanIndexForward = true,
        ReturnConsumedCapacity = "TOTAL"
    };

    String keyConditionExpression = "CustomerId = :v_customerId";
    Dictionary<string,AttributeValue> expressionAttributeValues = new
    Dictionary<string,AttributeValue> {

```

```

        {":v_customerId", new AttributeValue {
            S = "bob@example.com"
        })
    };

    if (indexName == "IsOpenIndex")
    {
        Console.WriteLine("\nUsing index: '" + indexName
                        + "':: Bob's orders that are open.");
        Console.WriteLine("Only a user-specified list of attributes are returned
\n");
        queryRequest.IndexName = indexName;

        keyConditionExpression += " and IsOpen = :v_isOpen";
        expressionAttributeValues.Add(":v_isOpen", new AttributeValue
        {
            N = "1"
        });

        // ProjectionExpression
        queryRequest.ProjectionExpression = "OrderCreationDate, ProductCategory,
ProductName, OrderStatus";
    }
    else if (indexName == "OrderCreationDateIndex")
    {
        Console.WriteLine("\nUsing index: '" + indexName
                        + "':: Bob's orders that were placed after 01/31/2013.");
        Console.WriteLine("Only the projected attributes are returned\n");
        queryRequest.IndexName = indexName;

        keyConditionExpression += " and OrderCreationDate > :v_Date";
        expressionAttributeValues.Add(":v_Date", new AttributeValue
        {
            N = "20130131"
        });

        // Select
        queryRequest.Select = "ALL_PROJECTED_ATTRIBUTES";
    }
    else
    {
        Console.WriteLine("\nNo index: All of Bob's orders, by OrderId:\n");
    }
    queryRequest.KeyConditionExpression = keyConditionExpression;
    queryRequest.ExpressionAttributeValues = expressionAttributeValues;

    var result = client.Query(queryRequest);
    var items = result.Items;
    foreach (var currentItem in items)
    {
        foreach (string attr in currentItem.Keys)
        {
            if (attr == "OrderId" || attr == "IsOpen"
                || attr == "OrderCreationDate")
            {
                Console.WriteLine(attr + "----> " + currentItem[attr].N);
            }
            else
            {
                Console.WriteLine(attr + "----> " + currentItem[attr].S);
            }
        }
        Console.WriteLine();
    }
}

```

```

        Console.WriteLine("\nConsumed capacity: " +
result.ConsumedCapacity.CapacityUnits + "\n");
    }

    private static void DeleteTable(string tableName)
{
    Console.WriteLine("Deleting table " + tableName + "...");
    client.DeleteTable(new DeleteTableRequest()
    {
        TableName = tableName
    });
    WaitForTableToDelete(tableName);
}

public static void LoadData()
{
    Console.WriteLine("Loading data into table " + tableName + "...");

    Dictionary<string, AttributeValue> item = new Dictionary<string,
AttributeValue>();

    item["CustomerId"] = new AttributeValue
    {
        S = "alice@example.com"
    };
    item["OrderId"] = new AttributeValue
    {
        N = "1"
    };
    item["IsOpen"] = new AttributeValue
    {
        N = "1"
    };
    item["OrderCreationDate"] = new AttributeValue
    {
        N = "20130101"
    };
    item["ProductCategory"] = new AttributeValue
    {
        S = "Book"
    };
    item["ProductName"] = new AttributeValue
    {
        S = "The Great Outdoors"
    };
    item["OrderStatus"] = new AttributeValue
    {
        S = "PACKING ITEMS"
    };
    /* no ShipmentTrackingId attribute */
    PutItemRequest putItemRequest = new PutItemRequest
    {
        TableName = tableName,
        Item = item,
        ReturnItemCollectionMetrics = "SIZE"
    };
    client.PutItem(putItemRequest);

    item = new Dictionary<string, AttributeValue>();
    item["CustomerId"] = new AttributeValue
    {
        S = "alice@example.com"
    };
    item["OrderId"] = new AttributeValue
    {
        N = "2"
    }
}

```

```

};

item["IsOpen"] = new AttributeValue
{
    N = "1"
};
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130221"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Bike"
};
item["ProductName"] = new AttributeValue
{
    S = "Super Mountain"
};
item["OrderStatus"] = new AttributeValue
{
    S = "ORDER RECEIVED"
};
/* no ShipmentTrackingId attribute */
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "alice@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "3"
};
/* no IsOpen attribute */
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130304"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Music"
};
item["ProductName"] = new AttributeValue
{
    S = "A Quiet Interlude"
};
item["OrderStatus"] = new AttributeValue
{
    S = "IN TRANSIT"
};
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "176493"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};

```

```
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "bob@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "1"
};
/* no IsOpen attribute */
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130111"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Movie"
};
item["ProductName"] = new AttributeValue
{
    S = "Calm Before The Storm"
};
item["OrderStatus"] = new AttributeValue
{
    S = "SHIPPING DELAY"
};
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "859323"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "bob@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "2"
};
/* no IsOpen attribute */
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130124"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Music"
};
item["ProductName"] = new AttributeValue
{
    S = "E-Z Listening"
};
item["OrderStatus"] = new AttributeValue
{
    S = "DELIVERED"
};
```

```
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "756943"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "bob@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "3"
};
/* no IsOpen attribute */
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130221"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Music"
};
item["ProductName"] = new AttributeValue
{
    S = "Symphony 9"
};
item["OrderStatus"] = new AttributeValue
{
    S = "DELIVERED"
};
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "645193"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "bob@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "4"
};
item["IsOpen"] = new AttributeValue
{
    N = "1"
};
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130222"
};
```

```

};

item["ProductCategory"] = new AttributeValue
{
    S = "Hardware"
};
item["ProductName"] = new AttributeValue
{
    S = "Extra Heavy Hammer"
};
item["OrderStatus"] = new AttributeValue
{
    S = "PACKING ITEMS"
};
/* no ShipmentTrackingId attribute */
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "bob@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "5"
};
/* no IsOpen attribute */
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130309"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Book"
};
item["ProductName"] = new AttributeValue
{
    S = "How To Cook"
};
item["OrderStatus"] = new AttributeValue
{
    S = "IN TRANSIT"
};
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "440185"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "bob@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "5"
};
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130309"
};
item["OrderStatus"] = new AttributeValue
{
    S = "IN TRANSIT"
};
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "440185"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

```

```

{
    N = "6"
};
/* no IsOpen attribute */
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130318"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Luggage"
};
item["ProductName"] = new AttributeValue
{
    S = "Really Big Suitcase"
};
item["OrderStatus"] = new AttributeValue
{
    S = "DELIVERED"
};
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "893927"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
    ReturnItemCollectionMetrics = "SIZE"
};
client.PutItem(putItemRequest);

item = new Dictionary<string, AttributeValue>();
item["CustomerId"] = new AttributeValue
{
    S = "bob@example.com"
};
item["OrderId"] = new AttributeValue
{
    N = "7"
};
/* no IsOpen attribute */
item["OrderCreationDate"] = new AttributeValue
{
    N = "20130324"
};
item["ProductCategory"] = new AttributeValue
{
    S = "Golf"
};
item["ProductName"] = new AttributeValue
{
    S = "PGA Pro II"
};
item["OrderStatus"] = new AttributeValue
{
    S = "OUT FOR DELIVERY"
};
item["ShipmentTrackingId"] = new AttributeValue
{
    S = "383283"
};
putItemRequest = new PutItemRequest
{
    TableName = tableName,
    Item = item,
}

```

```

        ReturnItemCollectionMetrics = "SIZE"
    };
    client.PutItem(putItemRequest);
}

private static void WaitUntilTableReady(string tableName)
{
    string status = null;
    // Let us wait until table is created. Call DescribeTable.
    do
    {
        System.Threading.Thread.Sleep(5000); // Wait 5 seconds.
        try
        {
            var res = client.DescribeTable(new DescribeTableRequest
            {
                TableName = tableName
            });

            Console.WriteLine("Table name: {0}, status: {1}",
                res.Table.TableName,
                res.Table.TableStatus);
            status = res.Table.TableStatus;
        }
        catch (ResourceNotFoundException)
        {
            // DescribeTable is eventually consistent. So you might
            // get resource not found. So we handle the potential exception.
        }
    } while (status != "ACTIVE");
}

private static void WaitForTableToDelete(string tableName)
{
    bool tablePresent = true;

    while (tablePresent)
    {
        System.Threading.Thread.Sleep(5000); // Wait 5 seconds.
        try
        {
            var res = client.DescribeTable(new DescribeTableRequest
            {
                TableName = tableName
            });

            Console.WriteLine("Table name: {0}, status: {1}",
                res.Table.TableName,
                res.Table.TableStatus);
        }
        catch (ResourceNotFoundException)
        {
            tablePresent = false;
        }
    }
}
}

```

## Working with Local Secondary Indexes: AWS CLI

You can use the AWS CLI to create an Amazon DynamoDB table with one or more Local Secondary Indexes, describe the indexes on the table, and perform queries using the indexes.

## Topics

- [Create a table with a Local Secondary Index \(p. 576\)](#)
- [Describe a table with a Local Secondary Index \(p. 576\)](#)
- [Query a Local Secondary Index \(p. 576\)](#)

## Create a table with a Local Secondary Index

Local Secondary Indexes must be created at the same time you create a table. To do this, use the `--create-table` parameter and provide your specifications for one or more Local Secondary Indexes. The following example creates a table (`Music`) to hold information about songs in a music collection. The partition key is `Artist` and the sort key is `SongTitle`. A secondary index, `AlbumTitleIndex` on the `AlbumTitle` attribute facilitates queries by album title.

```
aws dynamodb create-table \
    --table-name Music \
    --attribute-definitions AttributeName=Artist,AttributeType=S
    AttributeName=SongTitle,AttributeType=S \
        AttributeName=AlbumTitle,AttributeType=S \
    --key-schema AttributeName=Artist,KeyType=HASH AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput \
        ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --local-secondary-indexes \
        "[{\\"IndexName\\": \\"AlbumTitleIndex\\",
        \\"KeySchema\\": [{\\\"AttributeName\\": \\"Artist\\", \\"KeyType\\": \\"HASH\\\"},
            {\\\"AttributeName\\": \\"AlbumTitle\\", \\"KeyType\\": \\"RANGE\\\"}],
        \\"Projection\\": {\\\"ProjectionType\\": \\"INCLUDE\\\", \\"NonKeyAttributes\\": [\\\"Genre\\",
            \\"Year\\\"]}}]"
```

You must wait until DynamoDB creates the table and sets the table status to `ACTIVE`. After that, you can begin putting data items into the table. You can use [describe-table](#) to determine the status of the table creation.

## Describe a table with a Local Secondary Index

To get information about local secondary indexes on a table, use the `describe-table` parameter. For each index, you can access its name, key schema, and projected attributes.

```
aws dynamodb describe-table --table-name Music
```

## Query a Local Secondary Index

You can use the `query` operation on a Local Secondary Index in much the same way that you query a table. You must specify the index name, the query criteria for the index sort key, and the attributes that you want to return. In this example, the index is `AlbumTitleIndex` and the index sort key is `AlbumTitle`.

The only attributes returned are those that have been projected into the index. You could modify this query to select non-key attributes too, but this would require table fetch activity that is relatively expensive. For more information about table fetches, see [Attribute projections \(p. 542\)](#).

```
aws dynamodb query \
    --table-name Music \
    --index-name AlbumTitleIndex \
    --key-condition-expression "Artist = :v_artist and AlbumTitle = :v_title" \
    --expression-attribute-values '{\":v_artist\":{\"S\":\"Acme Band\"}, \":v_title\":{\"S\":\"Songs About Life\"} }'
```

# Managing complex workflows with DynamoDB transactions

Amazon DynamoDB transactions simplify the developer experience of making coordinated, all-or-nothing changes to multiple items both within and across tables. Transactions provide atomicity, consistency, isolation, and durability (ACID) in DynamoDB, helping you to maintain data correctness in your applications.

You can use the DynamoDB transactional read and write APIs to manage complex business workflows that require adding, updating, or deleting multiple items as a single, all-or-nothing operation. For example, a video game developer can ensure that players' profiles are updated correctly when they exchange items in a game or make in-game purchases.

With the transaction write API, you can group multiple `Put`, `Update`, `Delete`, and `ConditionCheck` actions. You can then submit the actions as a single `TransactWriteItems` operation that either succeeds or fails as a unit. The same is true for multiple `Get` actions, which you can group and submit as a single `TransactGetItems` operation.

There is no additional cost to enable transactions for your DynamoDB tables. You pay only for the reads or writes that are part of your transaction. DynamoDB performs two underlying reads or writes of every item in the transaction: one to prepare the transaction and one to commit the transaction. These two underlying read/write operations are visible in your Amazon CloudWatch metrics.

To get started with DynamoDB transactions, download the latest AWS SDK or the AWS Command Line Interface (AWS CLI). Then follow the [DynamoDB transactions example \(p. 585\)](#).

The following sections provide a detailed overview of the transaction APIs and how you can use them in DynamoDB.

## Topics

- [Amazon DynamoDB Transactions: How it works \(p. 577\)](#)
- [Using IAM with DynamoDB transactions \(p. 583\)](#)
- [DynamoDB transactions example \(p. 585\)](#)

## Amazon DynamoDB Transactions: How it works

With Amazon DynamoDB transactions, you can group multiple actions together and submit them as a single all-or-nothing `TransactWriteItems` or `TransactGetItems` operation. The following sections describe API operations, capacity management, best practices, and other details about using transactional operations in DynamoDB.

## Topics

- [TransactWriteItems API \(p. 578\)](#)
- [TransactGetItems API \(p. 579\)](#)
- [Isolation levels for DynamoDB transactions \(p. 579\)](#)
- [Transaction conflict handling in DynamoDB \(p. 581\)](#)
- [Using transactional APIs in DynamoDB Accelerator \(DAX\) \(p. 581\)](#)
- [Capacity management for transactions \(p. 582\)](#)
- [Best practices for transactions \(p. 582\)](#)
- [Using transactional APIs with global tables \(p. 582\)](#)
- [DynamoDB Transactions vs. the AWSLabs transactions client library \(p. 583\)](#)

## TransactWriteItems API

`TransactWriteItems` is a synchronous and idempotent write operation that groups up to 25 write actions in a single all-or-nothing operation. These actions can target up to 25 distinct items in one or more DynamoDB tables within the same AWS account and in the same Region. The aggregate size of the items in the transaction cannot exceed 4 MB. The actions are completed atomically so that either all of them succeed or none of them succeeds.

### Note

A `TransactWriteItems` operation differs from a `BatchWriteItem` operation in that all the actions it contains must be completed successfully, or no changes are made at all. With a `BatchWriteItem` operation, it is possible that only some of the actions in the batch succeed while the others do not.

You can't target the same item with multiple operations within the same transaction. For example, you can't perform a `ConditionCheck` and also an `Update` action on the same item in the same transaction.

You can add the following types of actions to a transaction:

- `Put` — Initiates a `PutItem` operation to create a new item or replace an old item with a new item, conditionally or without specifying any condition.
- `Update` — Initiates an `UpdateItem` operation to edit an existing item's attributes or add a new item to the table if it does not already exist. Use this action to add, delete, or update attributes on an existing item conditionally or without a condition.
- `Delete` — Initiates a `DeleteItem` operation to delete a single item in a table identified by its primary key.
- `ConditionCheck` — Checks that an item exists or checks the condition of specific attributes of the item.

Once a transaction completes, the changes made within that transaction are propagated to global secondary indexes (GSIs), streams, and backups. Since propagation is not immediate or instantaneous, if a table is restored from backup ([RestoreTableFromBackup](#)) or exported to a point in time ([ExportTableToPointInTime](#)) mid-propagation, it might contain some but not all of the changes made during a recent transaction.

## Idempotency

You can optionally include a client token when you make a `TransactWriteItems` call to ensure that the request is *idempotent*. Making your transactions idempotent helps prevent application errors if the same operation is submitted multiple times due to a connection time-out or other connectivity issue.

If the original `TransactWriteItems` call was successful, the subsequent `TransactWriteItems` calls with the same client token return successfully without making any changes. If the `ReturnConsumedCapacity` parameter is set, the initial `TransactWriteItems` call returns the number of write capacity units consumed in making the changes. Subsequent `TransactWriteItems` calls with the same client token return the number of read capacity units consumed in reading the item.

### Important points about idempotency

- A client token is valid for 10 minutes after the request that uses it finishes. After 10 minutes, any request that uses the same client token is treated as a new request. You should not reuse the same client token for the same request after 10 minutes.
- If you repeat a request with the same client token within the 10-minute idempotency window but change some other request parameter, DynamoDB returns an `IdempotentParameterMismatch` exception.

## Error handling for writing

Write transactions don't succeed under the following circumstances:

- When a condition in one of the condition expressions is not met.
- When a transaction validation error occurs because more than one action in the same `TransactWriteItems` operation targets the same item.
- When a `TransactWriteItems` request conflicts with an ongoing `TransactWriteItems` operation on one or more items in the `TransactWriteItems` request. In this case, the request fails with a `TransactionCanceledException`.
- When there is insufficient provisioned capacity for the transaction to be completed.
- When an item size becomes too large (larger than 400 KB), or a local secondary index (LSI) becomes too large, or a similar validation error occurs because of changes made by the transaction.
- When there is a user error, such as an invalid data format.

For more information about how conflicts with `TransactWriteItems` operations are handled, see [Transaction conflict handling in DynamoDB \(p. 581\)](#).

## TransactGetItems API

`TransactGetItems` is a synchronous read operation that groups up to 25 Get actions together. These actions can target up to 25 distinct items in one or more DynamoDB tables within the same AWS account and Region. The aggregate size of the items in the transaction can't exceed 4 MB.

The Get actions are performed atomically so that either all of them succeed or all of them fail:

- Get — Initiates a `GetItem` operation to retrieve a set of attributes for the item with the given primary key. If no matching item is found, Get does not return any data.

## Error handling for reading

Read transactions don't succeed under the following circumstances:

- When a `TransactGetItems` request conflicts with an ongoing `TransactWriteItems` operation on one or more items in the `TransactGetItems` request. In this case, the request fails with a `TransactionCanceledException`.
- When there is insufficient provisioned capacity for the transaction to be completed.
- When there is a user error, such as an invalid data format.

For more information about how conflicts with `TransactGetItems` operations are handled, see [Transaction conflict handling in DynamoDB \(p. 581\)](#).

## Isolation levels for DynamoDB transactions

The isolation levels of transactional operations (`TransactWriteItems` or `TransactGetItems`) and other operations are as follows.

### SERIALIZABLE

*Serializable* isolation ensures that the results of multiple concurrent operations are the same as if no operation begins until the previous one has finished.

There is serializable isolation between the following types of operation:

- Between any transactional operation and any standard write operation (`PutItem`, `UpdateItem`, or `DeleteItem`).
- Between any transactional operation and any standard read operation (`GetItem`).
- Between a `TransactWriteItems` operation and a `TransactGetItems` operation.

Although there is serializable isolation between transactional operations, and each individual standard writes in a `BatchWriteItem` operation, there is no serializable isolation between the transaction and the `BatchWriteItem` operation as a unit.

Similarly, the isolation level between a transactional operation and individual `GetItems` in a `BatchGetItem` operation is serializable. But the isolation level between the transaction and the `BatchGetItem` operation as a unit is *read-committed*.

A single `GetItem` request is serializable with respect to a `TransactWriteItems` request in one of two ways, either before or after the `TransactWriteItems` request. Multiple `GetItem` requests, against keys in a concurrent `TransactWriteItems` requests can be run in any order, and therefore the results are *read-committed*.

For example, if `GetItem` requests for item A and item B are run concurrently with a `TransactWriteItems` request that modifies both item A and item B, there are four possibilities:

- Both `GetItem` requests are run before the `TransactWriteItems` request.
- Both `GetItem` requests are run after the `TransactWriteItems` request.
- `GetItem` request for item A is run before the `TransactWriteItems` request. For item B the `GetItem` is run after `TransactWriteItems`.
- `GetItem` request for item B is run before the `TransactWriteItems` request. For item A the `GetItem` is run after `TransactWriteItems`.

If serializable isolation level is preferred for multiple `GetItem` requests, then please use `TransactGetItems`.

## READ-COMMITTED

*Read-committed* isolation ensures that read operations always return committed values for an item. Read-committed isolation does not prevent modifications of the item immediately after the read operation.

The isolation level is read-committed between any transactional operation and any read operation that involves multiple standard reads (`BatchGetItem`, `Query`, or `Scan`). If a transactional write updates an item in the middle of a `BatchGetItem`, `Query`, or `Scan` operation, the read operation returns the new committed value.

## Operation summary

To summarize, the following table shows the isolation levels between a transaction operation (`TransactWriteItems` or `TransactGetItems`) and other operations.

Operation	Isolation Level
<code>DeleteItem</code>	<i>Serializable</i>
<code>PutItem</code>	<i>Serializable</i>
<code>UpdateItem</code>	<i>Serializable</i>
<code>GetItem</code>	<i>Serializable</i>

Operation	Isolation Level
BatchGetItem	<i>Read-committed*</i>
BatchWriteItem	<i>NOT Serializable*</i>
Query	<i>Read-committed</i>
Scan	<i>Read-committed</i>
Other transactional operation	<i>Serializable</i>

Levels marked with an asterisk (\*) apply to the operation as a unit. However, individual actions within those operations have a *Serializable* isolation level.

## Transaction conflict handling in DynamoDB

A transactional conflict can occur during concurrent item-level requests on an item within a transaction. Transaction conflicts can occur in the following scenarios:

- A `PutItem`, `UpdateItem`, or `DeleteItem` request for an item conflicts with an ongoing `TransactWriteItems` request that includes the same item.
- An item within a `TransactWriteItems` request is part of another ongoing `TransactWriteItems` request.
- An item within a `TransactGetItems` request is part of an ongoing `TransactWriteItems`, `BatchWriteItem`, `PutItem`, `UpdateItem`, or `DeleteItem` request.

### Note

- When a `PutItem`, `UpdateItem`, or `DeleteItem` request is rejected, the request fails with a `TransactionConflictException`.
- If any item-level request within `TransactWriteItems` or `TransactGetItems` is rejected, the request fails with a `TransactionCanceledException`. If that request fails, AWS SDKs do not retry the request.

If you are using the AWS SDK for Java, the exception contains the list of `CancellationReasons`, ordered according to the list of items in the `TransactItems` request parameter. For other languages, a string representation of the list is included in the exception's error message.

- If an ongoing `TransactWriteItems` or `TransactGetItems` operation conflicts with a concurrent `GetItem` request, both operations can succeed.

The [TransactionConflict CloudWatch metric](#) is incremented for each failed item-level request.

## Using transactional APIs in DynamoDB Accelerator (DAX)

`TransactWriteItems` and `TransactGetItems` are both supported in DynamoDB Accelerator (DAX) with the same isolation levels as in DynamoDB.

`TransactWriteItems` writes through DAX. DAX passes a `TransactWriteItems` call to DynamoDB and returns the response. To populate the cache after the write, DAX calls `TransactGetItems` in the background for each item in the `TransactWriteItems` operation, which consumes additional read capacity units. (For more information, see [Capacity management for transactions \(p. 582\)](#).) This functionality enables you to keep your application logic simple and use DAX for both transactional operations and nontransactional ones.

`TransactGetItems` calls are passed through DAX without the items being cached locally. This is the same behavior as for strongly consistent read APIs in DAX.

## Capacity management for transactions

There is no additional cost to enable transactions for your DynamoDB tables. You pay only for the reads or writes that are part of your transaction. DynamoDB performs two underlying reads or writes of every item in the transaction: one to prepare the transaction and one to commit the transaction. The two underlying read/write operations are visible in your Amazon CloudWatch metrics.

Plan for the additional reads and writes that are required by transactional APIs when you are provisioning capacity to your tables. For example, suppose that your application runs one transaction per second, and each transaction writes three 500-byte items in your table. Each item requires two write capacity units (WCUs): one to prepare the transaction and one to commit the transaction. Therefore, you would need to provision six WCUs to the table.

If you were using DynamoDB Accelerator (DAX) in the previous example, you would also use two read capacity units (RCUs) for each item in the `TransactWriteItems` call. So you would need to provision six additional RCUs to the table.

Similarly, if your application runs one read transaction per second, and each transaction reads three 500-byte items in your table, you would need to provision six read capacity units (RCUs) to the table. Reading each item requires two RCUs: one to prepare the transaction and one to commit the transaction.

Also, default SDK behavior is to retry transactions in case of a `TransactionInProgressException` exception. Plan for the additional read-capacity units (RCUs) that these retries consume. The same is true if you are retrying transactions in your own code using a `ClientRequestToken`.

## Best practices for transactions

Consider the following recommended practices when using DynamoDB transactions.

- Enable automatic scaling on your tables, or ensure that you have provisioned enough throughput capacity to perform the two read or write operations for every item in your transaction.
- If you are not using an AWS provided SDK, include a `ClientRequestToken` attribute when you make a `TransactWriteItems` call to ensure that the request is idempotent.
- Don't group operations together in a transaction if it's not necessary. For example, if a single transaction with 10 operations can be broken up into multiple transactions without compromising the application correctness, we recommend splitting up the transaction. Simpler transactions improve throughput and are more likely to succeed.
- Multiple transactions updating the same items simultaneously can cause conflicts that cancel the transactions. We recommend following DynamoDB best practices for data modeling to minimize such conflicts.
- If a set of attributes is often updated across multiple items as part of a single transaction, consider grouping the attributes into a single item to reduce the scope of the transaction.
- Avoid using transactions for ingesting data in bulk. For bulk writes, it is better to use `BatchWriteItem`.

## Using transactional APIs with global tables

Transactional operations provide atomicity, consistency, isolation, and durability (ACID) guarantees only within the region where the write is made originally. Transactions are not supported across regions in global tables. For example, if you have a global table with replicas in the US East (Ohio) and US West (Oregon) regions and perform a `TransactWriteItems` operation in the US East (N. Virginia) Region, you

may observe partially completed transactions in US West (Oregon) Region as changes are replicated. Changes will only be replicated to other regions once they have been committed in the source region.

## DynamoDB Transactions vs. the AWSLabs transactions client library

DynamoDB transactions provide a more cost-effective, robust, and performant replacement for the [AWSLabs](#) transactions client library. We suggest that you update your applications to use the native, server-side transaction APIs.

## Using IAM with DynamoDB transactions

You can use AWS Identity and Access Management (IAM) to restrict the actions that transactional operations can perform in Amazon DynamoDB. For more information about using IAM policies in DynamoDB, see [Using identity-based policies \(IAM policies\) with Amazon DynamoDB \(p. 1075\)](#).

Permissions for Put, Update, Delete, and Get actions are governed by the permissions used for the underlying PutItem, UpdateItem, DeleteItem, and GetItem operations. For the ConditionCheck action, you can use the dynamodb:ConditionCheck permission in IAM policies.

The following are examples of IAM policies that you can use to configure the DynamoDB transactions.

### Example 1: Allow transactional operations

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:ConditionCheckItem",  
                "dynamodb:PutItem",  
                "dynamodb:UpdateItem",  
                "dynamodb:DeleteItem",  
                "dynamodb:GetItem"  
            ],  
            "Resource": [  
                "arn:aws:dynamodb:*:*:table/table04"  
            ]  
        }  
    ]  
}
```

### Example 2: Allow only transactional operations

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:ConditionCheckItem",  
                "dynamodb:PutItem",  
                "dynamodb:UpdateItem",  
                "dynamodb:DeleteItem",  
                "dynamodb:GetItem"  
            ],  
            "Resource": [  
                "arn:aws:dynamodb:*:*:table/table04"  
            ]  
        }  
    ]  
}
```

```
        "arn:aws:dynamodb:*.*:table/table04"
    ],
    "Condition": {
        "ForAnyValue:StringEquals": {
            "dynamodb:EnclosingOperation": [
                "TransactWriteItems",
                "TransactGetItems"
            ]
        }
    }
}
```

### Example 3: Allow nontransactional reads and writes, and block transactional reads and writes

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Deny",
            "Action": [
                "dynamodb:ConditionCheckItem",
                "dynamodb:PutItem",
                "dynamodb:UpdateItem",
                "dynamodb>DeleteItem",
                "dynamodb:GetItem"
            ],
            "Resource": [
                "arn:aws:dynamodb:*.*:table/table04"
            ],
            "Condition": {
                "ForAnyValue:StringEquals": {
                    "dynamodb:EnclosingOperation": [
                        "TransactWriteItems",
                        "TransactGetItems"
                    ]
                }
            }
        },
        {
            "Effect": "Allow",
            "Action": [
                "dynamodb:PutItem",
                "dynamodb>DeleteItem",
                "dynamodb:GetItem",
                "dynamodb:UpdateItem"
            ],
            "Resource": [
                "arn:aws:dynamodb:*.*:table/table04"
            ]
        }
    ]
}
```

### Example 4: Prevent information from being returned on a ConditionCheck failure

```
{
```

```

    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                "dynamodb:ConditionCheckItem",
                "dynamodb:PutItem",
                "dynamodb:UpdateItem",
                "dynamodb:DeleteItem",
                "dynamodb:GetItem"
            ],
            "Resource": "arn:aws:dynamodb:*::table/table01",
            "Condition": {
                "StringEqualsIfExists": {
                    "dynamodb:ReturnValues": "NONE"
                }
            }
        }
    ]
}

```

## DynamoDB transactions example

As an example of a situation in which Amazon DynamoDB transactions can be useful, consider this sample Java application for an online marketplace.

The application has three DynamoDB tables in the backend:

- **Customers** — This table stores details about the marketplace customers. Its primary key is a `CustomerId` unique identifier.
- **ProductCatalog** — This table stores details such as price and availability about the products for sale in the marketplace. Its primary key is a `ProductId` unique identifier.
- **Orders** — This table stores details about orders from the marketplace. Its primary key is an `OrderId` unique identifier.

### Making an order

The following code snippets illustrate how to use DynamoDB transactions to coordinate the multiple steps that are required to create and process an order. Using a single all-or-nothing operation ensures that if any part of the transaction fails, no actions in the transaction are run and no changes are made.

In this example, you set up an order from a customer whose `customerId` is `09e8e9c8-ec48`. You then run it as a single transaction using the following simple order-processing workflow:

1. Determine that the customer ID is valid.
2. Make sure that the product is `IN_STOCK`, and update the product status to `SOLD`.
3. Make sure that the order does not already exist, and create the order.

### Validate the customer

First, define an action to verify that a customer with `customerId` equal to `09e8e9c8-ec48` exists in the customer table.

```

final String CUSTOMER_TABLE_NAME = "Customers";
final String CUSTOMER_PARTITION_KEY = "CustomerId";
final String customerId = "09e8e9c8-ec48";

```

```

final HashMap<String, AttributeValue> customerItemKey = new HashMap<>();
customerItemKey.put(CUSTOMER_PARTITION_KEY, new AttributeValue(customerId));

ConditionCheck checkCustomerValid = new ConditionCheck()
    .withTableName(CUSTOMER_TABLE_NAME)
    .withKey(customerItemKey)
    .withConditionExpression("attribute_exists(" + CUSTOMER_PARTITION_KEY + ")");

```

## Update the product status

Next, define an action to update the product status to `SOLD` if the condition that the product status is currently set to `IN_STOCK` is true. Setting the `ReturnValuesOnConditionCheckFailure` parameter returns the item if the item's product status attribute was not equal to `IN_STOCK`.

```

final String PRODUCT_TABLE_NAME = "ProductCatalog";
final String PRODUCT_PARTITION_KEY = "ProductId";
HashMap<String, AttributeValue> productItemKey = new HashMap<>();
productItemKey.put(PRODUCT_PARTITION_KEY, new AttributeValue(productKey));

Map<String, AttributeValue> expressionAttributeValues = new HashMap<>();
expressionAttributeValues.put(":new_status", new AttributeValue("SOLD"));
expressionAttributeValues.put(":expected_status", new AttributeValue("IN_STOCK"));

Update markItemSold = new Update()
    .withTableName(PRODUCT_TABLE_NAME)
    .withKey(productItemKey)
    .withUpdateExpression("SET ProductStatus = :new_status")
    .withExpressionAttributeValues(expressionAttributeValues)
    .withConditionExpression("ProductStatus = :expected_status")
    .withReturnValuesOnConditionCheckFailure(ReturnValuesOnConditionCheckFailure.ALL_OLD);

```

## Create the order

Lastly, create the order as long as an order with that `OrderId` does not already exist.

```

final String ORDER_PARTITION_KEY = "OrderId";
final String ORDER_TABLE_NAME = "Orders";

HashMap<String, AttributeValue> orderItem = new HashMap<>();
orderItem.put(ORDER_PARTITION_KEY, new AttributeValue(orderId));
orderItem.put(PRODUCT_PARTITION_KEY, new AttributeValue(productKey));
orderItem.put(CUSTOMER_PARTITION_KEY, new AttributeValue(customerId));
orderItem.put("OrderStatus", new AttributeValue("CONFIRMED"));
orderItem.put("OrderTotal", new AttributeValue("100"));

Put createOrder = new Put()
    .withTableName(ORDER_TABLE_NAME)
    .withItem(orderItem)
    .withReturnValuesOnConditionCheckFailure(ReturnValuesOnConditionCheckFailure.ALL_OLD)
    .withConditionExpression("attribute_not_exists(" + ORDER_PARTITION_KEY + ")");

```

## Run the transaction

The following example illustrates how to run the actions defined previously as a single all-or-nothing operation.

```

Collection<TransactWriteItem> actions = Arrays.asList(
    new TransactWriteItem().withConditionCheck(checkCustomerValid),
    new TransactWriteItem().withUpdate(markItemSold),

```

```

        new TransactWriteItem().withPut(createOrder));

TransactWriteItemsRequest placeOrderTransaction = new TransactWriteItemsRequest()
    .withTransactItems(actions)
    .withReturnConsumedCapacity(ReturnConsumedCapacity.TOTAL);

// Run the transaction and process the result.
try {
    client.transactWriteItems(placeOrderTransaction);
    System.out.println("Transaction Successful");

} catch (ResourceNotFoundException rnf) {
    System.err.println("One of the table involved in the transaction is not found" +
rnf.getMessage());
} catch (InternalServerException ise) {
    System.err.println("Internal Server Error" + ise.getMessage());
} catch (TransactionCanceledException tce) {
    System.out.println("Transaction Canceled " + tce.getMessage());
}

```

## Reading the order details

The following example shows how to read the completed order transactionally across the `Orders` and `ProductCatalog` tables.

```

HashMap<String, AttributeValue> productItemKey = new HashMap<>();
productItemKey.put(PRODUCT_PARTITION_KEY, new AttributeValue(productKey));

HashMap<String, AttributeValue> orderKey = new HashMap<>();
orderKey.put(ORDER_PARTITION_KEY, new AttributeValue(orderId));

Get readProductSold = new Get()
    .withTableName(PRODUCT_TABLE_NAME)
    .withKey(productItemKey);
Get readCreatedOrder = new Get()
    .withTableName(ORDER_TABLE_NAME)
    .withKey(orderKey);

Collection<TransactGetItem> getActions = Arrays.asList(
    new TransactGetItem().withGet(readProductSold),
    new TransactGetItem().withGet(readCreatedOrder));

TransactGetItemsRequest readCompletedOrder = new TransactGetItemsRequest()
    .withTransactItems(getActions)
    .withReturnConsumedCapacity(ReturnConsumedCapacity.TOTAL);

// Run the transaction and process the result.
try {
    TransactGetItemsResult result = client.transactGetItems(readCompletedOrder);
    System.out.println(result.getResponses());
} catch (ResourceNotFoundException rnf) {
    System.err.println("One of the table involved in the transaction is not found" +
rnf.getMessage());
} catch (InternalServerException ise) {
    System.err.println("Internal Server Error" + ise.getMessage());
} catch (TransactionCanceledException tce) {
    System.err.println("Transaction Canceled" + tce.getMessage());
}

```

## Additional examples

- [Using transactions from DynamoDBMapper](#)

# Change data capture with Amazon DynamoDB

Many applications benefit from capturing changes to items stored in a DynamoDB table, at the point in time when such changes occur. The following are some example use cases:

- A popular mobile app modifies data in a DynamoDB table, at the rate of thousands of updates per second. Another application captures and stores data about these updates, providing near-real-time usage metrics for the mobile app.
- A financial application modifies stock market data in a DynamoDB table. Different applications running in parallel track these changes in real time, compute value-at-risk, and automatically rebalance portfolios based on stock price movements.
- Sensors in transportation vehicles and industrial equipment send data to a DynamoDB table. Different applications monitor performance and send messaging alerts when a problem is detected, predict any potential defects by applying machine learning algorithms, and compress and archive data to Amazon Simple Storage Service (Amazon S3).
- An application automatically sends notifications to the mobile devices of all friends in a group as soon as one friend uploads a new picture.
- A new customer adds data to a DynamoDB table. This event invokes another application that sends a welcome email to the new customer.

DynamoDB supports streaming of item-level change data capture records in near-real time. You can build applications that consume these streams and take action based on the contents.

The following video will give you an introductory look at the change data capture concept.

## Table capacity modes

### Topics

- [Streaming options for change data capture \(p. 588\)](#)
- [Using Kinesis Data Streams to capture changes to DynamoDB \(p. 589\)](#)
- [Change data capture for DynamoDB Streams \(p. 598\)](#)

## Streaming options for change data capture

DynamoDB offers two streaming models for change data capture: Kinesis Data Streams for DynamoDB and DynamoDB Streams.

To help you choose the right solution for your application, the following table summarizes the features of each streaming model.

Properties	Kinesis Data Streams for DynamoDB	DynamoDB Streams
<b>Data retention</b>	Up to <a href="#">1 year</a> .	24 hours.
<b>Kinesis Client Library (KCL) support</b>	Supports <a href="#">KCL versions 1.X and 2.X</a> .	Supports <a href="#">KCL version 1.X</a> .
<b>Number of consumers</b>	Up to <a href="#">5 simultaneous</a> consumers per shard, or up to 20 simultaneous consumers per shard with <a href="#">enhanced fan-out</a> .	Up to <a href="#">2 simultaneous consumers</a> per shard.

Properties	Kinesis Data Streams for DynamoDB	DynamoDB Streams
<b>Throughput quotas</b>	Unlimited.	Subject to throughput <a href="#">quotas</a> by DynamoDB table and AWS Region.
<b>Record delivery model</b>	Pull model over HTTP using <a href="#">GetRecords</a> and with <a href="#">enhanced fan-out</a> , Kinesis Data Streams pushes the records over HTTP/2 by using <a href="#">SubscribeToShard</a> .	Pull model over HTTP using <a href="#">GetRecords</a> .
<b>Ordering of records</b>	The timestamp attribute on each stream record can be used to identify the actual order in which changes occurred in the DynamoDB table.	For each item that is modified in a DynamoDB table, the stream records appear in the same sequence as the actual modifications to the item.
<b>Duplicate records</b>	Duplicate records might occasionally appear in the stream.	No duplicate records appear in the stream.
<b>Stream processing options</b>	Process stream records using <a href="#">AWS Lambda</a> , <a href="#">Kinesis Data Analytics</a> , <a href="#">Kinesis data firehose</a> , or <a href="#">AWS Glue streaming ETL</a> .	Process stream records using <a href="#">AWS Lambda</a> or <a href="#">DynamoDB Streams Kinesis adapter</a> .

You can enable both streaming models on the same DynamoDB table.

## Using Kinesis Data Streams to capture changes to DynamoDB

You can use Amazon Kinesis Data Streams to capture changes to Amazon DynamoDB.

Kinesis Data Streams captures item-level modifications in any DynamoDB table and replicates them to a [Kinesis data stream](#). Your applications can access this stream and view item-level changes in near-real time. You can continuously capture and store terabytes of data per hour. You can take advantage of longer data retention time—and with enhanced fan-out capability, you can simultaneously reach two or more downstream applications. Other benefits include additional audit and security transparency.

Kinesis Data Streams also gives you access to [Amazon Kinesis Data Firehose](#) and [Amazon Kinesis Data Analytics](#). These services can help you build applications that power real-time dashboards, generate alerts, implement dynamic pricing and advertising, and implement sophisticated data analytics and machine learning algorithms.

**Note**

Using Kinesis data streams for DynamoDB is subject to both [Kinesis Data Streams pricing](#) for the data stream and [DynamoDB pricing](#) for the source table.

## How Kinesis Data Streams works with DynamoDB

When a Kinesis data stream is enabled for a DynamoDB table, the table sends out a data record that captures any changes to that table's data. This data record includes:

- The specific time any item was recently created, updated, or deleted
- That item's primary key

- An image of the item before the modification
- An image of the item after the modification

These data records are captured and published in near-real time. After they are written to the Kinesis data stream, they can be read just like any other record. You can use the Kinesis Client Library, use AWS Lambda, call the Kinesis Data Streams API, and use other connected services. For more information, see [Reading Data from Amazon Kinesis Data Streams](#) in the Amazon Kinesis Data Streams Developer Guide.

These changes to data are also captured asynchronously. Kinesis has no performance impact on a table that it's streaming from. The stream records stored in your Kinesis data stream are also encrypted at rest. For more information, see [Data Protection in Amazon Kinesis Data Streams](#).

The Kinesis data stream records might appear in a different sequence than the item changes occurred. The same item notifications might also appear more than once in the stream. You can check the `ApproximateCreationDateTime` attribute to identify the actual order that the item modifications occurred, and to identify duplicate records.

`ApproximateCreationDateTime` indicates the time of the modification in milliseconds. If more than one modification occurred to the same item within the same millisecond, the `ApproximateCreationDateTime` is increased by 1 millisecond to present a useful order of occurrence.

DynamoDB charges for using Kinesis Data Streams in change data capture units. 1 KB of change per single item counts as one change data capture unit. The KB of change in each item is calculated by the larger of the "before" and "after" images of the item written to the stream, using the same logic as [capacity unit consumption for write operations](#). Similar to how DynamoDB [on-demand](#) mode works, you don't need to provision capacity throughput for change data capture units.

#### Topics

- [Turning on a Kinesis data stream for your DynamoDB table \(p. 590\)](#)

### Turning on a Kinesis data stream for your DynamoDB table

You can enable or disable streaming to Kinesis from your existing DynamoDB table by using the AWS Management Console, the AWS SDK, or the AWS Command Line Interface (AWS CLI).

- You can only stream data from DynamoDB to Kinesis Data Streams in the same AWS account and AWS Region as your table.
- You can only stream data from a DynamoDB table to one Kinesis data stream.

## Getting started with Kinesis Data Streams for Amazon DynamoDB

This section describes how to use Kinesis Data Streams for Amazon DynamoDB tables with the Amazon DynamoDB console, the AWS Command Line Interface (AWS CLI), and the API.

All of these examples use the `Music` DynamoDB table that was created as part of the [Getting started with DynamoDB](#) tutorial.

#### Console

1. Sign in to the AWS Management Console and open the Kinesis console at <https://console.aws.amazon.com/kinesis/>.
2. Choose **Create data stream** and follow the instructions to create a stream called `samplestream`.

3. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
4. In the navigation pane on the left side of the console, choose **Tables**.
5. Choose the **Music** table.
6. Choose the **Exports and streams** tab.
7. Under **Kinesis data stream details**, choose the **Enable** button.

The screenshot shows the 'Exports and streams' tab for the 'Music' table. The 'Exports to S3' section displays 0 export jobs. Below it, the 'Amazon Kinesis data stream details' section shows that streaming is disabled. The 'Enable' button in this section is circled in red.

8. Choose **samplestream** from the dropdown list.
9. Choose the **Enable stream** button.

#### AWS CLI

1. Create a Kinesis Data Streams named **samplestream** by using the [create-stream command](#).

```
aws kinesis create-stream --stream-name samplestream --shard-count 3
```

See [Shard management considerations for Kinesis Data Streams \(p. 594\)](#) before setting the number of shards for the Kinesis data stream.

2. Check that the Kinesis stream is active and ready for use by using the [describe-stream command](#).

```
aws kinesis describe-stream --stream-name samplestream
```

3. Enable Kinesis streaming on the DynamoDB table by using the DynamoDB [enable-kinesis-streaming-destination command](#). Replace the `stream-arn` value with the one that was returned by `describe-stream` in the previous step.

```
aws dynamodb enable-kinesis-streaming-destination \
--table-name Music \
--stream-arn arn:aws:kinesis:us-west-2:123456789012:stream/samplestream
```

4. Check if Kinesis streaming is active on the table by using the DynamoDB `describe-kinesis-streaming-destination` command.

```
aws dynamodb describe-kinesis-streaming-destination --table-name Music
```

5. Write data to the DynamoDB table by using the `put-item` command, as described in the [DynamoDB Developer Guide](#).

```
aws dynamodb put-item \
--table-name Music \
--item \
'{"Artist": {"S": "No One You Know"}, "SongTitle": {"S": "Call Me Today"}, \
"AlbumTitle": {"S": "Somewhat Famous"}, "Awards": {"N": "1"}}'

aws dynamodb put-item \
--table-name Music \
--item \
'{"Artist": {"S": "Acme Band"}, "SongTitle": {"S": "Happy Day"}, \
"AlbumTitle": {"S": "Songs About Life"}, "Awards": {"N": "10"} }'
```

6. Use the Kinesis [get-records](#) CLI command to retrieve the Kinesis stream contents. Then use the following code snippet to deserialize the stream content.

```
/** 
 * Takes as input a Record fetched from Kinesis and does arbitrary processing as an example.
 */
public void processRecord(Record kinesisRecord) throws IOException {
    ByteBuffer kdsRecordByteBuffer = kinesisRecord.getData();
    JsonNode rootNode = OBJECT_MAPPER.readTree(kdsRecordByteBuffer.array());
    JsonNode dynamoDBRecord = rootNode.get("dynamodb");
    JsonNode oldItemImage = dynamoDBRecord.get("OldImage");
    JsonNode newItemImage = dynamoDBRecord.get("NewImage");
    Instant recordTimestamp = fetchTimestamp(dynamoDBRecord);

    /**
     * Say for example our record contains a String attribute named "stringName" and we want to fetch the value
     * of this attribute from the new item image. The following code fetches this value.
     */
    JsonNode attributeNode = newItemImage.get("stringName");
    JsonNode attributeValueNode = attributeNode.get("S"); // Using DynamoDB "S" type attribute
    String attributeValue = attributeValueNode.textValue();
    System.out.println(attributeValue);
}

private Instant fetchTimestamp(JsonNode dynamoDBRecord) {
    JsonNode timestampJson = dynamoDBRecord.get("ApproximateCreationDateTime");
    return Instant.ofEpochMilli(timestampJson.longValue());
}
```

Java

1. Follow the instructions in the Kinesis Data Streams developer guide to [create](#) a Kinesis data stream named `samplestream` using Java.

See [Shard management considerations for Kinesis Data Streams \(p. 594\)](#) before setting the number of shards for the Kinesis data stream.

2. Use the following code snippet to enable Kinesis streaming on the DynamoDB table

```
EnableKinesisStreamingDestinationRequest enableKdsRequest =
    EnableKinesisStreamingDestinationRequest.builder()
        .tableName(tableName)
        .streamArn(kdsArn)
        .build();

EnableKinesisStreamingDestinationResponse enableKdsResponse =
    ddbClient.enableKinesisStreamingDestination(enableKdsRequest);
```

3. Follow the instructions in the *Kinesis Data Streams developer guide* to [read](#) from the created data stream.
4. Use the following code snippet to deserialize the stream content

```
/**
 * Takes as input a Record fetched from Kinesis and does arbitrary processing as an
 * example.
 */
public void processRecord(Record kinesisRecord) throws IOException {
    ByteBuffer kdsRecordByteBuffer = kinesisRecord.getData();
    JsonNode rootNode = OBJECT_MAPPER.readTree(kdsRecordByteBuffer.array());
    JsonNode dynamoDBRecord = rootNode.get("dynamodb");
    JsonNode oldItemImage = dynamoDBRecord.get("OldImage");
    JsonNode newItemImage = dynamoDBRecord.get("NewImage");
    Instant recordTimestamp = fetchTimestamp(dynamoDBRecord);

    /**
     * Say for example our record contains a String attribute named "stringName"
     * and we wanted to fetch the value
     * of this attribute from the new item image, the below code would fetch this.
     */
    JsonNode attributeNode = newItemImage.get("stringName");
    JsonNode attributeValueNode = attributeNode.get("S"); // Using DynamoDB "S"
    type attribute
    String attributeValue = attributeValueNode.textValue();
    System.out.println(attributeValue);
}

private Instant fetchTimestamp(JsonNode dynamoDBRecord) {
    JsonNode timestampJson = dynamoDBRecord.get("ApproximateCreationDateTime");
    return Instant.ofEpochMilli(timestampJson.longValue());
}
```

To learn more about how to build consumers and connect your Kinesis data stream to other AWS services, see [Reading data from Kinesis Data Streams](#) in the *Amazon Kinesis Data Streams developer guide*.

## Configuring shards and monitoring change data capture with Kinesis Data Streams in DynamoDB

### Shard management considerations for Kinesis Data Streams

A Kinesis data stream counts its throughput in [shards](#). You will need to provision an appropriate number of shards on your Kinesis data stream to accommodate the change data capture records from DynamoDB. To determine the number of shards that the Kinesis data stream will need to support your DynamoDB table, consider the following:

- The average size of your DynamoDB table's record in bytes (`average_record_size_in_bytes`).
- The maximum number of write operations that your DynamoDB table will perform per second. This includes create, delete, and update data operations performed by your applications, as well as automatically generated operations like Time to Live generated deletes (`write_throughput`).
- The percentage of update and overwrite operations that you perform on your table, as compared to create or delete operations (`percentage_of_updates`). Keep in mind that update and overwrite operations replicate both the old and new images of the modified item to the stream. This generates twice the DynamoDB item size.

You can approximate the number of shards (`number_of_shards`) needed for your DynamoDB table's throughput with this formula:

```
number_of_shards = ceiling( ((write_throughput * (1+percentage_of_updates) * average_record_size_in_bytes) /1024 /1024), 1)
```

For example, you might have a maximum throughput of 40 write operations/second (`write_throughput`) with an average record size of 1285 bytes (`average_record_size_in_bytes`). If 25 percent of those write operations are update operations (`percentage_of_updates`), then you will need two shards (`number_of_shards`) to accommodate your DynamoDB streaming throughput: `ceiling( ((40 * (1+25) * 1285) / 1024 / 1024), 1 )`.

Note that this formula reflects only the shards that are needed to accommodate your DynamoDB streaming throughput. It doesn't represent the total number of shards needed in your Kinesis data stream, such as shards required to support Kinesis data stream consumers.

To learn more about determining the size of a Kinesis data stream, see [Determining the Initial Size of a Kinesis Data Stream](#).

### Monitoring change data capture with Kinesis Data Streams

DynamoDB provides several Amazon CloudWatch metrics to help you monitor the replication of change data capture to Kinesis. For a full list of CloudWatch metrics, see [DynamoDB Metrics and dimensions \(p. 1114\)](#).

To determine whether your stream has sufficient capacity, we recommend that you monitor the following items both during stream enabling and in production:

- `ThrottledPutRecordCount`: The number of records that were throttled by your Kinesis data stream because of insufficient Kinesis data stream capacity. You might experience some throttling during exceptional usage peaks, but the `ThrottledPutRecordCount` should remain as low as possible. DynamoDB retries sending throttled records to the Kinesis data stream, but this might result in higher replication latency.

If you experience excessive and regular throttling, you might need to increase the number of Kinesis stream shards proportionally to the observed write throughput of your table. To learn more about determining the size of a Kinesis data stream, see [Determining the Initial Size of a Kinesis Data Stream](#).

- `AgeOfOldestUnreplicatedRecord`: The elapsed time since the oldest item-level change yet to replicate to the Kinesis data stream appeared in the DynamoDB table. Under normal operation, `AgeOfOldestUnreplicatedRecord` should be in the order of milliseconds. This number grows based on unsuccessful replication attempts when these are caused by customer-controlled configuration choices.

Customer-controlled configuration examples that leads to unsuccessful replication attempts are an under-provisioned Kinesis data stream capacity that leads to excessive throttling, or a manual update to your Kinesis data stream's access policies that prevents DynamoDB from adding data to your data stream. To keep this metric as low as possible, you might need to ensure the right provisioning of your Kinesis data stream capacity, and make sure that DynamoDB's permissions are unchanged.

- `FailedToReplicateRecordCount`: The number of records that DynamoDB failed to replicate to your Kinesis data stream. Certain items larger than 34 KB might expand in size to change data records that are larger than the 1 MB item size limit of Kinesis Data Streams. This size expansion occurs when these larger than 34 KB items include a large number of Boolean or empty attribute values. Boolean and empty attribute values are stored as 1 byte in DynamoDB, but expand up to 5 bytes when they're serialized using standard JSON for Kinesis Data Streams replication. DynamoDB can't replicate such change records to your Kinesis data stream. DynamoDB skips these change data records, and automatically continues replicating subsequent records.

You can create Amazon CloudWatch alarms that send an Amazon Simple Notification Service (Amazon SNS) message for notification when any of the preceding metrics exceed a specific threshold. For more information, see [Creating CloudWatch alarms to monitor DynamoDB \(p. 1131\)](#).

## Using IAM policies for Amazon Kinesis Data Streams and Amazon DynamoDB

The first time that you enable Amazon Kinesis Data Streams for Amazon DynamoDB, DynamoDB automatically creates an AWS Identity and Access Management (IAM) service-linked role for you. This role, `AWSServiceRoleForDynamoDBKinesisDataStreamsReplication`, allows DynamoDB to manage the replication of item-level changes to Kinesis Data Streams on your behalf. Don't delete this service-linked role.

For more information about service-linked roles, see [Using service-linked roles](#) in the *IAM User Guide*.

To enable Amazon Kinesis Data Streams for Amazon DynamoDB, you must have the following permissions on the table:

- `dynamodb:EnableKinesisStreamingDestination`
- `kinesis>ListStreams`
- `kinesis:PutRecords`

To describe Amazon Kinesis Data Streams for Amazon DynamoDB for a given DynamoDB table, you must have the following permissions on the table.

- `dynamodb:DescribeKinesisStreamingDestination`
- `kinesis:DescribeStreamSummary`
- `kinesis:DescribeStream`

To disable Amazon Kinesis Data Streams for Amazon DynamoDB, you must have the following permissions on the table.

- `dynamodb:DisableKinesisStreamingDestination`

The following examples show how to use IAM policies to grant permissions for Amazon Kinesis Data Streams for Amazon DynamoDB.

### Example: Enable Amazon Kinesis Data Streams for Amazon DynamoDB

The following IAM policy grants permissions to enable Amazon Kinesis Data Streams for Amazon DynamoDB for the `Music` table and does not grant permissions to disable or describe Kinesis Data Streams for DynamoDB for the `Music` table.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": "iam:CreateServiceLinkedRole",  
            "Resource": "arn:aws:iam::*:role/aws-service-role/  
kinesisreplication.dynamodb.amazonaws.com/  
AWSServiceRoleForDynamoDBKinesisDataStreamsReplication",  
            "Condition": {"StringLike": {"iam:AWSServiceName":  
"kinesisreplication.dynamodb.amazonaws.com"}}  
        },  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:EnableKinesisStreamingDestination"  
            ],  
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"  
        }  
    ]  
}
```

### Example: Disable Amazon Kinesis Data Streams for Amazon DynamoDB

The following IAM policy grants permissions to disable Amazon Kinesis Data Streams for Amazon DynamoDB for the `Music` table and does not grant permissions to enable or describe Amazon Kinesis Data Streams for Amazon DynamoDB for the `Music` table.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:DisableKinesisStreamingDestination"  
            ],  
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"  
        }  
    ]  
}
```

### Example: Selectively apply permissions for Amazon Kinesis Data Streams for Amazon DynamoDB based on resource

The following IAM policy grants permissions to enable and describe Amazon Kinesis Data Streams for Amazon DynamoDB for the `Music` table and denies permissions to disable Amazon Kinesis Data Streams for Amazon DynamoDB for the `Orders` table.

```
{
```

```

    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                "dynamodb:EnableKinesisStreamingDestination",
                "dynamodb:DescribeKinesisStreamingDestination"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
        },
        {
            "Effect": "Deny",
            "Action": [
                "dynamodb:DisableKinesisStreamingDestination"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Orders"
        }
    ]
}

```

## Using service-linked roles for Kinesis Data Streams for DynamoDB

Amazon Kinesis Data Streams for Amazon DynamoDB uses AWS Identity and Access Management (IAM) [service-linked roles](#). A service-linked role is a unique type of IAM role that is linked directly to Kinesis Data Streams for DynamoDB. Service-linked roles are predefined by Kinesis Data Streams for DynamoDB and include all the permissions that the service requires to call other AWS services on your behalf.

A service-linked role makes setting up Kinesis Data Streams for DynamoDB easier because you don't have to manually add the necessary permissions. Kinesis Data Streams for DynamoDB defines the permissions of its service-linked roles, and unless defined otherwise, only Kinesis Data Streams for DynamoDB can assume its roles. The defined permissions include the trust policy and the permissions policy, and that permissions policy cannot be attached to any other IAM entity.

For information about other services that support service-linked roles, see [AWS Services That Work with IAM](#) and look for the services that have **Yes** in the **Service-Linked Role** column. Choose a **Yes** with a link to view the service-linked role documentation for that service.

### Service-linked role permissions for Kinesis Data Streams for DynamoDB

Kinesis Data Streams for DynamoDB uses the service-linked role named **AWSServiceRoleForDynamoDBKinesisDataStreamsReplication**. The purpose of the service-linked role is to allow Amazon DynamoDB to manage the replication of item-level changes to Kinesis Data Streams, on your behalf..

The **AWSServiceRoleForDynamoDBKinesisDataStreamsReplication** service-linked role trusts the following services to assume the role:

- `kinesisreplication.dynamodb.amazonaws.com`

The role permissions policy allows Kinesis Data Streams for DynamoDB to complete the following actions on the specified resources:

- Actions: `Put records` and `describe` on Kinesis stream

You must configure permissions to allow an IAM entity (such as a user, group, or role) to create, edit, or delete a service-linked role. For more information, see [Service-Linked Role Permissions](#) in the *IAM User Guide*.

## [Creating a service-linked role for Kinesis Data Streams for DynamoDB](#)

You don't need to manually create a service-linked role. When you enable Kinesis Data Streams for DynamoDB in the AWS Management Console, the AWS CLI, or the AWS API, Kinesis Data Streams for DynamoDB creates the service-linked role for you.

If you delete this service-linked role, and then need to create it again, you can use the same process to recreate the role in your account. When you enable Kinesis Data Streams for DynamoDB, Kinesis Data Streams for DynamoDB creates the service-linked role for you again.

## [Editing a service-linked role for Kinesis Data Streams for DynamoDB](#)

Kinesis Data Streams for DynamoDB does not allow you to edit the `AWSServiceRoleForDynamoDBKinesisDataStreamsReplication` service-linked role. After you create a service-linked role, you cannot change the name of the role because various entities might reference the role. However, you can edit the description of the role using IAM. For more information, see [Editing a Service-Linked Role](#) in the *IAM User Guide*.

## [Deleting a service-linked role for Kinesis Data Streams for DynamoDB](#)

You can also use the IAM console, the AWS CLI or the AWS API to manually delete the service-linked role. To do this, you must first manually clean up the resources for your service-linked role and then you can manually delete it.

### **Note**

If the Kinesis Data Streams for DynamoDB service is using the role when you try to delete the resources, then the deletion might fail. If that happens, wait for a few minutes and try the operation again.

### [To manually delete the service-linked role using IAM](#)

Use the IAM console, the AWS CLI, or the AWS API to delete the `AWSServiceRoleForDynamoDBKinesisDataStreamsReplication` service-linked role. For more information, see [Deleting a Service-Linked Role](#) in the *IAM User Guide*.

## [Change data capture for DynamoDB Streams](#)

DynamoDB Streams captures a time-ordered sequence of item-level modifications in any DynamoDB table and stores this information in a log for up to 24 hours. Applications can access this log and view the data items as they appeared before and after they were modified, in near-real time.

Encryption at rest encrypts the data in DynamoDB streams. For more information, see [DynamoDB encryption at rest \(p. 1062\)](#).

A *DynamoDB stream* is an ordered flow of information about changes to items in a DynamoDB table. When you enable a stream on a table, DynamoDB captures information about every modification to data items in the table.

Whenever an application creates, updates, or deletes items in the table, DynamoDB Streams writes a stream record with the primary key attributes of the items that were modified. A *stream record* contains information about a data modification to a single item in a DynamoDB table. You can configure the stream so that the stream records capture additional information, such as the "before" and "after" images of modified items.

DynamoDB Streams helps ensure the following:

- Each stream record appears exactly once in the stream.

- For each item that is modified in a DynamoDB table, the stream records appear in the same sequence as the actual modifications to the item.

DynamoDB Streams writes stream records in near-real time so that you can build applications that consume these streams and take action based on the contents.

#### Topics

- [Endpoints for DynamoDB Streams \(p. 599\)](#)
- [Enabling a stream \(p. 599\)](#)
- [Reading and processing a stream \(p. 600\)](#)
- [DynamoDB Streams and Time to Live \(p. 602\)](#)
- [Using the DynamoDB Streams Kinesis adapter to process stream records \(p. 605\)](#)
- [DynamoDB Streams low-level API: Java example \(p. 617\)](#)
- [DynamoDB Streams and AWS Lambda triggers \(p. 621\)](#)

## Endpoints for DynamoDB Streams

AWS maintains separate endpoints for DynamoDB and DynamoDB Streams. To work with database tables and indexes, your application must access a DynamoDB endpoint. To read and process DynamoDB Streams records, your application must access a DynamoDB Streams endpoint in the same Region.

The naming convention for DynamoDB Streams endpoints is `streams.dynamodb.<region>.amazonaws.com`. For example, if you use the endpoint `dynamodb.us-west-2.amazonaws.com` to access DynamoDB, you would use the endpoint `streams.dynamodb.us-west-2.amazonaws.com` to access DynamoDB Streams.

#### Note

For a complete list of DynamoDB and DynamoDB Streams Regions and endpoints, see [Regions and endpoints](#) in the *AWS General Reference*.

The AWS SDKs provide separate clients for DynamoDB and DynamoDB Streams. Depending on your requirements, your application can access a DynamoDB endpoint, a DynamoDB Streams endpoint, or both at the same time. To connect to both endpoints, your application must instantiate two clients—one for DynamoDB and one for DynamoDB Streams.

## Enabling a stream

You can enable a stream on a new table when you create it using the AWS CLI or one of the AWS SDKs. You can also enable or disable a stream on an existing table, or change the settings of a stream. DynamoDB Streams operates asynchronously, so there is no performance impact on a table if you enable a stream.

The easiest way to manage DynamoDB Streams is by using the AWS Management Console.

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. On the DynamoDB console dashboard, choose **Tables** and select an existing table.
3. On the **Exports and streams** tab, in the **DynamoDB stream details** section, choose **Enable**.
4. In the **Enable DynamoDB stream** window, choose the information that will be written to the stream whenever the data in the table is modified:
  - **Key attributes only** — Only the key attributes of the modified item.
  - **New image** — The entire item, as it appears after it was modified.

- **Old image** — The entire item, as it appeared before it was modified.
- **New and old images** — Both the new and the old images of the item.

When the settings are as you want them, choose **Enable stream**.

5. (Optional) To disable an existing stream, choose **Disable** under **DynamoDB stream details**.

You can also use the `CreateTable` or `UpdateTable` API operations to enable or modify a stream. The `StreamSpecification` parameter determines how the stream is configured:

- `StreamEnabled` — Specifies whether a stream is enabled (`true`) or disabled (`false`) for the table.
- `StreamViewType` — Specifies the information that will be written to the stream whenever data in the table is modified:
  - `KEYS_ONLY` — Only the key attributes of the modified item.
  - `NEW_IMAGE` — The entire item, as it appears after it was modified.
  - `OLD_IMAGE` — The entire item, as it appeared before it was modified.
  - `NEW_AND_OLD_IMAGES` — Both the new and the old images of the item.

You can enable or disable a stream at any time. However, you receive a `ResourceInUseException` if you try to enable a stream on a table that already has a stream. You receive a `ValidationException` if you try to disable a stream on a table that doesn't have a stream.

When you set `StreamEnabled` to `true`, DynamoDB creates a new stream with a unique stream descriptor assigned to it. If you disable and then re-enable a stream on the table, a new stream is created with a different stream descriptor.

Every stream is uniquely identified by an Amazon Resource Name (ARN). The following is an example ARN for a stream on a DynamoDB table named `TestTable`.

```
arn:aws:dynamodb:us-west-2:111122223333:table/TestTable/stream/2015-05-11T21:21:33.291
```

To determine the latest stream descriptor for a table, issue a DynamoDB `DescribeTable` request and look for the `LatestStreamArn` element in the response.

**Note**

It is not possible to edit a `StreamViewType` once a stream has been setup. If you need to make changes to a stream after it has been setup, you must disable the current stream and create a new one.

## Reading and processing a stream

To read and process a stream, your application must connect to a DynamoDB Streams endpoint and issue API requests.

A stream consists of *stream records*. Each stream record represents a single data modification in the DynamoDB table to which the stream belongs. Each stream record is assigned a sequence number, reflecting the order in which the record was published to the stream.

Stream records are organized into groups, or *shards*. Each shard acts as a container for multiple stream records, and contains information required for accessing and iterating through these records. The stream records within a shard are removed automatically after 24 hours.


Shards are ephemeral: They are created and deleted automatically, as needed. Any shard can also split into multiple new shards; this also occurs automatically. (It's also possible for a parent shard to have just

one child shard.) A shard might split in response to high levels of write activity on its parent table, so that applications can process records from multiple shards in parallel.

If you disable a stream, any shards that are open will be closed. The data in the stream will continue to be readable for 24 hours.

Because shards have a lineage (parent and children), an application must always process a parent shard before it processes a child shard. This helps ensure that the stream records are also processed in the correct order. (If you use the DynamoDB Streams Kinesis Adapter, this is handled for you. Your application processes the shards and stream records in the correct order. It automatically handles new or expired shards, in addition to shards that split while the application is running. For more information, see [Using the DynamoDB Streams Kinesis adapter to process stream records \(p. 605\)](#).)

The following diagram shows the relationship between a stream, shards in the stream, and stream records in the shards.



#### Note

If you perform a `PutItem` or `UpdateItem` operation that does not change any data in an item, DynamoDB Streams does *not* write a stream record for that operation.

To access a stream and process the stream records within, you must do the following:

- Determine the unique ARN of the stream that you want to access.
- Determine which shards in the stream contain the stream records that you are interested in.
- Access the shards and retrieve the stream records that you want.

#### Note

No more than two processes at most should be reading from the same streams shard at the same time. Having more than two readers per shard can result in throttling.

The DynamoDB Streams API provides the following actions for use by application programs:

- [`ListStreams`](#) — Returns a list of stream descriptors for the current account and endpoint. You can optionally request just the stream descriptors for a particular table name.
- [`DescribeStream`](#) — Returns detailed information about a given stream. The output includes a list of shards associated with the stream, including the shard IDs.
- [`GetShardIterator`](#) — Returns a *shard iterator*, which describes a location within a shard. You can request that the iterator provide access to the oldest point, the newest point, or a particular point in the stream.

- [GetRecords](#) — Returns the stream records from within a given shard. You must provide the shard iterator returned from a [GetShardIterator](#) request.

For complete descriptions of these API operations, including example requests and responses, see the [Amazon DynamoDB Streams API Reference](#).

## Data retention limit for DynamoDB Streams

All data in DynamoDB Streams is subject to a 24-hour lifetime. You can retrieve and analyze the last 24 hours of activity for any given table. However, data that is older than 24 hours is susceptible to trimming (removal) at any moment.

If you disable a stream on a table, the data in the stream continues to be readable for 24 hours. After this time, the data expires and the stream records are automatically deleted. There is no mechanism for manually deleting an existing stream. You must wait until the retention limit expires (24 hours), and all the stream records will be deleted.

## DynamoDB Streams and Time to Live

You can back up, or otherwise process, items that are deleted by [Time to Live \(p. 378\)](#) (TTL) by enabling Amazon DynamoDB Streams on the table and processing the streams records of the expired items.

The streams record contains a user identity field `Records[<index>].userIdentity`.

Items that are deleted by the Time to Live process after expiration have the following fields:

- `Records[<index>].userIdentity.type`  
"Service"
- `Records[<index>].userIdentity.principalId`  
"dynamodb.amazonaws.com"

The following JSON shows the relevant portion of a single streams record.

```
"Records": [
    {
        ...
        "userIdentity": {
            "type": "Service",
            "principalId": "dynamodb.amazonaws.com"
        }
        ...
    }
]
```

## Using DynamoDB Streams and Lambda to archive TTL deleted items

Combining [DynamoDB Time to Live \(TTL\)](#), [DynamoDB Streams](#), and [AWS Lambda](#) can help simplify archiving data, reduce DynamoDB storage costs, and reduce code complexity. Using Lambda as the stream consumer provides many advantages, most notably the cost reduction compared to other consumers such as Kinesis Client Library (KCL). You aren't charged for `GetRecords` API calls on your DynamoDB stream when using Lambda to consume events, and Lambda can provide event filtering

by identifying JSON patterns in a stream event. With event-pattern content filtering, you can define up to five different filters to control which events are sent to Lambda for processing. This helps reduce invocations of your Lambda functions, simplifies code, and reduces overall cost.

While DynamoDB Streams contains all data modifications, such as Create, Modify, and Remove actions, this can result in unwanted invocations of your archive Lambda function. For example, say you have a table with 2 million data modifications per hour flowing into the stream, but less than 5 percent of these are item deletes that will expire through the TTL process and need to be archived. With [Lambda event source filters](#), the Lambda function will only invoke 100,000 times per hour. The result with event filtering is that you're charged only for the needed invocations instead of the 2 million invocations you would have without event filtering.

Event filtering is applied to the [Lambda event source mapping](#), which is a resource that reads from a chosen event—the DynamoDB stream—and invokes a Lambda function. In the following diagram, you can see how a Time to Live deleted item is consumed by a Lambda function using streams and event filters.



### DynamoDB Time to Live event filter pattern

Adding the following JSON to your event source mapping [filter criteria](#) allows invocation of your Lambda function only for TTL deleted items:

```
{
  "Filters": [
    {
      "Pattern": { "userIdentity": { "type": ["Service"], "principalId": ["dynamodb.amazonaws.com"] } }
    }
  ]
}
```

### Create an AWS Lambda event source mapping

Use the following code snippets to create a filtered event source mapping which you can connect to a table's DynamoDB stream. Each code block includes the event filter pattern.

#### AWS CLI

```
aws lambda create-event-source-mapping \
--event-source-arn 'arn:aws:dynamodb:eu-west-1:012345678910:table/test/' \
stream/2021-12-10T00:00:00.000' \
--batch-size 10 \
--enabled \
--function-name test_func \
--starting-position LATEST \
--filter-criteria '{"Filters": [{"Pattern": {"userIdentity": {"type": ["Service"], "principalId": ["dynamodb.amazonaws.com"] }}}]}'
```

#### Java

```
LambdaClient client = LambdaClient.builder()
    .region(Region.EU_WEST_1)
    .build();
```

```

Filter userIdentity = Filter.builder()
    .pattern("{\"userIdentity\":{\"type\":[\"Service\"],\"principalId\":"
    ["dynamodb.amazonaws.com"]}}")
    .build();

FilterCriteria filterCriteria = FilterCriteria.builder()
    .filters(userIdentity)
    .build();

CreateEventSourceMappingRequest mappingRequest =
    CreateEventSourceMappingRequest.builder()
        .eventSourceArn("arn:aws:dynamodb:eu-west-1:012345678910:table/test/"
    stream/2021-12-10T00:00:00.000")
        .batchSize(10)
        .enabled(Boolean.TRUE)
        .functionName("test_func")
        .startingPosition("LATEST")
        .filterCriteria(filterCriteria)
        .build();

try{
    CreateEventSourceMappingResponse eventSourceMappingResponse =
    client.createEventSourceMapping(mappingRequest);
    System.out.println("The mapping ARN is
    "+eventSourceMappingResponse.eventSourceArn());

}catch (ServiceException e){
    System.out.println(e.getMessage());
}

```

## Node

```

const client = new LambdaClient({ region: "eu-west-1" });

const input = {
    EventSourceArn: "arn:aws:dynamodb:eu-west-1:012345678910:table/test/
    stream/2021-12-10T00:00:00.000",
    BatchSize: 10,
    Enabled: true,
    FunctionName: "test_func",
    StartingPosition: "LATEST",
    FilterCriteria: { "Filters": [ { "Pattern": "{\"userIdentity\":{\"type\":[\"Service\"],\"principalId\":["
    "dynamodb.amazonaws.com"]}}" } ] }
}

const command = new CreateEventSourceMappingCommand(input);

try {
    const results = await client.send(command);
    console.log(results);
} catch (err) {
    console.error(err);
}

```

## Python

```

session = boto3.session.Session(region_name = 'eu-west-1')
client = session.client('lambda')

try:
    response = client.create_event_source_mapping(

```

```
EventSourceArn='arn:aws:dynamodb:eu-west-1:012345678910:table/test/  
stream/2021-12-10T00:00:00.000',  
BatchSize=10,  
Enabled=True,  
FunctionName='test_func',  
StartingPosition='LATEST',  
FilterCriteria={  
    'Filters': [  
        {  
            'Pattern': "{\"userIdentity\": {\"type\": [\"Service\"]}, \"principalId  
\": [\"dynamodb.amazonaws.com\"]}}"  
        },  
    ]  
}  
print(response)  
except Exception as e:  
    print(e)
```

JSON

```
{  
    "userIdentity": {  
        "type": ["Service"],  
        "principalId": ["dynamodb.amazonaws.com"]  
    }  
}
```


## Using the DynamoDB Streams Kinesis adapter to process stream records

Using the Amazon Kinesis Adapter is the recommended way to consume streams from Amazon DynamoDB. The DynamoDB Streams API is intentionally similar to that of Kinesis Data Streams, a service for real-time processing of streaming data at massive scale. In both services, data streams are composed of shards, which are containers for stream records. Both services' APIs contain `ListStreams`, `DescribeStream`, `GetShards`, and `GetShardIterator` operations. (Although these DynamoDB Streams actions are similar to their counterparts in Kinesis Data Streams, they are not 100 percent identical.)

You can write applications for Kinesis Data Streams using the Kinesis Client Library (KCL). The KCL simplifies coding by providing useful abstractions above the low-level Kinesis Data Streams API. For more information about the KCL, see the [Developing consumers using the Kinesis client library](#) in the *Amazon Kinesis Data Streams Developer Guide*.

As a DynamoDB Streams user, you can use the design patterns found within the KCL to process DynamoDB Streams shards and stream records. To do this, you use the DynamoDB Streams Kinesis Adapter. The Kinesis Adapter implements the Kinesis Data Streams interface so that the KCL can be used for consuming and processing records from DynamoDB Streams.

The following diagram shows how these libraries interact with one another.



With the DynamoDB Streams Kinesis Adapter in place, you can begin developing against the KCL interface, with the API calls seamlessly directed at the DynamoDB Streams endpoint.

When your application starts, it calls the KCL to instantiate a worker. You must provide the worker with configuration information for the application, such as the stream descriptor and AWS credentials, and the name of a record processor class that you provide. As it runs the code in the record processor, the worker performs the following tasks:

- Connects to the stream.
- Enumerates the shards within the stream.
- Coordinates shard associations with other workers (if any).
- Instantiates a record processor for every shard it manages.

- Pulls records from the stream.
- Pushes the records to the corresponding record processor.
- Checkpoints processed records.
- Balances shard-worker associations when the worker instance count changes.
- Balances shard-worker associations when shards are split.

**Note**

For a description of the KCL concepts listed here, see [Developing consumers using the Kinesis client library](#) in the *Amazon Kinesis Data Streams Developer Guide*.

For more information on using streams with AWS Lambda see [DynamoDB Streams and AWS Lambda triggers \(p. 621\)](#)

## Walkthrough: DynamoDB Streams Kinesis adapter

This section is a walkthrough of a Java application that uses the Amazon Kinesis Client Library and the Amazon DynamoDB Streams Kinesis Adapter. The application shows an example of data replication, in which write activity from one table is applied to a second table, with both tables' contents staying in sync. For the source code, see [Complete program: DynamoDB Streams Kinesis adapter \(p. 610\)](#).

The program does the following:

1. Creates two DynamoDB tables named `KCL-Demo-src` and `KCL-Demo-dst`. Each of these tables has a stream enabled on it.
2. Generates update activity in the source table by adding, updating, and deleting items. This causes data to be written to the table's stream.
3. Reads the records from the stream, reconstructs them as DynamoDB requests, and applies the requests to the destination table.
4. Scans the source and destination tables to ensure that their contents are identical.
5. Cleans up by deleting the tables.

These steps are described in the following sections, and the complete application is shown at the end of the walkthrough.

### Topics

- [Step 1: Create DynamoDB tables \(p. 607\)](#)
- [Step 2: Generate update activity in source table \(p. 608\)](#)
- [Step 3: Process the stream \(p. 608\)](#)
- [Step 4: Ensure that both tables have identical contents \(p. 609\)](#)
- [Step 5: Clean up \(p. 609\)](#)
- [Complete program: DynamoDB Streams Kinesis adapter \(p. 610\)](#)

### Step 1: Create DynamoDB tables

The first step is to create two DynamoDB tables—a source table and a destination table. The `StreamViewType` on the source table's stream is `NEW_IMAGE`. This means that whenever an item is modified in this table, the item's "after" image is written to the stream. In this way, the stream keeps track of all write activity on the table.

The following example shows the code that is used for creating both tables.

```

java.util.List<AttributeDefinition> attributeDefinitions = new
    ArrayList<AttributeDefinition>();
attributeDefinitions.add(new
    AttributeDefinition().withAttributeName("Id").withAttributeType("N"));

java.util.List<KeySchemaElement> keySchema = new ArrayList<KeySchemaElement>();
keySchema.add(new KeySchemaElement().withAttributeName("Id").withKeyType(KeyType.HASH)); // Partition
// key

ProvisionedThroughput provisionedThroughput = new
    ProvisionedThroughput().withReadCapacityUnits(2L)
        .withWriteCapacityUnits(2L);

StreamSpecification streamSpecification = new StreamSpecification();
streamSpecification.setStreamEnabled(true);
streamSpecification.setStreamViewType(StreamViewType.NEW_IMAGE);
CreateTableRequest createTableRequest = new CreateTableRequest().withTableName(tableName)
    .withAttributeDefinitions(attributeDefinitions).withKeySchema(keySchema)

    .withProvisionedThroughput(provisionedThroughput).withStreamSpecification(streamSpecification);

```

### Step 2: Generate update activity in source table

The next step is to generate some write activity on the source table. While this activity is taking place, the source table's stream is also updated in near-real time.

The application defines a helper class with methods that call the `PutItem`, `UpdateItem`, and `DeleteItem` API operations for writing the data. The following code example shows how these methods are used.

```

StreamsAdapterDemoHelper.putItem(dynamoDBClient, tableName, "101", "test1");
StreamsAdapterDemoHelper.updateItem(dynamoDBClient, tableName, "101", "test2");
StreamsAdapterDemoHelper.deleteItem(dynamoDBClient, tableName, "101");
StreamsAdapterDemoHelper.putItem(dynamoDBClient, tableName, "102", "demo3");
StreamsAdapterDemoHelper.updateItem(dynamoDBClient, tableName, "102", "demo4");
StreamsAdapterDemoHelper.deleteItem(dynamoDBClient, tableName, "102");

```

### Step 3: Process the stream

Now the program begins processing the stream. The DynamoDB Streams Kinesis Adapter acts as a transparent layer between the KCL and the DynamoDB Streams endpoint, so that the code can fully use KCL rather than having to make low-level DynamoDB Streams calls. The program performs the following tasks:

- It defines a record processor class, `StreamsRecordProcessor`, with methods that comply with the KCL interface definition: `initialize`, `processRecords`, and `shutdown`. The `processRecords` method contains the logic required for reading from the source table's stream and writing to the destination table.
- It defines a class factory for the record processor class (`StreamsRecordProcessorFactory`). This is required for Java programs that use the KCL.
- It instantiates a new KCL Worker, which is associated with the class factory.
- It shuts down the worker when record processing is complete.

To learn more about the KCL interface definition, see [Developing consumers using the Kinesis client library](#) in the *Amazon Kinesis Data Streams Developer Guide*.

The following code example shows the main loop in `StreamsRecordProcessor`. The `case` statement determines what action to perform, based on the `OperationType` that appears in the stream record.

```

for (Record record : records) {
    String data = new String(record.getData().array(), Charset.forName("UTF-8"));
    System.out.println(data);
    if (record instanceof RecordAdapter) {
        com.amazonaws.services.dynamodbv2.model.Record streamRecord =
        ((RecordAdapter) record)
            .getInternalObject();

        switch (streamRecord.getEventName()) {
            case "INSERT":
            case "MODIFY":
                StreamsAdapterDemoHelper.putItem(dynamoDBClient, tableName,
                    streamRecord.getDynamodb().getNewImage());
                break;
            case "REMOVE":
                StreamsAdapterDemoHelper.deleteItem(dynamoDBClient, tableName,
                    streamRecord.getDynamodb().getKeys().get("Id").getN());
        }
    }
    checkpointCounter += 1;
    if (checkpointCounter % 10 == 0) {
        try {
            checkpointer.checkpoint();
        }
        catch (Exception e) {
            e.printStackTrace();
        }
    }
}
}

```

#### Step 4: Ensure that both tables have identical contents

At this point, the source and destination tables' contents are in sync. The application issues `Scan` requests against both tables to verify that their contents are, in fact, identical.

The `DemoHelper` class contains a `ScanTable` method that calls the low-level `Scan` API. The following example shows how this is used.

```

if (StreamsAdapterDemoHelper.scanTable(dynamoDBClient, srcTable).getItems()
    .equals(StreamsAdapterDemoHelper.scanTable(dynamoDBClient, destTable).getItems())) {
    System.out.println("Scan result is equal.");
}
else {
    System.out.println("Tables are different!");
}

```

#### Step 5: Clean up

The demo is complete, so the application deletes the source and destination tables. See the following code example. Even after the tables are deleted, their streams remain available for up to 24 hours, after which they are automatically deleted.

```

dynamoDBClient.deleteTable(new DeleteTableRequest().withTableName(srcTable));
dynamoDBClient.deleteTable(new DeleteTableRequest().withTableName(destTable));

```

## Complete program: DynamoDB Streams Kinesis adapter

The following is the complete Java program that performs the tasks described in [Walkthrough: DynamoDB Streams Kinesis adapter \(p. 607\)](#). When you run it, you should see output similar to the following.

```
Creating table KCL-Demo-src
Creating table KCL-Demo-dest
Table is active.
Creating worker for stream: arn:aws:dynamodb:us-west-2:111122223333:table/KCL-Demo-src/
stream/2015-05-19T22:48:56.601
Starting worker...
Scan result is equal.
Done.
```

### Important

To run this program, ensure that the client application has access to DynamoDB and Amazon CloudWatch using policies. For more information, see [Using identity-based policies \(IAM policies\) with Amazon DynamoDB \(p. 1075\)](#).

The source code consists of four .java files:

- `StreamsAdapterDemo.java`
- `StreamsRecordProcessor.java`
- `StreamsRecordProcessorFactory.java`
- `StreamsAdapterDemoHelper.java`

### [StreamsAdapterDemo.java](#)

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples;

import com.amazonaws.auth.AWS CredentialsProvider;
import com.amazonaws.auth.DefaultAWS CredentialsProviderChain;
import com.amazonaws.regions.Regions;
import com.amazonaws.services.cloudwatch.AmazonCloudWatch;
import com.amazonaws.services.cloudwatch.AmazonCloudWatchClientBuilder;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBStreams;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBStreamsClientBuilder;
import com.amazonaws.services.dynamodbv2.model.DeleteTableRequest;
import com.amazonaws.services.dynamodbv2.model.DescribeTableResult;
import com.amazonaws.services.dynamodbv2.streamsadapter.AmazonDynamoDBStreamsAdapterClient;
import com.amazonaws.services.dynamodbv2.streamsadapter.StreamsWorkerFactory;
import com.amazonaws.services.kinesis.clientlibrary.interfaces.v2.IRecordProcessorFactory;
```

```

import com.amazonaws.services.kinesis.clientlibrary.lib.worker.InitialPositionInStream;
import
com.amazonaws.services.kinesis.clientlibrary.lib.worker.KinesisClientLibConfiguration;
import com.amazonaws.services.kinesis.clientlibrary.lib.worker.Worker;

public class StreamsAdapterDemo {
    private static Worker worker;
    private static KinesisClientLibConfiguration workerConfig;
    private static IRecordProcessorFactory recordProcessorFactory;

    private static AmazonDynamoDB dynamoDBClient;
    private static AmazonCloudWatch cloudWatchClient;
    private static AmazonDynamoDBStreams dynamoDBStreamsClient;
    private static AmazonDynamoDBStreamsAdapterClient adapterClient;

    private static String tablePrefix = "KCL-Demo";
    private static String streamArn;

    private static Regions awsRegion = Regions.US_EAST_2;

    private static AWSCredentialsProvider awsCredentialsProvider =
DefaultAWSCredentialsProviderChain.getInstance();

    /**
     * @param args
     */
    public static void main(String[] args) throws Exception {
        System.out.println("Starting demo...");

        dynamoDBClient = AmazonDynamoDBClientBuilder.standard()
            .withRegion(awsRegion)
            .build();
        cloudWatchClient = AmazonCloudWatchClientBuilder.standard()
            .withRegion(awsRegion)
            .build();
        dynamoDBStreamsClient = AmazonDynamoDBStreamsClientBuilder.standard()
            .withRegion(awsRegion)
            .build();
        adapterClient = new AmazonDynamoDBStreamsAdapterClient(dynamoDBStreamsClient);
        String srcTable = tablePrefix + "-src";
        String destTable = tablePrefix + "-dest";
        recordProcessorFactory = new StreamsRecordProcessorFactory(dynamoDBClient,
destTable);

        setUpTables();

        workerConfig = new KinesisClientLibConfiguration("streams-adapter-demo",
streamArn,
awsCredentialsProvider,
"streams-demo-worker")
            .withMaxRecords(1000)
            .withIdleTimeBetweenReadsInMillis(500)
            .withInitialPositionInStream(InitialPositionInStream.TRIM_HORIZON);

        System.out.println("Creating worker for stream: " + streamArn);
        worker = StreamsWorkerFactory.createDynamoDbStreamsWorker(recordProcessorFactory,
workerConfig, adapterClient, dynamoDBClient, cloudWatchClient);
        System.out.println("Starting worker...");
        Thread t = new Thread(worker);
        t.start();

        Thread.sleep(25000);
        worker.shutdown();
        t.join();

        if (StreamsAdapterDemoHelper.scanTable(dynamoDBClient, srcTable).getItems()

```

```

.equals(StreamsAdapterDemoHelper.scanTable(dynamoDBClient, destTable).getItems())) {
    System.out.println("Scan result is equal.");
}
else {
    System.out.println("Tables are different!");
}

System.out.println("Done.");
cleanupAndExit(0);
}

private static void setUpTables() {
    String srcTable = tablePrefix + "-src";
    String destTable = tablePrefix + "-dest";
    streamArn = StreamsAdapterDemoHelper.createTable(dynamoDBClient, srcTable);
    StreamsAdapterDemoHelper.createTable(dynamoDBClient, destTable);

    awaitTableCreation(srcTable);

    performOps(srcTable);
}

private static void awaitTableCreation(String tableName) {
    Integer retries = 0;
    Boolean created = false;
    while (!created && retries < 100) {
        DescribeTableResult result =
StreamsAdapterDemoHelper.describeTable(dynamoDBClient, tableName);
        created = result.getTable().getTableStatus().equals("ACTIVE");
        if (created) {
            System.out.println("Table is active.");
            return;
        }
        else {
            retries++;
            try {
                Thread.sleep(1000);
            }
            catch (InterruptedException e) {
                // do nothing
            }
        }
    }
    System.out.println("Timeout after table creation. Exiting...");
    cleanupAndExit(1);
}

private static void performOps(String tableName) {
    StreamsAdapterDemoHelper.putItem(dynamoDBClient, tableName, "101", "test1");
    StreamsAdapterDemoHelper.updateItem(dynamoDBClient, tableName, "101", "test2");
    StreamsAdapterDemoHelper.deleteItem(dynamoDBClient, tableName, "101");
    StreamsAdapterDemoHelper.putItem(dynamoDBClient, tableName, "102", "demo3");
    StreamsAdapterDemoHelper.updateItem(dynamoDBClient, tableName, "102", "demo4");
    StreamsAdapterDemoHelper.deleteItem(dynamoDBClient, tableName, "102");
}

private static void cleanupAndExit(Integer returnValue) {
    String srcTable = tablePrefix + "-src";
    String destTable = tablePrefix + "-dest";
    dynamoDBClient.deleteTable(new DeleteTableRequest().withTableName(srcTable));
    dynamoDBClient.deleteTable(new DeleteTableRequest().withTableName(destTable));
    System.exit(returnValue);
}
}

```

### StreamsRecordProcessor.java

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
  
package com.amazonaws.codesamples;  
  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;  
import com.amazonaws.services.dynamodbv2.streamsadapter.model.RecordAdapter;  
import com.amazonaws.services.kinesis.clientlibrary.interfaces.v2.IRecordProcessor;  
import com.amazonaws.services.kinesis.clientlibrary.lib.worker.ShutdownReason;  
import com.amazonaws.services.kinesis.clientlibrary.types.InitializationInput;  
import com.amazonaws.services.kinesis.clientlibrary.types.ProcessRecordsInput;  
import com.amazonaws.services.kinesis.clientlibrary.types.ShutdownInput;  
import com.amazonaws.services.kinesis.model.Record;  
  
import java.nio.charset.Charset;  
  
public class StreamsRecordProcessor implements IRecordProcessor {  
    private Integer checkpointCounter;  
  
    private final AmazonDynamoDB dynamoDBClient;  
    private final String tableName;  
  
    public StreamsRecordProcessor(AmazonDynamoDB dynamoDBClient2, String tableName) {  
        this.dynamoDBClient = dynamoDBClient2;  
        this.tableName = tableName;  
    }  
  
    @Override  
    public void initialize(InitializationInput initializationInput) {  
        checkpointCounter = 0;  
    }  
  
    @Override  
    public void processRecords(ProcessRecordsInput processRecordsInput) {  
        for (Record record : processRecordsInput.getRecords()) {  
            String data = new String(record.getData().array(), Charset.forName("UTF-8"));  
            System.out.println(data);  
            if (record instanceof RecordAdapter) {  
                com.amazonaws.services.dynamodbv2.model.Record streamRecord =  
                ((RecordAdapter) record)  
                    .getInternalObject();  
  
                switch (streamRecord.getEventName()) {  
                    case "INSERT":  
                    case "MODIFY":  
                        StreamsAdapterDemoHelper.putItem(dynamoDBClient, tableName,  
                            streamRecord.getDynamodb().getNewImage());  
                }  
            }  
        }  
    }  
}
```

```

        break;
    case "REMOVE":
        StreamsAdapterDemoHelper.deleteItem(dynamoDBClient, tableName,
streamRecord.getDynamodb().getKeys().get("Id").getN());
    }
}
checkpointCounter += 1;
if (checkpointCounter % 10 == 0) {
    try {
        processRecordsInput.getCheckpointer().checkpoint();
    }
    catch (Exception e) {
        e.printStackTrace();
    }
}
}
}

@Override
public void shutdown(ShutdownInput shutdownInput) {
    if (shutdownInput.getShutdownReason() == ShutdownReason.TERMINATE) {
        try {
            shutdownInput.getCheckpointer().checkpoint();
        }
        catch (Exception e) {
            e.printStackTrace();
        }
    }
}
}

```

### StreamsRecordProcessorFactory.java

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.kinesis.clientlibrary.interfaces.v2.IRecordProcessor;
import com.amazonaws.services.kinesis.clientlibrary.interfaces.v2.IRecordProcessorFactory;

public class StreamsRecordProcessorFactory implements IRecordProcessorFactory {
    private final String tableName;
    private final AmazonDynamoDB dynamoDBClient;

    public StreamsRecordProcessorFactory(AmazonDynamoDB dynamoDBClient, String tableName) {
        this.tableName = tableName;
    }
}

```

```
        this.dynamoDBClient = dynamoDBClient;
    }

    @Override
    public IRecordProcessor createProcessor() {
        return new StreamsRecordProcessor(dynamoDBClient, tableName);
    }
}
```

### StreamsAdapterDemoHelper.java

```
/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples;

import java.util.ArrayList;
import java.util.HashMap;
import java.util.Map;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.model.AttributeAction;
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
import com.amazonaws.services.dynamodbv2.model.AttributeValueUpdate;
import com.amazonaws.services.dynamodbv2.model.CreateTableRequest;
import com.amazonaws.services.dynamodbv2.model.CreateTableResult;
import com.amazonaws.services.dynamodbv2.model.DeleteItemRequest;
import com.amazonaws.services.dynamodbv2.model.DescribeTableRequest;
import com.amazonaws.services.dynamodbv2.model.DescribeTableResult;
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;
import com.amazonaws.services.dynamodbv2.model.KeyType;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;
import com.amazonaws.services.dynamodbv2.model.PutItemRequest;
import com.amazonaws.services.dynamodbv2.model.ResourceInUseException;
import com.amazonaws.services.dynamodbv2.model.ScanRequest;
import com.amazonaws.services.dynamodbv2.model.ScanResult;
import com.amazonaws.services.dynamodbv2.model.StreamSpecification;
import com.amazonaws.services.dynamodbv2.model.StreamViewType;
import com.amazonaws.services.dynamodbv2.model.UpdateItemRequest;

public class StreamsAdapterDemoHelper {

    /**
     * @return StreamArn
     */
    public static String createTable(AmazonDynamoDB client, String tableName) {
        java.util.List<AttributeDefinition> attributeDefinitions = new
ArrayList<AttributeDefinition>();
        attributeDefinitions.add(new
AttributeDefinition().withAttributeName("Id").withAttributeType("N"));
    }
}
```

```

        java.util.List<KeySchemaElement> keySchema = new ArrayList<KeySchemaElement>();
        keySchema.add(new
KeySchemaElement().withAttributeName("Id").withKeyType(KeyType.HASH)); // Partition

        // key

        ProvisionedThroughput provisionedThroughput = new
ProvisionedThroughput().withReadCapacityUnits(2L)
                    .withWriteCapacityUnits(2L);

        StreamSpecification streamSpecification = new StreamSpecification();
        streamSpecification.setStreamEnabled(true);
        streamSpecification.setStreamViewType(StreamViewType.NEW_IMAGE);
        CreateTableRequest createTableRequest = new
CreateTableRequest().withTableName(tableName)
                    .withAttributeDefinitions(attributeDefinitions).withKeySchema(keySchema)

        .withProvisionedThroughput(provisionedThroughput).withStreamSpecification(streamSpecification);

        try {
            System.out.println("Creating table " + tableName);
            CreateTableResult result = client.createTable(createTableRequest);
            return result.getTableDescription().getLatestStreamArn();
        }
        catch (ResourceInUseException e) {
            System.out.println("Table already exists.");
            return describeTable(client, tableName).getTable().getLatestStreamArn();
        }
    }

    public static DescribeTableResult describeTable(AmazonDynamoDB client, String
tableName) {
    return client.describeTable(new DescribeTableRequest().withTableName(tableName));
}

    public static ScanResult scanTable(AmazonDynamoDB dynamoDBClient, String tableName) {
        return dynamoDBClient.scan(new ScanRequest().withTableName(tableName));
    }

    public static void putItem(AmazonDynamoDB dynamoDBClient, String tableName, String id,
String val) {
        java.util.Map<String, AttributeValue> item = new HashMap<String, AttributeValue>();
        item.put("Id", new AttributeValue().withN(id));
        item.put("attribute-1", new AttributeValue().withS(val));

        PutItemRequest putItemRequest = new
PutItemRequest().withTableName(tableName).withItem(item);
        dynamoDBClient.putItem(putItemRequest);
    }

    public static void putItem(AmazonDynamoDB dynamoDBClient, String tableName,
        java.util.Map<String, AttributeValue> items) {
        PutItemRequest putItemRequest = new
PutItemRequest().withTableName(tableName).withItem(items);
        dynamoDBClient.putItem(putItemRequest);
    }

    public static void updateItem(AmazonDynamoDB dynamoDBClient, String tableName, String
id, String val) {
        java.util.Map<String, AttributeValue> key = new HashMap<String, AttributeValue>();
        key.put("Id", new AttributeValue().withN(id));

        Map<String, AttributeValueUpdate> attributeUpdates = new HashMap<String,
AttributeValueUpdate>();
        AttributeValueUpdate update = new
AttributeValueUpdate().withAction(AttributeAction.PUT)

```

```
        .withValue(new AttributeValue().withS(val));
    attributeUpdates.put("attribute-2", update);

    UpdateItemRequest updateItemRequest = new
UpdateItemRequest().withTableName(tableName).withKey(key)
        .withAttributeUpdates(attributeUpdates);
    dynamoDBClient.updateItem(updateItemRequest);
}

public static void deleteItem(AmazonDynamoDB dynamoDBClient, String tableName, String
id) {
    java.util.Map<String, AttributeValue> key = new HashMap<String, AttributeValue>();
    key.put("Id", new AttributeValue().withN(id));

    DeleteItemRequest deleteItemRequest = new
DeleteItemRequest().withTableName(tableName).withKey(key);
    dynamoDBClient.deleteItem(deleteItemRequest);
}

}
```

## DynamoDB Streams low-level API: Java example

### Note

The code on this page is not exhaustive and does not handle all scenarios for consuming Amazon DynamoDB Streams. The recommended way to consume stream records from DynamoDB is through the Amazon Kinesis Adapter using the Kinesis Client Library (KCL), as described in [Using the DynamoDB Streams Kinesis adapter to process stream records \(p. 605\)](#).

This section contains a Java program that shows DynamoDB Streams in action. The program does the following:

1. Creates a DynamoDB table with a stream enabled.
2. Describes the stream settings for this table.
3. Modifies data in the table.
4. Describes the shards in the stream.
5. Reads the stream records from the shards.
6. Cleans up.

When you run the program, you will see output similar to the following.

```
Issuing CreateTable request for TestTableForStreams
Waiting for TestTableForStreams to be created...
Current stream ARN for TestTableForStreams: arn:aws:dynamodb:us-east-2:123456789012:table/
TestTableForStreams/stream/2018-03-20T16:49:55.208
Stream enabled: true
Update view type: NEW_AND_OLD_IMAGES

Performing write activities on TestTableForStreams
Processing item 1 of 100
Processing item 2 of 100
Processing item 3 of 100
...
Processing item 100 of 100

Shard: {ShardId: shardId-1234567890-..., SequenceNumberRange: {StartingSequenceNumber:
01234567890..., }, }
Shard iterator: EjYFEkX2a26eVTWe...
```

```

    ApproximateCreationDateTime: Tue Mar 20 09:50:00 PDT 2018,Keys:
{Id={N: 1,}},NewImage: {Message={S: New item!}, Id={N: 1,}},SequenceNumber:
100000000003218256368,SizeBytes: 24,StreamViewType: NEW_AND_OLD_IMAGES}
    {ApproximateCreationDateTime: Tue Mar 20 09:50:00 PDT 2018,Keys: {Id={N:
1,}},NewImage: {Message={S: This item has changed,}, Id={N: 1,}},OldImage:
{Message={S: New item!}, Id={N: 1,}},SequenceNumber: 200000000003218256412,SizeBytes:
56,StreamViewType: NEW_AND_OLD_IMAGES}
    {ApproximateCreationDateTime: Tue Mar 20 09:50:00 PDT 2018,Keys: {Id={N:
1,}},OldImage: {Message={S: This item has changed,}, Id={N: 1,}},SequenceNumber:
300000000003218256413,SizeBytes: 36,StreamViewType: NEW_AND_OLD_IMAGES}
...
Deleting the table...
Demo complete

```

## Example

```

/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples;

import java.util.ArrayList;
import java.util.Arrays;
import java.util.HashMap;
import java.util.List;
import java.util.Map;

import com.amazonaws.AmazonClientException;
import com.amazonaws.auth.DefaultAWSCredentialsProviderChain;
import com.amazonaws.regions.Regions;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBStreams;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBStreamsClientBuilder;
import com.amazonaws.services.dynamodbv2.model.AttributeAction;
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
import com.amazonaws.services.dynamodbv2.model.AttributeValueUpdate;
import com.amazonaws.services.dynamodbv2.model.CreateTableRequest;
import com.amazonaws.services.dynamodbv2.model.DescribeStreamRequest;
import com.amazonaws.services.dynamodbv2.model.DescribeStreamResult;
import com.amazonaws.services.dynamodbv2.model.DescribeTableResult;
import com.amazonaws.services.dynamodbv2.model.GetRecordsRequest;
import com.amazonaws.services.dynamodbv2.model.GetRecordsResult;
import com.amazonaws.services.dynamodbv2.model.GetShardIteratorRequest;
import com.amazonaws.services.dynamodbv2.model.GetShardIteratorResult;
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;
import com.amazonaws.services.dynamodbv2.model.KeyType;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;
import com.amazonaws.services.dynamodbv2.model.Record;
import com.amazonaws.services.dynamodbv2.model.Shard;
```

```

import com.amazonaws.services.dynamodbv2.model.ShardIteratorType;
import com.amazonaws.services.dynamodbv2.model.StreamSpecification;
import com.amazonaws.services.dynamodbv2.model.StreamViewType;
import com.amazonaws.services.dynamodbv2.util.TableUtils;

public class StreamsLowLevelDemo {

    public static void main(String args[]) throws InterruptedException {

        AmazonDynamoDB dynamoDBClient = AmazonDynamoDBClientBuilder
            .standard()
            .withRegion(Regions.US_EAST_2)
            .withCredentials(new DefaultAWSCredentialsProviderChain())
            .build();

        AmazonDynamoDBStreams streamsClient =
            AmazonDynamoDBStreamsClientBuilder
                .standard()
                .withRegion(Regions.US_EAST_2)
                .withCredentials(new DefaultAWSCredentialsProviderChain())
                .build();

        // Create a table, with a stream enabled
        String tableName = "TestTableForStreams";

        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>(
            Arrays.asList(new AttributeDefinition()
                .withAttributeName("Id")
                .withAttributeType("N")));

        ArrayList<KeySchemaElement> keySchema = new ArrayList<>(
            Arrays.asList(new KeySchemaElement()
                .withAttributeName("Id")
                .withKeyType(KeyType.HASH))); // Partition key

        StreamSpecification streamSpecification = new StreamSpecification()
            .withStreamEnabled(true)
            .withStreamViewType(StreamViewType.NEW_AND_OLD_IMAGES);

        CreateTableRequest createTableRequest = new
        CreateTableRequest().withTableName(tableName)
            .withKeySchema(keySchema).withAttributeDefinitions(attributeDefinitions)
            .withProvisionedThroughput(new ProvisionedThroughput()
                .withReadCapacityUnits(10L)
                .withWriteCapacityUnits(10L))
            .withStreamSpecification(streamSpecification);

        System.out.println("Issuing CreateTable request for " + tableName);
        dynamoDBClient.createTable(createTableRequest);
        System.out.println("Waiting for " + tableName + " to be created...");

        try {
            TableUtils.waitUntilActive(dynamoDBClient, tableName);
        } catch (AmazonClientException e) {
            e.printStackTrace();
        }

        // Print the stream settings for the table
        DescribeTableResult describeTableResult = dynamoDBClient.describeTable(tableName);
        String streamArn = describeTableResult.getTable().getLatestStreamArn();
        System.out.println("Current stream ARN for " + tableName + ": " +
            describeTableResult.getTable().getLatestStreamArn());
        StreamSpecification streamSpec =
        describeTableResult.getTable().getStreamSpecification();
        System.out.println("Stream enabled: " + streamSpec.getStreamEnabled());
        System.out.println("Update view type: " + streamSpec.getStreamViewType());
    }
}

```

```

System.out.println();

// Generate write activity in the table

System.out.println("Performing write activities on " + tableName);
int maxItemCount = 100;
for (Integer i = 1; i <= maxItemCount; i++) {
    System.out.println("Processing item " + i + " of " + maxItemCount);

    // Write a new item
    Map<String,AttributeValue> item = new HashMap<>();
    item.put("Id", new AttributeValue().withN(i.toString()));
    item.put("Message", new AttributeValue().withS("New item!"));
    dynamoDBClient.putItem(tableName, item);

    // Update the item
    Map<String,AttributeValue> key = new HashMap<>();
    key.put("Id", new AttributeValue().withN(i.toString()));
    Map<String,AttributeValueUpdate> attributeUpdates = new HashMap<>();
    attributeUpdates.put("Message", new AttributeValueUpdate()
        .withAction(AttributeAction.PUT)
        .WithValue(new AttributeValue()
            .withS("This item has changed")));
    dynamoDBClient.updateItem(tableName, key, attributeUpdates);

    // Delete the item
    dynamoDBClient.deleteItem(tableName, key);
}

// Get all the shard IDs from the stream. Note that DescribeStream returns
// the shard IDs one page at a time.
String lastEvaluatedShardId = null;

do {
    DescribeStreamResult describeStreamResult = streamsClient.describeStream(
        new DescribeStreamRequest()
            .withStreamArn(streamArn)
            .withExclusiveStartShardId(lastEvaluatedShardId));
    List<Shard> shards = describeStreamResult.getStreamDescription().getShards();

    // Process each shard on this page

    for (Shard shard : shards) {
        String shardId = shard.getShardId();
        System.out.println("Shard: " + shard);

        // Get an iterator for the current shard

        GetShardIteratorRequest getShardIteratorRequest = new
GetShardIteratorRequest()
            .withStreamArn(streamArn)
            .withShardId(shardId)
            .withShardIteratorType(ShardIteratorType.TRIM_HORIZON);
        GetShardIteratorResult getShardIteratorResult =
            streamsClient.getShardIterator(getShardIteratorRequest);
        String currentShardIter = getShardIteratorResult.getShardIterator();

        // Shard iterator is not null until the Shard is sealed (marked as
READ_ONLY).
        // To prevent running the loop until the Shard is sealed, which will be on
average
        // 4 hours, we process only the items that were written into DynamoDB and
then exit.
        int processedRecordCount = 0;
        while (currentShardIter != null && processedRecordCount < maxItemCount) {

```

```

        System.out.println("      Shard iterator: " +
currentShardIter.substring(380));

        // Use the shard iterator to read the stream records

        GetRecordsResult getRecordsResult = streamsClient.getRecords(new
GetRecordsRequest()
            .withShardIterator(currentShardIter));
        List<Record> records = getRecordsResult.getRecords();
        for (Record record : records) {
            System.out.println("      " + record.getDynamodb());
        }
        processedRecordCount += records.size();
        currentShardIter = getRecordsResult.getNextShardIterator();
    }
}

// If LastEvaluatedShardId is set, then there is
// at least one more page of shard IDs to retrieve
lastEvaluatedShardId =
describeStreamResult.getStreamDescription().getLastEvaluatedShardId();

} while (lastEvaluatedShardId != null);

// Delete the table
System.out.println("Deleting the table...");
dynamoDBClient.deleteTable(tableName);

System.out.println("Demo complete");
}
}

```

## DynamoDB Streams and AWS Lambda triggers

### Topics

- [Tutorial: Process new items with DynamoDB Streams and Lambda \(p. 622\)](#)
- [Best practices with Lambda \(p. 628\)](#)

Amazon DynamoDB is integrated with AWS Lambda so that you can create *triggers*—pieces of code that automatically respond to events in DynamoDB Streams. With triggers, you can build applications that react to data modifications in DynamoDB tables.

If you enable DynamoDB Streams on a table, you can associate the stream Amazon Resource Name (ARN) with an AWS Lambda function that you write. Immediately after an item in the table is modified, a new record appears in the table's stream. AWS Lambda polls the stream and invokes your Lambda function synchronously when it detects new stream records.

The Lambda function can perform any actions you specify, such as sending a notification or initiating a workflow. For example, you can write a Lambda function to simply copy each stream record to persistent storage, such as Amazon Simple Storage Service (Amazon S3), to create a permanent audit trail of write activity in your table. Or suppose that you have a mobile gaming app that writes to a GameScores table. Whenever the `TopScore` attribute of the GameScores table is updated, a corresponding stream record is written to the table's stream. This event could then trigger a Lambda function that posts a congratulatory message on a social media network. (The function would simply ignore any stream records that are not updates to GameScores or that do not modify the `TopScore` attribute.)

If your function returns an error, Lambda retries the batch until it processes successfully or the data expires. You can also configure Lambda to retry with a smaller batch, limit the number of retries, discard records once they become too old, and other options.

For more information about AWS Lambda, see the [AWS Lambda Developer Guide](#).


## Tutorial: Process new items with DynamoDB Streams and Lambda

### Topics

- [Step 1: Create a DynamoDB table with a stream enabled \(p. 623\)](#)
- [Step 2: Create a Lambda execution role \(p. 623\)](#)
- [Step 3: Create an Amazon SNS topic \(p. 624\)](#)
- [Step 4: Create and test a Lambda function \(p. 625\)](#)
- [Step 5: Create and test a trigger \(p. 627\)](#)

In this tutorial, you will create an AWS Lambda trigger to process a stream from a DynamoDB table.

The scenario for this tutorial is Woofer, a simple social network. Woofer users communicate using *barks* (short text messages) that are sent to other Woofer users. The following diagram shows the components and workflow for this application.



1. A user writes an item to a DynamoDB table (`BarkTable`). Each item in the table represents a bark.
2. A new stream record is written to reflect that a new item has been added to `BarkTable`.
3. The new stream record triggers an AWS Lambda function (`publishNewBark`).
4. If the stream record indicates that a new item was added to `BarkTable`, the Lambda function reads the data from the stream record and publishes a message to a topic in Amazon Simple Notification Service (Amazon SNS).
5. The message is received by subscribers to the Amazon SNS topic. (In this tutorial, the only subscriber is an email address.)

### Before You Begin

This tutorial uses the AWS Command Line Interface AWS CLI. If you have not done so already, follow the instructions in the [AWS Command Line Interface User Guide](#) to install and configure the AWS CLI.

## Step 1: Create a DynamoDB table with a stream enabled

In this step, you create a DynamoDB table (`BarkTable`) to store all of the barks from Woofer users. The primary key is composed of `Username` (partition key) and `Timestamp` (sort key). Both of these attributes are of type string.

`BarkTable` has a stream enabled. Later in this tutorial, you create a trigger by associating an AWS Lambda function with the stream.

1. Enter the following command to create the table.

```
aws dynamodb create-table \
    --table-name BarkTable \
    --attribute-definitions AttributeName=Username,AttributeType=S
    AttributeName=Timestamp,AttributeType=S \
    --key-schema AttributeName=Username,KeyType=HASH
    AttributeName=Timestamp,KeyType=RANGE \
    --provisioned-throughput ReadCapacityUnits=5,WriteCapacityUnits=5 \
    --stream-specification StreamEnabled=true,StreamViewType=NEW_AND_OLD_IMAGES
```

2. In the output, look for the `LatestStreamArn`.

```
...
"LatestStreamArn": "arn:aws:dynamodb:region:accountID:table/BarkTable/stream/timestamp"
...
```

Make a note of the `region` and the `accountID`, because you need them for the other steps in this tutorial.

## Step 2: Create a Lambda execution role

In this step, you create an AWS Identity and Access Management (IAM) role (`WooferLambdaRole`) and assign permissions to it. This role is used by the Lambda function that you create in [Step 4: Create and test a Lambda function \(p. 625\)](#).

You also create a policy for the role. The policy contains all of the permissions that the Lambda function needs at runtime.

1. Create a file named `trust-relationship.json` with the following contents.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Principal": {
                "Service": "lambda.amazonaws.com"
            },
            "Action": "sts:AssumeRole"
        }
    ]
}
```

2. Enter the following command to create `WooferLambdaRole`.

```
aws iam create-role --role-name WooferLambdaRole \
    --path "/service-role/" \
    --assume-role-policy-document file://trust-relationship.json
```

3. Create a file named `role-policy.json` with the following contents. (Replace `region` and `accountID` with your AWS Region and account ID.)

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": "lambda:InvokeFunction",
            "Resource": "arn:aws:lambda:region:accountID:function:publishNewBark*"
        },
        {
            "Effect": "Allow",
            "Action": [
                "logs:CreateLogGroup",
                "logs:CreateLogStream",
                "logs:PutLogEvents"
            ],
            "Resource": "arn:aws:logs:region:accountID:*"
        },
        {
            "Effect": "Allow",
            "Action": [
                "dynamodb:DescribeStream",
                "dynamodb:GetRecords",
                "dynamodb:GetShardIterator",
                "dynamodb>ListStreams"
            ],
            "Resource": "arn:aws:dynamodb:region:accountID:table/BarkTable/stream/*"
        },
        {
            "Effect": "Allow",
            "Action": [
                "sns:Publish"
            ],
            "Resource": [
                "*"
            ]
        }
    ]
}
```

The policy has four statements that allow `WooferLambdaRole` to do the following:

- Run a Lambda function (`publishNewBark`). You create the function later in this tutorial.
  - Access Amazon CloudWatch Logs. The Lambda function writes diagnostics to CloudWatch Logs at runtime.
  - Read data from the DynamoDB stream for `BarkTable`.
  - Publish messages to Amazon SNS.
4. Enter the following command to attach the policy to `WooferLambdaRole`.

```
aws iam put-role-policy --role-name WooferLambdaRole \
--policy-name WooferLambdaRolePolicy \
--policy-document file://role-policy.json
```

### Step 3: Create an Amazon SNS topic

In this step, you create an Amazon SNS topic (`wooferTopic`) and subscribe an email address to it. Your Lambda function uses this topic to publish new barks from Woofer users.

1. Enter the following command to create a new Amazon SNS topic.

```
aws sns create-topic --name wooferTopic
```

2. Enter the following command to subscribe an email address to `wooferTopic`. (Replace `region` and `accountID` with your AWS Region and account ID, and replace `example@example.com` with a valid email address.)

```
aws sns subscribe \
    --topic-arn arn:aws:sns:region:accountID:wooferTopic \
    --protocol email \
    --notification-endpoint example@example.com
```

3. Amazon SNS sends a confirmation message to your email address. Choose the **Confirm subscription** link in that message to complete the subscription process.

#### Step 4: Create and test a Lambda function

In this step, you create an AWS Lambda function (`publishNewBark`) to process stream records from `BarkTable`.

The `publishNewBark` function processes only the stream events that correspond to new items in `BarkTable`. The function reads data from such an event, and then invokes Amazon SNS to publish it.

1. Create a file named `publishNewBark.js` with the following contents. Replace `region` and `accountID` with your AWS Region and account ID.

```
'use strict';
var AWS = require("aws-sdk");
var sns = new AWS.SNS();

exports.handler = (event, context, callback) => {

    event.Records.forEach((record) => {
        console.log('Stream record: ', JSON.stringify(record, null, 2));

        if (record.eventName == 'INSERT') {
            var who = JSON.stringify(record.dynamodb.NewImage.Username.S);
            var when = JSON.stringify(record.dynamodb.NewImage.Timestamp.S);
            var what = JSON.stringify(record.dynamodb.NewImage.Message.S);
            var params = {
                Subject: 'A new bark from ' + who,
                Message: 'Woofer user ' + who + ' barked the following at ' + when + ':'
                '\n\n' + what,
                TopicArn: 'arn:aws:sns:region:accountID:wooferTopic'
            };
            sns.publish(params, function(err, data) {
                if (err) {
                    console.error("Unable to send message. Error JSON:", JSON.stringify(err, null, 2));
                } else {
                    console.log("Results from sending message: ", JSON.stringify(data, null, 2));
                }
            });
        }
    });
    callback(null, `Successfully processed ${event.Records.length} records.`);
};
```

2. Create a zip file to contain `publishNewBark.js`. If you have the `zip` command-line utility, you can enter the following command to do this.

```
zip publishNewBark.zip publishNewBark.js
```

3. When you create the Lambda function, you specify the Amazon Resource Name (ARN) for `WooferLambdaRole`, which you created in [Step 2: Create a Lambda execution role \(p. 623\)](#). Enter the following command to retrieve this ARN.

```
aws iam get-role --role-name WooferLambdaRole
```

In the output, look for the ARN for `WooferLambdaRole`.

```
...
"Arn": "arn:aws:iam::region:role/service-role/WooferLambdaRole"
...
```

Enter the following command to create the Lambda function. Replace `roleARN` with the ARN for `WooferLambdaRole`.

```
aws lambda create-function \
--region region \
--function-name publishNewBark \
--zip-file file:///publishNewBark.zip \
--role roleARN \
--handler publishNewBark.handler \
--timeout 5 \
--runtime nodejs10.x
```

4. Now test `publishNewBark` to verify that it works. To do this, you provide input that resembles a real record from DynamoDB Streams.

Create a file named `payload.json` with the following contents.

```
{
    "Records": [
        {
            "eventID": "7de3041dd709b024af6f29e4fa13d34c",
            "eventName": "INSERT",
            "eventVersion": "1.1",
            "eventSource": "aws:dynamodb",
            "awsRegion": "region",
            "dynamodb": {
                "ApproximateCreationDateTime": 1479499740,
                "Keys": {
                    "Timestamp": {
                        "S": "2016-11-18:12:09:36"
                    },
                    "Username": {
                        "S": "John Doe"
                    }
                },
                "NewImage": {
                    "Timestamp": {
                        "S": "2016-11-18:12:09:36"
                    },
                    "Message": {
                        "S": "This is a bark from the Woofer social network"
                    },
...
```

```
        "Username": {
            "S": "John Doe"
        }
    },
    "SequenceNumber": "1302160000000001596893679",
    "SizeBytes": 112,
    "StreamViewType": "NEW_IMAGE"
},
"eventSourceARN": "arn:aws:dynamodb:region:123456789012:table/BarkTable/
stream/2016-11-16T20:42:48.104"
}
]
```

Enter the following command to test the publishNewBark function.

```
aws lambda invoke --function-name publishNewBark --payload file://payload.json --cli-
binary-format raw-in-base64-out output.txt
```

If the test was successful, you will see the following output.

```
{
    "StatusCode": 200
}
```

In addition, the `output.txt` file will contain the following text.

```
"Successfully processed 1 records."
```

You will also receive a new email message within a few minutes.

**Note**

AWS Lambda writes diagnostic information to Amazon CloudWatch Logs. If you encounter errors with your Lambda function, you can use these diagnostics for troubleshooting purposes:

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, choose **Logs**.
3. Choose the following log group: `/aws/lambda/publishNewBark`
4. Choose the latest log stream to view the output (and errors) from the function.

## Step 5: Create and test a trigger

In [Step 4: Create and test a Lambda function \(p. 625\)](#), you tested the Lambda function to ensure that it ran correctly. In this step, you create a *trigger* by associating the Lambda function (`publishNewBark`) with an event source (the `BarkTable` stream).

1. When you create the trigger, you need to specify the ARN for the `BarkTable` stream. Enter the following command to retrieve this ARN.

```
aws dynamodb describe-table --table-name BarkTable
```

In the output, look for the `LatestStreamArn`.

```
...
"LatestStreamArn": "arn:aws:dynamodb:region:accountID:table/BarkTable/stream/timestamp
```

...

2. Enter the following command to create the trigger. Replace `streamARN` with the actual stream ARN.

```
aws lambda create-event-source-mapping \
--region region \
--function-name publishNewBark \
--event-source streamARN \
--batch-size 1 \
--starting-position TRIM_HORIZON
```

3. Test the trigger. Enter the following command to add an item to BarkTable.

```
aws dynamodb put-item \
--table-name BarkTable \
--item Username={S="Jane
Doe"},Timestamp={S="2016-11-18:14:32:17"},Message={S="Testing...1...2...3"}
```

You should receive a new email message within a few minutes.

4. Open the DynamoDB console and add a few more items to BarkTable. You must specify values for the `Username` and `Timestamp` attributes. (You should also specify a value for `Message`, even though it is not required.) You should receive a new email message for each item you add to BarkTable.

The Lambda function processes only new items that you add to BarkTable. If you update or delete an item in the table, the function does nothing.

#### Note

AWS Lambda writes diagnostic information to Amazon CloudWatch Logs. If you encounter errors with your Lambda function, you can use these diagnostics for troubleshooting purposes.

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, choose **Logs**.
3. Choose the following log group: /aws/lambda/publishNewBark
4. Choose the latest log stream to view the output (and errors) from the function.

## Best practices with Lambda

An AWS Lambda function runs within a *container*—an execution environment that is isolated from other functions. When you run a function for the first time, AWS Lambda creates a new container and begins executing the function's code.

A Lambda function has a *handler* that is run once per invocation. The handler contains the main business logic for the function. For example, the Lambda function shown in [Step 4: Create and test a Lambda function \(p. 625\)](#) has a handler that can process records in a DynamoDB stream.

You can also provide initialization code that runs one time only—after the container is created, but before AWS Lambda runs the handler for the first time. The Lambda function shown in [Step 4: Create and test a Lambda function \(p. 625\)](#) has initialization code that imports the SDK for JavaScript in Node.js, and creates a client for Amazon SNS. These objects should only be defined once, outside of the handler.

After the function runs, AWS Lambda might opt to reuse the container for subsequent invocations of the function. In this case, your function handler might be able to reuse the resources that you defined in your initialization code. (You cannot control how long AWS Lambda will retain the container, or whether the container will be reused at all.)

For DynamoDB triggers using AWS Lambda, we recommend the following:

- AWS service clients should be instantiated in the initialization code, not in the handler. This allows AWS Lambda to reuse existing connections, for the duration of the container's lifetime.
- In general, you do not need to explicitly manage connections or implement connection pooling because AWS Lambda manages this for you.

For more information, see [Best practices for working with AWS Lambda functions](#) in the *AWS Lambda Developer Guide*.

## Using On-Demand backup and restore for DynamoDB

You can use the DynamoDB on-demand backup capability to create full backups of your tables for long-term retention, and archiving for regulatory compliance needs. You can back up and restore your table data anytime with a single click on the AWS Management Console or with a single API call. Backup and restore actions run with no impact on table performance or availability.

The following video will give you an introductory look at the backup and restore concept.

### [Backup and restore](#)

There are two options available for creating and managing DynamoDB on-demand backups:

- AWS Backup service
- DynamoDB

With AWS Backup, you can configure backup policies and monitor activity for your AWS resources and on-premises workloads in one place. Using DynamoDB with AWS Backup, you can copy your on-demand backups across AWS accounts and Regions, add cost allocation tags to on-demand backups, and transition on-demand backups to cold storage for lower costs. To use these advanced features, you must [opt in](#) to AWS Backup. Opt-in choices apply to the specific account and AWS Region, so you might have to opt in to multiple Regions using the same account. For more information, see the [AWS Backup Developer Guide](#).

The on-demand backup and restore process scales without degrading the performance or availability of your applications. It uses a new and unique distributed technology that lets you complete backups in seconds regardless of table size. You can create backups that are consistent within seconds across thousands of partitions without worrying about schedules or long-running backup processes. All on-demand backups are cataloged, discoverable, and retained until they are explicitly deleted.

In addition, on-demand backup and restore operations don't affect performance or API latencies. Backups are preserved regardless of table deletion. For more information, see [Using DynamoDB backup and restore \(p. 636\)](#).

DynamoDB on-demand backups are available at no additional cost beyond the normal pricing that's associated with backup storage size. DynamoDB on-demand backups cannot be copied to a different account or Region. To create backup copies across AWS accounts and Regions and for other advanced features, you should use AWS Backup. If you use AWS Backup features you will be billed for them by AWS Backup. For more information about AWS Region availability and pricing, see [Amazon DynamoDB pricing](#).

### Topics

- [Using AWS Backup with DynamoDB \(p. 630\)](#)

- [Using DynamoDB backup and restore \(p. 636\)](#)

## Using AWS Backup with DynamoDB

Amazon DynamoDB can help you meet regulatory compliance and business continuity requirements through enhanced backup features in AWS Backup. AWS Backup is a fully managed data protection service that makes it easy to centralize and automate backups across AWS services, in the cloud, and on premises. Using this service, you can configure backup policies and monitor activity for your AWS resources in one place. To use AWS Backup, you must affirmatively [opt-in](#). Opt-in choices apply to the specific account and AWS Region, so you might have to opt in to multiple Regions using the same account. For more information, see the [AWS Backup Developer Guide](#).

Amazon DynamoDB is natively integrated with AWS Backup. You can use AWS Backup to schedule, copy, tag and life cycle your DynamoDB on-demand backups automatically. You can continue to view and restore these backups from the DynamoDB console. You can use the DynamoDB console, API, and AWS Command Line Interface (AWS CLI) to enable automatic backups for your DynamoDB tables.

### Note

Any backups made through DynamoDB will remain unchanged. You will still be able to create backups through the current DynamoDB workflow.

Enhanced backup features available through AWS Backup include:

**Scheduled backups** - You can set up regularly scheduled backups of your DynamoDB tables using backup plans.

**Cross-account and cross-Region copying** - You can automatically copy your backups to another backup vault in a different AWS Region or account, which allows you to support your data protection requirements.

**Cold storage tiering** - You can configure your backups to implement life cycle rules to delete or transition backups to colder storage. This can help you optimize your backup costs.

**Tags** - You can automatically tag your backups for billing and cost allocation purposes.

**Encryption** – DynamoDB on-demand backups managed through AWS Backup are now stored in the AWS Backup vault. This allows you to encrypt and secure your backups by using an AWS KMS key that is independent from your DynamoDB table encryption key.

**Audit backups** – You can use AWS Backup Audit Manager to audit the compliance of your AWS Backup policies and to find backup activity and resources that are not yet compliant with the controls that you defined. You can also use it to automatically generate an audit trail of daily and on-demand reports for your backup governance purposes.

**Secure backups using the WORM model** – You can use AWS Backup Vault Lock to enable a write-once-read-many (WORM) setting for your backups. With AWS Backup Vault Lock, you can add an additional layer of defense that protects backups from inadvertent or malicious delete operations, changes to backup retention periods, and updates to lifecycle settings. To learn more, see [AWS Backup Vault Lock](#).

These enhanced backup features are available in all AWS Regions. To learn more about these features, see the [AWS Backup Developer Guide](#).

### Topics

- [Backing up and restoring DynamoDB tables with AWS Backup: How it works \(p. 631\)](#)
- [Creating backups of DynamoDB tables with AWS Backup \(p. 632\)](#)
- [Copying a backup of a DynamoDB table with AWS Backup \(p. 633\)](#)
- [Restoring a backup of a DynamoDB table from AWS Backup \(p. 634\)](#)
- [Deleting a backup of a DynamoDB table with AWS Backup \(p. 635\)](#)

- [Usage notes \(p. 635\)](#)

## Backing up and restoring DynamoDB tables with AWS Backup: How it works

You can use the on-demand backup feature to create full backups of your Amazon DynamoDB tables. This section provides an overview of what happens during the backup and restore process.

### Backups

When you create an on-demand backup with AWS Backup, a time marker of the request is cataloged. The backup is created asynchronously by applying all changes until the time of the request to the last full table snapshot.

Each time you create an on-demand backup, the entire table data is backed up. There is no limit to the number of on-demand backups that can be taken.

**Note**

Unlike DynamoDB Backups, backups made with AWS Backup are not instantaneous.

While a backup is in progress, you can't do the following:

- Pause or cancel the backup operation.
- Delete the source table of the backup.
- Disable backups on a table if a backup for that table is in progress.

AWS Backup provides automated backup schedules, retention management, and lifecycle management. This removes the need for custom scripts and manual processes. AWS Backup runs the backups and deletes them when they expire. For more information, see the [AWS Backup Developer Guide](#).

If you're using the console, any backups created using AWS Backup are listed on the **Backups** tab with the **Backup type** set to `AWS_BACKUP`.

**Note**

You can't delete backups marked with a **Backup type** of `AWS_BACKUP` using the DynamoDB console. To manage these backups, use the AWS Backup console.

To learn how to perform a backup, see [Backing up a DynamoDB table \(p. 638\)](#).

### Restores

You restore a table without consuming any provisioned throughput on the table. You can do a full table restore from your DynamoDB backup, or you can configure the destination table settings. When you do a restore, you can change the following table settings:

- Global secondary indexes (GSIs)
- Local secondary indexes (LSIs)
- Billing mode
- Provisioned read and write capacity
- Encryption settings

**Important**

When you do a full table restore, the destination table is set with the same provisioned read capacity units and write capacity units that the source table had when the backup was requested. The restore process also restores the local secondary indexes and the global secondary indexes.

You can copy a backup of your DynamoDB table data to a different AWS Region and then restore it in that new Region. You can copy and then restore backups between AWS commercial Regions, AWS China Regions, and AWS GovCloud (US) Regions. You pay only for the data you copy from the source Region and the data you restore to a new table in the destination Region.

AWS Backup will restore the tables with all the original indexes.

You must manually set up the following on the restored table:

- Auto scaling policies
- AWS Identity and Access Management (IAM) policies
- Amazon CloudWatch metrics and alarms
- Tags
- Stream settings
- Time to Live (TTL) settings

You can only restore the entire table data to a new table from a backup. You can write to the restored table only after it becomes active.

**Note**

AWS Backup restores are nondestructive. You can't overwrite an existing table during a restore operation.

Service metrics show that 95 percent of customers' table restores complete in less than one hour. However, restore times are directly related to the configuration of your tables (such as the size of your tables and the number of underlying partitions) and other related variables. A best practice when planning for disaster recovery is to regularly document average restore completion times and establish how these times affect your overall Recovery Time Objective.

To learn how to perform a restore, see [Restoring a DynamoDB table from a backup \(p. 640\)](#).

You can use IAM policies for access control. For more information, see [Using IAM with DynamoDB backup and restore \(p. 644\)](#).

All backup and restore console and API actions are captured and recorded in AWS CloudTrail for logging, continuous monitoring, and auditing.

## Creating backups of DynamoDB tables with AWS Backup

This section describes how to enable AWS Backup to create on-demand and scheduled backups from your DynamoDB tables.

**Topics**

- [Enabling AWS Backup features \(p. 632\)](#)
- [On-demand backups \(p. 633\)](#)
- [Scheduled backups \(p. 633\)](#)

### Enabling AWS Backup features

You must enable AWS Backup to use it with DynamoDB.

To enable AWS Backup, go through the following steps:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.

2. In the navigation pane on the left side of the console, choose **Backups**.
3. In the Backup Settings window, choose **Enable**.
4. A confirmation screen will appear. Choose **Enable features**.

AWS Backup features are now available for your DynamoDB tables.

If you choose to disable AWS Backup features after they've been enabled, follow these steps:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Backups**.
3. In the Backup Settings window, choose **Disable**.
4. A confirmation screen will appear. Choose **Disable features**.

If you can't enable or disable the AWS Backup features, your AWS admin may need to perform those actions.

## On-demand backups

To create an on-demand backup of a DynamoDB table, follow these steps:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Backups**.
3. Choose **Create backup**.
4. From the dropdown menu that appears, choose **Create an on-demand backup**.
5. To create a backup managed by AWS Backup with warm storage and other basic features, choose **Default Settings**. To create a backup that can be transitioned to cold storage, or to create a backup with DynamoDB features instead of AWS Backup, choose **Customize settings**.

If you want to create this backup with previous DynamoDB features instead, choose **Customize settings** and then choose **Backup with DynamoDB**.

6. When you have completed the settings, choose **Create backup**.

## Scheduled backups

To schedule a backup, follow these steps.

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Backups**.
3. From the dropdown menu that appears, choose **Schedule backups with AWS Backup**.
4. You will be taken to AWS Backup to create a backup plan.

## Copying a backup of a DynamoDB table with AWS Backup

You can make a copy of a current backup. You can copy backups to multiple AWS accounts or AWS Regions on demand or automatically as part of a scheduled backup plan. You can also automate a sequence of cross-account and cross-Region copies for Amazon DynamoDB Encryption Client.

Cross-Region replication is especially valuable if you have business continuity or compliance requirements to store backups a minimum distance away from your production data.

Cross-account backups are useful for securely copying your backups to one or more AWS accounts in your organization for operational or security reasons. If your original backup is inadvertently deleted, you can copy the backup from its destination account to its source account, and then start the restore. Before you can do this, you must have two accounts that belong to the same organization in the Organizations service.

Copies inherit the source backup's configuration unless you specify otherwise, with one exception: if you specify that your new copy "Never" expire. With this setting, the new copy still inherits its source expiration date. If you want your new backup copy to be permanent, either set your source backups to never expire, or specify your new copy to expire 100 years after its creation.

**Note**

If you're copying to another account, you must first have permission from that account.

To copy a backup, do the following:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Backups**.
3. Select the check box next to the backup you want to copy.
  - If the backup you want to copy is grayed out, you must enable [advanced features with AWS Backup](#). Then create a new backup. You can now copy this new backup to other Regions and accounts, and copy any other new backups going forward.
4. Choose **Copy**.
5. If you want to copy the backup to another account or Region, select the check box next to **Copy the recovery point to another destination**. Then select whether you will to copy to another Region in your account, or to a different account in a different Region.

**Note**

To restore a backup to another Region or account, you must first copy the backup to that Region or account.

6. Select the desired vault the file will be copied into. You can also create a new backup vault if desired.
7. Choose **Copy backup**.

## Restoring a backup of a DynamoDB table from AWS Backup

This section describes how to restore a backup of a DynamoDB table from AWS Backup.

**Topics**

- [Restoring a DynamoDB table from AWS Backup \(p. 634\)](#)
- [Restoring a DynamoDB table to another Region or account \(p. 635\)](#)

### Restoring a DynamoDB table from AWS Backup

To restore your DynamoDB tables from AWS Backup, follow these steps:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Backups** tab.
4. Select the check box next to the previous backup that you want to restore from.
5. Choose **Restore**. You will be taken to the **Restore table from backup** screen.
6. Enter the name for the newly restored table, the encryption that this new table will have, the key you want the restore to be encrypted with, and other options.

7. When you're finished, choose **Restore**.
8. You will see a notification that the request to restore was submitted successfully. To view the progress of restoring the table, choose **View details**.

This will take you to the AWS Backup console for further information on the progress of the task.

## Restoring a DynamoDB table to another Region or account

To restore a DynamoDB table to another Region or account, you will first need to copy the backup to that new Region or account. In order to copy to another account, that account must first grant you permission. After you have copied your DynamoDB backup to the new Region or account, it can be restored with the process in the previous section.

## Deleting a backup of a DynamoDB table with AWS Backup

This section describes how to delete a backup of a DynamoDB table with AWS Backup.

A DynamoDB backup created through AWS Backup features is stored in an AWS Backup vault.

In order to delete this kind of backup, do the following:

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Backups**.
3. On the screen that follows, choose **Continue to AWS Backup**.

You will be taken to the AWS Backup console.

## Usage notes

This section describes the technical differences between on-demand backups managed by AWS Backup and DynamoDB.

AWS Backup has some different workflows and behaviors than DynamoDB. These include:

**Encryption** - Backups created with the AWS Backup plan are stored in an encrypted vault with a key that is managed by the AWS Backup service. The vault has access control policies for additional security.

**Backup ARN** - The backup files created by AWS Backup will now have an AWS Backup ARN, which could impact the user permission model. Backup resource names (ARNs) will change from `arn:aws:dynamodb` to `arn:aws:backup`.

**Deleting backups** - Backups that are created with AWS Backup can only be deleted from the AWS Backup vault. You will not be able to delete AWS Backup files from the DynamoDB console.

**Backup process** - Unlike DynamoDB backups, backups made with AWS Backup are not instantaneous.

**Billing** - Backups of DynamoDB tables with AWS Backup features are billed from AWS Backup.

**IAM roles** - If you're managing access through IAM roles, you will also need to configure a new IAM role with these new permissions:

```
"dynamodb:StartAwsBackupJob",
"dynamodb:RestoreTableFromAwsBackup"
```

`dynamodb:StartAwsBackupJob` is needed for a successful backup with AWS Backup features, and `dynamodb:RestoreTableFromAwsBackup` is needed to restore from a backup made with AWS Backup features.

To see these permissions in a complete IAM policy, see Example 8 in [Using IAM](#).

## Using DynamoDB backup and restore

Amazon DynamoDB supports stand-alone on-demand backup and restores features. Those features are available to you independent of whether you use AWS Backup.

You can use the DynamoDB on-demand backup capability to create full backups of your tables for long-term retention and archival for regulatory compliance needs. You can back up and restore your table data anytime with a single click on the AWS Management Console or with a single API call. Backup and restore actions run with zero impact on table performance or availability.

You can create table backups using the console, the AWS Command Line Interface (AWS CLI), or the DynamoDB API. For more information, see [Backing up a DynamoDB table \(p. 638\)](#).

For information about restoring a table from a backup, see [Restoring a DynamoDB table from a backup \(p. 640\)](#).

## Backing up and restoring DynamoDB tables with DynamoDB: How it works

You can use the DynamoDB on-demand backup feature to create full backups of your Amazon DynamoDB tables. This feature is available independently from AWS backup. This section provides an overview of what happens during the DynamoDB backup and restore process.

### Backups

When you create an on-demand backup with DynamoDB, a time marker of the request is cataloged. The backup is created asynchronously by applying all changes until the time of the request to the last full table snapshot. DynamoDB backup requests are processed instantaneously and become available for restore within minutes.

#### Note

Each time you create an on-demand backup, the entire table data is backed up. There is no limit to the number of on-demand backups that can be taken.

All backups in DynamoDB work without consuming any provisioned throughput on the table.

DynamoDB backups do not guarantee causal consistency across items; however, the skew between updates in a backup is usually much less than a second.

While a backup is in progress, you can't do the following:

- Pause or cancel the backup operation.
- Delete the source table of the backup.
- Disable backups on a table if a backup for that table is in progress.

If you don't want to create scheduling scripts and cleanup jobs, you can use AWS Backup to create backup plans with schedules and retention policies for your DynamoDB tables. AWS Backup runs the backups and deletes them when they expire. For more information, see the [AWS Backup Developer Guide](#).

In addition to AWS Backup, you can schedule periodic or future backups by using AWS Lambda functions. For more information, see the blog post [A serverless solution to schedule your Amazon DynamoDB On-Demand backup](#).

If you're using the console, any backups created using AWS Backup are listed on the **Backups** tab with the **Backup type** set to **AWS**.

**Note**

You can't delete backups marked with a **Backup type** of AWS using the DynamoDB console. To manage these backups, use the AWS Backup console.

To learn how to perform a backup, see [Backing up a DynamoDB table \(p. 638\)](#).

## Restores

You restore a table without consuming any provisioned throughput on the table. You can do a full table restore from your DynamoDB backup, or you can configure the destination table settings. When you do a restore, you can change the following table settings:

- Global secondary indexes (GSIs)
- Local secondary indexes (LSIs)
- Billing mode
- Provisioned read and write capacity
- Encryption settings

**Important**

When you do a full table restore, the destination table is set with the same provisioned read capacity units and write capacity units as the source table, as recorded at the time the backup was requested. The restore process also restores the local secondary indexes and the global secondary indexes.

You can also restore your DynamoDB table data across AWS Regions such that the restored table is created in a different Region from where the backup resides. You can do cross-Region restores between AWS commercial Regions, AWS China Regions, and AWS GovCloud (US) Regions. You pay only for the data that you transfer out of the source Region and for restoring to a new table in the destination Region.

Restores can be faster and more cost-efficient if you choose to exclude some or all secondary indexes from being created on the new restored table.

You must manually set up the following on the restored table:

- Auto scaling policies
- AWS Identity and Access Management (IAM) policies
- Amazon CloudWatch metrics and alarms
- Tags
- Stream settings
- Time to Live (TTL) settings

You can only restore the entire table data to a new table from a backup. You can write to the restored table only after it becomes active.

**Note**

You can't overwrite an existing table during a restore operation.

Service metrics show that 95 percent of customers' table restores complete in less than one hour. However, restore times are directly related to the configuration of your tables (such as the size of your tables and the number of underlying partitions) and other related variables. A best practice when planning for disaster recovery is to regularly document average restore completion times and establish how these times affect your overall Recovery Time Objective.

To learn how to perform a restore, see [Restoring a DynamoDB table from a backup \(p. 640\)](#).

You can use IAM policies for access control. For more information, see [Using IAM with DynamoDB backup and restore \(p. 644\)](#).

All backup and restore console and API actions are captured and recorded in AWS CloudTrail for logging, continuous monitoring, and auditing.

## Backing up a DynamoDB table

This section describes how to use the Amazon DynamoDB console or the AWS Command Line Interface to back up a table.

### Topics

- [Creating a table backup \(console\) \(p. 638\)](#)
- [Creating a table backup \(AWS CLI\) \(p. 639\)](#)

### Creating a table backup (console)

Follow these steps to create a backup named `MusicBackup` for an existing `Music` table using the AWS Management Console.

#### To create a table backup

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. You can create a backup by doing one of the following:
  - On the **Backups** tab of the `Music` table, choose **Create backup**.
  - In the navigation pane on the left side of the console, choose **Backups**. Then choose **Create backup**.
3. Make sure that `Music` is the table name, and enter `MusicBackup` for the backup name. Then, choose **Create** to create the backup.

### Create backup

**Backup settings** [Info](#)

Source table	Music
Backup name	MusicBackup
Between 3 and 255 characters in length. Only A-Z, a-z, 0-9, underscore characters, hyphens, and periods are allowed.	
<a href="#">Cancel</a> <a href="#">Create backup</a>	

#### Note

If you create backups using the **Backups** section in the navigation pane, the table isn't preselected for you. You have to manually choose the source table name for the backup.

While the backup is being created, the backup status is set to **Creating**. After the backup is complete, the backup status changes to **Available**.

On-demand backups (1)					Info		Restore	Delete	Create backup
<input type="text"/> Find backups by ARN or name									
1									
	Name	Status	Creatio...	ARN					
<input type="checkbox"/>	MusicBackup	Available	August 23...	arn:aws:dynamodb:us-w...					

## Creating a table backup (AWS CLI)

Follow these steps to create a backup for an existing table `Music` using the AWS CLI.

### To create a table backup

- Create a backup with the name `MusicBackup` for the `Music` table.

```
aws dynamodb create-backup --table-name Music \
    --backup-name MusicBackup
```

While the backup is being created, the backup status is set to `CREATING`.

```
{
    "BackupDetails": {
        "BackupName": "MusicBackup",
        "BackupArn": "arn:aws:dynamodb:us-east-1:123456789012:table/Music/
    backup/01489602797149-73d8d5bc",
        "BackupStatus": "CREATING",
        "BackupCreationDateTime": 1489602797.149
    }
}
```

After the backup is complete, its `BackupStatus` should change to `AVAILABLE`. To confirm this, use the `describe-backup` command. You can get the input value of `backup-arn` from the output of the previous step or by using the `list-backups` command.

```
aws dynamodb describe-backup \
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/01489173575360-
b308cd7d
```

To keep track of your backups, you can use the `list-backups` command. It lists all your backups that are in `CREATING` or `AVAILABLE` status.

```
aws dynamodb list-backups
```

The `list-backups` command and the `describe-backup` command are useful to check information about the source table of the backup.

## Restoring a DynamoDB table from a backup

This section describes how to restore a table from a backup using the Amazon DynamoDB console or the AWS Command Line Interface (AWS CLI).

### Note

If you want to use the AWS CLI, you must configure it first. For more information, see [Accessing DynamoDB \(p. 60\)](#).

### Topics

- [Restoring a table from a backup \(console\) \(p. 640\)](#)
- [Restoring a table from a backup \(AWS CLI\) \(p. 642\)](#)


## Restoring a table from a backup (console)

The following procedure shows how to restore the `Music` table by using the `MusicBackup` file that is created in the [Backing up a DynamoDB table \(p. 638\)](#) tutorial.

### Note

This procedure assumes that the `Music` table no longer exists before restoring it using the `MusicBackup` file.

### To restore a table from a backup

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Backups**.
3. In the list of backups, choose `MusicBackup`.  

4. Choose **Restore**.
5. Enter `Music` as the new table name. Confirm the backup name and other backup details. Then choose **Restore table** to start the restore process.

### Note

You can restore the table to the same AWS Region or to a different Region from where the backup resides. You can also exclude secondary indexes from being created on the new restored table. In addition, you can specify a different encryption mode.

Tables restored from backups are always created using the DynamoDB Standard table class.

## Restore table from backup Info

Restoring a table from a backup will restore it as a new table.

### Restore settings

#### Name of restored table

This name will identify your restored table.

Music

Between 3 and 255 characters in length. Only A–Z, a–z, 0–9, underscore characters, hyphens, and periods allowed.

#### Secondary indexes

Restore the entire table

Your restored table will include all local and global secondary indexes.

Restore the table without secondary indexes

Your restored table will exclude all local and global secondary indexes. Restoring this way can be faster and more cost efficient.

### Destination AWS Region

Same Region (Oregon)

Restore the table to the same Region as the original table.

Cross-Region

Restore the table to a different Region for greater redundancy but with higher data transfer costs.

### ▼ Encryption at rest - optional

All user data stored in Amazon DynamoDB is fully encrypted at rest. By default, Amazon DynamoDB manages the encryption key, and you are not charged any fee for using it.

#### Encryption key management Info

Owned by Amazon DynamoDB

The key is owned and managed by DynamoDB. You are not charged an additional fee for using this customer master key (CMK).

AWS managed CMK

The key is stored in your account and is managed by AWS Key Management Service (AWS KMS). AWS KMS charges apply.

Stored in your account, and owned and managed by you

Choose a key that is owned and managed by you, and stored in AWS KMS.

ⓘ The time it takes to restore a table from a backup can vary and is based on multiple variables. After your table is restored from the backup, you might need to reapply configuration settings. [Learn more](#) ↗

Cancel

Restore

The table that is being restored is shown with the status **Creating**. After the restore process is finished, the status of the **Music** table changes to **Active**.

## Restoring a table from a backup (AWS CLI)

Follow these steps to use the AWS CLI to restore the `Music` table using the `MusicBackup` that is created in the [Backing up a DynamoDB table \(p. 638\)](#) tutorial.

### To restore a table from a backup

1. Confirm the backup that you want to restore by using the `list-backups` command. This example uses `MusicBackup`.

```
aws dynamodb list-backups
```

To get additional details for the backup, use the `describe-backup` command. You can get the input `backup-arn` from the previous step.

```
aws dynamodb describe-backup \  
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/01489173575360-  
b308cd7d
```

2. Restore the table from the backup. In this case, the `MusicBackup` restores the `Music` table to the same AWS Region.

```
aws dynamodb restore-table-from-backup \  
--target-table-name Music \  
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/01489173575360-  
b308cd7d
```

3. Restore the table from the backup with custom table settings. In this case, the `MusicBackup` restores the `Music` table and specifies an encryption mode for the restored table.

#### Note

The `sse-specification-override` parameter takes the same values as the `sse-specification-override` parameter used in the `CreateTable` command. To learn more, see [Managing encrypted tables in DynamoDB \(p. 1065\)](#).

```
aws dynamodb restore-table-from-backup \  
--target-table-name Music \  
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/01581080476474-  
e177ebe2 \  
--sse-specification-override Enabled=true,SSEType=KMS,KMSMasterKeyId=abcd1234-abcd-1234-  
a123-ab1234a1b234
```

You can restore the table to a different AWS Region from where the backup resides.

#### Note

- The `sse-specification-override` parameter is mandatory for cross-Region restores but optional for restores in the same Region as the source table.
- When performing a cross-Region restore from the command line, you must set the default AWS Region to the desired destination Region. To learn more, see [Command line options](#) in the [AWS Command Line Interface User Guide](#).

```
aws dynamodb restore-table-from-backup \  
--target-table-name Music \  
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/01581080476474-  
e177ebe2 \  
--sse-specification-override Enabled=true,SSEType=KMS
```

You can override the billing mode and the provisioned throughput for the restored table.

```
aws dynamodb restore-table-from-backup \
--target-table-name Music \
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/01489173575360-
b308cd7d \
--billing-mode-override PAY_PER_REQUEST
```

You can exclude some or all secondary indexes from being created on the restored table.

**Note**

Restores can be faster and more cost-efficient if you exclude some or all secondary indexes from being created on the restored table.

```
aws dynamodb restore-table-from-backup \
--target-table-name Music \
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/01581081403719-
db9c1f91 \
--global-secondary-index-override '[]' \
--sse-specification-override Enabled=true,SSEType=KMS
```

**Note**

The secondary indexes provided should match existing indexes. You cannot create new indexes at the time of restore.

You can use a combination of different overrides. For example, you can use a single global secondary index and change provisioned throughput at the same time, as follows.

```
aws dynamodb restore-table-from-backup \
--target-table-name Music \
--backup-arn arn:aws:dynamodb:eu-west-1:123456789012:table/Music/
backup/01581082594992-303b6239 \
--billing-mode-override PROVISIONED \
--provisioned-throughput ReadCapacityUnits=100,WriteCapacityUnits=100 \
--global-secondary-index-override IndexName=singers-
index,KeySchema=[{"AttributeName=SingerName,KeyType=HASH"}],Projection="{ProjectionType=KEYS_ONLY}",I
\
--sse-specification-override Enabled=true,SSEType=KMS
```

To verify the restore, use the `describe-table` command to describe the `Music` table.

```
aws dynamodb describe-table --table-name Music
```

The table that is being restored from the backup is shown with the status **Creating**. After the restore process is finished, the status of the `Music` table changes to **Active**.

**Important**

While a restore is in progress, don't modify or delete your IAM role policy; otherwise, unexpected behavior can result. For example, suppose that you removed write permissions for a table while that table is being restored. In this case, the underlying `RestoreTableFromBackup` operation would not be able to write any of the restored data to the table.

After the restore operation is complete, you can modify or delete your IAM role policy.

IAM policies involving [source IP restrictions](#) for accessing the target restore table should have the `aws:ViaAWSService` key set to `false` to ensure that the restrictions apply only to requests made directly by a principal. Otherwise, the restore will be canceled.

If your backup is encrypted with an AWS managed key or a customer managed key, don't disable or delete the key while a restore is in progress, or the restore will fail.

After the restore operation is complete, you can change the encryption key for the restored table and disable or delete the old key.

## Deleting a DynamoDB table backup

This section describes how to use the AWS Management Console or the AWS Command Line Interface (AWS CLI) to delete an Amazon DynamoDB table backup.

### Note

If you want to use the AWS CLI, you have to configure it first. For more information, see [Using the AWS CLI \(p. 61\)](#).

### Topics

- [Deleting a table backup \(console\) \(p. 644\)](#)
- [Deleting a table backup \(AWS CLI\) \(p. 644\)](#)

## Deleting a table backup (console)

The following procedure shows how to use the console to delete the `MusicBackup` that is created in the [Backing up a DynamoDB table \(p. 638\)](#) tutorial.

### To delete a backup

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Backups**.
3. In the list of backups, choose `MusicBackup`.

On-demand backups (1/1) <a href="#">Info</a>					<a href="#">C</a>	<a href="#">Restore</a>	<a href="#">Delete</a>	<a href="#">Create backup</a>
<input type="text"/> Find backups by ARN or name					<a href="#">C</a>	<a href="#">Restore</a>	<a href="#">Delete</a>	<a href="#">Create backup</a>
<input checked="" type="checkbox"/>	Name	Table	Status	Creation t...	<a href="#">ARN</a>			
<input checked="" type="checkbox"/>	MusicBackup	Music	<span>Available</span>	August 23, 2...	<a href="#">arn:aws:dynamodb:us-v...</a>			

4. Choose **Delete**. Confirm that you want to delete the backup by typing `delete` and clicking **Delete**.

## Deleting a table backup (AWS CLI)

The following example deletes a backup for an existing table `Music` table using the AWS CLI.

```
aws dynamodb delete-backup \
--backup-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music/
backup/01489602797149-73d8d5bc
```

## Using IAM with DynamoDB backup and restore

You can use AWS Identity and Access Management (IAM) to restrict Amazon DynamoDB backup and restore actions for some resources. The `CreateBackup` and `RestoreTableFromBackup` APIs operate on a per-table basis.

For more information about using IAM policies in DynamoDB, see [Using identity-based policies \(IAM policies\) with Amazon DynamoDB \(p. 1075\)](#).

The following are examples of IAM policies that you can use to configure specific backup and restore functionality in DynamoDB.

## Example 1: Allow the CreateBackup and RestoreTableFromBackup actions

The following IAM policy grants permissions to allow the `CreateBackup` and `RestoreTableFromBackup` DynamoDB actions on all tables:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:CreateBackup",  
                "dynamodb:RestoreTableFromBackup",  
                "dynamodb:PutItem",  
                "dynamodb:UpdateItem",  
                "dynamodb:DeleteItem",  
                "dynamodb:GetItem",  
                "dynamodb:Query",  
                "dynamodb:Scan",  
                "dynamodb:BatchWriteItem"  
            ],  
            "Resource": "*"  
        }  
    ]  
}
```

### Important

DynamoDB `RestoreTableFromBackup` permissions are necessary on the source backup, and DynamoDB read and write permissions on the target table are necessary for restore functionality.

DynamoDB `RestoreTableToPointInTime` permissions are necessary on the source table, and DynamoDB read and write permissions on the target table are necessary for restore functionality.

## Example 2: Allow CreateBackup and deny RestoreTableFromBackup

The following IAM policy grants permissions for the `CreateBackup` action and denies the `RestoreTableFromBackup` action:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": ["dynamodb:CreateBackup"],  
            "Resource": "*"  
        },  
        {  
            "Effect": "Deny",  
            "Action": ["dynamodb:RestoreTableFromBackup"],  
            "Resource": "*"  
        }  
    ]  
}
```

## Example 3: Allow ListBackups and deny CreateBackup and RestoreTableFromBackup

The following IAM policy grants permissions for the `ListBackups` action and denies the `CreateBackup` and `RestoreTableFromBackup` actions:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": ["dynamodb>ListBackups"],  
            "Resource": "*"  
        },  
        {  
            "Effect": "Deny",  
            "Action": [  
                "dynamodb>CreateBackup",  
                "dynamodb>RestoreTableFromBackup"  
            ],  
            "Resource": "*"  
        }  
    ]  
}
```

#### Example 4: Allow ListBackups and deny DeleteBackup

The following IAM policy grants permissions for the `ListBackups` action and denies the `DeleteBackup` action:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": ["dynamodb>ListBackups"],  
            "Resource": "*"  
        },  
        {  
            "Effect": "Deny",  
            "Action": ["dynamodb>DeleteBackup"],  
            "Resource": "*"  
        }  
    ]  
}
```

#### Example 5: Allow RestoreTableFromBackup and DescribeBackup for all resources and deny DeleteBackup for a specific backup

The following IAM policy grants permissions for the `RestoreTableFromBackup` and `DescribeBackup` actions and denies the `DeleteBackup` action for a specific backup resource:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb>DescribeBackup",  
                "dynamodb>RestoreTableFromBackup",  
            ],  
            "Resource": "arn:aws:dynamodb:us-east-1:123456789012:table/Music/  
backup/01489173575360-b308cd7d"  
        },  
        {  
            "Effect": "Deny",  
            "Action": ["dynamodb>DeleteBackup"],  
            "Resource": "arn:aws:dynamodb:us-east-1:123456789012:table/Music/  
backup/01489173575360-b308cd7d"  
        }  
    ]  
}
```

```
        "Effect": "Allow",
        "Action": [
            "dynamodb:PutItem",
            "dynamodb:UpdateItem",
            "dynamodb>DeleteItem",
            "dynamodb:GetItem",
            "dynamodb:Query",
            "dynamodb:Scan",
            "dynamodb:BatchWriteItem"
        ],
        "Resource": "*"
    },
{
    "Effect": "Deny",
    "Action": [
        "dynamodb>DeleteBackup"
    ],
    "Resource": "arn:aws:dynamodb:us-east-1:123456789012:table/Music/
backup/01489173575360-b308cd7d"
}
]
```

**Important**

DynamoDB RestoreTableFromBackup permissions are necessary on the source backup, and DynamoDB read and write permissions on the target table are necessary for restore functionality.

DynamoDB RestoreTableToPointInTime permissions are necessary on the source table, and DynamoDB read and write permissions on the target table are necessary for restore functionality.

## Example 6: Allow CreateBackup for a specific table

The following IAM policy grants permissions for the CreateBackup action on the Movies table only:

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": ["dynamodb>CreateBackup"],
            "Resource": [
                "arn:aws:dynamodb:us-east-1:123456789012:table/Movies"
            ]
        }
    ]
}
```

## Example 7: Allow ListBackups

The following IAM policy grants permissions for the ListBackups action:

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": ["dynamodb>ListBackups"],
            "Resource": "*"
        }
    ]
}
```

}

**Important**

You cannot grant permissions for the `ListBackups` action on a specific table.

### Example 8: Allow access to AWS Backup features

You will need API permissions for the `StartAwsBackupJob` action for a successful backup with advanced features, and the `dynamodb:RestoreTableFromAwsBackup` action to successfully restore that backup.

The following IAM policy grants AWS Backup the permissions to trigger backups with advanced features and restores. Also note that if the tables are encrypted the policy will need access to the AWS KMS key.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "DescribeQueryScanBooksTable",  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:StartAwsBackupJob",  
                "dynamodb:DescribeTable",  
                "dynamodb:Query",  
                "dynamodb:Scan"  
            ],  
            "Resource": "arn:aws:dynamodb:us-west-2:account-id:table/Books"  
        },  
        {  
            "Sid": "AllowRestoreFromAwsBackup",  
            "Effect": "Allow",  
            "Action": ["dynamodb:RestoreTableFromAwsBackup"],  
            "Resource": "*"  
        },  
    ]  
}
```

### Example 9: Deny `RestoreTableToPointInTime` for a Specific Source Table

The following IAM policy denies permissions for the `RestoreTableToPointInTime` action for a specific source table:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Deny",  
            "Action": [  
                "dynamodb:RestoreTableToPointInTime"  
            ],  
            "Resource": "arn:aws:dynamodb:us-east-1:123456789012:table/Music"  
        }  
    ]  
}
```

### Example 10: Deny `RestoreTableFromBackup` for all Backups for a Specific Source Table

The following IAM policy denies permissions for the `RestoreTableToPointInTime` action for all backups for a specific source table:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Deny",  
            "Action": [  
                "dynamodb:RestoreTableFromBackup"  
            ],  
            "Resource": "arn:aws:dynamodb:us-east-1:123456789012:table/Music/backup/*"  
        }  
    ]  
}
```

## Point-in-time recovery for DynamoDB

You can create on-demand backups of your Amazon DynamoDB tables, or you can enable continuous backups using point-in-time recovery. For more information about on-demand backups, see [Using On-Demand backup and restore for DynamoDB \(p. 629\)](#).

Point-in-time recovery helps protect your DynamoDB tables from accidental write or delete operations. With point-in-time recovery, you don't have to worry about creating, maintaining, or scheduling on-demand backups. For example, suppose that a test script writes accidentally to a production DynamoDB table. With point-in-time recovery, you can restore that table to any point in time during the last 35 days. DynamoDB maintains incremental backups of your table.

In addition, point-in-time operations don't affect performance or API latencies. For more information, see [Point-in-time recovery: How it works \(p. 649\)](#).

You can restore a DynamoDB table to a point in time using the AWS Management Console, the AWS Command Line Interface (AWS CLI), or the DynamoDB API. The point-in-time recovery process restores to a new table. For more information, see [Restoring a DynamoDB table to a point in time \(p. 651\)](#).

For more information about AWS Region availability and pricing, see [Amazon DynamoDB pricing](#).

### Topics

- [Point-in-time recovery: How it works \(p. 649\)](#)
- [Before you begin using point-in-time recovery \(p. 651\)](#)
- [Restoring a DynamoDB table to a point in time \(p. 651\)](#)

## Point-in-time recovery: How it works

Amazon DynamoDB point-in-time recovery (PITR) provides automatic backups of your DynamoDB table data. This section provides an overview of how the process works in DynamoDB.

### Enabling point-in-time recovery

You can enable point-in-time recovery using the AWS Management Console, AWS Command Line Interface (AWS CLI), or the DynamoDB API. When enabled, point-in-time recovery provides continuous backups until you explicitly turn it off. For more information, see [Restoring a DynamoDB table to a point in time \(p. 651\)](#).

After you enable point-in-time recovery, you can restore to any point in time within `EarliestRestorableDateTime` and `LatestRestorableDateTime`. `LatestRestorableDateTime` is typically 5 minutes before the current time.

**Note**

The point-in-time recovery process always restores to a new table.

## Restoring a table using point-in-time recovery

For `EarliestRestorableDateTime`, you can restore your table to any point in time during the last 35 days. The retention period is a fixed 35 days (5 calendar weeks) and can't be modified. Any number of users can run up to four concurrent restores (any type of restore) in a given account.

**Important**

If you disable point-in-time recovery and later re-enable it on a table, you reset the start time for which you can recover that table. As a result, you can only immediately restore that table using the `LatestRestorableDateTime`.

When you restore using point-in-time recovery, DynamoDB restores your table data to the state based on the selected date and time (day:hour:minute:second) to a new table.

You restore a table without consuming any provisioned throughput on the table. You can do a full table restore using point-in-time recovery, or you can configure the destination table settings. You can change the following table settings on the restored table:

- Global secondary indexes (GSIs)
- Local secondary indexes (LSIs)
- Billing mode
- Provisioned read and write capacity
- Encryption settings

**Important**

When you do a full table restore, all table settings for the restored table come from the current settings of the source table at the time of the restore. For example, suppose that a table's provisioned throughput was recently lowered to 50 read capacity units and 50 write capacity units. You then restore the table's state to three weeks ago, at which time its provisioned throughput was set to 100 read capacity units and 100 write capacity units. In this case, DynamoDB restores your table data to that point in time, but uses the current provisioned throughput (50 read capacity units and 50 write capacity units).

You can also restore your DynamoDB table data across AWS Regions such that the restored table is created in a different Region from where the source table resides. You can do cross-Region restores between AWS commercial Regions, AWS China Regions, and AWS GovCloud (US) Regions. You pay only for the data you transfer out of the source Region and for restoring to a new table in the destination Region.

**Note**

Cross-Region restore is not supported if the source or destination Region is Asia Pacific (Hong Kong) or Middle East (Bahrain).

Restores can be faster and more cost-efficient if you exclude some or all indexes from being created on the restored table.

You must manually set the following on the restored table:

- Auto scaling policies
- AWS Identity and Access Management (IAM) policies
- Amazon CloudWatch metrics and alarms
- Tags
- Stream settings
- Time to Live (TTL) settings

- Point-in-time recovery settings

The time it takes you to restore a table varies based on multiple factors. The point-in-time restore times are not always correlated directly to the size of the table. For more information, see [Restores \(p. 637\)](#).

## Deleting a table with point-in-time recovery enabled

When you delete a table that has point-in-time recovery enabled, DynamoDB automatically creates a backup—called a system backup—and retains it for 35 days (at no additional cost). You can use the system backup to restore the deleted table to the state it was in just before deletion. All system backups follow a standard naming convention of `table-name$DeletedTableBackup`.

**Note**

When you delete a table, you no longer have access to the table to perform a point-in-time recovery.

## Before you begin using point-in-time recovery

Before you enable point-in-time recovery (PITR) on an Amazon DynamoDB table, consider the following:

- If you disable point-in-time recovery and later re-enable it on a table, you reset the start time for which you can recover that table. As a result, you can only immediately restore that table using the [LatestRestorableDateTime](#).
- You can enable point-in-time recovery on each local replica of a global table. When you restore the table, the backup restores to an independent table that is not part of the global table. If you are using [Version 2019.11.21 \(Current\) \(p. 308\)](#) of global tables, you can create a new global table from the restored table. For more information, see [Global tables: How it works \(p. 308\)](#).
- You can also restore your DynamoDB table data across AWS Regions such that the restored table is created in a different Region from where the source table resides. You can do cross-Region restores between AWS commercial Regions, AWS China Regions, and AWS GovCloud (US) Regions. You pay only for the data you transfer out of the source Region and for restoring to a new table in the destination Region.
- AWS CloudTrail logs all console and API actions for point-in-time recovery to enable logging, continuous monitoring, and auditing. For more information, see [Logging DynamoDB operations by using AWS CloudTrail \(p. 1133\)](#).

## Restoring a DynamoDB table to a point in time

Amazon DynamoDB point-in-time recovery (PITR) provides continuous backups of your DynamoDB table data. You can restore a table to a point in time using the DynamoDB console or the AWS Command Line Interface (AWS CLI). The point-in-time recovery process restores to a new table.

If you want to use the AWS CLI, you must configure it first. For more information, see [Accessing DynamoDB \(p. 60\)](#).

**Topics**

- [Restoring a DynamoDB table to a point in time \(console\) \(p. 651\)](#)
- [Restoring a table to a point in time \(AWS CLI\) \(p. 652\)](#)

## Restoring a DynamoDB table to a point in time (console)

The following example demonstrates how to use the DynamoDB console to restore an existing table named `Music` to a point in time.

**Note**

This procedure assumes that you have enabled point-in-time recovery. To enable it for the `Music` table, on the **Backups** tab, in the **Point-in-time recovery (PITR)** section, choose **Edit** and then check the box next to **Enable point-in-time-recovery**.

**To restore a table to a point in time**

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. In the list of tables, choose the `Music` table.
4. On the **Backups** tab of the `Music` table, in the **Point-in-time recovery (PITR)** section, choose **Restore**.
5. For the new table name, enter `MusicMinutesAgo`.

**Note**

You can restore the table to the same AWS Region or to a different Region from where the source table resides. You can also exclude secondary indexes from being created on the restored table. In addition, you can specify a different encryption mode.

6. To confirm the restorable time, set the restore date and time to **Earliest**. Then choose **Restore** to start the restore process.

The table that is being restored is shown with the status **Restoring**. After the restore process is finished, the status of the `MusicMinutesAgo` table changes to **Active**.

## Restoring a table to a point in time (AWS CLI)

The following procedure shows how to use the AWS CLI to restore an existing table named `Music` to a point in time.

**Note**

This procedure assumes that you have enabled point-in-time recovery. To enable it for the `Music` table, run the following command.

```
aws dynamodb update-continuous-backups \
  --table-name Music \
  --point-in-time-recovery-specification PointInTimeRecoveryEnabled=True
```

**To restore a table to a point in time**

1. Confirm that point-in-time recovery is enabled for the `Music` table by using the `describe-continuous-backups` command.

```
aws dynamodb describe-continuous-backups \
  --table-name Music
```

Continuous backups (automatically enabled on table creation) and point-in-time recovery are enabled.

```
{
  "ContinuousBackupsDescription": {
    "PointInTimeRecoveryDescription": {
      "PointInTimeRecoveryStatus": "ENABLED",
      "EarliestRestorableDateTime": 1519257118.0,
      "LatestRestorableDateTime": 1520018653.01
    }
  }
}
```

```

    },
    "ContinuousBackupsStatus": "ENABLED"
}
}
```

2. Restore the table to a point in time. In this case, the `Music` table is restored to the `LatestRestorableDateTime` (~5 minutes ago) to the same AWS Region.

```

aws dynamodb restore-table-to-point-in-time \
--source-table-name Music \
--target-table-name MusicMinutesAgo \
--use-latest-restorable-time
```

**Note**

You can also restore to a specific point in time. To do this, run the command using the `--restore-date-time` argument, and specify a timestamp. You can specify any point in time during the last 35 days. For example, the following command restores the table to the `EarliestRestorableDateTime`.

```

aws dynamodb restore-table-to-point-in-time \
--source-table-name Music \
--target-table-name MusicEarliestRestorableDateTime \
--no-use-latest-restorable-time \
--restore-date-time 1519257118.0
```

Specifying the `--no-use-latest-restorable-time` argument is optional when restoring to a specific point in time.

3. Restore the table to a point in time with custom table settings. In this case, the `Music` table is restored to the `LatestRestorableDateTime` (~5 minutes ago).

You can specify a different encryption mode for the restored table, as follows.

**Note**

The `sse-specification-override` parameter takes the same values as the `sse-specification-override` parameter used in the `CreateTable` command. To learn more, see [Managing encrypted tables in DynamoDB \(p. 1065\)](#).

```

aws dynamodb restore-table-to-point-in-time \
--source-table-name Music \
--target-table-name MusicMinutesAgo \
--use-latest-restorable-time \
--sse-specification-override Enabled=true,SSEType=KMS,KMSMasterKeyId=abcd1234-
abcd-1234-a123-ab1234a1b234
```

You can restore the table to a different AWS Region from where the source table resides.

**Note**

- The `sse-specification-override` parameter is mandatory for cross-Region restores but optional for restores to the same Region as the source table.
- The `source-table-arn` parameter must be provided for cross-Region restores.
- When performing a cross-Region restore from the command line, you must set the default AWS Region to the desired destination Region. To learn more, see [Command line options](#) in the [AWS Command Line Interface User Guide](#).

```

aws dynamodb restore-table-to-point-in-time \
--source-table-arn arn:aws:dynamodb:us-east-1:123456789012:table/Music \
```

API Version 2012-08-10

```
--target-table-name MusicMinutesAgo \
--use-latest-restorable-time \
--sse-specification-override Enabled=true,SSEType=KMS,KMSMasterKeyId=abcd1234-
abcd-1234-a123-ab1234a1b234
```

You can override the billing mode and the provisioned throughput for the restored table.

```
aws dynamodb restore-table-to-point-in-time \
--source-table-name Music \
--target-table-name MusicMinutesAgo \
--use-latest-restorable-time \
--billing-mode-override PAY_PER_REQUEST
```

You can exclude some or all secondary indexes from being created on the restored table.

**Note**

Restores can be faster and more cost-efficient if you exclude some or all secondary indexes from being created on the new restored table.

```
aws dynamodb restore-table-to-point-in-time \
--source-table-name Music \
--target-table-name MusicMinutesAgo \
--use-latest-restorable-time \
--global-secondary-index-override '[]'
```

You can use a combination of different overrides. For example, you can use a single global secondary index and change provisioned throughput at the same time, as follows.

```
aws dynamodb restore-table-to-point-in-time \
--source-table-name Music \
--target-table-name MusicMinutesAgo \
--billing-mode-override PROVISIONED \
--provisioned-throughput-override ReadCapacityUnits=100,WriteCapacityUnits=100 \
--global-secondary-index-override IndexName=singers-
index,KeySchema=[{"AttributeName=SingerName,KeyType=HASH"}],Projection="{ProjectionType=KEYS_ONLY}" \
\
--sse-specification-override Enabled=true,SSEType=KMS \
--use-latest-restorable-time
```

To verify the restore, use the `describe-table` command to describe the `MusicEarliestRestorableDateTime` table.

```
aws dynamodb describe-table --table-name MusicEarliestRestorableDateTime
```

The table that is being restored is shown with the status **Creating** and restore in progress as **true**. After the restore process is finished, the status of the `MusicEarliestRestorableDateTime` table changes to **Active**.

**Important**

While a restore is in progress, don't modify or delete the AWS Identity and Access Management (IAM) policies that grant the IAM entity (for example, user, group, or role) permission to perform the restore. Otherwise, unexpected behavior can result. For example, suppose that you remove write permissions for a table while that table is being restored. In this case, the underlying `RestoreTableToPointInTime` operation can't write any of the restored data to the table. IAM policies involving source IP restrictions for accessing the target restore table can similarly cause issues.

You can modify or delete permissions only after the restore operation is completed.

# In-memory acceleration with DynamoDB Accelerator (DAX)

Amazon DynamoDB is designed for scale and performance. In most cases, the DynamoDB response times can be measured in single-digit milliseconds. However, there are certain use cases that require response times in microseconds. For these use cases, DynamoDB Accelerator (DAX) delivers fast response times for accessing eventually consistent data.

DAX is a DynamoDB-compatible caching service that enables you to benefit from fast in-memory performance for demanding applications. DAX addresses three core scenarios:

1. As an in-memory cache, DAX reduces the response times of eventually consistent read workloads by an order of magnitude from single-digit milliseconds to microseconds.
2. DAX reduces operational and application complexity by providing a managed service that is API-compatible with DynamoDB. Therefore, it requires only minimal functional changes to use with an existing application.
3. For read-heavy or bursty workloads, DAX provides increased throughput and potential operational cost savings by reducing the need to overprovision read capacity units. This is especially beneficial for applications that require repeated reads for individual keys.

DAX supports server-side encryption. With encryption at rest, the data persisted by DAX on disk will be encrypted. DAX writes data to disk as part of propagating changes from the primary node to read replicas. For more information, see [DAX encryption at rest \(p. 744\)](#).

DAX also supports encryption in transit, ensuring that all requests and responses between your application and the cluster are encrypted by transport level security (TLS), and connections to the cluster can be authenticated by verification of a cluster x509 certificate. For more information, see [DAX encryption in transit \(p. 746\)](#).

## Topics

- [Use cases for DAX \(p. 656\)](#)
- [DAX usage notes \(p. 656\)](#)
- [DAX: How it works \(p. 657\)](#)
- [DAX cluster components \(p. 660\)](#)
- [Creating a DAX cluster \(p. 664\)](#)
- [DAX and DynamoDB consistency models \(p. 672\)](#)
- [Developing with the DynamoDB Accelerator \(DAX\) client \(p. 679\)](#)
- [Managing DAX clusters \(p. 712\)](#)
- [Monitoring DAX \(p. 718\)](#)
- [DAX T3/T2 burstable instances \(p. 733\)](#)
- [DAX access control \(p. 734\)](#)
- [DAX encryption at rest \(p. 744\)](#)
- [DAX encryption in transit \(p. 746\)](#)
- [Using service-linked IAM roles for DAX \(p. 747\)](#)
- [Accessing DAX across AWS accounts \(p. 749\)](#)
- [DAX cluster sizing guide \(p. 756\)](#)

- [DAX API reference \(p. 758\)](#)

## Use cases for DAX

DAX provides access to eventually consistent data from DynamoDB tables, with microsecond latency. A Multi-AZ DAX cluster can serve millions of requests per second.

DAX is ideal for the following types of applications:

- Applications that require the fastest possible response time for reads. Some examples include real-time bidding, social gaming, and trading applications. DAX delivers fast, in-memory read performance for these use cases.
- Applications that read a small number of items more frequently than others. For example, consider an ecommerce system that has a one-day sale on a popular product. During the sale, demand for that product (and its data in DynamoDB) would sharply increase, compared to all of the other products. To mitigate the impacts of a "hot" key and a non-uniform traffic distribution, you could offload the read activity to a DAX cache until the one-day sale is over.
- Applications that are read-intensive, but are also cost-sensitive. With DynamoDB, you provision the number of reads per second that your application requires. If read activity increases, you can increase your tables' provisioned read throughput (at an additional cost). Or, you can offload the activity from your application to a DAX cluster, and reduce the number of read capacity units that you need to purchase otherwise.
- Applications that require repeated reads against a large set of data. Such an application could potentially divert database resources from other applications. For example, a long-running analysis of regional weather data could temporarily consume all the read capacity in a DynamoDB table. This situation would negatively impact other applications that need to access the same data. With DAX, the weather analysis could be performed against cached data instead.

DAX is *not* ideal for the following types of applications:

- Applications that require strongly consistent reads (or that cannot tolerate eventually consistent reads).
- Applications that do not require microsecond response times for reads, or that do not need to offload repeated read activity from underlying tables.
- Applications that are write-intensive, or that do not perform much read activity.
- Applications that are already using a different caching solution with DynamoDB, and are using their own client-side logic for working with that caching solution.

## DAX usage notes

- For a list of AWS Regions where DAX is available, see [Amazon DynamoDB pricing](#).
- DAX supports applications written in Go, Java, Node.js, Python, and .NET, using AWS-provided clients for those programming languages.
- DAX is only available for the EC2-VPC platform.
- The DAX cluster service role policy must allow the dynamodb:DescribeTable action in order to maintain metadata about the DynamoDB table.
- DAX clusters maintain metadata about the attribute names of items they store. That metadata is maintained indefinitely (even after the item has expired or been evicted from the cache). Applications that use an unbounded number of attribute names can, over time, cause memory exhaustion in the DAX cluster. This limitation applies only to top-level attribute names, not nested attribute names. Examples of problematic top-level attribute names include timestamps, UUIDs, and session IDs.

This limitation applies only to attribute names, not their values. Items like the following are not a problem.

```
{  
    "Id": 123,  
    "Title": "Bicycle 123",  
    "CreationDate": "2017-10-24T01:02:03+00:00"  
}
```

But items like the following are a problem if there are enough of them and they each have a different timestamp.

```
{  
    "Id": 123,  
    "Title": "Bicycle 123",  
    "2017-10-24T01:02:03+00:00": "created"  
}
```

## DAX: How it works


Amazon DynamoDB Accelerator (DAX) is designed to run within an Amazon Virtual Private Cloud (Amazon VPC) environment. The Amazon VPC service defines a virtual network that closely resembles a traditional data center. With a VPC, you have control over its IP address range, subnets, routing tables, network gateways, and security settings. You can launch a DAX cluster in your virtual network and control access to the cluster by using Amazon VPC security groups.

**Note**

If you created your AWS account after December 4, 2013, you already have a default VPC in each AWS Region. The VPC is ready for you to use immediately—without having to perform any additional configuration steps.

For more information, see [Default VPC and default subnets](#) in the *Amazon VPC User Guide*.

The following diagram shows a high-level overview of DAX.



To create a DAX cluster, you use the AWS Management Console. Unless you specify otherwise, your DAX cluster runs within your default VPC. To run your application, you launch an Amazon EC2 instance into your Amazon VPC. You then deploy your application (with the DAX client) on the EC2 instance.

At runtime, the DAX client directs all of your application's DynamoDB API requests to the DAX cluster. If DAX can process one of these API requests directly, it does so. Otherwise, it passes the request through to DynamoDB.

Finally, the DAX cluster returns the results to your application.

#### Topics

- [How DAX processes requests \(p. 658\)](#)
- [Item cache \(p. 659\)](#)
- [Query cache \(p. 660\)](#)

## How DAX processes requests

A DAX cluster consists of one or more nodes. Each node runs its own instance of the DAX caching software. One of the nodes serves as the primary node for the cluster. Additional nodes (if present) serve as read replicas. For more information, see [Nodes \(p. 660\)](#).

Your application can access DAX by specifying the endpoint for the DAX cluster. The DAX client software works with the cluster endpoint to perform intelligent load balancing and routing.

## Read operations

DAX can respond to the following API calls:

- `GetItem`
- `BatchGetItem`
- `Query`
- `Scan`

If the request specifies *eventually consistent reads* (the default behavior), it tries to read the item from DAX:

- If DAX has the item available (a *cache hit*), DAX returns the item to the application without accessing DynamoDB.
- If DAX does not have the item available (a *cache miss*), DAX passes the request through to DynamoDB. When it receives the response from DynamoDB, DAX returns the results to the application. But it also writes the results to the cache on the primary node.

#### Note

If there are any read replicas in the cluster, DAX automatically keeps the replicas in sync with the primary node. For more information, see [Clusters \(p. 661\)](#).

If the request specifies *strongly consistent reads*, DAX passes the request through to DynamoDB. The results from DynamoDB are not cached in DAX. Instead, they are simply returned to the application.

## Write operations

The following DAX API operations are considered "write-through":

- `BatchWriteItem`

- [UpdateItem](#)
- [DeleteItem](#)
- [PutItem](#)

With these operations, data is first written to the DynamoDB table, and then to the DAX cluster. The operation is successful only if the data is successfully written to *both* the table and to DAX.

## Other operations

DAX does not recognize any DynamoDB operations for managing tables (such as `CreateTable`, `UpdateTable`, and so on). If your application needs to perform these operations, it must access DynamoDB directly rather than using DAX.

For detailed information about DAX and DynamoDB consistency, see [DAX and DynamoDB consistency models \(p. 672\)](#).

For information about how transactions work in DAX, see [Using transactional APIs in DynamoDB Accelerator \(DAX\) \(p. 581\)](#).

## Request rate limiting

If the number of requests sent to DAX exceeds the capacity of a node, DAX limits the rate at which it accepts additional requests by returning a `ThrottlingException`. DAX continuously evaluates your CPU utilization to determine the volume of requests it can process while maintaining a healthy cluster state.

You can monitor the [ThrottledRequestCount metric \(p. 720\)](#) that DAX publishes to Amazon CloudWatch. If you see these exceptions regularly, you should consider [scaling up your cluster \(p. 714\)](#).

## Item cache

DAX maintains an *item cache* to store the results from `GetItem` and `BatchGetItem` operations. The items in the cache represent eventually consistent data from DynamoDB, and are stored by their primary key values.

When an application sends a `GetItem` or `BatchGetItem` request, DAX tries to read the items directly from the item cache using the specified key values. If the items are found (cache hit), DAX returns them to the application immediately. If the items are not found (cache miss), DAX sends the request to DynamoDB. DynamoDB processes the requests using eventually consistent reads and returns the items to DAX. DAX stores them in the item cache and then returns them to the application.

The item cache has a Time to Live (TTL) setting, which is 5 minutes by default. DAX assigns a timestamp to every item that it writes to the item cache. An item expires if it has remained in the cache for longer than the TTL setting. If you issue a `GetItem` request on an expired item, this is considered a cache miss, and DAX sends the `GetItem` request to DynamoDB.

### Note

You can specify the TTL setting for the item cache when you create a new DAX cluster. For more information, see [Managing DAX clusters \(p. 712\)](#).

DAX also maintains a least recently used (LRU) list for the item cache. The LRU list tracks when an item was first written to the cache, and when the item was last read from the cache. If the item cache becomes full, DAX evicts older items (even if they haven't expired yet) to make room for new items. The LRU algorithm is always enabled for the item cache and is not user-configurable.

If you specify zero as the *item cache* TTL setting, items in the item cache will only be refreshed due to an LRU eviction or a "[write-through](#)" operation.

For detailed information about the consistency of the item cache in DAX, see [DAX item cache behavior \(p. 673\)](#).

## Query cache

DAX also maintains a *query cache* to store the results from `Query` and `Scan` operations. The items in this cache represent result sets from queries and scans on DynamoDB tables. These result sets are stored by their parameter values.

When an application sends a `Query` or `Scan` request, DAX tries to read a matching result set from the query cache using the specified parameter values. If the result set is found (cache hit), DAX returns it to the application immediately. If the result set is not found (cache miss), DAX sends the request to DynamoDB. DynamoDB processes the requests using eventually consistent reads and returns the result set to DAX. DAX stores it in the query cache and then returns it to the application.

### Note

You can specify the TTL setting for the query cache when you create a new DAX cluster. For more information, see [Managing DAX clusters \(p. 712\)](#).

DAX also maintains an LRU list for the query cache. The list tracks when a result set was first written to the cache, and when the result was last read from the cache. If the query cache becomes full, DAX evicts older result sets (even if they have not expired yet) to make room for new result sets. The LRU algorithm is always enabled for the query cache, and is not user-configurable.

If you specify zero as the *query cache* TTL setting, the query response will not be cached.

For detailed information about the consistency of the query cache in DAX, see [DAX query cache behavior \(p. 675\)](#).

## DAX cluster components

An Amazon DynamoDB Accelerator (DAX) cluster consists of AWS infrastructure components. This section describes these components and how they work together.

### Topics

- [Nodes \(p. 660\)](#)
- [Clusters \(p. 661\)](#)
- [Regions and availability zones \(p. 661\)](#)
- [Parameter groups \(p. 662\)](#)
- [Security groups \(p. 662\)](#)
- [Cluster ARN \(p. 662\)](#)
- [Cluster endpoint \(p. 662\)](#)
- [Node endpoints \(p. 663\)](#)
- [Subnet groups \(p. 663\)](#)
- [Events \(p. 663\)](#)
- [Maintenance window \(p. 663\)](#)

## Nodes

A *node* is the smallest building block of a DAX cluster. Each node runs an instance of the DAX software, and maintains a single replica of the cached data.

You can scale your DAX cluster in one of two ways:

- By adding more nodes to the cluster. This increases the overall read throughput of the cluster.

- By using a larger node type. Larger node types provide more capacity and can increase throughput. (You must create a new cluster with the new node type.)

Every node within a cluster is of the same node type and runs the same DAX caching software. For a list of available node types, see [Amazon DynamoDB pricing](#).

## Clusters

A *cluster* is a logical grouping of one or more nodes that DAX manages as a unit. One of the nodes in the cluster is designated as the *primary* node, and the other nodes (if any) are *read replicas*.

The primary node is responsible for the following:

- Fulfilling application requests for cached data.
- Handling write operations to DynamoDB.
- Evicting data from the cache according to the cluster's eviction policy.

When changes are made to cached data on the primary node, DAX propagates the changes to all of the read replica nodes.

Read replicas are responsible for the following:

- Fulfilling application requests for cached data.
- Evicting data from the cache according to the cluster's eviction policy.

However, unlike the primary node, read replicas don't write to DynamoDB.

Read replicas serve two additional purposes:

- **Scalability.** If you have a large number of application clients that need to access DAX concurrently, you can add more replicas for read-scaling. DAX spreads the load evenly across all the nodes in the cluster. (Another way to increase throughput is to use larger cache node types.)
- **High availability.** In the event of a primary node failure, DAX automatically fails over to a read replica and designates it as the new primary. If a replica node fails, other nodes in the DAX cluster can still serve requests until the failed node can be recovered. For maximum fault tolerance, you should deploy read replicas in separate Availability Zones. This configuration ensures that your DAX cluster can continue to function, even if an entire Availability Zone becomes unavailable.

A DAX cluster can support up to 11 nodes per cluster (the primary node plus a maximum of 10 read replicas).

### Important

For production usage, we strongly recommend using DAX with at least three nodes, where each node is placed in different Availability Zones. Three nodes are required for a DAX cluster to be fault-tolerant.

A DAX cluster can be deployed with one or two nodes for development or test workloads. One- and two-node clusters are not fault-tolerant, and we don't recommend using fewer than three nodes for production use. If a one- or two-node cluster encounters software or hardware errors, the cluster can become unavailable or lose cached data.

## Regions and availability zones

A DAX cluster in an AWS Region can only interact with DynamoDB tables that are in the same Region. For this reason, ensure that you launch your DAX cluster in the correct Region. If you have DynamoDB tables in other Regions, you must launch DAX clusters in those Regions too.

Each Region is designed to be completely isolated from the other Regions. Within each Region are multiple Availability Zones. By launching your nodes in different Availability Zones, you can achieve the greatest possible fault tolerance.

**Important**

Don't place all of your cluster's nodes in a single Availability Zone. In this configuration, your DAX cluster becomes unavailable if there is an Availability Zone failure.

For production usage, we strongly recommend using DAX with at least three nodes, where each node is placed in different Availability Zones. Three nodes are required for a DAX cluster to be fault-tolerant.

A DAX cluster can be deployed with one or two nodes for development or test workloads. One- and two-node clusters are not fault-tolerant, and we don't recommend using fewer than three nodes for production use. If a one- or two-node cluster encounters software or hardware errors, the cluster can become unavailable or lose cached data.

## Parameter groups

*Parameter groups* are used to manage runtime settings for DAX clusters. DAX has several parameters that you can use to optimize performance (such as defining a TTL policy for cached data). A parameter group is a named set of parameters that you can apply to a cluster. You can thereby ensure that all the nodes in that cluster are configured in exactly the same way.

## Security groups

A DAX cluster runs in an Amazon Virtual Private Cloud (Amazon VPC) environment. This environment is a virtual network that is dedicated to your AWS account and is isolated from other VPCs. A *security group* acts as a virtual firewall for your VPC, allowing you to control inbound and outbound network traffic.

When you launch a cluster in your VPC, you add an *ingress* rule to your security group to allow incoming network traffic. The ingress rule specifies the protocol (TCP) and port number (8111) for your cluster. After you add this rule to your security group, the applications that are running within your VPC can access the DAX cluster.

## Cluster ARN

Every DAX cluster is assigned an *Amazon Resource Name* (ARN). The ARN format is as follows.

```
arn:aws:dax:region:accountID:cache/clusterName
```

You use the cluster ARN in an IAM policy to define permissions for DAX API operations. For more information, see [DAX access control \(p. 734\)](#).

## Cluster endpoint

Every DAX cluster provides a *cluster endpoint* for use by your application. By accessing the cluster using its endpoint, your application does not need to know the hostnames and port numbers of individual nodes in the cluster. Your application automatically "knows" all the nodes in the cluster, even if you add or remove read replicas.

The following is an example of a cluster endpoint in the us-east-1 region that is not configured to use encryption in transit.

```
dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

The following is an example of a cluster endpoint in the same region that is configured to use encryption in transit.

```
daxs://my-encrypted-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

## Node endpoints

Each of the individual nodes in a DAX cluster has its own hostname and port number. The following is an example of a *node endpoint*.

```
myDAXcluster-a.2cmrw1.clustercfg.dax.use1.cache.amazonaws.com:8111
```

Your application can access a node directly by using its endpoint. However, we recommend that you treat the DAX cluster as a single unit and access it using the cluster endpoint instead. The cluster endpoint insulates your application from having to maintain a list of nodes and keep that list up to date when you add or remove nodes from the cluster.

## Subnet groups

Access to DAX cluster nodes is restricted to applications running on Amazon EC2 instances within an Amazon VPC environment. You can use *subnet groups* to grant cluster access from Amazon EC2 instances running on specific subnets. A subnet group is a collection of subnets (typically private) that you can designate for your clusters running in an Amazon VPC environment.

When you create a DAX cluster, you must specify a subnet group. DAX uses that subnet group to select a subnet and IP addresses within that subnet to associate with your nodes.

## Events

DAX records significant events within your clusters, such as a failure to add a node, success in adding a node, or changes to security groups. By monitoring key events, you can know the current state of your clusters and, depending upon the event, be able to take corrective action. You can access these events using the AWS Management Console or the `DescribeEvents` action in the DAX management API.

You can also request that notifications be sent to a specific Amazon Simple Notification Service (Amazon SNS) topic. Then you will know immediately when an event occurs in your DAX cluster.

## Maintenance window

Every cluster has a weekly maintenance window during which any system changes are applied. If you don't specify a preferred maintenance window when you create or modify a cache cluster, DAX assigns a 60-minute maintenance window on a randomly selected day of the week.

The 60-minute maintenance window is selected at random from an 8-hour block of time per AWS Region. The following table lists the time blocks for each Region from which the default maintenance windows are assigned.

Region code	Region name	Maintenance window
ap-northeast-1	Asia Pacific (Tokyo) Region	13:00–21:00 UTC
ap-southeast-1	Asia Pacific (Singapore) Region	14:00–22:00 UTC
ap-southeast-2	Asia Pacific (Sydney) Region	12:00–20:00 UTC

Region code	Region name	Maintenance window
ap-south-1	Asia Pacific (Mumbai) Region	17:30–1:30 UTC
cn-northwest-1	China (Ningxia) Region	23:00–07:00 UTC
cn-north-1	China (Beijing) Region	14:00–22:00 UTC
eu-central-1	Europe (Frankfurt) Region	23:00–07:00 UTC
eu-west-1	Europe (Ireland) Region	22:00–06:00 UTC
eu-west-2	Europe (London) Region	23:00–07:00 UTC
eu-west-3	Europe (Paris) Region	23:00–07:00 UTC
sa-east-1	South America (São Paulo) Region	01:00–09:00 UTC
us-east-1	US East (N. Virginia) Region	03:00–11:00 UTC
us-east-2	US East (Ohio) Region	23:00–07:00 UTC
us-west-1	US West (N. California) Region	06:00–14:00 UTC
us-west-2	US West (Oregon) Region	06:00–14:00 UTC

The maintenance window should fall at the time of lowest usage and thus might need modification from time to time. You can specify a time range of up to 24 hours in duration during which any maintenance activities that you request should occur.

## Creating a DAX cluster

This section walks you through the first-time setup and usage of Amazon DynamoDB Accelerator (DAX) in your default Amazon Virtual Private Cloud (Amazon VPC) environment. You can create your first DAX cluster using either the AWS Command Line Interface (AWS CLI) or the AWS Management Console.

After you create your DAX cluster, you can access it from an Amazon EC2 instance running in the same VPC. You can then use your DAX cluster with an application program. For more information, see [Developing with the DynamoDB Accelerator \(DAX\) client \(p. 679\)](#).

### Topics

- [Creating an IAM service role for DAX to access DynamoDB \(p. 664\)](#)
- [Creating a DAX cluster using the AWS CLI \(p. 666\)](#)
- [Creating a DAX cluster using the AWS Management Console \(p. 670\)](#)

## Creating an IAM service role for DAX to access DynamoDB

For your DAX cluster to access DynamoDB tables on your behalf, you must create a *service role*. A service role is an AWS Identity and Access Management (IAM) role that authorizes an AWS service to act on your behalf. The service role allows DAX to access your DynamoDB tables, as if you were accessing those tables yourself. You must create the service role before you can create the DAX cluster.

If you are using the console, the workflow for creating a cluster checks for the presence of a pre-existing DAX service role. If none is found, the console creates a new service role for you. For more information, see [the section called "Step 2: Create a DAX cluster" \(p. 671\)](#).

If you are using the AWS CLI, you must specify a DAX service role that you have created previously. Otherwise, you need to create a new service role beforehand. For more information, see [Step 1: Create an IAM service role for DAX to access DynamoDB using the AWS CLI \(p. 666\)](#).

## Permissions required to create a service role

The AWS managed `AdministratorAccess` policy provides all the permissions needed for creating a DAX cluster and a service role. If your IAM user has `AdministratorAccess` attached, no further action is needed.

Otherwise, you must add the following permissions to your IAM policy so that your IAM user can create the service role:

- `iam:CreateRole`
- `iam:CreatePolicy`
- `iam:AttachRolePolicy`
- `iam:PassRole`

Attach these permissions to the user who is trying to perform the action.

### Note

The `iam:CreateRole`, `iam:CreatePolicy`, `iam:AttachRolePolicy`, and `iam:PassRole` permissions are not included in the AWS managed policies for DynamoDB. This is by design because these permissions provide the possibility of privilege escalation: That is, a user could use these permissions to create a new administrator policy and then attach that policy to an existing role. For this reason, you (the administrator of your DAX cluster) must explicitly add these permissions to your policy.

## Troubleshooting

If your user policy is missing the `iam:CreateRole`, `iam:CreatePolicy`, and `iam:AttachPolicy` permissions, you will get error messages. The following table lists these messages and describes how to correct the problems.

If you see this error message...	Do the following:
User: <code>arn:aws:iam::accountID:user/<i>userName</i></code> is not authorized to perform: <code>iam:CreateRole</code> on resource: <code>arn:aws:iam::accountID:role/service-role/<i>roleName</i></code>	Add <code>iam:CreateRole</code> to your user policy.
User: <code>arn:aws:iam::accountID:user/<i>userName</i></code> is not authorized to perform: <code>iam:CreatePolicy</code> on resource: policy <code><i>policyName</i></code>	Add <code>iam:CreatePolicy</code> to your user policy.
User: <code>arn:aws:iam::accountID:user/<i>userName</i></code> is not authorized to perform:	Add <code>iam:AttachRolePolicy</code> to your user policy.

If you see this error message...	Do the following:
<code>iam:AttachRolePolicy on resource: role daxServiceRole</code>	

For more information about the IAM policies required for DAX cluster administration, see [DAX access control \(p. 734\)](#).

## Creating a DAX cluster using the AWS CLI

This section describes how to create an Amazon DynamoDB Accelerator (DAX) cluster using the AWS Command Line Interface (AWS CLI). If you haven't already done so, you must install and configure the AWS CLI. To do this, see the following instructions in the *AWS Command Line Interface User Guide*:

- [Installing the AWS CLI](#)
- [Configuring the AWS CLI](#)

**Important**

To manage DAX clusters using the AWS CLI, install or upgrade to version 1.11.110 or higher.

All of the AWS CLI examples use the `us-west-2` Region and fictitious account IDs.

**Topics**

- [Step 1: Create an IAM service role for DAX to access DynamoDB using the AWS CLI \(p. 666\)](#)
- [Step 2: Create a subnet group \(p. 668\)](#)
- [Step 3: Create a DAX cluster using the AWS CLI \(p. 668\)](#)
- [Step 4: Configure security group inbound rules using the AWS CLI \(p. 669\)](#)

## Step 1: Create an IAM service role for DAX to access DynamoDB using the AWS CLI

Before you can create an Amazon DynamoDB Accelerator (DAX) cluster, you must create a service role for it. A *service role* is an AWS Identity and Access Management (IAM) role that authorizes an AWS service to act on your behalf. The service role allows DAX to access your DynamoDB tables as if you were accessing those tables yourself.

In this step, you create an IAM policy and then attach that policy to an IAM role. This enables you to assign the role to a DAX cluster so that it can perform DynamoDB operations on your behalf.

### To create an IAM service role for DAX

1. Create a file named `service-trust-relationship.json` with the following contents.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Principal": {  
                "Service": "dax.amazonaws.com"  
            },  
            "Action": "sts:AssumeRole"  
        }  
    ]  
}
```

```
    ]  
}
```

2. Create the service role.

```
aws iam create-role \  
  --role-name DAXServiceRoleForDynamoDBAccess \  
  --assume-role-policy-document file://service-trust-relationship.json
```

3. Create a file named `service-role-policy.json` with the following contents.

```
{  
  "Version": "2012-10-17",  
  "Statement": [  
    {  
      "Action": [  
        "dynamodb:DescribeTable",  
        "dynamodb:PutItem",  
        "dynamodb:GetItem",  
        "dynamodb:UpdateItem",  
        "dynamodb:DeleteItem",  
        "dynamodb:Query",  
        "dynamodb:Scan",  
        "dynamodb:BatchGetItem",  
        "dynamodb:BatchWriteItem",  
        "dynamodb:ConditionCheckItem"  
      ],  
      "Effect": "Allow",  
      "Resource": [  
        "arn:aws:dynamodb:us-west-2:accountID:*"  
      ]  
    }  
  ]  
}
```

Replace `accountID` with your AWS account ID. To find your AWS account ID, in the upper-right corner of the console, choose your login ID. Your AWS account ID appears in the drop-down menu.

In the Amazon Resource Name (ARN) in the example, `accountID` must be a 12-digit number. Don't use hyphens or any other punctuation.

4. Create an IAM policy for the service role.

```
aws iam create-policy \  
  --policy-name DAXServicePolicyForDynamoDBAccess \  
  --policy-document file://service-role-policy.json
```

In the output, note the ARN for the policy that you created, as in the following example.

```
arn:aws:iam::123456789012:policy/DAXServicePolicyForDynamoDBAccess
```

5. Attach the policy to the service role. Replace `arn` in the following code with the actual role ARN from the previous step.

```
aws iam attach-role-policy \  
  --role-name DAXServiceRoleForDynamoDBAccess \  
  --policy-arn arn
```

Next, you specify a subnet group for your default VPC. A *subnet group* is a collection of one or more subnets within your VPC. See [Step 2: Create a subnet group \(p. 668\)](#).

## Step 2: Create a subnet group

Follow this procedure to create a subnet group for your Amazon DynamoDB Accelerator (DAX) cluster using the AWS Command Line Interface (AWS CLI).

### Note

If you already created a subnet group for your default VPC, you can skip this step.

DAX is designed to run within an Amazon Virtual Private Cloud environment (Amazon VPC). If you created your AWS account after December 4, 2013, you already have a default VPC in each AWS Region. For more information, see [Default VPC and default subnets](#) in the *Amazon VPC User Guide*.

### To create a subnet group

1. To determine the identifier for your default VPC, enter the following command.

```
aws ec2 describe-vpcs
```

In the output, note the identifier for your default VPC, as in the following example.

```
vpc-12345678
```

2. Determine the subnet IDs associated with your default VPC. Replace `vpcID` with your actual VPC ID—for example, `vpc-12345678`.

```
aws ec2 describe-subnets \
--filters "Name=vpc-id,Values=vpcID" \
--query "Subnets[*].SubnetId"
```

In the output, note the subnet identifiers—for example, `subnet-11111111`.

3. Create the subnet group. Ensure that you specify at least one subnet ID in the `--subnet-ids` parameter.

```
aws dax create-subnet-group \
--subnet-group-name my-subnet-group \
--subnet-ids subnet-11111111 subnet-22222222 subnet-33333333 subnet-44444444
```

To create the cluster, see [Step 3: Create a DAX cluster using the AWS CLI \(p. 668\)](#).

## Step 3: Create a DAX cluster using the AWS CLI

Follow this procedure to use the AWS Command Line Interface (AWS CLI) to create an Amazon DynamoDB Accelerator (DAX) cluster in your default Amazon VPC.

### To create a DAX cluster

1. Get the Amazon Resource Name (ARN) for your service role.

```
aws iam get-role \
--role-name DAXServiceRoleForDynamoDBAccess \
--query "Role.Arn" --output text
```

In the output, note the service role ARN, as in the following example.

```
arn:aws:iam::123456789012:role/DAXServiceRoleForDynamoDBAccess
```

2. Create the DAX cluster. Replace `roleARN` with the ARN from the previous step.

```
aws dax create-cluster \
--cluster-name mydaxcluster \
--node-type dax.r4.large \
--replication-factor 3 \
--iam-role-arn roleARN \
--subnet-group my-subnet-group \
--sse-specification Enabled=true \
--region us-west-2
```

All of the nodes in the cluster are of type `dax.r4.large` (`--node-type`). There are three nodes (`--replication-factor`)—one primary node and two replicas.

**Note**

Since `sudo` and `grep` are reserved keywords, you cannot create a DAX cluster with these words in the cluster name. For example, `sudo` and `sudocluster` are invalid cluster names.

To view the cluster status, enter the following command.

```
aws dax describe-clusters
```

The status is shown in the output—for example, "Status": "creating".

**Note**

Creating the cluster takes several minutes. When the cluster is ready, its status changes to available. In the meantime, proceed to [Step 4: Configure security group inbound rules using the AWS CLI \(p. 669\)](#) and follow the instructions there.

## Step 4: Configure security group inbound rules using the AWS CLI

The nodes in your Amazon DynamoDB Accelerator (DAX) cluster use the default security group for your Amazon VPC. For the default security group, you must authorize inbound traffic on TCP port 8111 for unencrypted clusters or port 9111 for encrypted clusters. This allows Amazon EC2 instances in your Amazon VPC to access your DAX cluster.

**Note**

If you launched your DAX cluster with a different security group (other than `default`), you must perform this procedure for that group instead.

### To configure security group inbound rules

1. To determine the default security group identifier, enter the following command. Replace `vpcID` with your actual VPC ID (from [Step 2: Create a subnet group \(p. 668\)](#)).

```
aws ec2 describe-security-groups \
--filters Name=vpc-id,Values=vpcID,Name=group-name,Values=default \
--query "SecurityGroups[*].{GroupName:GroupName,GroupId:GroupId}"
```

In the output, note the security group identifier—for example, `sg-01234567`.

2. Then enter the following. Replace `sgID` with your actual security group identifier. Use port 8111 for unencrypted clusters and 9111 for encrypted clusters.

```
aws ec2 authorize-security-group-ingress \
--group-id sgID --protocol tcp --port 8111
```

# Creating a DAX cluster using the AWS Management Console

This section describes how to create an Amazon DynamoDB Accelerator (DAX) cluster using the AWS Management Console.

## Topics

- [Step 1: Create a subnet group using the AWS Management Console \(p. 670\)](#)
- [Step 2: Create a DAX cluster using the AWS Management Console \(p. 671\)](#)
- [Step 3: Configure security group inbound rules using the AWS Management Console \(p. 672\)](#)

## Step 1: Create a subnet group using the AWS Management Console

Follow this procedure to create a subnet group for your Amazon DynamoDB Accelerator (DAX) cluster using the AWS Management Console.

### Note

If you already created a subnet group for your default VPC, you can skip this step.

DAX is designed to run within an Amazon Virtual Private Cloud (Amazon VPC) environment. If you created your AWS account after December 4, 2013, you already have a default VPC in each AWS Region. For more information, see [Default VPC and default subnets](#) in the *Amazon VPC User Guide*.

As part of the creation process for a DAX cluster, you must specify a *subnet group*. A subnet group is a collection of one or more subnets within your VPC. When you create your DAX cluster, the nodes are deployed to the subnets within the subnet group.

### To create a subnet group

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, under **DAX**, choose **Subnet groups**.
3. Choose **Create subnet group**.
4. In the **Create subnet group** window, do the following:
  - a. **Name**—Enter a short name for the subnet group.
  - b. **Description**—Enter a description for the subnet group.
  - c. **VPC ID**—Choose the identifier for your Amazon VPC environment.
  - d. **Subnets**—Choose one or more subnets from the list.

### Note

The subnets are distributed among multiple Availability Zones. If you plan to create a multi-node DAX cluster (a primary node and one or more read replicas), we recommend that you choose multiple subnet IDs. Then DAX can deploy the cluster nodes into multiple Availability Zones. If an Availability Zone becomes unavailable, DAX automatically fails over to a surviving Availability Zone. Your DAX cluster will continue to function without interruption.

When the settings are as you want them, choose **Create subnet group**.

To create the cluster, see [Step 2: Create a DAX cluster using the AWS Management Console \(p. 671\)](#).

## Step 2: Create a DAX cluster using the AWS Management Console

Follow this procedure to create an Amazon DynamoDB Accelerator (DAX) cluster in your default Amazon VPC.

### To create a DAX cluster

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, under **DAX**, choose **Clusters**.
3. Choose **Create cluster**.
4. In the **Create cluster** window, do the following:

- a. **Cluster name**—Enter a short name for your DAX cluster.

#### Note

Since `sudo` and `grep` are reserved keywords, you cannot create a DAX cluster with these words in the cluster name. For example, `sudo` and `sudocluster` are invalid cluster names.

- b. **Cluster description**—Enter a description for the cluster.
- c. **Node types**—Choose the node type for all of the nodes in the cluster.
- d. **Cluster size**—Choose the number of nodes in the cluster. A cluster consists of one primary node and up to nine read replicas.

#### Note

If you want to create a single-node cluster, choose **1**. Your cluster will consist of one primary node.

If you want to create a multi-node cluster, choose a number between **3** (one primary and two read replicas) and **10** (one primary and nine read replicas).

#### Important

For production usage, we strongly recommend using DAX with at least three nodes, where each node is placed in a different Availability Zone. Three nodes are required for a DAX cluster to be fault-tolerant.

A DAX cluster can be deployed with one or two nodes for development or test workloads. One- and two-node clusters are not fault-tolerant, and we don't recommend using fewer than three nodes for production use. If a one- or two-node cluster encounters software or hardware errors, the cluster can become unavailable or lose cached data.

- e. Choose **Next**.
- f. **Subnet group**—Select **Choose existing** and choose the subnet group that you created in [Step 1: Create a subnet group using the AWS Management Console \(p. 670\)](#).
- g. **Access control**—Choose the **default** security group.
- h. **Availability Zones (AZ)**—Choose **Automatic**.
- i. Choose next.
- j. **IAM service role for DynamoDB access**—Choose **Create new**, and enter the following information:
  - **IAM role name**—Enter a name for an IAM role, for example, `DAXServiceRole`. The console creates a new IAM role, and your DAX cluster assumes this role at runtime.
  - Select the box next to **Create policy**.
  - **IAM role policy**—Choose **Read/Write**. This allows the DAX cluster to perform read and write operations in DynamoDB.

- **New IAM policy name**—Enter a name for an IAM policy, for example, `DAXServicePolicy`. The console creates a new IAM policy and attaches the policy to the IAM role.
  - **Target DynamoDB table**—Choose **All tables**.
- k. **Encryption**—Choose **Enable encryption at rest** and **Enable encryption in transit** For more information, see [DAX encryption at rest \(p. 744\)](#) and [DAX encryption in transit \(p. 746\)](#).

A separate service role for DAX to access Amazon EC2 is also required. DAX automatically creates this service role for you. For more information, see [Using service-linked roles for DAX](#).

5. When the settings are as you want them, choose **Launch cluster**.

On the **Clusters** screen, your DAX cluster will be listed with a status of **Creating**.

**Note**

Creating the cluster takes several minutes. When the cluster is ready, its status changes to **Available**.

In the meantime, proceed to [Step 3: Configure security group inbound rules using the AWS Management Console \(p. 672\)](#) and follow the instructions there.

## Step 3: Configure security group inbound rules using the AWS Management Console

Your Amazon DynamoDB Accelerator (DAX) cluster communicates via TCP port 8111 (for unencrypted clusters) or 9111 (for encrypted clusters), so you must authorize inbound traffic on that port. This allows Amazon EC2 instances in your Amazon VPC to access your DAX cluster.

**Note**

If you launched your DAX cluster with a different security group (other than `default`), you must perform this procedure for that group instead.

### To configure security group inbound rules

1. Open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.
2. In the navigation pane, choose **Security Groups**.
3. Choose the **default** security group. On the **Actions** menu, choose **Edit inbound rules**.
4. Choose **Add Rule**, and enter the following information:
  - **Port Range**—Enter **8111** (if your cluster is unencrypted) or **9111** (if your cluster is encrypted).
  - **Source**—Enter **default**, and then choose the identifier for your default security group.

When the settings are as you want them, choose **Save**.

## DAX and DynamoDB consistency models

Amazon DynamoDB Accelerator (DAX) is a write-through caching service that is designed to simplify the process of adding a cache to DynamoDB tables. Because DAX operates separately from DynamoDB, it is important that you understand the consistency models of both DAX and DynamoDB to ensure that your applications behave as you expect.

In many use cases, the way that your application uses DAX affects the consistency of data within the DAX cluster, and the consistency of data between DAX and DynamoDB.

## Topics

- [Consistency among DAX cluster nodes \(p. 673\)](#)
- [DAX item cache behavior \(p. 673\)](#)
- [DAX query cache behavior \(p. 675\)](#)
- [Strongly consistent and transactional reads \(p. 676\)](#)
- [Negative caching \(p. 676\)](#)
- [Strategies for writes \(p. 676\)](#)

# Consistency among DAX cluster nodes

To achieve high availability for your application, we recommend that you provision your DAX cluster with at least three nodes. Then place those nodes in multiple Availability Zones within a Region.

When your DAX cluster is running, it replicates the data among all of the nodes in the cluster (assuming that you provisioned more than one node). Consider an application that performs a successful `UpdateItem` using DAX. This action causes the item cache in the primary node to be modified with the new value. That value is then replicated to all the other nodes in the cluster. This replication is eventually consistent and usually takes less than one second to complete.

In this scenario, it's possible for two clients to read the same key from the same DAX cluster but receive different values, depending on the node that each client accessed. The nodes are all consistent when the update has been fully replicated throughout all the nodes in the cluster. (This behavior is similar to the eventually consistent nature of DynamoDB.)

If you are building an application that uses DAX, that application should be designed so that it can tolerate eventually consistent data.

## DAX item cache behavior


Every DAX cluster has two distinct caches—an *item* cache and a *query* cache. For more information, see [DAX: How it works \(p. 657\)](#).

This section addresses the consistency implications of reading from and writing to the DAX item cache.

### Consistency of reads

With DynamoDB, the `GetItem` operation performs an eventually consistent read by default. Suppose that you use `UpdateItem` with the DynamoDB client. If you then try to read the same item immediately afterward, you might see the data as it appeared before the update. This is due to propagation delay across all the DynamoDB storage locations. Consistency is usually reached within seconds. So if you retry the read, you will likely see the updated item.

When you use `GetItem` with the DAX client, the operation (in this case, an eventually consistent read) proceeds as shown following.



1. The DAX client issues a `GetItem` request. DAX tries to read the requested item from the item cache. If the item is in the cache (*cache hit*), DAX returns it to the application.
2. If the item is not available (*cache miss*), DAX performs an eventually consistent `GetItem` operation against DynamoDB.
3. DynamoDB returns the requested item, and DAX stores it in the item cache.
4. DAX returns the item to the application.
5. (Not shown) If the DAX cluster contains more than one node, the item is replicated to all the other nodes in the cluster.

The item remains in the DAX item cache, subject to the Time to Live (TTL) setting and the least recently used (LRU) algorithm for the cache. For more information, see [DAX: How it works \(p. 657\)](#).

However, during this period, DAX doesn't re-read the item from DynamoDB. If someone else updates the item using a DynamoDB client, bypassing DAX entirely, a `GetItem` request using the DAX client yields different results from the same `GetItem` request using the DynamoDB client. In this scenario, DAX and DynamoDB hold inconsistent values for the same key until the TTL for the DAX item expires.

If an application modifies data in an underlying DynamoDB table, bypassing DAX, the application needs to anticipate and tolerate data inconsistencies that might arise.

**Note**

In addition to `GetItem`, the DAX client also supports `BatchGetItem` requests. `BatchGetItem` is essentially a wrapper around one or more `GetItem` requests, so DAX treats each of these as an individual `GetItem` operation.

## Consistency of writes

DAX is a write-through cache, which simplifies the process of keeping the DAX item cache consistent with the underlying DynamoDB tables.

The DAX client supports the same write API operations as DynamoDB (`PutItem`, `UpdateItem`, `DeleteItem`, `BatchWriteItem`, and `TransactWriteItems`). When you use these operations with the DAX client, the items are modified in both DAX and DynamoDB. DAX updates the items in its item cache, regardless of the TTL value for these items.

For example, suppose that you issue a `GetItem` request from the DAX client to read an item from the `ProductCatalog` table. (The partition key is `Id`, and there is no sort key.) You retrieve the item whose `Id` is 101. The `QuantityOnHand` value for that item is 42. DAX stores the item in its item cache with a specific TTL. For this example, assume that the TTL is 10 minutes. Then, 3 minutes later, another application uses the DAX client to update the same item so that its `QuantityOnHand` value is now 41. Assuming that the item is not updated again, any subsequent reads of the same item during the next 10 minutes return the cached value for `QuantityOnHand` (41).

## How DAX processes writes

DAX is intended for applications that require high-performance reads. As a write-through cache, DAX passes your writes through to DynamoDB synchronously, then automatically and asynchronously replicates resulting updates to your item cache across all nodes in the cluster. You don't need to manage cache invalidation logic because DAX handles it for you.

DAX supports the following write operations: `PutItem`, `UpdateItem`, `DeleteItem`, `BatchWriteItem`, and `TransactWriteItems`.

When you send a `PutItem`, `UpdateItem`, `DeleteItem`, or `BatchWriteItem` request to DAX, the following occurs:

- DAX sends the request to DynamoDB.
- DynamoDB replies to DAX, confirming that the write succeeded.
- DAX writes the item to its item cache.
- DAX returns success to the requester.

When you send a `TransactWriteItems` request to DAX, the following occurs:

- DAX sends the request to DynamoDB.
- DynamoDB replies to DAX, confirming that the transaction completed.
- DAX returns success to the requester.
- In the background, DAX makes a `TransactGetItems` request for each item in the `TransactWriteItems` request to store the item in the item cache. `TransactGetItems` is used to ensure [serializable isolation \(p. 579\)](#).

If a write to DynamoDB fails for any reason, including throttling, the item is not cached in DAX. The exception for the failure is returned to the requester. This ensures that data is not written to the DAX cache unless it is first written successfully to DynamoDB.

### Note

Every write to DAX alters the state of the item cache. However, writes to the item cache don't affect the query cache. (The DAX item cache and query cache serve different purposes, and operate independently from one another.)

## DAX query cache behavior

DAX caches the results from `Query` and `Scan` requests in its query cache. However, these results don't affect the item cache at all. When your application issues a `Query` or `Scan` request with DAX, the result set is saved in the query cache—not in the item cache. You can't "warm up" the item cache by performing a `Scan` operation because the item cache and query cache are separate entities.

## Consistency of query-update-query

Updates to the item cache, or to the underlying DynamoDB table, do not invalidate or modify the results stored in the query cache.

To illustrate, consider the following scenario. An application is working with the `DocumentRevisions` table, which has `DocId` as its partition key and `RevisionNumber` as its sort key.

1. A client issues a `Query` for `DocId` 101, for all items with `RevisionNumber` greater than or equal to 5. DAX stores the result set in the query cache and returns the result set to the user.
2. The client issues a `PutItem` request for `DocId` 101 with a `RevisionNumber` value of 20.
3. The client issues the same `Query` as described in step 1 (`DocId` 101 and `RevisionNumber >= 5`).

In this scenario, the cached result set for the `Query` issued in step 3 is identical to the result set that was cached in step 1. The reason is that DAX does not invalidate `Query` or `Scan` result sets based on updates to individual items. The `PutItem` operation from step 2 is only reflected in the DAX query cache when the TTL for the `Query` expires.

Your application should consider the TTL value for the query cache and how long your application can tolerate inconsistent results between the query cache and the item cache.

## Strongly consistent and transactional reads

To perform a strongly consistent `GetItem`, `BatchGetItem`, `Query`, or `Scan` request, you set the `ConsistentRead` parameter to `true`. DAX passes strongly consistent read requests to DynamoDB. When it receives a response from DynamoDB, DAX returns the results to the client, but it does not cache the results. DAX can't serve strongly consistent reads by itself because it's not tightly coupled to DynamoDB. For this reason, any subsequent reads from DAX would have to be eventually consistent reads. And any subsequent strongly consistent reads would have to be passed through to DynamoDB.

DAX handles `TransactGetItems` requests the same way it handles strongly consistent reads. DAX passes all `TransactGetItems` requests to DynamoDB. When it receives a response from DynamoDB, DAX returns the results to the client, but it doesn't cache the results.

## Negative caching

DAX supports negative cache entries in both the item cache and the query cache. A *negative cache entry* occurs when DAX can't find requested items in an underlying DynamoDB table. Instead of generating an error, DAX caches an empty result and returns that result to the user.

For example, suppose that an application sends a `GetItem` request to a DAX cluster, and that there is no matching item in the DAX item cache. This causes DAX to read the corresponding item from the underlying DynamoDB table. If the item doesn't exist in DynamoDB, DAX stores an empty item in its item cache and returns the empty item to the application. Now suppose that the application sends another `GetItem` request for the same item. DAX finds the empty item in the item cache and returns it to the application immediately. It does not consult DynamoDB at all.

A negative cache entry remains in the DAX item cache until its item TTL has expired, its LRU is invoked, or the item is modified using `PutItem`, `UpdateItem`, or `DeleteItem`.

The DAX query cache handles negative cache results in a similar way. If an application performs a `Query` or `Scan`, and the DAX query cache doesn't contain a cached result, DAX sends the request to DynamoDB. If there are no matching items in the result set, DAX stores an empty result set in the query cache and returns the empty result set to the application. Subsequent `Query` or `Scan` requests yield the same (empty) result set, until the TTL for that result set has expired.

## Strategies for writes

The write-through behavior of DAX is appropriate for many application patterns. However, there are some application patterns where a write-through model might not be appropriate.

For applications that are sensitive to latency, writing through DAX incurs an extra network hop. So a write to DAX is a little slower than a write directly to DynamoDB. If your application is sensitive to write latency, you can reduce the latency by writing directly to DynamoDB instead. For more information, see [Write-around \(p. 678\)](#).

For write-intensive applications (such as those that perform bulk data loading), you might not want to write all of the data through DAX because only a small percentage of that data is ever read by the application. When you write large amounts of data through DAX, it must invoke its LRU algorithm to make room in the cache for the new items to be read. This diminishes the effectiveness of DAX as a read cache.


When you write an item to DAX, the item cache state is altered to accommodate the new item. (For example, DAX might need to evict older data from the item cache to make room for the new item.) The new item remains in the item cache, subject to the cache's LRU algorithm and the TTL setting for the cache. As long as the item persists in the item cache, DAX doesn't re-read the item from DynamoDB.

## Write-through

The DAX item cache implements a write-through policy. For more information, see [How DAX processes writes \(p. 675\)](#).

When you write an item, DAX ensures that the cached item is synchronized with the item as it exists in DynamoDB. This is helpful for applications that need to re-read an item immediately after writing it. However, if other applications write directly to a DynamoDB table, the item in the DAX item cache is no longer in sync with DynamoDB.

To illustrate, consider two users (Alice and Bob), who are working with the `ProductCatalog` table. Alice accesses the table using DAX, but Bob bypasses DAX and accesses the table directly in DynamoDB.



1. Alice updates an item in the `ProductCatalog` table. DAX forwards the request to DynamoDB, and the update succeeds. DAX then writes the item to its item cache and returns a successful response to Alice. From that point on, until the item is ultimately evicted from the cache, any user who reads the item from DAX sees the item with Alice's update.

2. A short time later, Bob updates the same `ProductCatalog` item that Alice wrote. However, Bob updates the item directly in DynamoDB. DAX does not automatically refresh its item cache in response to updates via DynamoDB. Therefore, DAX users don't see Bob's update.
3. Alice reads the item from DAX again. The item is in the item cache, so DAX returns it to Alice without accessing the DynamoDB table.


In this scenario, Alice and Bob see different representations of the same `ProductCatalog` item. This is the case until DAX evicts the item from the item cache, or until another user updates the same item again using DAX.

## Write-around

If your application needs to write large quantities of data (such as a bulk data load), it might make sense to bypass DAX and write the data directly to DynamoDB. Such a *write-around* strategy reduces write latency. However, the item cache doesn't remain in sync with the data in DynamoDB.

If you decide to use a write-around strategy, remember that DAX populates its item cache whenever applications use the DAX client to read data. This can be advantageous in some cases because it ensures that only the most frequently read data is cached (as opposed to the most frequently written data).

For example, consider a user (Charlie) who wants to work with a different table, the `GameScores` table, using DAX. The partition key for `GameScores` is `UserId`, so all of Charlie's scores would have the same `UserId`.



1. Charlie wants to retrieve all of his scores, so he sends a `Query` to DAX. Assuming that this query has not been issued before, DAX forwards the query to DynamoDB for processing. It stores the results in the DAX query cache, and then returns the results to Charlie. The result set remains available in the query cache until it is evicted.
2. Now suppose that Charlie plays the Meteor Blasters game and achieves a high score. Charlie sends an `UpdateItem` request to DynamoDB, modifying an item in the `GameScores` table.
3. Finally, Charlie decides to rerun his earlier `Query` to retrieve all of his data from `GameScores`. Charlie does not see his high score for Meteor Blasters in the results. This is because the query results come from the query cache, not the item cache. The two caches are independent from one another, so a change in one cache does not affect the other cache.

DAX does not refresh result sets in the query cache with the most current data from DynamoDB. Each result set in the query cache is current as of the time that the `Query` or `Scan` operation was performed. Thus, Charlie's `Query` results don't reflect his `PutItem` operation. This is the case until DAX evicts the result set from the query cache.

## Developing with the DynamoDB Accelerator (DAX) client

To use DAX from an application, you use the DAX client for your programming language. The DAX client is designed for minimal disruption to your existing Amazon DynamoDB applications—with only a few simple code modifications needed.

### Note

DAX clients for various programming languages are available on the following site:

- <http://dax-sdk.s3-website-us-west-2.amazonaws.com>

This section demonstrates how to launch an Amazon EC2 instance in your default Amazon VPC, connect to the instance, and run a sample application. It also provides information about how to modify your existing application so that it can use your DAX cluster.

### Topics

- [Tutorial: Running a sample application using DynamoDB Accelerator \(DAX\) \(p. 679\)](#)
- [Modifying an existing application to use DAX \(p. 711\)](#)

## Tutorial: Running a sample application using DynamoDB Accelerator (DAX)

This tutorial demonstrates how to launch an Amazon EC2 instance in your default virtual private cloud (VPC), connect to the instance, and run a sample application that uses Amazon DynamoDB Accelerator (DAX).

### Note

To complete this tutorial, you must have a DAX cluster running in your default VPC. If you haven't created a DAX cluster, see [Creating a DAX cluster \(p. 664\)](#) for instructions.

### Topics

- [Step 1: Launch an Amazon EC2 instance \(p. 679\)](#)
- [Step 2: Create an IAM user and policy \(p. 681\)](#)
- [Step 3: Configure an Amazon EC2 instance \(p. 682\)](#)
- [Step 4: Run a sample application \(p. 682\)](#)

## Step 1: Launch an Amazon EC2 instance

When your Amazon DynamoDB Accelerator (DAX) cluster is available, you can launch an Amazon EC2 instance in your default Amazon VPC. You can then install and run DAX client software on that instance.

### To launch an EC2 instance

1. Sign in to the AWS Management Console and open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.

2. Choose **Launch Instance**, and do the following:

**Step 1: Choose an Amazon Machine Image (AMI)**

1. In the list of AMIs, find the **Amazon Linux AMI**, and choose **Select**.

**Step 2: Choose an Instance Type**

1. In the list of instance types, choose **t2.micro**.
2. Choose **Next: Configure Instance Details**.

**Step 3: Configure Instance Details**

1. For **Network**, choose your default VPC.
2. Choose **Next: Add Storage**.

**Step 4: Add Storage**

1. Skip this step by choosing **Next: Add Tags**.

**Step 5: Add Tags**

1. Skip this step by choosing **Next: Configure Security Group**.

**Step 6: Configure Security Group**

1. Choose **Select an existing security group**.
2. In the list of security groups, choose **default**. This is the default security group for your VPC.
3. Choose **Next: Review and Launch**.

**Step 7: Review Instance Launch**

1. Choose **Launch**.
3. In the **Select an existing key pair or create a new key pair** window, do one of the following:
  - If you don't have an Amazon EC2 key pair, choose **Create a new key pair** and follow the instructions. You are asked to download a private key file (.pem file). You need this file later when you log in to your Amazon EC2 instance.
  - If you already have an existing Amazon EC2 key pair, go to **Select a key pair** and choose your key pair from the list. You must already have the private key file (.pem file) available in order to log in to your Amazon EC2 instance.
4. After configuring your key pair, choose **Launch Instances**.
5. In the console navigation pane, choose **EC2 Dashboard**, and then choose the instance that you launched. In the lower pane, on the **Description** tab, find the **Public DNS** for your instance, for example: ec2-11-22-33-44.us-west-2.compute.amazonaws.com. Make a note of this public DNS name because you need it for [Step 3: Configure an Amazon EC2 instance \(p. 682\)](#).

**Note**

It takes a few minutes for your Amazon EC2 instance to become available. In the meantime, proceed to [Step 2: Create an IAM user and policy \(p. 681\)](#) and follow the instructions there.

## Step 2: Create an IAM user and policy

In this step, you create an AWS Identity and Access Management (IAM) user with a policy that grants access to your Amazon DynamoDB Accelerator (DAX) cluster and to DynamoDB. You can then run applications that interact with your DAX cluster.

### To create an IAM user and policy

1. Open the IAM console at <https://console.aws.amazon.com/iam/>.
2. In the navigation pane, choose **Users**.
3. Choose **Add user**.
4. On the **Details** page, enter the following information:
  - **User name**—Enter a unique name, for example: **MyDAXUser**.
  - **Access type**—Choose **Programmatic access**.

Choose **Next: Permissions**.

5. On the **Set permissions** page, choose **Attach existing policies directly**, and then choose **Create policy**.
6. On the **Create policy** page, choose **Create Your Own Policy**.
7. On the **Review policy** page, provide the following information:
  - **Policy Name**—Enter a unique name, for example, **MyDAXUserPolicy**.
  - **Description**—Enter a short description for the policy.
  - **Policy Document**—Copy and paste the following document.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Action": [  
                "dax:*"  
            ],  
            "Effect": "Allow",  
            "Resource": [  
                "*"  
            ]  
        },  
        {  
            "Action": [  
                "dynamodb:*"  
            ],  
            "Effect": "Allow",  
            "Resource": [  
                "*"  
            ]  
        }  
    ]  
}
```

Choose **Create policy**.

8. Return to the **Permissions** page. In the list of policies, choose **Refresh**.
9. To narrow the list of policies, choose **Filter, Customer managed**. Choose the IAM policy that you created in the previous step (for example: **MyDAXUserPolicy**), and then choose **Next: Review**.

10. On the **Review** page, choose **Create user**.
11. On the **Complete** page, go to the **Secret access key** and choose **Show**. After you do this, copy both the **Access key ID** and **Secret access key**. You need both of these identifiers for [Step 3: Configure an Amazon EC2 instance \(p. 682\)](#).

## Step 3: Configure an Amazon EC2 instance

When your Amazon EC2 instance is available, you can log in to the instance and prepare it for use.

### Note

The following steps assume that you are connecting to your Amazon EC2 instance from a computer running Linux. For other ways to connect, see [Connect to Your Linux Instance](#) in the *Amazon EC2 User Guide for Linux Instances*.

### To configure the EC2 instance

1. Open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.
2. Use the `ssh` command to log in to your Amazon EC2 instance, as shown in the following example.

```
ssh -i my-keypair.pem ec2-user@public-dns-name
```

You need to specify your private key file (`.pem` file) and the public DNS name of your instance. (See [Step 1: Launch an Amazon EC2 instance \(p. 679\)](#).)

The login ID is `ec2-user`. No password is required.

3. After you log in to your EC2 instance, configure your AWS credentials as shown following. Enter your AWS access key ID and secret key (from [Step 2: Create an IAM user and policy \(p. 681\)](#)), and set the default Region name to your current Region. (In the following example, the default Region name is `us-west-2`.)

```
aws configure

AWS Access Key ID [None]: AKIAIOSFODNN7EXAMPLE
AWS Secret Access Key [None]: wJalrXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY
Default region name [None]: us-west-2
Default output format [None]:
```

After launching and configuring your Amazon EC2 instance, you can test the functionality of DAX using one of the available sample applications. For more information, see [Step 4: Run a sample application \(p. 682\)](#).

## Step 4: Run a sample application

To help you test Amazon DynamoDB Accelerator (DAX) functionality, you can run one of the available sample applications on your Amazon EC2 instance.

### Topics

- [DAX SDK for Go \(p. 683\)](#)
- [Java and DAX \(p. 684\)](#)
- [.NET and DAX \(p. 689\)](#)
- [Node.js and DAX \(p. 697\)](#)
- [Python and DAX \(p. 705\)](#)

## DAX SDK for Go

Follow this procedure to run the Amazon DynamoDB Accelerator (DAX) SDK for Go sample application on your Amazon EC2 instance.

### To run the SDK for Go sample for DAX

1. Set up the SDK for Go on your Amazon EC2 instance:

- a. Install the Go programming language (Golang).

```
sudo yum install -y golang
```

- b. Test that Golang is installed and running correctly.

```
go version
```

A message like this should appear.

```
go version go1.15.5 linux/amd64
```

The remaining instructions rely on module support, which became the default with Go version 1.13.

2. Install the sample Golang application.

```
go get github.com/aws-samples/aws-dax-go-sample
```

3. Run the following Golang programs. The first program creates a DynamoDB table named TryDaxGoTable. The second program writes data to the table.

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go -service dynamodb -command create-table
```

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go -service dynamodb -command put-item
```

4. Run the following Golang programs.

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go -service dynamodb -command get-item
```

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go -service dynamodb -command query
```

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go -service dynamodb -command scan
```

Take note of the timing information—the number of milliseconds required for the GetItem, Query, and Scan tests.

5. In the previous step, you ran the programs against the DynamoDB endpoint. Now, run the programs again, but this time, the GetItem, Query, and Scan operations are processed by your DAX cluster.

To determine the endpoint for your DAX cluster, choose one of the following:

API Version 2012-08-10

- **Using the DynamoDB console** — Choose your DAX cluster. The cluster endpoint is shown on the console, as in the following example.

```
dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

- **Using the AWS CLI** — Enter the following command.

```
aws dax describe-clusters --query "Clusters[*].ClusterDiscoveryEndpoint"
```

The cluster endpoint is shown in the output, as in the following example.

```
{  
    "Address": "my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com",  
    "Port": 8111,  
    "URL": "dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com"  
}
```

Now run the programs again, but this time, specify the cluster endpoint as a command line parameter.

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go  
-service dax -command get-item -endpoint my-cluster.16fzcv.dax-clusters.us-  
east-1.amazonaws.com:8111
```

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go  
-service dax -command query -endpoint my-cluster.16fzcv.dax-clusters.us-  
east-1.amazonaws.com:8111
```

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go  
-service dax -command scan -endpoint my-cluster.16fzcv.dax-clusters.us-  
east-1.amazonaws.com:8111
```

Look at the rest of the output, and take note of the timing information. The elapsed times for `GetItem`, `Query`, and `Scan` should be significantly lower with DAX than with DynamoDB.

6. Run the following Golang program to delete `TryDaxGoTable`.

```
go run ~/go/pkg/mod/github.com/aws-samples/aws-dax-go-sample@v1.0.2/try_dax.go -service  
dynamodb -command delete-table
```

## Java and DAX

DAX SDK for Java 2.x is compatible with [AWS SDK for Java 2.x](#). It's built on top of Java 8+ and includes support for non-blocking I/O. For information about using DAX with AWS SDK for Java 1.x, see [Using DAX with AWS SDK for Java 1.x \(p. 1399\)](#)

### Using the client as a Maven dependency

Follow these steps to use the client for the DAX SDK for Java in your application as a dependency.

1. Download and install Apache Maven. For more information, see [Downloading Apache Maven](#) and [Installing Apache Maven](#).

2. Add the client Maven dependency to your application's Project Object Model (POM) file. In this example, replace `x.x.x` with the actual version number of the client.

```
<!--Dependency:-->
<dependencies>
    <dependency>
        <groupId>software.amazon.dax</groupId>
        <artifactId>amazon-dax-client</artifactId>
        <version>x.x.x</version>
    </dependency>
</dependencies>
```

### TryDax sample code

After you've set up your workspace and added the DAX SDK as a dependency, copy [TryDax.java \(p. 686\)](#) into your project.

Run the code using this command.

```
java -cp classpath TryDax
```

You should see output similar to the following.

```
Creating a DynamoDB client

Attempting to create table; please wait...
Successfully created table. Table status: ACTIVE
Writing data to the table...
Writing 10 items for partition key: 1
Writing 10 items for partition key: 2
Writing 10 items for partition key: 3
...
Running GetItem and Query tests...
First iteration of each test will result in cache misses
Next iterations are cache hits

GetItem test - partition key 1-100 and sort keys 1-10
    Total time: 4390.240 ms - Avg time: 4.390 ms
    Total time: 3097.089 ms - Avg time: 3.097 ms
    Total time: 3273.463 ms - Avg time: 3.273 ms
    Total time: 3353.739 ms - Avg time: 3.354 ms
    Total time: 3533.314 ms - Avg time: 3.533 ms
Query test - partition key 1-100 and sort keys between 2 and 9
    Total time: 475.868 ms - Avg time: 4.759 ms
    Total time: 423.333 ms - Avg time: 4.233 ms
    Total time: 460.271 ms - Avg time: 4.603 ms
    Total time: 397.859 ms - Avg time: 3.979 ms
    Total time: 466.644 ms - Avg time: 4.666 ms

Attempting to delete table; please wait...
Successfully deleted table.
```

Take note of the timing information—the number of milliseconds required for the `GetItem` and `Query` tests. In this case, you ran the program against the DynamoDB endpoint. Now you'll run the program again, this time against your DAX cluster.

To determine the endpoint of your DAX cluster, choose one of the following:

- In the DynamoDB console, select your DAX cluster. The cluster endpoint is shown in the console, as in the following example.

```
dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

- Using the AWS CLI, enter the following command:

```
aws dax describe-clusters --query "Clusters[*].ClusterDiscoveryEndpoint"
```

The cluster endpoint address, port, and URL are shown in the output, as in the following example.

```
{  
    "Address": "my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com",  
    "Port": 8111,  
    "URL": "dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com"  
}
```

Now run the program again, but this time, specify the cluster endpoint URL as a command line parameter.

```
java -cp classpath TryDax dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

Look at the output and take note of the timing information. The elapsed times for `GetItem` and `Query` should be significantly lower with DAX than with DynamoDB.

## SDK metrics

With DAX SDK for Java 2.x, you can collect metrics about the service clients in your application and analyze the output in Amazon CloudWatch. See [Enabling SDK metrics](#) for more information.

### Note

The DAX SDK for Java only collects `ApiCallSuccessful` and `ApiCallDuration` metrics.

## TryDax.java

```
import java.util.Map;  
  
import software.amazon.awssdk.services.dynamodb.DynamoDbAsyncClient;  
import software.amazon.awssdk.services.dynamodb.model.AttributeDefinition;  
import software.amazon.awssdk.services.dynamodb.model.AttributeValue;  
import software.amazon.awssdk.services.dynamodb.model.BillingMode;  
import software.amazon.awssdk.services.dynamodb.model.CreateTableRequest;  
import software.amazon.awssdk.services.dynamodb.model.DeleteTableRequest;  
import software.amazon.awssdk.services.dynamodb.model.DescribeTableRequest;  
import software.amazon.awssdk.services.dynamodb.model.GetItemRequest;  
import software.amazon.awssdk.services.dynamodb.model.KeySchemaElement;  
import software.amazon.awssdk.services.dynamodb.model.KeyType;  
import software.amazon.awssdk.services.dynamodb.model.PutItemRequest;  
import software.amazon.awssdk.services.dynamodb.model.QueryRequest;  
import software.amazon.awssdk.services.dynamodb.model.ScalarAttributeType;  
import software.amazon.dax.ClusterDaxAsyncClient;  
import software.amazon.dax.Configuration;  
  
public class TryDax {  
    public static void main(String[] args) throws Exception {  
        DynamoDbAsyncClient ddbClient = DynamoDbAsyncClient.builder()  
            .build();  
  
        DynamoDbAsyncClient daxClient = null;  
        if (args.length >= 1) {  
            daxClient = ClusterDaxAsyncClient.builder()
```

```

        .overrideConfiguration(Configuration.builder()
            .url(args[0]) // e.g. dax://my-cluster.16fzcv.dax-clusters.us-
east-1.amazonaws.com
            .build())
        .build();
    }

    String tableName = "TryDaxTable";

    System.out.println("Creating table...");
    createTable(tableName, ddbClient);

    System.out.println("Populating table...");
    writeData(tableName, ddbClient, 100, 10);

    DynamoDbAsyncClient testClient = null;
    if (daxClient != null) {
        testClient = daxClient;
    } else {
        testClient = ddbClient;
    }

    System.out.println("Running GetItem and Query tests...");
    System.out.println("First iteration of each test will result in cache misses");
    System.out.println("Next iterations are cache hits\n");

    // GetItem
    getItemTest(tableName, testClient, 100, 10, 5);

    // Query
    queryTest(tableName, testClient, 100, 2, 9, 5);

    System.out.println("Deleting table...");
    deleteTable(tableName, ddbClient);
}

private static void createTable(String tableName, DynamoDbAsyncClient client) {
    try {
        System.out.println("Attempting to create table; please wait...");

        client.createTable(CreateTableRequest.builder()
            .tableName(tableName)
            .keySchema(KeySchemaElement.builder()
                .keyType(KeyType.HASH)
                .attributeName("pk")
                .build(), KeySchemaElement.builder()
                .keyType(KeyType.RANGE)
                .attributeName("sk")
                .build())
            .attributeDefinitions(AttributeDefinition.builder()
                .attributeName("pk")
                .attributeType(ScalarAttributeType.N)
                .build(), AttributeDefinition.builder()
                .attributeName("sk")
                .attributeType(ScalarAttributeType.N)
                .build())
            .billingMode(BillingMode.PAY_PER_REQUEST)
            .build()).get();
        client.waiter().waitUntilTableExists(DescribeTableRequest.builder()
            .tableName(tableName)
            .build()).get();
        System.out.println("Successfully created table.");
    } catch (Exception e) {
        System.err.println("Unable to create table: ");
        e.printStackTrace();
    }
}

```

```

        }

    }

    private static void deleteTable(String tableName, DynamoDbAsyncClient client) {
        try {
            System.out.println("\nAttempting to delete table; please wait...");
            client.deleteTable(DeleteTableRequest.builder()
                .tableName(tableName)
                .build()).get();
            client.waiter().waitUntilTableNotExists(DescribeTableRequest.builder()
                .tableName(tableName)
                .build()).get();
            System.out.println("Successfully deleted table.");
        } catch (Exception e) {
            System.err.println("Unable to delete table: ");
            e.printStackTrace();
        }
    }

    private static void writeData(String tableName, DynamoDbAsyncClient client, int pkmax,
int skmax) {
        System.out.println("Writing data to the table...");

        int stringSize = 1000;
        StringBuilder sb = new StringBuilder(stringSize);
        for (int i = 0; i < stringSize; i++) {
            sb.append('X');
        }
        String someData = sb.toString();

        try {
            for (int ipk = 1; ipk <= pkmax; ipk++) {
                System.out.println(("Writing " + skmax + " items for partition key: " +
ipk));
                for (int isk = 1; isk <= skmax; isk++) {
                    client.putItem(PutItemRequest.builder()
                        .tableName(tableName)
                        .item(Map.of("pk", attr(ipk), "sk", attr(isk), "someData",
attr(someData)))
                        .build()).get();
                }
            }
        } catch (Exception e) {
            System.err.println("Unable to write item:");
            e.printStackTrace();
        }
    }

    private static AttributeValue attr(int n) {
        return AttributeValue.builder().n(String.valueOf(n)).build();
    }

    private static AttributeValue attr(String s) {
        return AttributeValue.builder().s(s).build();
    }

    private static void getItemTest(String tableName, DynamoDbAsyncClient client, int pk,
int sk, int iterations) {
        long startTime, endTime;
        System.out.println("GetItem test - partition key 1-" + pk + " and sort keys 1-" +
sk);

        for (int i = 0; i < iterations; i++) {
            startTime = System.nanoTime();
            try {

```

```

        for (int ipk = 1; ipk <= pk; ipk++) {
            for (int isk = 1; isk <= sk; isk++) {
                client.getItem(GetItemRequest.builder()
                    .tableName(tableName)
                    .key(Map.of("pk", attr(ipk), "sk", attr(isk)))
                    .build()).get();
            }
        }
    } catch (Exception e) {
        System.err.println("Unable to get item:");
        e.printStackTrace();
    }
endTime = System.nanoTime();
printTime(startTime, endTime, pk * sk);
}
}

private static void queryTest(String tableName, DynamoDbAsyncClient client, int pk, int sk1, int sk2, int iterations) {
    long startTime, endTime;
    System.out.println("Query test - partition key 1-" + pk + " and sort keys between " +
+ sk1 + " and " + sk2);

    for (int i = 0; i < iterations; i++) {
        startTime = System.nanoTime();
        for (int ipk = 1; ipk <= pk; ipk++) {
            try {
                // Pagination API for Query.
                client.queryPaginator(QueryRequest.builder()
                    .tableName(tableName)
                    .keyConditionExpression("pk = :pkval and sk between :skval1
and :skval2")
                    .expressionAttributeValues(Map.of(":pkval", attr(ipk),
":skval1", attr(sk1), ":skval2", attr(sk2)))
                    .build()).items().subscribe((item) -> {
                        }).get();
            } catch (Exception e) {
                System.err.println("Unable to query table:");
                e.printStackTrace();
            }
        }
        endTime = System.nanoTime();
        printTime(startTime, endTime, pk);
    }
}

private static void printTime(long startTime, long endTime, int iterations) {
    System.out.format("\tTotal time: %.3f ms - ", (endTime - startTime) / (1000000.0));
    System.out.format("Avg time: %.3f ms\n", (endTime - startTime) / (iterations *
1000000.0));
}
}

```

## .NET and DAX

Follow these steps to run the .NET sample on your Amazon EC2 instance.

### Note

This tutorial uses the .NET 6 SDK, but will work with the .NET Core SDK also. It shows how you can run a program in your default Amazon VPC to access your Amazon DynamoDB Accelerator (DAX) cluster. If you prefer, you can use the AWS Toolkit for Visual Studio to write a .NET application and deploy it into your VPC.

For more information, see [Creating and Deploying Elastic Beanstalk Applications in .NET Using AWS Toolkit for Visual Studio](#) in the [AWS Elastic Beanstalk Developer Guide](#).

## To run the .NET sample for DAX

1. Go to the [Microsoft Downloads page](#) and download the latest .NET 6 (or .NET Core) SDK for Linux. The downloaded file is `dotnet-sdk-N.N.N-linux-x64.tar.gz`.
2. Extract the SDK files.

```
mkdir dotnet
tar zxvf dotnet-sdk-N.N.N-linux-x64.tar.gz -C dotnet
```

Replace `N.N.N` with the actual version number of the .NET SDK (for example: `6.0.100`).

3. Verify the installation.

```
alias dotnet=$HOME/dotnet/dotnet
dotnet --version
```

This should print the version number of the .NET SDK.

**Note**

Instead of the version number, you might receive the following error:  
`error: libunwind.so.8: cannot open shared object file: No such file or directory`  
To resolve the error, install the `libunwind` package.

```
sudo yum install -y libunwind
```

After you do this, you should be able to run the `dotnet --version` command without any errors.

4. Create a new .NET project.

```
dotnet new console -o myApp
```

This requires a few minutes to perform a one-time-only setup. When it is complete, run the sample project.

```
dotnet run --project myApp
```

You should receive the following message: `Hello World!`

5. The `myApp/myApp.csproj` file contains metadata about your project. To use the DAX client in your application, modify the file so that it looks like the following.

```
<Project Sdk="Microsoft.NET.Sdk">
  <PropertyGroup>
    <OutputType>Exe</OutputType>
    <TargetFramework>net6.0</TargetFramework>
  </PropertyGroup>
  <ItemGroup>
    <PackageReference Include="AWSSDK.DAX.Client" Version="*" />
  </ItemGroup>
</Project>
```

6. Download the sample program source code (.zip file).

```
wget http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/samples/TryDax.zip
```

---

When the download is complete, extract the source files.

API Version 2012-08-10

```
unzip TryDax.zip
```

7. Now run the sample programs, one at a time. For each program, copy its contents into the `myApp/Program.cs`, and then run the `MyApp` project.

Run the following .NET programs. The first program creates a DynamoDB table named `TryDaxTable`. The second program writes data to the table.

```
cp TryDax/dotNet/01-CreateTable.cs myApp/Program.cs
dotnet run --project MyApp

cp TryDax/dotNet/02-Write-Data.cs myApp/Program.cs
dotnet run --project MyApp
```

8. Next, run some programs to perform `GetItem`, `Query`, and `Scan` operations on your DAX cluster. To determine the endpoint for your DAX cluster, choose one of the following:

- **Using the DynamoDB console** — Choose your DAX cluster. The cluster endpoint is shown on the console, as in the following example.

```
dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

- **Using the AWS CLI** — Enter the following command.

```
aws dax describe-clusters --query "Clusters[*].ClusterDiscoveryEndpoint"
```

The cluster endpoint is shown in the output, as in the following example.

```
{
    "Address": "my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com",
    "Port": 8111,
    "URL": "dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com"
}
```

Now run the following programs, specifying your cluster endpoint as a command line parameter. (Replace the sample endpoint with your actual DAX cluster endpoint.)

```
cp TryDax/dotNet/03-GetItem-Test.cs myApp/Program.cs
dotnet run --project MyApp dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com

cp TryDax/dotNet/04-Query-Test.cs myApp/Program.cs
dotnet run --project MyApp dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com

cp TryDax/dotNet/05-Scan-Test.cs myApp/Program.cs
dotnet run --project MyApp dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

Take note of the timing information—the number of milliseconds required for the `GetItem`, `Query`, and `Scan` tests.

9. Run the following .NET program to delete `TryDaxTable`.

```
cp TryDax/dotNet/06-DeleteTable.cs myApp/Program.cs
dotnet run --project MyApp
```

For more information about these programs, see the following sections:

- [01-CreateTable.cs \(p. 692\)](#)
- [02-Write-Data.cs \(p. 693\)](#)
- [03-GetItem-Test.cs \(p. 693\)](#)
- [04-Query-Test.cs \(p. 694\)](#)
- [05-Scan-Test.cs \(p. 696\)](#)
- [06>DeleteTable.cs \(p. 696\)](#)

### 01-CreateTable.cs

The 01-CreateTable.cs program creates a table (TryDaxTable). The remaining .NET programs in this section depend on this table.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.Model;

namespace ClientTest
{
    class Program
    {
        public static async Task Main(string[] args)
        {
            AmazonDynamoDBClient client = new AmazonDynamoDBClient();

            var tableName = "TryDaxTable";

            var request = new CreateTableRequest()
            {
                TableName = tableName,
                KeySchema = new List<KeySchemaElement>()
                {
                    new KeySchemaElement{ AttributeName = "pk",KeyType = "HASH" },
                    new KeySchemaElement{ AttributeName = "sk",KeyType = "RANGE" }
                },
                AttributeDefinitions = new List<AttributeDefinition>()
                {
                    new AttributeDefinition{ AttributeName = "pk",AttributeType = "N" },
                    new AttributeDefinition{ AttributeName = "sk",AttributeType = "N" }
                },
                ProvisionedThroughput = new ProvisionedThroughput()
                {
                    ReadCapacityUnits = 10,
                    WriteCapacityUnits = 10
                }
            };

            var response = await client.CreateTableAsync(request);

            Console.WriteLine("Hit <enter> to continue...");
            Console.ReadLine();
        }
    }
}
```

## 02-Write-Data.cs

The 02-Write-Data.cs program writes test data to TryDaxTable.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.  
// SPDX-License-Identifier: Apache-2.0  
  
using System;  
using System.Collections.Generic;  
using System.Threading.Tasks;  
using Amazon.DynamoDBv2;  
using Amazon.DynamoDBv2.Model;  
  
namespace ClientTest  
{  
    class Program  
    {  
        public static async Task Main(string[] args)  
        {  
            AmazonDynamoDBClient client = new AmazonDynamoDBClient();  
  
            var tableName = "TryDaxTable";  
  
            string someData = new string('X', 1000);  
            var pkmax = 10;  
            var skmax = 10;  
  
            for (var ipk = 1; ipk <= pkmax; ipk++)  
            {  
                Console.WriteLine($"Writing {skmax} items for partition key: {ipk}");  
                for (var isk = 1; isk <= skmax; isk++)  
                {  
                    var request = new PutItemRequest()  
                    {  
                        TableName = tableName,  
                        Item = new Dictionary<string, AttributeValue>()  
                        {  
                            { "pk", new AttributeValue{N = ipk.ToString()} },  
                            { "sk", new AttributeValue{N = isk.ToString()} },  
                            { "someData", new AttributeValue{S = someData} }  
                        };  
                    };  
                    var response = await client.PutItemAsync(request);  
                }  
            }  
  
            Console.WriteLine("Hit <enter> to continue...");  
            Console.ReadLine();  
        }  
    }  
}
```

## 03-GetItem-Test.cs

The 03-GetItem-Test.cs program performs GetItem operations on TryDaxTable.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.  
// SPDX-License-Identifier: Apache-2.0  
  
using System;
```

```
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.DAX;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;

namespace ClientTest
{
    class Program
    {
        public static async Task Main(string[] args)
        {
            string endpointUri = args[0];
            Console.WriteLine($"Using DAX client - endpointUri={endpointUri}");

            var clientConfig = new DaxClientConfig(endpointUri)
            {
                AwsCredentials = FallbackCredentialsFactory.GetCredentials()
            };
            var client = new ClusterDaxClient(clientConfig);

            var tableName = "TryDaxTable";

            var pk = 1;
            var sk = 10;
            var iterations = 5;

            var startTime = System.DateTime.Now;

            for (var i = 0; i < iterations; i++)
            {
                for (var ipk = 1; ipk <= pk; ipk++)
                {
                    for (var isk = 1; isk <= sk; isk++)
                    {
                        var request = new GetItemRequest()
                        {
                            TableName = tableName,
                            Key = new Dictionary<string, AttributeValue>()
                            {{"pk", new AttributeValue {N = ipk.ToString()}}, {"sk", new AttributeValue {N = isk.ToString()} } }
                        };
                        var response = await client.GetItemAsync(request);
                        Console.WriteLine($"GetItem succeeded for pk: {ipk},sk: {isk}");
                    }
                }
            }

            var endTime = DateTime.Now;
            TimeSpan timeSpan = endTime - startTime;
            Console.WriteLine($"Total time: {timeSpan.TotalMilliseconds} milliseconds");

            Console.WriteLine("Hit <enter> to continue...");
            Console.ReadLine();
        }
    }
}
```

#### 04-Query-Test.cs

The 04-Query-Test.cs program performs Query operations on TryDaxTable.

```

// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
// SPDX-License-Identifier: Apache-2.0

using System;
using System.Collections.Generic;
using System.Threading.Tasks;
using Amazon.Runtime;
using Amazon.DAX;
using Amazon.DynamoDBv2.Model;

namespace ClientTest
{
    class Program
    {
        public static async Task Main(string[] args)
        {
            string endpointUri = args[0];
            Console.WriteLine($"Using DAX client - endpointUri={endpointUri}");

            var clientConfig = new DaxClientConfig(endpointUri)
            {
                AwsCredentials = FallbackCredentialsFactory.GetCredentials()
            };
            var client = new ClusterDaxClient(clientConfig);

            var tableName = "TryDaxTable";

            var pk = 5;
            var sk1 = 2;
            var sk2 = 9;
            var iterations = 5;

            var startTime = DateTime.Now;

            for (var i = 0; i < iterations; i++)
            {
                var request = new QueryRequest()
                {
                    TableName = tableName,
                    KeyConditionExpression = "pk = :pkval and sk between :skval1
and :skval2",
                    ExpressionAttributeValues = new Dictionary<string, AttributeValue>() {
                        {"":pkval", new AttributeValue {N = pk.ToString()} },
                        {"":skval1", new AttributeValue {N = sk1.ToString()} },
                        {"":skval2", new AttributeValue {N = sk2.ToString()} }
                    }
                };
                var response = await client.QueryAsync(request);
                Console.WriteLine($"{i}: Query succeeded");
            }

            var endTime = DateTime.Now;
            TimeSpan timeSpan = endTime - startTime;
            Console.WriteLine($"Total time: {timeSpan.TotalMilliseconds} milliseconds");

            Console.WriteLine("Hit <enter> to continue...");
            Console.ReadLine();
        }
    }
}

```

## 05-Scan-Test.cs

The 05-Scan-Test.cs program performs Scan operations on TryDaxTable.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.  
// SPDX-License-Identifier: Apache-2.0  
  
using System;  
using System.Threading.Tasks;  
using Amazon.Runtime;  
using Amazon.DAX;  
using Amazon.DynamoDBv2.Model;  
  
namespace ClientTest  
{  
    class Program  
    {  
        public static async Task Main(string[] args)  
        {  
            string endpointUri = args[0];  
            Console.WriteLine($"Using DAX client - endpointUri={endpointUri}");  
  
            var clientConfig = new DaxClientConfig(endpointUri)  
            {  
                AwsCredentials = FallbackCredentialsFactory.GetCredentials()  
            };  
            var client = new ClusterDaxClient(clientConfig);  
  
            var tableName = "TryDaxTable";  
  
            var iterations = 5;  
  
            var startTime = DateTime.Now;  
  
            for (var i = 0; i < iterations; i++)  
            {  
                var request = new ScanRequest()  
                {  
                    TableName = tableName  
                };  
                var response = await client.ScanAsync(request);  
                Console.WriteLine($"{i}: Scan succeeded");  
            }  
  
            var endTime = DateTime.Now;  
            TimeSpan timeSpan = endTime - startTime;  
            Console.WriteLine($"Total time: {timeSpan.TotalMilliseconds} milliseconds");  
  
            Console.WriteLine("Hit <enter> to continue...");  
            Console.ReadLine();  
        }  
    }  
}
```

## 06-DeleteTable.cs

The 06-DeleteTable.cs program deletes TryDaxTable. Run this program after you have finished testing.

```
// Copyright Amazon.com, Inc. or its affiliates. All Rights Reserved.
```

```
// SPDX-License-Identifier: Apache-2.0

using System;
using System.Threading.Tasks;
using Amazon.DynamoDBv2.Model;
using Amazon.DynamoDBv2;

namespace ClientTest
{
    class Program
    {
        public static async Task Main(string[] args)
        {
            AmazonDynamoDBClient client = new AmazonDynamoDBClient();

            var tableName = "TryDaxTable";

            var request = new DeleteTableRequest()
            {
                TableName = tableName
            };

            var response = await client.DeleteTableAsync(request);

            Console.WriteLine("Hit <enter> to continue...");
            Console.ReadLine();
        }
    }
}
```

## Node.js and DAX

Follow these steps to run the Node.js sample application on your Amazon EC2 instance.

### To run the Node.js sample for DAX

1. Set up Node.js on your Amazon EC2 instance, as follows:

- a. Install node version manager (nvm).

```
curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.35.3/install.sh | bash
```

- b. Use nvm to install Node.js.

```
nvm install 12.16.3
```

- c. Test that Node.js is installed and running correctly.

```
node -e "console.log('Running Node.js ' + process.version)"
```

This should display the following message.

```
Running Node.js v12.16.3
```

2. Install the DAX Node.js client using the node package manager (npm).

```
npm install amazon-dax-client
```

3. Download the sample program source code (.zip file).

```
wget http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/samples/TryDax.zip
```

When the download is complete, extract the source files.

```
unzip TryDax.zip
```

4. Run the following Node.js programs. The first program creates an Amazon DynamoDB table named TryDaxTable. The second program writes data to the table.

```
node 01-create-table.js  
node 02-write-data.js
```

5. Run the following Node.js programs.

```
node 03-getitem-test.js  
node 04-query-test.js  
node 05-scan-test.js
```

Take note of the timing information—the number of milliseconds required for the GetItem, Query, and Scan tests.

6. In the previous step, you ran the programs against the DynamoDB endpoint. Run the programs again, but this time, the GetItem, Query and Scan operations are processed by your DAX cluster.

To determine the endpoint for your DAX cluster, choose one of the following.

- **Using the DynamoDB console**—Choose your DAX cluster. The cluster endpoint is shown on the console, as in the following example.

```
dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

- **Using the AWS CLI**—Enter the following command.

```
aws dax describe-clusters --query "Clusters[*].ClusterDiscoveryEndpoint"
```

The cluster endpoint is shown in the output, as in the following example.

```
{  
    "Address": "my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com",  
    "Port": 8111,  
    "URL": "dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com"  
}
```

Now run the programs again, but this time, specify the cluster endpoint as a command line parameter.

```
node 03-getitem-test.js dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com  
node 04-query-test.js dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com  
node 05-scan-test.js dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

Look at the rest of the output, and take note of the timing information. The elapsed times for GetItem, Query, and Scan should be significantly lower with DAX than with DynamoDB.

7. Run the following Node.js program to delete TryDaxTable.

```
node 06-delete-table
```

For more information about these programs, see the following sections:

- [01-create-table.js \(p. 699\)](#)
- [02-write-data.js \(p. 700\)](#)
- [03-getitem-test.js \(p. 701\)](#)
- [04-query-test.js \(p. 702\)](#)
- [05-scan-test.js \(p. 703\)](#)
- [06-delete-table.js \(p. 704\)](#)

### 01-create-table.js

The `01-create-table.js` program creates a table (`TryDaxTable`). The remaining Node.js programs in this section depend on this table.

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
const AmazonDaxClient = require('amazon-dax-client');  
var AWS = require("aws-sdk");  
  
var region = "us-west-2";  
  
AWS.config.update({  
    region: region  
});  
  
var dynamodb = new AWS.DynamoDB() //low-level client  
  
var tableName = "TryDaxTable";  
  
var params = {  
    TableName : tableName,  
    KeySchema: [  
        { AttributeName: "pk", KeyType: "HASH"}, //Partition key  
        { AttributeName: "sk", KeyType: "RANGE" } //Sort key  
    ],  
    AttributeDefinitions: [  
        { AttributeName: "pk", AttributeType: "N" },  
        { AttributeName: "sk", AttributeType: "N" }  
    ],  
    ProvisionedThroughput: {  
        ReadCapacityUnits: 10,  
        WriteCapacityUnits: 10  
    }  
};
```

```
dynamodb.createTable(params, function(err, data) {
    if (err) {
        console.error("Unable to create table. Error JSON:", JSON.stringify(err, null, 2));
    } else {
        console.log("Created table. Table description JSON:", JSON.stringify(data, null,
2));
    }
});
```

## 02-write-data.js

The 02-write-data.js program writes test data to TryDaxTable.

```
/** 
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
*/
const AmazonDaxClient = require('amazon-dax-client');
var AWS = require("aws-sdk");

var region = "us-west-2";

AWS.config.update({
    region: region
});

var ddbClient = new AWS.DynamoDB.DocumentClient()

var tableName = "TryDaxTable";

var someData = "X".repeat(1000);
var pkmax = 10;
var skmax = 10;

for (var ipk = 1; ipk <= pkmax; ipk++)  {

    for (var isk = 1; isk <= skmax; isk++) {
        var params = {
            TableName: tableName,
            Item: {
                "pk": ipk,
                "sk": isk,
                "someData": someData
            }
        };
        // 
        //put item

        ddbClient.put(params, function(err, data) {
            if (err) {
                console.error("Unable to write data: ", JSON.stringify(err, null, 2));
            }
        });
    }
}
```

```
        } else {
            console.log("PutItem succeeded");
        }
    });
}

}
```

### 03-getitem-test.js

The 03-getitem-test.js program performs GetItem operations on TryDaxTable.

```
/*
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
const AmazonDaxClient = require('amazon-dax-client');
var AWS = require("aws-sdk");

var region = "us-west-2";

AWS.config.update({
    region: region
});

var ddbClient = new AWS.DynamoDB.DocumentClient()
var daxClient = null;

if (process.argv.length > 2) {
    var dax = new AmazonDaxClient({endpoints: [process.argv[2]], region: region})
    daxClient = new AWS.DynamoDB.DocumentClient({service: dax });
}

var client = daxClient != null ? daxClient : ddbClient;
var tableName = "TryDaxTable";

var pk = 1;
var sk = 10;
var iterations = 5;

for (var i = 0; i < iterations; i++) {

    var startTime = new Date().getTime();

    for (var ipk = 1; ipk <= pk; ipk++) {
        for (var isk = 1; isk <= sk; isk++) {

            var params = {
                TableName: tableName,
                Key:{

                    "pk": ipk,
                    "sk": isk
                }
            }
        }
    }
}
```

```

    };

    client.get(params, function(err, data) {
        if (err) {
            console.error("Unable to read item. Error JSON:", JSON.stringify(err,
null, 2));
        } else {
            // GetItem succeeded
        }
    });
}

var endTime = new Date().getTime();
console.log("\tTotal time: ", (endTime - startTime) , "ms - Avg time: ", (endTime -
startTime) / iterations, "ms");

}

```

#### [04-query-test.js](#)

The 04-query-test.js program performs Query operations on TryDaxTable.

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
const AmazonDaxClient = require('amazon-dax-client');
var AWS = require("aws-sdk");

var region = "us-west-2";

AWS.config.update({
    region: region
});

var ddbClient = new AWS.DynamoDB.DocumentClient()
var daxClient = null;

if (process.argv.length > 2) {
    var dax = new AmazonDaxClient({endpoints: [process.argv[2]], region: region})
    daxClient = new AWS.DynamoDB.DocumentClient({service: dax });
}

var client = daxClient != null ? daxClient : ddbClient;
var tableName = "TryDaxTable";

var pk = 5;
var sk1 = 2;
var sk2 = 9;
var iterations = 5;

var params = {

```

```

TableName: tableName,
KeyConditionExpression: "pk = :pkval and sk between :skval1 and :skval2",
ExpressionAttributeValues: {
    ":pkval":pk,
    ":skval1":sk1,
    ":skval2":sk2
}
};

for (var i = 0; i < iterations; i++) {
    var startTime = new Date().getTime();

    client.query(params, function(err, data) {
        if (err) {
            console.error("Unable to read item. Error JSON:", JSON.stringify(err, null,
2));
        } else {
            // Query succeeded
        }
    });
}

var endTime = new Date().getTime();
console.log("\tTotal time: ", (endTime - startTime) , "ms - Avg time: ", (endTime -
startTime) / iterations, "ms");

}

```

### 05-scan-test.js

The 05-scan-test.js program performs Scan operations on TryDaxTable.

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
const AmazonDaxClient = require('amazon-dax-client');
var AWS = require("aws-sdk");

var region = "us-west-2";

AWS.config.update({
    region: region
});

var ddbClient = new AWS.DynamoDB.DocumentClient()
var daxClient = null;

if (process.argv.length > 2) {
    var dax = new AmazonDaxClient({endpoints: [process.argv[2]], region: region})
    daxClient = new AWS.DynamoDB.DocumentClient({service: dax });
}

var client = daxClient != null ? daxClient : ddbClient;

```

```
var tableName = "TryDaxTable";

var iterations = 5;

var params = {
    TableName: tableName
};
var startTime = new Date().getTime();
for (var i = 0; i < iterations; i++) {

    client.scan(params, function(err, data) {
        if (err) {
            console.error("Unable to read item. Error JSON:", JSON.stringify(err, null,
2));
        } else {
            // Scan succeeded
        }
    });
}

var endTime = new Date().getTime();
console.log("\tTotal time: ", (endTime - startTime) , "ms - Avg time: ", (endTime -
startTime) / iterations, "ms");
```

### 06-delete-table.js

The 06-delete-table.js program deletes TryDaxTable. Run this program after you have finished testing.

```
/** 
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
const AmazonDaxClient = require('amazon-dax-client');
var AWS = require("aws-sdk");

var region = "us-west-2";

AWS.config.update({
    region: region
});

var dynamodb = new AWS.DynamoDB(); //low-level client

var tableName = "TryDaxTable";

var params = {
    TableName : tableName
};
```

```
dynamodb.deleteTable(params, function(err, data) {  
    if (err) {  
        console.error("Unable to delete table. Error JSON:", JSON.stringify(err, null, 2));  
    } else {  
        console.log("Deleted table. Table description JSON:", JSON.stringify(data, null,  
2));  
    }  
});
```

## Python and DAX

Follow this procedure to run the Python sample application on your Amazon EC2 instance.

### To run the Python sample for DAX

1. Install the DAX Python client using the pip utility.

```
pip install amazon-dax-client
```

2. Download the sample program source code (.zip file).

```
wget http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/samples/TryDax.zip
```

When the download is complete, extract the source files.

```
unzip TryDax.zip
```

3. Run the following Python programs. The first program creates an Amazon DynamoDB table named TryDaxTable. The second program writes data to the table.

```
python 01-create-table.py  
python 02-write-data.py
```

4. Run the following Python programs.

```
python 03-getitem-test.py  
python 04-query-test.py  
python 05-scan-test.py
```

Take note of the timing information—the number of milliseconds required for the GetItem, Query, and Scan tests.

5. In the previous step, you ran the programs against the DynamoDB endpoint. Now run the programs again, but this time, the GetItem, Query, and Scan operations are processed by your DAX cluster.

To determine the endpoint for your DAX cluster, choose one of the following:

- **Using the DynamoDB console** — Choose your DAX cluster. The cluster endpoint is shown on the console, as in the following example.

```
dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

- **Using the AWS CLI** — Enter the following command.

```
aws dax describe-clusters --query "Clusters[*].ClusterDiscoveryEndpoint"
```

The cluster endpoint is shown in the output, as in this example.

```
{  
    "Address": "my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com",  
    "Port": 8111,  
    "URL": "dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com"  
}
```

Run the programs again, but this time, specify the cluster endpoint as a command line parameter.

```
python 03-getitem-test.py dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com  
python 04-query-test.py dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com  
python 05-scan-test.py dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

Look at the rest of the output, and take note of the timing information. The elapsed times for `GetItem`, `Query`, and `Scan` should be significantly lower with DAX than with DynamoDB.

6. Run the following Python program to delete `TryDaxTable`.

```
python 06-delete-table.py
```

For more information about these programs, see the following sections:

- [01-create-table.py \(p. 706\)](#)
- [02-write-data.py \(p. 707\)](#)
- [03-getitem-test.py \(p. 707\)](#)
- [04-query-test.py \(p. 708\)](#)
- [05-scan-test.py \(p. 710\)](#)
- [06-delete-table.py \(p. 710\)](#)

### [01-create-table.py](#)

The `01-create-table.py` program creates a table (`TryDaxTable`). The remaining Python programs in this section depend on this table.

```
import boto3  
  
def create_dax_table(dyn_resource=None):  
    """  
    Creates a DynamoDB table.  
  
    :param dyn_resource: Either a Boto3 or DAX resource.  
    :return: The newly created table.  
    """  
    if dyn_resource is None:  
        dyn_resource = boto3.resource('dynamodb')  
  
    table_name = 'TryDaxTable'  
    params = {  
        'TableName': table_name,  
        'KeySchema': [  
            {'AttributeName': 'partition_key', 'KeyType': 'HASH'},  
            {'AttributeName': 'sort_key', 'KeyType': 'RANGE'}  
        ],  
        'AttributeDefinitions': [  
            {'AttributeName': 'partition_key', 'AttributeType': 'N'},  
            {'AttributeName': 'sort_key', 'AttributeType': 'S'}  
        ],  
        'ProvisionedThroughput': {  
            'ReadCapacityUnits': 5,  
            'WriteCapacityUnits': 5  
        }  
    }  
  
    table = dynamodb.create_table(**params)  
    return table
```

```

        {'AttributeName': 'sort_key', 'AttributeType': 'N'}
    ],
    'ProvisionedThroughput': {
        'ReadCapacityUnits': 10,
        'WriteCapacityUnits': 10
    }
}
table = dyn_resource.create_table(**params)
print(f"Creating {table_name}...")
table.wait_until_exists()
return table

if __name__ == '__main__':
    dax_table = create_dax_table()
    print(f"Created table.")

```

### [02-write-data.py](#)

The 02-write-data.py program writes test data to TryDaxTable.

```

import boto3

def write_data_to_dax_table(key_count, item_size, dyn_resource=None):
    """
    Writes test data to the demonstration table.

    :param key_count: The number of partition and sort keys to use to populate the
                      table. The total number of items is key_count * key_count.
    :param item_size: The size of non-key data for each test item.
    :param dyn_resource: Either a Boto3 or DAX resource.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    some_data = 'X' * item_size

    for partition_key in range(1, key_count + 1):
        for sort_key in range(1, key_count + 1):
            table.put_item(Item={
                'partition_key': partition_key,
                'sort_key': sort_key,
                'some_data': some_data
            })
        print(f"Put item ({partition_key}, {sort_key}) succeeded.")

    if __name__ == '__main__':
        write_key_count = 10
        write_item_size = 1000
        print(f"Writing {write_key_count}*{write_key_count} items to the table. "
              f"Each item is {write_item_size} characters.")
        write_data_to_dax_table(write_key_count, write_item_size)

```

### [03-getitem-test.py](#)

The 03-getitem-test.py program performs GetItem operations on TryDaxTable. This example is given for the Region eu-west-1.

```
import argparse
```

```

import sys
import time
import amazondax
import boto3

def get_item_test(key_count, iterations, dyn_resource=None):
    """
    Gets items from the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param key_count: The number of items to get from the table in each iteration.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    start = time.perf_counter()
    for _ in range(iterations):
        for partition_key in range(1, key_count + 1):
            for sort_key in range(1, key_count + 1):
                table.get_item(Key={
                    'partition_key': partition_key,
                    'sort_key': sort_key
                })
                print('.', end='')
                sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end

if __name__ == '__main__':
    parser = argparse.ArgumentParser()
    parser.add_argument(
        'endpoint_url', nargs='?',
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not used.")
    args = parser.parse_args()

    test_key_count = 10
    test_iterations = 50
    if args.endpoint_url:
        print(f"Getting each item from the table {test_iterations} times, "
              f"using the DAX client.")
        # Use a with statement so the DAX client closes the cluster after completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args, region_name='eu-west-1') as dax:
            test_start, test_end = get_item_test(
                test_key_count, test_iterations, dyn_resource=dax)
    else:
        print(f"Getting each item from the table {test_iterations} times, "
              f"using the Boto3 client.")
        test_start, test_end = get_item_test(
            test_key_count, test_iterations)
    print(f"Total time: {test_end - test_start:.4f} sec. Average time: "
          f"{{(test_end - test_start)/ test_iterations}}")

```

## 04-query-test.py

The 04-query-test.py program performs Query operations on TryDaxTable.

```

import argparse
import time
import sys
import amazondax
import boto3
from boto3.dynamodb.conditions import Key


def query_test(partition_key, sort_keys, iterations, dyn_resource=None):
    """
    Queries the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param partition_key: The partition key value to use in the query. The query
                          returns items that have partition keys equal to this value.
    :param sort_keys: The range of sort key values for the query. The query returns
                     items that have sort key values between these two values.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    key_condition_expression = \
        Key('partition_key').eq(partition_key) & \
        Key('sort_key').between(*sort_keys)

    start = time.perf_counter()
    for _ in range(iterations):
        table.query(KeyConditionExpression=key_condition_expression)
        print('.', end='')
        sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end


if __name__ == '__main__':
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        'endpoint_url', nargs='?',
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not used.")
    args = parser.parse_args()

    test_partition_key = 5
    test_sort_keys = (2, 9)
    test_iterations = 100
    if args.endpoint_url:
        print(f"Querying the table {test_iterations} times, using the DAX client.")
        # Use a with statement so the DAX client closes the cluster after completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as dax:
            test_start, test_end = query_test(
                test_partition_key, test_sort_keys, test_iterations, dyn_resource=dax)
    else:
        print(f"Querying the table {test_iterations} times, using the Boto3 client.")
        test_start, test_end = query_test(
            test_partition_key, test_sort_keys, test_iterations)

    print(f"Total time: {test_end - test_start:.4f} sec. Average time: "
          f"{{(test_end - test_start)/test_iterations}}")

```

## 05-scan-test.py

The 05-scan-test.py program performs Scan operations on TryDaxTable.

```
import argparse
import time
import sys
import amazondax
import boto3

def scan_test(iterations, dyn_resource=None):
    """
    Scans the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    start = time.perf_counter()
    for _ in range(iterations):
        table.scan()
        print('.', end='')
        sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end

if __name__ == '__main__':
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        'endpoint_url', nargs='?',
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not used.")
    args = parser.parse_args()

    test_iterations = 100
    if args.endpoint_url:
        print(f"Scanning the table {test_iterations} times, using the DAX client.")
        # Use a with statement so the DAX client closes the cluster after completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as dax:
            test_start, test_end = scan_test(test_iterations, dyn_resource=dax)
    else:
        print(f"Scanning the table {test_iterations} times, using the Boto3 client.")
        test_start, test_end = scan_test(test_iterations)
    print(f"Total time: {test_end - test_start:.4f} sec. Average time: "
          f"{(test_end - test_start)/test_iterations}.")
```

## 06-delete-table.py

The 06-delete-table.py program deletes TryDaxTable. Run this program after you have finished testing Amazon DynamoDB Accelerator (DAX) functionality.

```
import boto3
```

```
def delete_dax_table(dyn_resource=None):
    """
    Deletes the demonstration table.

    :param dyn_resource: Either a Boto3 or DAX resource.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    table.delete()

    print(f"Deleting {table.name}...")
    table.wait_until_not_exists()

if __name__ == '__main__':
    delete_dax_table()
    print("Table deleted!")
```

## Modifying an existing application to use DAX

If you already have a Java application that uses Amazon DynamoDB, you can modify it so that it can access your DynamoDB Accelerator (DAX) cluster. You don't have to rewrite the entire application because the DAX Java client is similar to the DynamoDB low-level client included in the AWS SDK for Java 2.x. See [Working with items in DynamoDB](#) for details.

**Note**

This example uses AWS SDK for Java 2.x. For the legacy SDK for Java 1.x version, see [Modifying an existing SDK for Java 1.x application to use DAX \(p. 1408\)](#).

To modify your program, replace the DynamoDB client with a DAX client.

```
Region region = Region.US_EAST_1;

// Create an asynchronous DynamoDB client
DynamoDbAsyncClient client = DynamoDbAsyncClient.builder()
    .region(region)
    .build();

// Create an asynchronous DAX client
DynamoDbAsyncClient client = ClusterDaxAsyncClient.builder()
    .overrideConfiguration(Configuration.builder()
        .url(<cluster url>) // for example, "dax://my-cluster.16fzcv.dax-
clusters.us-east-1.amazonaws.com"
        .region(region)
        .addMetricPublisher(cloudWatchMetricsPub) // optionally enable SDK
metric collection
    .build())
    .build();
```

You can also use the high-level library that is part of the AWS SDK for Java 2.x, replacing the DynamoDB client with a DAX client.

```
Region region = Region.US_EAST_1;
DynamoDbAsyncClient dax = ClusterDaxAsyncClient.builder()
    .overrideConfiguration(Configuration.builder()
        .url(<cluster url>) // for example, "dax://my-cluster.16fzcv.dax-clusters.us-
east-1.amazonaws.com"
        .region(region)
    .build())
```

```
.build();  
  
DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()  
    .dynamoDbClient(dax)  
    .build();
```

For more information, see [Mapping items in DynamoDB tables](#).

## Managing DAX clusters

This section addresses some of the common management tasks for Amazon DynamoDB Accelerator (DAX) clusters.

### Topics

- [IAM permissions for managing a DAX cluster \(p. 712\)](#)
- [Scaling a DAX cluster \(p. 714\)](#)
- [Customizing DAX cluster settings \(p. 715\)](#)
- [Configuring TTL settings \(p. 715\)](#)
- [Tagging support for DAX \(p. 716\)](#)
- [AWS CloudTrail integration \(p. 717\)](#)
- [Deleting a DAX cluster \(p. 717\)](#)

## IAM permissions for managing a DAX cluster

When you administer a DAX cluster using the AWS Management Console or the AWS Command Line Interface (AWS CLI), we strongly recommend that you narrow the scope of actions that users can perform. By doing so, you help mitigate risk while following the principle of least privilege.

The following discussion focuses on access control for the DAX management APIs. For more information, see [Amazon DynamoDB accelerator](#) in the *Amazon DynamoDB API Reference*.

### Note

For more detailed information about managing AWS Identity and Access Management (IAM) permissions, see the following:

- IAM and creating DAX clusters: [Creating a DAX cluster \(p. 664\)](#).
- IAM and DAX data plane operations: [DAX access control \(p. 734\)](#).

For the DAX management APIs, you can't scope API actions to a specific resource. The `Resource` element must be set to `"*"`. This is different from DAX data plane API operations, such as `GetItem`, `Query`, and `Scan`. Data plane operations are exposed through the DAX client, and those operations *can* be scoped to specific resources.

To illustrate, consider the following IAM policy document.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Action": [  
                "dax:*"  
            ],  
            "Effect": "Allow",  
            "Resource": "*"  
        }  
    ]}
```

```

        "Resource": [
            "arn:aws:dax:us-west-2:123456789012:cache/DAXCluster01"
        ]
    }
}

```

Suppose that the intent of this policy is to allow DAX management API calls for the cluster DAXCluster01—and only that cluster.

Now suppose that a user issues the following AWS CLI command.

```
aws dax describe-clusters
```

This command fails with a Not Authorized exception because the underlying `DescribeClusters` API call can't be scoped to a specific cluster. Even though the policy is syntactically valid, the command fails because the `Resource` element must be set to `"*"`. However, if the user runs a program that sends DAX data plane calls (such as `GetItem` or `Query`) to DAXCluster01, those calls *do* succeed. This is because DAX data plane APIs can be scoped to specific resources (in this case, DAXCluster01).

If you want to write a single comprehensive IAM policy to encompass both DAX management APIs and DAX data plane APIs, we suggest that you include two distinct statements in the policy document. One of these statements should address the DAX data plane APIs, while the other statement addresses the DAX management APIs.

The following example policy shows this approach. Note how the `DAXDataAPIs` statement is scoped to the DAXCluster01 resource, but the resource for `DAXManagementAPIs` must be `"*"`. The actions shown in each statement are for illustration only. You can customize them as needed for your application.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DAXDataAPIs",
            "Action": [
                "dax:GetItem",
                "dax:BatchGetItem",
                "dax:Query",
                "dax:Scan",
                "dax:PutItem",
                "dax:UpdateItem",
                "dax:DeleteItem",
                "dax:BatchWriteItem"
            ],
            "Effect": "Allow",
            "Resource": [
                "arn:aws:dax:us-west-2:123456789012:cache/DAXCluster01"
            ]
        },
        {
            "Sid": "DAXManagementAPIs",
            "Action": [
                "dax>CreateParameterGroup",
                "dax>CreateSubnetGroup",
                "dax:DecreaseReplicationFactor",
                "dax>DeleteCluster",
                "dax>DeleteParameterGroup",
                "dax>DeleteSubnetGroup",
                "dax:DescribeClusters",
                "dax:DescribeDefaultParameters",
                "dax:DescribeEvents",
                "dax:DescribeReplicaGroup"
            ],
            "Effect": "Allow",
            "Resource": "*"
        }
    ]
}
```

```
        "dax:DescribeParameterGroups",
        "dax:DescribeParameters",
        "dax:DescribeSubnetGroups",
        "dax:IncreaseReplicationFactor",
        "dax>ListTags",
        "dax:RebootNode",
        "dax:TagResource",
        "dax:UntagResource",
        "dax:UpdateCluster",
        "dax:UpdateParameterGroup",
        "dax:UpdateSubnetGroup"
    ],
    "Effect": "Allow",
    "Resource": [
        "*"
    ]
}
]
```

## Scaling a DAX cluster

There are two options available for scaling a DAX cluster. The first option is *horizontal scaling*, where you add read replicas to the cluster. The second option is *vertical scaling*, where you select different node types. For advice on how to approach choosing an appropriate cluster size and node type for your application, see [DAX cluster sizing guide \(p. 756\)](#).

### Horizontal scaling

With horizontal scaling, you can improve throughput for read operations by adding more read replicas to the cluster. A single DAX cluster supports up to 10 read replicas, and you can add or remove replicas while the cluster is running.

The following AWS CLI examples show how to increase or decrease the number of nodes. The `--new-replication-factor` argument specifies the total number of nodes in the cluster. One of the nodes is the primary node, and the other nodes are read replicas.

```
aws dax increase-replication-factor \
--cluster-name MyNewCluster \
--new-replication-factor 5
```

```
aws dax decrease-replication-factor \
--cluster-name MyNewCluster \
--new-replication-factor 3
```

#### Note

The cluster status changes to `modifying` when you modify the replication factor. The status changes to `available` when the modification is complete.

### Vertical scaling

If you have a large working set of data, your application might benefit from using larger node types. Larger nodes can enable the cluster to store more data in memory, reducing cache misses and improving overall application performance of the application. (All of the nodes in a DAX cluster must be of the same type.)

If your DAX cluster has a high rate of write operations or cache misses, your application might also benefit from using larger node types. Write operations and cache misses consume resources on the

cluster's primary node. Therefore, using larger node types might increase the performance of the primary node and thereby allow a higher throughput for these types of operations.

You can't modify the node types on a running DAX cluster. Instead, you must create a new cluster with the desired node type. For a list of supported node types, see [Nodes \(p. 660\)](#).

You can create a new DAX cluster using the AWS Management Console, [AWS CloudFormation](#), the AWS CLI, or the [AWS SDK](#). (For the AWS CLI, use the `--node-type` parameter to specify the node type.)

## Customizing DAX cluster settings

When you create a DAX cluster, the following default settings are used:

- Automatic cache eviction enabled with Time to Live (TTL) of 5 minutes
- No preference for Availability Zones
- No preference for maintenance windows
- Notifications disabled

For new clusters, you can customize the settings at creation time. To do this in the AWS Management Console, clear **Use default settings** to modify the following settings:

- **Network and Security**—Allows you to run individual DAX cluster nodes in different Availability Zones within the current AWS Region. If you choose **No Preference**, the nodes are distributed among Availability Zones automatically.
- **Parameter Group**—A named set of parameters that are applied to every node in the cluster. You can use a parameter group to specify cache TTL behavior. You can change the value of any given parameter within a parameter group (except default parameter group `default.dax.1.0`) at any time.
- **Maintenance Window**—A weekly time period during which software upgrades and patches are applied to the nodes in the cluster. You can choose the start day, start time, and duration of the maintenance window. If you choose **No Preference**, the maintenance window is selected at random from an 8-hour block of time per Region. For more information, see [Maintenance window \(p. 663\)](#).

### Note

**Parameter Group** and **Maintenance Window** can also be changed at any time on a running cluster.

When a maintenance event occurs, DAX can notify you using Amazon Simple Notification Service (Amazon SNS). To configure notifications, choose an option from the **Topic for SNS notification** selector. You can create a new Amazon SNS topic, or use an existing topic.

For more information about setting up and subscribing to an Amazon SNS topic, see [Getting started with Amazon SNS](#) in the *Amazon Simple Notification Service Developer Guide*.

## Configuring TTL settings

DAX maintains two caches for data that it reads from DynamoDB:

- **Item cache**—For items retrieved using `GetItem` or `BatchGetItem`.
- **Query cache**—For result sets retrieved using `Query` or `Scan`.

For more information, see [Item cache \(p. 659\)](#) and [Query cache \(p. 660\)](#).

The default TTL for each of these caches is 5 minutes. If you want to use different TTL settings, you can launch a DAX cluster using a custom parameter group. To do this on the console, choose **DAX | Parameter groups** in the navigation pane.

You can also perform these tasks using the AWS CLI. The following example shows how to launch a new DAX cluster using a custom parameter group. In this example, the item cache TTL is set to 10 minutes, and the query cache TTL is set to 3 minutes.

1. Create a new parameter group.

```
aws dax create-parameter-group \
--parameter-group-name custom-ttl
```

2. Set the item cache TTL to 10 minutes (600000 milliseconds).

```
aws dax update-parameter-group \
--parameter-group-name custom-ttl \
--parameter-name-values "ParameterName=record-ttl-millis,ParameterValue=600000"
```

3. Set the query cache TTL to 3 minutes (180000 milliseconds).

```
aws dax update-parameter-group \
--parameter-group-name custom-ttl \
--parameter-name-values "ParameterName=query-ttl-millis,ParameterValue=180000"
```

4. Verify that the parameters have been set correctly.

```
aws dax describe-parameters --parameter-group-name custom-ttl \
--query "Parameters[*].[ParameterName,Description,ParameterValue]"
```

You can now launch a new DAX cluster with this parameter group.

```
aws dax create-cluster \
--cluster-name MyNewCluster \
--node-type dax.r3.large \
--replication-factor 3 \
--iam-role-arn arn:aws:iam::123456789012:role/DAXServiceRole \
--parameter-group custom-ttl
```

**Note**

You can't modify a parameter group that is being used by a running DAX instance.

## Tagging support for DAX

Many AWS services, including DynamoDB, support *tagging*—the ability to label resources with user-defined names. You can assign tags to DAX clusters, allowing you to quickly identify all of your AWS resources that have the same tag, or to categorize your AWS bills by the tags you assign.

For more information, see [Adding tags and labels to resources \(p. 329\)](#).

## Using the AWS Management Console

### To manage DAX cluster tags

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.

2. In the navigation pane, under **DAX**, choose **Clusters**.
3. Choose the cluster that you want to work with.
4. Choose the **Tags** tab. You can add, list, edit, or delete your tags here.

When the settings are as you want them, choose **Apply Changes**.

## Using the AWS CLI

When you use the AWS CLI to manage DAX cluster tags, you must first determine the Amazon Resource Name (ARN) for the cluster. The following example shows how to determine the ARN for a cluster named `MyDAXCluster`.

```
aws dax describe-clusters \
--cluster-name MyDAXCluster \
--query "Clusters[*].ClusterArn"
```

In the output, the ARN will look similar to this: `arn:aws:dax:us-west-2:123456789012:cache/MyDAXCluster`

The following example shows how to tag the cluster.

```
aws dax tag-resource \
--resource-name arn:aws:dax:us-west-2:123456789012:cache/MyDAXCluster \
--tags="Key=ClusterUsage,Value=prod"
```

List all the tags for a cluster.

```
aws dax list-tags \
--resource-name arn:aws:dax:us-west-2:123456789012:cache/MyDAXCluster
```

To remove a tag, specify its key.

```
aws dax untag-resource \
--resource-name arn:aws:dax:us-west-2:123456789012:cache/MyDAXCluster \
--tag-keys ClusterUsage
```

## AWS CloudTrail integration

DAX is integrated with AWS CloudTrail, allowing you to audit DAX cluster activities. You can use CloudTrail logs to view all the changes that have been made at the cluster level. You can also see changes to cluster components such as nodes, subnet groups, and parameter groups. For more information, see [Logging DynamoDB operations by using AWS CloudTrail \(p. 1133\)](#).

## Deleting a DAX cluster

If you are no longer using a DAX cluster, you should delete it to avoid being charged for unused resources.

You can delete a DAX cluster using the console or the AWS CLI. The following is an example.

```
aws dax delete-cluster --cluster-name mydaxcluster
```

# Monitoring DAX

Monitoring is an important part of maintaining the reliability, availability, and performance of Amazon DynamoDB Accelerator (DAX) and your AWS solutions. You should collect monitoring data from all parts of your AWS solution so that you can more easily debug a multi-point failure, if one occurs.

Before you start monitoring DAX, you should create a monitoring plan that includes answers to the following questions:

- What are your monitoring goals?
- What resources will you monitor?
- How often will you monitor these resources?
- What monitoring tools will you use?
- Who will perform the monitoring tasks?
- Who should be notified when something goes wrong?

The next step is to establish a baseline for normal DAX performance in your environment, by measuring performance at various times and under different load conditions. As you monitor DAX, you should consider storing historical monitoring data. This stored data gives you a baseline from which to compare current performance data, identify normal performance patterns and performance anomalies, and devise methods to address issues.

To establish a baseline, you should, at a minimum, monitor the following items both during load testing and in production:

- CPU utilization and throttled requests, so that you can determine whether you might need to use a larger node type in your cluster. The CPU utilization of your cluster is available through the [CPUUtilization CloudWatch metric \(p. 720\)](#).
- Operation latency (as measured on the client side) should remain consistently within your application's latency requirements.
- Error rates should remain low, as seen from the [ErrorRequestCount](#), [FaultRequestCount](#), and [FailedRequestCount CloudWatch metrics \(p. 720\)](#).

Apart from the preceding items, you should, at a minimum, monitor the following additional items in production:

- Estimated database size and evicted size, so that you can determine whether the cluster's node type has sufficient memory to hold your working set.
- Client connections, so that you can monitor for any unexplained spikes in connections to the cluster.

## Topics

- [Monitoring tools \(p. 718\)](#)
- [Monitoring with Amazon CloudWatch \(p. 719\)](#)
- [Logging DAX operations using AWS CloudTrail \(p. 733\)](#)

## Monitoring tools

AWS provides tools that you can use to monitor Amazon DynamoDB Accelerator (DAX). You can configure some of these tools to do the monitoring for you, and some require manual intervention. We recommend that you automate monitoring tasks as much as possible.

## Topics

- [Automated monitoring tools \(p. 719\)](#)
- [Manual monitoring tools \(p. 719\)](#)

## Automated monitoring tools

You can use the following automated monitoring tools to watch DAX and report when something is wrong:

- **Amazon CloudWatch Alarms** – Watch a single metric over a time period that you specify, and perform one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The action is a notification sent to an Amazon Simple Notification Service (Amazon SNS) topic or Amazon EC2 Auto Scaling policy. CloudWatch alarms do not invoke actions simply because they are in a particular state; the state must have changed and been maintained for a specified number of periods. For more information, see [Monitoring with Amazon CloudWatch \(p. 1114\)](#).
- **Amazon CloudWatch Logs** – Monitor, store, and access your log files from AWS CloudTrail or other sources. For more information, see [Monitoring Log Files](#) in the *Amazon CloudWatch User Guide*.
- **Amazon CloudWatch Events** – Match events and route them to one or more target functions or streams to make changes, capture state information, and take corrective action. For more information, see [What Is Amazon CloudWatch Events](#) in the *Amazon CloudWatch User Guide*.
- **AWS CloudTrail Log Monitoring** – Share log files between accounts, monitor CloudTrail log files in real time by sending them to CloudWatch Logs, write log processing applications in Java, and validate that your log files have not changed after delivery by CloudTrail. For more information, see [Working with CloudTrail Log Files](#) in the *AWS CloudTrail User Guide*.

## Manual monitoring tools

Another important part of monitoring DAX involves manually monitoring those items that the CloudWatch alarms don't cover. The DAX, CloudWatch, Trusted Advisor, and other AWS Management Console dashboards provide an at-a-glance view of the state of your AWS environment. We recommend that you also check the log files on DAX.

- The DAX dashboard shows the following:
  - Service health
- The CloudWatch home page shows the following:
  - Current alarms and status
  - Graphs of alarms and resources
  - Service health status

In addition, you can use CloudWatch to do the following:

- Create [customized dashboards](#) to monitor the services that you care about.
- Graph metric data to troubleshoot issues and discover trends.
- Search and browse all of your AWS resource metrics.
- Create and edit alarms to be notified of problems.

## Monitoring with Amazon CloudWatch

You can monitor Amazon DynamoDB Accelerator (DAX) using Amazon CloudWatch, which collects and processes raw data from DAX into readable, near real-time metrics. These statistics are recorded for a period of two weeks. You can then access historical information for a better perspective on how

your web application or service is performing. By default, DAX metric data is sent to CloudWatch automatically. For more information, see [What Is Amazon CloudWatch?](#) in the *Amazon CloudWatch User Guide*.

#### Topics

- [How do I use DAX metrics? \(p. 720\)](#)
- [Viewing DAX metrics and dimensions \(p. 720\)](#)
- [Creating CloudWatch alarms to monitor DAX \(p. 731\)](#)

## How do I use DAX metrics?

The metrics reported by DAX provide information that you can analyze in different ways. The following list shows some common uses for the metrics. These are suggestions to get you started, and not a comprehensive list.

How Can I?	Relevant Metrics
Determine if any system errors occurred	Monitor <code>FaultRequestCount</code> to determine if any requests resulted in an HTTP 500 (server error) code. This can indicate a DAX internal service error or an HTTP 500 in the underlying table's <a href="#">SystemErrors metric</a> .
Determine if any user errors occurred	Monitor <code>ErrorRequestCount</code> to determine if any requests resulted in an HTTP 400 (client error) code. If you see the error count growing, you might want to investigate and make sure you are sending correct client requests.
Determine if any cache misses occurred	Monitor <code>ItemCacheMisses</code> to determine the number of times an item was not found in the cache, and <code>QueryCacheMisses</code> and <code>ScanCacheMisses</code> to determine the number of times a query or scan result was not found in the cache.
Monitor cache hit rates	Use <a href="#">CloudWatch Metric Math</a> to define a cache hit rate metric using math expressions.  For example, for the item cache, you can use the expression $m1 / \text{SUM}([m1, m2]) * 100$ , where <code>m1</code> is the <code>ItemCacheHits</code> metric and <code>m2</code> is the <code>ItemCacheMisses</code> metric for your cluster. For the query and scan caches, you can follow the same pattern using the corresponding query and scan cache metric.

## Viewing DAX metrics and dimensions

When you interact with Amazon DynamoDB, it sends metrics and dimensions to Amazon CloudWatch. You can use the following procedures to view the metrics for DynamoDB Accelerator (DAX).

### To view metrics (console)

Metrics are grouped first by the service namespace, and then by the various dimension combinations within each namespace.

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, choose **Metrics**.
3. Select the **DAX** namespace.

## To view metrics (AWS CLI)

- At a command prompt, use the following command.

```
aws cloudwatch list-metrics --namespace "AWS/DAX"
```

## DAX metrics and dimensions

The following sections contain the metrics and dimensions that DAX sends to CloudWatch.

### DAX Metrics

The following metrics are available from DAX. DAX sends metrics to CloudWatch only when they have a non-zero value.

#### Note

CloudWatch aggregates the following DAX metrics at one-minute intervals:

- CPUUtilization
- CacheMemoryUtilization
- NetworkBytesIn
- NetworkBytesOut
- NetworkPacketsIn
- NetworkPacketsOut
- GetItemRequestCount
- BatchGetItemRequestCount
- BatchWriteItemRequestCount
- DeleteItemRequestCount
- PutItemRequestCount
- UpdateItemRequestCount
- TransactWriteItemsCount
- TransactGetItemsCount
- ItemCacheHits
- ItemCacheMisses
- QueryCacheHits
- QueryCacheMisses
- ScanCacheHits
- ScanCacheMisses
- TotalRequestCount
- ErrorRequestCount
- FaultRequestCount
- FailedRequestCount
- QueryRequestCount
- ScanRequestCount
- ClientConnections
- EstimatedDbSize

- `EvictedSize`
- `CPUCreditUsage`
- `CPUCreditBalance`
- `CPUSurplusCreditBalance`
- `CPUSurplusCreditsCharged`

Not all statistics, such as `Average` or `Sum`, are applicable for every metric. However, all of these values are available through the DAX console, or by using the CloudWatch console, AWS CLI, or AWS SDKs for all metrics. In the following table, each metric has a list of valid statistics that are applicable to that metric.

Metric	Description
<code>CPUUtilization</code>	<p>The percentage of CPU utilization of the node or cluster.</p> <p>Units: Percent</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• <code>Minimum</code></li> <li>• <code>Maximum</code></li> <li>• <code>Average</code></li> </ul>
<code>CacheMemoryUtilization</code>	<p>The percentage of available cache memory that is in use by the item cache and query cache on the node or cluster. Cached data starts to be evicted prior to memory utilization reaching 100% (see <code>EvictedSize</code> metric). If <code>CacheMemoryUtilization</code> reaches 100% on any node, write requests will be throttled and you should consider switching to a cluster with a larger node type.</p> <p>Units: Percent</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• <code>Minimum</code></li> <li>• <code>Maximum</code></li> <li>• <code>Average</code></li> </ul>
<code>NetworkBytesIn</code>	<p>The number of bytes received on all network interfaces by the node or cluster.</p> <p>Units: Bytes</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• <code>Minimum</code></li> <li>• <code>Maximum</code></li> <li>• <code>Average</code></li> </ul>
<code>NetworkBytesOut</code>	<p>The number of bytes sent out on all network interfaces by the node or cluster. This metric identifies the volume of outgoing traffic in terms of the number of bytes on a single node or cluster.</p> <p>Units: Bytes</p> <p>Valid Statistics:</p>

Metric	Description
	<ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> </ul>
<code>NetworkPacketsIn</code>	<p>The number of packets received on all network interfaces by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> </ul>
<code>NetworkPacketsOut</code>	<p>The number of packets sent out on all network interfaces by the node or cluster. This metric identifies the volume of outgoing traffic in terms of the number of packets on a single node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> </ul>
<code>GetItemRequestCount</code>	<p>The number of <code>.GetItem</code> requests handled by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
<code>BatchGetItemRequestCount</code>	<p>The number of <code>BatchGetItem</code> requests handled by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
BatchWriteItemRequestCount	<p>The number of <code>BatchWriteItem</code> requests handled by the node or cluster.</p> <p><b>Units:</b> Count</p> <p><b>Valid Statistics:</b></p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
DeleteItemRequestCount	<p>The number of <code>DeleteItem</code> requests handled by the node or cluster.</p> <p><b>Units:</b> Count</p> <p><b>Valid Statistics:</b></p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
PutItemRequestCount	<p>The number of <code>PutItem</code> requests handled by the node or cluster.</p> <p><b>Units:</b> Count</p> <p><b>Valid Statistics:</b></p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
UpdateItemRequestCount	<p>The number of <code>UpdateItem</code> requests handled by the node or cluster.</p> <p><b>Units:</b> Count</p> <p><b>Valid Statistics:</b></p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
TransactWriteItemCount	<p>The number of <code>TransactWriteItems</code> requests handled by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
TransactGetItemCount	<p>The number of <code>TransactGetItems</code> requests handled by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ItemCacheHits	<p>The number of times an item was returned from the cache by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ItemCacheMisses	<p>The number of times an item was not in the node or cluster cache, and had to be retrieved from DynamoDB.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
QueryCacheHits	<p>The number of times a query result was returned from the node or cluster cache.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
QueryCacheMisses	<p>The number of times a query result was not in the node or cluster cache, and had to be retrieved from DynamoDB.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ScanCacheHits	<p>The number of times a scan result was returned from the node or cluster cache.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ScanCacheMisses	<p>The number of times a scan result was not in the node or cluster cache, and had to be retrieved from DynamoDB.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
TotalRequestCount	<p>Total number of requests handled by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ErrorRequestCount	<p>Total number of requests that resulted in a user error reported by the node or cluster. Requests that were throttled by the node or cluster are included.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ThrottledRequestCount	<p>Total number of requests throttled by the node or cluster. Requests that were throttled by DynamoDB are not included, and can be monitored using <a href="#">DynamoDB Metrics (p. 1114)</a>.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
FaultRequestCount	<p>Total number of requests that resulted in an internal error reported by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
FailedRequestCount	<p>Total number of requests that resulted in an error reported by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
QueryRequestCount	<p>The number of query requests handled by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ScanRequestCount	<p>The number of scan requests handled by the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
ClientConnections	<p>The number of simultaneous connections made by clients to the node or cluster.</p> <p>Units: Count</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
EstimatedDbSize	<p>An approximation of the amount of data cached in the item cache and the query cache by the node or cluster.</p> <p>Units: Bytes</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> </ul>
EvictedSize	<p>The amount of data that was evicted by the node or cluster to make room for newly requested data. If the miss rate goes up, and you see this metric also growing, it probably means that your working set has increased. You should consider switching to a cluster with a larger node type.</p> <p>Units: Bytes</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• Sum</li> </ul>
CPUCreditUsage	<p>The number of CPU credits spent by the node for CPU utilization. One CPU credit equals one vCPU running at 100% utilization for one minute or an equivalent combination of vCPUs, utilization, and time (for example, one vCPU running at 50% utilization for two minutes or two vCPUs running at 25% utilization for two minutes).</p> <p>CPU credit metrics are available at a five-minute frequency only. If you specify a period greater than five minutes, use the <code>Sum</code> statistic instead of the <code>Average</code>.</p> <p>Units: Credits (vCPU-minutes)</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
CPUCreditBalance	<p>The number of earned CPU credits that a node has accrued since it was launched or started.</p> <p>Credits are accrued in the credit balance after they are earned, and removed from the credit balance when they are spent. The credit balance has a maximum limit, determined by the DAX node size. After the limit is reached, any new credits that are earned are discarded.</p> <p>The credits in the CPUCreditBalance are available for the node to spend to burst beyond its baseline CPU utilization.</p> <p>Units: Credits (vCPU-minutes)</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>
CPUSurplusCreditBalance	<p>The number of surplus credits that have been spent by a DAX node when its CPUCreditBalance value is zero.</p> <p>The CPUSurplusCreditBalance value is paid down by earned CPU credits. If the number of surplus credits exceeds the maximum number of credits that the node can earn in a 24-hour period, the spent surplus credits above the maximum incur an additional charge.</p> <p>Units: Credits (vCPU-minutes)</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

Metric	Description
CPUSurplusCreditsCharged	<p>The number of spent surplus credits that are not paid down by earned CPU credits, and which thus incur an additional charge.</p> <p>Spent surplus credits are charged when the spent surplus credits exceed the maximum number of credits that the node can earn in a 24-hour period. Spent surplus credits above the maximum are charged at the end of the hour or when the node is terminated.</p> <p>Units: Credits (vCPU-minutes)</p> <p>Valid Statistics:</p> <ul style="list-style-type: none"> <li>• Minimum</li> <li>• Maximum</li> <li>• Average</li> <li>• SampleCount</li> <li>• Sum</li> </ul>

**Note**

The CPUCreditUsage, CPUCreditBalance, CPUSurplusCreditBalance, and CPUSurplusCreditsCharged metrics are available only for T3 nodes.

### Dimensions for DAX Metrics

The metrics for DAX are qualified by the values for the account, cluster ID, or cluster ID and node ID combination. You can use the CloudWatch console to retrieve DAX data along any of the dimensions in the following table.

Dimension	Description
Account	Provides aggregated statistics across all metrics in an account.
ClusterId	Limits the data to a cluster.
ClusterId, NodeId	Limits the data to a node within a cluster.

## Creating CloudWatch alarms to monitor DAX

You can create an Amazon CloudWatch alarm that sends an Amazon Simple Notification Service (Amazon SNS) message when the alarm changes state. An alarm watches a single metric over a time period that you specify. It performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The action is a notification that is sent to an Amazon SNS topic or Auto Scaling policy. Alarms invoke actions for sustained state changes only. CloudWatch alarms do not invoke actions simply because they are in a particular state. The state must have changed and been maintained for a specified number of periods.

## How can I be notified of query cache misses?

1. Create an Amazon SNS topic, `arn:aws:sns:us-west-2:522194210714:QueryMissAlarm`.

For more information, see [Set Up Amazon Simple Notification Service](#) in the *Amazon CloudWatch User Guide*.

2. Create the alarm.

```
aws cloudwatch put-metric-alarm \
--alarm-name QueryCacheMissesAlarm \
--alarm-description "Alarm over query cache misses" \
--namespace AWS/DAX \
--metric-name QueryCacheMisses \
--dimensions Name=ClusterID,Value=myCluster \
--statistic Sum \
--threshold 8 \
--comparison-operator GreaterThanOrEqualToThreshold \
--period 60 \
--evaluation-periods 1 \
--alarm-actions arn:aws:sns:us-west-2:522194210714:QueryMissAlarm
```

3. Test the alarm.

```
aws cloudwatch set-alarm-state --alarm-name QueryCacheMissesAlarm --state-reason
"initializing" --state-value OK
```

```
aws cloudwatch set-alarm-state --alarm-name QueryCacheMissesAlarm --state-reason
"initializing" --state-value ALARM
```

### Note

You can increase or decrease the threshold to one that makes sense for your application. You can also use [CloudWatch Metric Math](#) to define a cache miss rate metric and set an alarm over that metric.

## How can I be notified if requests cause any internal error in the cluster?

1. Create an Amazon SNS topic, `arn:aws:sns:us-west-2:123456789012:notify-on-system-errors`.

For more information, see [Set Up Amazon Simple Notification Service](#) in the *Amazon CloudWatch User Guide*.

2. Create the alarm.

```
aws cloudwatch put-metric-alarm \
--alarm-name FaultRequestCountAlarm \
--alarm-description "Alarm when a request causes an internal error" \
--namespace AWS/DAX \
--metric-name FaultRequestCount \
--dimensions Name=ClusterID,Value=myCluster \
--statistic Sum \
--threshold 0 \
--comparison-operator GreaterThanThreshold \
--period 60 \
--unit Count \
--evaluation-periods 1 \
--alarm-actions arn:aws:sns:us-east-1:123456789012:notify-on-system-errors
```

3. Test the alarm.

```
aws cloudwatch set-alarm-state --alarm-name FaultRequestCountAlarm --state-reason  
"initializing" --state-value OK
```

```
aws cloudwatch set-alarm-state --alarm-name FaultRequestCountAlarm --state-reason  
"initializing" --state-value ALARM
```

## Logging DAX operations using AWS CloudTrail

Amazon DynamoDB Accelerator (DAX) is integrated with AWS CloudTrail, a service that provides a record of actions taken by a user, role, or an AWS service in DAX.

To learn more about DAX and CloudTrail, see the [DynamoDB Accelerator \(DAX\) section in Logging DynamoDB operations by using AWS CloudTrail \(p. 1133\)](#).

## DAX T3/T2 burstable instances

DAX allows you to choose between fixed performance instances (such as R4 and R5) and burstable performance instances (such as T2 and T3). Burstable performance instances provide a baseline level of CPU performance with the ability to burst above the baseline when needed.

Baseline performance and the ability to burst above it are governed by CPU credits. Burstable performance instances accumulate CPU credits continuously, at a rate determined by the instance size, when the workload is below the baseline threshold. These credits may then be consumed when the workload increases. A CPU credit provides the performance of a full CPU core for one minute.

Many workloads don't need consistently high levels of CPU, but benefit significantly from having full access to very fast CPUs when they need them. Burstable performance instances are engineered specifically for these use cases. If you need consistently high CPU performance for your database, we recommend you use fixed performance instances.

### DAX T2 instance family

DAX T2 instances are burstable general-purpose performance instances that provide a baseline level of CPU performance with the ability to burst above the baseline. T2 instances are a good choice for test and development workloads which need price predictability. DAX T2 instances are configured for standard mode, which means that if the instance is running low on accrued credits, CPU utilization is gradually lowered to the baseline level. For more information on standard mode, refer to [Standard mode for burstable performance instances](#) in the Amazon EC2 User Guide for Linux Instances.

### DAX T3 instance family

DAX T3 instances are the next generation burstable general-purpose instance type, providing a baseline level of CPU performance with the ability to burst CPU usage at any time for as long as required. T3 instances offer a balance of compute, memory, and network resources and are ideal for workloads with moderate CPU usage that experience temporary spikes in use. DAX T3 instances are configured for unlimited mode, which means they can burst beyond the baseline over a 24-hour window for an additional charge. For more information on unlimited mode, refer to [Unlimited mode for burstable performance instances](#) in the Amazon EC2 User Guide for Linux Instances.

DAX T3 instances can sustain high CPU performance for as long as a workload requires it. For most general-purpose workloads, T3 instances will provide ample performance without any additional

charges. The hourly T3 instance price automatically covers all interim spikes in usage when the average CPU utilization of a T3 instance is at or less than the baseline over a 24-hour window.

For example, a `dax.t3.small` instance receives credits continuously at a rate of 24 CPU credits per hour. This capability provides baseline performance equivalent to 20% of a CPU core ( $20\% \times 60 \text{ minutes} = 12 \text{ minutes}$ ). If the instance does not use the credits it receives, they are stored in its CPU credit balance up to a maximum of 576 CPU credits. When the `t3.small` instance needs to burst to more than 20% of a core, it draws from its CPU credit balance to handle this surge automatically.

While DAX T2 instances are restricted to baseline performance once the CPU credit balance is drawn down to zero, DAX T3 instances can burst above the baseline even when their CPU credit balance is zero. For the vast majority of workloads, where the average CPU utilization is at or below the baseline performance, the basic hourly price for `t3.small` covers all CPU bursts. If the instance happens to run at an average 25% CPU utilization (5% above baseline) over a period of 24 hours after its CPU credit balance is drawn to zero, it will be charged an additional 11.52 cents ( $9.6 \text{ cents/vCPU-hour} \times 1 \text{ vCPU} \times 5\% \times 24 \text{ hours}$ ). See [Amazon DynamoDB Pricing](#) for pricing details.

## DAX access control

DynamoDB Accelerator (DAX) is designed to work together with DynamoDB, to seamlessly add a caching layer to your applications. However, DAX and DynamoDB have separate access control mechanisms. Both services use AWS Identity and Access Management (IAM) to implement their respective security policies, but the security models for DAX and DynamoDB are different.

*We highly recommend that you understand both security models*, so that you can implement proper security measures for your applications that use DAX.

This section describes the access control mechanisms provided by DAX and provides sample IAM policies that you can tailor to your needs.

With DynamoDB, you can create IAM policies that limit the actions a user can perform on individual DynamoDB resources. For example, you can create a user role that only allows the user to perform read-only actions on a particular DynamoDB table. (For more information, see [the section called “Identity and access management” \(p. 1070\)](#).) By comparison, the DAX security model focuses on cluster security, and the ability of the cluster to perform DynamoDB API actions on your behalf.

### Warning

If you are currently using IAM roles and policies to restrict access to DynamoDB tables data, then the use of DAX can **subvert** those policies. For example, a user could have access to a DynamoDB table via DAX but not have explicit access to the same table accessing DynamoDB directly. For more information, see [the section called “Identity and access management” \(p. 1070\)](#).

DAX does not enforce user-level separation on data in DynamoDB. Instead, users inherit the permissions of the DAX cluster's IAM policy when they access that cluster. Thus, when accessing DynamoDB tables via DAX, the only access controls that are in effect are the permissions in the DAX cluster's IAM policy. No other permissions are recognized.

If you require isolation, we recommend that you create additional DAX clusters and scope the IAM policy for each cluster accordingly. For example, you could create multiple DAX clusters and allow each cluster to access only a single table.

## IAM service role for DAX

When you create a DAX cluster, you must associate the cluster with an IAM role. This is known as the *service role* for the cluster.

Suppose that you wanted to create a new DAX cluster named *DAXCluster01*. You could create a service role named *DAXServiceRole*, and associate the role with *DAXCluster01*. The policy

for *DAXServiceRole* would define the DynamoDB actions that *DAXCluster01* could perform, on behalf of the users who interact with *DAXCluster01*.

When you create a service role, you must specify a trust relationship between *DAXServiceRole* and the DAX service itself. A trust relationship determines which entities can assume a role and make use of its permissions. The following is an example trust relationship document for *DAXServiceRole*:

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Principal": {  
                "Service": "dax.amazonaws.com"  
            },  
            "Action": "sts:AssumeRole"  
        }  
    ]  
}
```

This trust relationship allows a DAX cluster to assume *DAXServiceRole* and perform DynamoDB API calls on your behalf.

The DynamoDB API actions that are allowed are described in an IAM policy document, which you attach to *DAXServiceRole*. The following is an example policy document.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "DaxAccessPolicy",  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:DescribeTable",  
                "dynamodb:PutItem",  
                "dynamodb:GetItem",  
                "dynamodb:UpdateItem",  
                "dynamodb:DeleteItem",  
                "dynamodb:Query",  
                "dynamodb:Scan",  
                "dynamodb:BatchGetItem",  
                "dynamodb:BatchWriteItem",  
                "dynamodb:ConditionCheckItem"  
            ],  
            "Resource": [  
                "arn:aws:dynamodb:us-west-2:123456789012:table/Books"  
            ]  
        }  
    ]  
}
```

This policy allows DAX to perform necessary DynamoDB API actions on a DynamoDB table. The `dynamodb:DescribeTable` action is required for DAX to maintain metadata about the table, and the others are read and write actions performed on items in the table. The table, named `Books`, is in the us-west-2 Region and is owned by AWS account ID 123456789012.

## IAM policy to allow DAX cluster access

After you create a DAX cluster, you need to grant permissions to an IAM user so that the user can access the DAX cluster.

For example, suppose that you want to grant access to *DAXCluster01* to an IAM user named Alice. You would first create an IAM policy (*AliceAccessPolicy*) that defines the DAX clusters and DAX API actions that the recipient can access. You would then confer access by attaching this policy to user Alice.

The following policy document gives the recipient full access on *DAXCluster01*.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Action": [
                "dax:*"
            ],
            "Effect": "Allow",
            "Resource": [
                "arn:aws:dax:us-west-2:123456789012:cache/DAXCluster01"
            ]
        }
    ]
}
```

The policy document allows access to the DAX cluster, but it does not grant any DynamoDB permissions. (The DynamoDB permissions are conferred by the DAX service role.)

For user Alice, you would first create *AliceAccessPolicy* with the policy document shown previously. You would then attach the policy to Alice.


**Note**

Instead of attaching the policy to an IAM user, you could attach it to an IAM role. That way, all of the users who assume that role would have the permissions that you defined in the policy.

The user policy, together with the DAX service role, determine the DynamoDB resources and API actions that the recipient can access via DAX.

## Case study: Accessing DynamoDB and DAX

The following scenario can help further your understanding of IAM policies for use with DAX. (This scenario is referred to throughout the rest of this section.) The following diagram shows a high-level overview of the scenario.




In this scenario, there are the following entities:

- An IAM user (Bob).
- An IAM role (**BobUserRole**). Bob assumes this role at runtime.
- An IAM policy (**BobAccessPolicy**). This policy is attached to **BobUserRole**. **BobAccessPolicy** defines the DynamoDB and DAX resources that **BobUserRole** is allowed to access.
- A DAX cluster (**DAXCluster01**).
- An IAM service role (**DAXServiceRole**). This role allows **DAXCluster01** to access DynamoDB.
- An IAM policy (**DAXAccessPolicy**). This policy is attached to **DAXServiceRole**. **DAXAccessPolicy** defines the DynamoDB APIs and resources that **DAXCluster01** is allowed to access.
- A DynamoDB table (**Books**).

The combination of policy statements in **BobAccessPolicy** and **DAXAccessPolicy** determine what Bob can do with the **Books** table. For example, Bob might be able to access **Books** directly (using the DynamoDB endpoint), indirectly (using the DAX cluster), or both. Bob might also be able to read data from **Books**, write data to **Books**, or both.

## Access to DynamoDB, but no access with DAX



It is possible to allow direct access to a DynamoDB table, while preventing indirect access using a DAX cluster. For direct access to DynamoDB, the permissions for **BobUserRole** are determined by **BobAccessPolicy** (which is attached to the role).

### Read-only access to DynamoDB (only)

*Bob* can access DynamoDB with **BobUserRole**. The IAM policy attached to this role (**BobAccessPolicy**) determines the DynamoDB tables that **BobUserRole** can access, and what APIs that **BobUserRole** can invoke.

Consider the following policy document for **BobAccessPolicy**.

```
{
  "Version": "2012-10-17",
```

```
"Statement": [
    {
        "Sid": "DynamoDBAccessStmt",
        "Effect": "Allow",
        "Action": [
            "dynamodb:GetItem",
            "dynamodb:BatchGetItem",
            "dynamodb:Query",
            "dynamodb:Scan"
        ],
        "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
    }
]
```

When this document is attached to `BobAccessPolicy`, it allows `BobUserRole` to access the DynamoDB endpoint and perform read-only operations on the Books table.

DAX does not appear in this policy, so access via DAX is denied.


## Read/write access to DynamoDB (only)

If `BobUserRole` requires read/write access to DynamoDB, the following policy would work.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DynamoDBAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Query",
                "dynamodb:Scan",
                "dynamodb:PutItem",
                "dynamodb:UpdateItem",
                "dynamodb:DeleteItem",
                "dynamodb:BatchWriteItem",
                "dynamodb:ConditionCheckItem"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
        }
    ]
}
```

Again, DAX does not appear in this policy, so access via DAX is denied.

## Access to DynamoDB and to DAX



To allow access to a DAX cluster, you must include DAX-specific actions in an IAM policy.

The following DAX-specific actions correspond to their similarly named counterparts in the DynamoDB API:

- `dax:GetItem`
- `dax:BatchGetItem`
- `dax:Query`
- `dax:Scan`
- `dax:PutItem`
- `dax:UpdateItem`
- `dax:DeleteItem`
- `dax:BatchWriteItem`
- `dax:ConditionCheckItem`

The same is true for the `dax:EnclosingOperation` condition key.

## Read-only access to DynamoDB and read-only access to DAX

Suppose that Bob requires read-only access to the `Books` table, from DynamoDB and from DAX. The following policy (attached to `BobUserRole`) confers this access.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DAXAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dax:GetItem",
                "dax:BatchGetItem",
                "dax:Query",
                "dax:Scan"
            ],
            "Resource": [
                "arn:aws:dax:us-west-2:123456789012:table/Books"
            ]
        }
    ]
}
```

```

        ],
        "Resource": "arn:aws:dax:us-west-2:123456789012:cache/DAXCluster01"
    },
    {
        "Sid": "DynamoDBAccessStmt",
        "Effect": "Allow",
        "Action": [
            "dynamodb:GetItem",
            "dynamodb:BatchGetItem",
            "dynamodb:Query",
            "dynamodb:Scan"
        ],
        "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
    }
]
}

```

The policy has a statement for DAX access (`DAXAccessStmt`) and another statement for DynamoDB access (`DynamoDBAccessStmt`). These statements allow Bob to send `GetItem`, `BatchGetItem`, `Query`, and `Scan` requests to `DAXCluster01`.

However, the service role for `DAXCluster01` would also require read-only access to the `Books` table in DynamoDB. The following IAM policy, attached to `DAXServiceRole`, would fulfill this requirement.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DynamoDBAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Query",
                "dynamodb:Scan"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
        }
    ]
}

```

## Read/write access to DynamoDB and read-only with DAX

For a given user role, you can provide read/write access to a DynamoDB table, while also allowing read-only access via DAX.

For Bob, the IAM policy for `BobUserRole` would need to allow DynamoDB read and write actions on the `Books` table, while also supporting read-only actions via `DAXCluster01`.

The following example policy document for `BobUserRole` confers this access.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DAXAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dax:.GetItem",
                "dax:BatchGetItem",
                "dax:Query",
                "dax:Scan"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
        }
    ]
}

```

```

        ],
        "Resource": "arn:aws:dax:us-west-2:123456789012:cache/DAXCluster01"
    },
    {
        "Sid": "DynamoDBAccessStmt",
        "Effect": "Allow",
        "Action": [
            "dynamodb:GetItem",
            "dynamodb:BatchGetItem",
            "dynamodb:Query",
            "dynamodb:Scan",
            "dynamodb:PutItem",
            "dynamodb:UpdateItem",
            "dynamodb:DeleteItem",
            "dynamodb:BatchWriteItem",
            "dynamodb:DescribeTable",
            "dynamodb:ConditionCheckItem"
        ],
        "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
    }
]
}

```

In addition, `DAXServiceRole` would require an IAM policy that allows `DAXCluster01` to perform read-only actions on the `Books` table.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DynamoDBAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Query",
                "dynamodb:Scan",
                "dynamodb:DescribeTable"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
        }
    ]
}

```

## Read/write access to DynamoDB and read/write access to DAX

Now suppose that Bob required read/write access to the `Books` table, directly from DynamoDB or indirectly from `DAXCluster01`. The following policy document, attached to `BobAccessPolicy`, confers this access.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DAXAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dax:GetItem",
                "dax:BatchGetItem",
                "dax:Query",
                "dax:Scan",
                "dax:PutItem",
                "dax:UpdateItem",
                "dax:DeleteItem"
            ],
            "Resource": "arn:aws:dax:us-west-2:123456789012:cluster/DAXCluster01"
        }
    ]
}

```


```
        "dax:UpdateItem",
        "dax:DeleteItem",
        "dax:BatchWriteItem",
        "dax:ConditionCheckItem"
    ],
    "Resource": "arn:aws:dax:us-west-2:123456789012:cache/DAXCluster01"
},
{
    "Sid": "DynamoDBAccessStmt",
    "Effect": "Allow",
    "Action": [
        "dynamodb:GetItem",
        "dynamodb:BatchGetItem",
        "dynamodb:Query",
        "dynamodb:Scan",
        "dynamodb:PutItem",
        "dynamodb:UpdateItem",
        "dynamodb:DeleteItem",
        "dynamodb:BatchWriteItem",
        "dynamodb:DescribeTable",
        "dynamodb:ConditionCheckItem"
    ],
    "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
}
]
```

In addition, `DAXServiceRole` would require an IAM policy that allows `DAXCluster01` to perform read/write actions on the `Books` table.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DynamoDBAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Query",
                "dynamodb:Scan",
                "dynamodb:PutItem",
                "dynamodb:UpdateItem",
                "dynamodb:DeleteItem",
                "dynamodb:BatchWriteItem",
                "dynamodb:DescribeTable"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
        }
    ]
}
```

## Access to DynamoDB via DAX, but no direct access to DynamoDB

In this scenario, Bob can access the `Books` table via DAX, but he does not have direct access to the `Books` table in DynamoDB. Thus, when Bob gains access to DAX, he also gains access to a DynamoDB table that he otherwise might not be able to access. When you configure an IAM policy for the DAX service role, remember that any user that is given access to the DAX cluster via the user access policy gains access to the tables specified in that policy. In this case, `BobAccessPolicy` gains access to the tables specified in `DAXAccessPolicy`.



If you are currently using IAM roles and policies to restrict access to DynamoDB tables and data, using DAX can subvert those policies. In the following policy, Bob has access to a DynamoDB table via DAX but does not have explicit direct access to the same table in DynamoDB.

The following policy document (**BobAccessPolicy**), attached to **BobUserRole**, would confer this access.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DAXAccessStmt",
            "Effect": "Allow",
            "Action": [
                "dax:GetItem",
                "dax:BatchGetItem",
                "dax:Query",
                "dax:Scan",
                "dax:PutItem",
                "dax:UpdateItem",
                "dax:DeleteItem",
                "dax:BatchWriteItem",
                "dax:ConditionCheckItem"
            ],
            "Resource": "arn:aws:dax:us-west-2:123456789012:cache/DAXCluster01"
        }
    ]
}
```

In this access policy, there are no permissions to access DynamoDB directly.

Together with **BobAccessPolicy**, the following **DAXAccessPolicy** gives **BobUserRole** access to the DynamoDB table **Books** even though **BobUserRole** cannot directly access the **Books** table.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {

```

```

    "Sid": "DynamoDBAccessStmt",
    "Effect": "Allow",
    "Action": [
        "dynamodb:GetItem",
        "dynamodb:BatchGetItem",
        "dynamodb:Query",
        "dynamodb:Scan",
        "dynamodb:PutItem",
        "dynamodb:UpdateItem",
        "dynamodb:DeleteItem",
        "dynamodb:BatchWriteItem",
        "dynamodb:DescribeTable",
        "dynamodb:ConditionCheckItem"
    ],
    "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
}
]
}

```

As this example shows, when you configure access control for the user access policy and the DAX cluster access policy, you must fully understand the end-to-end access to ensure that the principle of least privilege is observed. Also ensure that giving a user access to a DAX cluster does not subvert previously established access control policies.

## DAX encryption at rest

Amazon DynamoDB Accelerator (DAX) encryption at rest provides an additional layer of data protection by helping secure your data from unauthorized access to the underlying storage. Organizational policies, industry or government regulations, and compliance requirements might require the use of encryption at rest to protect your data. You can use encryption to increase the data security of your applications that are deployed in the cloud.

With encryption at rest, the data persisted by DAX on disk is encrypted using 256-bit Advanced Encryption Standard, also known as AES-256 encryption. DAX writes data to disk as part of propagating changes from the primary node to read replicas.

DAX encryption at rest automatically integrates with AWS Key Management Service (AWS KMS) for managing the single service default key that is used to encrypt your clusters. If a service default key doesn't exist when you create your encrypted DAX cluster, AWS KMS automatically creates a new AWS managed key for you. This key is used with encrypted clusters that are created in the future. AWS KMS combines secure, highly available hardware and software to provide a key management system scaled for the cloud.

After your data is encrypted, DAX handles the decryption of your data transparently with minimal impact on performance. You don't need to modify your applications to use encryption.

**Note**

DAX does not call AWS KMS for every single DAX operation. DAX only uses the key at the cluster launch. Even if access is revoked, DAX can still access the data until the cluster is shut down. Customer-specified AWS KMS keys are not supported.

DAX encryption at rest is available for the following cluster node types.

Family	Node type
Memory-optimized (R4 and R5)	dax.r4.large
	dax.r4.xlarge

Family	Node type
	dax.r4.2xlarge
	dax.r4.4xlarge
	dax.r4.8xlarge
	dax.r4.16xlarge
	dax.r5.large
	dax.r5.xlarge
	dax.r5.2xlarge
	dax.r5.4xlarge
	dax.r5.8xlarge
	dax.r5.12xlarge
	dax.r5.16xlarge
	dax.r5.24xlarge
General purpose (T2)	dax.t2.small
	dax.t2.medium
General purpose (T3)	dax.t3.small
	dax.t3.medium

**Important**

DAX encryption at rest is not supported for `dax.r3.*` node types.

You cannot enable or disable encryption at rest after a cluster has been created. You must re-create the cluster to enable encryption at rest if it was not enabled at creation.

DAX encryption at rest is offered at no additional cost (AWS KMS encryption key usage charges apply). For information about pricing, see [Amazon DynamoDB pricing](#).

## Enabling encryption at rest using the AWS Management Console

Follow these steps to enable DAX encryption at rest on a table using the console.

### To enable DAX encryption at rest

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, under **DAX**, choose **Clusters**.
3. Choose **Create cluster**.
4. For **Cluster name**, enter a short name for your cluster. Choose the **node type** for all of the nodes in the cluster, and for the cluster size, use **3 nodes**.
5. In **Encryption**, make sure that **Enable encryption** is selected.

## Encryption

### Enable encryption at rest

Protects your data while it is stored, at no additional cost. You cannot change this setting after enabling encryption when possible.

### Enable encryption in transit

Protects your data in transit, at no additional cost. Only the latest versions of the DAX clients support this feature. You cannot change this setting after the cluster is created. We recommend enabling this setting.

6. After choosing the IAM role, subnet group, security groups, and cluster settings, choose **Launch cluster**.

To confirm that the cluster is encrypted, check the cluster details under the **Clusters** pane. Encryption should be **ENABLED**.

## DAX encryption in transit

Amazon DynamoDB Accelerator (DAX) supports encryption in transit of data between your application and your DAX cluster, enabling you to use DAX in applications with stringent encryption requirements.

Regardless of whether or not you choose encryption in transit, traffic between your application and your DAX cluster remains in your Amazon VPC. This traffic is routed to Elastic Network Interfaces with private IPs in your VPC that are attached to the nodes of your cluster. With your VPC as the trust boundary, you have significant control over the security of your data through the use of standard tools like security groups, subnet segmentation with Network ACLs, and VPC flow tracing. DAX encryption in transit adds to this baseline level of confidentiality, ensuring that all requests and responses between the application and the cluster are encrypted by transport level security (TLS), and connections to the cluster can be authenticated by verification of a cluster x509 certificate. Data written to disk by DAX can also be encrypted if you choose [encryption at rest \(p. 744\)](#) when creating your DAX cluster.

Using encryption in transit with DAX is easy. Simply select this option when creating a new cluster, and use a recent version of any of the [DAX clients \(p. 679\)](#) in your application. Clusters that use encryption in transit do not support unencrypted traffic, so there is no chance to misconfigure your application and bypass encryption. The DAX client will use the cluster's x509 certificate to authenticate the identity of the cluster when it establishes connections, ensuring that your DAX requests go where intended. All methods of creating DAX clusters support encryption in transit: the AWS Management Console, AWS CLI, all SDKs, and AWS CloudFormation.

Encryption in transit cannot be enabled on an existing DAX cluster. To use encryption in transit in an existing DAX application, create a new cluster with encryption in transit enabled, shift your application's traffic to it, then delete the old cluster.

# Using service-linked IAM roles for DAX

Amazon DynamoDB Accelerator (DAX) uses AWS Identity and Access Management (IAM) [service-linked roles](#). A service-linked role is a unique type of IAM role that is linked directly to DAX. Service-linked roles are predefined by DAX and include all the permissions that the service requires to call other AWS services on your behalf.

A service-linked role makes setting up DAX easier because you don't have to manually add the necessary permissions. DAX defines the permissions of its service-linked roles, and unless defined otherwise, only DAX can assume its roles. The defined permissions include the trust policy and the permissions policy. That permissions policy can't be attached to any other IAM entity.

You can delete the roles only after first deleting their related resources. This protects your DAX resources because you can't inadvertently remove permission to access the resources.

For information about other services that support service-linked roles, see [AWS Services That Work with IAM](#) in the *IAM User Guide*. Look for the services that have **Yes** in the **Service-linked roles** column. Choose a **Yes** link to view the service-linked role documentation for that service.

## Topics

- [Service-linked role permissions for DAX \(p. 747\)](#)
- [Creating a service-linked role for DAX \(p. 748\)](#)
- [Editing a service-linked role for DAX \(p. 748\)](#)
- [Deleting a service-linked role for DAX \(p. 748\)](#)

## Service-linked role permissions for DAX

DAX uses the service-linked role named `AWSServiceRoleForDAX`. This role allows DAX to call services on behalf of your DAX cluster.

### Important

The `AWSServiceRoleForDAX` service-linked role makes it easier for you to set up and maintain a DAX cluster. However, you must still grant each cluster access to DynamoDB before you can use it. For more information, see [DAX access control \(p. 734\)](#).

The `AWSServiceRoleForDAX` service-linked role trusts the following services to assume the role:

- `dax.amazonaws.com`

The role permissions policy allows DAX to complete the following actions on the specified resources:

- Actions on `ec2`:
  - `AuthorizeSecurityGroupIngress`
  - `CreateNetworkInterface`
  - `CreateSecurityGroup`
  - `DeleteNetworkInterface`
  - `DeleteSecurityGroup`
  - `DescribeAvailabilityZones`
  - `DescribeNetworkInterfaces`
  - `DescribeSecurityGroups`
  - `DescribeSubnets`
  - `DescribeVpcs`

- `ModifyNetworkInterfaceAttribute`
- `RevokeSecurityGroupIngress`

You must configure permissions to allow an IAM entity (such as a user, group, or role) to create, edit, or delete a service-linked role. For more information, see [Service-Linked Role Permissions](#) in the *IAM User Guide*.

#### To allow an IAM entity to create `AWSServiceRoleForDAX` service-linked roles

Add the following policy statement to the permissions for that IAM entity.

```
{  
    "Effect": "Allow",  
    "Action": [  
        "iam:CreateServiceLinkedRole"  
    ],  
    "Resource": "*",  
    "Condition": {"StringLike": {"iam:AWSServiceName": "dax.amazonaws.com"}}  
}
```

## Creating a service-linked role for DAX

You don't need to manually create a service-linked role. When you create a cluster, DAX creates the service-linked role for you.

#### Important

If you were using the DAX service before February 28, 2018, when it began supporting service-linked roles, DAX created the `AWSServiceRoleForDAX` role in your account. For more information, see [A New Role Appeared in My AWS Account](#) in the *IAM User Guide*.

If you delete this service-linked role and then need to create it again, you can use the same process to re-create the role in your account. When you create an instance or a cluster, DAX creates the service-linked role for you again.

## Editing a service-linked role for DAX

DAX does not allow you to edit the `AWSServiceRoleForDAX` service-linked role. After you create a service-linked role, you cannot change the name of the role because various entities might reference the role. However, you can edit the description of the role using IAM. For more information, see [Editing a Service-Linked Role](#) in the *IAM User Guide*.

## Deleting a service-linked role for DAX

If you no longer need to use a feature or service that requires a service-linked role, we recommend that you delete that role. That way you don't have an unused entity that is not actively monitored or maintained. However, you must delete all of your DAX clusters before you can delete the service-linked role.

## Cleaning up a service-linked role

Before you can use IAM to delete a service-linked role, you must first confirm that the role has no active sessions and remove any resources used by the role.

#### To check whether the service-linked role has an active session in the IAM console

1. Sign in to the AWS Management Console and open the IAM console at <https://console.aws.amazon.com/iam/>.

2. In the navigation pane of the IAM console, choose **Roles**. Then choose the name (not the check box) of the **AWSServiceRoleForDAX** role.
3. On the **Summary** page for the selected role, choose the **Access Advisor** tab.
4. On the **Access Advisor** tab, review recent activity for the service-linked role.

**Note**

If you are unsure whether DAX is using the **AWSServiceRoleForDAX** role, you can try to delete the role. If the service is using the role, the deletion fails, and you can view the Regions where the role is being used. If the role is being used, you must delete your DAX clusters before you can delete the role. You can't revoke the session for a service-linked role.

If you want to remove the **AWSServiceRoleForDAX** role, you must first delete all of your DAX clusters.

## Deleting all of your DAX clusters

Use one of these procedures to delete each of your DAX clusters.

### To delete a DAX cluster (console)

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, under **DAX**, choose **Clusters**.
3. Choose **Actions**, and then choose **Delete**.
4. In the **Delete cluster confirmation** box, choose **Delete**.

### To delete a DAX cluster (AWS CLI)

See [delete-cluster](#) in the *AWS CLI Command Reference*.

### To delete a DAX cluster (API)

See [DeleteCluster](#) in the *Amazon DynamoDB API Reference*.

## Deleting the service-linked role

### To manually delete the service-linked role using IAM

Use the IAM console, the IAM CLI, or the IAM API to delete the **AWSServiceRoleForDAX** service-linked role. For more information, see [Deleting a Service-Linked Role](#) in the *IAM User Guide*.

# Accessing DAX across AWS accounts

Imagine that you have a DynamoDB Accelerator (DAX) cluster running in one AWS account (account A), and the DAX cluster needs to be accessible from an Amazon Elastic Compute Cloud (Amazon EC2) instance in another AWS account (account B). In this tutorial, you accomplish this by launching an EC2 instance in account B with an IAM role from account B. You then use temporary security credentials from the EC2 instance to assume an IAM role from account A. Finally, you use the temporary security credentials from assuming the IAM role in account A to make application calls over an Amazon VPC peering connection to the DAX cluster in account A. In order to perform these tasks you will need administrative access in both AWS accounts.

### Topics

- [Set up IAM \(p. 750\)](#)
- [Set up a VPC \(p. 751\)](#)

- [Modify the DAX client to allow cross-account access \(p. 753\)](#)

## Set up IAM

1. Create a text file named `AssumeDaxRoleTrust.json` with the following content, which allows Amazon EC2 to work on your behalf.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Principal": {  
                "Service": "ec2.amazonaws.com"  
            },  
            "Action": "sts:AssumeRole"  
        }  
    ]  
}
```

2. In account B, create a role that Amazon EC2 can use when launching instances.

```
aws iam create-role \  
    --role-name AssumeDaxRole \  
    --assume-role-policy-document file://AssumeDaxRoleTrust.json
```

3. Create a text file named `AssumeDaxRolePolicy.json` with the following content, which allows code running on the EC2 instance in account B to assume an IAM role in account A. Replace `accountA` with the actual ID of account A.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": "sts:AssumeRole",  
            "Resource": "arn:aws:iam::accountA:role/DaxCrossAccountRole"  
        }  
    ]  
}
```

4. Add that policy to the role you just created.

```
aws iam put-role-policy \  
    --role-name AssumeDaxRole \  
    --policy-name AssumeDaxRolePolicy \  
    --policy-document file://AssumeDaxRolePolicy.json
```

5. Create an instance profile to allow instances to use the role.

```
aws iam create-instance-profile \  
    --instance-profile-name AssumeDaxInstanceProfile
```

6. Associate the role with the instance profile.

```
aws iam add-role-to-instance-profile \  
    --instance-profile-name AssumeDaxInstanceProfile \  
    --role-name AssumeDaxRole
```

7. Create a text file named `DaxCrossAccountRoleTrust.json` with the following content, which allows account B to assume an account A role. Replace `accountB` with the actual ID of account B.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Principal": {
                "AWS": "arn:aws:iam::accountB:role/AssumeDaxRole"
            },
            "Action": "sts:AssumeRole"
        }
    ]
}
```

8. In account A, create the role that account B can assume.

```
aws iam create-role \
--role-name DaxCrossAccountRole \
--assume-role-policy-document file://DaxCrossAccountRoleTrust.json
```

9. Create a text file named `DaxCrossAccountPolicy.json` that allows access to the DAX cluster. Replace `dax-cluster-arn` with the correct Amazon Resource Name (ARN) of your DAX cluster.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Effect": "Allow",
            "Action": [
                "dax:GetItem",
                "dax:BatchGetItem",
                "dax:Query",
                "dax:Scan",
                "dax:PutItem",
                "dax:UpdateItem",
                "dax:DeleteItem",
                "dax:BatchWriteItem",
                "dax:ConditionCheckItem"
            ],
            "Resource": "dax-cluster-arn"
        }
    ]
}
```

10. In account A, add the policy to the role.

```
aws iam put-role-policy \
--role-name DaxCrossAccountRole \
--policy-name DaxCrossAccountPolicy \
--policy-document file://DaxCrossAccountPolicy.json
```

## Set up a VPC

1. Find the subnet group of account A's DAX cluster. Replace `cluster-name` with the name of the DAX cluster that account B must access.

```
aws dax describe-clusters \
```

```
--cluster-name cluster-name
--query 'Clusters[0].SubnetGroup'
```

- Using that *subnet-group*, find the cluster's VPC.

```
aws dax describe-subnet-groups \
--subnet-group-name subnet-group \
--query 'SubnetGroups[0].VpcId'
```

- Using that *vpc-id*, find the VPC's CIDR.

```
aws ec2 describe-vpcs \
--vpc vpc-id \
--query 'Vpcs[0].CidrBlock'
```

- From account B, create a VPC using a different, non-overlapping CIDR than the one found in the previous step. Then, create at least one subnet. You can use either the [VPC creation wizard](#) in the AWS Management Console or the [AWS CLI](#).
- From account B, request a peering connection to the account A VPC as described in [Creating and accepting a VPC peering connection](#). From account A, accept the connection.
- From account B, find the new VPC's routing table. Replace *vpc-id* with the ID of the VPC you created in account B.

```
aws ec2 describe-route-tables \
--filters 'Name=vpc-id,Values=vpc-id' \
--query 'RouteTables[0].RouteTableId'
```

- Add a route to send traffic destined for account A's CIDR to the VPC peering connection. Remember to replace each *user input placeholder* with the correct values for your accounts.

```
aws ec2 create-route \
--route-table-id accountB-route-table-id \
--destination-cidr accountA-vpc-cidr \
--vpc-peering-connection-id peering-connection-id
```

- From account A, find the DAX cluster's route table using the *vpc-id* you found previously.

```
aws ec2 describe-route-tables \
--filters 'Name=vpc-id, Values=accountA-vpc-id' \
--query 'RouteTables[0].RouteTableId'
```

- From account A, add a route to send traffic destined for account B's CIDR to the VPC peering connection. Replace each *user input placeholder* with the correct values for your accounts.

```
aws ec2 create-route \
--route-table-id accountA-route-table-id \
--destination-cidr accountB-vpc-cidr \
--vpc-peering-connection-id peering-connection-id
```

- From account B, launch an EC2 instance in the VPC that you created earlier. Give it the `AssumeDaxInstanceProfile`. You can use either the [launch wizard](#) in the AWS Management Console or the [AWS CLI](#). Take note of the instance's security group.
- From account A, find the security group used by the DAX cluster. Remember to replace *cluster-name* with the name of your DAX cluster.

```
aws dax describe-clusters \
--cluster-name cluster-name \
--query 'Clusters[0].SecurityGroups[0].SecurityGroupIdentifier'
```

12. Update the DAX cluster's security group to allow inbound traffic from the security group of the EC2 instance you created in account B. Remember to replace the *user input placeholders* with the correct values for your accounts.

```
aws ec2 authorize-security-group-ingress \
--group-id accountA-security-group-id \
--protocol tcp \
--port 8111 \
--source-group accountB-security-group-id \
--group-owner accountB-id
```

At this point, an application on account B's EC2 instance is able to use the instance profile to assume the `arn:aws:iam::accountA-id:role/DaxCrossAccountRole` role and use the DAX cluster.

## Modify the DAX client to allow cross-account access

### Note

AWS Security Token Service (AWS STS) credentials are temporary credentials. Some clients handle refreshing automatically, while others require additional logic to refresh the credentials. We recommend that you follow the guidance of the appropriate documentation.

#### Java

This section helps you modify your existing DAX client code to allow cross-account DAX access. If you don't have DAX client code already, you can find working code examples in the [Java and DAX \(p. 684\)](#) tutorial.

1. Add the following imports.

```
import com.amazonaws.auth.STSSummarySessionCredentialsProvider;
import com.amazonaws.services.securitytoken.AWSIdentityTokenService;
import com.amazonaws.services.identitytoken.AWSIdentityTokenServiceClientBuilder;
```

2. Get a credentials provider from AWS STS and create a DAX client object. Remember to replace each *user input placeholder* with the correct values for your accounts.

```
AWSIdentityTokenService awsIdentityTokenService =
AWSIdentityTokenServiceClientBuilder
.standard()
.withRegion(region)
.build();

STSSummarySessionCredentialsProvider credentials = new
STSSummarySessionCredentialsProvider.Builder("arn:aws:iam::accountA:role/
RoleName", "TryDax")
.withIdentityTokenService(awsIdentityTokenService)
.build();

DynamoDB client = AmazonDAXClientBuilder.standard()
.withRegion(region)
.withEndpointConfiguration(dax_endpoint)
.withCredentials(credentials)
.build();
```

## .NET

This section helps you modify your existing DAX client code to allow cross-account DAX access. If you don't have DAX client code already, you can find working code examples in the [.NET and DAX \(p. 689\)](#) tutorial.

1. Add the [AWSSDK.SecurityToken](#) NuGet package to the solution.

```
<PackageReference Include="AWSSDK.SecurityToken" Version="latest version" />
```

2. Use the `SecurityToken` and `SecurityToken.Model` packages.

```
using Amazon.SecurityToken;
using Amazon.SecurityToken.Model;
```

3. Get temporary credentials from `AmazonSimpleTokenService` and create a `ClusterDaxClient` object. Remember to replace each `user input placeholder` with the correct values for your accounts.

```
IAmazonSecurityTokenService sts = new AmazonSecurityTokenServiceClient();

var assumeRoleResponse = sts.AssumeRole(new AssumeRoleRequest
{
    RoleArn = "arn:aws:iam::accountA:role/RoleName",
    RoleSessionName = "TryDax"
});

Credentials credentials = assumeRoleResponse.Credentials;

var clientConfig = new DaxClientConfig(dax_endpoint, port)
{
    AwsCredentials = assumeRoleResponse.Credentials
};

var client = new ClusterDaxClient(clientConfig);
```

## Go

This section helps you modify your existing DAX client code to allow cross-account DAX access. If you don't have DAX client code already, you can find [working code examples on GitHub](#).

1. Import the AWS STS and session packages.

```
import (
    "github.com/aws/aws-sdk-go/aws/session"
    "github.com/aws/aws-sdk-go/service/sts"
    "github.com/aws/aws-sdk-go/aws/credentials/stscreds"
)
```

2. Get temporary credentials from `AmazonSimpleTokenService` and create a DAX client object. Remember to replace each `user input placeholder` with the correct values for your accounts.

```
sess, err := session.NewSession(&aws.Config{
    Region: aws.String(region)),
}
if err != nil {
    return nil, err
}
```

```

stsClient := sts.New(sess)
arp := &stscreds.AssumeRoleProvider{
    Duration:    900 * time.Second,
    ExpiryWindow: 10 * time.Second,
    RoleARN:      "arn:aws:iam::accountA:role/role_name",
    Client:       stsClient,
    RoleSessionName: "session_name",
}
cfg := dax.DefaultConfig()

cfg.HostPorts = []string{dax_endpoint}
cfg.Region = region
cfg.Credentials = credentials.NewCredentials(arp)
daxClient := dax.New(cfg)

```

### Python

This section helps you modify your existing DAX client code to allow cross-account DAX access. If you don't have DAX client code already, you can find working code examples in the [Python and DAX \(p. 705\)](#) tutorial.

1. Import boto3.

```
import boto3
```

2. Get temporary credentials from sts and create an AmazonDaxClient object. Remember to replace each *user input placeholder* with the correct values for your accounts.

```

sts = boto3.client('sts')
stsresponse =
    sts.assume_role(RoleArn='arn:aws:iam::accountA:role/RoleName', RoleSessionName='tryDax')
credentials = botocore.session.get_session()['Credentials']

dax = amazondax.AmazonDaxClient(session, region_name=region,
    endpoints=[dax_endpoint], aws_access_key_id=credentials['AccessKeyId'],
    aws_secret_access_key=credentials['SecretAccessKey'],
    aws_session_token=credentials['SessionToken'])
client = dax

```

### Node.js

This section helps you modify your existing DAX client code to allow cross-account DAX access. If you don't have DAX client code already, you can find working code examples in the [Node.js and DAX \(p. 697\)](#) tutorial. Remember to replace each *user input placeholder* with the correct values for your accounts.

```

const AmazonDaxClient = require('amazon-dax-client');
const AWS = require('aws-sdk');
const region = 'region';
const endpoints = [daxEndpoint1, ...];

const getCredentials = async() => {
    return new Promise((resolve, reject) => {
        const sts = new AWS.STS();
        const roleParams = {
            RoleArn: 'arn:aws:iam::accountA:role/RoleName',
            RoleSessionName: 'tryDax',
        };
        sts.assumeRole(roleParams, (err, session) => {

```

```
        if(err) {
          reject(err);
        } else {
          resolve({
            accessKeyId: session.Credentials.AccessKeyId,
            secretAccessKey: session.Credentials.SecretAccessKey,
            sessionToken: session.Credentials.SessionToken,
          });
        }
      });
    });
  };
}

const createDaxClient = async() => {
  const credentials = await getCredentials();
  const daxClient = new AmazonDaxClient({endpoints: endpoints, region: region,
  accessKeyId: credentials.accessKeyId, secretAccessKey: credentials.secretAccessKey,
  sessionToken: credentials.sessionToken});
  return new AWS.DynamoDB.DocumentClient({service: daxClient});
};

createDaxClient().then((client) => {
  client.get(...);
  ...
}).catch((error) => {
  console.log('Caught an error: ' + error);
});
```

## DAX cluster sizing guide

This guide provides advice for choosing an appropriate Amazon DynamoDB Accelerator (DAX) cluster size and node type for your application. These instructions guide you through the steps of estimating your application's DAX traffic, selecting a cluster configuration, and testing it.

If you have an existing DAX cluster and want to evaluate whether it has the appropriate number and size of nodes, please refer to [Scaling a DAX cluster \(p. 714\)](#).

### Topics

- [Overview \(p. 756\)](#)
- [Estimating traffic \(p. 757\)](#)
- [Load testing \(p. 757\)](#)

## Overview

It's important to scale your DAX cluster appropriately for your workload, whether you're creating a new cluster or maintaining an existing cluster. As time goes on and your application's workload changes, you should periodically revisit your scaling decisions to make sure that they are still appropriate.

The process typically follows these steps:

1. **Estimating traffic.** In this step, you make predictions about the volume of traffic that your application will send to DAX, the nature of the traffic (read vs. write operations), and the expected cache hit rate.
2. **Load testing.** In this step, you create a cluster and send traffic to it mirroring your estimates from the previous step. Repeat this step until you find a suitable cluster configuration.
3. **Production monitoring.** While your application is using DAX in production, you should [monitor the cluster \(p. 718\)](#) to continuously validate that it is still scaled correctly as your workload changes over time.

## Estimating traffic

There are three main factors that characterize a typical DAX workload:

- Cache hit rate
- [Read capacity units \(p. 287\)](#) (RCUs) per second
- [Write capacity units \(p. 288\)](#) (WCUs) per second

### Estimating cache hit rate

If you already have a DAX cluster, you can use the `ItemCacheHits` and `ItemCacheMisses` [Amazon CloudWatch metrics \(p. 720\)](#) to determine the cache hit rate. The cache hit rate is equal to  $\text{ItemCacheHits} / (\text{ItemCacheHits} + \text{ItemCacheMisses})$ . If your workload includes `Query` or `Scan` operations, you should also look at the `QueryCacheHits`, `QueryCacheMisses`, `ScanCacheHits`, and `ScanCacheMisses` metrics. Cache hit rates vary from one application to another and are heavily influenced by the cluster's Time to Live (TTL) setting. Typical hit rates for applications using DAX are 85–95 percent.

### Estimating read and write capacity units

If you already have DynamoDB tables for your application, look at the `ConsumedReadCapacityUnits` and `ConsumedWriteCapacityUnits` [CloudWatch metrics \(p. 720\)](#). Use the `Sum` statistic and divide by the number of seconds in the period.

If you also already have a DAX cluster, remember that the DynamoDB `ConsumedReadCapacityUnits` metric only accounts for cache misses. So, to get an idea of the read capacity units per second handled by your DAX cluster, divide the number by your cache miss rate (that is,  $1 - \text{cache hit rate}$ ).

If you don't already have a DynamoDB table, see the documentation about [read capacity units \(p. 287\)](#) and [write capacity units \(p. 288\)](#) to estimate your traffic based on your application's estimated request rate, items accessed per request, and item size.

When making traffic estimates, plan for future growth and for expected and unexpected peaks to ensure that your cluster has enough headroom for traffic increases.

## Load testing

The next step after estimating traffic is to test the cluster configuration under load.

1. For your initial load test, we recommend that you start with the `dax.r4.large` node type, the lowest-cost fixed performance, memory-optimized node type.
2. A fault-tolerant cluster requires at least three nodes, spread across three Availability Zones. In this case, if an Availability Zone becomes unavailable, the effective number of Availability Zones is reduced by one-third. For your initial load test, we recommend that you start with a two-node cluster, which simulates the failure of one Availability Zone in a three-node cluster.
3. Drive sustained traffic (as estimated in the previous step) to your test cluster for the duration of the load test.
4. Monitor the performance of the cluster during the load test.

Ideally, the traffic profile that you drive during the load test should be as similar as possible to your application's real traffic. This includes the distribution of operations (for example, 70 percent `GetItem`, 25 percent `Query`, and 5 percent `PutItem`), the request rate for each operation, the number of items accessed per request, and the distribution of item sizes. To achieve a cache hit rate similar to your application's expected cache hit rate, pay close attention to the distribution of keys in your test traffic.

**Note**

Be careful when load testing T2 node types (`dax.t2.small` and `dax.t2.medium`). T2 node types provide [burstable CPU performance](#) that varies over time depending on the node's CPU credit balance. A DAX cluster running on T2 nodes might appear to be operating normally, but if any node is bursting above the [baseline performance](#) of its instance, the node is spending its accrued CPU credit balance. When the credit balance runs low, [performance is gradually lowered](#) to the baseline performance level.

[Monitor your DAX cluster \(p. 718\)](#) during the load test to determine whether the node type that you're using for the load test is the right node type for you. In addition, during a load test, you should monitor your request rate and cache hit rate to ensure that your test infrastructure is actually driving the amount of traffic you intend.

If load testing indicates that the selected cluster configuration can't sustain your application's workload, we recommend [switching to a larger node type \(p. 714\)](#), especially if you see high CPU utilization on the primary node in the cluster, high eviction rates, or high cache memory utilization. If hit rates are consistently high, and the ratio of read to write traffic is high, you may want to consider [adding more nodes to your cluster \(p. 714\)](#). Refer to [Scaling a DAX cluster \(p. 714\)](#) for additional guidance on when to use a larger node type (vertical scaling) or add more nodes (horizontal scaling).

You should repeat your load test after making changes to your cluster configuration.

## DAX API reference

For more information about Amazon DynamoDB Accelerator (DAX) APIs, see [Amazon DynamoDB accelerator](#) in the Amazon DynamoDB API Reference.

# NoSQL Workbench for DynamoDB

NoSQL Workbench for Amazon DynamoDB is a cross-platform client-side GUI application for modern database development and operations and is available for Windows, macOS, and Linux. NoSQL Workbench is a unified visual IDE tool that provides data modeling, data visualization, and query development features to help you design, create, query, and manage DynamoDB tables.

## Data Modeling

With NoSQL Workbench for DynamoDB, you can build new data models from, or design models based on, existing data models that satisfy your application's data access patterns. You can also import and export the designed data model at the end of the process. For more information, see [Building data models with NoSQL Workbench \(p. 760\)](#).

## Data Visualization

The data model visualizer provides a canvas where you can map queries and visualize the access patterns (facets) of the application without having to write code. Every facet corresponds to a different access pattern in DynamoDB. You can manually add data to your data model. For more information, see [Visualizing data access patterns \(p. 773\)](#).

## Operation Building

NoSQL Workbench provides a rich graphical user interface for you to develop and test queries. You can use the *operation builder* to view, explore, and query datasets. You can also use the structured operation builder to build and perform data plane operations. It supports projection and condition expression, and lets you generate sample code in multiple languages. For more information, see [Exploring datasets and building operations with NoSQL Workbench \(p. 786\)](#).

## Topics

- [Download NoSQL Workbench \(p. 759\)](#)
- [Building data models with NoSQL Workbench \(p. 760\)](#)
- [Visualizing data access patterns \(p. 773\)](#)
- [Exploring datasets and building operations with NoSQL Workbench \(p. 786\)](#)
- [Sample data models for NoSQL Workbench \(p. 808\)](#)
- [Release history for NoSQL Workbench \(p. 810\)](#)

# Download NoSQL Workbench

Follow these instructions to download and install NoSQL Workbench for Amazon DynamoDB.

## To download and install NoSQL Workbench

1. Download the appropriate version of NoSQL Workbench for your operating system.

Operating system	Download link	Checksum link
macOS	<a href="#">Download for macOS</a>	<a href="#">Checksum</a>
Windows	<a href="#">Download for Windows</a>	<a href="#">Checksum</a>
Linux*	<a href="#">Download for Linux</a>	<a href="#">Checksum</a>

- \* NoSQL Workbench supports Ubuntu 12.04, Fedora 21, and Debian 8 or any newer versions of these Linux distributions.
- 2. Start the application that you downloaded, and follow the onscreen instructions to install NoSQL Workbench.

## Building data models with NoSQL Workbench

You can use the data modeler tool in NoSQL Workbench for Amazon DynamoDB to build new data models, or to design models based on existing data models that satisfy your applications' data access patterns. The data modeler includes a few sample data models to help you get started.

### Topics


- [Creating a new data model \(p. 760\)](#)
- [Importing an existing data model \(p. 766\)](#)
- [Exporting a data model \(p. 769\)](#)
- [Editing an existing data model \(p. 771\)](#)

## Creating a new data model


Follow these steps to create a new data model in Amazon DynamoDB using NoSQL Workbench.

### To create a new data model


1. Open NoSQL Workbench, and in the navigation pane on the left side, choose the **Data modeler** icon.



2. Choose **Create data model**.



3. Enter a name, author and description for the data model, and then choose **Create**.
4. Choose **Add table**.



For more information about tables, see [Working with tables in DynamoDB](#).

5. Specify the following:
  - **Table name** — Enter a unique name for the table.
  - **Partition key** — Enter a partition key name and specify its type.
  - If you want to add a sort key:
    1. Select **Add sort key**.
    2. Specify the sort key name and its type.
    - 3.

\* Table name

Employee



Primary key attributes

\* Partition key

LoginAlias

String



Add sort key

6. To add other attributes, do the following for each attribute:

1. Choose **Add other attribute**.
2. Specify the attribute name and type.

Other attributes

\* Attribute name

FirstName

String



\* Attribute name

LastName

String



\* Attribute name

ManagerLoginAlias

String



\* Attribute name

Designation

String



\* Attribute name

Skills

String Set



+ Add other attribute

7. Add a facet:

**Note**

Facets represent an application's different data access patterns for DynamoDB.

- Select **Add facets**.
- Choose **Add facet**.

+ Add other attribute

Add facets ⓘ

ⓘ Facet is a virtual construct in NoSQL Workbench for Amazon DynamoDB, and not a functional construct in DynamoDB itself.

ⓘ No facet added

+ Add facet

- Specify the following:
  - The **Facet name**.
  - A **Partition key alias**.
  - A **Sort key alias**.
  - Choose the **Other attributes** that are part of this facet.

Choose **Add facet**.

Add facets ⓘ

ⓘ Facet is a virtual construct in NoSQL Workbench for Amazon DynamoDB, and not a functional construct in DynamoDB itself.

ⓘ No facet added

Add facet

\* Facet name SongDetails

\* Partition key alias SongId

\* Sort key alias Metadata

Other attributes Title ⓘ Artist ⓘ TotalDownloads ⓘ

Cancel

Add facet

Repeat this step if you want to add more facets.

8. If you want to add a global secondary index, choose **Add global secondary index**.

Specify the **Global secondary index name**, **Partition key attribute**, and **Projection type**.

Global secondary indexes

Global secondary index name

\* Partition key FirstName

Add sort key

\* Sort key LastName

Projection type ALL

For more information about working with global secondary indexes in DynamoDB, see [Global secondary indexes](#).

9. By default, your table will use provisioned capacity mode with auto scaling enabled on both read and write capacity. If you want to change these settings, uncheck "Default settings" under **Capacity settings**.

Capacity settings

Default settings

The default settings use provisioned capacity mode with auto scaling enabled on both read and write capacity.

Select your desired capacity mode, read and write capacity, and auto scaling IAM role (if applicable).

### Capacity settings

Default settings

 The default settings use provisioned capacity mode with auto scaling enabled on both read and write capacity.

#### Capacity mode

Provisioned 

On-demand 

#### Provisioned read capacity

Enable auto scaling 

\* Minimum capacity units

1

\* Maximum capacity units

10

\* Target utilization (%)

70

#### Provisioned write capacity

Enable auto scaling 

\* Minimum capacity units

1

\* Maximum capacity units

10

\* Target utilization (%)

70

#### Auto scaling IAM role

\* Role name


API Version 2012-08-10

765

This service-linked role is required to enable auto scaling through NoSQL Workbench. If the role does not already exist in your account and you have the required AWS Identity and

For more information about DynamoDB capacity settings, see [Read/write capacity mode \(p. 17\)](#).

10. Choose **Add table definition**.




For more information about the `CreateTable` API operation, see [CreateTable](#) in the *Amazon DynamoDB API Reference*.

## Importing an existing data model


You can use NoSQL Workbench for Amazon DynamoDB to build a data model by importing and modifying an existing model. You can import data models in either NoSQL Workbench model format or in [AWS CloudFormation JSON template format](#).

### To import a data model


1. In NoSQL Workbench, in the navigation pane on the left side, choose the **Data modeler** icon.




2. Hover your mouse over **Import data model**.



In the dropdown list, choose whether the model you want to import is in NoSQL Workbench model format or CloudFormation JSON template format. If you have an existing data model open in NoSQL Workbench, you'll have the option to import a CloudFormation template into the current model.



3. Choose a model to import.



4. If the model you're importing is in CloudFormation template format, you'll see a list of tables to be imported and have an opportunity to specify a data model name, author, and description.

## Create data model for Amazon DynamoDB

Only CloudFormation resources related to DynamoDB: tables and any related application auto scaling, *i* will be imported. Some fields within these resources are not supported by NoSQL Workbench and will also not be imported, including LocalSecondaryIndexes, RoleARN, and PolicyName.

### Successfully imported tables (1)

 Employee

### Data model information

\* Name

Enter data model name

Author

Enter author name

Description

Describe this data model

[Cancel](#)


[Create](#)

## Exporting a data model


After you create a data model using NoSQL Workbench for Amazon DynamoDB, you can save and export the model in either NoSQL Workbench model format or [AWS CloudFormation JSON template format](#).

### To export a data model


1. In NoSQL Workbench, in the navigation pane on the left side, choose the **Data modeler** icon.




2. Hover your mouse over **Export data model**.



In the dropdown list, choose whether to export your data model in NoSQL Workbench model format or CloudFormation JSON template format.




3. Choose a location to save your model.



## Editing an existing data model

### To edit an existing model

1. In NoSQL Workbench, in the navigation pane on the left side, choose the **Data modeler** button.



2. Choose the table you wish to edit.

**Choose Edit.**

3. Make the needed edits, and then choose **Save edits**.

**To manually edit an existing model and add a facet**

1. Export your model. For more information, see [Exporting a data model \(p. 769\)](#).
2. Open the exported file in an editor.
3. Locate the `DataModel` Object for the table you want to create a facet for.

Add a `TableFacets` array representing all the facets for the table.

For each facet add an object to the `TableFacets` array. Each array element has the following properties:

- `FacetName`: A name for your facet. This value must be unique across the model.
- `PartitionKeyAlias` — A friendly name for the table's partition key. This alias is displayed when you view the facet in NoSQL Workbench.
- `SortKeyAlias` — A friendly name for the table's sort key. This alias is displayed when you view the facet in NoSQL Workbench. This property is not needed if the table has no sort key defined.
- `NonKeyAttributes` — An array of attribute names that are needed for the access pattern. These names must map to the attribute names that are defined for the table.

```
{
  "modelName": "Music Library Data Model",
  "dataModel": [
    {
      "tableName": "Songs",
      "keyAttributes": {
        "partitionKey": {
          "attributeName": "Id",
          "attributeType": "S"
        },
        "sortKey": {
          "attributeName": "Metadata",
          "attributeType": "S"
        }
      },
      "nonKeyAttributes": [
        {
          "attributeName": "DownloadMonth",
          "attributeType": "S"
        },
        {
          "attributeName": "TotalDownloadsInMonth",
          "attributeType": "S"
        }
      ]
    }
  ]
}
```

```

    },
    {
        "AttributeName": "Title",
        "AttributeType": "S"
    },
    {
        "AttributeName": "Artist",
        "AttributeType": "S"
    },
    {
        "AttributeName": "TotalDownloads",
        "AttributeType": "S"
    },
    {
        "AttributeName": "DownloadTimestamp",
        "AttributeType": "S"
    }
],
"TableFacets": [
    {
        "FacetName": "SongDetails",
        "KeyAttributeAlias": {
            "PartitionKeyAlias": "SongId",
            "SortKeyAlias": "Metadata"
        },
        "NonKeyAttributes": [
            "Title",
            "Artist",
            "TotalDownloads"
        ]
    },
    {
        "FacetName": "Downloads",
        "KeyAttributeAlias": {
            "PartitionKeyAlias": "SongId",
            "SortKeyAlias": "Metadata"
        },
        "NonKeyAttributes": [
            "DownloadTimestamp"
        ]
    }
]
}

```

4. You can now import the modified model into NoSQL Workbench. For more information, see [Importing an existing data model \(p. 766\)](#).

## Visualizing data access patterns

You can use the visualizer tool in NoSQL Workbench for Amazon DynamoDB to map queries and visualize different access patterns (known as *facets*) of an application. Every facet corresponds to a different access pattern in DynamoDB. You can also manually add data to your data model or import data from MySQL.

### Topics

- [Adding sample data to a data model \(p. 774\)](#)
- [Importing sample data from a CSV file \(p. 775\)](#)
- [Viewing data access patterns \(p. 776\)](#)
- [Viewing all tables in a data model using aggregate view \(p. 780\)](#)

- [Committing a data model to DynamoDB \(p. 781\)](#)


## Adding sample data to a data model

By adding sample data to your model, you can display data when visualizing the model and its various data access patterns, or *facets*.

Follow these steps to add sample data to a data model using NoSQL Workbench for Amazon DynamoDB.

### To add sample data

1. In the navigation pane on the left side, choose the **visualizer** icon.



2. In the visualizer, choose **Update** next to the table name.

The screenshot shows the Visualizer interface on the right. It has a sidebar with the same navigation options as the first screenshot. On the main screen, it displays a "Data model" dropdown set to "Music Library Data Model" with up and down arrows below it. Below that, there is a table row for "Songs" with an "Update" button to its right, which is also highlighted with a red rectangular box.

**3. Choose Add Data.**

[FACET] SongDetails				
Add data <span style="border: 1px solid red; padding: 2px;"> </span> Edit data				
SongId (Partition key) : String	Metadata (Sort key) : String	Title : String	Artist : String	TotalDownloads : String

**4. Enter the sample data into the empty textboxes, and choose **Add new row** to add additional rows. When done choose **Save**.**

[FACET] SongDetails				
Cancel <span style="border: 1px solid red; padding: 2px;"> </span> Save				
SongId (Partition key) : String	Metadata (Sort key) : String	Title : String	Artist : String	TotalDownloads : String
12	ACME Album	ACME Best Song	ACME	4
<span style="border: 1px solid red; padding: 2px;">+ Add new row</span>				

## Importing sample data from a CSV file


If you have preexisting sample data in a CSV file, you can import it into NoSQL Workbench. This enables you to quickly populate your model with sample data without having to enter it line by line.

The column names in the CSV file must match the attribute names in your data model, but they do not need to be in the same order. For example, if your data model has attributes called `LoginAlias`, `FirstName`, and `LastName`, your CSV columns could be `LastName`, `FirstName`, and `LoginAlias`.


Data import from a CSV file is limited to 150 rows at a time.

### To import data from a CSV file into NoSQL Workbench

1. In the navigation pane on the left side, choose the **visualizer** icon.



2. In the visualizer, choose **Update** next to the table name.



3. Choose **Import CSV file**.

[TABLE] Songs							
<a href="#">Import CSV file</a> <a href="#">Add data</a> <a href="#">Edit data</a>							
Id (Partition key) : String	Metadata (Sort key) : String	DownloadMonth : String	TotalDownloadsIn Month : String	Title : String	Artist : String	TotalDownloads : String	DownloadTimestamp : String
1	Month-01-2018	01-2018	3				
2	Month-01-2018	01-2018	4				

4. Select your CSV file and click **Open**. The data in the CSV file will be appended to your table.

**Note**

If your CSV file contains one or more rows that have the same keys as items already in your table, you will have the option of overwriting the existing items or appending them to the end of the table. If you choose to append the items, the suffix "-Copy" will be added to each duplicate item's key to differentiate the duplicate items from the items that were already in the table.

## Viewing data access patterns

In NoSQL Workbench, *facets* represent an application's different data access patterns for Amazon DynamoDB. Facets give you a way to view a subset of the data in a table, without having to see records that don't meet the constraints of the facet. Facets are considered a visual data modeling tool, and don't exist as a usable construct in DynamoDB, as they are purely an aid to modeling of access patterns.

### Import sample data model


1. On the left, choose **Amazon DynamoDB**
2. In the Sample data models section, hover your mouse over Music Library Data Model and choose **Import**

The screenshot shows the AWS NoSQL Workbench interface. On the left, a navigation pane lists several options: AWS database catalog, Amazon DynamoDB (highlighted with a red box), Data modeler, Visualizer (highlighted with a red box), Operation builder, Documentation (with a link icon), and Email us (with a link icon). The main content area is titled "Sample data models". It displays a table with two columns: "Data model name" and "Skill level". The data includes:

Data model name	Skill level
AWS Discussion Forum Data Model	Introductory
Bookmarks Data Model	Introductory
Employee Data Model	Introductory
Ski Resort Data Model	Introductory
Credit Card Offers Data Model	Advanced
Music Library Data Model	Advanced

A blue "Import" button is located at the bottom right of the table.


3. In the navigation pane on the left side, choose the **visualizer** icon.



4. Choose the Songs table to expand it. You'll be shown an aggregate view of your data.

The screenshot shows the AWS NoSQL Workbench interface. On the left, the navigation bar includes options like AWS database catalog, Amazon DynamoDB, Data modeler, Visualizer (which is selected and highlighted with a red box), Operation builder, Documentation, and Email us. The main area is titled "Visualizer" and shows a "Data model" section with "Music Library Data Model" selected. Below this is a "Songs" facet entry with an "Update" dropdown arrow. A large "Aggregate view" panel on the right displays data from a "Songs" table with a Global Secondary Index (GSI) named "DownloadsByMonth". The table has columns for Primary key (Partition key: Id, Sort key: Metadata), Attributes (Title, Artist, TotalDownloads), and Details (DownloadTimestamp, Month-01-2018). An "Export to PNG" button is visible in the top right corner of the aggregate view panel.

5. Choose **Facets** drop-down arrow to expand the available facets
6. Choose the SongDetails facet to vizualize the data with the SongDetails facet applied



The screenshot shows the AWS NoSQL Workbench Visualizer interface. On the left, a navigation pane lists options: AWS database catalog, Amazon DynamoDB, Data modeler, Visualizer (which is selected and highlighted in blue), Operation builder, Documentation, and Email us. The main area is titled '[FACET] SongDetails'. It displays a table with the following schema and data:

SongId (Partition key) :	Metadata (Sort key) :	Title : String	Artist : String	TotalDownloads :
String	String	String	String	String
1	Details	Wild Love	Argyboots	3
2	Details	Example Song Title	Jorge Souza	4

At the bottom of the main area, there are buttons for 'Import CSV file', 'Add data', and 'Edit data'.

You can also edit the facet definitions using the Data Modeler. For more information, see [Editing an existing data model \(p. 771\)](#).


## Viewing all tables in a data model using aggregate view

The aggregate view in NoSQL Workbench for Amazon DynamoDB represents all the tables in a data model. For each table, the following information appears:

- Table column names.
- Sample data.
- All global secondary indexes that are associated with the table. The following information is displayed for each index:
  - Index column names
  - Sample data

### To view all table information

1. In the navigation pane on the left side, choose the **visualizer** icon.



2. In the visualizer, choose **Aggregate view**.

The screenshot shows the "Visualizer" interface with a sidebar on the left containing icons for "AWS database catalog", "Amazon DynamoDB", "Data modeler", "Visualizer" (highlighted with a red box), "Operation builder", "Documentation", and "Email us". The main area is titled "Aggregate view" and contains a table with the following data:

Primary key	Attributes			
	Partition key: ForumName	Threads	Messages	Views
Amazon DynamoDB	Category	Threads	Messages	Views
Amazon Web Services	2	4	1000	
Amazon Simple Notification Service	Category	Threads	Messages	Views
Amazon Web Services	5	5	1200	
Amazon Simple Queue Service	Category	Threads	Messages	Views
Amazon Web Services	9	6	1300	
Amazon MQ	Category	Threads	Messages	Views
Amazon Web Services	22	7	1400	
Amazon EMR	Category	Threads	Messages	Views

## Committing a data model to DynamoDB


When you are satisfied with your data model, you can commit the model to Amazon DynamoDB.

### Note


- This action results in the creation of server-side resources in AWS for the tables and global secondary indexes represented in the data model.
- Tables are created with the following characteristics:
  - Auto scaling is set to 70 percent target utilization.
  - Provisioned capacity is set to 5 read capacity units and 5 write capacity units.
- Global secondary indexes are created with provisioned capacity of 10 read capacity units and 5 write capacity units.

### To commit the data model to DynamoDB

1. In the navigation pane on the left side, choose the **visualizer** icon.



2. Choose **Commit to DynamoDB**.



3. Choose an already existing connection, or create a new connection by choosing the **Add new remote connection** tab.

- To add a new connection, specify the following information:
  - **Account Alias**
  - **AWS Region**
  - **Access key ID**
  - **Secret access key**

For more information about how to obtain the access keys, see [Getting an AWS access key](#).

- You can optionally specify the following:
  - **Session token**
  - **IAM role ARN**
- If you don't want to sign up for a free tier account, and prefer to use [DynamoDB local \(downloadable version\)](#):
  1. Choose the **Add a new DynamoDB local connection** tab

2. Specify the **Connection name** and **Port**.
4. Choose **Commit**.

## Commit to Amazon DynamoDB

On this page, you create server-side resources such as tables and global secondary indexes for the selected data model. If a table that uses auto scaling is being committed and a failure occurs while enabling auto scaling, table creation and item insertion will still be attempted and can be completed successfully. If the table has been created but auto scaling has not been enabled, use the DynamoDB console to enable auto scaling manually for the created table. If a table with auto scaling is being committed to DynamoDB local, auto scaling will not be enabled because it is not supported.

Use saved connections

Add a new remote connection

Add a new DynamoDB local connection

To use DynamoDB, you must have an AWS account. You can use AWS Identity and Access Management (IAM) roles and temporary security credentials to grant users in your AWS account access to your DynamoDB resources from NoSQL Workbench.

[Setting up DynamoDB](#)

Connection name

\* AWS Region

AWS Region

\* Access key ID

AWS access key ID

\* Secret access key

AWS secret access key

Session token

AWS session token

IAM role ARN

IAM role ARN

Persist connection

If you select this check box, AWS connection secrets will be persisted in

/Users/[REDACTED]/.aws/credentials

[Cancel](#)

[Reset](#)

[Commit](#)

# Exploring datasets and building operations with NoSQL Workbench

NoSQL Workbench for Amazon DynamoDB provides a rich graphical user interface for developing and testing queries. You can use the operation builder in NoSQL Workbench to view, explore, and query datasets. You can use the structured operation builder to build and perform data plane operations, with support for projection and condition expressions, and generate sample code in multiple languages. You can also save as many as 50 DynamoDB data-plane operations in the operation builder.

## Topics


- [Exploring datasets \(p. 786\)](#)
- [Building complex operations \(p. 790\)](#)
- [Exporting data to a CSV file \(p. 807\)](#)

## Exploring datasets


To explore your Amazon DynamoDB tables, you first need to connect to your AWS account.

### To add a connection to your database

1. In NoSQL Workbench, in the navigation pane on the left side, choose the **Operation builder** icon.



2. Choose **Add connection**.



3. Specify the following information:

- **Account alias**
- **AWS Region**
- **Access key ID**
- **Secret access key**

For more information about how to obtain the access keys, see [Getting an AWS access key](#).

You can optionally, specify the following:

- [Session token](#)
- [IAM role ARN](#)

4. Choose **Connect**.

## Add a new database connection



A remote connection lets you access the DynamoDB web service in different AWS Regions.

A DynamoDB local connection lets you access the DynamoDB local server running on your computer.

Remote

DynamoDB local

\* Connection name

Connection 3

\* Default AWS Region

Default AWS Region

\* Access key ID

AWS Access key ID

\* Secret access key

AWS secret access key

Session token

AWS session token



IAM role ARN

IAM role ARN



Persist connection

If you select this check box, AWS connection secrets will be persisted in

C:\Users\m\*\*\*\*\*\aws\credentials

Cancel

Reset

Connect

If you don't want to sign up for a free tier account, and prefer to use [DynamoDB local \(downloadable version\)](#):

- a. Choose the **Local** tab on the connection screen
- b. Specify the following information:
  - **Connection name**
  - **Port**
- c. Choose the **connect** button.

Add a new database connection

*i* A remote connection can let you interact with DynamoDB servers in different regions.  
A local connection can let you interact with the DynamoDB Local server on your machine.

Remote    Local

*i* Please setup the dynamoDB local server on your machine before adding a connection.  
[Setting Up DynamoDB Local](#)

\* Connection name: Connection 1

\* Hostname: localhost

\* Port: 8000

5. On the created connection, choose **Open**.

The screenshot shows the AWS NoSQL Workbench interface. On the left, a sidebar menu lists "AWS database catalog", "Amazon DynamoDB", "Data modeler", "Visualizer", and "Operation builder". The "Operation builder" item is highlighted in blue. The main right-hand panel is titled "Operation builder" and displays "Active connections" with a count of 1. Below this, there is a list of connections: "Connection 2" (Remote) with an "Open" button, which is also highlighted with a red box. The "Connection 2" row has a "Delete" icon at the end.

After connecting to your DynamoDB database, the list of available tables appears in the left pane. Choose one of the tables to return a sample of the data stored in the table.

You can now run queries against the selected table.

#### To run queries on a table

1. In the **Attribute name** list, choose the attribute that you want to query on.
2. Specify the comparison operator.
3. Specify the data type of the value.
4. Specify the value to query for.
5. Choose **Scan**.


For more information about this operation, see [Scan](#) in the *Amazon DynamoDB API Reference*.

## Building complex operations

The operation builder in NoSQL Workbench for Amazon DynamoDB provides a visual interface where you can perform complex data plane operations. It includes support for projection expressions and condition expressions. Once you've built an operation, you can save it for later use (up to 50 operations can be saved). You can then browse a list of your frequently used data-plane operations in the **Saved Operations** menu, and use them to automatically populate and build a new operation. You can also generate sample code for these operations, in multiple languages.

The NoSQL Workbench supports building [PartiQL](#) for DynamoDB statements, which allows you to interact with Dynamodb using a SQL-compatible query language. The NoSQL Workbench also supports building DynamoDB CRUD API operations.

To use the NoSQL Workbench to build operations, in the navigation pane on the left side, choose the **Operation builder** icon.



#### Topics

- [Building PartiQL statements \(p. 791\)](#)

- [Building API operations \(p. 795\)](#)

## Building PartiQL statements

To use the NoSQL Workbench to build [PartiQL for DynamoDB](#) statements choose **PartiQL operations** at the top right corner of the NoSQL Workbench.

You can build the following PartiQL statement types in the operation builder.

### Topics

- [Singleton statements \(p. 791\)](#)
- [Transactions \(p. 792\)](#)
- [Batch \(p. 793\)](#)

### Singleton statements

To run or generate code for a PartiQL statement, do the following.

1  PartiQL statement    PartiQL transaction    PartiQL batch

Statement

```
1 SELECT *
2 FROM Music
3 WHERE Artist=? and SongTitle=?
```

Optional request parameters 3.a

Enable strongly consistent reads

Parameters i

Attribute type	Attribute value
String	Acme Band

Attribute type	Attribute value
String	PartiQL Rocks

+ Add new parameter 3.b

5      4      6

Clear form   Run   Generate code   Save operation

▲ Hide operation

1. Choose **PartiQL statement**.
2. Enter a valid [PartiQL statement](#).
3. If your statement uses parameters
  - a. Choose **Optional request parameters**.

- b. Choose **Add new parameters**.
  - c. Enter the attribute type and value
  - d. If you want to add additional parameters, repeat steps b and c.
4. If you want to generate code, choose **Generate code**.
- Select your desired language from the displayed tabs. You can now copy this code and use it in your application.
5. If you want the operation to be run immediately, choose **Run**.
  6. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

## Transactions

To run or generate code for a PartiQL transaction, do the following.

PartiQL statement   **PartiQL transaction**   PartiQL batch

1      7      6      8

*i* Read and write operations are not supported in the same PartiQL transaction request. A SELECT statement cannot be in the same request with INSERT, UPDATE, and DELETE statements.

1. Choose and then enter a title

**Statement**

1 `SELECT * FROM Music WHERE Artist=? AND SongTitle=?` 3

Optional request parameters 4.a

Parameters *i*

Attribute type	Attribute value
String	4.c Acme Band
Attribute type	Attribute value
String	PartiQL Rocks

+ Add new parameter 4.b

+ Add a new statement 2

Clear Delete

▲ Hide operation

1. Choose **PartiQL transaction**.
2. Choose **Add a new statement**.
3. Enter a valid [PartiQL statement](#).

**Note**

Read and write operations are not supported in the same PartiQL transaction request. A SELECT statement cannot be in the same request with INSERT, UPDATE, and DELETE statements. See [Performing transactions with PartiQL for DynamoDB](#) for more details.

4. If your statement uses parameters
  - a. Choose **Optional request parameters**.
  - b. Choose **Add new parameters**.
  - c. Enter the attribute type and value
  - d. If you want to add additional parameters, repeat steps b and c.
5. If you want to add more statements repeat steps 2 to 4.
6. If you want to generate code, choose **Generate code**.

Select your desired language from the displayed tabs. You can now copy this code and use it in your application.

7. If you want the operation to be run immediately, choose **Run**.
8. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

## Batch

To run or generate code for a PartiQL batch, do the following.

PartiQL statement
 PartiQL transaction
 PartiQL batch
1

Delete all statements
Collapse all statements
Run
Generate code
Save operation

7
6
8

i Read and write operations are not supported in the same PartiQL batch request, which means a SELECT statement cannot be in the same request with INSERT, UPDATE, and DELETE statements. Write operations to the same item are not allowed. As with the BatchGetItem operation, only singleton read operations are supported. Scan and query operations are not supported.

⊕ 1. Choose and then enter a title

**Statement**

```
1 SELECT * FROM Music WHERE Artist=? AND SongTitle=? 3
```

Optional request parameters 4.a

Enable strongly consistent reads  i

Parameters i

Attribute type	Attribute value	4.c
String	Acme Band	<span style="border: 1px solid red; padding: 2px;">4.c</span>
Attribute type	Attribute value	
String	PartiQL Rocks	<span style="border: 1px solid red; padding: 2px;">4.b</span>

Clear
Delete

+ Add new statement 2

i Hide operation

1. Choose **PartiQL batch**.
2. Choose **Add a new statement**.
3. Enter a valid [PartiQL statement](#).

#### Note

Read and write operations are not supported in the same PartiQL batch request, which means a SELECT statement cannot be in the same request with INSERT, UPDATE, and DELETE statements. Write operations to the same item are not allowed. As with the BatchGetItem operation, only singleton read operations are supported. Scan and query operations are not supported. See [Running batch operations with PartiQL for DynamoDB](#) for more details.

API Version 2012-08-10

794

4. If your statement uses parameters
  - a. Choose **Optional request parameters**.
  - b. Choose **Add new parameters**.
  - c. Enter the attribute type and value
  - d. If you want to add additional parameters, repeat steps b and c.
5. If you want to add more statements repeat steps 2 to 4.
6. If you want to generate code, choose **Generate code**.  
Select your desired language from the displayed tabs. You can now copy this code and use it in your application.
7. If you want the operation to be run immediately, choose **Run**.
8. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

## Building API operations

To use the NoSQL Workbench to build DynamoDB CRUD APIs, select **Interface-based operations** at the top right corner of the NoSQL Workbench.

Then go to the **Operations** drop-down and choose the operation that you want to build.

The screenshot shows the AWS NoSQL Workbench interface. On the left is a sidebar with icons for AWS database catalog, Amazon DynamoDB, Data modeler, Visualizer, Operation builder (which is selected and highlighted in blue), Documentation, and Email us. The main area is titled "Operation builder". It has sections for "Connection" (with dropdowns for "Name" set to "user1" and "Region" set to "us-east-1"), "Tables" (with a search bar), and a "Build operations" sidebar. The "Build operations" sidebar contains a "Operations" section with a dropdown menu open, showing options like "Choose an operation", "Control plane operations" (with "DeleteTable" and "CreateTable" listed), "UpdateTable" (which is highlighted in blue), and "Data plane operations" (with "UpdateItem" and "PutItem" listed). A note at the bottom of the sidebar says "Choose a table from the navigation bar".

You can perform the following operations in the operation builder.

### [Table Operations \(p. 796\)](#)

- [Delete Table \(p. 796\)](#)
- [Create Table \(p. 796\)](#)
- [Update Table \(p. 798\)](#)

### [Item Operations \(p. 799\)](#)

- [Get Item \(p. 799\)](#)
- [Put Item \(p. 800\)](#)
- [Update Item \(p. 801\)](#)
- [Delete Item \(p. 802\)](#)
- [Query \(p. 803\)](#)
- [Scan \(p. 804\)](#)
- [Transact Get Items \(p. 805\)](#)
- [Transact Write Items \(p. 806\)](#)

## Table operations

### Delete table

To run or generate code for a `Delete Table` operation, do the following.

1. Select **Delete Table** from the Operations dropdown list.
2. Select the table from the **Table name** dropdown list.
3. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

4. If you want the operation to be run immediately, choose **Run**.

In the confirmation window that appears, confirm by entering the table name and selecting **Delete**.

The screenshot shows the 'Operation builder' interface. On the left, there's a sidebar with 'Connection' (user1, us-east-1) and 'Tables' (Search table). The main area is titled 'Build operations' with tabs for 'PartiQL operations' (selected) and 'Interface-based operations'. Under 'Operations', 'DeleteTable' is selected. Under 'Table name', 'NoSQLTest1' is selected. At the bottom right are 'Run' and 'Generate code' buttons. A message at the bottom says 'No result to display'.

Results of the operation will appear in the results tab at the bottom of the screen.

For more information about this operation, see [Delete table](#) in the *Amazon DynamoDB API Reference*.

### Create table

To run or generate code for a `Create Table` operation, do the following.

1. Select **Create Table** from the Operations dropdown list.
2. Enter the table name desired.
3. Create a partition key.

4. Configure the table as desired. You can create a Global Secondary Index, enable autoscaling, and other options.
5. To customize capacity settings, go to **Capacity Settings** and uncheck the box next to **Default settings**.
  - You can now select either **Provisioned** or **On-demand capacity**.

With Provisioned selected, you can set minimum and maximum read and write capacity units. You can also enable or disable auto scaling.

- If the table is currently set to OnDemand, you will be unable to specify a provisioned throughput.
- If you switch from OnDemand to Provisioned throughput, then Autoscaling will automatically be applied to all GSIs with: min: 1, max: 10; target: 70%.

6. If you want to clear all new settings you've made and start over, select **Clear form**.

7. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

8. If you want the operation to be run immediately, choose **Run**.

Results of the operation will appear in the results tab at the bottom of the screen.

9. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

The screenshot shows the Amazon DynamoDB Operation builder interface. The left sidebar contains sections for Connection (with dropdowns for Name and Region), Tables (with a search bar), and Saved operations (with a search bar). The main area is titled 'Build operations' and has tabs for 'PartiQL operations' and 'Interface-based operations' (which is selected). The 'Operations' section shows 'CreateTable' selected. The 'Primary key attributes' section shows 'pk1' as the partition key. The 'Global secondary indexes' section has a '+ Add global secondary index' button. The 'Capacity settings' section has a checked 'Default settings' checkbox with a note below it stating 'The default settings use provisioned capacity mode with auto scaling enabled on both read and write capacity.' At the bottom are buttons for 'Clear form', 'Run', 'Generate code', and 'Save operation'.

For more information about this operation, see [Create table](#) in the *Amazon DynamoDB API Reference*.

### [Update table](#)

To run or generate code for an `Update Table` operation, do the following.

1. Select **Update Table** from the Operations dropdown list.
2. Select the desired operation from the **Update operations** dropdown list.
3. Select the table from the **Table name** dropdown list.
4. Update the selected table as desired. You can create a GSI, update provisioned throughputs and other options.
5. If you select Create GSI, Update Provisioned Throughput or Update Provisioned Throughput for GSI the Capacity settings option will appear.
6. To customize capacity settings, go to **Capacity Settings**. Then uncheck the option for either **Inherit capacity settings from base table** or **On-demand**.
  - You can now select either **Provisioned** or **On-demand capacity**.

With Provisioned selected, you can set minimum and maximum read and write capacity units. You can also enable or disable auto scaling.

- If the table is currently set to OnDemand, you will be unable to specify a provisioned throughput.
  - If you switch from OnDemand to Provisioned throughput, then Autoscaling will automatically be applied to all GSIs with: min: 1, max: 10; target: 70%.
7. If you want to clear the settings you've just entered and start over, **Clear form**.
  8. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

9. If you want the operation to be run immediately, choose **Run**.

Results of the operation will appear in the results tab at the bottom of the screen.

10. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

**Operation builder**

**Build operations** ⓘ

PartiQL operations Interface-based operations

Operations	Table name	Update operations
UpdateTable	NoSQLTest1	Create GSI

**Global secondary indexes** ⓘ

\* Global secondary index name: GSI1

\* Partition key: pk2 String

Add sort key ⓘ

Projection type: ALL

**Capacity settings** ⓘ

Inherit capacity settings from base table

By default, global secondary indexes inherit the capacity settings of the base table. However, if the table is using provisioned capacity mode, you can establish the capacity settings of each global secondary index individually.

Clear form Run Generate code Save operation

For more information about this operation, see [Update table](#) in the *Amazon DynamoDB API Reference*.

## Item operations

### Get item

To run or generate code for a Get Item operation, do the following.

1. Specify the partition key value.
2. If you want to add a projection expression , do the following:
  - a. Choose **Projection expression**.
  - b. Choose the + (plus sign) next to **Projection expression**.
  - c. Specify the **Attribute name**.

Data plane operations      Table

GetItem      Music

\* Partition key      Attribute value for partition key: Artist

\* Sort key      Attribute value for sort key: SongTitle

Projection expression [?](#) [+](#)

\* Projected attribute      Attribute name [?](#) [X](#)

Other parameters [>](#)

[Clear form](#) [Run](#) [Generate code](#) [Save operation](#)

---

3. If you want to generate code, choose **Generate code**.

Select your desired language from the displayed tabs. You can now copy this code and use it in your application.

4. If you want the operation to be run immediately, choose **Run**.
5. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

For more information about this operation, see [GetItem](#) in the *Amazon DynamoDB API Reference*.

### [Put item](#)

To run or generate code for a `Put Item` operation, do the following.

1. Specify the partition key value.
2. Specify the sort key value, if one exists.
3. If you want to add non-key attributes, do the following:
  - a. Choose the **+** (plus sign) next to **Other attributes**.
  - b. Specify the **Attribute name**, **Type**, and **Value**.
4. If a condition expression must be satisfied for the `Put Item` operation to succeed, do the following:
  - a. Choose **Condition**.
  - b. Specify the attribute name, comparison operator, attribute type, and attribute value.
  - c. If other conditions are needed, choose **Condition** again.

For more information, see [Condition expressions \(p. 361\)](#).

Data plane operations      Table

PutItem      Music

\* Partition key      Attribute value for partition key: Artist

\* Sort key      Attribute value for sort key: SongTitle

Other attributes + i

Attribute name	Attribute type	Attribute value
Attribute name	String	<empty>

Condition expression + Condition + Child expression i

And Or Negate ( )

\* Condition    Negate Attribute name = Attribute type Attribute value ( )

Clear form Run Generate code Save operation

5. If you want to generate code, choose **Generate code**.

Select your desired language from the displayed tabs. You can now copy this code and use it in your application.

6. If you want the operation to be run immediately, choose **Run**.
7. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

For more information about this operation, see [PutItem](#) in the *Amazon DynamoDB API Reference*.

## Update item

To run or generate code for an `Update Item` operation, do the following:

1. Enter the partition key value.
2. Enter the sort key value, if one exists.
3. In **Update expression**, choose the expression in the list.
4. Choose the **+** (plus sign) for the expression.
5. Enter the attribute name and attribute value for the selected expression.
6. If you want to add more expressions, choose another expression in the **Update Expression** drop-down list, and then select the **+**.
7. If a condition expression must be satisfied for the `Update Item` operation to succeed, do the following:

- a. Choose **Condition**.
- b. Specify the attribute name, comparison operator, attribute type, and attribute value.
- c. If other conditions are needed, choose **Condition** again.

For more information, see [Condition expressions \(p. 361\)](#).

The screenshot shows the AWS Lambda function configuration page. At the top, it says "Lambda function configuration" and "Function name: my-function". Below that, there are tabs for "Basic" (selected), "Code", "Environment", "Logs", and "Metrics". Under the "Basic" tab, there's a "Handler" dropdown set to "index.handler", an "Execution role" dropdown set to "Lambda execution role", and a "Region" dropdown set to "US East (N. Virginia)". The "Code" tab shows the Lambda code in a text editor. The "Environment" tab shows environment variables. The "Logs" tab shows log events. The "Metrics" tab shows metrics. At the bottom, there are buttons for "Save changes" and "Test".

8. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

9. If you want the operation to be run immediately, choose **Run**.
10. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

For more information about this operation, see [UpdateItem](#) in the *Amazon DynamoDB API Reference*.


## Delete item

To run or generate code for a `Delete Item` operation, do the following.

1. Enter the partition key value.
2. Enter the sort key value, if one exists.
3. If a condition expression must be satisfied for the `Delete Item` operation to succeed, do the following:
  - a. Choose **Condition**.
  - b. Specify the attribute name, comparison operator, attribute type, and attribute value.

- c. If other conditions are needed, choose **Condition** again.

For more information, see [Condition expressions \(p. 361\)](#).



The screenshot shows the AWS Lambda console interface for configuring a DeleteItem operation. At the top, under 'Data plane operations' and 'Table', 'DeleteItem' is selected for the operation type and 'Music' is chosen as the table. Below this, two fields are filled: 'Partition key' with 'Artist' and 'Sort key' with 'SongTitle'. Under 'Condition expression', there are buttons for '+ Condition' and '+ Child expression', with 'And' selected. A 'Negate' toggle switch is off. At the bottom, there are four buttons: 'Clear form', 'Run', 'Generate code', and 'Save operation'.

4. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

5. If you want the operation to be run immediately, choose **Run**.
6. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

For more information about this operation, see [DeleteItem](#) in the *Amazon DynamoDB API Reference*.

## Query

To run or generate code for a **Query** operation, do the following.

1. Specify the partition key value.
2. If a sort key is needed for the **Query** operation:
  - a. Select **Sort key**.
  - b. Specify the comparison operator, attribute type, and attribute value.
3. If not all the attributes should be returned with the operation result, select **Projection expression**.
4. Choose the + (plus sign).
5. Enter the attribute to return with the query result.
6. If more attributes are needed, choose the + .
7. If a condition expression must be satisfied for the **Query** operation to succeed, do the following:
  - a. Choose **Condition**.
  - b. Specify the attribute name, comparison operator, attribute type, and attribute value.

- c. If other conditions are needed, choose **Condition** again.

For more information, see [Condition expressions \(p. 361\)](#).

The screenshot shows the Amazon DynamoDB Query console interface. At the top, there are dropdown menus for 'Data plane operations' (set to 'Query') and 'Table' (set to 'Music'). Below these are fields for 'Partition key' (set to 'Artist') and 'Sort key'. A checkbox for 'Projection expression' is checked. Under 'Filter expression', there are buttons for '+ Condition' and '+ Child expression', and a toggle switch between 'And', 'Or', and 'Negate' (which is selected). Below the filter expression are fields for 'Condition Negate', 'Attribute name', an operator (=), 'Attribute type', and 'Attribute value'. At the bottom, there are buttons for 'Clear form', 'Run', 'Generate code' (highlighted in blue), and 'Save operation'.

8. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

9. If you want the operation to be run immediately, choose **Run**.
10. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

For more information about this operation, see [Query](#) in the *Amazon DynamoDB API Reference*.

## Scan

To run or generate code for a Scan operation, do the following.

1. If not all the attributes should be returned with the operation result, select **Projection expression**.
2. Choose the + (plus sign).
3. Specify the attribute to return with the query result.
4. If more attributes are needed, choose the + again.
5. If a condition expression must be satisfied for the scan operation to succeed, do the following:
  - a. Choose **Condition**.

- b. Specify the attribute name, comparison operator, attribute type, and attribute value.
- c. If other conditions are needed, choose **Condition** again.

For more information, see [Condition expressions \(p. 361\)](#).

6. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

7. If you want the operation to be run immediately, choose **Run**.
8. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

### [TransactGetItems](#)

To run or generate code for a `TransactGetItems` operation, do the following.

1. Choose the + (plus sign).
2. Follow the instructions for the [Get item \(p. 799\)](#) operation.

When you are done specifying the details of the operation, choose the + (plus sign) if you want to add more operations.

The screenshot shows the AWS Lambda console interface for creating a `TransactGetItems` operation. On the left, there's a sidebar with a dropdown menu set to "Data plane operations" and a sub-menu with "TransactGetItems". The main workspace contains a list of actions. One action is explicitly named "1. GetItem", and another one below it is also labeled "1. GetItem". The "1. GetItem" action is currently selected and expanded, showing its configuration details. These details include:

- "Table Name": Set to "Music".
- "Partition key": Set to "Artist".
- "Sort key": Set to "SongTitle".
- A checked checkbox for "Projection expression".
- A field for "Projected attribute" with "Attribute name" and a delete icon.

At the bottom of the workspace, there are three buttons: "Run", "Generate code", and "Save operation".

To change the order of actions, choose an action in the list on the left side, and then choose the up or down arrows to move it up or down in the list.

To delete an action, choose the action in the list, and then choose the **Delete** (trash can) icon.

3. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

4. If you want the operation to be run immediately, choose **Run**.
5. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

For more information about transactions, see [Amazon DynamoDB transactions](#).

### TransactWriteItems

To run or generate code for a `TransactWriteItems` operation, do the following.


1. In the **Actions** drop-down list, choose the operation that you want.
  - For `DeleteItem`, follow the instructions for the [Delete item \(p. 802\)](#) operation.
  - For `PutItem`, follow the instructions for the [Put item \(p. 800\)](#) operation.
  - For `UpdateItem`, follow the instructions for the [Update item \(p. 801\)](#) operation.

When you are done specifying the details of the operation, choose the **+** button.

The screenshot shows the 'Data plane operations' section of the Amazon DynamoDB developer console. A dropdown menu is open, showing 'TransactWriteItems' as the selected option. On the right, the 'PutItem' action is selected from a list of actions (DeleteItem, PutItem, UpdateItem, ConditionCheck). The 'PutItem' form is displayed, requiring 'Table name' (set to 'Music'), 'Partition key' (set to 'Artist'), and 'Sort key' (set to 'SongTitle'). There are also fields for 'Other attributes' and 'Condition expression'. At the bottom, there are three buttons: 'Run', 'Generate code', and 'Save operation'.

To change the order of actions, choose an action in the list on the left side, and then choose the up or down arrows to move it up or down in the list.

To delete an action, choose the action in the list, and then choose the **Delete** (trash can) icon.



## 1. DeleteItem

## 2. PutItem

## 3. ConditionCheck

2. If you want to generate code, choose **Generate code**.

Choose the tab for the language that you want. You can now copy this code and use it in your application.

3. If you want the operation to be run immediately, choose **Run**.
4. If you want to save this operation for later use, choose **Save operation**, then enter a name for your operation and click **Save**.

For more information about transactions, see [Amazon DynamoDB transactions](#).

## Exporting data to a CSV file

You can export the results of a query from Operation Builder to a CSV file. This enables you to load the data into a spreadsheet or process it using your preferred programming language.

### Exporting to CSV

1. In the Operation Builder, run an operation of your choice, such as a Scan or Query.

#### Note

The operation may be a PartiQL statement or an API operation, but it may not be a batch or transaction operation.

2. In the **Results** panel, choose **Export to CSV**.

Results

---

Items returned (2)

[Export to CSV](#)

#	Awards ▾	AlbumTitle ▾	Artist ▾	SongTitle ▾
1	1	Somewhat Famous	No One You Know	Call My Today
2	10	Updated Album Title 2	Acme Band	Happy Day

3. Choose a filename and location for your CSV file and select **Save**.

## Sample data models for NoSQL Workbench

The home page for the modeler and visualizer display a number of sample models that ship with the NoSQL Workbench. This section describes these models and their potential uses.

### Topics

- [Employee data model \(p. 808\)](#)
- [Discussion forum data model \(p. 808\)](#)
- [Music library data model \(p. 809\)](#)
- [Ski resort data model \(p. 809\)](#)
- [Credit card offers data model \(p. 809\)](#)
- [Bookmarks data model \(p. 810\)](#)

## Employee data model

This data model is an introductory model. It represents an employee's basic details such as a unique alias, first name, last name, designation, manager, and skills.

This data model depicts a few techniques such as handling complex attribute such as having more than one skill. This model is also an example of one-to-many relationship through the manager and thier reporting employees that has been achieved by the secondary index DirectReports.

The access patterns facilitated by this data model are:

- Retrieval of an employee record using the employee's login alias, facilitated by a table called Employee.
- Search for employees by name, facilitated by the Employee table's global secondary index called Name.
- Retrieval of all direct reports of a manager using the manager's login alias, facilitated by the Employee table's global secondary index called DirectReports.

## Discussion forum data model

This data model represents a discussion forums. Using this model customers can engage with the developer community, ask questions, and respond to other customers' posts. Each AWS service has a dedicated forum. Anyone can start a new discussion thread by posting a message in a forum, and each thread receives any number of replies.

The access patterns facilitated by this data model are:

- Retrieval of a forum record using the forum's name, facilitated by a table called Forum.

- Retrieval of a specific thread or all threads for a forum, facilitated by a table called `Thread`.
- Search for replies using the posting user's email address, facilitated by the `Reply` table's global secondary index called `PostedBy-Message-Index`.

## Music library data model

This data model represents a music library that has a large collection of songs and showcases its most downloaded songs in near-real time.

The access patterns facilitated by this data model are:

- Retrieval of a song record, facilitated by a table called `Songs`.
- Retrieval of a specific download record or all download records for a song, facilitated by a table called `Songs`.
- Retrieval of a specific monthly download count record or all monthly download count records for a song, facilitated by a table called `Song`.
- Retrieval of all records (including song record, download records, and monthly download count records) for a song, facilitated by a table called `Songs`.
- Search for most downloaded songs, facilitated by the `Songs` table's global secondary index called `DownloadsByMonth`.

## Ski resort data model

This data model represents a ski resort that has a large collection of data for each ski lift collected daily.

The access patterns facilitated by this data model are:

- Retrieval of all data for a given ski lift or overall resort, dynamic and static, facilitated by a table called `SkiLifts`.
- Retrieval of all dynamic data (including unique lift riders, snow coverage, avalanche danger, and lift status) for a ski lift or the overall resort on a specific date, facilitated by a table called `SkiLifts`.
- Retrieval of all static data (including if the lift is for experienced riders only, vertical feet the lift rises, and lift riding time) for a specific ski lift, facilitated by a table called `SkiLifts`.
- Retrieval of date of data recorded for a specific ski lift or the overall resort sorted by total unique riders, facilitated by the `SkiLifts` table's global secondary index called `SkiLiftsByRiders`.

## Credit card offers data model

This data model is used by a Credit Card Offers Application.

A credit card provider produces offers over time. These offers include balance transfers without fees, increased credit limits, lower interest rates, cash back, and airline miles. After a customer accepts or declines these offers, the respective offer status is updated accordingly.

The access patterns facilitated by this data model are:

- Retrieval of account records using `AccountId`, as facilitated by the main table.
- Retrieval of all the accounts with few projected items, as facilitated by the secondary index `AccountIndex`.
- Retrieval of accounts and all the offer records associated with those accounts by using `AccountId`, as facilitated by the main table.

- Retrieval of accounts and specific offer records associated with those accounts by using `AccountId` and `OfferId`, as facilitated by the main table.
- Retrieval of all `ACCEPTED/DECLINED` offer records of specific `OfferType` associated with accounts using `AccountId`, `OfferType`, and `Status`, as facilitated by the secondary index `GSI1`.
- Retrieval of offers and associated offer item records using `OfferId`, as facilitated by the main table.

## Bookmarks data model

This data model is used store bookmarks for customers.

A customer can have many bookmarks and a bookmark can belong to many customers. This data model represents a many-to-many relationship.

The access patterns facilitated by this data model are:

- A single query by `customerId` can now return customer data as well as bookmarks.
- A query `ByEmail` index returns customer data by email address. Note that bookmarks are not retrieved by this index.
- A query `ByUrl` index gets bookmarks data by URL. Note that we have `customerId` as the sort key for the index because the same URL can be bookmarked by multiple customers.
- A query `ByCustomerFolder` index gets bookmarks by folder for each customer.

## Release history for NoSQL Workbench

The following table describes the important changes in each release of the *NoSQL Workbench* client tool.

Change	Description	Date
Support for control plane operations	Operation Builder now supports control plane operations.	June 1, 2022
CSV import and export	You can now import sample data from a CSV file in the Visualizer tool, and also export the results of an Operation Builder query to a CSV file.	October 11, 2021
Save operations	The Operation Builder in NoSQL Workbench now supports saving operations for later use.	July 12, 2021
Capacity settings and CloudFormation import/export	NoSQL Workbench for Amazon DynamoDB now supports specifying a read/write capacity mode for tables, and can now import and export data models in AWS CloudFormation format.	April 21, 2021
Support for PartiQL	NoSQL Workbench for Amazon DynamoDB adds support for building PartiQL statements for DynamoDB.	December 4, 2020

Change	Description	Date
Support for Linux.	NoSQL Workbench for Amazon DynamoDB is supported on Linux—Ubuntu, Fedora, and Debian.	May 4, 2020
NoSQL Workbench for Amazon DynamoDB – GA.	NoSQL Workbench for Amazon DynamoDB is generally available.	March 2, 2020
Support for IAM roles and temporary security credentials.	NoSQL Workbench for Amazon DynamoDB adds support for AWS Identity and Access Management (IAM) roles and temporary security credentials.	December 19, 2019
Support for <a href="#">DynamoDB Local (Downloadable Version)</a> .	The NoSQL Workbench now supports connecting to <a href="#">DynamoDB Local (Downloadable Version)</a> to design, create, query, and manage DynamoDB tables.	November 8, 2019
NoSQL Workbench preview released.	This is the initial release of NoSQL Workbench for DynamoDB. Use NoSQL Workbench to design, create, query, and manage DynamoDB tables. For more information, see <a href="#">NoSQL Workbench for Amazon DynamoDB (Preview)</a> .	September 16, 2019

# Code examples for DynamoDB using AWS SDKs

The following code examples show how to use DynamoDB with an AWS software development kit (SDK).

The examples are divided into the following categories:

## **Actions**

Code excerpts that show you how to call individual service functions.

## **Scenarios**

Code examples that show you how to accomplish a specific task by calling multiple functions within the same service.

## **Cross-service examples**

Sample applications that work across multiple AWS services.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## **Code examples**

- [Actions for DynamoDB using AWS SDKs \(p. 813\)](#)
  - [Create a DynamoDB table using an AWS SDK \(p. 813\)](#)
  - [Delete a DynamoDB table using an AWS SDK \(p. 823\)](#)
  - [Delete an item from a DynamoDB table using an AWS SDK \(p. 829\)](#)
  - [Get a batch of DynamoDB items using an AWS SDK \(p. 837\)](#)
  - [Get an item from a DynamoDB table using an AWS SDK \(p. 841\)](#)
  - [Get information about a DynamoDB table \(p. 848\)](#)
  - [List DynamoDB tables using an AWS SDK \(p. 853\)](#)
  - [Put an item in a DynamoDB table using an AWS SDK \(p. 859\)](#)
  - [Query a DynamoDB table using an AWS SDK \(p. 868\)](#)
  - [Run a PartiQL statement on a DynamoDB table using an AWS SDK \(p. 880\)](#)
  - [Run batches of PartiQL statements on a DynamoDB table using an AWS SDK \(p. 889\)](#)
  - [Scan a DynamoDB table using an AWS SDK \(p. 902\)](#)
  - [Update an item in a DynamoDB table using an AWS SDK \(p. 910\)](#)
  - [Write a batch of DynamoDB items using an AWS SDK \(p. 921\)](#)
- [Scenarios for DynamoDB using AWS SDKs \(p. 928\)](#)
  - [Accelerate DynamoDB reads with DAX using an AWS SDK \(p. 928\)](#)
  - [Get started using DynamoDB tables, items, and queries using an AWS SDK \(p. 934\)](#)
  - [Query a DynamoDB table by using batches of PartiQL statements and an AWS SDK \(p. 991\)](#)
  - [Query a DynamoDB table using PartiQL and an AWS SDK \(p. 1023\)](#)
- [Cross-service examples for DynamoDB using AWS SDKs \(p. 1050\)](#)
  - [Build an application to submit data to a DynamoDB table \(p. 1050\)](#)

- Create an API Gateway REST API to track COVID-19 data (p. 1051)
- Create a messenger application with Step Functions (p. 1052)
- Create a dynamic web application to track DynamoDB data (p. 1053)
- Create a websocket chat application with API Gateway (p. 1054)
- Detect PPE in images with Amazon Rekognition using an AWS SDK (p. 1055)
- Invoke a Lambda function from a browser (p. 1056)
- Save EXIF and other image information using an AWS SDK (p. 1056)
- Use API Gateway to invoke a Lambda function (p. 1057)
- Use Step Functions to invoke Lambda functions (p. 1058)
- Use scheduled events to invoke a Lambda function (p. 1059)

## Actions for DynamoDB using AWS SDKs

The following code examples demonstrate how to perform individual DynamoDB actions with AWS SDKs. These excerpts call the DynamoDB API and are not intended to be run in isolation. Each example includes a link to GitHub, where you can find instructions on how to set up and run the code in context.

The following examples include only the most commonly used actions. For a complete list, see the [Amazon DynamoDB API Reference](#).

### Examples

- Create a DynamoDB table using an AWS SDK (p. 813)
- Delete a DynamoDB table using an AWS SDK (p. 823)
- Delete an item from a DynamoDB table using an AWS SDK (p. 829)
- Get a batch of DynamoDB items using an AWS SDK (p. 837)
- Get an item from a DynamoDB table using an AWS SDK (p. 841)
- Get information about a DynamoDB table (p. 848)
- List DynamoDB tables using an AWS SDK (p. 853)
- Put an item in a DynamoDB table using an AWS SDK (p. 859)
- Query a DynamoDB table using an AWS SDK (p. 868)
- Run a PartiQL statement on a DynamoDB table using an AWS SDK (p. 880)
- Run batches of PartiQL statements on a DynamoDB table using an AWS SDK (p. 889)
- Scan a DynamoDB table using an AWS SDK (p. 902)
- Update an item in a DynamoDB table using an AWS SDK (p. 910)
- Write a batch of DynamoDB items using an AWS SDK (p. 921)

## Create a DynamoDB table using an AWS SDK

The following code examples show how to create a DynamoDB table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

    ///<summary>
    /// Creates a new Amazon DynamoDB table and then waits for the new
    /// table to become active.
    ///</summary>
    ///<param name="client">An initialized Amazon DynamoDB client object.</param>
    ///<param name="tableName">The name of the table to create.</param>
    ///<returns>A Boolean value indicating the success of the operation.</returns>
    public static async Task<bool> CreateMovieTableAsync(AmazonDynamoDBClient
client, string tableName)
{
    var response = await client.CreateTableAsync(new CreateTableRequest
{
    TableName = tableName,
    AttributeDefinitions = new List<AttributeDefinition>()
    {
        new AttributeDefinition
        {
            AttributeName = "title",
            AttributeType = "S",
        },
        new AttributeDefinition
        {
            AttributeName = "year",
            AttributeType = "N",
        },
    },
    KeySchema = new List<KeySchemaElement>()
    {
        new KeySchemaElement
        {
            AttributeName = "year",
            KeyType = "HASH",
        },
        new KeySchemaElement
        {
            AttributeName = "title",
            KeyType = "RANGE",
        },
    },
    ProvisionedThroughput = new ProvisionedThroughput
    {
        ReadCapacityUnits = 5,
        WriteCapacityUnits = 5,
    },
});
}

// Wait until the table is ACTIVE and then report success.
Console.WriteLine("Waiting for table to become active...");

var request = new DescribeTableRequest
{
    TableName = response.TableDescription.TableName,
};

TableStatus status;

int sleepDuration = 2000;

do
{
    System.Threading.Thread.Sleep(sleepDuration);

    var describeTableResponse = await
client.DescribeTableAsync(request);
}

```

```
        status = describeTableResponse.Table.TableStatus;

        Console.WriteLine(".");
    }
    while (status != "ACTIVE");

    return status == TableStatus.ACTIVE;
}
```

- For API details, see [CreateTable](#) in *AWS SDK for .NET API Reference*.

C++

**SDK for C++**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
if (!region.empty())
    clientConfig.region = region;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

std::cout << "Creating table " << table <<
    " with a simple primary key: \"Name\"" << std::endl;

Aws::DynamoDB::Model::CreateTableRequest req;

Aws::DynamoDB::Model::AttributeDefinition hashKey;
hashKey.setAttributeName("Name");
hashKey.setAttributeType(Aws::DynamoDB::Model::ScalarAttributeType::S);
req.addAttributeDefinitions(hashKey);

Aws::DynamoDB::Model::KeySchemaElement keyselt;

keyselt.setAttributeName("Name").WithKeyType(Aws::DynamoDB::Model::KeyType::HASH);
req.addKeySchema(keyselt);

Aws::DynamoDB::Model::ProvisionedThroughput thruput;
thruput.WithReadCapacityUnits(5).WithWriteCapacityUnits(5);
req.setProvisionedThroughput(thruput);
req.setTableName(table);

const Aws::DynamoDB::Model::CreateTableOutcome& result =
dynamoClient.CreateTable(req);
if (result.IsSuccess())
{
    std::cout << "Table \" " <<
result getResult().GetTableDescription().GetTableName() <<
    " created!" << std::endl;
}
else
{
    std::cout << "Failed to create table: " <<
result GetError().GetMessage();
}
```

- For API details, see [CreateTable](#) in *AWS SDK for C++ API Reference*.

Go

**SDK for Go V2**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// CreateMovieTable creates a DynamoDB table with a composite primary key defined
// as
// a string sort key named `title`, and a numeric partition key named `year`.
// This function uses NewTableExistsWaiter to wait for the table to be created by
// DynamoDB before it returns.
func (basics TableBasics) CreateMovieTable() (*types.TableDescription, error) {
    var tableDesc *types.TableDescription
    table, err := basics.DynamoDbClient.CreateTable(context.TODO(),
        &dynamodb.CreateTableInput{
            AttributeDefinitions: []types.AttributeDefinition{
                {AttributeName: aws.String("year"),
                    AttributeType: types.ScalarAttributeTypeN,
                },
                {AttributeName: aws.String("title"),
                    AttributeType: types.ScalarAttributeTypeS,
                },
            },
            KeySchema: []types.KeySchemaElement{
                {AttributeName: aws.String("year"),
                    KeyType:      types.KeyTypeHash,
                },
                {AttributeName: aws.String("title"),
                    KeyType:      types.KeyTypeRange,
                },
            },
            TableName: aws.String(basics.TableName),
            ProvisionedThroughput: &types.ProvisionedThroughput{
                ReadCapacityUnits: aws.Int64(10),
                WriteCapacityUnits: aws.Int64(10),
            },
        })
    if err != nil {
        log.Printf("Couldn't create table %v. Here's why: %v\n", basics.TableName, err)
    } else {
        waiter := dynamodb.NewTableExistsWaiter(basics.DynamoDbClient)
        err = waiter.Wait(context.TODO(), &dynamodb.DescribeTableInput{
            TableName: aws.String(basics.TableName)}, 5*time.Minute)
        if err != nil {
            log.Printf("Wait for table exists failed. Here's why: %v\n", err)
        }
        tableDesc = table.TableDescription
    }
    return tableDesc, err
}
```

- For API details, see [CreateTable in AWS SDK for Go API Reference](#).

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static String createTable(DynamoDbClient ddb, String tableName, String key) {
    DynamoDbWaiter dbWaiter = ddb.waiter();
    CreateTableRequest request = CreateTableRequest.builder()
        .attributeDefinitions(AttributeDefinition.builder()
            .attributeName(key)
            .attributeType(ScalarAttributeType.S)
            .build())
        .keySchema(KeySchemaElement.builder()
            .attributeName(key)
            .keyType(KeyType.HASH)
            .build())
        .provisionedThroughput(ProvisionedThroughput.builder()
            .readCapacityUnits(new Long(10))
            .writeCapacityUnits(new Long(10))
            .build())
        .tableName(tableName)
        .build();

    String newTable = "";
    try {
        CreateTableResponse response = ddb.createTable(request);
        DescribeTableRequest tableRequest = DescribeTableRequest.builder()
            .tableName(tableName)
            .build();

        // Wait until the Amazon DynamoDB table is created.
        WaiterResponse<DescribeTableResponse> waiterResponse =
        dbWaiter.waitUntilTableExists(tableRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        newTable = response.tableDescription().tableName();
        return newTable;
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return "";
}
```

- For API details, see [CreateTable in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create service client module using ES6 syntax.
```

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon DynamoDB service client object.
const ddbClient = new DynamoDBClient({ region: REGION });
export { ddbClient };
```

Create the table.

```
// Import required AWS SDK clients and commands for Node.js
import { CreateTableCommand } from "@aws-sdk/client-dynamodb";
import { ddbClient } from "./libs/ddbClient.js";

// Set the parameters
export const params = {
    AttributeDefinitions: [
        {
            AttributeName: "Season", //ATTRIBUTE_NAME_1
            AttributeType: "N", //ATTRIBUTE_TYPE
        },
        {
            AttributeName: "Episode", //ATTRIBUTE_NAME_2
            AttributeType: "N", //ATTRIBUTE_TYPE
        },
    ],
    KeySchema: [
        {
            AttributeName: "Season", //ATTRIBUTE_NAME_1
            KeyType: "HASH",
        },
        {
            AttributeName: "Episode", //ATTRIBUTE_NAME_2
            KeyType: "RANGE",
        },
    ],
    ProvisionedThroughput: {
        ReadCapacityUnits: 1,
        WriteCapacityUnits: 1,
    },
    TableName: "TEST_TABLE", //TABLE_NAME
    StreamSpecification: {
        StreamEnabled: false,
    },
};

export const run = async () => {
    try {
        const data = await ddbClient.send(new CreateTableCommand(params));
        console.log("Table Created", data);
        return data;
    } catch (err) {
        console.log("Error", err);
    }
};
run();
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [CreateTable in AWS SDK for JavaScript API Reference](#).

**SDK for JavaScript V2**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
    AttributeDefinitions: [
        {
            AttributeName: 'CUSTOMER_ID',
            AttributeType: 'N'
        },
        {
            AttributeName: 'CUSTOMER_NAME',
            AttributeType: 'S'
        }
    ],
    KeySchema: [
        {
            AttributeName: 'CUSTOMER_ID',
            KeyType: 'HASH'
        },
        {
            AttributeName: 'CUSTOMER_NAME',
            KeyType: 'RANGE'
        }
    ],
    ProvisionedThroughput: {
        ReadCapacityUnits: 1,
        WriteCapacityUnits: 1
    },
    TableName: 'CUSTOMER_LIST',
    StreamSpecification: {
        StreamEnabled: false
    }
};

// Call DynamoDB to create the table
ddb.createTable(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Table Created", data);
    }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [CreateTable in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

suspend fun createNewTable(tableNameVal: String, key: String): String? {

    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef)
        keySchema = listOf(keySchemaVal)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        var tableArn: String
        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        tableArn = response.tableDescription!!.tableArn.toString()
        println("Table $tableArn is ready")
        return tableArn
    }
}

```

- For API details, see [CreateTable in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a table.

```

$tableName = "ddb_demo_table_$uuid";
 getService->createTable(
    $tableName,
    [
        new DynamoDBAttribute('year', 'N', 'HASH'),
        new DynamoDBAttribute('title', 'S', 'RANGE')
    ]
);

public function createTable(string $tableName, array $attributes)
{
    $keySchema = [];
    $attributeDefinitions = [];

```

```

foreach ($attributes as $attribute) {
    if (is_a($attribute, DynamoDBAttribute::class)) {
        $keySchema[] = ['AttributeName' => $attribute->AttributeName,
'KeyType' => $attribute->KeyType];
        $attributeDefinitions[] =
            ['AttributeName' => $attribute->AttributeName, 'AttributeType'
=> $attribute->AttributeType];
    }
}

$this->dynamoDbClient->createTable([
    'TableName' => $tableName,
    'KeySchema' => $keySchema,
    'AttributeDefinitions' => $attributeDefinitions,
    'ProvisionedThroughput' => ['ReadCapacityUnits' => 10,
    'WriteCapacityUnits' => 10],
]);
}

```

- For API details, see [CreateTable](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a table for storing movie data.

```

class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def create_table(self, table_name):
        """
        Creates an Amazon DynamoDB table that can be used to store movie data.
        The table uses the release year of the movie as the partition key and the
        title as the sort key.

        :param table_name: The name of the table to create.
        :return: The newly created table.
        """
        try:
            self.table = self.dyn_resource.create_table(
                TableName=table_name,
                KeySchema=[
                    {'AttributeName': 'year', 'KeyType': 'HASH'}, # Partition key
                    {'AttributeName': 'title', 'KeyType': 'RANGE'} # Sort key
                ],
                AttributeDefinitions=[
                    {'AttributeName': 'year', 'AttributeType': 'N'},
                    {'AttributeName': 'title', 'AttributeType': 'S'}
                ],
                ProvisionedThroughput={'ReadCapacityUnits': 10,
                'WriteCapacityUnits': 10})
            self.table.wait_until_exists()
        except ClientError as err:

```

```
logger.error(
    "Couldn't create table %s. Here's why: %s: %s",
    err.response['Error']['Code'], err.response['Error']['Message'])
raise
else:
    return self.table
```

- For API details, see [CreateTable](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Creates an Amazon DynamoDB table that can be used to store movie data.
# The table uses the release year of the movie as the partition key and the
# title as the sort key.
#
# @param table_name [String] The name of the table to create.
# @return [Aws::DynamoDB::Table] The newly created table.
def create_table(table_name)
  @table = @dynamo_resource.create_table(
    table_name: table_name,
    key_schema: [
      {attribute_name: "year", key_type: "HASH"}, # Partition key
      {attribute_name: "title", key_type: "RANGE"} # Sort key
    ],
    attribute_definitions: [
      {attribute_name: "year", attribute_type: "N"},
      {attribute_name: "title", attribute_type: "S"}
    ],
    provisioned_throughput: {read_capacity_units: 10, write_capacity_units: 10})
  @dynamo_resource.client.wait_until(:table_exists, table_name: table_name)
rescue Aws::Errors::ServiceError => e
  puts("Couldn't create table #{table_name}. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
else
  @table
end
```

- For API details, see [CreateTable](#) in *AWS SDK for Ruby API Reference*.

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn create_table(client: &Client, table: &str, key: &str) -> Result<(), Error>
{
```

```
let a_name: String = key.into();
let table_name: String = table.into();

let ad = AttributeDefinition::builder()
    .attribute_name(&a_name)
    .attribute_type(ScalarAttributeType::S)
    .build();

let ks = KeySchemaElement::builder()
    .attribute_name(&a_name)
    .key_type(KeyType::Hash)
    .build();

let pt = ProvisionedThroughput::builder()
    .read_capacity_units(10)
    .write_capacity_units(5)
    .build();

match client
    .create_table()
    .table_name(table_name)
    .key_schema(ks)
    .attribute_definitions(ad)
    .provisioned_throughput(pt)
    .send()
    .await
{
    Ok(_) => println!("Added table {} with key {}", table, key),
    Err(e) => {
        println!("Got an error creating table:");
        println!("{}: {}", e);
        process::exit(1);
    }
};

Ok(())
}
```

- For API details, see [CreateTable in AWS SDK for Rust API reference](#).

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Delete a DynamoDB table using an AWS SDK

The following code examples show how to delete a DynamoDB table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static async Task<bool> DeleteTableAsync(AmazonDynamoDBClient
client, string tableName)
{
    var request = new DeleteTableRequest
    {
```

```
        TableName = tableName,
    };

    var response = await client.DeleteTableAsync(request);
    if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
    {
        Console.WriteLine($"Table {response.TableDescription.TableName} successfully deleted.");
        return true;
    }
    else
    {
        Console.WriteLine("Could not delete table.");
        return false;
    }
}
```

- For API details, see [DeleteTable in AWS SDK for .NET API Reference](#).

## C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
if (!region.empty())
    clientConfig.region = region;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

Aws::DynamoDB::Model::DeleteTableRequest dtr;
dtr.SetTableName(table);

const Aws::DynamoDB::Model::DeleteTableOutcome& result =
dynamoClient.DeleteTable(dtr);
if (result.IsSuccess())
{
    std::cout << "Your Table \" " <<
result.GetResult().GetTableDescription().GetTableName() << " was deleted!\n";
}
else
{
    std::cout << "Failed to delete table: " <<
result.GetError().GetMessage();
}
```

- For API details, see [DeleteTable in AWS SDK for C++ API Reference](#).

## Go

### SDK for Go V2

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// DeleteTable deletes the DynamoDB table and all of its data.
func (basics TableBasics) DeleteTable() error {
    _, err := basics.DynamoDbClient.DeleteTable(context.TODO(),
        &dynamodb.DeleteTableInput{
            TableName: aws.String(basics.TableName)})
    if err != nil {
        log.Printf("Couldn't delete table %v. Here's why: %v\n", basics.TableName, err)
    }
    return err
}
```

- For API details, see [DeleteTable in AWS SDK for Go API Reference](#).

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName) {

    DeleteTableRequest request = DeleteTableRequest.builder()
        .tableName(tableName)
        .build();

    try {
        ddb.deleteTable(request);

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    System.out.println(tableName + " was successfully deleted!");
}
```

- For API details, see [DeleteTable in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.  
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";  
// Set the AWS Region.  
export const REGION = "REGION"; // For example, "us-east-1".  
// Create an Amazon DynamoDB service client object.  
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Delete the table.

```
// Import required AWS SDK clients and commands for Node.js  
import { DeleteTableCommand } from "@aws-sdk/client-dynamodb";  
import { ddbClient } from "./libs/ddbClient.js";  
  
// Set the parameters  
export const params = {  
    TableName: "CUSTOMER_LIST_NEW",  
};  
  
export const run = async () => {  
    try {  
        const data = await ddbClient.send(new DeleteTableCommand(params));  
        console.log("Success, table deleted", data);  
        return data;  
    } catch (err) {  
        console.log("Error", err);  
    }  
};  
run();
```

- For API details, see [DeleteTable in AWS SDK for JavaScript API Reference](#).

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js  
var AWS = require('aws-sdk');  
// Set the region  
AWS.config.update({region: 'REGION'});  
  
// Create the DynamoDB service object  
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});  
  
var params = {  
    TableName: process.argv[2]  
};  
  
// Call DynamoDB to delete the specified table  
ddb.deleteTable(params, function(err, data) {  
    if (err && err.code === 'ResourceNotFoundException') {  
        console.log("Error: Table not found");  
    } else if (err && err.code === 'ResourceInUseException') {  
        console.log("Error: Table in use");  
    } else {  
        console.log("Success", data);  
    }  
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [DeleteTable in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun deleteDynamoDBTable(tableNameVal: String) {  
  
    val request = DeleteTableRequest {  
        tableName = tableNameVal  
    }  
  
    DynamoDbClient { region = "us-east-1" }.use { ddb ->  
        ddb.deleteTable(request)  
        println("$tableNameVal was deleted")  
    }  
}
```

- For API details, see [DeleteTable in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public function deleteTable(string $TableName)  
{  
    $this->customWaiter(function () use ($TableName) {  
        return $this->dynamoDbClient->deleteTable([  
            'TableName' => $TableName,  
        ]);  
    });  
}
```

- For API details, see [DeleteTable in AWS SDK for PHP API Reference](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
```

```
"""Encapsulates an Amazon DynamoDB table of movie data."""
def __init__(self, dyn_resource):
    """
    :param dyn_resource: A Boto3 DynamoDB resource.
    """
    self.dyn_resource = dyn_resource
    self.table = None

def delete_table(self):
    """
    Deletes the table.
    """
    try:
        self.table.delete()
        self.table = None
    except ClientError as err:
        logger.error(
            "Couldn't delete table. Here's why: %s: %s",
            err.response['Error']['Code'], err.response['Error']['Message'])
        raise
```

- For API details, see [DeleteTable in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Deletes the table.
def delete_table
  @table.delete
  @table = nil
rescue Aws::Errors::ServiceError => e
  puts("Couldn't delete table. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
end
```

- For API details, see [DeleteTable in AWS SDK for Ruby API Reference](#).

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn delete_table(client: &Client, table: &str) -> Result<(), Error> {
    client.delete_table().table_name(table).send().await?;

    println!("Deleted table");
```

```
        Ok(())
}
```

- For API details, see [DeleteTable in AWS SDK for Rust API reference](#).

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Delete an item from a DynamoDB table using an AWS SDK

The following code examples show how to delete an item from a DynamoDB table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Deletes a single item from a DynamoDB table.
/// </summary>
/// <param name="client">The initialized DynamoDB client object.</param>
/// <param name="tableName">The name of the table from which the item
/// will be deleted.</param>
/// <param name="movieToDelete">A movie object containing the title and
/// year of the movie to delete.</param>
/// <returns>A Boolean value indicating the success or failure of the
/// delete operation.</returns>
public static async Task<bool> DeleteItemAsync(
    AmazonDynamoDBClient client,
    string tableName,
    Movie movieToDelete)
{
    var key = new Dictionary<string, AttributeValue>
    {
        ["title"] = new AttributeValue { S = movieToDelete.Title },
        ["year"] = new AttributeValue { N =
movieToDelete.Year.ToString() },
    };

    var request = new DeleteItemRequest
    {
        TableName = tableName,
        Key = key,
    };

    var response = await client.DeleteItemAsync(request);
    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [DeleteItem in AWS SDK for .NET API Reference](#).

Go

**SDK for Go V2**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// DeleteMovie removes a movie from the DynamoDB table.
func (basics TableBasics) DeleteMovie(movie Movie) error {
    _, err := basics.DynamoDbClient.DeleteItem(context.TODO(),
        &dynamodb.DeleteItemInput{
            TableName: aws.String(basics.TableName), Key: movie.GetKey(),
        })
    if err != nil {
        log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
            err)
    }
    return err
}
```

- For API details, see [DeleteItem in AWS SDK for Go API Reference](#).

Java

**SDK for Java 2.x**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
public static void deleteDynamoDBItem(DynamoDbClient ddb, String tableName,
    String key, String keyVal) {
    HashMap<String,AttributeValue> keyToGet = new HashMap<>();
    keyToGet.put(key, AttributeValue.builder()
        .s(keyVal)
        .build());

    DeleteItemRequest deleteReq = DeleteItemRequest.builder()
        .tableName(tableName)
        .key(keyToGet)
        .build();

    try {
        ddb.deleteItem(deleteReq);
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
}
```

- For API details, see [DeleteItem in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.  
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";  
// Set the AWS Region.  
export const REGION = "REGION"; // For example, "us-east-1".  
// Create an Amazon DynamoDB service client object.  
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the document client.

```
// Create a service client module using ES6 syntax.  
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";  
import { ddbClient } from "./ddbClient.js";  
// Set the AWS Region.  
const REGION = "REGION"; // For example, "us-east-1".  
  
const marshallOptions = {  
    // Whether to automatically convert empty strings, blobs, and sets to `null`.  
    convertEmptyValues: false, // false, by default.  
    // Whether to remove undefined values while marshalling.  
    removeUndefinedValues: false, // false, by default.  
    // Whether to convert typeof object to map attribute.  
    convertClassInstanceToMap: false, // false, by default.  
};  
  
const unmarshallOptions = {  
    // Whether to return numbers as a string instead of converting them to native  
    // JavaScript numbers.  
    wrapNumbers: false, // false, by default.  
};  
  
const translateConfig = { marshallOptions, unmarshallOptions };  
  
// Create the DynamoDB document client.  
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);  
  
export { ddbDocClient };
```

Delete an item from a table using the DynamoDB document client.

```
import { DeleteCommand } from "@aws-sdk/lib-dynamodb";  
import { ddbDocClient } from "../libs/ddbDocClient.js";  
  
// Set the parameters.  
export const params = {  
    TableName: "TABLE_NAME",
```

```

    Key: {
      primaryKey: "VALUE_1",
      sortKey: "VALUE_2",
    },
  };

export const deleteItem = async () => {
  try {
    const data = await ddbDocClient.send(new DeleteCommand(params));
    console.log("Success - item deleted");
  } catch (err) {
    console.log("Error", err);
  }
};
deleteItem();

```

Delete an item from a table using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];

export const run = async (tableName, movieYear1, movieTitle1) => {
  const params = {
    Statement: "DELETE FROM " + tableName + " where title=? and year=?",
    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
  };
  try {
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
    console.log("Success. Item deleted.");
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(tableName, movieYear1, movieTitle1);

```

Delete an item from a table by batch using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2
) => {
  try {

```

```
const params = {
  Statements: [
    {
      Statement: "DELETE FROM " + tableName + " where year=? and title=?",
      Parameters: [{ N: movieYear1 }, { S: movieTitle1 }],
    },
    {
      Statement: "DELETE FROM " + tableName + " where year=? and title=?",
      Parameters: [{ N: movieYear2 }, { S: movieTitle2 }],
    },
  ],
};

const data = await ddbDocClient.send(
  new BatchExecuteStatementCommand(params)
);
console.log("Success. Items deleted.", data);
return "Run successfully"; // For unit tests.
} catch (err) {
  console.error(err);
}
};

run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [DeleteItem in AWS SDK for JavaScript API Reference](#).

#### SDK for JavaScript V2

**Tip**

To learn how to set up and run this example, see [GitHub](#).

Delete an item from a table.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
  TableName: 'TABLE',
  Key: {
    'KEY_NAME': {N: 'VALUE'}
  }
};

// Call DynamoDB to delete the item from the table
ddb.deleteItem(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

Delete an item from a table using the DynamoDB document client.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
```

```
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
  Key: {
    'HASH_KEY': VALUE
  },
  TableName: 'TABLE'
};

docClient.delete(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data);
  }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [DeleteItem in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun deleteDynamoDBItem(tableNameVal: String, keyName: String, keyVal: String) {

    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.S(keyVal)

    val request = DeleteItemRequest {
        tableName = tableNameVal
        key = keyToGet
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.deleteItem(request)
        println("Item with key matching $keyVal was deleted")
    }
}
```

- For API details, see [DeleteItem in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
$key = [
    'Item' => [
        'title' => [
            'S' => $movieName,
        ],
        'year' => [
            'N' => $movieYear,
        ],
    ],
];
];

$service->deleteItemByKey($tableName, $key);
echo "But, bad news, this was a trap. That movie has now been deleted
because of your rating...harsh.\n";

public function deleteItemByKey(string $tableName, array $key)
{
    $this->dynamoDbClient->deleteItem([
        'Key' => $key['Item'],
        'TableName' => $tableName,
    ]);
}
```

- For API details, see [DeleteItem in AWS SDK for PHP API Reference](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def delete_movie(self, title, year):
        """
        Deletes a movie from the table.

        :param title: The title of the movie to delete.
        :param year: The release year of the movie to delete.
        """
        try:
            self.table.delete_item(Key={'year': year, 'title': title})
        except ClientError as err:
            logger.error(
                "Couldn't delete movie %s. Here's why: %s: %s",
                title,
                err.response['Error']['Code'],
                err.response['Error']['Message']
            )
            raise
```

You can specify a condition so that an item is deleted only when it meets certain criteria.

```
class UpdateQueryWrapper:
```

```
def __init__(self, table):
    self.table = table

def delete_underrated_movie(self, title, year, rating):
    """
    Deletes a movie only if it is rated below a specified value. By using a
    condition expression in a delete operation, you can specify that an item is
    deleted only when it meets certain criteria.

    :param title: The title of the movie to delete.
    :param year: The release year of the movie to delete.
    :param rating: The rating threshold to check before deleting the movie.
    """
    try:
        self.table.delete_item(
            Key={'year': year, 'title': title},
            ConditionExpression="info.rating <= :val",
            ExpressionAttributeValues={":val": Decimal(str(rating))})
    except ClientError as err:
        if err.response['Error']['Code'] == "ConditionalCheckFailedException":
            logger.warning(
                "Didn't delete %s because its rating is greater than %s.", title,
                rating)
        else:
            logger.error(
                "Couldn't delete movie %s. Here's why: %s: %s", title,
                err.response['Error']['Code'], err.response['Error']
            ['Message'])
            raise
    
```

- For API details, see [DeleteItem in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Deletes a movie from the table.
#
# @param title [String] The title of the movie to delete.
# @param year [Integer] The release year of the movie to delete.
def delete_movie(title, year)
    @table.delete_item(key: {"year" => year, "title" => title})
rescue Aws::Errors::ServiceError => e
    puts("Couldn't delete movie #{title}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
end
```

- For API details, see [DeleteItem in AWS SDK for Ruby API Reference](#).

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
async fn delete_item(client: &Client, table: &str, key: &str, value: &str) ->
    Result<(), Error> {
    match client
        .delete_item()
        .table_name(table)
        .key(key, AttributeValue::S(value.into()))
        .send()
        .await
    {
        Ok(_) => println!("Deleted item from table"),
        Err(e) => {
            println!("Got an error deleting item from table:");
            println!("{}: {}", "{}", e);
            process::exit(1);
        }
    };
    Ok(())
}
```

- For API details, see [DeleteItem in AWS SDK for Rust API reference](#).

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Get a batch of DynamoDB items using an AWS SDK

The following code examples show how to get a batch of DynamoDB items.

.NET

### AWS SDK for .NET

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Gets information about an existing movie from the table.
/// </summary>
/// <param name="client">An initialized Amazon DynamoDB client object.</param>
/// <param name="newMovie">A Movie object containing information about
/// the movie to retrieve.</param>
/// <param name="tableName">The name of the table containing the movie.</param>
/// <returns>A Dictionary object containing information about the item
/// retrieved.</returns>
public static async Task<Dictionary<string, AttributeValue>>
GetItemAsync(AmazonDynamoDBClient client, Movie newMovie, string tableName)
{
    var key = new Dictionary<string, AttributeValue>
    {
```

```
        ["title"] = new AttributeValue { S = newMovie.Title },
        ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
    };

    var request = new GetItemRequest
    {
        Key = key,
        TableName = tableName,
    };

    var response = await client.GetItemAsync(request);
    return response.Item;
}
```

- For API details, see [BatchGetItem](#) in *AWS SDK for .NET API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon DynamoDB service client object.
const ddbClient = new DynamoDBClient({ region: REGION });
export { ddbClient };
```

Get the items.

```
// Import required AWS SDK clients and commands for Node.js
import { BatchGetItemCommand } from "@aws-sdk/client-dynamodb";
import { ddbClient } from "./libs/ddbClient.js";

// Set the parameters
export const params = {
    RequestItems: {
        TABLE_NAME: [
            Keys: [
                {
                    KEY_NAME_1: { N: "KEY_VALUE" },
                    KEY_NAME_2: { N: "KEY_VALUE" },
                    KEY_NAME_3: { N: "KEY_VALUE" },
                },
            ],
            ProjectionExpression: "ATTRIBUTE_NAME",
        ],
    },
};

export const run = async () => {
    try {
        const data = await ddbClient.send(new BatchGetItemCommand(params));
        console.log("Success, items retrieved", data);
    }
}
```

```
        return data;
    } catch (err) {
        console.log("Error", err);
    }
};

run();
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [BatchGetItem](#) in *AWS SDK for JavaScript API Reference*.

### SDK for JavaScript V2

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
    RequestItems: [
        {
            'TABLE_NAME': {
                Keys: [
                    {'KEY_NAME': {N: 'KEY_VALUE_1'}},
                    {'KEY_NAME': {N: 'KEY_VALUE_2'}},
                    {'KEY_NAME': {N: 'KEY_VALUE_3'}}
                ],
                ProjectionExpression: 'KEY_NAME, ATTRIBUTE'
            }
        }
    ];
};

ddb.batchGetItem(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        data.Responses.TABLE_NAME.forEach(function(element, index, array) {
            console.log(element);
        });
    }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [BatchGetItem](#) in *AWS SDK for JavaScript API Reference*.

### Python

#### SDK for Python (Boto3)

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
import decimal
```

```
import json
import logging
import os
import pprint
import time
import boto3
from botocore.exceptions import ClientError

logger = logging.getLogger(__name__)
dynamodb = boto3.resource('dynamodb')

MAX_GET_SIZE = 100 # Amazon DynamoDB rejects a get batch larger than 100 items.

def do_batch_get(batch_keys):
    """
    Gets a batch of items from Amazon DynamoDB. Batches can contain keys from
    more than one table.

    When Amazon DynamoDB cannot process all items in a batch, a set of unprocessed
    keys is returned. This function uses an exponential backoff algorithm to retry
    getting the unprocessed keys until all are retrieved or the specified
    number of tries is reached.

    :param batch_keys: The set of keys to retrieve. A batch can contain at most 100
                       keys. Otherwise, Amazon DynamoDB returns an error.
    :return: The dictionary of retrieved items grouped under their respective
             table names.
    """
    tries = 0
    max_tries = 5
    sleepy_time = 1 # Start with 1 second of sleep, then exponentially increase.
    retrieved = {key: [] for key in batch_keys}
    while tries < max_tries:
        response = dynamodb.batch_get_item(RequestItems=batch_keys)
        # Collect any retrieved items and retry unprocessed keys.
        for key in response.get('Responses', []):
            retrieved[key] += response['Responses'][key]
        unprocessed = response['UnprocessedKeys']
        if len(unprocessed) > 0:
            batch_keys = unprocessed
            unprocessed_count = sum(
                [len(batch_key['Keys']) for batch_key in batch_keys.values()])
            logger.info(
                "%s unprocessed keys returned. Sleep, then retry.", unprocessed_count)
            tries += 1
            if tries < max_tries:
                logger.info("Sleeping for %s seconds.", sleepy_time)
                time.sleep(sleepy_time)
                sleepy_time = min(sleepy_time * 2, 32)
            else:
                break
    return retrieved
```

- For API details, see [BatchGetItem](#) in [AWS SDK for Python \(Boto3\) API Reference](#).

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

# Get an item from a DynamoDB table using an AWS SDK

The following code examples show how to get an item from a DynamoDB table.

C++

## SDK for C++

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);
Aws::DynamoDB::Model::GetItemRequest req;

// Set up the request.
req.SetTableName(table);
Aws::DynamoDB::Model::AttributeValue hashKey;
hashKey.SetS(keyval);
req.AddKey(key, hashKey);

// Retrieve the item's fields and values
const Aws::DynamoDB::Model::GetItemOutcome& result =
dynamoClient.GetItem(req);
if (result.IsSuccess())
{
    // Reference the retrieved fields/values.
    const Aws::Map<Aws::String, Aws::DynamoDB::Model::AttributeValue>& item
= result.GetResult().GetItem();
    if (item.size() > 0)
    {
        // Output each retrieved field and its value.
        for (const auto& i : item)
            std::cout << "Values: " << i.first << ":" << i.second.GetS()
<< std::endl;
    }
    else
    {
        std::cout << "No item found with the key " << key << std::endl;
    }
}
else
{
    std::cout << "Failed to get item: " << result.GetError().GetMessage();
}
```

- For API details, see [GetItem](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the examples.  
// It contains a DynamoDB service client that is used to act on the specified table.  
type TableBasics struct {  
    DynamoDbClient *dynamodb.Client  
    TableName      string  
}  
  
  
// GetMovie gets movie data from the DynamoDB table by using the primary composite key  
// made of title and year.  
func (basics TableBasics) GetMovie(title string, year int) (Movie, error) {  
    movie := Movie{Title: title, Year: year}  
    response, err := basics.DynamoDbClient.GetItem(context.TODO(),  
        &dynamodb.GetItemInput{  
            Key: movie.GetKey(), TableName: aws.String(basics.TableName),  
        })  
    if err != nil {  
        log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)  
    } else {  
        err = attributevalue.UnmarshalMap(response.Item, &movie)  
        if err != nil {  
            log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)  
        }  
    }  
    return movie, err  
}
```

- For API details, see [GetItem](#) in *AWS SDK for Go API Reference*.

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Gets an item from a table by using the `DynamoDbClient`.

```
public static int queryTable(DynamoDbClient ddb, String tableName, String partitionKeyName, String partitionKeyVal, String partitionAlias) {  
  
    // Set up an alias for the partition key name in case it's a reserved word.  
    HashMap<String, String> attrNameAlias = new HashMap<String, String>();  
    attrNameAlias.put(partitionAlias, partitionKeyName);  
  
    // Set up mapping of the partition name with the value.  
    HashMap<String, AttributeValue> attrValues = new HashMap<>();  
  
    attrValues.put(":+" + partitionKeyName, AttributeValue.builder()  
        .s(partitionKeyVal)  
        .build());  
  
    QueryRequest queryReq = QueryRequest.builder()  
        .tableName(tableName)  
        .keyConditionExpression(partitionAlias + " = :" + partitionKeyName)  
        .expressionAttributeNames(attrNameAlias)  
        .expressionAttributeValues(attrValues)  
        .build();
```

```
try {
    QueryResponse response = ddb.query(queryReq);
    return response.count();

} catch (DynamoDbException e) {
    System.err.println(e.getMessage());
    System.exit(1);
}
return -1;
}
```

- For API details, see [GetItem](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Get an item from a table.

```
import { GetCommand } from "@aws-sdk/lib-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

// Set the parameters.
export const params = {
  TableName: "TABLE_NAME",
  Key: {
    primaryKey: "VALUE_1",
    sortKey: "VALUE_2",
  },
};

export const getItem = async () => {
  try {
    const data = await ddbDocClient.send(new GetCommand(params));
    console.log("Success :", data.Item);
  } catch (err) {
    console.log("Error", err);
  }
};
getItem();
```

Get an item from a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient";

const tableName = process.argv[2];
const movieTitle1 = process.argv[3];

export const run = async (tableName, movieTitle1) => {
  const params = {
    Statement: "SELECT * FROM " + tableName + " where title=?",
    Parameters: [{ S: movieTitle1 }],
  };
  try {
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
    for (let i = 0; i < data.Items.length; i++) {
      console.log(
        "Success. The query return the following data. Item " + i,
        data.Items[i].year,
        data.Items[i].title,
        data.Items[i].info
      );
    }
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(tableName, movieTitle1);
```

Get items by batch from a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2
) => {
  const params = {
    Statements: [
      {
        Statement: "SELECT * FROM " + tableName + " where title=? and year=?",
        Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
      },
      {
        Statement: "SELECT * FROM " + tableName + " where title=? and year=?",
        Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
      },
    ],
  };
  try {
    const data = await ddbDocClient.send(
      new BatchExecuteStatementCommand(params)
    );
    for (let i = 0; i < data.Responses.length; i++) {
      console.log(data.Responses[i].Item.year);
      console.log(data.Responses[i].Item.title);
    }
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);
```

- For API details, see [GetItem](#) in *AWS SDK for JavaScript API Reference*.

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Get an item from a table.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
  TableName: 'TABLE',
```

```
    Key: {
      'KEY_NAME': {N: '001'}
    },
    ProjectionExpression: 'ATTRIBUTE_NAME'
  };

// Call DynamoDB to read the item from the table
ddb.getItem(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

Get an item from a table using the DynamoDB document client.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
  TableName: 'EPISODES_TABLE',
  Key: {'KEY_NAME': VALUE}
};

docClient.get(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Item);
  }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [GetItem](#) in [AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun getSpecificItem(tableNameVal: String, keyName: String, keyVal: String)
{
  val keyToGet = mutableMapOf<String, AttributeValue>()
  keyToGet[keyName] = AttributeValue.S(keyVal)

  val request = GetItemRequest {
```

```
        key = keyToGet
        tableName = tableNameVal
    }

DynamoDbClient { region = "us-east-1" }.use { ddb ->
    val returnedItem = ddb.getItem(request)
    val numbersMap = returnedItem.item
    numbersMap?.forEach { key1 ->
        println(key1.key)
        println(key1.value)
    }
}
```

- For API details, see [GetItem](#) in *AWS SDK for Kotlin API reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
$movie = $service->getItemByKey($tableName, $key);
echo "\nThe movie {$movie['Item']['title'][0]} was released in
{$movie['Item'][0]['year'][0]}\n";

public function getItemByKey(string $tableName, array $key)
{
    return $this->dynamoDbClient->getItem([
        'Key' => $key['Item'],
        'TableName' => $tableName,
    ]);
}
```

- For API details, see [GetItem](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def get_movie(self, title, year):
        """
        Gets movie data from the table for a specific movie.

```

```
:param title: The title of the movie.
:param year: The release year of the movie.
:return: The data about the requested movie.
"""
try:
    response = self.table.get_item(Key={'year': year, 'title': title})
except ClientError as err:
    logger.error(
        "Couldn't get movie %s from table %s. Here's why: %s: %s",
        title, self.table.name,
        err.response['Error']['Code'], err.response['Error']['Message'])
    raise
else:
    return response['Item']
```

- For API details, see [GetItem](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Gets movie data from the table for a specific movie.
#
# @param title [String] The title of the movie.
# @param year [Integer] The release year of the movie.
# @return [Hash] The data about the requested movie.
def get_movie(title, year)
    response = @table.get_item(key: {"year" => year, "title" => title})
rescue Aws::Errors::ServiceError => e
    puts("Couldn't get movie #{title} from table #{@table.name}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
else
    response.item
end
```

- For API details, see [GetItem](#) in *AWS SDK for Ruby API Reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Get information about a DynamoDB table

The following code examples show how to get information about a DynamoDB table.

### C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
```

```

if (!region.empty())
    clientConfig.region = region;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

Aws::DynamoDB::Model::DescribeTableRequest dtr;
dtr.SetTableName(table);

const Aws::DynamoDB::Model::DescribeTableOutcome& result =
dynamoClient.DescribeTable(dtr);

if (result.IsSuccess())
{
    const Aws::DynamoDB::Model::TableDescription& td =
result.GetResult().GetTable();
    std::cout << "Table name : " << td.GetTableName() << std::endl;
    std::cout << "Table ARN : " << td.GetTableArn() << std::endl;
    std::cout << "Status : " <<
Aws::DynamoDB::Model::TableStatusMapper::GetNameForTableStatus(td.GetTableStatus())
<< std::endl;
    std::cout << "Item count : " << td.GetItemCount() << std::endl;
    std::cout << "Size (bytes): " << td.GetTableSizeBytes() << std::endl;

    const Aws::DynamoDB::Model::ProvisionedThroughputDescription& ptd =
td.GetProvisionedThroughput();
    std::cout << "Throughput" << std::endl;
    std::cout << " Read Capacity : " << ptd.GetReadCapacityUnits() <<
std::endl;
    std::cout << " Write Capacity: " << ptd.GetWriteCapacityUnits() <<
std::endl;

    const Aws::Vector<Aws::DynamoDB::Model::AttributeDefinition>& ad =
td.GetAttributeDefinitions();
    std::cout << "Attributes" << std::endl;
    for (const auto& a : ad)
        std::cout << " " << a.getAttributeName() << "(" <<

Aws::DynamoDB::Model::ScalarAttributeTypeMapper::GetNameForScalarAttributeType(a.getAttributeT
<<
        ")" << std::endl;
}
else
{
    std::cout << "Failed to describe table: " <<
result.GetError().GetMessage();
}

```

- For API details, see [DescribeTable](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```

// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
}

```

```
    TableName      string
}

// TableExists determines whether a DynamoDB table exists.
func (basics TableBasics) TableExists() (bool, error) {
    exists := true
    _, err := basics.DynamoDbClient.DescribeTable(
        context.TODO(), &dynamodb.DescribeTableInput{TableName:
            aws.String(basics.TableName)},
    )
    if err != nil {
        var notFoundEx *types.ResourceNotFoundException
        if errors.As(err, &notFoundEx) {
            log.Printf("Table %v does not exist.\n", basics.TableName)
            err = nil
        } else {
            log.Printf("Couldn't determine existence of table %v. Here's why: %v\n",
                basics.TableName, err)
        }
        exists = false
    }
    return exists, err
}
```

- For API details, see [DescribeTable](#) in *AWS SDK for Go API Reference*.

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static void describeDynamoDBTable(DynamoDbClient ddb, String tableName ) {
    DescribeTableRequest request = DescribeTableRequest.builder()
        .tableName(tableName)
        .build();

    try {
        TableDescription tableInfo = ddb.describeTable(request).table();
        if (tableInfo != null) {
            System.out.format("Table name : %s\n", tableInfo.tableName());
            System.out.format("Table ARN : %s\n", tableInfo.tableArn());
            System.out.format("Status : %s\n", tableInfo.tableStatus());
            System.out.format("Item count : %d\n",
                tableInfo.itemCount().longValue());
            System.out.format("Size (bytes): %d\n",
                tableInfo.tableSizeBytes().longValue());

            ProvisionedThroughputDescription throughputInfo =
                tableInfo.provisionedThroughput();
            System.out.println("Throughput");
            System.out.format(" Read Capacity : %d\n",
                throughputInfo.readCapacityUnits().longValue());
            System.out.format(" Write Capacity: %d\n",
                throughputInfo.writeCapacityUnits().longValue());
        }
    }
```

```
        List<AttributeDefinition> attributes =
    tableInfo.attributeDefinitions();
    System.out.println("Attributes");

    for (AttributeDefinition a : attributes) {
        System.out.format(" %s (%s)\n", a.attributeName(),
a.attributeType());
    }
}

} catch (DynamoDbException e) {
    System.err.println(e.getMessage());
    System.exit(1);
}
System.out.println("\nDone!");
}
```

- For API details, see [DescribeTable](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon DynamoDB service client object.
const ddbClient = new DynamoDBClient({ region: REGION });
export { ddbClient };
```

Describe the table.

```
// Import required AWS SDK clients and commands for Node.js
import { DescribeTableCommand } from "@aws-sdk/client-dynamodb";
import { ddbClient } from "./libs/ddbClient.js";

// Set the parameters
export const params = { TableName: "TABLE_NAME" }; //TABLE_NAME

export const run = async () => {
    try {
        const data = await ddbClient.send(new DescribeTableCommand(params));
        console.log("Success", data);
        // console.log("Success", data.Table.KeySchema);
        return data;
    } catch (err) {
        console.log("Error", err);
    }
};
run();
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).

- For API details, see [DescribeTable](#) in *AWS SDK for JavaScript API Reference*.

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
  TableName: process.argv[2]
};

// Call DynamoDB to retrieve the selected table descriptions
ddb.describeTable(params, function(err, data) {
  if (err) {
    console.log("Error", err);
  } else {
    console.log("Success", data.Table.KeySchema);
  }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [DescribeTable](#) in *AWS SDK for JavaScript API Reference*.

## Python

## SDK for Python (Boto3)

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def exists(self, table_name):
        """
        Determines whether a table exists. As a side effect, stores the table in
        a member variable.

        :param table_name: The name of the table to check.
        :return: True when the table exists; otherwise, False.
        """
        try:
            table = self.dyn_resource.Table(table_name)
            table.load()
            exists = True
        except ClientError as err:
```

```
if err.response['Error']['Code'] == 'ResourceNotFoundException':
    exists = False
else:
    logger.error(
        "Couldn't check for existence of %s. Here's why: %s: %s",
        table_name,
        err.response['Error']['Code'], err.response['Error']
    ['Message'])
    raise
else:
    self.table = table
return exists
```

- For API details, see [DescribeTable](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Determines whether a table exists. As a side effect, stores the table in
# a member variable.
#
# @param table_name [String] The name of the table to check.
# @return [Boolean] True when the table exists; otherwise, False.
def exists?(table_name)
    table = Aws::DynamoDB::Table.new(table_name)
    table.load
    @table = table
rescue Aws::DynamoDB::Errors::ResourceNotFoundException
    puts("Table #{table_name} doesn't exist. Let's create it.")
    false
rescue Aws::Errors::ServiceError => e
    puts("Couldn't check for existence of #{table_name}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
else
    !@table.nil?
end
```

- For API details, see [DescribeTable](#) in *AWS SDK for Ruby API Reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## List DynamoDB tables using an AWS SDK

The following code examples show how to list DynamoDB tables.

### C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

Aws::DynamoDB::Model::ListTablesRequest listTablesRequest;
listTablesRequest.SetLimit(50);
do
{
    const Aws::DynamoDB::Model::ListTablesOutcome& lto =
dynamoClient.ListTables(listTablesRequest);
    if (!lto.IsSuccess())
    {
        std::cout << "Error: " << lto.GetError().GetMessage() << std::endl;
        return 1;
    }

    for (const auto& s : lto.GetResult().GetTableNames())
        std::cout << s << std::endl;

    listTablesRequest.SetExclusiveStartTableName(lto.GetResult().GetLastEvaluatedTableName());
} while (!listTablesRequest.GetExclusiveStartTableName().empty());
```

- For API details, see [ListTables](#) in [AWS SDK for C++ API Reference](#).

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName      string
}

// ListTables lists the DynamoDB table names for the current account.
func (basics TableBasics) ListTables() ([]string, error) {
    var tableNames []string
    tables, err := basics.DynamoDbClient.ListTables(
        context.TODO(), &dynamodb.ListTablesInput{})
    if err != nil {
        log.Printf("Couldn't list tables. Here's why: %v\n", err)
    } else {
        tableNames = tables.TableNames
    }
    return tableNames, err
}
```

- For API details, see [ListTables](#) in [AWS SDK for Go API Reference](#).

Java

**SDK for Java 2.x**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
public static void listAllTables(DynamoDbClient ddb){

    boolean moreTables = true;
    String lastName = null;

    while(moreTables) {
        try {
            ListTablesResponse response = null;
            if (lastName == null) {
                ListTablesRequest request =
ListTablesRequest.builder().build();
                response = ddb.listTables(request);
            } else {
                ListTablesRequest request = ListTablesRequest.builder()
                    .exclusiveStartTableName(lastName).build();
                response = ddb.listTables(request);
            }

            List<String> tableNames = response.tableNames();
            if (tableNames.size() > 0) {
                for (String curName : tableNames) {
                    System.out.format("* %s\n", curName);
                }
            } else {
                System.out.println("No tables found!");
                System.exit(0);
            }

            lastName = response.lastEvaluatedTableName();
            if (lastName == null) {
                moreTables = false;
            }
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
    System.out.println("\nDone!");
}
```

- For API details, see [ListTables](#) in *AWS SDK for Java 2.x API Reference*.

JavaScript

**SDK for JavaScript V3**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create service client module using ES6 syntax.
```

```
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon DynamoDB service client object.
const ddbClient = new DynamoDBClient({ region: REGION });
export { ddbClient };
```

List the tables.

```
// Import required AWS SDK clients and commands for Node.js
import { ListTablesCommand } from "@aws-sdk/client-dynamodb";
import { ddbClient } from "./libs/ddbClient.js";

export const run = async () => {
  try {
    const data = await ddbClient.send(new ListTablesCommand({}));
    console.log(data);
    // console.log(data.TableNames.join("\n"));
    return data;
  } catch (err) {
    console.error(err);
  }
};
run();
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [ListTables](#) in [AWS SDK for JavaScript API Reference](#).

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

// Call DynamoDB to retrieve the list of tables
ddb.listTables({Limit: 10}, function(err, data) {
  if (err) {
    console.log("Error", err.code);
  } else {
    console.log("Table names are ", data.TableNames);
  }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [ListTables](#) in [AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun listAllTables() {  
  
    DynamoDbClient { region = "us-east-1" }.use { ddb ->  
        val response = ddb.listTables(ListTablesRequest {})  
        response.tableNames?.forEach { tableName ->  
            println("Table name is $tableName")  
        }  
    }  
}
```

- For API details, see [ListTables](#) in *AWS SDK for Kotlin API reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public function listTables($exclusiveStartTableName = "", $limit = 100)  
{  
    $this->dynamoDbClient->listTables([  
        'ExclusiveStartTableName' => $exclusiveStartTableName,  
        'Limit' => $limit,  
    ]);  
}
```

- For API details, see [ListTables](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:  
    """Encapsulates an Amazon DynamoDB table of movie data."""  
    def __init__(self, dyn_resource):  
        """  
        :param dyn_resource: A Boto3 DynamoDB resource.  
        """  
        self.dyn_resource = dyn_resource  
        self.table = None  
  
    def list_tables(self):  
        """
```

```
Lists the Amazon DynamoDB tables for the current account.

:return: The list of tables.
"""
try:
    tables = []
    for table in self.dyn_resource.tables.all():
        print(table.name)
        tables.append(table)
except ClientError as err:
    logger.error(
        "Couldn't list tables. Here's why: %s: %s",
        err.response['Error']['Code'], err.response['Error']['Message'])
    raise
else:
    return tables
```

- For API details, see [ListTables](#) in *AWS SDK for Python (Boto3) API Reference*.

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn list_tables(client: &Client) -> Result<(), Error> {
    let paginator = client.list_tables().intoPaginator().items().send();
    let table_names = paginator.collect::<Result<Vec<_>, _>>().await?;

    println!("Tables:");

    for name in &table_names {
        println!("  {}", name);
    }

    println!("Found {} tables", table_names.len());
    Ok(())
}
```

Determine whether table exists.

```
async fn does_table_exist(client: &Client, table: &str) -> Result<bool, Error> {
    let table_exists = client
        .list_tables()
        .send()
        .await
        .expect("should succeed")
        .tableNames()
        .asRef()
        .unwrap()
        .contains(&table.into());

    Ok(table_exists)
}
```

- For API details, see [ListTables](#) in *AWS SDK for Rust API reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Put an item in a DynamoDB table using an AWS SDK

The following code examples show how to put an item in a DynamoDB table.

### .NET

#### AWS SDK for .NET

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Adds a new item to the table.
/// </summary>
/// <param name="client">An initialized Amazon DynamoDB client object.</param>
/// <param name="newMovie">A Movie object containing information for
/// the movie to add to the table.</param>
/// <param name="tableName">The name of the table where the item will be
/// added.</param>
/// <returns>A Boolean value that indicates the results of adding the
/// item.</returns>
public static async Task<bool> PutItemAsync(AmazonDynamoDBClient client,
Movie newMovie, string tableName)
{
    var item = new Dictionary<string, AttributeValue>
    {
        ["title"] = new AttributeValue { S = newMovie.Title },
        ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
    };

    var request = new PutItemRequest
    {
        TableName = tableName,
        Item = item,
    };

    var response = await client.PutItemAsync(request);
    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [PutItem](#) in *AWS SDK for .NET API Reference*.

### C++

#### SDK for C++

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
```

```
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

Aws::DynamoDB::Model::PutItemRequest putItemRequest;
putItemRequest.SetTableName(table);

Aws::DynamoDB::Model::AttributeValue av;
av.SetS(keyVal);

Aws::DynamoDB::Model::AttributeValue album;
album.SetS(AlbumTitleValue);

Aws::DynamoDB::Model::AttributeValue awards;
awards.SetS(AwardVal);

Aws::DynamoDB::Model::AttributeValue song;
song.SetS(SongTitleVal);

// Add all AttributeValue objects.
putItemRequest.AddItem(key, av);
putItemRequest.AddItem(albumTitle, album);
putItemRequest.AddItem(Awards, awards);
putItemRequest.AddItem(SongTitle, song);

const Aws::DynamoDB::Model::PutItemOutcome result =
dynamoClient.PutItem(putItemRequest);
if (!result.IsSuccess())
{
    std::cout << result.GetError().GetMessage() << std::endl;
    return 1;
}
std::cout << "Successfully added Item!" << std::endl;
```

- For API details, see [PutItem](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName      string
}

// AddMovie adds a movie the DynamoDB table.
func (basics TableBasics) AddMovie(movie Movie) error {
    item, err := attributevalue.MarshalMap(movie)
    if err != nil {
        panic(err)
    }
    _, err = basics.DynamoDbClient.PutItem(context.TODO(), &dynamodb.PutItemInput{
        TableName: aws.String(basics.TableName), Item: item,
    })
}
```

```
if err != nil {
    log.Printf("Couldn't add item to table. Here's why: %v\n", err)
}
return err
}
```

- For API details, see [PutItem](#) in *AWS SDK for Go API Reference*.

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Puts an item into a table by using the enhanced client.

```
public static void putRecord(DynamoDbEnhancedClient enhancedClient) {

    try {
        DynamoDbTable<Customer> custTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));

        // Create an Instant value.
        LocalDate localDate = LocalDate.parse("2020-04-07");
        LocalDateTime localDateTime = localDate.atStartOfDay();
        Instant instant = localDateTime.toInstant(ZoneOffset.UTC);

        // Populate the Table.
        Customer custRecord = new Customer();
        custRecord.setCustName("Tom red");
        custRecord.setId("id119");
        custRecord.setEmail("tred@noserver.com");
        custRecord.setRegistrationDate(instant);

        // Put the customer data into an Amazon DynamoDB table.
        custTable.putItem(custRecord);

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    System.out.println("Customer data added to the table.");
}
```

- For API details, see [PutItem](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
```

```
// Set the AWS Region.  
export const REGION = "REGION"; // For example, "us-east-1".  
// Create an Amazon DynamoDB service client object.  
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.  
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";  
import { ddbClient } from "./ddbClient.js";  
// Set the AWS Region.  
const REGION = "REGION"; // For example, "us-east-1".  
  
const marshallOptions = {  
    // Whether to automatically convert empty strings, blobs, and sets to `null`.  
    convertEmptyValues: false, // false, by default.  
    // Whether to remove undefined values while marshalling.  
    removeUndefinedValues: false, // false, by default.  
    // Whether to convert typeof object to map attribute.  
    convertClassInstanceToMap: false, // false, by default.  
};  
  
const unmarshallOptions = {  
    // Whether to return numbers as a string instead of converting them to native  
    // JavaScript numbers.  
    wrapNumbers: false, // false, by default.  
};  
  
const translateConfig = { marshallOptions, unmarshallOptions };  
  
// Create the DynamoDB document client.  
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);  
  
export { ddbDocClient };
```

Put an item in a table using the DynamoDB document client.

```
import { PutCommand } from "@aws-sdk/lib-dynamodb";  
import { ddbDocClient } from "../libs/ddbDocClient.js";  
  
export const putItem = async () => {  
    // Set the parameters.  
    export const params = {  
        TableName: "TABLE_NAME",  
        Item: {  
            primaryKey: "VALUE_1",  
            sortKey: "VALUE_2",  
        },  
    };  
    try {  
        const data = await ddbDocClient.send(new PutCommand(params));  
        console.log("Success - item added or updated", data);  
    } catch (err) {  
        console.log("Error", err.stack);  
    }  
};  
putItem();
```

Put an item in a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];

export const run = async (tableName, movieTitle1, movieYear1) => {
  const params = {
    Statement: "INSERT INTO " + tableName + " value {'title':?, 'year':?}",
    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
  };
  try {
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
    console.log("Success. Item added.");
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
}
run(tableName, movieTitle1, movieYear1);
```

Put items by batch in a table using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2
) => {
  const params = {
    Statements: [
      {
        Statement:
          "INSERT INTO " + tableName + " value {'title':?, 'year':?}",
        Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
      },
      {
        Statement:
          "INSERT INTO " + tableName + " value {'title':?, 'year':?}",
        Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
      },
    ],
  };
  try {
    const data = await ddbDocClient.send(
      new BatchExecuteStatementCommand(params)
    );
    console.log("Success. Items added.");
  } catch (err) {
    console.error(err);
  }
}
```

```
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};

run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);
```

- For API details, see [PutItem](#) in *AWS SDK for JavaScript API Reference*.

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Put an item in a table.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create the DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
    TableName: 'CUSTOMER_LIST',
    Item: {
        'CUSTOMER_ID' : {N: '001'},
        'CUSTOMER_NAME' : {S: 'Richard Roe'}
    }
};

// Call DynamoDB to add the item to the table
ddb.putItem(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Success", data);
    }
});
```

Put an item in a table using the DynamoDB document client.

```
// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
    TableName: 'TABLE',
    Item: {
        'HASHKEY': VALUE,
        'ATTRIBUTE_1': 'STRING_VALUE',
        'ATTRIBUTE_2': VALUE_2
    }
};

docClient.put(params, function(err, data) {
    if (err) {
```

```
        console.log("Error", err);
    } else {
        console.log("Success", data);
    });
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [PutItem](#) in [AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun putItemInTable(
    tableNameVal: String,
    key: String,
    keyVal: String,
    albumTitle: String,
    albumTitleValue: String,
    awards: String,
    awardVal: String,
    songTitle: String,
    songTitleVal: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()

    // Add all content to the table.
    itemValues[key] = AttributeValue.S(keyVal)
    itemValues[songTitle] = AttributeValue.S(songTitleVal)
    itemValues[albumTitle] = AttributeValue.S(albumTitleValue)
    itemValues[awards] = AttributeValue.S(awardVal)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println(" A new item was placed into $tableNameVal.")
    }
}
```

- For API details, see [PutItem](#) in [AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
echo "What's the name of the last movie you watched?\n";
while (empty($movieName)) {
    $movieName = testable_readline("Movie name: ");
}
echo "And what year was it released?\n";
$movieYear = "year";
while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
    $movieYear = testable_readline("Year released: ");
}

$service->putItem([
    'Item' => [
        'year' => [
            'N' => "$movieYear",
        ],
        'title' => [
            'S' => $movieName,
        ],
    ],
    'TableName' => $tableName,
]);
}

public function putItem(array $array)
{
    $this->dynamoDbClient->putItem($array);
}
```

- For API details, see [PutItem](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def add_movie(self, title, year, plot, rating):
        """
        Adds a movie to the table.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :param plot: The plot summary of the movie.
        :param rating: The quality rating of the movie.
        """
        try:
            self.table.put_item(
                Item={
                    'year': year,
                    'title': title,
                    'info': {'plot': plot, 'rating': Decimal(str(rating))}})
        except ClientError as err:
```

```
logger.error(
    "Couldn't add movie %s to table %s. Here's why: %s: %s",
    title, self.table.name,
    err.response['Error']['Code'], err.response['Error']['Message'])
raise
```

- For API details, see [PutItem](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Adds a movie to the table.
#
# @param title [String] The title of the movie.
# @param year [Integer] The release year of the movie.
# @param plot [String] The plot summary of the movie.
# @param rating [Float] The quality rating of the movie.
def add_movie(title:, year:, plot:, rating:)
  @table.put_item(
    item: {
      "year" => year,
      "title" => title,
      "info" => {"plot" => plot, "rating" => rating}})
  rescue Aws::Errors::ServiceError => e
    puts("Couldn't add movie #{title} to table #{@table.name}. Here's why:")
    puts("\t#{e.code}: #{e.message}")
    raise
end
```

- For API details, see [PutItem](#) in *AWS SDK for Ruby API Reference*.

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn add_item(
    client: &Client,
    table: &str,
    username: &str,
    p_type: &str,
    age: &str,
    first: &str,
    last: &str,
) -> Result<(), Error> {
    let user_av = AttributeValue::S(username.into());
    let type_av = AttributeValue::S(p_type.into());
    let age_av = AttributeValue::S(age.into());
```

```

let first_av = AttributeValue::S(first.into());
let last_av = AttributeValue::S(last.into());

let request = client
    .put_item()
    .table_name(table)
    .item("username", user_av)
    .item("account_type", type_av)
    .item("age", age_av)
    .item("first_name", first_av)
    .item("last_name", last_av);

println!("Executing request [{:?}] to add item...", request);

request.send().await?;

println!(
    "Added user {}, {}, age {} as {} user",
    username, first, last, age, p_type
);

Ok(())
}

```

- For API details, see [PutItem](#) in *AWS SDK for Rust API reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Query a DynamoDB table using an AWS SDK

The following code examples show how to query a DynamoDB table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

///<summary>
/// Queries the table for movies released in a particular year and
/// then displays the information for the movies returned.
///</summary>
///<param name="client">The initialized DynamoDB client object.</param>
///<param name="tableName">The name of the table to query.</param>
///<param name="year">The release year for which we want to
/// view movies.</param>
///<returns>The number of movies that match the query.</returns>
public static async Task<int> QueryMoviesAsync(AmazonDynamoDBClient client,
string tableName, int year)
{
    var movieTable = Table.LoadTable(client, tableName);
    var filter = new QueryFilter("year", QueryOperator.Equal, year);

    Console.WriteLine("\nFind movies released in: {year}:");

    var config = new QueryOperationConfig()
    {

```

```

        Limit = 10, // 10 items per page.
        Select = SelectValues.SpecificAttributes,
        AttributesToGet = new List<string>
        {
            "title",
            "year",
        },
        ConsistentRead = true,
        Filter = filter,
    };

    // Value used to track how many movies match the
    // supplied criteria.
    var moviesFound = 0;

    Search search = movieTable.Query(config);
    do
    {
        var movieList = await search.GetNextSetAsync();
        moviesFound += movieList.Count;

        foreach (var movie in movieList)
        {
            DisplayDocument(movie);
        }
    }
    while (!search.IsDone);

    return moviesFound;
}

```

- For API details, see [Query](#) in *AWS SDK for .NET API Reference*.

## C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

Aws::Client::ClientConfiguration clientConfig;

Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);
Aws::DynamoDB::Model::QueryRequest req;

req.SetTableName(table);

// Set query key condition expression
req.SetKeyConditionExpression(partitionKeyAttributeName +
"= :valueToMatch");

// Set Expression AttributeValues
Aws::Map< Aws::String, Aws::DynamoDB::Model::AttributeValue>
attributeValues;
attributeValues.emplace(":valueToMatch", partitionKeyValue);

req.SetExpressionAttributeValues(attributeValues);

// Perform Query operation
const Aws::DynamoDB::Model::QueryOutcome& result = dynamoClient.Query(req);
if (result.IsSuccess())

```

```

    {
        // Reference the retrieved items
        const Aws::Vector<Aws::Map<Aws::String,
        Aws::DynamoDB::Model::AttributeValue>>& items = result.GetResult().GetItems();
        if(items.size() > 0)
        {
            std::cout << "Number of items retrieved from Query: " <<
            items.size() << std::endl;
            //Iterate each item and print
            for(const auto &item: items)
            {
                std::cout <<
                "*****" << std::endl;
                // Output each retrieved field and its value
                for (const auto& i : item)
                    std::cout << i.first << ":" << i.second.GetS() << std::endl;
            }
        }
        else
        {
            std::cout << "No item found in table: " << table << std::endl;
        }
    }
    else
    {
        std::cout << "Failed to Query items: " <<
        result.GetError().GetMessage();
    }
}

```

- For API details, see [Query](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```

// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// Query gets all movies in the DynamoDB table that were released in the specified
// year.
// The function uses the `expression` package to build the key condition expression
// that is used in the query.
func (basics TableBasics) Query(releaseYear int) ([]Movie, error) {
    var err error
    var response *dynamodb.QueryOutput
    var movies []Movie
    keyEx := expression.Key("year").Equal(expression.Value(releaseYear))
    expr, err := expression.NewBuilder().WithKeyCondition(keyEx).Build()
    if err != nil {

```

```
    log.Printf("Couldn't build expression for query. Here's why: %v\n", err)
} else {
    response, err = basics.DynamoDbClient.Query(context.TODO(), &dynamodb.QueryInput{
        TableName:                 aws.String(basics.TableName),
        ExpressionAttributeNames: expr.Names(),
        ExpressionAttributeValues: expr.Values(),
        KeyConditionExpression:   expr.KeyCondition(),
    })
    if err != nil {
        log.Printf("Couldn't query for movies released in %v. Here's why: %v\n",
            releaseYear, err)
    } else {
        err = attributevalue.UnmarshalListOfMaps(response.Items, &movies)
        if err != nil {
            log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
        }
    }
}
return movies, err
}
```

- For API details, see [Query](#) in *AWS SDK for Go API Reference*.

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Queries a table by using the enhanced client.

```
public static String queryTable(DynamoDbEnhancedClient enhancedClient) {

    try{
        DynamoDbTable<Customer> mappedTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));
        QueryConditional queryConditional =
QueryConditional.keyEqualTo(Key.builder()
            .partitionValue("id101")
            .build());

        // Get items in the table and write out the ID value.
        Iterator<Customer> results =
mappedTable.query(queryConditional).items().iterator();
        String result="";

        while (results.hasNext()) {
            Customer rec = results.next();
            result = rec.getId();
            System.out.println("The record id is "+result);
        }
        return result;
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return "";
}
```

Queries a table by using the enhanced client and a secondary index.

```

public static void queryIndex(DynamoDbClient ddb, String tableName) {

    try {
        // Create a DynamoDbEnhancedClient and use the DynamoDbClient object.
        DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
            .dynamoDbClient(ddb)
            .build();

        //Create a DynamoDbTable object based on Movies.
        DynamoDbTable<Movies> table = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
        String dateVal = "2013";

        DynamoDbIndex<Movies> secIndex = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class)) .index("year-index");
        AttributeValue attVal = AttributeValue.builder()
            .n(dateVal)
            .build();

        // Create a QueryConditional object that's used in the query operation.
        QueryConditional queryConditional = QueryConditional
            .keyEqualTo(Key.builder().partitionValue(attVal)
            .build());

        // Get items in the table.
        SdkIterable<Page<Movies>> results =
secIndex.query(QueryEnhancedRequest.builder()
            .queryConditional(queryConditional)
            .limit(300)
            .build());

        // Display the results.
        results.forEach(page -> {
            List<Movies> allMovies = page.items();
            for (Movies myMovies: allMovies) {
                System.out.println("The movie title is " + myMovies.getTitle()
+ ". The year is " + myMovies.getYear());
            }
        });

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}

```

Queries a table by using the DynamoDbClient.

```

public static int queryTable(DynamoDbClient ddb, String tableName, String
partitionKeyName, String partitionKeyVal, String partitionAlias) {

    // Set up an alias for the partition key name in case it's a reserved word.
    HashMap<String, String> attrNameAlias = new HashMap<String, String>();
    attrNameAlias.put(partitionAlias, partitionKeyName);

    // Set up mapping of the partition name with the value.
    HashMap<String, AttributeValue> attrValues = new HashMap<>();

    attrValues.put(":+" + partitionKeyName, AttributeValue.builder()
        .s(partitionKeyVal)

```

```
.build());  
  
QueryRequest queryReq = QueryRequest.builder()  
.tableName(tableName)  
.keyConditionExpression(partitionAlias + " = :" + partitionKeyName)  
.expressionAttributeNames(attrNameAlias)  
.expressionAttributeValues(attrValues)  
.build();  
  
try {  
    QueryResponse response = ddb.query(queryReq);  
    return response.count();  
  
} catch (DynamoDbException e) {  
    System.err.println(e.getMessage());  
    System.exit(1);  
}  
return -1;  
}
```

Queries a table by using the DynamoDbClient and a secondary index.

```
public static void queryIndex(DynamoDbClient ddb, String tableName) {  
  
    try {  
        Map<String, String> expressionAttributesNames = new HashMap<>();  
        expressionAttributesNames.put("#year", "year");  
        Map<String, AttributeValue> expressionAttributeValues = new  
        HashMap<>();  
        expressionAttributeValues.put(":yearValue",  
        AttributeValue.builder().n("2013").build());  
  
        QueryRequest request = QueryRequest.builder()  
            .tableName(tableName)  
            .indexName("year-index")  
            .keyConditionExpression("#year = :yearValue")  
            .expressionAttributeNames(expressionAttributesNames)  
            .expressionAttributeValues(expressionAttributeValues)  
            .build();  
  
        System.out.println("== Movie Titles ==");  
        QueryResponse response = ddb.query(request);  
        response.items()  
            .forEach(movie -> System.out.println(movie.get("title").s()));  
  
    } catch (DynamoDbException e) {  
        System.err.println(e.getMessage());  
        System.exit(1);  
    }  
}
```

- For API details, see [Query](#) in [AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
const REGION = "REGION"; //e.g. "us-east-1"
// Create an Amazon DynamoDB service client object.
const ddbClient = new DynamoDBClient({ region: REGION });
export { ddbClient };
```

Query the table.

```
// Import required AWS SDK clients and commands for Node.js
import { QueryCommand } from "@aws-sdk/client-dynamodb";
import { ddbClient } from "./libs/ddbClient.js";

// Set the parameters
export const params = {
    KeyConditionExpression: "Season = :s and Episode > :e",
    FilterExpression: "contains (Subtitle, :topic)",
    ExpressionAttributeValues: {
        ":s": { N: "1" },
        ":e": { N: "2" },
        ":topic": { S: "SubTitle" },
    },
    ProjectionExpression: "Episode, Title, Subtitle",
    TableName: "EPISODES_TABLE",
};

export const run = async () => {
    try {
        const data = await ddbClient.send(new QueryCommand(params));
        return data;
        data.Items.forEach(function (element, index, array) {
            console.log(element.Title.S + " (" + element.Subtitle.S + ")");
        });
    } catch (err) {
        console.error(err);
    }
};
run();
```

Create the client for the DynamoDB document client.

```
// Create service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient";

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};
```

```

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB Document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };

```

Query the table using the DynamoDB document client.

```

import { QueryCommand } from "@aws-sdk/lib-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

// Set the parameters.
export const params = {
    ExpressionAttributeNames: { "#r": "rank", "#y": "year" },
    ProjectionExpression: "#r, #y, title",
    TableName: "TABLE_NAME",
    ExpressionAttributeValues: {
        ":t": "MOVIE_NAME",
        ":y": "MOVIE_YEAR",
        ":r": "MOVIE_RANK",
    },
    KeyConditionExpression: "title = :t and #y = :y",
    FilterExpression: "info.#r = :r",
};

export const queryTable = async () => {
    try {
        const data = await ddbDocClient.send(new QueryCommand(params));
        for (let i = 0; i < data.Items.length; i++) {
            console.log(
                "Success. Items with rank of " +
                "MOVIE_RANK" +
                " include\n" +
                "Year = " +
                data.Items[i].year +
                " Title = " +
                data.Items[i].title
            );
        }
    } catch (err) {
        console.log("Error", err);
    }
};
queryTable();

```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [Query in AWS SDK for JavaScript API Reference](#).

#### SDK for JavaScript V2

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```

// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB document client

```

```
var docClient = new AWS.DynamoDB.DocumentClient({apiVersion: '2012-08-10'});

var params = {
    ExpressionAttributeValues: {
        ':s': 2,
        ':e': 9,
        ':topic': 'PHRASE'
    },
    KeyConditionExpression: 'Season = :s and Episode > :e',
    FilterExpression: 'contains (Subtitle, :topic)',
    TableName: 'EPISODES_TABLE'
};

docClient.query(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Success", data.Items);
    }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [Query](#) in [AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun queryDynTable(
    tableNameVal: String,
    partitionKeyName: String,
    partitionKeyVal: String,
    partitionAlias: String
): Int {

    val attrNameAlias = mutableMapOf<String, String>()
    attrNameAlias[partitionAlias] = partitionKeyName

    // Set up mapping of the partition name with the value.
    val attrValues = mutableMapOf<String, AttributeValue>()
    attrValues[":$partitionKeyName"] = AttributeValue.S(partitionKeyVal)

    val request = QueryRequest {
        tableName = tableNameVal
        keyConditionExpression = "$partitionAlias = :$partitionKeyName"
        expressionAttributeNames = attrNameAlias
        this.expressionAttributeValues = attrValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.query(request)
        return response.count
    }
}
```

- For API details, see [Query](#) in *AWS SDK for Kotlin API reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
$birthKey = [
    'Key' => [
        'year' => [
            'N' => "$birthYear",
        ],
    ],
];
$result = $service->query($tableName, $birthKey);

public function query(string $tableName, $key)
{
    $expressionAttributeValues = [];
    $expressionAttributeNames = [];
    $keyConditionExpression = "";
    $index = 1;
    foreach ($key as $name => $value) {
        $keyConditionExpression .= "#" . array_key_first($value) . " = :"v
$index,";
        $expressionAttributeNames["#" . array_key_first($value)] =
array_key_first($value);
        $hold = array_pop($value);
        $expressionAttributeValues[":v{$index}"] = [
            array_key_first($hold) => array_pop($hold),
        ];
    }
    $keyConditionExpression = substr($keyConditionExpression, 0, -1);
    $query = [
        'ExpressionAttributeValues' => $expressionAttributeValues,
        'ExpressionAttributeNames' => $expressionAttributeNames,
        'KeyConditionExpression' => $keyConditionExpression,
        'TableName' => $tableName,
    ];
    return $this->dynamoDbClient->query($query);
}
```

- For API details, see [Query](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Query items by using a key condition expression.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
```

```

"""
:param dyn_resource: A Boto3 DynamoDB resource.
"""
self.dyn_resource = dyn_resource
self.table = None

def query_movies(self, year):
    """
    Queries for movies that were released in the specified year.

    :param year: The year to query.
    :return: The list of movies that were released in the specified year.
    """
    try:
        response =
self.table.query(KeyConditionExpression=Key('year').eq(year))
    except ClientError as err:
        logger.error(
            "Couldn't query for movies released in %s. Here's why: %s: %s",
year,
            err.response['Error']['Code'], err.response['Error']['Message'])
        raise
    else:
        return response['Items']

```

Query items and project them to return a subset of data.

```

class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table

    def query_and_project_movies(self, year, title_bounds):
        """
        Query for movies that were released in a specified year and that have
titles
        that start within a range of letters. A projection expression is used
        to return a subset of data for each movie.

        :param year: The release year to query.
        :param title_bounds: The range of starting letters to query.
        :return: The list of movies.
        """
        try:
            response = self.table.query(
                ProjectionExpression="#yr, title, info.genres, info.actors[0]",
                ExpressionAttributeNames={"#yr": "year"},
                KeyConditionExpression=(
                    Key('year').eq(year) &
                    Key('title').between(title_bounds['first'],
title_bounds['second'])))
        except ClientError as err:
            if err.response['Error']['Code'] == "ValidationException":
                logger.warning(
                    "There's a validation error. Here's the message: %s: %s",
                    err.response['Error']['Code'], err.response['Error']
['Message'])
            else:
                logger.error(
                    "Couldn't query for movies. Here's why: %s: %s",
                    err.response['Error']['Code'], err.response['Error']
['Message'])
                raise
            else:
                return response['Items']

```

- For API details, see [Query](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Queries for movies that were released in the specified year.
#
# @param year [Integer] The year to query.
# @return [Array] The list of movies that were released in the specified year.
def query_movies(year)
    response = @table.query(
        key_condition_expression: "#yr = :year",
        expression_attribute_names: {"#yr" => "year"},
        expression_attribute_values: {":year" => year})
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't query for movies released in #{year}. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        response.items
    end
```

- For API details, see [Query](#) in *AWS SDK for Ruby API Reference*.

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Find the movies made in the specified year.

```
fn movies_in_year(client: &Client, table_name: &str, year: u16) -> Query {
    client
        .query()
        .table_name(table_name)
        .key_condition_expression("#yr = :yyyy")
        .expression_attribute_names("#yr", "year")
        .expression_attribute_values(":yyyy", AttributeValue::N(year.to_string()))
}
```

- For API details, see [Query](#) in *AWS SDK for Rust API reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Run a PartiQL statement on a DynamoDB table using an AWS SDK

The following code examples show how to run a PartiQL statement on a DynamoDB table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Use an INSERT statement to add an item.

```
/// <summary>
/// Inserts a single movie into the movies table.
/// </summary>
/// <param name="tableName">The name of the table.</param>
/// <param name="movieTitle">The title of the movie to insert.</param>
/// <param name="year">The year that the movie was released.</param>
/// <returns>A Boolean value that indicates the success or failure of
/// the INSERT operation.</returns>
public static async Task<bool> InsertSingleMovie(string tableName, string
movieTitle, int year)
{
    string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?, 'year': ?}}";

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = insertBatch,
    Parameters = new List<AttributeValue>
    {
        new AttributeValue { S = movieTitle },
        new AttributeValue { N = year.ToString() },
    },
});
}

return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

Use a SELECT statement to get an item.

```
/// <summary>
/// Uses a PartiQL SELECT statement to retrieve a single movie from the
/// movie database.
/// </summary>
/// <param name="tableName">The name of the movie table.</param>
/// <param name="movieTitle">The title of the movie to retrieve.</param>
/// <returns>A list of movie data. If no movie matches the supplied
/// title, the list is empty.</returns>
public static async Task<List<Dictionary<string, AttributeValue>>>
GetSingleMovie(string tableName, string movieTitle)
{
    string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
    var parameters = new List<AttributeValue>
{
```

```

        new AttributeValue { S = movieTitle },
    };

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = selectSingle,
    Parameters = parameters,
});

return response.Items;
}

```

Use a SELECT statement to get a list of items.

```

/// <summary>
/// Retrieve multiple movies by year using a SELECT statement.
/// </summary>
/// <param name="tableName">The name of the movie table.</param>
/// <param name="year">The year the movies were released.</param>
/// <returns></returns>
public static async Task<List<Dictionary<string,AttributeValue>>>
GetMovies(string tableName, int year)
{
    string selectSingle = $"SELECT * FROM {tableName} WHERE year = ?";
    var parameters = new List<AttributeValue>
    {
        new AttributeValue { N = year.ToString() },
    };

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = selectSingle,
    Parameters = parameters,
});

    return response.Items;
}

```

Use an UPDATE statement to update an item.

```

/// <summary>
/// Updates a single movie in the table, adding information for the
/// producer.
/// </summary>
/// <param name="tableName">the name of the table.</param>
/// <param name="producer">The name of the producer.</param>
/// <param name="movieTitle">The movie title.</param>
/// <param name="year">The year the movie was released.</param>
/// <returns>A Boolean value that indicates the success of the
/// UPDATE operation.</returns>
public static async Task<bool> UpdateSingleMovie(string tableName, string
producer, string movieTitle, int year)
{
    string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

```

```
var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = insertSingle,
    Parameters = new List<AttributeValue>
    {
        new AttributeValue { S = producer },
        new AttributeValue { S = movieTitle },
        new AttributeValue { N = year.ToString() },
    },
});

return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

Use a DELETE statement to delete a single movie.

```
/// <summary>
/// Deletes a single movie from the table.
/// </summary>
/// <param name="tableName">The name of the table.</param>
/// <param name="movieTitle">The title of the movie to delete.</param>
/// <param name="year">The year that the movie was released.</param>
/// <returns>A Boolean value that indicates the success of the
/// DELETE operation.</returns>
public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
{
    var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = deleteSingle,
    Parameters = new List<AttributeValue>
    {
        new AttributeValue { S = movieTitle },
        new AttributeValue { N = year.ToString() },
    },
});

    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [ExecuteStatement](#) in *AWS SDK for .NET API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Use an INSERT statement to add an item.

```
// AddMovie runs a PartiQL INSERT statement to add a movie to the DynamoDB table.
```

```
func (runner PartiQLRunner) AddMovie(movie Movie) error {
    params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
    movie.Info})
    if err != nil {
        panic(err)
    }
    _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
            fmt.Sprintf("INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
            runner.TableName)),
        Parameters: params,
    })
    if err != nil {
        log.Printf("Couldn't insert an item with PartiQL. Here's why: %v\n", err)
    }
    return err
}
```

Use a SELECT statement to get an item.

```
// GetMovie runs a PartiQL SELECT statement to get a movie from the DynamoDB table
// by
// title and year.
func (runner PartiQLRunner) GetMovie(title string, year int) (Movie, error) {
    var movie Movie
    params, err := attributevalue.MarshalList([]interface{}{title, year})
    if err != nil {
        panic(err)
    }
    response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
            fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
            runner.TableName)),
        Parameters: params,
    })
    if err != nil {
        log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
    } else {
        err = attributevalue.UnmarshalMap(response.Items[0], &movie)
        if err != nil {
            log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
        }
    }
    return movie, err
}
```

Use a SELECT statement to get a list of items and project the results.

```
// GetAllMovies runs a PartiQL SELECT statement to get all movies from the DynamoDB
// table.
// The results are projected to return only the title and rating of each movie.
func (runner PartiQLRunner) GetAllMovies() ([]map[string]interface{}, error) {
    var output []map[string]interface{}
    response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
```

```
    fmt.Sprintf("SELECT title, info.rating FROM \"%v\"", runner.TableName)),
})
if err != nil {
    log.Printf("Couldn't get movies. Here's why: %v\n", err)
} else {
    err = attributevalue.UnmarshalListOfMaps(response.Items, &output)
    if err != nil {
        log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
    }
}
return output, err
}
```

Use an UPDATE statement to update an item.

```
// UpdateMovie runs a PartiQL UPDATE statement to update the rating of a movie that
// already exists in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovie(movie Movie, rating float64) error {
    params, err := attributevalue.MarshalList([]interface{}{rating, movie.Title,
    movie.Year})
    if err != nil {
        panic(err)
    }
    _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
            fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
            runner.TableName)),
        Parameters: params,
    })
    if err != nil {
        log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
    }
    return err
}
```

Use a DELETE statement to delete an item.

```
// DeleteMovie runs a PartiQL DELETE statement to remove a movie from the DynamoDB
// table.
func (runner PartiQLRunner) DeleteMovie(movie Movie) error {
    params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
    if err != nil {
        panic(err)
    }
    _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
            fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
            runner.TableName)),
        Parameters: params,
    })
    if err != nil {
        log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
        err)
    }
    return err
}
```

- For API details, see [ExecuteStatement](#) in *AWS SDK for Go API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.  
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";  
// Set the AWS Region.  
export const REGION = "eu-west-1"; // For example, "us-east-1".  
// Create an Amazon DynamoDB service client object.  
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.  
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";  
import { ddbClient } from "./ddbClient.js";  
// Set the AWS Region.  
const REGION = "eu-west-1"; // For example, "us-east-1".  
  
const marshallOptions = {  
    // Whether to automatically convert empty strings, blobs, and sets to `null`.  
    convertEmptyValues: false, // false, by default.  
    // Whether to remove undefined values while marshalling.  
    removeUndefinedValues: false, // false, by default.  
    // Whether to convert typeof object to map attribute.  
    convertClassInstanceToMap: false, // false, by default.  
};  
  
const unmarshallOptions = {  
    // Whether to return numbers as a string instead of converting them to native  
    // JavaScript numbers.  
    wrapNumbers: false, // false, by default.  
};  
  
const translateConfig = { marshallOptions, unmarshallOptions };  
  
// Create the DynamoDB document client.  
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);  
  
export { ddbDocClient };
```

Create an item using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.  
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";  
import { ddbDocClient } from "../libs/ddbDocClient.js";  
  
const tableName = process.argv[2];
```

```
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];

export const run = async (tableName, movieTitle1, movieYear1) => {
    const params = {
        Statement: "INSERT INTO " + tableName + " value {'title':?, 'year':?}",
        Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
    };
    try {
        const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
        console.log("Success. Item added.");
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};
run(tableName, movieTitle1, movieYear1);
```

Get an item using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient";

const tableName = process.argv[2];
const movieTitle1 = process.argv[3];

export const run = async (tableName, movieTitle1) => {
    const params = {
        Statement: "SELECT * FROM " + tableName + " where title=?",
        Parameters: [{ S: movieTitle1 }],
    };
    try {
        const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
        for (let i = 0; i < data.Items.length; i++) {
            console.log(
                "Success. The query return the following data. Item " + i,
                data.Items[i].year,
                data.Items[i].title,
                data.Items[i].info
            );
        }
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};
run(tableName, movieTitle1);
```

Update an item using PartiQL.

```
// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const producer1 = process.argv[5];
```

```

export const run = async (tableName, movieYear1, movieTitle1, producer1) => {
  const params = {
    Statement:
      "UPDATE " + tableName + " SET Producer=? where title=? and year=?",
    Parameters: [{ S: producer1 }, { S: movieTitle1 }, { N: movieYear1 }],
  };
  try {
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
    console.log("Success. Item updated.");
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(tableName, movieYear1, movieTitle1, producer1);

```

Delete an item using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];

export const run = async (tableName, movieYear1, movieTitle1) => {
  const params = {
    Statement: "DELETE FROM " + tableName + " where title=? and year=?",
    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
  };
  try {
    const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
    console.log("Success. Item deleted.");
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(tableName, movieYear1, movieTitle1);

```

- For API details, see [ExecuteStatement](#) in *AWS SDK for JavaScript API Reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

public function insertItemByPartiQL(string $statement, array $parameters)
{
    $this->dynamoDbClient->executeStatement([
        'Statement' => "$statement",
        'Parameters' => $parameters,
    ]);
}

public function getItemByPartiQL(string $tableName, array $key): Result

```

```
{  
    list($statement, $parameters) = $this->buildStatementAndParameters("SELECT", $tableName, $key['Item']);  
  
    return $this->dynamoDbClient->executeStatement([  
        'Parameters' => $parameters,  
        'Statement' => $statement,  
    ]);  
}  
  
public function updateItemByPartiQL(string $statement, array $parameters)  
{  
    $this->dynamoDbClient->executeStatement([  
        'Statement' => $statement,  
        'Parameters' => $parameters,  
    ]);  
}  
  
public function deleteItemByPartiQL(string $statement, array $parameters)  
{  
    $this->dynamoDbClient->executeStatement([  
        'Statement' => $statement,  
        'Parameters' => $parameters,  
    ]);  
}
```

- For API details, see [ExecuteStatement](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class PartiQLWrapper:  
    """  
    Encapsulates a DynamoDB resource to run PartiQL statements.  
    """  
    def __init__(self, dyn_resource):  
        """  
        :param dyn_resource: A Boto3 DynamoDB resource.  
        """  
        self.dyn_resource = dyn_resource  
  
    def run_partiql(self, statement, params):  
        """  
        Runs a PartiQL statement. A Boto3 resource is used even though  
        `execute_statement` is called on the underlying `client` object because the  
        resource transforms input and output from plain old Python objects (POPOs)  
        to  
        the DynamoDB format. If you create the client directly, you must do these  
        transforms yourself.  
  
        :param statement: The PartiQL statement.  
        :param params: The list of PartiQL parameters. These are applied to the  
                      statement in the order they are listed.  
        :return: The items returned from the statement, if any.  
        """  
        try:  
            output = self.dyn_resource.meta.client.execute_statement(  
                Statement=statement, Parameters=params)
```

```
        except ClientError as err:
            if err.response['Error']['Code'] == 'ResourceNotFoundException':
                logger.error(
                    "Couldn't execute PartiQL '%s' because the table does not
exist.", statement)
            else:
                logger.error(
                    "Couldn't execute PartiQL '%s'. Here's why: %s: %s", statement,
                    err.response['Error']['Code'], err.response['Error']
                ['Message'])
            raise
        else:
            return output
```

- For API details, see [ExecuteStatement](#) in *AWS SDK for Python (Boto3) API Reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Run batches of PartiQL statements on a DynamoDB table using an AWS SDK

The following code examples show how to run batches of PartiQL statements on a DynamoDB table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Use batches of INSERT statements to add items.

```
/// <summary>
///
/// </summary>
/// <param name="tableName"></param>
/// <param name="title1"></param>
/// <param name="title2"></param>
/// <param name="year1"></param>
/// <param name="year2"></param>
/// <returns></returns>
public static async Task<bool> GetBatch(
    string tableName,
    string title1,
    string title2,
    int year1,
    int year2)
{
    var getBatch = $"SELECT FROM {tableName} WHERE title = ? AND year = ?";
    var statements = new List<BatchStatementRequest>
    {
        new BatchStatementRequest
        {
            Statement = getBatch,
            Parameters = new List<AttributeValue>
            {
```

```

        new AttributeValue { S = title1 },
        new AttributeValue { N = year1.ToString() },
    },
},
new BatchStatementRequest
{
    Statement = getBatch,
    Parameters = new List<AttributeValue>
    {
        new AttributeValue { S = title2 },
        new AttributeValue { N = year2.ToString() },
    },
}
};

var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});

if (response.Responses.Count > 0)
{
    response.Responses.ForEach(r =>
    {
        Console.WriteLine($"{r.Item["title"]}\t{r.Item["year"]}");
    });
    return true;
}
else
{
    Console.WriteLine($"Couldn't find either {title1} or {title2}.");
    return false;
}
}
}

```

Use batches of SELECT statements to get items.

```

/// <summary>
/// Inserts movies imported from a JSON file into the movie table by
/// using an Amazon DynamoDB PartiQL INSERT statement.
/// </summary>
/// <param name="tableName">The name of the table into which the movie
/// information will be inserted.</param>
/// <param name="movieFileName">The name of the JSON file that contains
/// movie information.</param>
/// <returns>A Boolean value that indicates the success or failure of
/// the insert operation.</returns>
public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
{
    // Get the list of movies from the JSON file.
    var movies = ImportMovies(movieFileName);

    var success = false;

    if (movies is not null)
    {
        // Insert the movies in a batch using PartiQL. Because the
        // batch can contain a maximum of 25 items, insert 25 movies

```

```

        // at a time.
        string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?, 
'year': ?}}";
        var statements = new List<BatchStatementRequest>();

        try
        {
            for (var indexOffset = 0; indexOffset < 250; indexOffset += 25)
            {
                for (var i = indexOffset; i < indexOffset + 25; i++)
                {
                    statements.Add(new BatchStatementRequest
                    {
                        Statement = insertBatch,
                        Parameters = new List<AttributeValue>
                        {
                            new AttributeValue { S = movies[i].Title },
                            new AttributeValue { N =
movies[i].Year.ToString() },
                        },
                    });
                }

                var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});
            }

            // Wait between batches for movies to be successfully
added.
            System.Threading.Thread.Sleep(3000);

            success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

            // Clear the list of statements for the next batch.
            statements.Clear();
        }
        catch (AmazonDynamoDBException ex)
        {
            Console.WriteLine(ex.Message);
        }
    }

    return success;
}

/// <summary>
/// Loads the contents of a JSON file into a list of movies to be
/// added to the DynamoDB table.
/// </summary>
/// <param name="movieFileName">The full path to the JSON file.</param>
/// <returns>A generic list of movie objects.</returns>
public static List<Movie> ImportMovies(string movieFileName)
{
    if (!File.Exists(movieFileName))
    {
        return null;
    }

    using var sr = new StreamReader(movieFileName);
    string json = sr.ReadToEnd();
    var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);
}

```

```

        if (allMovies is not null)
        {
            // Return the first 250 entries.
            return allMovies.GetRange(0, 250);
        }
        else
        {
            return null;
        }
    }
}

```

Use batches of UPDATE statements to update items.

```

/// <summary>
/// Updates information for multiple movies.
/// </summary>
/// <param name="tableName">The name of the table containing the
/// movies to be updated.</param>
/// <param name="producer1">The producer name for the first movie
/// to update.</param>
/// <param name="title1">The title of the first movie.</param>
/// <param name="year1">The year that the first movie was released.</param>
/// <param name="producer2">The producer name for the second
/// movie to update.</param>
/// <param name="title2">The title of the second movie.</param>
/// <param name="year2">The year that the second movie was released.</
param>
/// <returns>A Boolean value that indicates the success of the update.</
returns>
public static async Task<bool> UpdateBatch(
    string tableName,
    string producer1,
    string title1,
    int year1,
    string producer2,
    string title2,
    int year2)
{
    string updateBatch = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";
    var statements = new List<BatchStatementRequest>
    {
        new BatchStatementRequest
        {
            Statement = updateBatch,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = producer1 },
                new AttributeValue { S = title1 },
                new AttributeValue { N = year1.ToString() },
            },
        },
        new BatchStatementRequest
        {
            Statement = updateBatch,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = producer2 },
                new AttributeValue { S = title2 },
                new AttributeValue { N = year2.ToString() },
            },
        }
    };
}

```

```

        },
    }
};

var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});

return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}

```

Use batches of DELETE statements to delete items.

```

/// <summary>
/// Deletes multiple movies using a PartiQL BatchExecuteAsync
/// statement.
/// </summary>
/// <param name="tableName">The name of the table containing the
/// moves that will be deleted.</param>
/// <param name="title1">The title of the first movie.</param>
/// <param name="year1">The year the first movie was released.</param>
/// <param name="title2">The title of the second movie.</param>
/// <param name="year2">The year the second movie was released.</param>
/// <returns>A Boolean value indicating the success of the operation.</
returns>
public static async Task<bool> DeleteBatch(
    string tableName,
    string title1,
    int year1,
    string title2,
    int year2)
{

    string updateBatch = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";
    var statements = new List<BatchStatementRequest>
    {
        new BatchStatementRequest
        {
            Statement = updateBatch,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = title1 },
                new AttributeValue { N = year1.ToString() },
            },
        },
        new BatchStatementRequest
        {
            Statement = updateBatch,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = title2 },
                new AttributeValue { N = year2.ToString() },
            },
        },
    };
}

var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});

```

```
{  
    Statements = statements,  
});  
  
return response.HttpStatusCode == System.Net.HttpStatusCode.OK;  
}
```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for .NET API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Use batches of INSERT statements to add items.

```
// AddMovieBatch runs a batch of PartiQL INSERT statements to add multiple movies  
// to the  
// DynamoDB table.  
func (runner PartiQLRunner) AddMovieBatch(movies []Movie) error {  
    statementRequests := make([]types.BatchStatementRequest, len(movies))  
    for index, movie := range movies {  
        params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,  
        movie.Info})  
        if err != nil {  
            panic(err)  
        }  
        statementRequests[index] = types.BatchStatementRequest{  
            Statement: aws.String(fmt.Sprintf(  
                "INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",  
                runner.TableName)),  
            Parameters: params,  
        }  
    }  
  
    _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),  
    &dynamodb.BatchExecuteStatementInput{  
        Statements: statementRequests,  
    })  
    if err != nil {  
        log.Printf("Couldn't insert a batch of items with PartiQL. Here's why: %v\n",  
        err)  
    }  
    return err  
}
```

Use batches of SELECT statements to get items.

```
// GetMovieBatch runs a batch of PartiQL SELECT statements to get multiple movies  
// from  
// the DynamoDB table by title and year.  
func (runner PartiQLRunner) GetMovieBatch(movies []Movie) ([]Movie, error) {  
    statementRequests := make([]types.BatchStatementRequest, len(movies))  
    for index, movie := range movies {  
        params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})  
    }
```

```

if err != nil {
    panic(err)
}
statementRequests[index] = types.BatchStatementRequest{
    Statement: aws.String(
        fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
runner.TableName)),
    Parameters: params,
}
}

output, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
&dynamodb.BatchExecuteStatementInput{
    Statements: statementRequests,
})
var outMovies []Movie
if err != nil {
    log.Printf("Couldn't get a batch of items with PartiQL. Here's why: %v\n", err)
} else {
    for _, response := range output.Responses {
        var movie Movie
        err = attributevalue.UnmarshalMap(response.Item, &movie)
        if err != nil {
            log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
        } else {
            outMovies = append(outMovies, movie)
        }
    }
}
return outMovies, err
}

```

Use batches of UPDATE statements to update items.

```

// UpdateMovieBatch runs a batch of PartiQL UPDATE statements to update the rating
// of
// multiple movies that already exist in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovieBatch(movies []Movie, ratings []float64)
error {
statementRequests := make([]types.BatchStatementRequest, len(movies))
for index, movie := range movies {
    params, err := attributevalue.MarshalList([]interface{}{ratings[index],
movie.Title, movie.Year})
    if err != nil {
        panic(err)
    }
    statementRequests[index] = types.BatchStatementRequest{
        Statement: aws.String(
            fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
runner.TableName)),
        Parameters: params,
    }
}

_, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
&dynamodb.BatchExecuteStatementInput{
    Statements: statementRequests,
})
if err != nil {
    log.Printf("Couldn't update the batch of movies. Here's why: %v\n", err)
}
return err
}

```

```
}
```

Use batches of DELETE statements to delete items.

```
// DeleteMovieBatch runs a batch of PartiQL DELETE statements to remove multiple
// movies
// from the DynamoDB table.
func (runner PartiQLRunner) DeleteMovieBatch(movies []Movie) error {
    statementRequests := make([]types.BatchStatementRequest, len(movies))
    for index, movie := range movies {
        params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
        if err != nil {
            panic(err)
        }
        statementRequests[index] = types.BatchStatementRequest{
            Statement: aws.String(
                fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?", runner.TableName)),
            Parameters: params,
        }
    }

    _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
        &dynamodb.BatchExecuteStatementInput{
            Statements: statementRequests,
        })
    if err != nil {
        log.Printf("Couldn't delete the batch of movies. Here's why: %v\n", err)
    }
    return err
}
```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for Go API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "eu-west-1"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
```

```

const REGION = "eu-west-1"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };

```

Create a batch of items using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
    tableName,
    movieYear1,
    movieTitle1,
    movieYear2,
    movieTitle2
) => {
    const params = {
        Statements: [
            {
                Statement:
                    "INSERT INTO " + tableName + " value {'title':?:, 'year':?}",
                Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
            },
            {
                Statement:
                    "INSERT INTO " + tableName + " value {'title':?:, 'year':?}",
                Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
            },
        ],
    };
    try {
        const data = await ddbDocClient.send(
            new BatchExecuteStatementCommand(params)
        );
        console.log("Success. Items added.");
        return "Run successfully"; // For unit tests.
    }
}

```

```

        } catch (err) {
            console.error(err);
        }
    };
run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);

```

Get a batch of items using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
    tableName,
    movieYear1,
    movieTitle1,
    movieYear2,
    movieTitle2
) => {
    const params = {
        Statements: [
            {
                Statement: "SELECT * FROM " + tableName + " where title=? and year=?",
                Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
            },
            {
                Statement: "SELECT * FROM " + tableName + " where title=? and year=?",
                Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
            },
        ],
    };
    try {
        const data = await ddbDocClient.send(
            new BatchExecuteStatementCommand(params)
        );
        for (let i = 0; i < data.Responses.length; i++) {
            console.log(data.Responses[i].Item.year);
            console.log(data.Responses[i].Item.title);
        }
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};
run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);

```

Update a batch of items using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];

```

```

const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[6];
const movieTitle2 = process.argv[7];
const producer1 = process.argv[5];
const producer2 = process.argv[8];

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2,
  producer1,
  producer2
) => {
  const params = {
    Statements: [
      {
        Statement:
          "UPDATE " + tableName + " SET producer=? where title=? and year=?",
        Parameters: [{ S: producer1 }, { S: movieTitle1 }, { N: movieYear1 }],
      },
      {
        Statement:
          "UPDATE " + tableName + " SET producer=? where title=? and year=?",
        Parameters: [{ S: producer2 }, { S: movieTitle2 }, { N: movieYear2 }],
      },
    ],
  };
  try {
    const data = await ddbDocClient.send(
      new BatchExecuteStatementCommand(params)
    );
    console.log("Success. Items updated.");
    return "Run successfully"; // For unit tests.
  } catch (err) {
    console.error(err);
  }
};
run(
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2,
  producer1,
  producer2
);

```

Delete a batch of items using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[5];
const movieTitle2 = process.argv[6];

export const run = async (
  tableName,
  movieYear1,

```

```

        movieTitle1,
        movieYear2,
        movieTitle2
    ) => {
    try {
        const params = {
            Statements: [
                {
                    Statement: "DELETE FROM " + tableName + " where year=? and title=?",
                    Parameters: [{ N: movieYear1 }, { S: movieTitle1 }],
                },
                {
                    Statement: "DELETE FROM " + tableName + " where year=? and title=?",
                    Parameters: [{ N: movieYear2 }, { S: movieTitle2 }],
                },
            ],
        };
        const data = await ddbDocClient.send(
            new BatchExecuteStatementCommand(params)
        );
        console.log("Success. Items deleted.", data);
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};
run(tableName, movieYear1, movieTitle1, movieYear2, movieTitle2);

```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for JavaScript API Reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

public function getItemByPartiQLBatch(string $tableName, array $keys): Result
{
    $statements = [];
    foreach ($keys as $key) {
        list($statement, $parameters) = $this->buildStatementAndParameters("SELECT", $tableName, $key['Item']);
        $statements[] = [
            'Statement' => "$statement",
            'Parameters' => $parameters,
        ];
    }

    return $this->dynamoDbClient->batchExecuteStatement([
        'Statements' => $statements,
    ]);
}

public function insertItemByPartiQLBatch(string $statement, array $parameters)
{
    $this->dynamoDbClient->batchExecuteStatement([
        'Statements' => [
            [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ],
        ],
    ]);
}

```

```

        ],
    ]);

public function updateItemByPartiQLBatch(string $statement, array $parameters)
{
    $this->dynamoDbClient->batchExecuteStatement([
        'Statements' => [
            [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ],
        ],
    ]);
}

public function deleteItemByPartiQLBatch(string $statement, array $parameters)
{
    $this->dynamoDbClient->batchExecuteStatement([
        'Statements' => [
            [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ],
        ],
    ]);
}

```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

class PartiQLBatchWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource

    def run_partiql(self, statements, param_list):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because the
        resource transforms input and output from plain old Python objects (POPOs)
        to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statements: The batch of PartiQL statements.
        :param param_list: The batch of PartiQL parameters that are associated with
                           each statement. This list must be in the same order as
                           the
                           statements.
        :return: The responses returned from running the statements, if any.

```

```
"""
try:
    output = self.dyn_resource.meta.client.batch_execute_statement(
        Statements=[{
            'Statement': statement, 'Parameters': params
        } for statement, params in zip(statements, param_list)])
except ClientError as err:
    if err.response['Error']['Code'] == 'ResourceNotFoundException':
        logger.error(
            "Couldn't execute batch of PartiQL statements because the table"
            "does not exist.")
    else:
        logger.error(
            "Couldn't execute batch of PartiQL statements. Here's why: %s",
            err.response['Error']['Code'], err.response['Error']
            ['Message'])
        raise
else:
    return output
```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for Python (Boto3) API Reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Scan a DynamoDB table using an AWS SDK

The following code examples show how to scan a DynamoDB table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public static async Task<int> ScanTableAsync(
    AmazonDynamoDBClient client,
    string tableName,
    int startYear,
    int endYear)
{
    var request = new ScanRequest
    {
        TableName = tableName,
        ExpressionAttributeNames = new Dictionary<string, string>
        {
            { "#yr", "year" },
        },
        ExpressionAttributeValues = new Dictionary<string, AttributeValue>
        {
            { ":y_a", new AttributeValue { N = startYear.ToString() } },
            { ":y_z", new AttributeValue { N = endYear.ToString() } },
        },
        FilterExpression = "#yr between :y_a and :y_z",
        ProjectionExpression = "#yr, title, info.actors[0], info.directors,
        info.running_time_secs",
    };
}
```

```
// Keep track of how many movies were found.  
int foundCount = 0;  
  
var response = new ScanResponse();  
do  
{  
    response = await client.ScanAsync(request);  
    foundCount += response.Items.Count;  
    response.Items.ForEach(i => DisplayItem(i));  
}  
while (response.LastEvaluatedKey.Count > 1);  
return foundCount;  
}
```

- For API details, see [Scan](#) in *AWS SDK for .NET API Reference*.

## C++

### SDK for C++

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;  
  
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);  
Aws::DynamoDB::Model::ScanRequest req;  
req.SetTableName(table);  
  
if (!projection.empty())  
    req.SetProjectionExpression(projection);  
  
// Perform scan on table  
const Aws::DynamoDB::Model::ScanOutcome& result = dynamoClient.Scan(req);  
if (result.IsSuccess())  
{  
    // Reference the retrieved items  
    const Aws::Vector<Aws::Map<Aws::String,  
Aws::DynamoDB::Model::AttributeValue>>& items = result.GetResult().GetItems();  
    if(items.size() > 0)  
    {  
        std::cout << "Number of items retrieved from scan: " <<  
items.size() << std::endl;  
        //Iterate each item and print  
        for(const auto &item: items)  
        {  
            std::cout <<  
"*****" << std::endl;  
            //Output each retrieved field and its value  
            for (const auto& i : item)  
                std::cout << i.first << ":" << i.second.GetS() << std::endl;  
        }  
    }  
  
    else  
    {  
        std::cout << "No item found in table: " << table << std::endl;  
    }  
}
```

```
{  
    std::cout << "Failed to Scan items: " <<  
result.GetError().GetMessage();  
}
```

- For API details, see [Scan](#) in *AWS SDK for C++ API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the  
examples.  
// It contains a DynamoDB service client that is used to act on the specified  
table.  
type TableBasics struct {  
    DynamoDbClient *dynamodb.Client  
    TableName      string  
}  
  
  
// Scan gets all movies in the DynamoDB table that were released in a range of  
years  
// and projects them to return a reduced set of fields.  
// The function uses the `expression` package to build the filter and projection  
// expressions.  
func (basics TableBasics) Scan(startYear int, endYear int) ([]Movie, error) {  
    var movies []Movie  
    var err error  
    var response *dynamodb.ScanOutput  
    filtEx := expression.Name("year").Between(expression.Value(startYear),  
        expression.Value(endYear))  
    projEx := expression.NamesList(  
        expression.Name("year"), expression.Name("title"),  
        expression.Name("info.rating"))  
    expr, err :=  
        expression.NewBuilder().WithFilter(filtEx).WithProjection(projEx).Build()  
    if err != nil {  
        log.Printf("Couldn't build expressions for scan. Here's why: %v\n", err)  
    } else {  
        response, err = basics.DynamoDbClient.Scan(context.TODO(), &dynamodb.ScanInput{  
            TableName:                 aws.String(basics.TableName),  
            ExpressionAttributeNames: expr.Names(),  
            ExpressionAttributeValues: expr.Values(),  
            FilterExpression:          expr.Filter(),  
            ProjectionExpression:     expr.Projection(),  
        })  
        if err != nil {  
            log.Printf("Couldn't scan for movies released between %v and %v. Here's why: %v  
\n",  
                startYear, endYear, err)  
        } else {  
            err = attributevalue.UnmarshalListOfMaps(response.Items, &movies)  
            if err != nil {  
                log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)  
            }  
        }  
    }  
}
```

```
    }
    return movies, err
}
```

- For API details, see [Scan in AWS SDK for Go API Reference](#).

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Scans an Amazon DynamoDB table by using the enhanced client.

```
public static void scan( DynamoDbEnhancedClient enhancedClient ) {
    try{
        DynamoDbTable<Customer> custTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));
        Iterator<Customer> results = custTable.scan().items().iterator();
        while (results.hasNext()) {
            Customer rec = results.next();
            System.out.println("The record id is "+rec.getId());
            System.out.println("The name is " +rec.getCustName());
        }

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    System.out.println("Done");
}
```

- For API details, see [Scan in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
```

```
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Scan a table using the DynamoDB document client.

```
// Import required AWS SDK clients and commands for Node.js.
import { ddbDocClient } from "../libs/ddbDocClient.js";
import { ScanCommand } from "@aws-sdk/lib-dynamodb";
// Set the parameters.
export const params = {
    TableName: "TABLE_NAME",
    ProjectionExpression: "#r, #y, title",
    ExpressionAttributeNames: { "#r": "rank", "#y": "year" },
    FilterExpression: "title = :t and #y = :y and info.#r = :r",
    ExpressionAttributeValues: {
        ":r": "MOVIE_RANK",
        ":y": "MOVIE_YEAR",
        ":t": "MOVIE_NAME",
    },
};

export const scanTable = async () => {
    try {
        const data = await ddbDocClient.send(new ScanCommand(params));
        console.log("success", data.Items);
    } catch (err) {
        console.log("Error", err);
    }
};
scanTable();
```

- For API details, see [Scan in AWS SDK for JavaScript API Reference](#).

#### SDK for JavaScript V2

##### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Load the AWS SDK for Node.js.
```

```
var AWS = require("aws-sdk");
// Set the AWS Region.
AWS.config.update({ region: "REGION" });

// Create DynamoDB service object.
var ddb = new AWS.DynamoDB({ apiVersion: "2012-08-10" });

const params = {
    // Specify which items in the results are returned.
    FilterExpression: "Subtitle = :topic AND Season = :s AND Episode = :e",
    // Define the expression attribute value, which are substitutes for the values
    // you want to compare.
    ExpressionAttributeValues: {
        ":topic": {S: "SubTitle2"}, 
        ":s": {N: 1}, 
        ":e": {N: 2},
    },
    // Set the projection expression, which are the attributes that you want.
    ProjectionExpression: "Season, Episode, Title, Subtitle",
    TableName: "EPISODES_TABLE",
};

ddb.scan(params, function (err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Success", data);
        data.Items.forEach(function (element, index, array) {
            console.log(
                "printing",
                element.Title.S + " (" + element.Subtitle.S + ")"
            );
        });
    }
});
```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [Scan in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun scanItems(tableNameVal: String) {

    val request = ScanRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.scan(request)
        response.items?.forEach { item ->
            item.keys.forEach { key ->
                println("The key name is $key\n")
            }
        }
    }
}
```

```
        println("The value is ${item[key]}")
    }
}
}
```

- For API details, see [Scan](#) in *AWS SDK for Kotlin API reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
$yearsKey = [
    'Key' => [
        'year' => [
            'N' => [
                'minRange' => 1990,
                'maxRange' => 1999,
            ],
        ],
    ],
];
$filter = "year between 1990 and 1999";
echo "\nHere's a list of all the movies released in the 90s:\n";
$result = $service->scan($tableName, $yearsKey, $filter);
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    echo $movie['title'] . "\n";
}

public function scan(string $tableName, array $key, string $filters)
{
    $query = [
        'ExpressionAttributeNames' => [ '#year' => 'year'],
        'ExpressionAttributeValues' => [
            ':min' => [ 'N' => '1990'],
            ':max' => [ 'N' => '1999'],
        ],
        'FilterExpression' => "#year between :min and :max",
        'TableName' => $tableName,
    ];
    return $this->dynamoDbClient->scan($query);
}
```

- For API details, see [Scan](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
```

```

"""
:param dyn_resource: A Boto3 DynamoDB resource.
"""

self.dyn_resource = dyn_resource
self.table = None

def scan_movies(self, year_range):
    """
    Scans for movies that were released in a range of years.
    Uses a projection expression to return a subset of data for each movie.

    :param year_range: The range of years to retrieve.
    :return: The list of movies released in the specified years.
    """

    movies = []
    scan_kwarg = {
        'FilterExpression': Key('year').between(year_range['first'],
                                              year_range['second']),
        'ProjectionExpression': "#yr, title, info.rating",
        'ExpressionAttributeNames': {"#yr": "year"}}
    try:
        done = False
        start_key = None
        while not done:
            if start_key:
                scan_kwarg['ExclusiveStartKey'] = start_key
            response = self.table.scan(**scan_kwarg)
            movies.extend(response.get('Items', []))
            start_key = response.get('LastEvaluatedKey', None)
            done = start_key is None
    except ClientError as err:
        logger.error(
            "Couldn't scan for movies. Here's why: %s: %s",
            err.response['Error']['Code'], err.response['Error']['Message'])
        raise

    return movies

```

- For API details, see [Scan in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

# Scans for movies that were released in a range of years.
# Uses a projection expression to return a subset of data for each movie.
#
# @param year_range [Hash] The range of years to retrieve.
# @return [Array] The list of movies released in the specified years.
def scan_movies(year_range)
    movies = []
    scan_hash = {
        filter_expression: "#yr between :start_yr and :end_yr",
        projection_expression: "#yr, title, info.rating",
        expression_attribute_names: {"#yr" => "year"},
        expression_attribute_values: {
            ":start_yr" => year_range[:start], ":end_yr" => year_range[:end]}
    }
    done = false

```

```
start_key = nil
until done
  scan_hash[:exclusive_start_key] = start_key unless start_key.nil?
  response = @table.scan(scan_hash)
  movies.concat(response.items) unless response.items.nil?
  start_key = response.last_evaluated_key
  done = start_key.nil?
end
rescue Aws::Errors::ServiceError => e
  puts("Couldn't scan for movies. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
else
  movies
end
```

- For API details, see [Scan](#) in *AWS SDK for Ruby API Reference*.

## Rust

### SDK for Rust

#### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
async fn list_items(client: &Client, table: &str) -> Result<(), Error> {
    let items: Result<Vec<_>, _> = client
        .scan()
        .table_name(table)
        .into_paginator()
        .items()
        .send()
        .collect()
        .await;

    println!("Items in table:");
    for item in items? {
        println!("  {:?}", item);
    }

    Ok(())
}
```

- For API details, see [Scan](#) in *AWS SDK for Rust API reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Update an item in a DynamoDB table using an AWS SDK

The following code examples show how to update an item in a DynamoDB table.

.NET

AWS SDK for .NET

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// Updates an existing item in the movies table.
/// </summary>
/// <param name="client">An initialized Amazon DynamoDB client object.</param>
/// <param name="newMovie">A Movie object containing information for
/// the movie to update.</param>
/// <param name="newInfo">A MovieInfo object that contains the
/// information that will be changed.</param>
/// <param name="tableName">The name of the table that contains the
/// movie.</param>
/// <returns>A Boolean value that indicates the success of the operation.</returns>
public static async Task<bool> UpdateItemAsync(
    AmazonDynamoDBClient client,
    Movie newMovie,
    MovieInfo newInfo,
    string tableName)
{
    var key = new Dictionary<string, AttributeValue>
    {
        ["title"] = new AttributeValue { S = newMovie.Title },
        ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
    };
    var updates = new Dictionary<string, AttributeValueUpdate>
    {
        ["info.plot"] = new AttributeValueUpdate
        {
            Action = AttributeAction.PUT,
            Value = new AttributeValue { S = newInfo.Plot },
        },
        ["info.rating"] = new AttributeValueUpdate
        {
            Action = AttributeAction.PUT,
            Value = new AttributeValue { N = newInfo.Rank.ToString() },
        },
    };

    var request = new UpdateItemRequest
    {
        AttributeUpdates = updates,
        Key = key,
        TableName = tableName,
    };

    var response = await client.UpdateItemAsync(request);

    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [UpdateItem in AWS SDK for .NET API Reference](#).

C++

**SDK for C++**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
Aws::Client::ClientConfiguration clientConfig;
Aws::DynamoDB::DynamoDBClient dynamoClient(clientConfig);

// *** Define UpdateItem request arguments
// Define TableName argument.
Aws::DynamoDB::Model::UpdateItemRequest request;
request.SetTableName(tableName);

// Define KeyName argument.
Aws::DynamoDB::Model::AttributeValue attribValue;
attribValue.SetS(keyValue);
request.AddKey("id", attribValue);

// Construct the SET update expression argument.
Aws::String update_expression("SET #a = :valueA");
request.SetUpdateExpression(update_expression);

// Parse the attribute name and value. Syntax: "name=value".
auto parsed = Aws::Utils::StringUtils::Split(attributeNameAndValue, '=');

if (parsed.size() != 2)
{
    std::cout << "Invalid argument syntax: " << attributeNameAndValue <<
USAGE;
    return 1;
}

// Construct attribute name argument
// Note: Setting the ExpressionAttributeNames argument is required only
// when the name is a reserved word, such as "default". Otherwise, the
// name can be included in the update_expression, as in
// "SET MyAttributeName = :valueA"
Aws::Map< Aws::String, Aws::String> expressionAttributeNames;
expressionAttributeNames["#a"] = parsed[0];
request.SetExpressionAttributeNames(expressionAttributeNames);

// Construct attribute value argument.
Aws::DynamoDB::Model::AttributeValue attributeUpdatedValue;
attributeUpdatedValue.SetS(parsed[1]);
Aws::Map< Aws::String, Aws::DynamoDB::Model::AttributeValue>
expressionAttributeValues;
expressionAttributeValues[":valueA"] = attributeUpdatedValue;
request.SetExpressionAttributeValues(expressionAttributeValues);

// Update the item.
const Aws::DynamoDB::Model::UpdateItemOutcome& result =
dynamoClient.UpdateItem(request);
if (!result.IsSuccess())
{
    std::cout << result.GetError().GetMessage() << std::endl;
    return 1;
}
std::cout << "Item was updated" << std::endl;
```

- For API details, see [UpdateItem in AWS SDK for C++ API Reference](#).

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// UpdateMovie updates the rating and plot of a movie that already exists in the
// DynamoDB table. This function uses the `expression` package to build the update
// expression.
func (basics TableBasics) UpdateMovie(movie Movie)
    (map[string]map[string]interface{}, error) {
    var err error
    var response *dynamodb.UpdateItemOutput
    var attributeMap map[string]map[string]interface{}
    update := expression.Set(expression.Name("info.rating"),
        expression.Value(movie.Info["rating"]))
    update.Set(expression.Name("info.plot"), expression.Value(movie.Info["plot"]))
    expr, err := expression.NewBuilder().WithUpdate(update).Build()
    if err != nil {
        log.Printf("Couldn't build expression for update. Here's why: %v\n", err)
    } else {
        response, err = basics.DynamoDbClient.UpdateItem(context.TODO(),
            &dynamodb.UpdateItemInput{
                TableName:           aws.String(basics.TableName),
                Key:                movie.GetKey(),
                ExpressionAttributeNames: expr.Names(),
                ExpressionAttributeValues: expr.Values(),
                UpdateExpression:      expr.Update(),
                ReturnValue:          types.ReturnValueUpdatedNew,
            })
        if err != nil {
            log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
        } else {
            err = attributevalue.UnmarshalMap(response.Attributes, &attributeMap)
            if err != nil {
                log.Printf("Couldn't unmarshal update response. Here's why: %v\n", err)
            }
        }
    }
    return attributeMap, err
}
```

- For API details, see [UpdateItem in AWS SDK for Go API Reference](#).

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Updates an item located in a table by using the enhanced client.

```
public static String modifyItem(DynamoDbEnhancedClient enhancedClient, String keyVal, String email) {

    try {

        DynamoDbTable<Customer> mappedTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));
        Key key = Key.builder()
            .partitionValue(keyVal)
            .build();

        // Get the item by using the key and update the email value.
        Customer customerRec = mappedTable.getItem(r->r.key(key));
        customerRec.setEmail(email);
        mappedTable.updateItem(customerRec);
        return customerRec.getEmail();

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    return "";
}
```

- For API details, see [UpdateItem in AWS SDK for Java 2.x API Reference](#).

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
```

```

const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };

```

Update an item in a table using the DynamoDB document client.

```

import { UpdateCommand } from "@aws-sdk/lib-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

export const updateItem = async () => {
    // Set the parameters.
    const params = {
        TableName: "TABLE_NAME",
        Key: {
            title: "MOVIE_NAME",
            year: "MOVIE_YEAR",
        },
        ProjectionExpression: "#r",
        ExpressionAttributeNames: { "#r": "rank" },
        UpdateExpression: "set info.plot = :p, info.#r = :r",
        ExpressionAttributeValues: {
            ":p": "MOVIE_PLOT",
            ":r": "MOVIE_RANK",
        },
    };
    try {
        const data = await ddbDocClient.send(new UpdateCommand(params));
        console.log("Success - item added or updated", data);
        return data;
    } catch (err) {
        console.log("Error", err);
    }
};
updateItem();

```

Update an item in a table using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { ExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

```

```

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const producer1 = process.argv[5];

export const run = async (tableName, movieYear1, movieTitle1, producer1) => {
    const params = {
        Statement:
            "UPDATE " + tableName + " SET Producer=? where title=? and year=?",
        Parameters: [{ S: producer1 }, { S: movieTitle1 }, { N: movieYear1 }],
    };
    try {
        const data = await ddbDocClient.send(new ExecuteStatementCommand(params));
        console.log("Success. Item updated.");
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};
run(tableName, movieYear1, movieTitle1, producer1);

```

Update items by batch in a table using PartiQL.

```

// Import required AWS SDK clients and commands for Node.js.
import { BatchExecuteStatementCommand } from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";

const tableName = process.argv[2];
const movieYear1 = process.argv[3];
const movieTitle1 = process.argv[4];
const movieYear2 = process.argv[6];
const movieTitle2 = process.argv[7];
const producer1 = process.argv[5];
const producer2 = process.argv[8];

export const run = async (
    tableName,
    movieYear1,
    movieTitle1,
    movieYear2,
    movieTitle2,
    producer1,
    producer2
) => {
    const params = {
        Statements: [
            {
                Statement:
                    "UPDATE " + tableName + " SET producer=? where title=? and year=?",
                Parameters: [{ S: producer1 }, { S: movieTitle1 }, { N: movieYear1 }],
            },
            {
                Statement:
                    "UPDATE " + tableName + " SET producer=? where title=? and year=?",
                Parameters: [{ S: producer2 }, { S: movieTitle2 }, { N: movieYear2 }],
            },
        ],
    };
    try {
        const data = await ddbDocClient.send(
            new BatchExecuteStatementCommand(params)
        );
    }
};

```

```
        console.log("Success. Items updated.");
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.error(err);
    }
};

run(
    tableName,
    movieYear1,
    movieTitle1,
    movieYear2,
    movieTitle2,
    producer1,
    producer2
);
```

- For API details, see [UpdateItem in AWS SDK for JavaScript API Reference](#).

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
suspend fun updateTableItem(
    tableNameVal: String,
    keyName: String,
    keyVal: String,
    name: String,
    updateVal: String
) {

    val itemKey = mutableMapOf<String, AttributeValue>()
    itemKey[keyName] = AttributeValue.S(keyVal)

    val updatedValues = mutableMapOf<String, AttributeValueUpdate>()
    updatedValues[name] = AttributeValueUpdate {
        value = AttributeValue.S(updateVal)
        action = AttributeAction.Put
    }

    val request = UpdateItemRequest {
        tableName = tableNameVal
        key = itemKey
        attributeUpdates = updatedValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.updateItem(request)
        println("Item in $tableNameVal was updated")
    }
}
```

- For API details, see [UpdateItem in AWS SDK for Kotlin API reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
echo "What rating would you like to give {$movie['Item']['title']['S']}?\n";
$rating = 0;
while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 || $rating > 10) {
    $rating = testable_readline("Rating (1-10): ");
}
$service->updateItemAttributeByKey($tableName, $key, 'rating', 'N', $rating);

public function updateItemAttributeByKey(
    string $tableName,
    array $key,
    string $attributeName,
    string $attributeType,
    string $newValue
) {
    $this->dynamoDbClient->updateItem([
        'Key' => $key['Item'],
        'TableName' => $tableName,
        'UpdateExpression' => "set #NV=:NV",
        'ExpressionAttributeNames' => [
            '#NV' => $attributeName,
        ],
        'ExpressionAttributeValues' => [
            ':NV' => [
                $attributeType => $newValue
            ]
        ],
    ]);
}
```

- For API details, see [UpdateItem in AWS SDK for PHP API Reference](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Update an item by using an update expression.

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def update_movie(self, title, year, rating, plot):
        """
        Updates rating and plot data for a movie in the table.

```

```

:param title: The title of the movie to update.
:param year: The release year of the movie to update.
:param rating: The updated rating to give the movie.
:param plot: The updated plot summary to give the movie.
:return: The fields that were updated, with their new values.
"""
try:
    response = self.table.update_item(
        Key={'year': year, 'title': title},
        UpdateExpression="set info.rating=:r, info.plot=:p",
        ExpressionAttributeValues={
            ':r': Decimal(str(rating)), ':p': plot},
        ReturnValues="UPDATED_NEW")
except ClientError as err:
    logger.error(
        "Couldn't update movie %s in table %s. Here's why: %s: %s",
        title, self.table.name,
        err.response['Error']['Code'], err.response['Error']['Message'])
    raise
else:
    return response['Attributes']

```

Update an item by using an update expression that includes an arithmetic operation.

```

class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table

    def update_rating(self, title, year, rating_change):
        """
        Updates the quality rating of a movie in the table by using an arithmetic
        operation in the update expression. By specifying an arithmetic operation,
        you can adjust a value in a single request, rather than first getting its
        value and then setting its new value.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating_change: The amount to add to the current rating for the
        movie.
        :return: The updated rating.
        """
        try:
            response = self.table.update_item(
                Key={'year': year, 'title': title},
                UpdateExpression="set info.rating = info.rating + :val",
                ExpressionAttributeValues={':val': Decimal(str(rating_change))},
                ReturnValues="UPDATED_NEW")
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title, self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise
        else:
            return response['Attributes']

```

Update an item only when it meets certain conditions.

```

class UpdateQueryWrapper:
    def __init__(self, table):
        self.table = table

```

```

def remove_actors(self, title, year, actor_threshold):
    """
        Removes an actor from a movie, but only when the number of actors is
    greater
        than a specified threshold. If the movie does not list more than the
    threshold,
        no actors are removed.

    :param title: The title of the movie to update.
    :param year: The release year of the movie to update.
    :param actor_threshold: The threshold of actors to check.
    :return: The movie data after the update.
    """
    try:
        response = self.table.update_item(
            Key={'year': year, 'title': title},
            UpdateExpression="remove info.actors[0]",
            ConditionExpression="size(info.actors) > :num",
            ExpressionAttributeValues={':num': actor_threshold},
            ReturnValues="ALL_NEW")
    except ClientError as err:
        if err.response['Error']['Code'] == "ConditionalCheckFailedException":
            logger.warning(
                "Didn't update %s because it has fewer than %s actors.", title, actor_threshold + 1)
        else:
            logger.error(
                "Couldn't update movie %s. Here's why: %s: %s", title, err.response['Error']['Code'], err.response['Error']
                ['Message'])
            raise
    else:
        return response['Attributes']

```

- For API details, see [UpdateItem in AWS SDK for Python \(Boto3\) API Reference](#).

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

# Updates rating and plot data for a movie in the table.
#
# @param title [String] The title of the movie to update.
# @param year [Int] The release year of the movie to update.
# @param rating [Float] The updated rating to give the movie.
# @param plot [String] The updated plot summary to give the movie.
# @return [Hash] The fields that were updated, with their new values.
def update_movie(title:, year:, rating:, plot:)
    response = @table.update_item(
        key: {"year" => year, "title" => title},
        update_expression: "set info.rating=:r, info.plot=:p",
        expression_attribute_values: {":r" => rating, ":p" => plot },
        return_values: "UPDATED_NEW")
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't update movie #{title} in table #{@table.name}. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else

```

```
    response.attributes
end
```

- For API details, see [UpdateItem](#) in *AWS SDK for Ruby API Reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Write a batch of DynamoDB items using an AWS SDK

The following code examples show how to write a batch of DynamoDB items.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Writes a batch of items to the movie table.

```
/// <summary>
/// Loads the contents of a JSON file into a list of movies to be
/// added to the DynamoDB table.
/// </summary>
/// <param name="movieFileName">The full path to the JSON file.</param>
/// <returns>A generic list of movie objects.</returns>
public static List<Movie> ImportMovies(string movieFileName)
{
    if (!File.Exists(movieFileName))
    {
        return null;
    }

    using var sr = new StreamReader(movieFileName);
    string json = sr.ReadToEnd();
    var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

    // Now return the first 250 entries.
    return allMovies.GetRange(0, 250);
}

/// <summary>
/// Writes 250 items to the movie table.
/// </summary>
/// <param name="client">The initialized DynamoDB client object.</param>
/// <param name="movieFileName">A string containing the full path to
/// the JSON file containing movie data.</param>
/// <returns>A long integer value representing the number of movies
/// imported from the JSON file.</returns>
public static async Task<long> BatchWriteItemsAsync(
    AmazonDynamoDBClient client,
    string movieFileName)
{
    var movies = ImportMovies(movieFileName);
    if (movies is null)
    {
        Console.WriteLine("Couldn't find the JSON file with movie data.");
        return 0;
    }

    var batchWriteRequest = new BatchWriteItemRequest()
    {
        RequestItems = movies
    };

    var response = await client.BatchWriteItemAsync(batchWriteRequest);
    return response.Succeeded ? response.Count : 0;
}
```

```
        }

        var context = new DynamoDBContext(client);

        var bookBatch = context.CreateBatchWrite<Movie>();
        bookBatch.AddPutItems(movies);

        Console.WriteLine("Adding imported movies to the table.");
        await bookBatch.ExecuteAsync();

        return movies.Count;
    }
}
```

- For API details, see [BatchWriteItem](#) in *AWS SDK for .NET API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// AddMovieBatch adds a slice of movies to the DynamoDB table. The function sends
// batches of 25 movies to DynamoDB until all movies are added or it reaches the
// specified maximum.
func (basics TableBasics) AddMovieBatch(movies []Movie, maxMovies int) (int, error) {
    var err error
    var item map[string]types.AttributeValue
    written := 0
    batchSize := 25 // DynamoDB allows a maximum batch size of 25 items.
    start := 0
    end := start + batchSize
    for start < maxMovies && start < len(movies) {
        var writeReqs []types.WriteRequest
        if end > len(movies) {
            end = len(movies)
        }
        for _, movie := range movies[start:end] {
            item, err = attributevalue.MarshalMap(movie)
            if err != nil {
                log.Printf("Couldn't marshal movie %v for batch writing. Here's why: %v\n",
                    movie.Title, err)
            } else {
                writeReqs = append(
                    writeReqs,
                    types.WriteRequest{PutRequest: &types.PutRequest{Item: item}},
                )
            }
        }
    }
}
```

```

    }
    _, err = basics.DynamoDbClient.BatchWriteItem(context.TODO(),
&dynamodb.BatchWriteItemInput{
    RequestItems: map[string][]types.WriteRequest{basics.TableName: writeReqs}})
    if err != nil {
        log.Printf("Couldn't add a batch of movies to %v. Here's why: %v\n",
basics.TableName, err)
    } else {
        written += len(writeReqs)
    }
    start = end
    end += batchSize
}

return written, err
}

```

- For API details, see [BatchWriteItem](#) in *AWS SDK for Go API Reference*.

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Inserts many items into a table by using the enhanced client.

```

public static void putBatchRecords(DynamoDbEnhancedClient enhancedClient) {

    try {
        DynamoDbTable<Customer> mappedTable = enhancedClient.table("Customer",
TableSchema.fromBean(Customer.class));
        LocalDate localDate = LocalDate.parse("2020-04-07");
        LocalDateTime localDateTime = localDate.atStartOfDay();
        Instant instant = localDateTime.toInstant(ZoneOffset.UTC);

        Customer record2 = new Customer();
        record2.setCustName("Fred Pink");
        record2.setId("id110");
        record2.setEmail("fredp@noserver.com");
        record2.setRegistrationDate(instant) ;

        Customer record3 = new Customer();
        record3.setCustName("Susan Pink");
        record3.setId("id120");
        record3.setEmail("spink@noserver.com");
        record3.setRegistrationDate(instant) ;

        BatchWriteItemEnhancedRequest batchWriteItemEnhancedRequest =
BatchWriteItemEnhancedRequest.builder()
            .writeBatches(WriteBatch.builder(Customer.class)
                .mappedTableResource(mappedTable)
                .addPutItem(r -> r.item(record2))
                .addPutItem(r -> r.item(record3))
                .build())
            .build();

        // Add these two items to the table.
        enhancedClient.batchWriteItem(batchWriteItemEnhancedRequest);
        System.out.println("done");
    }
}

```

```
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
```

- For API details, see [BatchWriteItem](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Add the items to the table.

```
import fs from "fs";
```

```

import * as R from "ramda";
import { ddbDocClient } from "../libs/ddbDocClient.js";
import { BatchWriteCommand } from "@aws-sdk/lib-dynamodb";

export const writeData = async () => {
    // Before you run this example, download 'movies.json' from https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GettingStarted.Js.02.html,
    // and put it in the same folder as the example.
    // Get the movie data parse to convert into a JSON object.
    const allMovies = JSON.parse(fs.readFileSync("moviedata.json", "utf8"));
    // Split the table into segments of 25.
    const dataSegments = R.splitEvery(25, allMovies);
    const TABLE_NAME = "TABLE_NAME"
    try {
        // Loop batch write operation 10 times to upload 250 items.
        for (let i = 0; i < 10; i++) {
            const segment = dataSegments[i];
            for (let j = 0; j < 25; j++) {
                const params = {
                    RequestItems: [
                        [TABLE_NAME]: [
                            {
                                // Destination Amazon DynamoDB table name.
                                PutRequest: {
                                    Item: {
                                        year: segment[j].year,
                                        title: segment[j].title,
                                        info: segment[j].info,
                                    },
                                },
                            ],
                        ],
                    ];
                };
                const data = ddbDocClient.send(new BatchWriteCommand(params));
            }
            console.log("Success, table updated.");
        }
    } catch (error) {
        console.log("Error", error);
    }
};
writeData();

```

- For API details, see [BatchWriteItem](#) in *AWS SDK for JavaScript API Reference*.

## SDK for JavaScript V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

```

// Load the AWS SDK for Node.js
var AWS = require('aws-sdk');
// Set the region
AWS.config.update({region: 'REGION'});

// Create DynamoDB service object
var ddb = new AWS.DynamoDB({apiVersion: '2012-08-10'});

var params = {
    RequestItems: [
        "TABLE_NAME": [
            {
                PutRequest: {

```

```

        Item: {
            "KEY": { "N": "KEY_VALUE" },
            "ATTRIBUTE_1": { "S": "ATTRIBUTE_1_VALUE" },
            "ATTRIBUTE_2": { "N": "ATTRIBUTE_2_VALUE" }
        }
    },
    {
        PutRequest: {
            Item: {
                "KEY": { "N": "KEY_VALUE" },
                "ATTRIBUTE_1": { "S": "ATTRIBUTE_1_VALUE" },
                "ATTRIBUTE_2": { "N": "ATTRIBUTE_2_VALUE" }
            }
        }
    }
]
}
);

ddb.batchWriteItem(params, function(err, data) {
    if (err) {
        console.log("Error", err);
    } else {
        console.log("Success", data);
    }
});

```

- For more information, see [AWS SDK for JavaScript Developer Guide](#).
- For API details, see [BatchWriteItem](#) in [AWS SDK for JavaScript API Reference](#).

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

public function writeBatch(string $TableName, array $Batch, int $depth = 2)
{
    if (--$depth <= 0) {
        throw new Exception("Max depth exceeded. Please try with fewer batch
items or increase depth.");
    }

    $marshal = new Marshaler();
    $total = 0;
    foreach (array_chunk($Batch, 25) as $Items) {
        foreach ($Items as $Item) {
            $BatchWrite['RequestItems'][$TableName][] = ['PutRequest' =>
['Item' => $marshal->marshalItem($Item)]];
        }
        try {
            echo "Batching another " . count($Items) . " for a total of " .
($total += count($Items)) . " items!\n";
            $response = $this->dynamoDbClient->batchWriteItem($BatchWrite);
            $BatchWrite = [];
        } catch (Exception $e) {
            echo "uh oh...";
            echo $e->getMessage();
            die();
        }
    }
}

```

```
        }
        if ($total >= 250) {
            echo "250 movies is probably enough. Right? We can stop there.\n";
            break;
        }
    }
}
```

- For API details, see [BatchWriteItem](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def write_batch(self, movies):
        """
        Fills an Amazon DynamoDB table with the specified data, using the Boto3
        Table.batch_writer() function to put the items in the table.
        Inside the context manager, Table.batch_writer builds a list of
        requests. On exiting the context manager, Table.batch_writer starts sending
        batches of write requests to Amazon DynamoDB and automatically
        handles chunking, buffering, and retrying.

        :param movies: The data to put in the table. Each item must contain at
        least
                           the keys required by the schema that was specified when the
                           table was created.
        """
        try:
            with self.table.batch_writer() as writer:
                for movie in movies:
                    writer.put_item(Item=movie)
        except ClientError as err:
            logger.error(
                "Couldn't load data into table %s. Here's why: %s: %s",
                self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise
```

- For API details, see [BatchWriteItem](#) in *AWS SDK for Python (Boto3) API Reference*.

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
# Fills an Amazon DynamoDB table with the specified data. Items are sent in
# batches of 25 until all items are written.
#
# @param movies [Enumerable] The data to put in the table. Each item must contain
at least
#                                     the keys required by the schema that was specified
when the
#                                     table was created.
def write_batch(movies)
  index = 0
  slice_size = 25
  while index < movies.length
    movie_items = []
    movies[index, slice_size].each do |movie|
      movie_items.append({put_request: { item: movie }})
    end
    @dynamo_resource.batch_write_item({request_items: { @table.name =>
movie_items }})
    index += slice_size
  end
rescue Aws::Errors::ServiceError => e
  puts(
    "Couldn't load data into table #{@table.name}. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
end
```

- For API details, see [BatchWriteItem](#) in [AWS SDK for Ruby API Reference](#).

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Scenarios for DynamoDB using AWS SDKs

The following code examples show you how to implement common scenarios in DynamoDB with AWS SDKs. These scenarios show you how to accomplish specific tasks by calling multiple functions within DynamoDB. Each scenario includes a link to GitHub, where you can find instructions on how to set up and run the code.

### Examples

- [Accelerate DynamoDB reads with DAX using an AWS SDK \(p. 928\)](#)
- [Get started using DynamoDB tables, items, and queries using an AWS SDK \(p. 934\)](#)
- [Query a DynamoDB table by using batches of PartiQL statements and an AWS SDK \(p. 991\)](#)
- [Query a DynamoDB table using PartiQL and an AWS SDK \(p. 1023\)](#)

## Accelerate DynamoDB reads with DAX using an AWS SDK

The following code example shows how to:

- Create and write data to a table with both the DAX and SDK clients.

- Get, query, and scan the table with both the DAX and SDK clients and compare their performance.

For more information, see [Developing with the DynamoDB Accelerator Client](#).

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a table with either the DAX or Boto3 client.

```
import boto3

def create_dax_table(dyn_resource=None):
    """
    Creates a DynamoDB table.

    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The newly created table.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table_name = 'TryDaxTable'
    params = {
        'TableName': table_name,
        'KeySchema': [
            {'AttributeName': 'partition_key', 'KeyType': 'HASH'},
            {'AttributeName': 'sort_key', 'KeyType': 'RANGE'}
        ],
        'AttributeDefinitions': [
            {'AttributeName': 'partition_key', 'AttributeType': 'N'},
            {'AttributeName': 'sort_key', 'AttributeType': 'N'}
        ],
        'ProvisionedThroughput': {
            'ReadCapacityUnits': 10,
            'WriteCapacityUnits': 10
        }
    }
    table = dyn_resource.create_table(**params)
    print(f"Creating {table_name}...")
    table.wait_until_exists()
    return table

if __name__ == '__main__':
    dax_table = create_dax_table()
    print(f"Created table.")
```

Write test data to the table.

```
import boto3

def write_data_to_dax_table(key_count, item_size, dyn_resource=None):
    """
    Writes test data to the demonstration table.

    :param key_count: The number of partition and sort keys to use to populate the
    """
    pass
```

```

        table. The total number of items is key_count * key_count.
:param item_size: The size of non-key data for each test item.
:param dyn_resource: Either a Boto3 or DAX resource.
"""
if dyn_resource is None:
    dyn_resource = boto3.resource('dynamodb')

table = dyn_resource.Table('TryDaxTable')
some_data = 'X' * item_size

for partition_key in range(1, key_count + 1):
    for sort_key in range(1, key_count + 1):
        table.put_item(Item={
            'partition_key': partition_key,
            'sort_key': sort_key,
            'some_data': some_data
        })
    print(f"Put item ({partition_key}, {sort_key}) succeeded.")

if __name__ == '__main__':
    write_key_count = 10
    write_item_size = 1000
    print(f"Writing {write_key_count}*{write_key_count} items to the table. "
          f"Each item is {write_item_size} characters.")
    write_data_to_dax_table(write_key_count, write_item_size)

```

Get items for a number of iterations for both the DAX client and the Boto3 client and report the time spent for each.

```

import argparse
import sys
import time
import amazondax
import boto3

def get_item_test(key_count, iterations, dyn_resource=None):
    """
    Gets items from the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param key_count: The number of items to get from the table in each iteration.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    start = time.perf_counter()
    for _ in range(iterations):
        for partition_key in range(1, key_count + 1):
            for sort_key in range(1, key_count + 1):
                table.get_item(Key={
                    'partition_key': partition_key,
                    'sort_key': sort_key
                })
                print('.')
                sys.stdout.flush()
    print()

```

```

        end = time.perf_counter()
        return start, end

if __name__ == '__main__':
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        'endpoint_url', nargs='?',
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not used.")
    args = parser.parse_args()

    test_key_count = 10
    test_iterations = 50
    if args.endpoint_url:
        print(f"Getting each item from the table {test_iterations} times, "
              f"using the DAX client.")
        # Use a with statement so the DAX client closes the cluster after
        completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as dax:
            test_start, test_end = get_item_test(
                test_key_count, test_iterations, dyn_resource=dax)
    else:
        print(f"Getting each item from the table {test_iterations} times, "
              f"using the Boto3 client.")
        test_start, test_end = get_item_test(
            test_key_count, test_iterations)
    print(f"Total time: {test_end - test_start:.4f} sec. Average time: "
          f"{{(test_end - test_start)/ test_iterations}}")

```

Query the table for a number of iterations for both the DAX client and the Boto3 client and report the time spent for each.

```

import argparse
import time
import sys
import amazondax
import boto3
from boto3.dynamodb.conditions import Key

def query_test(partition_key, sort_keys, iterations, dyn_resource=None):
    """
    Queries the table a specified number of times. The time before the
    first iteration and the time after the last iteration are both captured
    and reported.

    :param partition_key: The partition key value to use in the query. The query
                         returns items that have partition keys equal to this
                         value.
    :param sort_keys: The range of sort key values for the query. The query returns
                     items that have sort key values between these two values.
    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    key_condition_expression = \

```

```

        Key('partition_key').eq(partition_key) & \
        Key('sort_key').between(*sort_keys)

    start = time.perf_counter()
    for _ in range(iterations):
        table.query(KeyConditionExpression=key_condition_expression)
        print('.', end='')
        sys.stdout.flush()
    print()
    end = time.perf_counter()
    return start, end

if __name__ == '__main__':
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        'endpoint_url', nargs='?',
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not used.")
    args = parser.parse_args()

    test_partition_key = 5
    test_sort_keys = (2, 9)
    test_iterations = 100
    if args.endpoint_url:
        print(f"Querying the table {test_iterations} times, using the DAX client.")
        # Use a with statement so the DAX client closes the cluster after completion.
        with amazonadax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as dax:
            test_start, test_end = query_test(
                test_partition_key, test_sort_keys, test_iterations,
                dyn_resource=dax)
        else:
            print(f"Querying the table {test_iterations} times, using the Boto3 client.")
            test_start, test_end = query_test(
                test_partition_key, test_sort_keys, test_iterations)

    print(f"Total time: {test_end - test_start:.4f} sec. Average time: "
          f"{{(test_end - test_start)/test_iterations}}")

```

Scan the table for a number of iterations for both the DAX client and the Boto3 client and report the time spent for each.

```

import argparse
import time
import sys
import amazonadax
import boto3

def scan_test(iterations, dyn_resource=None):
    """
    Scans the table a specified number of times. The time before the first iteration and the time after the last iteration are both captured and reported.

    :param iterations: The number of iterations to run.
    :param dyn_resource: Either a Boto3 or DAX resource.
    :return: The start and end times of the test.
    """

```

```

if dyn_resource is None:
    dyn_resource = boto3.resource('dynamodb')

table = dyn_resource.Table('TryDaxTable')
start = time.perf_counter()
for _ in range(iterations):
    table.scan()
    print('.', end='')
    sys.stdout.flush()
print()
end = time.perf_counter()
return start, end

if __name__ == '__main__':
    # pylint: disable=not-context-manager
    parser = argparse.ArgumentParser()
    parser.add_argument(
        'endpoint_url', nargs='?',
        help="When specified, the DAX cluster endpoint. Otherwise, DAX is not used.")
    args = parser.parse_args()

    test_iterations = 100
    if args.endpoint_url:
        print(f"Scanning the table {test_iterations} times, using the DAX client.")
        # Use a with statement so the DAX client closes the cluster after completion.
        with amazondax.AmazonDaxClient.resource(endpoint_url=args.endpoint_url) as dax:
            test_start, test_end = scan_test(test_iterations, dyn_resource=dax)
    else:
        print(f"Scanning the table {test_iterations} times, using the Boto3 client.")
        test_start, test_end = scan_test(test_iterations)
    print(f"Total time: {test_end - test_start:.4f} sec. Average time: "
          f"{{(test_end - test_start)/test_iterations}}")

```

Delete the table.

```

import boto3

def delete_dax_table(dyn_resource=None):
    """
    Deletes the demonstration table.

    :param dyn_resource: Either a Boto3 or DAX resource.
    """
    if dyn_resource is None:
        dyn_resource = boto3.resource('dynamodb')

    table = dyn_resource.Table('TryDaxTable')
    table.delete()

    print(f"Deleting {table.name}...")
    table.wait_until_not_exists()

if __name__ == '__main__':
    delete_dax_table()
    print("Table deleted!")

```

- For API details, see the following topics in *AWS SDK for Python (Boto3) API Reference*.
  - [CreateTable](#)
  - [DeleteTable](#)
  - [GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Get started using DynamoDB tables, items, and queries using an AWS SDK

The following code examples show how to:

- Create a table that can hold movie data.
- Put, get, and update a single movie in the table.
- Write movie data to the table from a sample JSON file.
- Query for movies that were released in a given year.
- Scan for movies that were released in a range of years.
- Delete a movie from the table.
- Delete the table.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
/// <summary>
/// This example application performs the following basic Amazon DynamoDB
/// functions:
///
///     CreateTableAsync
///     PutItemAsync
///     UpdateItemAsync
///     BatchWriteItemAsync
///     GetItemAsync
///     DeleteItemAsync
///     Query
///     Scan
///     DeleteItemAsync
///
/// The code in this example uses the AWS SDK for .NET version 3.7 and .NET 5.
/// Before you run this example, download 'movies.json' from
/// https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
/// GettingStarted.Js.02.html,
/// and put it in the same folder as the example.
/// </summary>
namespace DynamoDB_Basics_Scenario
```

```
{
    using System;
    using System.Threading.Tasks;
    using Amazon.DynamoDBv2;

    public class DynamoDB_Basics
    {
        // Separator for the console display.
        private static readonly string SepBar = new('-', 80);

        public static async Task Main()
        {
            var client = new AmazonDynamoDBClient();

            var tableName = "movie_table";
            var movieFileName = "moviedata.json";

            DisplayInstructions();

            // Create a new table and wait for it to be active.
            Console.WriteLine($"Creating the new table: {tableName}");

            var success = await DynamoDbMethods.CreateMovieTableAsync(client,
                tableName);

            if (success)
            {
                Console.WriteLine($"\\nTable: {tableName} successfully created.");
            }
            else
            {
                Console.WriteLine($"\\nCould not create {tableName}.");
            }

            WaitForEnter();

            // Add a single new movie to the table.
            var newMovie = new Movie
            {
                Year = 2021,
                Title = "Spider-Man: No Way Home",
            };

            success = await DynamoDbMethods.PutItemAsync(client, newMovie,
                tableName);
            if (success)
            {
                Console.WriteLine($"Added {newMovie.Title} to the table.");
            }
            else
            {
                Console.WriteLine("Could not add movie to table.");
            }

            WaitForEnter();

            // Update the new movie by adding a plot and rank.
            var newInfo = new MovieInfo
            {
                Plot = "With Spider-Man's identity now revealed, Peter asks" +
                    "Doctor Strange for help. When a spell goes wrong, dangerous" +
                    "foes from other worlds start to appear, forcing Peter to" +
                    "discover what it truly means to be Spider-Man.",
                Rank = 9,
            };
        }
}
```

```
        success = await DynamoDbMethods.UpdateItemAsync(client, newMovie,
newInfo, tableName);
        if (success)
        {
            Console.WriteLine($"Successfully updated the movie:
{newMovie.Title}");
        }
        else
        {
            Console.WriteLine("Could not update the movie.");
        }

        WaitForEnter();

        // Add a batch of movies to the DynamoDB table from a list of
        // movies in a JSON file.
        var itemCount = await DynamoDbMethods.BatchWriteItemsAsync(client,
movieFileName);
        Console.WriteLine($"Added {itemCount} movies to the table.");

        WaitForEnter();

        // Get a movie by key. (partition + sort)
        var lookupMovie = new Movie
        {
            Title = "Jurassic Park",
            Year = 1993,
        };

        Console.WriteLine("Looking for the movie \"Spider-Man: No Way Home
\".");
        var item = await DynamoDbMethods.GetItemAsync(client, lookupMovie,
tableName);
        if (item.Count > 0)
        {
            DynamoDbMethods.DisplayItem(item);
        }
        else
        {
            Console.WriteLine($"Couldn't find {lookupMovie.Title}");
        }

        WaitForEnter();

        // Delete a movie.
        var movieToDelete = new Movie
        {
            Title = "The Town",
            Year = 2010,
        };

        success = await DynamoDbMethods.DeleteItemAsync(client, tableName,
movieToDelete);

        if (success)
        {
            Console.WriteLine($"Successfully deleted {movieToDelete.Title}.");
        }
        else
        {
            Console.WriteLine($"Could not delete {movieToDelete.Title}.");
        }

        WaitForEnter();

        // Use Query to find all the movies released in 2010.
```

```

        int findYear = 2010;
        Console.WriteLine($"Movies released in {findYear}");
        var queryCount = await DynamoDbMethods.QueryMoviesAsync(client,
tableName, findYear);
        Console.WriteLine($"Found {queryCount} movies released in {findYear}");

        WaitForEnter();

        // Use Scan to get a list of movies from 2001 to 2011.
        int startYear = 2001;
        int endYear = 2011;
        var scanCount = await DynamoDbMethods.ScanTableAsync(client, tableName,
startYear, endYear);
        Console.WriteLine($"Found {scanCount} movies released between
{startYear} and {endYear}");

        WaitForEnter();

        // Delete the table.
        success = await DynamoDbMethods.DeleteTableAsync(client, tableName);

        if (success)
        {
            Console.WriteLine($"Successfully deleted {tableName}");
        }
        else
        {
            Console.WriteLine($"Could not delete {tableName}");
        }

        Console.WriteLine("The DynamoDB Basics example application is done.");

        WaitForEnter();
    }

    /// <summary>
    /// Displays the description of the application on the console.
    /// </summary>
    private static void DisplayInstructions()
    {
        Console.Clear();
        Console.WriteLine();
        Console.Write(new string(' ', 28));
        Console.WriteLine("DynamoDB Basics Example");
        Console.WriteLine(SepBar);
        Console.WriteLine("This demo application shows the basics of using
DynamoDB with the AWS SDK for");
        Console.WriteLine(".NET version 3.7 and .NET Core 5.");
        Console.WriteLine(SepBar);
        Console.WriteLine("The application does the following:");
        Console.WriteLine("\t1. Creates a table with partition: year and
sort:title.");
        Console.WriteLine("\t2. Adds a single movie to the table.");
        Console.WriteLine("\t3. Adds movies to the table from
moviedata.json.");
        Console.WriteLine("\t4. Updates the rating and plot of the movie that
was just added.");
        Console.WriteLine("\t5. Gets a movie using its key (partition +
sort).");
        Console.WriteLine("\t6. Deletes a movie.");
        Console.WriteLine("\t7. Uses QueryAsync to return all movies released
in a given year.");
        Console.WriteLine("\t8. Uses ScanAsync to return all movies released
within a range of years.");
        Console.WriteLine("\t9. Finally, it deletes the table that was just
created.");
    }
}

```

```
        WaitForEnter();
    }

    /// <summary>
    /// Simple method to wait for the Enter key to be pressed.
    /// </summary>
    private static void WaitForEnter()
    {
        Console.WriteLine("\nPress <Enter> to continue.");
        Console.WriteLine(SepBar);
        _ = Console.ReadLine();
    }
}
```

Creates a table to contain movie data.

```
    ///> An initialized Amazon DynamoDB client object.</param>
    ///> The name of the table to create.</param>
    ///> A Boolean value indicating the success of the operation.</returns>
    public static async Task<bool> CreateMovieTableAsync(AmazonDynamoDBClient
client, string tableName)
    {
        var response = await client.CreateTableAsync(new CreateTableRequest
        {
            TableName = tableName,
            AttributeDefinitions = new List<AttributeDefinition>()
            {
                new AttributeDefinition
                {
                    AttributeName = "title",
                    AttributeType = "S",
                },
                new AttributeDefinition
                {
                    AttributeName = "year",
                    AttributeType = "N",
                },
            },
            KeySchema = new List<KeySchemaElement>()
            {
                new KeySchemaElement
                {
                    AttributeName = "year",
                    KeyType = "HASH",
                },
                new KeySchemaElement
                {
                    AttributeName = "title",
                    KeyType = "RANGE",
                },
            },
            ProvisionedThroughput = new ProvisionedThroughput
            {
                ReadCapacityUnits = 5,
                WriteCapacityUnits = 5,
            }
        });
        return response;
    }
}
```

```

        },
    });

    // Wait until the table is ACTIVE and then report success.
    Console.WriteLine("Waiting for table to become active...");

    var request = new DescribeTableRequest
    {
        TableName = response.TableDescription.TableName,
    };

    TableStatus status;

    int sleepDuration = 2000;

    do
    {
        System.Threading.Thread.Sleep(sleepDuration);

        var describeTableResponse = await
client.DescribeTableAsync(request);
        status = describeTableResponse.Table.TableStatus;

        Console.WriteLine(".");
    }
    while (status != "ACTIVE");

    return status == TableStatus.ACTIVE;
}

```

Adds a single movie to the table.

```

/// <summary>
/// Adds a new item to the table.
/// </summary>
/// <param name="client">An initialized Amazon DynamoDB client object.</param>
/// <param name="newMovie">A Movie object containing information for
/// the movie to add to the table.</param>
/// <param name="tableName">The name of the table where the item will be
/// added.</param>
/// <returns>A Boolean value that indicates the results of adding the
/// item.</returns>
public static async Task<bool> PutItemAsync(AmazonDynamoDBClient client,
Movie newMovie, string tableName)
{
    var item = new Dictionary<string, AttributeValue>
    {
        ["title"] = new AttributeValue { S = newMovie.Title },
        ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
    };

    var request = new PutItemRequest
    {
        TableName = tableName,
        Item = item,
    };

    var response = await client.PutItemAsync(request);
    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}

```

Updates a single item in a table.

```

    ///<summary>
    /// Updates an existing item in the movies table.
    ///</summary>
    ///<param name="client">An initialized Amazon DynamoDB client object.</param>
    ///<param name="newMovie">A Movie object containing information for
    /// the movie to update.</param>
    ///<param name="newInfo">A MovieInfo object that contains the
    /// information that will be changed.</param>
    ///<param name="tableName">The name of the table that contains the
    movie.</param>
    ///<returns>A Boolean value that indicates the success of the operation.</returns>
    public static async Task<bool> UpdateItemAsync(
        AmazonDynamoDBClient client,
        Movie newMovie,
        MovieInfo newInfo,
        string tableName)
    {
        var key = new Dictionary<string, AttributeValue>
        {
            ["title"] = new AttributeValue { S = newMovie.Title },
            ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
        };
        var updates = new Dictionary<string, AttributeValueUpdate>
        {
            ["info.plot"] = new AttributeValueUpdate
            {
                Action = AttributeAction.PUT,
                Value = new AttributeValue { S = newInfo.Plot },
            },
            ["info.rating"] = new AttributeValueUpdate
            {
                Action = AttributeAction.PUT,
                Value = new AttributeValue { N = newInfo.Rank.ToString() },
            },
        };

        var request = new UpdateItemRequest
        {
            AttributeUpdates = updates,
            Key = key,
            TableName = tableName,
        };

        var response = await client.UpdateItemAsync(request);

        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

```

Retrieves a single item from the movie table.

```

    ///<summary>
    /// Gets information about an existing movie from the table.
    ///</summary>

```

```

/// <param name="client">An initialized Amazon DynamoDB client object.</param>
/// <param name="newMovie">A Movie object containing information about
/// the movie to retrieve.</param>
/// <param name="tableName">The name of the table containing the movie.</param>
/// <returns>A Dictionary object containing information about the item
/// retrieved.</returns>
public static async Task<Dictionary<string, AttributeValue>>
GetItemAsync(AmazonDynamoDBClient client, Movie newMovie, string tableName)
{
    var key = new Dictionary<string, AttributeValue>
    {
        ["title"] = new AttributeValue { S = newMovie.Title },
        ["year"] = new AttributeValue { N = newMovie.Year.ToString() },
    };

    var request = new GetItemRequest
    {
        Key = key,
        TableName = tableName,
    };

    var response = await client.GetItemAsync(request);
    return response.Item;
}

```

Writes a batch of items to the movie table.

```

/// <summary>
/// Loads the contents of a JSON file into a list of movies to be
/// added to the DynamoDB table.
/// </summary>
/// <param name="movieFileName">The full path to the JSON file.</param>
/// <returns>A generic list of movie objects.</returns>
public static List<Movie> ImportMovies(string movieFileName)
{
    if (!File.Exists(movieFileName))
    {
        return null;
    }

    using var sr = new StreamReader(movieFileName);
    string json = sr.ReadToEnd();
    var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

    // Now return the first 250 entries.
    return allMovies.GetRange(0, 250);
}

/// <summary>
/// Writes 250 items to the movie table.
/// </summary>
/// <param name="client">The initialized DynamoDB client object.</param>
/// <param name="movieFileName">A string containing the full path to
/// the JSON file containing movie data.</param>
/// <returns>A long integer value representing the number of movies
/// imported from the JSON file.</returns>
public static async Task<long> BatchWriteItemsAsync(
    AmazonDynamoDBClient client,
    string movieFileName)
{

```

```

var movies = ImportMovies(movieFileName);
if (movies is null)
{
    Console.WriteLine("Couldn't find the JSON file with movie data.");
    return 0;
}

var context = new DynamoDBContext(client);

var bookBatch = context.CreateBatchWrite<Movie>();
bookBatch.AddPutItems(movies);

Console.WriteLine("Adding imported movies to the table.");
await bookBatch.ExecuteAsync();

return movies.Count;
}

```

Deletes a single item from the table.

```

/// <summary>
/// Deletes a single item from a DynamoDB table.
/// </summary>
/// <param name="client">The initialized DynamoDB client object.</param>
/// <param name="tableName">The name of the table from which the item
/// will be deleted.</param>
/// <param name="movieToDelete">A movie object containing the title and
/// year of the movie to delete.</param>
/// <returns>A Boolean value indicating the success or failure of the
/// delete operation.</returns>
public static async Task<bool> DeleteItemAsync(
    AmazonDynamoDBClient client,
    string tableName,
    Movie movieToDelete)
{
    var key = new Dictionary<string, AttributeValue>
    {
        ["title"] = new AttributeValue { S = movieToDelete.Title },
        ["year"] = new AttributeValue { N =
            movieToDelete.Year.ToString() },
    };

    var request = new DeleteItemRequest
    {
        TableName = tableName,
        Key = key,
    };

    var response = await client.DeleteItemAsync(request);
    return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}

```

Queries the table for movies released in a particular year.

```

/// <summary>
/// Queries the table for movies released in a particular year and
/// then displays the information for the movies returned.
/// </summary>

```

```

/// <param name="client">The initialized DynamoDB client object.</param>
/// <param name="tableName">The name of the table to query.</param>
/// <param name="year">The release year for which we want to
/// view movies.</param>
/// <returns>The number of movies that match the query.</returns>
public static async Task<int> QueryMoviesAsync(AmazonDynamoDBClient client,
string tableName, int year)
{
    var movieTable = Table.LoadTable(client, tableName);
    var filter = new QueryFilter("year", QueryOperator.Equal, year);

    Console.WriteLine("\nFind movies released in: {year}:");

    var config = new QueryOperationConfig()
    {
        Limit = 10, // 10 items per page.
        Select = SelectValues.SpecificAttributes,
        AttributesToGet = new List<string>
        {
            "title",
            "year",
        },
        ConsistentRead = true,
        Filter = filter,
    };

    // Value used to track how many movies match the
    // supplied criteria.
    var moviesFound = 0;

    Search search = movieTable.Query(config);
    do
    {
        var movieList = await search.GetNextSetAsync();
        moviesFound += movieList.Count;

        foreach (var movie in movieList)
        {
            DisplayDocument(movie);
        }
    }
    while (!search.IsDone);

    return moviesFound;
}

```

Scans the table for movies released in a range of years.

```

public static async Task<int> ScanTableAsync(
    AmazonDynamoDBClient client,
    string tableName,
    int startYear,
    int endYear)
{
    var request = new ScanRequest
    {
        TableName = tableName,
        ExpressionAttributeNames = new Dictionary<string, string>
        {
            { "#yr", "year" },
        },
        ExpressionAttributeValues = new Dictionary<string, AttributeValue>
        {

```

```

        { ":y_a", new AttributeValue { N = startYear.ToString() } },
        { ":y_z", new AttributeValue { N = endYear.ToString() } },
    },
    FilterExpression = "#yr between :y_a and :y_z",
    ProjectionExpression = "#yr, title, info.actors[0], info.directors,
info.running_time_secs",
};

// Keep track of how many movies were found.
int foundCount = 0;

var response = new ScanResponse();
do
{
    response = await client.ScanAsync(request);
    foundCount += response.Items.Count;
    response.Items.ForEach(i => DisplayItem(i));
}
while (response.LastEvaluatedKey.Count > 1);
return foundCount;
}

```

Deletes the movie table.

```

public static async Task<bool> DeleteTableAsync(AmazonDynamoDBClient
client, string tableName)
{
    var request = new DeleteTableRequest
    {
        TableName = tableName,
    };

    var response = await client.DeleteTableAsync(request);
    if (response.HttpStatusCode == System.Net.HttpStatusCode.OK)
    {
        Console.WriteLine($"Table {response.TableDescription.TableName}
successfully deleted.");
        return true;
    }
    else
    {
        Console.WriteLine("Could not delete table.");
        return false;
    }
}

```

- For API details, see the following topics in *AWS SDK for .NET API Reference*.
  - [BatchWriteItem](#)
  - [CreateTable](#)
  - [DeleteItem](#)
  - [DeleteTable](#)
  - [DescribeTable](#)
  - [GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)

- [UpdateItem](#)

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a struct and methods that call DynamoDB actions.

```
// TableBasics encapsulates the Amazon DynamoDB service actions used in the
// examples.
// It contains a DynamoDB service client that is used to act on the specified
// table.
type TableBasics struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// TableExists determines whether a DynamoDB table exists.
func (basics TableBasics) TableExists() (bool, error) {
    exists := true
    _, err := basics.DynamoDbClient.DescribeTable(
        context.TODO(), &dynamodb.DescribeTableInput{TableName:
            aws.String(basics.TableName)},
    )
    if err != nil {
        var notFoundEx *types.ResourceNotFoundException
        if errors.As(err, &notFoundEx) {
            log.Printf("Table %v does not exist.\n", basics.TableName)
            err = nil
        } else {
            log.Printf("Couldn't determine existence of table %v. Here's why: %v\n",
                basics.TableName, err)
        }
        exists = false
    }
    return exists, err
}

// CreateMovieTable creates a DynamoDB table with a composite primary key defined
// as
// a string sort key named `title`, and a numeric partition key named `year`.
// This function uses NewTableExistsWaiter to wait for the table to be created by
// DynamoDB before it returns.
func (basics TableBasics) CreateMovieTable() (*types.TableDescription, error) {
    var tableDesc *types.TableDescription
    table, err := basics.DynamoDbClient.CreateTable(context.TODO(),
        &dynamodb.CreateTableInput{
            AttributeDefinitions: []types.AttributeDefinition{
                {
                    AttributeName: aws.String("year"),
                    AttributeType: types.ScalarAttributeTypeN,
                },
                {
                    AttributeName: aws.String("title"),
                    AttributeType: types.ScalarAttributeTypeS,
                },
            },
            KeySchema: []types.KeySchemaElement{
                {
                    AttributeName: aws.String("year"),
                },
            },
        },
    )
    if err != nil {
        log.Printf("Error creating table: %v\n", err)
        return nil, err
    }
    tableDesc = table
    return tableDesc, nil
}
```

```

        KeyType:      types.KeyTypeHash,
    }, {
        AttributeName: aws.String("title"),
        KeyType:      types.KeyTypeRange,
    }),
    TableName: aws.String(basics.TableName),
    ProvisionedThroughput: &types.ProvisionedThroughput{
        ReadCapacityUnits:  aws.Int64(10),
        WriteCapacityUnits: aws.Int64(10),
    },
})
if err != nil {
    log.Printf("Couldn't create table %v. Here's why: %v\n", basics.TableName, err)
} else {
    waiter := dynamodb.NewTableExistsWaiter(basics.DynamoDbClient)
    err = waiter.Wait(context.TODO(), &dynamodb.DescribeTableInput{
        TableName: aws.String(basics.TableName)}, 5*time.Minute)
    if err != nil {
        log.Printf("Wait for table exists failed. Here's why: %v\n", err)
    }
    tableDesc = table.TableDescription
}
return tableDesc, err
}

// ListTables lists the DynamoDB table names for the current account.
func (basics TableBasics) ListTables() ([]string, error) {
    var tableNames []string
    tables, err := basics.DynamoDbClient.ListTables(
        context.TODO(), &dynamodb.ListTablesInput{})
    if err != nil {
        log.Printf("Couldn't list tables. Here's why: %v\n", err)
    } else {
        tableNames = tables.TableNames
    }
    return tableNames, err
}

// AddMovie adds a movie to the DynamoDB table.
func (basics TableBasics) AddMovie(movie Movie) error {
    item, err := attributevalue.MarshalMap(movie)
    if err != nil {
        panic(err)
    }
    _, err = basics.DynamoDbClient.PutItem(context.TODO(), &dynamodb.PutItemInput{
        TableName: aws.String(basics.TableName), Item: item,
    })
    if err != nil {
        log.Printf("Couldn't add item to table. Here's why: %v\n", err)
    }
    return err
}

// UpdateMovie updates the rating and plot of a movie that already exists in the
// DynamoDB table. This function uses the `expression` package to build the update
// expression.
func (basics TableBasics) UpdateMovie(movie Movie)
    (map[string]map[string]interface{}, error) {
    var err error
    var response *dynamodb.UpdateItemOutput

```

```

var attributeMap map[string]map[string]interface{}
update := expression.Set(expression.Name("info.rating"),
expression.Value(movie.Info["rating"]))
update.Set(expression.Name("info.plot"), expression.Value(movie.Info["plot"]))
expr, err := expression.NewBuilder().WithUpdate(update).Build()
if err != nil {
    log.Printf("Couldn't build expression for update. Here's why: %v\n", err)
} else {
    response, err = basics.DynamoDbClient.UpdateItem(context.TODO(),
&dynamodb.UpdateItemInput{
    TableName:                 aws.String(basics.TableName),
    Key:                      movie.GetKey(),
    ExpressionAttributeNames: expr.Names(),
    ExpressionAttributeValues: expr.Values(),
    UpdateExpression:         expr.Update(),
    ReturnValue:               types.ReturnValueUpdatedNew,
})
if err != nil {
    log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
} else {
    err = attributevalue.UnmarshalMap(response.Attributes, &attributeMap)
    if err != nil {
        log.Printf("Couldn't unmarshal update response. Here's why: %v\n", err)
    }
}
}
return attributeMap, err
}

// AddMovieBatch adds a slice of movies to the DynamoDB table. The function sends
// batches of 25 movies to DynamoDB until all movies are added or it reaches the
// specified maximum.
func (basics TableBasics) AddMovieBatch(movies []Movie, maxMovies int) (int, error)
{
var err error
var item map[string]types.AttributeValue
written := 0
batchSize := 25 // DynamoDB allows a maximum batch size of 25 items.
start := 0
end := start + batchSize
for start < maxMovies && start < len(movies) {
    var writeReqs []types.WriteRequest
    if end > len(movies) {
        end = len(movies)
    }
    for _, movie := range movies[start:end] {
        item, err = attributevalue.MarshalMap(movie)
        if err != nil {
            log.Printf("Couldn't marshal movie %v for batch writing. Here's why: %v\n",
movie.Title, err)
        } else {
            writeReqs = append(
                writeReqs,
                types.WriteRequest{PutRequest: &types.PutRequest{Item: item}},
            )
        }
    }
    _, err = basics.DynamoDbClient.BatchWriteItem(context.TODO(),
&dynamodb.BatchWriteItemInput{
    RequestItems: map[string][]types.WriteRequest{basics.TableName: writeReqs}})
    if err != nil {
        log.Printf("Couldn't add a batch of movies to %v. Here's why: %v\n",
basics.TableName, err)
    } else {
}
}
}

```

```

        written += len(writeReqs)
    }
    start = end
    end += batchSize
}

return written, err
}

// GetMovie gets movie data from the DynamoDB table by using the primary composite
// key
// made of title and year.
func (basics TableBasics) GetMovie(title string, year int) (Movie, error) {
    movie := Movie{Title: title, Year: year}
    response, err := basics.DynamoDbClient.GetItem(context.TODO(),
        &dynamodb.GetItemInput{
            Key: movie.GetKey(), TableName: aws.String(basics.TableName),
        })
    if err != nil {
        log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
    } else {
        err = attributevalue.UnmarshalMap(response.Item, &movie)
        if err != nil {
            log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
        }
    }
    return movie, err
}

// Query gets all movies in the DynamoDB table that were released in the specified
// year.
// The function uses the `expression` package to build the key condition expression
// that is used in the query.
func (basics TableBasics) Query(releaseYear int) ([]Movie, error) {
    var err error
    var response *dynamodb.QueryOutput
    var movies []Movie
    keyEx := expression.Key("year").Equal(expression.Value(releaseYear))
    expr, err := expression.NewBuilder().WithKeyCondition(keyEx).Build()
    if err != nil {
        log.Printf("Couldn't build expression for query. Here's why: %v\n", err)
    } else {
        response, err = basics.DynamoDbClient.Query(context.TODO(), &dynamodb.QueryInput{
            TableName:           aws.String(basics.TableName),
            ExpressionAttributeNames: expr.Names(),
            ExpressionAttributeValues: expr.Values(),
            KeyConditionExpression:   expr.KeyCondition(),
        })
        if err != nil {
            log.Printf("Couldn't query for movies released in %v. Here's why: %v\n",
                releaseYear, err)
        } else {
            err = attributevalue.UnmarshalListOfMaps(response.Items, &movies)
            if err != nil {
                log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
            }
        }
    }
    return movies, err
}

```

```

// Scan gets all movies in the DynamoDB table that were released in a range of
// years
// and projects them to return a reduced set of fields.
// The function uses the `expression` package to build the filter and projection
// expressions.
func (basics TableBasics) Scan(startYear int, endYear int) ([]Movie, error) {
    var movies []Movie
    var err error
    var response *dynamodb.ScanOutput
    filtEx := expression.Name("year").Between(expression.Value(startYear),
        expression.Value(endYear))
    projEx := expression.NamesList(
        expression.Name("year"), expression.Name("title"),
        expression.Name("info.rating"))
    expr, err :=
        expression.NewBuilder().WithFilter(filtEx).WithProjection(projEx).Build()
    if err != nil {
        log.Printf("Couldn't build expressions for scan. Here's why: %v\n", err)
    } else {
        response, err = basics.DynamoDbClient.Scan(context.TODO(), &dynamodb.ScanInput{
            TableName: aws.String(basics.TableName),
            ExpressionAttributeNames: expr.Names(),
            ExpressionAttributeValues: expr.Values(),
            FilterExpression: expr.Filter(),
            ProjectionExpression: expr.Projection(),
        })
        if err != nil {
            log.Printf("Couldn't scan for movies released between %v and %v. Here's why: %v\n",
                startYear, endYear, err)
        } else {
            err = attributevalue.UnmarshalListOfMaps(response.Items, &movies)
            if err != nil {
                log.Printf("Couldn't unmarshal query response. Here's why: %v\n", err)
            }
        }
    }
    return movies, err
}

// DeleteMovie removes a movie from the DynamoDB table.
func (basics TableBasics) DeleteMovie(movie Movie) error {
    _, err := basics.DynamoDbClient.DeleteItem(context.TODO(),
        &dynamodb.DeleteItemInput{
            TableName: aws.String(basics.TableName), Key: movie.GetKey(),
        })
    if err != nil {
        log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
            err)
    }
    return err
}

// DeleteTable deletes the DynamoDB table and all of its data.
func (basics TableBasics) DeleteTable() error {
    _, err := basics.DynamoDbClient.DeleteTable(context.TODO(),
        &dynamodb.DeleteTableInput{
            TableName: aws.String(basics.TableName)})
    if err != nil {
        log.Printf("Couldn't delete table %v. Here's why: %v\n", basics.TableName, err)
    }
}

```

```
    return err
}
```

Run an interactive scenario to create the table and perform actions on it.

```
// RunMovieScenario is an interactive example that shows you how to use the AWS SDK
// for Go
// to create and use an Amazon DynamoDB table that stores data about movies.
//
// 1. Create a table that can hold movie data.
// 2. Put, get, and update a single movie in the table.
// 3. Write movie data to the table from a sample JSON file.
// 4. Query for movies that were released in a given year.
// 5. Scan for movies that were released in a range of years.
// 6. Delete a movie from the table.
// 7. Delete the table.
//
// This example creates a DynamoDB service client from the specified sdkConfig so
// that
// you can replace it with a mocked or stubbed config for unit testing.
//
// It uses a questioner from the `demotools` package to get input during the
// example.
// This package can be found in the ..\..\demotools folder of this repo.
//
// The specified movie sampler is used to get sample data from a URL that is loaded
// into the named table.
func RunMovieScenario(
    sdkConfig aws.Config, questioner demotools.IQuestioner, tableName string,
    movieSampler actions.IMovieSampler) {
    defer func() {
        if r := recover(); r != nil {
            fmt.Printf("Something went wrong with the demo.")
        }
    }()

    log.Println(strings.Repeat("-", 88))
    log.Println("Welcome to the Amazon DynamoDB getting started demo.")
    log.Println(strings.Repeat("-", 88))

    tableBasics := actions.TableBasics{TableName: tableName,
        DynamoDbClient: dynamodb.NewFromConfig(sdkConfig)}

    exists, err := tableBasics.TableExists()
    if err != nil {
        panic(err)
    }
    if !exists {
        log.Printf("Creating table %v...\n", tableName)
        _, err = tableBasics.CreateMovieTable()
        if err != nil {
            panic(err)
        } else {
            log.Printf("Created table %v.\n", tableName)
        }
    } else {
        log.Printf("Table %v already exists.\n", tableName)
    }

    var customMovie actions.Movie
    customMovie.Title = questioner.Ask("Enter a movie title to add to the table:",
        []demotools.IAnswerValidator{demotools.NotEmpty{}})
```

```

customMovie.Year = questioner.AskInt("What year was it released?",
    []demotools.IAnswerValidator{demotools.NotEmpty{}, demotools.InIntRange{
        Lower: 1900, Upper: 2030}})
customMovie.Info = map[string]interface{}{}
customMovie.Info["rating"] = questioner.AskFloat64(
    "Enter a rating between 1 and 10:", []demotools.IAnswerValidator{
        demotools.NotEmpty{}, demotoools.InFloatRange{Lower: 1, Upper: 10}})
customMovie.Info["plot"] = questioner.Ask("What's the plot? ",
    []demotools.IAnswerValidator{demotools.NotEmpty{}})
err = tableBasics.AddMovie(customMovie)
if err == nil {
    log.Printf("Added %v to the movie table.\n", customMovie.Title)
}
log.Println(strings.Repeat("-", 88))

log.Printf("Let's update your movie. You previously rated it %v.\n",
    customMovie.Info["rating"])
customMovie.Info["rating"] = questioner.AskFloat64(
    "What new rating would you give it?", []demotools.IAnswerValidator{
        demotools.NotEmpty{}, demotoools.InFloatRange{Lower: 1, Upper: 10}})
log.Printf("You summarized the plot as '%v'.\n", customMovie.Info["plot"])
customMovie.Info["plot"] = questioner.Ask("What would you say now?",
    []demotools.IAnswerValidator{demotools.NotEmpty{}})
attributes, err := tableBasics.UpdateMovie(customMovie)
if err == nil {
    log.Printf("Updated %v with new values.\n", customMovie.Title)
    for _, attVal := range attributes {
        for valKey, val := range attVal {
            log.Printf("\t%v: %v\n", valKey, val)
        }
    }
}
log.Println(strings.Repeat("-", 88))

log.Printf("Getting movie data from %v and adding 250 movies to the table...\n",
    movieSampler.GetURL())
movies := movieSampler.GetSampleMovies()
written, err := tableBasics.AddMovieBatch(movies, 250)
if err != nil {
    panic(err)
} else {
    log.Printf("Added %v movies to the table.\n", written)
}

show := 10
if show > written {
    show = written
}
log.Printf("The first %v movies in the table are:", show)
for index, movie := range movies[:show] {
    log.Printf("\t%v. %v\n", index+1, movie.Title)
}
movieIndex := questioner.AskInt(
    "Enter the number of a movie to get info about it: ",
    []demotools.IAnswerValidator{
        demotoools.InIntRange{Lower: 1, Upper: show}}),
)
movie, err := tableBasics.GetMovie(movies[movieIndex-1].Title,
    movies[movieIndex-1].Year)
if err == nil {
    log.Println(movie)
}
log.Println(strings.Repeat("-", 88))

log.Println("Let's get a list of movies released in a given year.")
releaseYear := questioner.AskInt("Enter a year between 1972 and 2018: ",

```

```

    []demotools.IAnswerValidator{demotools.InIntRange{Lower: 1972, Upper: 2018}}},
)
releases, err := tableBasics.Query(releaseYear)
if err == nil {
    if len(releases) == 0 {
        log.Printf("I couldn't find any movies released in %v!\n", releaseYear)
    } else {
        for _, movie := range releases {
            log.Println(movie)
        }
    }
}
log.Println(strings.Repeat("-", 88))

log.Println("Now let's scan for movies released in a range of years.")
startYear := questioner.AskInt("Enter a year: ", []demotools.IAnswerValidator{
    demotools.InIntRange{Lower: 1972, Upper: 2018}})
endYear := questioner.AskInt("Enter another year: ", []demotoools.IAnswerValidator{
    demotools.InIntRange{Lower: 1972, Upper: 2018}})
releases, err = tableBasics.Scan(startYear, endYear)
if err == nil {
    if len(releases) == 0 {
        log.Printf("I couldn't find any movies released between %v and %v!\n",
startYear, endYear)
    } else {
        log.Printf("Found %v movies. In this list, the plot is <nil> because "+
            "we used a projection expression when scanning for items to return only "+
            "the title, year, and rating.\n", len(releases))
        for _, movie := range releases {
            log.Println(movie)
        }
    }
}
log.Println(strings.Repeat("-", 88))

var tables []string
if questioner.AskBool("Do you want to list all of your tables? (y/n) ", "y") {
    tables, err = tableBasics.ListTables()
    if err == nil {
        log.Printf("Found %v tables:", len(tables))
        for _, table := range tables {
            log.Printf("\t%v", table)
        }
    }
}
log.Println(strings.Repeat("-", 88))

log.Printf("Let's remove your movie '%v'.\n", customMovie.Title)
if questioner.AskBool("Do you want to delete it from the table? (y/n) ", "y") {
    err = tableBasics.DeleteMovie(customMovie)
}
if err == nil {
    log.Printf("Deleted %v.\n", customMovie.Title)
}

if questioner.AskBool("Delete the table, too? (y/n)", "y") {
    err = tableBasics.DeleteTable()
} else {
    log.Println("Don't forget to delete the table when you're done or you might " +
        "incur charges on your account.")
}
if err == nil {
    log.Printf("Deleted table %v.\n", tableBasics.TableName)
}

log.Println(strings.Repeat("-", 88))

```

```
    log.Println("Thanks for watching!")
    log.Println(strings.Repeat("-", 88))
}
```

- For API details, see the following topics in *AWS SDK for Go API Reference*.
  - [BatchWriteItem](#)
  - [CreateTable](#)
  - [DeleteItem](#)
  - [DeleteTable](#)
  - [DescribeTable](#)
  - [.GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)
  - [UpdateItem](#)

Java

## SDK for Java 2.x

### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a DynamoDB table.

```
// Create a table with a Sort key.
public static void createTable(DynamoDbClient ddb, String tableName) {

    DynamoDbWaiter dbWaiter = ddb.waiter();
    ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

    // Define attributes.
    attributeDefinitions.add(AttributeDefinition.builder()
        .attributeName("year")
        .attributeType("N")
        .build());

    attributeDefinitions.add(AttributeDefinition.builder()
        .attributeName("title")
        .attributeType("S")
        .build());

    ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
    KeySchemaElement key = KeySchemaElement.builder()
        .attributeName("year")
        .keyType(KeyType.HASH)
        .build();

    KeySchemaElement key2 = KeySchemaElement.builder()
        .attributeName("title")
        .keyType(KeyType.RANGE)
        .build();

    // Add KeySchemaElement objects to the list.
    tableKey.add(key);
    tableKey.add(key2);

    CreateTableRequest request = CreateTableRequest.builder()
```

```

.keySchema(tableKey)
.provisionedThroughput(ProvisionedThroughput.builder()
    .readCapacityUnits(new Long(10))
    .writeCapacityUnits(new Long(10))
    .build())
.attributeDefinitions(attributeDefinitions)
.tableName(tableName)
.build();

try {
    CreateTableResponse response = ddb.createTable(request);
    DescribeTableRequest tableRequest = DescribeTableRequest.builder()
        .tableName(tableName)
        .build();

    // Wait until the Amazon DynamoDB table is created.
    WaiterResponse<DescribeTableResponse> waiterResponse =
    dbWaiter.waitUntilTableExists(tableRequest);
    waiterResponse.matched().response().ifPresent(System.out::println);
    String newTable = response.tableDescription().tableName();
    System.out.println("The " +newTable + " was successfully created.");

} catch (DynamoDbException e) {
    System.err.println(e.getMessage());
    System.exit(1);
}
}
}

```

Create a helper function to download and extract the sample JSON file.

```

// Load data into the table.
public static void loadData(DynamoDbClient ddb, String tableName, String
fileName) throws IOException {

    DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
        .dynamoDbClient(ddb)
        .build();

    DynamoDbTable<Movies> mappedTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
    JsonParser parser = new JsonFactory().createParser(new File(fileName));
    com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
    Iterator<JsonNode> iter = rootNode.iterator();
    ObjectNode currentNode;
    int t = 0 ;
    while (iter.hasNext()) {

        // Only add 200 Movies to the table.
        if (t == 200)
            break ;
        currentNode = (ObjectNode) iter.next();

        int year = currentNode.path("year").asInt();
        String title = currentNode.path("title").asText();
        String info = currentNode.path("info").toString();

        Movies movies = new Movies();
        movies.setYear(year);
        movies.setTitle(title);
        movies.setInfo(info);

        // Put the data into the Amazon DynamoDB Movie table.
        mappedTable.putItem(movies);
    }
}
}

```

```

        t++;
    }
}
```

Get an item from a table.

```

public static void getItem(DynamoDbClient ddb) {

    HashMap<String,AttributeValue> keyToGet = new HashMap<>();
    keyToGet.put("year", AttributeValue.builder()
        .n("1933")
        .build());

    keyToGet.put("title", AttributeValue.builder()
        .s("King Kong")
        .build());

    GetItemRequest request = GetItemRequest.builder()
        .key(keyToGet)
        .tableName("Movies")
        .build();

    try {
        Map<String,AttributeValue> returnedItem = ddb.getItem(request).item();

        if (returnedItem != null) {
            Set<String> keys = returnedItem.keySet();
            System.out.println("Amazon DynamoDB table attributes: \n");

            for (String key1 : keys) {
                System.out.format("%s: %s\n", key1,
                    returnedItem.get(key1).toString());
            }
        } else {
            System.out.format("No item found with the key %s!\n", "year");
        }
    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
}
```

Full example.

```

public class Scenario {

    public static void main(String[] args) throws IOException {

        final String usage = "\n" +
            "Usage:\n" +
            "  <fileName>\n\n" +
            "Where:\n" +
            "  fileName - The path to the moviedata.json file that you can
download from the Amazon DynamoDB Developer Guide.\n" ;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String tableName = "Movies";
```

```

        String fileName = args[0];
        ProfileCredentialsProvider credentialsProvider =
ProfileCredentialsProvider.create();
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
            .region(region)
            .credentialsProvider(credentialsProvider)
            .build();

        System.out.println("***** Creating an Amazon DynamoDB table named Movies
with a key named year and a sort key named title.");
        createTable(ddb, tableName);

        System.out.println("***** Loading data into the Amazon DynamoDB table.");
        loadData(ddb, tableName, fileName);

        System.out.println("***** Getting data from the Movie table.");
        getItem(ddb) ;

        System.out.println("***** Putting a record into the Amazon DynamoDB
table.");
        putRecord(ddb);

        System.out.println("***** Updating a record.");
        updateTableItem(ddb, tableName);

        System.out.println("***** Scanning the Amazon DynamoDB table.");
        scanMovies(ddb, tableName);

        System.out.println("***** Querying the Movies released in 2013.");
        queryTable(ddb);

        System.out.println("***** Deleting the Amazon DynamoDB table.");
        deleteDynamoDBTable(ddb, tableName);
        ddb.close();
    }

    // Create a table with a Sort key.
    public static void createTable(DynamoDbClient ddb, String tableName) {

        DynamoDbWaiter dbWaiter = ddb.waiter();
        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

        // Define attributes.
        attributeDefinitions.add(AttributeDefinition.builder()
            .attributeName("year")
            .attributeType("N")
            .build());

        attributeDefinitions.add(AttributeDefinition.builder()
            .attributeName("title")
            .attributeType("S")
            .build());

        ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
        KeySchemaElement key = KeySchemaElement.builder()
            .attributeName("year")
            .keyType(KeyType.HASH)
            .build();

        KeySchemaElement key2 = KeySchemaElement.builder()
            .attributeName("title")
            .keyType(KeyType.RANGE)
            .build();

        // Add KeySchemaElement objects to the list.
    }
}

```

```

        tableKey.add(key);
        tableKey.add(key2);

        CreateTableRequest request = CreateTableRequest.builder()
            .keySchema(tableKey)
            .provisionedThroughput(ProvisionedThroughput.builder()
                .readCapacityUnits(new Long(10))
                .writeCapacityUnits(new Long(10))
                .build())
            .attributeDefinitions(attributeDefinitions)
            .tableName(tableName)
            .build();

        try {
            CreateTableResponse response = ddb.createTable(request);
            DescribeTableRequest tableRequest = DescribeTableRequest.builder()
                .tableName(tableName)
                .build();

            // Wait until the Amazon DynamoDB table is created.
            WaiterResponse<DescribeTableResponse> waiterResponse =
            dbWaiter.waitUntilTableExists(tableRequest);
            waiterResponse.matched().response().ifPresent(System.out::println);
            String newTable = response.tableDescription().tableName();
            System.out.println("The " +newTable + " was successfully created.");

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Query the table.
    public static void queryTable(DynamoDbClient ddb) {
        try {
            DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
            .dynamoDbClient(ddb)
            .build();

            DynamoDbTable<Movies> custTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
            QueryConditional queryConditional = QueryConditional
                .keyEqualTo(Key.builder()
                    .partitionValue(2013)
                    .build());

            // Get items in the table and write out the ID value.
            Iterator<Movies> results =
custTable.query(queryConditional).items().iterator();
            String result="";

            while (results.hasNext()) {
                Movies rec = results.next();
                System.out.println("The title of the movie is "+rec.getTitle());
                System.out.println("The movie information is "+rec.getInfo());
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Scan the table.
    public static void scanMovies(DynamoDbClient ddb, String tableName) {

```

```

        System.out.println("***** Scanning all movies.\n");
        try{
            DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
                .dynamoDbClient(ddb)
                .build();

            DynamoDbTable<Movies> custTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
            Iterator<Movies> results = custTable.scan().items().iterator();
            while (results.hasNext()) {
                Movies rec = results.next();
                System.out.println("The movie title is "+rec.getTitle());
                System.out.println("The movie year is " +rec.getYear());
            }

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    // Load data into the table.
    public static void loadData(DynamoDbClient ddb, String tableName, String
fileName) throws IOException {

        DynamoDbEnhancedClient enhancedClient = DynamoDbEnhancedClient.builder()
            .dynamoDbClient(ddb)
            .build();

        DynamoDbTable<Movies> mappedTable = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));
        JsonParser parser = new JsonFactory().createParser(new File(fileName));
        com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
        Iterator<JsonNode> iter = rootNode.iterator();
        ObjectNode currentNode;
        int t = 0 ;
        while (iter.hasNext()) {

            // Only add 200 Movies to the table.
            if (t == 200)
                break ;
            currentNode = (ObjectNode) iter.next();

            int year = currentNode.path("year").asInt();
            String title = currentNode.path("title").asText();
            String info = currentNode.path("info").toString();

            Movies movies = new Movies();
            movies.setYear(year);
            movies.setTitle(title);
            movies.setInfo(info);

            // Put the data into the Amazon DynamoDB Movie table.
            mappedTable.putItem(movies);
            t++;
        }
    }

    // Update the record to include show only directors.
    public static void updateTableItem(DynamoDbClient ddb, String tableName){

        HashMap<String,AttributeValue> itemKey = new HashMap<>();
        itemKey.put("year", AttributeValue.builder().n("1933").build());
    }
}

```

```

        itemKey.put("title", AttributeValue.builder().s("King Kong").build());

        HashMap<String,AttributeValueUpdate> updatedValues = new HashMap<>();
        updatedValues.put("info", AttributeValueUpdate.builder()
            .value(AttributeValue.builder().s("{\"directors\":[\"Merian C. Cooper
\", \"Ernest B. Schoedsack\"]]}).build())
            .action(AttributeAction.PUT)
            .build());

        UpdateItemRequest request = UpdateItemRequest.builder()
            .tableName(tableName)
            .key(itemKey)
            .attributeUpdates(updatedValues)
            .build();

        try {
            ddb.updateItem(request);
        } catch (ResourceNotFoundException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }

        System.out.println("Item was updated!");
    }

    public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName) {

        DeleteTableRequest request = DeleteTableRequest.builder()
            .tableName(tableName)
            .build();

        try {
            ddb.deleteTable(request);
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
        System.out.println(tableName + " was successfully deleted!");
    }

    public static void putRecord(DynamoDbClient ddb) {

        try {
            DynamoDbEnhancedClient enhancedClient =
DynamoDbEnhancedClient.builder()
            .dynamoDbClient(ddb)
            .build();

            DynamoDbTable<Movies> table = enhancedClient.table("Movies",
TableSchema.fromBean(Movies.class));

            // Populate the Table.
            Movies record = new Movies();
            record.setYear(2020);
            record.setTitle("My Movie2");
            record.setInfo("no info");
            table.putItem(record);

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}

```

```

        System.out.println("Added a new movie to the table.");
    }

    public static void getItem(DynamoDbClient ddb) {

        HashMap<String,AttributeValue> keyToGet = new HashMap<>();
        keyToGet.put("year", AttributeValue.builder()
            .n("1933")
            .build());

        keyToGet.put("title", AttributeValue.builder()
            .s("King Kong")
            .build());

        GetItemRequest request = GetItemRequest.builder()
            .key(keyToGet)
            .tableName("Movies")
            .build();

        try {
            Map<String,AttributeValue> returnedItem = ddb.getItem(request).item();

            if (returnedItem != null) {
                Set<String> keys = returnedItem.keySet();
                System.out.println("Amazon DynamoDB table attributes: \n");

                for (String key1 : keys) {
                    System.out.format("%s: %s\n", key1,
                        returnedItem.get(key1).toString());
                }
            } else {
                System.out.format("No item found with the key %s!\n", "year");
            }
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }
}

```

- For API details, see the following topics in *AWS SDK for Java 2.x API Reference*.
  - [BatchWriteItem](#)
  - [CreateTable](#)
  - [DeleteItem](#)
  - [DeleteTable](#)
  - [DescribeTable](#)
  - [.GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)
  - [UpdateItem](#)

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a DynamoDB client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "REGION"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create a DynamoDB document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "REGION"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Run the scenario.

```
/*
import fs from "fs";
// A practical functional library used to split the data into segments.
import * as R from "ramda";
import { ddbClient } from "../libs/ddbClient.js";
import {
    CreateTableCommand,
    DeleteTableCommand,
} from "@aws-sdk/client-dynamodb";
import { ddbDocClient } from "../libs/ddbDocClient.js";
import {
    PutCommand,
    GetCommand,
    UpdateCommand,
    BatchWriteCommand,
    DeleteCommand,
    ScanCommand,
    QueryCommand,
```

```

} from "@aws-sdk/lib-dynamodb";

if (process.argv.length < 6) {
    console.log(
        "Usage: node dynamodbBasics.js <tableName> <newMovieName> <newMovieYear>
        <existingMovieName> <existingMovieYear> <newMovieRank> <newMoviePlot>\n" +
        "Example: node dynamodbBasics.js newmoviesbrmur newmoviename 2025 200 'MOVIE
        PLOT DETAILS'"
    );
}

// Helper function to delay running the code while the AWS service calls wait for
// responses.
function wait(ms) {
    var start = Date.now();
    var end = start;
    while (end < start + ms) {
        end = Date.now();
    }
}
// Set the parameters.
const tableName = process.argv[2];
const newMovieName = process.argv[3];
const newMovieYear = parseInt(process.argv[4]); // parseInt() converts the string
// into a number.
const existingMovieName = process.argv[5];
const existingMovieYear = parseInt(process.argv[6]);
const newMovieRank = parseInt(process.argv[7]);
const newMoviePlot = process.argv[8];

export const run = async (
    tableName,
    newMovieName,
    newMovieYear,
    existingMovieName,
    existingMovieYear,
    newMovieRank,
    newMoviePlot
) => {
    try {
        console.log("Creating table ...");
        // Set the parameters.
        const params = {
            AttributeDefinitions: [
                {
                    AttributeName: "title",
                    AttributeType: "S",
                },
                {
                    AttributeName: "year",
                    AttributeType: "N",
                },
            ],
            KeySchema: [
                {
                    AttributeName: "title",
                    KeyType: "HASH",
                },
                {
                    AttributeName: "year",
                    KeyType: "RANGE",
                },
            ],
            ProvisionedThroughput: {
                ReadCapacityUnits: 5,
                WriteCapacityUnits: 5,
            }
        };
        await dynamoDB.createTable(params).promise();
        console.log(`Table ${tableName} created successfully!`);
    } catch (err) {
        console.error(`Error creating table ${tableName}: ${err}`);
    }
};

```

```

    },
    TableName: tableName,
};

const data = await ddbClient.send(new CreateTableCommand(params));
console.log("Waiting for table to be created...");
wait(10000);
console.log(
    "Table created. Table name is ",
    data.TableDescription.TableName
);
try {
    const params = {
        TableName: tableName,
        Item: {
            title: newMovieName,
            year: newMovieYear,
        },
    };
    console.log("Adding movie...");
    const data = await ddbDocClient.send(new PutCommand(params));
    console.log("Success - single movie added.");
    try {
        // Before you run this example, download 'movies.json' from https://
docs.aws.amazon.com/amazondynamodb/latest/developerguide/GettingStarted.Js.02.html,
        // and put it in the same folder as the example.
        // Get the movie data parse to convert into a JSON object.
        const allMovies = JSON.parse(fs.readFileSync("moviedata.json", "utf8"));
        // Split the table into segments of 25.
        const dataSegments = R.splitEvery(25, allMovies);
        // Loop batch write operation 10 times to upload 250 items.
        console.log("Writing movies in batch to table...");
        for (let i = 0; i < 10; i++) {
            const segment = dataSegments[i];
            for (let j = 0; j < 25; j++) {
                const params = {
                    RequestItems: [
                        [tableName]: [
                            {
                                // Destination Amazon DynamoDB table name.
                                PutRequest: {
                                    Item: {
                                        year: segment[j].year,
                                        title: segment[j].title,
                                        info: segment[j].info,
                                    },
                                },
                            ],
                        ],
                    ],
                };
                const data = ddbDocClient.send(new BatchWriteCommand(params));
            }
        }
        wait(20000);
        console.log("Success, movies written to table.");
        try {
            const params = {
                TableName: tableName,
                Key: {
                    title: existingMovieName,
                    year: existingMovieYear,
                },
                // Define expressions for the new or updated attributes.
                ProjectionExpression: "#r",
                ExpressionAttributeNames: { "#r": "rank" },
                UpdateExpression: "set info.plot = :p, info.#r = :r",
            };
        }
    }
}

```

```

        ExpressionAttributeValues: {
            ":p": newMoviePlot,
            ":r": newMovieRank,
        },
        ReturnValue: "ALL_NEW",
    };
    console.log("Updating a single movie...");
    const data = await ddbClient.send(new UpdateCommand(params));
    console.log("Success - movie updated.");
    try {
        console.log("Getting movie....");
        const params = {
            TableName: tableName,
            Key: {
                title: existingMovieName,
                year: existingMovieYear,
            },
        };
        const data = await ddbDocClient.send(new GetCommand(params));
        console.log("Success getting item. Item details :", data.Item);
        try {
            const params = {
                TableName: tableName,
                Key: {
                    title: newMovieName,
                    year: newMovieYear,
                },
            };
            const data = await ddbDocClient.send(new DeleteCommand(params));
            console.log("Success - movie deleted.");
            try {
                console.log("Scanning table....");
                const params = {
                    TableName: tableName,
                    ProjectionExpression: "#r, #y, title",
                    ExpressionAttributeNames: { "#r": "rank", "#y": "year" },
                    FilterExpression: "title = :t and #y = :y and info.#r = :r",
                    ExpressionAttributeValues: {
                        ":r": newMovieRank,
                        ":y": existingMovieYear,
                        ":t": existingMovieName,
                    },
                };
                const data = await ddbClient.send(new ScanCommand(params));
                // Loop through and parse the response.
                for (let i = 0; i < data.Items.length; i++) {
                    console.log(
                        "Scan successful. Items with rank of " +
                        newMovieRank +
                        " include\n" +
                        "Year = " +
                        data.Items[i].year +
                        " Title = " +
                        data.Items[i].title
                    );
                }
            } catch {
                const params = {
                    ExpressionAttributeNames: { "#r": "rank", "#y": "year" },
                    ProjectionExpression: "#r, #y, title",
                    TableName: tableName,
                    UpdateExpression: "set #r = :r, title = :t, #y = :y",
                    ExpressionAttributeValues: {
                        ":t": existingMovieName,
                        ":y": existingMovieYear,
                    },
                };
            }
        }
    }
}

```

```

        ":r": newMovieRank,
    },
    KeyConditionExpression: "title = :t and #y = :y",
    FilterExpression: "info.#r = :r",
};

console.log("Querying table...");
const data = await ddbDocClient.send(
    new QueryCommand(params)
);
// Loop through and parse the response.
for (let i = 0; i < data.Items.length; i++) {
    console.log(
        "Query successful. Items with rank of " +
        newMovieRank +
        " include\n" +
        "Year = " +
        data.Items[i].year +
        " Title = " +
        data.Items[i].title
    );
}
try {
    console.log("Deleting a movie...");
    const params = {
        TableName: tableName,
        Key: {
            title: existingMovieName,
            year: existingMovieYear,
        },
    };
    const data = await ddbDocClient.send(
        new DeleteCommand(params)
    );
    console.log("Success - item deleted");
    try {
        console.log("Deleting the table...");
        const params = {
            TableName: tableName,
        };
        const data = await ddbDocClient.send(
            new DeleteTableCommand(params)
        );
        console.log("Success, table deleted.");
        return "Run successfully"; // For unit tests.
    } catch (err) {
        console.log("Error deleting table. ", err);
    }
} catch (err) {
    console.log("Error deleting movie. ", err);
}
} catch (err) {
    console.log("Error querying table. ", err);
}
} catch (err) {
    console.log("Error scanning table. ", err);
}
} catch (err) {
    console.log("Error deleting movie. ", err);
}
} catch (err) {
    console.log("Error getting item. ", err);
}
} catch (err) {
    console.log("Error adding movies by batch. ", err);
}
}

```

```
        } catch (err) {
            console.log("Error updating item. ", err);
        }
    } catch (err) {
        console.log("Error adding a single item. ", err);
    }
} catch (err) {
    console.log("Error creating table. ", err);
}
};

run(
    tableName,
    newMovieName,
    newMovieYear,
    existingMovieName,
    existingMovieYear,
    newMovieRank,
    newMoviePlot
);
```

- For API details, see the following topics in *AWS SDK for JavaScript API Reference*.
  - [BatchWriteItem](#)
  - [CreateTable](#)
  - [DeleteItem](#)
  - [DeleteTable](#)
  - [DescribeTable](#)
  - [GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)
  - [UpdateItem](#)

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a DynamoDB table.

```
suspend fun createScenarioTable(tableNameVal: String, key: String) {

    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
```

```

        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        println("The table was successfully created
        ${response.tableDescription?.tableArn}")
    }
}

```

Create a helper function to download and extract the sample JSON file.

```

// Load data into the table.
suspend fun loadData(tableName: String, fileName: String) {

    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode

    var t = 0
    while (iter.hasNext()) {

        if (t == 50)
            break

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()
        putMovie(tableName, year, title, info)
        t++
    }
}

suspend fun putMovie(
    tableNameVal: String,
    year: Int,
    title: String,
    info: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()

```

```

    val strVal = year.toString()
    // Add all content to the table.
    itemValues["year"] = AttributeValue.N(strVal)
    itemValues["title"] = AttributeValue.S(title)
    itemValues["info"] = AttributeValue.S(info)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println("Added $title to the Movie table.")
    }
}

```

Get an item from a table.

```

suspend fun getMovie(tableNameVal: String, keyName: String, keyVal: String) {

    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.N(keyVal)
    keyToGet["title"] = AttributeValue.S("King Kong")

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}

```

Full example.

```

suspend fun main(args: Array<String>) {

    val usage = """
        Usage:
        <fileName>

        Where:
        fileName - The path to the moviedata.json you can download from the
        Amazon DynamoDB Developer Guide.
    """

    if (args.size != 1) {
        println(usage)
        exitProcess(1)
    }

    // Get the moviedata.json from the Amazon DynamoDB Developer Guide.
    val tableName = "Movies"
    val fileName = args[0]
}

```

```

    val partitionAlias = "#a"

    println("Creating an Amazon DynamoDB table named Movies with a key named id and
a sort key named title.")
    createScenarioTable(tableName, "year")
    loadData(tableName, fileName)
    getMovie(tableName, "year", "1933")
    scanMovies(tableName)
    val count = queryMovieTable(tableName, "year", partitionAlias)
    println("There are $count Movies released in 2013.")
    deleteIssuesTable(tableName)
}

suspend fun createScenarioTable(tableNameVal: String, key: String) {

    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->

        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        println("The table was successfully created
${response.tableDescription?.tableArn}")
    }
}

// Load data into the table.
suspend fun loadData(tableName: String, fileName: String) {

    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode
}

```

```

var t = 0
while (iter.hasNext()) {

    if (t == 50)
        break

    currentNode = iter.next() as ObjectNode
    val year = currentNode.path("year").asInt()
    val title = currentNode.path("title").asText()
    val info = currentNode.path("info").toString()
    putMovie(tableName, year, title, info)
    t++
}
}

suspend fun putMovie(
    tableNameVal: String,
    year: Int,
    title: String,
    info: String
) {
    val itemValues = mutableMapOf<String, AttributeValue>()
    val strVal = year.toString()
    // Add all content to the table.
    itemValues["year"] = AttributeValue.N(strVal)
    itemValues["title"] = AttributeValue.S(title)
    itemValues["info"] = AttributeValue.S(info)

    val request = PutItemRequest {
        tableName = tableNameVal
        item = itemValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        ddb.putItem(request)
        println("Added $title to the Movie table.")
    }
}

suspend fun getMovie(tableNameVal: String, keyName: String, keyVal: String) {

    val keyToGet = mutableMapOf<String, AttributeValue>()
    keyToGet[keyName] = AttributeValue.N(keyVal)
    keyToGet["title"] = AttributeValue.S("King Kong")

    val request = GetItemRequest {
        key = keyToGet
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val returnedItem = ddb.getItem(request)
        val numbersMap = returnedItem.item
        numbersMap?.forEach { key1 ->
            println(key1.key)
            println(key1.value)
        }
    }
}

suspend fun deleteTable(tableNameVal: String) {

    val request = DeleteTableRequest {
        tableName = tableNameVal
    }
}

```

```

        DynamoDbClient { region = "us-east-1" }.use { ddb ->
            ddb.deleteTable(request)
            println("$tableNameVal was deleted")
        }
    }

suspend fun queryMovieTable(
    tableNameVal: String,
    partitionKeyName: String,
    partitionAlias: String
): Int {

    val attrNameAlias = mutableMapOf<String, String>()
    attrNameAlias[partitionAlias] = "year"

    // Set up mapping of the partition name with the value.
    val attrValues = mutableMapOf<String, AttributeValue>()
    attrValues[":$partitionKeyName"] = AttributeValue.N("2013")

    val request = QueryRequest {
        tableName = tableNameVal
        keyConditionExpression = "$partitionAlias = :$partitionKeyName"
        expressionAttributeNames = attrNameAlias
        this.expressionAttributeValues = attrValues
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.query(request)
        return response.count
    }
}

suspend fun scanMovies(tableNameVal: String) {

    val request = ScanRequest {
        tableName = tableNameVal
    }

    DynamoDbClient { region = "us-east-1" }.use { ddb ->
        val response = ddb.scan(request)
        response.items?.forEach { item ->
            item.keys.forEach { key ->
                println("The key name is $key\n")
                println("The value is ${item[key]}")
            }
        }
    }
}

```

- For API details, see the following topics in *AWS SDK for Kotlin API reference*.

- [BatchWriteItem](#)

- [CreateTable](#)

- [DeleteItem](#)

- [DeleteTable](#)

- [DescribeTable](#)

- [.GetItem](#)

- [PutItem](#)

- [Query](#)

- [Scan](#)

- [UpdateItem](#)

PHP

**SDK for PHP**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
namespace DynamoDb\Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;
use DynamoDb\DynamoDBService;

class GettingStartedWithDynamoDB
{
    public function run()
    {
        echo("-----\n");
        print("Welcome to the Amazon DynamoDB getting started demo using PHP!\n");
        echo("-----\n");

        $uuid = uniqid();
        $service = new DynamoDBService();

        $tableName = "ddb_demo_table_{$uuid}";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitFor("TableExists", ['TableName' =>
$tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }

        $service->putItem([
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
            'TableName' => $tableName,
        ]);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
```

```

        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
            $plot = testable_readline("Plot summary: ");
        }
        $key = [
            'Item' => [
                'title' => [
                    'S' => $movieName,
                ],
                'year' => [
                    'N' => $movieYear,
                ],
            ],
        ];
        $attributes = ["rating" =>
            [
                'AttributeName' => 'rating',
                'AttributeType' => 'N',
                'Value' => $rating,
            ],
            'plot' => [
                'AttributeName' => 'plot',
                'AttributeType' => 'S',
                'Value' => $plot,
            ]
        ];
        $service->updateItemAttributesByKey($tableName, $key, $attributes);
        echo "Movie added and updated.";

        $batch = json_decode(loadMovieData());
        $limit = 0;
        $service->writeBatch($tableName, $batch);

        $movie = $service->getItemByKey($tableName, $key);
        echo "\nThe movie {$movie['Item']['title']['S']} was released in
{$movie['Item']['year']['N']}\n";
        echo "What rating would you like to give {$movie['Item']['title']['S']}?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 || $rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        $service->updateItemAttributeByKey($tableName, $key, 'rating', 'N', $rating);

        $movie = $service->getItemByKey($tableName, $key);
        echo "Ok, you have rated {$movie['Item']['title']['S']} as a
{$movie['Item']['rating']['N']}\n";

        $service->deleteItemByKey($tableName, $key);
        echo "But, bad news, this was a trap. That movie has now been deleted
because of your rating...harsh.\n";

        echo "That's okay though. The book was better. Now, for something lighter,
in what year were you born?\n";
        $birthYear = "not a number";
        while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
            $birthYear = testable_readline("Birth year: ");
        }
    }

```

```

$birthKey = [
    'Key' => [
        'year' => [
            'N' => "$birthYear",
        ],
    ],
];
$result = $service->query($tableName, $birthKey);
$marshal = new Marshaler();
echo "Here are the movies in our collection released the year you were
born:\n";
$oops = "Oops! There were no movies released in that year (that we know
of).\n";
$display = "";
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    $display .= $movie['title'] . "\n";
}
echo ($display) ?: $oops;

$yearsKey = [
    'Key' => [
        'year' => [
            'N' => [
                'minRange' => 1990,
                'maxRange' => 1999,
            ],
        ],
    ],
];
$filter = "year between 1990 and 1999";
echo "\nHere's a list of all the movies released in the 90s:\n";
$result = $service->scan($tableName, $yearsKey, $filter);
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    echo $movie['title'] . "\n";
}

echo "\nCleaning up this demo by deleting table $tableName...\n";
$service->deleteTable($tableName);
}
}

```

- For API details, see the following topics in *AWS SDK for PHP API Reference*.
  - [BatchWriteItem](#)
  - [CreateTable](#)
  - [DeleteItem](#)
  - [DeleteTable](#)
  - [DescribeTable](#)
  - [.GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)
  - [UpdateItem](#)

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a class that encapsulates a DynamoDB table.

```
from decimal import Decimal
from io import BytesIO
import json
import logging
import os
from pprint import pprint
import requests
from zipfile import ZipFile
import boto3
from boto3.dynamodb.conditions import Key
from botocore.exceptions import ClientError
from question import Question

logger = logging.getLogger(__name__)

class Movies:
    """Encapsulates an Amazon DynamoDB table of movie data."""
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource
        self.table = None

    def exists(self, table_name):
        """
        Determines whether a table exists. As a side effect, stores the table in
        a member variable.

        :param table_name: The name of the table to check.
        :return: True when the table exists; otherwise, False.
        """
        try:
            table = self.dyn_resource.Table(table_name)
            table.load()
            exists = True
        except ClientError as err:
            if err.response['Error']['Code'] == 'ResourceNotFoundException':
                exists = False
            else:
                logger.error(
                    "Couldn't check for existence of %s. Here's why: %s: %s",
                    table_name,
                    err.response['Error']['Code'], err.response['Error']
                ['Message'])
                raise
        else:
            self.table = table
        return exists

    def create_table(self, table_name):
        """
        Creates an Amazon DynamoDB table that can be used to store movie data.
        The table uses the release year of the movie as the partition key and the
        title as the sort key.
        """
        pass
```

```

:param table_name: The name of the table to create.
:return: The newly created table.
"""
try:
    self.table = self.dyn_resource.create_table(
        TableName=table_name,
        KeySchema=[
            {'AttributeName': 'year', 'KeyType': 'HASH'}, # Partition key
            {'AttributeName': 'title', 'KeyType': 'RANGE'} # Sort key
        ],
        AttributeDefinitions=[
            {'AttributeName': 'year', 'AttributeType': 'N'},
            {'AttributeName': 'title', 'AttributeType': 'S'}
        ],
        ProvisionedThroughput={'ReadCapacityUnits': 10,
                               'WriteCapacityUnits': 10})
    self.table.wait_until_exists()
except ClientError as err:
    logger.error(
        "Couldn't create table %s. Here's why: %s: %s",
        err.response['Error']['Code'], err.response['Error']['Message'])
    raise
else:
    return self.table

def list_tables(self):
    """
    Lists the Amazon DynamoDB tables for the current account.

    :return: The list of tables.
    """
try:
    tables = []
    for table in self.dyn_resource.tables.all():
        print(table.name)
        tables.append(table)
except ClientError as err:
    logger.error(
        "Couldn't list tables. Here's why: %s: %s",
        err.response['Error']['Code'], err.response['Error']['Message'])
    raise
else:
    return tables

def write_batch(self, movies):
    """
    Fills an Amazon DynamoDB table with the specified data, using the Boto3
    Table.batch_writer() function to put the items in the table.
    Inside the context manager, Table.batch_writer builds a list of
    requests. On exiting the context manager, Table.batch_writer starts sending
    batches of write requests to Amazon DynamoDB and automatically
    handles chunking, buffering, and retrying.

    :param movies: The data to put in the table. Each item must contain at
    least
                    the keys required by the schema that was specified when the
                    table was created.
    """
try:
    with self.table.batch_writer() as writer:
        for movie in movies:
            writer.put_item(Item=movie)
except ClientError as err:
    logger.error(
        "Couldn't load data into table %s. Here's why: %s: %s",
        self.table.name,

```

```

        err.response['Error']['Code'], err.response['Error']['Message'])
        raise

    def add_movie(self, title, year, plot, rating):
        """
        Adds a movie to the table.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :param plot: The plot summary of the movie.
        :param rating: The quality rating of the movie.
        """
        try:
            self.table.put_item(
                Item={
                    'year': year,
                    'title': title,
                    'info': {'plot': plot, 'rating': Decimal(str(rating))}})
        except ClientError as err:
            logger.error(
                "Couldn't add movie %s to table %s. Here's why: %s: %s",
                title, self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise

    def get_movie(self, title, year):
        """
        Gets movie data from the table for a specific movie.

        :param title: The title of the movie.
        :param year: The release year of the movie.
        :return: The data about the requested movie.
        """
        try:
            response = self.table.get_item(Key={'year': year, 'title': title})
        except ClientError as err:
            logger.error(
                "Couldn't get movie %s from table %s. Here's why: %s: %s",
                title, self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])
            raise
        else:
            return response['Item']

    def update_movie(self, title, year, rating, plot):
        """
        Updates rating and plot data for a movie in the table.

        :param title: The title of the movie to update.
        :param year: The release year of the movie to update.
        :param rating: The updated rating to give the movie.
        :param plot: The updated plot summary to give the movie.
        :return: The fields that were updated, with their new values.
        """
        try:
            response = self.table.update_item(
                Key={'year': year, 'title': title},
                UpdateExpression="set info.rating=:r, info.plot=:p",
                ExpressionAttributeValues={
                    ':r': Decimal(str(rating)), ':p': plot},
                ReturnValues="UPDATED_NEW")
        except ClientError as err:
            logger.error(
                "Couldn't update movie %s in table %s. Here's why: %s: %s",
                title, self.table.name,
                err.response['Error']['Code'], err.response['Error']['Message'])

```

```

        raise
    else:
        return response['Attributes']

def query_movies(self, year):
    """
    Queries for movies that were released in the specified year.

    :param year: The year to query.
    :return: The list of movies that were released in the specified year.
    """
    try:
        response =
self.table.query(KeyConditionExpression=Key('year').eq(year))
    except ClientError as err:
        logger.error(
            "Couldn't query for movies released in %s. Here's why: %s: %s",
year,
            err.response['Error']['Code'], err.response['Error']['Message'])
        raise
    else:
        return response['Items']

def scan_movies(self, year_range):
    """
    Scans for movies that were released in a range of years.
    Uses a projection expression to return a subset of data for each movie.

    :param year_range: The range of years to retrieve.
    :return: The list of movies released in the specified years.
    """
    movies = []
    scan_kwargs = {
        'FilterExpression': Key('year').between(year_range['first'],
year_range['second']),
        'ProjectionExpression': "#yr, title, info.rating",
        'ExpressionAttributeNames': {"#yr": "year"}}
    try:
        done = False
        start_key = None
        while not done:
            if start_key:
                scan_kwargs['ExclusiveStartKey'] = start_key
            response = self.table.scan(**scan_kwargs)
            movies.extend(response.get('Items', []))
            start_key = response.get('LastEvaluatedKey', None)
            done = start_key is None
    except ClientError as err:
        logger.error(
            "Couldn't scan for movies. Here's why: %s: %s",
            err.response['Error']['Code'], err.response['Error']['Message'])
        raise

    return movies

def delete_movie(self, title, year):
    """
    Deletes a movie from the table.

    :param title: The title of the movie to delete.
    :param year: The release year of the movie to delete.
    """
    try:
        self.table.delete_item(Key={'year': year, 'title': title})
    except ClientError as err:
        logger.error(

```

```

        "Couldn't delete movie %s. Here's why: %s: %s", title,
        err.response['Error']['Code'], err.response['Error']['Message'])
    raise

def delete_table(self):
    """
    Deletes the table.
    """
    try:
        self.table.delete()
        self.table = None
    except ClientError as err:
        logger.error(
            "Couldn't delete table. Here's why: %s: %s",
            err.response['Error']['Code'], err.response['Error']['Message'])
    raise

```

Create a helper function to download and extract the sample JSON file.

```

def get_sample_movie_data(movie_file_name):
    """
    Gets sample movie data, either from a local file or by first downloading it
    from
    the Amazon DynamoDB developer guide.

    :param movie_file_name: The local file name where the movie data is stored in
    JSON format.
    :return: The movie data as a dict.
    """
    if not os.path.isfile(movie_file_name):
        print(f"Downloading {movie_file_name}...")
        movie_content = requests.get(
            'https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
samples/moviedata.zip')
        movie_zip = ZipFile(BytesIO(movie_content.content))
        movie_zip.extractall()

    try:
        with open(movie_file_name) as movie_file:
            movie_data = json.load(movie_file, parse_float=Decimal)
    except FileNotFoundError:
        print(f"File {movie_file_name} not found. You must first download the file
to "
              "run this demo. See the README for instructions.")
        raise
    else:
        # The sample file lists over 4000 movies, return only the first 250.
        return movie_data[:250]

```

Run an interactive scenario to create the table and perform actions on it.

```

def run_scenario(table_name, movie_file_name, dyn_resource):
    logging.basicConfig(level=logging.INFO, format='%(levelname)s: %(message)s')

    print('*'*88)
    print("Welcome to the Amazon DynamoDB getting started demo.")
    print('*'*88)

    movies = Movies(dyn_resource)
    movies_exists = movies.exists(table_name)
    if not movies_exists:

```

```

        print(f"\nCreating table {table_name}...")
        movies.create_table(table_name)
        print(f"\nCreated table {movies.table.name}.")\n\n

my_movie = Question.ask_questions([
    Question('title', "Enter the title of a movie you want to add to the table."),
    Question('year', "What year was it released?", Question.is_int),
    Question(
        'rating', "On a scale of 1 - 10, how do you rate it?",
        Question.is_float, Question.in_range(1, 10)),
    Question('plot', "Summarize the plot for me:")
])
movies.add_movie(**my_movie)
print(f"\nAdded '{my_movie['title']}' to '{movies.table.name}'")
print('*'*88)

movie_update = Question.ask_questions([
    Question(
        'rating',
        f"\nLet's update your movie.\nYou rated it {my_movie['rating']}, what
new "
        f"rating would you give it?", Question.is_float, Question.in_range(1,
10)),
    Question(
        'plot',
        f"You summarized the plot as '{my_movie['plot']}'.\nWhat would you say
now?")]
)
my_movie.update(movie_update)
updated = movies.update_movie(**my_movie)
print(f"\nUpdated '{my_movie['title']}' with new attributes:")
pprint(updated)
print('*'*88)

if not movies_exists:
    movie_data = get_sample_movie_data(movie_file_name)
    print(f"\nReading data from '{movie_file_name}' into your table.")
    movies.write_batch(movie_data)
    print(f"\nWrote {len(movie_data)} movies into {movies.table.name}.")
print('*'*88)

title = "The Lord of the Rings: The Fellowship of the Ring"
if Question.ask_question(
        f"Let's move on...do you want to get info about '{title}'? (y/n) ",
        Question.is_yesno):
    movie = movies.get_movie(title, 2001)
    print("\nHere's what I found:")
    pprint(movie)
print('*'*88)

ask_for_year = True
while ask_for_year:
    release_year = Question.ask_question(
        f"\nLet's get a list of movies released in a given year. Enter a year
between "
        f"1972 and 2018:", Question.is_int, Question.in_range(1972, 2018))
    releases = movies.query_movies(release_year)
    if releases:
        print(f"There were {len(releases)} movies released in {release_year}:")
        for release in releases:
            print(f"\t{release['title']}")
        ask_for_year = False
    else:
        print(f"I don't know about any movies released in {release_year}!")
        ask_for_year = Question.ask_question("Try another year? (y/n) ",
Question.is_yesno)

```

```

print('*88)

years = Question.ask_questions([
    Question(
        'first',
        f"\nNow let's scan for movies released in a range of years. Enter a
year: ",
        Question.is_int, Question.in_range(1972, 2018)),
    Question(
        'second', "Now enter another year: ",
        Question.is_int, Question.in_range(1972, 2018)))
releases = movies.scan_movies(years)
if releases:
    count = Question.ask_question(
        f"\nFound {len(releases)} movies. How many do you want to see? ",
        Question.is_int, Question.in_range(1, len(releases)))
    print(f"\nHere are your {count} movies:\n")
    pprint(releases[:count])
else:
    print(f"I don't know about any movies released between {years['first']} "
          f"and {years['second']}.")

print('*88)

if Question.ask_question(
    f"\nLet's remove your movie from the table. Do you want to remove "
    f"'{my_movie['title']}'? (y/n)", Question.is_yesno):
    movies.delete_movie(my_movie['title'], my_movie['year'])
    print(f"\nRemoved '{my_movie['title']}' from the table.")
print('*88)

if Question.ask_question(f"\nDelete the table? (y/n)", Question.is_yesno):
    movies.delete_table()
    print(f"Deleted {table_name}.")
else:
    print("Don't forget to delete the table when you're done or you might incur
"
      "charges on your account.")

print("\nThanks for watching!")
print('*88)

if __name__ == '__main__':
    try:
        run_scenario(
            'doc-example-table-movies', 'moviedata.json',
            boto3.resource('dynamodb'))
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")

```

This scenario uses the following helper class to ask questions at a command prompt.

```

class Question:
    """
    A helper class to ask questions at a command prompt and validate and convert
    the answers.
    """
    def __init__(self, key, question, *validators):
        """
        :param key: The key that is used for storing the answer in a dict, when
                   multiple questions are asked in a set.
        :param question: The question to ask.
        :param validators: The answer is passed through the list of validators
        until

```

```

the one fails or they all pass. Validators may also convert
answer to another form, such as from a str to an int.

"""
self.key = key
self.question = question
self.validators = Question.non_empty, *validators

@staticmethod
def ask_questions(questions):
    """
    Asks a set of questions and stores the answers in a dict.

    :param questions: The list of questions to ask.
    :return: A dict of answers.
    """
    answers = {}
    for question in questions:
        answers[question.key] = Question.ask_question(
            question.question, *question.validators)
    return answers

@staticmethod
def ask_question(question, *validators):
    """
    Asks a single question and validates it against a list of validators.
    When an answer fails validation, the complaint is printed and the question
    is asked again.

    :param question: The question to ask.
    :param validators: The list of validators that the answer must pass.
    :return: The answer, converted to its final form by the validators.
    """
    answer = None
    while answer is None:
        answer = input(question)
        for validator in validators:
            answer, complaint = validator(answer)
            if answer is None:
                print(complaint)
                break
    return answer

@staticmethod
def non_empty(answer):
    """
    Validates that the answer is not empty.
    :return: The non-empty answer, or None.
    """
    return answer if answer != '' else None, "I need an answer. Please?"

@staticmethod
def is_yesno(answer):
    """
    Validates a yes/no answer.
    :return: True when the answer is 'y'; otherwise, False.
    """
    return answer.lower() == 'y', ""

@staticmethod
def is_int(answer):
    """
    Validates that the answer can be converted to an int.
    :return: The int answer; otherwise, None.
    """
    try:

```

```

        int_answer = int(answer)
    except ValueError:
        int_answer = None
    return int_answer, f"{answer} must be a valid integer."

    @staticmethod
    def is_letter(answer):
        """
        Validates that the answer is a letter.
        :return The letter answer, converted to uppercase; otherwise, None.
        """
        return answer.upper() if answer.isalpha() else None, f"{answer} must be a single letter."

    @staticmethod
    def is_float(answer):
        """
        Validate that the answer can be converted to a float.
        :return The float answer; otherwise, None.
        """
        try:
            float_answer = float(answer)
        except ValueError:
            float_answer = None
        return float_answer, f"{answer} must be a valid float."

    @staticmethod
    def in_range(lower, upper):
        """
        Validate that the answer is within a range. The answer must be of a type
        that can be compared to the lower and upper bounds.
        :return: The answer, if it is within the range; otherwise, None.
        """
        def _validate(answer):
            return (
                answer if lower <= answer <= upper else None,
                f"{answer} must be between {lower} and {upper}.")
        return _validate

```

- For API details, see the following topics in *AWS SDK for Python (Boto3) API Reference*.
  - [BatchWriteItem](#)
  - [CreateTable](#)
  - [DeleteItem](#)
  - [DeleteTable](#)
  - [DescribeTable](#)
  - [GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)
  - [UpdateItem](#)

## Ruby

### SDK for Ruby

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a class that encapsulates a DynamoDB table.

```

require "aws-sdk-dynamodb"
require "json"
require "open-uri"
require "pp"
require "zip"
require_relative "question"

# Encapsulates an Amazon DynamoDB table of movie data.
class Movies
    attr_reader :dynamo_resource
    attr_reader :table

    def initialize(dynamo_resource)
        @dynamo_resource = dynamo_resource
    end

    # Determines whether a table exists. As a side effect, stores the table in
    # a member variable.
    #
    # @param table_name [String] The name of the table to check.
    # @return [Boolean] True when the table exists; otherwise, False.
    def exists?(table_name)
        table = Aws::DynamoDB::Table.new(table_name)
        table.load
        @table = table
        rescue Aws::DynamoDB::Errors::ResourceNotFoundException
            puts("Table #{table_name} doesn't exist. Let's create it.")
            false
        rescue Aws::Errors::ServiceError => e
            puts("Couldn't check for existence of #{table_name}. Here's why:")
            puts("\t#{e.code}: #{e.message}")
            raise
        else
            !@table.nil?
        end

        # Creates an Amazon DynamoDB table that can be used to store movie data.
        # The table uses the release year of the movie as the partition key and the
        # title as the sort key.
        #
        # @param table_name [String] The name of the table to create.
        # @return [Aws::DynamoDB::Table] The newly created table.
        def create_table(table_name)
            @table = @dynamo_resource.create_table(
                table_name: table_name,
                key_schema: [
                    {attribute_name: "year", key_type: "HASH"}, # Partition key
                    {attribute_name: "title", key_type: "RANGE"} # Sort key
                ],
                attribute_definitions: [
                    {attribute_name: "year", attribute_type: "N"},
                    {attribute_name: "title", attribute_type: "S"}
                ],
                provisioned_throughput: {read_capacity_units: 10, write_capacity_units: 10})
            @dynamo_resource.client.wait_until(:table_exists, table_name: table_name)
            rescue Aws::Errors::ServiceError => e
                puts("Couldn't create table #{table_name}. Here's why:")
                puts("\t#{e.code}: #{e.message}")
                raise
            else
                @table
            end
        end
    end
end

```

```

# Fills an Amazon DynamoDB table with the specified data. Items are sent in
# batches of 25 until all items are written.
#
# @param movies [Enumerable] The data to put in the table. Each item must contain
at least
#                               the keys required by the schema that was specified
when the
#                               table was created.
def write_batch(movies)
  index = 0
  slice_size = 25
  while index < movies.length
    movie_items = []
    movies[index, slice_size].each do |movie|
      movie_items.append({put_request: { item: movie }})
    end
    @dynamo_resource.batch_write_item({request_items: { @table.name =>
movie_items }})
    index += slice_size
  end
rescue Aws::Errors::ServiceError => e
  puts(
    "Couldn't load data into table #{@table.name}. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
end

# Adds a movie to the table.
#
# @param title [String] The title of the movie.
# @param year [Integer] The release year of the movie.
# @param plot [String] The plot summary of the movie.
# @param rating [Float] The quality rating of the movie.
def add_movie(title:, year:, plot:, rating:)
  @table.put_item(
    item: {
      "year" => year,
      "title" => title,
      "info" => {"plot" => plot, "rating" => rating}})
rescue Aws::Errors::ServiceError => e
  puts("Couldn't add movie #{title} to table #{@table.name}. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
end

# Gets movie data from the table for a specific movie.
#
# @param title [String] The title of the movie.
# @param year [Integer] The release year of the movie.
# @return [Hash] The data about the requested movie.
def get_movie(title, year)
  response = @table.get_item(key: {"year" => year, "title" => title})
rescue Aws::Errors::ServiceError => e
  puts("Couldn't get movie #{title} from table #{@table.name}. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
else
  response.item
end

# Updates rating and plot data for a movie in the table.
#
# @param title [String] The title of the movie to update.
# @param year [Int] The release year of the movie to update.
# @param rating [Float] The updated rating to give the movie.
# @param plot [String] The updated plot summary to give the movie.

```

```

# @return [Hash] The fields that were updated, with their new values.
def update_movie(title:, year:, rating:, plot:)
    response = @table.update_item(
        key: {"year" => year, "title" => title},
        update_expression: "set info.rating=:r, info.plot=:p",
        expression_attribute_values: { ":r" => rating, ":p" => plot },
        return_values: "UPDATED_NEW")
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't update movie #{title} in table #{@table.name}. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        response.attributes
    end

# Queries for movies that were released in the specified year.
#
# @param year [Integer] The year to query.
# @return [Array] The list of movies that were released in the specified year.
def query_movies(year)
    response = @table.query(
        key_condition_expression: "#yr = :year",
        expression_attribute_names: {"#yr" => "year"},
        expression_attribute_values: {":year" => year})
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't query for movies released in #{year}. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        response.items
    end

# Scans for movies that were released in a range of years.
# Uses a projection expression to return a subset of data for each movie.
#
# @param year_range [Hash] The range of years to retrieve.
# @return [Array] The list of movies released in the specified years.
def scan_movies(year_range)
    movies = []
    scan_hash = {
        filter_expression: "#yr between :start_yr and :end_yr",
        projection_expression: "#yr, title, info.rating",
        expression_attribute_names: {"#yr" => "year"},
        expression_attribute_values: {
            ":start_yr" => year_range[:start], ":end_yr" => year_range[:end]}
    }
    done = false
    start_key = nil
    until done
        scan_hash[:exclusive_start_key] = start_key unless start_key.nil?
        response = @table.scan(scan_hash)
        movies.concat(response.items) unless response.items.nil?
        start_key = response.last_evaluated_key
        done = start_key.nil?
    end
    rescue Aws::Errors::ServiceError => e
        puts("Couldn't scan for movies. Here's why:")
        puts("\t#{e.code}: #{e.message}")
        raise
    else
        movies
    end

# Deletes a movie from the table.
#
# @param title [String] The title of the movie to delete.

```

```

# @param year [Integer] The release year of the movie to delete.
def delete_movie(title, year)
  @table.delete_item(key: {"year" => year, "title" => title})
rescue Aws::Errors::ServiceError => e
  puts("Couldn't delete movie #{title}. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
end

# Deletes the table.
def delete_table
  @table.delete
  @table = nil
rescue Aws::Errors::ServiceError => e
  puts("Couldn't delete table. Here's why:")
  puts("\t#{e.code}: #{e.message}")
  raise
end
end

```

Create a helper function to download and extract the sample JSON file.

```

# Gets sample movie data, either from a local file or by first downloading it from
# the Amazon DynamoDB Developer Guide.
#
# @param movie_file_name [String] The local file name where the movie data is
# stored in JSON format.
# @return [Hash] The movie data as a Hash.
def get_sample_movie_data(movie_file_name)
  if !File.file?(movie_file_name)
    puts("Downloading #{movie_file_name}...")
    movie_content = URI.open(
      "https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/samples/
moviedata.zip"
    )
    movie_json = ""
    Zip::File.open_buffer(movie_content) do |zip|
      zip.each do |entry|
        movie_json = entry.get_input_stream.read
      end
    end
  else
    movie_json = File.read(movie_file_name)
  end
  movie_data = JSON.parse(movie_json)
  # The sample file lists over 4000 movies. This returns only the first 250.
  movie_data.slice(0, 250)
rescue Errno::ENOENT
  puts("File #{movie_file_name} not found. Before you can run this demo, you must
  "
  "download the file. For instructions, see the README.")
  raise
end

```

Run an interactive scenario to create the table and perform actions on it.

```

# Runs the DynamoDB getting started demo.
#
# @param movies [Movies] A wrapper class initialized with a DynamoDB resource.
# @param table_name [String] The name to give the movie table.
# @param movie_file_name [String] The name of a file that contains movie data in
# JSON

```

```

#                                     format. This data is loaded into the movie table
#                                     as part of the demo.
def run_scenario(movies, table_name, movie_file_name)
  puts("-" * 88)
  puts("Welcome to the DynamoDB getting started demo.")
  puts("-" * 88)

  movies_exists = movies.exists?(table_name)
  unless movies_exists
    puts("\nCreating table #{table_name}...")
    movies.create_table(table_name)
    puts("\nCreated table #{movies.table.name}.")
  end

  my_movie = {}
  my_movie[:title] = Question.ask("Enter the title of a movie to add to the table:")
  my_movie[:year] = Question.ask("What year was it released? ", method(:is_int))
  my_movie[:rating] = Question.ask(
    "On a scale of 1 - 10, how do you rate it? ", method(:is_float), in_range(1, 10)
  )
  my_movie[:plot] = Question.ask("Summarize the plot for me: ")

  movies.add_movie(**my_movie)
  puts("\nAdded '#{my_movie[:title]}' to '#{movies.table.name}'")
  puts("-" * 88)

  puts("Let's update your movie. You rated it #{my_movie[:rating]}")
  my_movie[:rating] = Question.ask("What new rating would you give it? ",
    method(:is_float), in_range(1, 10))
  puts("You summarized the plot as '#{my_movie[:plot]}'.")
  my_movie[:plot] = Question.ask("What would you say now? ")
  updated = movies.update_movie(**my_movie)
  puts("Updated '#{my_movie[:title]}' with new attributes:")
  pp(updated)
  puts("-" * 88)

  unless movies_exists
    movie_data = get_sample_movie_data(movie_file_name)
    puts("Reading data from '#{movie_file_name}' into your table.")
    movies.write_batch(movie_data)
    puts("Wrote #{movie_data.length} movies into #{movies.table.name}.")
    puts("-" * 88)
  end

  title = "The Lord of the Rings: The Fellowship of the Ring"
  if Question.ask("Let's move on. Do you want to get info about '#{title}'? (y/n)",
    method(:is_yesno))
    movie = movies.get_movie(title, 2001)
    puts("\nHere's what I found:")
    pp(movie)
    puts("-" * 88)
  end

  ask_for_year = true
  puts("Let's get a list of movies released in a given year.")
  while ask_for_year
    release_year = Question.ask(
      "Enter a year between 1972 and 2018: ", method(:is_int), in_range(1972, 2018))
    releases = movies.query_movies(release_year)
    if !releases.empty?
      puts("There were #{releases.length} movies released in #{release_year}:")
      releases.each do |release|

```

```

        puts("\t#{release["title"]}")
        ask_for_year = false
      end
    else
      puts("I don't know about any movies released in #{release_year}!")
      ask_for_year = Question.ask("Try another year? (y/n) ", method(:is_yesno))
      puts("-" * 88)
    end
  end

  years = {}
years[:start] = Question.ask(
  "Let's scan for movies released in a range of years. Enter a year: ",
  method(:is_int), in_range(1972, 2018))
years[:end] = Question.ask(
  "Now enter another year: ", method(:is_int), in_range(1972, 2018))
releases = movies.scan_movies(years)
if !releases.empty?
  puts("Found #{releases.length} movies.")
  count = Question.ask(
    "How many do you want to see? ", method(:is_int), in_range(1,
releases.length))
  puts("Here are your #{count} movies:")
  releases.take(count).each do |release|
    puts("\t#{release["title"]}")
  end
else
  puts("I don't know about any movies released between #{years[:start]} \"\
    and #{years[:end]}")
  puts("-" * 88)
end

puts("Let's remove your movie from the table.")
if Question.ask(
  "Do you want to remove '#{my_movie[:title]}'? (y/n) ", method(:is_yesno))
  movies.delete_movie(my_movie[:title], my_movie[:year])
  puts("Removed '#{my_movie[:title]}' from the table.")
  puts("-" * 88)
end

if Question.ask("Delete the table? (y/n) ", method(:is_yesno))
  movies.delete_table
  puts("Deleted #{table_name}.")
else
  puts("Don't forget to delete the table when you're done or you might incur \"\
    charges on your account.")
end

puts("\nThanks for watching!")
puts("-" * 88)
rescue Aws::Errors::ServiceError
  puts("Something went wrong with the demo.")
rescue Errno::ENOENT
  true
end

run_scenario(
  Movies.new(Aws::DynamoDB::Resource.new),
  "doc-example-table-movies", "moviedata.json",
  ) if $PROGRAM_NAME == __FILE__

```

This scenario uses the following helper class to ask questions at a command prompt.

```
# Asks a single question and validates it against a list of validators.
```

```

# When an answer fails validation, the complaint is printed and the question
# is asked again.
#
# @param question [String] The question to ask.
# @param validators [Array] The list of validators that the answer must pass.
# @return The answer, converted to its final form by the validators.
class Question
    def self.ask(question, *validators)
        answer = nil
        while answer.nil?
            puts(question)
            answer = gets.chomp
            validators.unshift(method(:non_empty)) unless validators[0] ==
method(:non_empty)
            validators.each do |validator|
                answer, complaint = validator.call(answer)
                if answer.nil?
                    puts(complaint)
                    break
                end
            end
        end
        answer
    end
end

# Validates that the answer is not empty.
# @return [Array] The non-empty answer, or nil.
def non_empty(answer)
    answer = nil unless answer != ""
    [answer, "I need an answer. Please?"]
end

# Validates a yes/no answer.
# @return [Array] True when the answer is 'y'; otherwise, False.
def is_yesno(answer)
    [answer.downcase == "y", ""]
end

# Validates that the answer can be converted to an int.
# @return [Array] The int answer; otherwise, nil.
def is_int(answer)
    int_answer = answer.to_i
    if int_answer == 0
        int_answer = nil
    end
    [int_answer, "#{answer} must be a valid integer."]
end

# Validates that the answer can be converted to a float.
# :return [Array] The float answer; otherwise, None.
def is_float(answer)
    float_answer = answer.to_f
    if float_answer == 0.0
        float_answer = nil
    end
    [float_answer, "#{answer} must be a valid float."]
end

# Validates that the answer is within a range. The answer must be of a type that
# can
# be compared to the lower and upper bounds.
# @return [Proc] A Proc that can be called to determine whether the answer is
# within
#           the expected range.
def in_range(lower, upper)

```

```
Proc.new { |answer|
    answer.between?(lower, upper) ? range_answer = answer : range_answer = nil
    [range_answer, "#{answer} must be between #{lower} and #{upper}."]
}
end
```

- For API details, see the following topics in *AWS SDK for Ruby API Reference*.
  - [BatchWriteItem](#)
  - [CreateTable](#)
  - [DeleteItem](#)
  - [DeleteTable](#)
  - [DescribeTable](#)
  - [GetItem](#)
  - [PutItem](#)
  - [Query](#)
  - [Scan](#)
  - [UpdateItem](#)

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Query a DynamoDB table by using batches of PartiQL statements and an AWS SDK

The following code examples show how to:

- Get a batch of items by running multiple SELECT statements.
- Add a batch of items by running multiple INSERT statements.
- Update a batch of items by running multiple UPDATE statements.
- Delete a batch of items by running multiple DELETE statements.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
// Before you run this example, download 'movies.json' from
// https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/
GettingStarted.Js.02.html,
// and put it in the same folder as the example.

// Separator for the console display.
var SepBar = new string('-', 80);
const string tableName = "movie_table";
const string movieFileName = "moviedata.json";

DisplayInstructions();

// Create the table and wait for it to be active.
```

```
Console.WriteLine($"Creating the movie table: {tableName}");

var success = await DynamoDBMethods.CreateMovieTableAsync(tableName);
if (success)
{
    Console.WriteLine($"Successfully created table: {tableName}.");
}

WaitForEnter();

// Add movie information to the table from moviedata.json. See the
// instructions at the top of this file to download the JSON file.
Console.WriteLine($"Inserting movies into the new table. Please wait...\"");
success = await PartiQLBatchMethods.InsertMovies(tableName, movieFileName);
if (success)
{
    Console.WriteLine("Movies successfully added to the table.");
}
else
{
    Console.WriteLine("Movies could not be added to the table.");
}

WaitForEnter();

// Update multiple movies by using the BatchExecute statement.
var title1 = "Star Wars";
var year1 = 1977;
var title2 = "Wizard of Oz";
var year2 = 1939;

Console.WriteLine($"Updating two movies with producer information: {title1} and
{title2}.");
success = await PartiQLBatchMethods.GetBatch(tableName, title1, title2, year1,
year2);
if (success)
{
    Console.WriteLine($"Successfully retrieved {title1} and {title2}.");
}
else
{
    Console.WriteLine("Select statement failed.");
}

WaitForEnter();

// Update multiple movies by using the BatchExecute statement.
var producer1 = "LucasFilm";
var producer2 = "MGM";

Console.WriteLine($"Updating two movies with producer information: {title1} and
{title2}.");
success = await PartiQLBatchMethods.UpdateBatch(tableName, producer1, title1,
year1, producer2, title2, year2);
if (success)
{
    Console.WriteLine($"Successfully updated {title1} and {title2}.");
}
else
{
    Console.WriteLine("Update failed.");
}

WaitForEnter();

// Delete multiple movies by using the BatchExecute statement.
```

```

Console.WriteLine($"Now we will delete {title1} and {title2} from the table.");
success = await PartiQLBatchMethods.DeleteBatch(tableName, title1, year1, title2,
    year2);

if (success)
{
    Console.WriteLine($"Deleted {title1} and {title2}");
}
else
{
    Console.WriteLine($"could not delete {title1} or {title2}");
}

WaitForEnter();

// DNow that the PartiQL Batch scenario is complete, delete the movie table.
success = await DynamoDBMethods.DeleteTableAsync(tableName);

if (success)
{
    Console.WriteLine($"Successfully deleted {tableName}");
}
else
{
    Console.WriteLine($"Could not delete {tableName}");
}

/// <summary>
/// Displays the description of the application on the console.
/// </summary>
void DisplayInstructions()
{
    Console.Clear();
    Console.WriteLine();
    Console.Write(new string(' ', 24));
    Console.WriteLine("DynamoDB PartiQL Basics Example");
    Console.WriteLine(SepBar);
    Console.WriteLine("This demo application shows the basics of using Amazon
DynamoDB with the AWS SDK for");
    Console.WriteLine(".NET version 3.7 and .NET 6.");
    Console.WriteLine(SepBar);
    Console.WriteLine("Creates a table by using the CreateTable method.");
    Console.WriteLine("Gets multiple movies by using a PartiQL SELECT statement.");
    Console.WriteLine("Updates multiple movies by using the ExecuteBatch method.");
    Console.WriteLine("Deletes multiple movies by using a PartiQL DELETE
statement.");
    Console.WriteLine("Cleans up the resources created for the demo by deleting the
table.");
    Console.WriteLine(SepBar);

    WaitForEnter();
}

/// <summary>
/// Simple method to wait for the <Enter> key to be pressed.
/// </summary>
void WaitForEnter()
{
    Console.WriteLine("\nPress <Enter> to continue.");
    Console.Write(SepBar);
    _ = Console.ReadLine();
}

/// <summary>

```

```

    /**
     * </summary>
     * <param name="tableName"></param>
     * <param name="title1"></param>
     * <param name="title2"></param>
     * <param name="year1"></param>
     * <param name="year2"></param>
     * <returns></returns>
    public static async Task<bool> GetBatch(
        string tableName,
        string title1,
        string title2,
        int year1,
        int year2)
    {
        var getBatch = $"SELECT FROM {tableName} WHERE title = ? AND year = ?";
        var statements = new List<BatchStatementRequest>
        {
            new BatchStatementRequest
            {
                Statement = getBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = title1 },
                    new AttributeValue { N = year1.ToString() },
                },
            },
            new BatchStatementRequest
            {
                Statement = getBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = title2 },
                    new AttributeValue { N = year2.ToString() },
                },
            }
        };

        var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});

        if (response.Responses.Count > 0)
        {
            response.Responses.ForEach(r =>
            {
                Console.WriteLine($"{r.Item["title"]}\t{r.Item["year"]}");
            });
            return true;
        }
        else
        {
            Console.WriteLine($"Couldn't find either {title1} or {title2}.");
            return false;
        }
    }

    /**
     * <summary>
     * Inserts movies imported from a JSON file into the movie table by
     * using an Amazon DynamoDB PartiQL INSERT statement.
    
```

```

    ///> </summary>
    ///> <param name="tableName">The name of the table into which the movie
    ///> information will be inserted.</param>
    ///> <param name="movieFileName">The name of the JSON file that contains
    ///> movie information.</param>
    ///> <returns>A Boolean value that indicates the success or failure of
    ///> the insert operation.</returns>
    public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
    {
        // Get the list of movies from the JSON file.
        var movies = ImportMovies(movieFileName);

        var success = false;

        if (movies is not null)
        {
            // Insert the movies in a batch using PartiQL. Because the
            // batch can contain a maximum of 25 items, insert 25 movies
            // at a time.
            string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?, 'year': ?}}";
            var statements = new List<BatchStatementRequest>();

            try
            {
                for (var indexOffset = 0; indexOffset < 250; indexOffset += 25)
                {
                    for (var i = indexOffset; i < indexOffset + 25; i++)
                    {
                        statements.Add(new BatchStatementRequest
                        {
                            Statement = insertBatch,
                            Parameters = new List<AttributeValue>
                            {
                                new AttributeValue { S = movies[i].Title },
                                new AttributeValue { N = movies[i].Year.ToString() }
                            }
                        });
                    }
                }

                var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
                {
                    Statements = statements,
                });

                // Wait between batches for movies to be successfully
                // added.
                System.Threading.Thread.Sleep(3000);

                success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

                // Clear the list of statements for the next batch.
                statements.Clear();
            }
            catch (AmazonDynamoDBException ex)
            {
                Console.WriteLine(ex.Message);
            }
        }
    }

    return success;

```

```

        }

        /// <summary>
        /// Loads the contents of a JSON file into a list of movies to be
        /// added to the DynamoDB table.
        /// </summary>
        /// <param name="movieFileName">The full path to the JSON file.</param>
        /// <returns>A generic list of movie objects.</returns>
        public static List<Movie> ImportMovies(string movieFileName)
        {
            if (!File.Exists(movieFileName))
            {
                return null;
            }

            using var sr = new StreamReader(movieFileName);
            string json = sr.ReadToEnd();
            var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

            if (allMovies is not null)
            {
                // Return the first 250 entries.
                return allMovies.GetRange(0, 250);
            }
            else
            {
                return null;
            }
        }

        /// <summary>
        /// Updates information for multiple movies.
        /// </summary>
        /// <param name="tableName">The name of the table containing the
        /// movies to be updated.</param>
        /// <param name="producer1">The producer name for the first movie
        /// to update.</param>
        /// <param name="title1">The title of the first movie.</param>
        /// <param name="year1">The year that the first movie was released.</param>
        /// <param name="producer2">The producer name for the second
        /// movie to update.</param>
        /// <param name="title2">The title of the second movie.</param>
        /// <param name="year2">The year that the second movie was released.</
param>
        /// <returns>A Boolean value that indicates the success of the update.</
returns>
        public static async Task<bool> UpdateBatch(
            string tableName,
            string producer1,
            string title1,
            int year1,
            string producer2,
            string title2,
            int year2)
        {

            string updateBatch = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";
            var statements = new List<BatchStatementRequest>
            {
                new BatchStatementRequest
                {
                    Statement = updateBatch,
                    Parameters = new List<AttributeValue>

```

```

        },
        new AttributeValue { S = producer1 },
        new AttributeValue { S = title1 },
        new AttributeValue { N = year1.ToString() },
    },
},
};

new BatchStatementRequest
{
    Statement = updateBatch,
    Parameters = new List<AttributeValue>
    {
        new AttributeValue { S = producer2 },
        new AttributeValue { S = title2 },
        new AttributeValue { N = year2.ToString() },
    },
}
};

var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});
}

return response.StatusCode == System.Net.HttpStatusCode.OK;
}

/// <summary>
/// Deletes multiple movies using a PartiQL BatchExecuteAsync
/// statement.
/// </summary>
/// <param name="tableName">The name of the table containing the
/// moves that will be deleted.</param>
/// <param name="title1">The title of the first movie.</param>
/// <param name="year1">The year the first movie was released.</param>
/// <param name="title2">The title of the second movie.</param>
/// <param name="year2">The year the second movie was released.</param>
/// <returns>A Boolean value indicating the success of the operation.</returns>
public static async Task<bool> DeleteBatch(
    string tableName,
    string title1,
    int year1,
    string title2,
    int year2)
{

    string updateBatch = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";
    var statements = new List<BatchStatementRequest>
    {
        new BatchStatementRequest
        {
            Statement = updateBatch,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = title1 },
                new AttributeValue { N = year1.ToString() },
            },
        },
        new BatchStatementRequest
        {
}

```

```
        Statement = updateBatch,
        Parameters = new List<AttributeValue>
        {
            new AttributeValue { S = title2 },
            new AttributeValue { N = year2.ToString() },
        },
    );
}

var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});

return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
}
```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for .NET API Reference*.

## Go

### SDK for Go V2

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a struct that is a receiver for methods that can run PartiQL statements.

```
// PartiQLRunner encapsulates the Amazon DynamoDB service actions used in the
// PartiQL examples. It contains a DynamoDB service client that is used to act on
// the
// specified table.
type PartiQLRunner struct {
    DynamoDbClient *dynamodb.Client
    TableName       string
}

// AddMovieBatch runs a batch of PartiQL INSERT statements to add multiple movies
// to the
// DynamoDB table.
func (runner PartiQLRunner) AddMovieBatch(movies []Movie) error {
    statementRequests := make([]types.BatchStatementRequest, len(movies))
    for index, movie := range movies {
        params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
        movie.Info})
        if err != nil {
            panic(err)
        }
        statementRequests[index] = types.BatchStatementRequest{
            Statement: aws.String(fmt.Sprintf(
                "INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
                runner.TableName)),
            Parameters: params,
        }
    }
    _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
    &dynamodb.BatchExecuteStatementInput{
```

```

        Statements: statementRequests,
    })
    if err != nil {
        log.Printf("Couldn't insert a batch of items with PartiQL. Here's why: %v\n",
        err)
    }
    return err
}

// GetMovieBatch runs a batch of PartiQL SELECT statements to get multiple movies
// from
// the DynamoDB table by title and year.
func (runner PartiQLRunner) GetMovieBatch(movies []Movie) ([]Movie, error) {
    statementRequests := make([]types.BatchStatementRequest, len(movies))
    for index, movie := range movies {
        params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
        if err != nil {
            panic(err)
        }
        statementRequests[index] = types.BatchStatementRequest{
            Statement: aws.String(
                fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?", runner.TableName)),
            Parameters: params,
        }
    }

    output, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
        &dynamodb.BatchExecuteStatementInput{
            Statements: statementRequests,
        })
    var outMovies []Movie
    if err != nil {
        log.Printf("Couldn't get a batch of items with PartiQL. Here's why: %v\n", err)
    } else {
        for _, response := range output.Responses {
            var movie Movie
            err = attributevalue.UnmarshalMap(response.Item, &movie)
            if err != nil {
                log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
            } else {
                outMovies = append(outMovies, movie)
            }
        }
    }
    return outMovies, err
}

// GetAllMovies runs a PartiQL SELECT statement to get all movies from the DynamoDB
// table.
// The results are projected to return only the title and rating of each movie.
func (runner PartiQLRunner) GetAllMovies() ([]map[string]interface{}, error) {
    var output []map[string]interface{}
    response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
        &dynamodb.ExecuteStatementInput{
            Statement: aws.String(
                fmt.Sprintf("SELECT title, info.rating FROM \"%v\"", runner.TableName)),
        })
    if err != nil {
        log.Printf("Couldn't get movies. Here's why: %v\n", err)
    } else {
        err = attributevalue.UnmarshalListOfMaps(response.Items, &output)
    }
}

```

```

        if err != nil {
            log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
        }
    }
    return output, err
}

// UpdateMovieBatch runs a batch of PartiQL UPDATE statements to update the rating
// of
// multiple movies that already exist in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovieBatch(movies []Movie, ratings []float64) error {
    statementRequests := make([]types.BatchStatementRequest, len(movies))
    for index, movie := range movies {
        params, err := attributevalue.MarshalList([]interface{}{ratings[index],
        movie.Title, movie.Year})
        if err != nil {
            panic(err)
        }
        statementRequests[index] = types.BatchStatementRequest{
            Statement: aws.String(
                fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
                runner.TableName)),
            Parameters: params,
        }
    }

    _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
    &dynamodb.BatchExecuteStatementInput{
        Statements: statementRequests,
    })
    if err != nil {
        log.Printf("Couldn't update the batch of movies. Here's why: %v\n", err)
    }
    return err
}

// DeleteMovieBatch runs a batch of PartiQL DELETE statements to remove multiple
// movies
// from the DynamoDB table.
func (runner PartiQLRunner) DeleteMovieBatch(movies []Movie) error {
    statementRequests := make([]types.BatchStatementRequest, len(movies))
    for index, movie := range movies {
        params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
        if err != nil {
            panic(err)
        }
        statementRequests[index] = types.BatchStatementRequest{
            Statement: aws.String(
                fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
                runner.TableName)),
            Parameters: params,
        }
    }

    _, err := runner.DynamoDbClient.BatchExecuteStatement(context.TODO(),
    &dynamodb.BatchExecuteStatementInput{
        Statements: statementRequests,
    })
    if err != nil {
        log.Printf("Couldn't delete the batch of movies. Here's why: %v\n", err)
    }
    return err
}

```

```
}
```

Run a scenario that creates a table and runs batches of PartiQL queries.

```
// RunPartiQLBatchScenario shows you how to use the AWS SDK for Go
// to run batches of PartiQL statements to query a table that stores data about
// movies.
//
// * Use batches of PartiQL statements to add, get, update, and delete data for
//   individual movies.
//
// This example creates an Amazon DynamoDB service client from the specified
// sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// This example creates and deletes a DynamoDB table to use during the scenario.
func RunPartiQLBatchScenario(sdkConfig aws.Config, tableName string) {
    defer func() {
        if r := recover(); r != nil {
            fmt.Printf("Something went wrong with the demo.")
        }
    }()

    log.Println(strings.Repeat("-", 88))
    log.Println("Welcome to the Amazon DynamoDB PartiQL batch demo.")
    log.Println(strings.Repeat("-", 88))

    tableBasics := actions.TableBasics{
        DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
        TableName:       tableName,
    }
    runner := actions.PartiQLRunner{
        DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
        TableName:       tableName,
    }

    exists, err := tableBasics.TableExists()
    if err != nil {
        panic(err)
    }
    if !exists {
        log.Printf("Creating table %v...\n", tableName)
        _, err = tableBasics.CreateMovieTable()
        if err != nil {
            panic(err)
        } else {
            log.Printf("Created table %v.\n", tableName)
        }
    } else {
        log.Printf("Table %v already exists.\n", tableName)
    }
    log.Println(strings.Repeat("-", 88))

    currentYear, _, _ := time.Now().Date()
    customMovies := []actions.Movie{
        Title: "House PartiQL",
        Year:  currentYear - 5,
        Info: map[string]interface{}{
            "plot":   "Wacky high jinks result from querying a mysterious database.",
            "rating": 8.5}},
        {
        Title: "House PartiQL 2",
        Year:  currentYear - 3,
```

```

Info: map[string]interface{}{
    "plot": "Moderate high jinks result from querying another mysterious
database.",
    "rating": 6.5}},
Title: "House PartiQL 3",
Year: currentYear - 1,
Info: map[string]interface{}{
    "plot": "Tepid high jinks result from querying yet another mysterious
database.",
    "rating": 2.5},
},
}

log.Printf("Inserting a batch of movies into table '%v'.\n", tableName)
err = runner.AddMovieBatch(customMovies)
if err == nil {
    log.Printf("Added %v movies to the table.\n", len(customMovies))
}
log.Println(strings.Repeat("-", 88))

log.Println("Getting data for a batch of movies.")
movies, err := runner.GetMovieBatch(customMovies)
if err == nil {
    for _, movie := range movies {
        log.Println(movie)
    }
}
log.Println(strings.Repeat("-", 88))

newRatings := []float64{7.7, 4.4, 1.1}
log.Println("Updating a batch of movies with new ratings.")
err = runner.UpdateMovieBatch(customMovies, newRatings)
if err == nil {
    log.Printf("Updated %v movies with new ratings.\n", len(customMovies))
}
log.Println(strings.Repeat("-", 88))

log.Println("Getting projected data from the table to verify our update.")
projections, err := runner.GetAllMovies()
if err == nil {
    for _, projection := range projections {
        log.Println(projection)
    }
}
log.Println(strings.Repeat("-", 88))

log.Println("Deleting a batch of movies.")
err = runner.DeleteMovieBatch(customMovies)
if err == nil {
    log.Printf("Deleted %v movies.\n", len(customMovies))
}

err = tableBasics.DeleteTable()
if err == nil {
    log.Printf("Deleted table %v.\n", tableBasics.TableName)
}

log.Println(strings.Repeat("-", 88))
log.Println("Thanks for watching!")
log.Println(strings.Repeat("-", 88))
}

```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for Go API Reference*.

Java

**SDK for Java 2.x**

**Tip**

To learn how to set up and run this example, see [GitHub](#).

```
public class ScenarioPartiQLBatch {

    public static void main(String [] args) throws IOException {

        String tableName = "MoviesPartiQLBatch";
        ProfileCredentialsProvider credentialsProvider =
ProfileCredentialsProvider.create();
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
            .credentialsProvider(credentialsProvider)
            .region(region)
            .build();

        System.out.println("***** Creating an Amazon DynamoDB table named "+tableName +" with a key named year and a sort key named title.");
        createTable(ddb, tableName);

        System.out.println("***** Adding multiple records into the "+ tableName +" table using a batch command.");
        putRecordBatch(ddb);

        System.out.println("***** Updating multiple records using a batch command.");
        updateTableItemBatch(ddb);

        System.out.println("***** Deleting multiple records using a batch command.");
        deleteItemBatch(ddb);

        System.out.println("***** Deleting the Amazon DynamoDB table.");
        deleteDynamoDBTable(ddb, tableName);
        ddb.close();
    }

    public static void createTable(DynamoDbClient ddb, String tableName) {
        DynamoDbWaiter dbWaiter = ddb.waiter();
        ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

        // Define attributes.
        attributeDefinitions.add(AttributeDefinition.builder()
            .attributeName("year")
            .attributeType("N")
            .build());

        attributeDefinitions.add(AttributeDefinition.builder()
            .attributeName("title")
            .attributeType("S")
            .build());

        ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
        KeySchemaElement key = KeySchemaElement.builder()
            .attributeName("year")
            .keyType(KeyType.HASH)
            .build();

        KeySchemaElement key2 = KeySchemaElement.builder()
            .attributeName("title")
```

```

        .keyType(KeyType.RANGE) // Sort
        .build();

    // Add KeySchemaElement objects to the list.
    tableKey.add(key);
    tableKey.add(key2);

    CreateTableRequest request = CreateTableRequest.builder()
        .keySchema(tableKey)
        .provisionedThroughput(ProvisionedThroughput.builder()
            .readCapacityUnits(new Long(10))
            .writeCapacityUnits(new Long(10))
            .build())
        .attributeDefinitions(attributeDefinitions)
        .tableName(tableName)
        .build();

    try {
        CreateTableResponse response = ddb.createTable(request);
        DescribeTableRequest tableRequest = DescribeTableRequest.builder()
            .tableName(tableName)
            .build();

        // Wait until the Amazon DynamoDB table is created.
        WaiterResponse<DescribeTableResponse> waiterResponse =
        dbWaiter.waitUntilTableExists(tableRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        String newTable = response.tableDescription().tableName();
        System.out.println("The " +newTable + " was successfully created.");

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
}

public static void putRecordBatch(DynamoDbClient ddb) {
    String sqlStatement = "INSERT INTO MoviesPartiQBatch VALUE {'year':?, 'title' : ?, 'info' : ?}";
    try {
        // Create three movies to add to the Amazon DynamoDB table.
        // Set data for Movie 1.
        List<AttributeValue> parameters = new ArrayList<>();

        AttributeValue att1 = AttributeValue.builder()
            .n(String.valueOf("2022"))
            .build();

        AttributeValue att2 = AttributeValue.builder()
            .s("My Movie 1")
            .build();

        AttributeValue att3 = AttributeValue.builder()
            .s("No Information")
            .build();

        parameters.add(att1);
        parameters.add(att2);
        parameters.add(att3);

        BatchStatementRequest statementRequestMovie1 =
        BatchStatementRequest.builder()
            .statement(sqlStatement)
            .parameters(parameters)
            .build();
    }
}

```

```
// Set data for Movie 2.
List<AttributeValue> parametersMovie2 = new ArrayList<>();
AttributeValue attMovie2 = AttributeValue.builder()
    .n(String.valueOf("2022"))
    .build();

AttributeValue attMovie2A = AttributeValue.builder()
    .s("My Movie 2")
    .build();

AttributeValue attMovie2B = AttributeValue.builder()
    .s("No Information")
    .build();

parametersMovie2.add(attMovie2);
parametersMovie2.add(attMovie2A);
parametersMovie2.add(attMovie2B);

BatchStatementRequest statementRequestMovie2 =
BatchStatementRequest.builder()
    .statement(sqlStatement)
    .parameters(parametersMovie2)
    .build();

// Set data for Movie 3.
List<AttributeValue> parametersMovie3 = new ArrayList<>();
AttributeValue attMovie3 = AttributeValue.builder()
    .n(String.valueOf("2022"))
    .build();

AttributeValue attMovie3A = AttributeValue.builder()
    .s("My Movie 3")
    .build();

AttributeValue attMovie3B = AttributeValue.builder()
    .s("No Information")
    .build();

parametersMovie3.add(attMovie3);
parametersMovie3.add(attMovie3A);
parametersMovie3.add(attMovie3B);

BatchStatementRequest statementRequestMovie3 =
BatchStatementRequest.builder()
    .statement(sqlStatement)
    .parameters(parametersMovie3)
    .build();

// Add all three movies to the list.
List<BatchStatementRequest> myBatchStatementList = new ArrayList<>();
myBatchStatementList.add(statementRequestMovie1);
myBatchStatementList.add(statementRequestMovie2);
myBatchStatementList.add(statementRequestMovie3);

BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
    .statements(myBatchStatementList)
    .build();

BatchExecuteStatementResponse response =
ddb.batchExecuteStatement(batchRequest);
System.out.println("ExecuteStatement successful: " +
response.toString());
System.out.println("Added new movies using a batch command.");

} catch (DynamoDbException e) {
```

```
        System.err.println(e.getMessage());
        System.exit(1);
    }

    public static void updateTableItemBatch(DynamoDbClient ddb){
        String sqlStatement = "UPDATE MoviesPartiQBatch SET info = 'directors\" : [\"Merian C. Cooper\", \"Ernest B. Schoedsack\" WHERE year=? AND title=?";
        List<AttributeValue> parametersRec1 = new ArrayList<>();

        // Update three records.
        AttributeValue att1 = AttributeValue.builder()
            .n(String.valueOf("2022"))
            .build();

        AttributeValue att2 = AttributeValue.builder()
            .s("My Movie 1")
            .build();

        parametersRec1.add(att1);
        parametersRec1.add(att2);

        BatchStatementRequest statementRequestRec1 =
        BatchStatementRequest.builder()
            .statement(sqlStatement)
            .parameters(parametersRec1)
            .build();

        // Update record 2.
        List<AttributeValue> parametersRec2 = new ArrayList<>();
        AttributeValue attRec2 = AttributeValue.builder()
            .n(String.valueOf("2022"))
            .build();

        AttributeValue attRec2a = AttributeValue.builder()
            .s("My Movie 2")
            .build();

        parametersRec2.add(attRec2);
        parametersRec2.add(attRec2a);
        BatchStatementRequest statementRequestRec2 =
        BatchStatementRequest.builder()
            .statement(sqlStatement)
            .parameters(parametersRec2)
            .build();

        // Update record 3.
        List<AttributeValue> parametersRec3 = new ArrayList<>();
        AttributeValue attRec3 = AttributeValue.builder()
            .n(String.valueOf("2022"))
            .build();

        AttributeValue attRec3a = AttributeValue.builder()
            .s("My Movie 3")
            .build();

        parametersRec3.add(attRec3);
        parametersRec3.add(attRec3a);
        BatchStatementRequest statementRequestRec3 =
        BatchStatementRequest.builder()
            .statement(sqlStatement)
            .parameters(parametersRec3)
            .build();

        // Add all three movies to the list.
        List<BatchStatementRequest> myBatchStatementList = new ArrayList<>();
```

```
myBatchStatementList.add(statementRequestRec1);
myBatchStatementList.add(statementRequestRec2);
myBatchStatementList.add(statementRequestRec3);

BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
    .statements(myBatchStatementList)
    .build();

try {
    BatchExecuteStatementResponse response =
ddb.batchExecuteStatement(batchRequest);
    System.out.println("ExecuteStatement successful: "+
response.toString());
    System.out.println("Updated three movies using a batch command.");

} catch (DynamoDbException e) {
    System.err.println(e.getMessage());
    System.exit(1);
}
System.out.println("Item was updated!");
}

public static void deleteItemBatch(DynamoDbClient ddb){
    String sqlStatement = "DELETE FROM MoviesPartiQBatch WHERE year = ? and
title=?";
    List<AttributeValue> parametersRec1 = new ArrayList<>();

    // Specify three records to delete.
    AttributeValue att1 = AttributeValue.builder()
        .n(String.valueOf("2022"))
        .build();

    AttributeValue att2 = AttributeValue.builder()
        .s("My Movie 1")
        .build();

    parametersRec1.add(att1);
    parametersRec1.add(att2);

    BatchStatementRequest statementRequestRec1 =
BatchStatementRequest.builder()
    .statement(sqlStatement)
    .parameters(parametersRec1)
    .build();

    // Specify record 2.
    List<AttributeValue> parametersRec2 = new ArrayList<>();
    AttributeValue attRec2 = AttributeValue.builder()
        .n(String.valueOf("2022"))
        .build();

    AttributeValue attRec2a = AttributeValue.builder()
        .s("My Movie 2")
        .build();

    parametersRec2.add(attRec2);
    parametersRec2.add(attRec2a);
    BatchStatementRequest statementRequestRec2 =
BatchStatementRequest.builder()
    .statement(sqlStatement)
    .parameters(parametersRec2)
    .build();

    // Specify record 3.
    List<AttributeValue> parametersRec3 = new ArrayList<>();
```

```
AttributeValue attRec3 = AttributeValue.builder()
    .n(String.valueOf("2022"))
    .build();

AttributeValue attRec3a = AttributeValue.builder()
    .s("My Movie 3")
    .build();

parametersRec3.add(attRec3);
parametersRec3.add(attRec3a);

BatchStatementRequest statementRequestRec3 =
BatchStatementRequest.builder()
    .statement(sqlStatement)
    .parameters(parametersRec3)
    .build();

// Add all three movies to the list.
List<BatchStatementRequest> myBatchStatementList = new ArrayList<>();
myBatchStatementList.add(statementRequestRec1);
myBatchStatementList.add(statementRequestRec2);
myBatchStatementList.add(statementRequestRec3);

BatchExecuteStatementRequest batchRequest =
BatchExecuteStatementRequest.builder()
    .statements(myBatchStatementList)
    .build();

try {
    ddb.batchExecuteStatement(batchRequest);
    System.out.println("Deleted three movies using a batch command.");

} catch (DynamoDbException e) {
    System.err.println(e.getMessage());
    System.exit(1);
}
}

public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName) {
    DeleteTableRequest request = DeleteTableRequest.builder()
        .tableName(tableName)
        .build();

    try {
        ddb.deleteTable(request);

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    System.out.println(tableName + " was successfully deleted!");
}

private static ExecuteStatementResponse executeStatementRequest(DynamoDbClient
ddb, String statement, List<AttributeValue> parameters ) {
    ExecuteStatementRequest request = ExecuteStatementRequest.builder()
        .statement(statement)
        .parameters(parameters)
        .build();

    return ddb.executeStatement(request);
}
}
```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.  
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";  
// Set the AWS Region.  
export const REGION = "eu-west-1"; // For example, "us-east-1".  
// Create an Amazon DynamoDB service client object.  
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the document client.

```
// Create a service client module using ES6 syntax.  
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";  
import { ddbClient } from "./ddbClient.js";  
// Set the AWS Region.  
const REGION = "eu-west-1"; // For example, "us-east-1".  
  
const marshallOptions = {  
    // Whether to automatically convert empty strings, blobs, and sets to `null`.  
    convertEmptyValues: false, // false, by default.  
    // Whether to remove undefined values while marshalling.  
    removeUndefinedValues: false, // false, by default.  
    // Whether to convert typeof object to map attribute.  
    convertClassInstanceToMap: false, // false, by default.  
};  
  
const unmarshallOptions = {  
    // Whether to return numbers as a string instead of converting them to native  
    // JavaScript numbers.  
    wrapNumbers: false, // false, by default.  
};  
  
const translateConfig = { marshallOptions, unmarshallOptions };  
  
// Create the DynamoDB document client.  
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);  
  
export { ddbDocClient };
```

Query items by batch.

```
/*  
import fs from "fs";  
// A practical functional library used to split the data into segments.  
import * as R from "ramda";  
import { ddbClient } from "../libs/ddbClient.js";  
import { ddbDocClient } from "../libs/ddbDocClient.js";  
import { BatchWriteCommand } from "@aws-sdk/lib-dynamodb";  
import {
```

```

CreateTableCommand,
BatchExecuteStatementCommand,
} from "@aws-sdk/client-dynamodb";
if (process.argv.length < 6) {
  console.log(
    "Usage: node partiQL_basics.js <tableName> <movieTitle1> <movieYear1>
<movieTitle1> <movieYear1> <producer1> <producer2> \n" +
    "Example: node partiQL_basics.js Movies_batch 2006 'The Departed' 2013 '2
Guns' 'New View Films' 'Old Thyme Films'"
  );
}

const tableName = process.argv[2];
const movieYear1 = parseInt(process.argv[3]);
const movieTitle1 = process.argv[4];
const movieYear2 = parseInt(process.argv[5]);
const movieTitle2 = process.argv[6];
const producer1 = process.argv[7];
const producer2 = process.argv[8];

// Helper function to delay running the code while the AWS service calls wait for
// responses.
function wait(ms) {
  var start = Date.now();
  var end = start;
  while (end < start + ms) {
    end = Date.now();
  }
}
// Set the parameters.

export const run = async (
  tableName,
  movieYear1,
  movieTitle1,
  movieYear2,
  movieTitle2,
  producer1,
  producer2
) => {
  try {
    console.log("Creating table ...");
    // Set the parameters.
    const params = {
      AttributeDefinitions: [
        {
          AttributeName: "title",
          AttributeType: "S",
        },
        {
          AttributeName: "year",
          AttributeType: "N",
        },
      ],
      KeySchema: [
        {
          AttributeName: "title",
          KeyType: "HASH",
        },
        {
          AttributeName: "year",
          KeyType: "RANGE",
        },
      ],
      ProvisionedThroughput: {
        ReadCapacityUnits: 5,

```

```

        WriteCapacityUnits: 5,
    },
    TableName: tableName,
};
const data = await ddbClient.send(new CreateTableCommand(params));
console.log("Waiting for table to be created...");
wait(10000);
console.log(
    "Table created. Table name is ",
    data.TableDescription.TableName
);
try {
    // Before you run this example, download 'movies.json' from https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/GettingStarted.Js.02.html,
    // and put it in the same folder as the example.
    // Get the movie data parse to convert into a JSON object.
    const allMovies = JSON.parse(fs.readFileSync("moviedata.json", "utf8"));
    // Split the table into segments of 25.
    const dataSegments = R.splitEvery(25, allMovies);
    // Loop batch write operation 10 times to upload 250 items.
    console.log("Writing movies in batch to table...");
    for (let i = 0; i < 10; i++) {
        const segment = dataSegments[i];
        for (let j = 0; j < 25; j++) {
            const params = {
                RequestItems: [
                    [tableName]: [
                        {
                            // Destination Amazon DynamoDB table name.
                            PutRequest: {
                                Item: {
                                    year: segment[j].year,
                                    title: segment[j].title,
                                    info: segment[j].info,
                                },
                            },
                        ],
                    ],
                ],
            };
            const data = ddbDocClient.send(new BatchWriteCommand(params));
        }
    }
    wait(10000);
    console.log("Success, movies written to table.");
    try {
        console.log("Getting movie....");
        const params = {
            Statements: [
                {
                    Statement:
                        "SELECT * FROM " + tableName + " where title=? and year=?",
                    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
                },
                {
                    Statement:
                        "SELECT * FROM " + tableName + " where title=? and year=?",
                    Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
                },
            ],
        };
        const data = await ddbDocClient.send(
            new BatchExecuteStatementCommand(params)
        );
        console.log("Success. The query return the following data.", data);
        for (let i = 0; i < data.Responses.length; i++) {

```

```
        console.log(data.Responses[i].Item.year);
        console.log(data.Responses[i].Item.title);
    }
    try {
        const params = {
            Statements: [
                {
                    Statement:
                        "DELETE FROM " + tableName + " where title=? and year=?",
                    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
                },
                {
                    Statement:
                        "DELETE FROM " + tableName + " where title=? and year=?",
                    Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
                },
            ],
        };
        const data = await ddbDocClient.send(
            new BatchExecuteStatementCommand(params)
        );
        console.log("Success. Items deleted by batch.");
    try {
        const params = {
            Statements: [
                {
                    Statement:
                        "INSERT INTO " +
                        tableName +
                        " value {'title':?, 'year':?}",
                    Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
                },
                {
                    Statement:
                        "INSERT INTO " +
                        tableName +
                        " value {'title':?, 'year':?}",
                    Parameters: [{ S: movieTitle2 }, { N: movieYear2 }],
                },
            ],
        };
        const data = await ddbDocClient.send(
            new BatchExecuteStatementCommand(params)
        );
        console.log("Success. Items added by batch.");
    try {
        const params = {
            Statements: [
                {
                    Statement:
                        "UPDATE " +
                        tableName +
                        " SET Producer=? where title=? and year=?",
                    Parameters: [
                        { S: producer1 },
                        { S: movieTitle1 },
                        { N: movieYear1 },
                    ],
                },
                {
                    Statement:
                        "UPDATE " +
                        tableName +
                        " SET Producer=? where title=? and year=?",
                    Parameters: [
                        { S: producer2 },
                    ],
                },
            ],
        };
    
```

```

        { S: movieTitle2 },
        { N: movieYear2 },
    ],
},
],
);
console.log("Updating movies...");
const data = await ddbDocClient.send(
    new BatchExecuteStatementCommand(params)
);
console.log("Success. Items updated by batch.");
return "Run successfully"; // For unit tests.
} catch (err) {
    console.log("Error updating items by batch. ", err);
}
} catch (err) {
    console.log("Error adding items to table by batch. ", err);
}
} catch (err) {
    console.log("Error deleting movies by batch. ", err);
}
} catch (err) {
    console.log("Error getting movies by batch. ", err);
}
} catch (err) {
    console.log("Error adding movies by batch. ", err);
}
} catch (err) {
    console.log("Error creating table. ", err);
}
);
run(
    tableName,
    movieYear1,
    movieTitle1,
    movieYear2,
    movieTitle2,
    producer1,
    producer2
);

```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for JavaScript API Reference*.

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

suspend fun main() {

    val ddb = DynamoDbClient { region = "us-east-1" }
    val tableName = "MoviesPartiQLBatch"
    println("Creating an Amazon DynamoDB table named $tableName with a key named id
and a sort key named title.")
    createTablePartiQLBatch(ddb, tableName, "year")
}

```

```

        putRecordBatch(ddb)
        updateTableItemBatchBatch(ddb)
        deleteItemsBatch(ddb)
        deleteTablePartiQLBatch(tableName)
    }

suspend fun createTablePartiQLBatch(ddb: DynamoDbClient, tableNameVal: String, key: String) {

    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }

    val response = ddb.createTable(request)
    ddb.waitUntilTableExists { // suspend call
        tableName = tableNameVal
    }
    println("The table was successfully created
    ${response.tableDescription?.tableArn}")
}

suspend fun putRecordBatch(ddb: DynamoDbClient) {

    val sqlStatement = "INSERT INTO MoviesPartiQBatch VALUE {'year':?, 'title' : ?, 'info' : ?}"

    // Create three movies to add to the Amazon DynamoDB table.
    val parametersMovie1 = mutableListOf<AttributeValue>()
    parametersMovie1.add(AttributeValue.N("2022"))
    parametersMovie1.add(AttributeValue.S("My Movie 1"))
    parametersMovie1.add(AttributeValue.S("No Information"))

    val statementRequestMovie1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersMovie1
    }

    // Set data for Movie 2.
}

```

```

val parametersMovie2 = mutableListOf<AttributeValue>()
parametersMovie2.add(AttributeValue.N("2022"))
parametersMovie2.add(AttributeValue.S("My Movie 2"))
parametersMovie2.add(AttributeValue.S("No Information"))

val statementRequestMovie2 = BatchStatementRequest {
    statement = sqlStatement
    parameters = parametersMovie2
}

// Set data for Movie 3.
val parametersMovie3 = mutableListOf<AttributeValue>()
parametersMovie3.add(AttributeValue.N("2022"))
parametersMovie3.add(AttributeValue.S("My Movie 3"))
parametersMovie3.add(AttributeValue.S("No Information"))

val statementRequestMovie3 = BatchStatementRequest {
    statement = sqlStatement
    parameters = parametersMovie3
}

// Add all three movies to the list.
val myBatchStatementList = mutableListOf<BatchStatementRequest>()
myBatchStatementList.add(statementRequestMovie1)
myBatchStatementList.add(statementRequestMovie2)
myBatchStatementList.add(statementRequestMovie3)

val batchRequest = BatchExecuteStatementRequest {
    statements = myBatchStatementList
}
val response = ddb.batchExecuteStatement(batchRequest)
println("ExecuteStatement successful: " + response.toString())
println("Added new movies using a batch command.")
}

suspend fun updateTableItemBatchBatch(ddb: DynamoDbClient) {
    val sqlStatement =
        "UPDATE MoviesPartiQBatch SET info = 'directors\":[\"Merian C. Cooper\",
\"Ernest B. Schoedsack\" where year=? and title=?"
    val parametersRec1 = mutableListOf<AttributeValue>()
    parametersRec1.add(AttributeValue.N("2022"))
    parametersRec1.add(AttributeValue.S("My Movie 1"))
    val statementRequestRec1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec1
    }

    // Update record 2.
    val parametersRec2 = mutableListOf<AttributeValue>()
    parametersRec2.add(AttributeValue.N("2022"))
    parametersRec2.add(AttributeValue.S("My Movie 2"))
    val statementRequestRec2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec2
    }

    // Update record 3.
    val parametersRec3 = mutableListOf<AttributeValue>()
    parametersRec3.add(AttributeValue.N("2022"))
    parametersRec3.add(AttributeValue.S("My Movie 3"))
    val statementRequestRec3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec3
    }

    // Add all three movies to the list.
}

```

```

val myBatchStatementList = mutableListOf<BatchStatementRequest>()
myBatchStatementList.add(statementRequestRec1)
myBatchStatementList.add(statementRequestRec2)
myBatchStatementList.add(statementRequestRec3)

val batchRequest = BatchExecuteStatementRequest {
    statements = myBatchStatementList
}

val response = ddb.batchExecuteStatement(batchRequest)
println("ExecuteStatement successful: $response")
println("Updated three movies using a batch command.")
println("Items were updated!")
}

suspend fun deleteItemsBatch(ddb: DynamoDbClient) {

    // Specify three records to delete.
    val sqlStatement = "DELETE FROM MoviesPartiQLBatch WHERE year = ? and title=?"
    val parametersRec1 = mutableListOf<AttributeValue>()
    parametersRec1.add(AttributeValue.N("2022"))
    parametersRec1.add(AttributeValue.S("My Movie 1"))

    val statementRequestRec1 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec1
    }

    // Specify record 2.
    val parametersRec2 = mutableListOf<AttributeValue>()
    parametersRec2.add(AttributeValue.N("2022"))
    parametersRec2.add(AttributeValue.S("My Movie 2"))
    val statementRequestRec2 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec2
    }

    // Specify record 3.
    val parametersRec3 = mutableListOf<AttributeValue>()
    parametersRec3.add(AttributeValue.N("2022"))
    parametersRec3.add(AttributeValue.S("My Movie 3"))
    val statementRequestRec3 = BatchStatementRequest {
        statement = sqlStatement
        parameters = parametersRec3
    }

    // Add all three movies to the list.
    val myBatchStatementList = mutableListOf<BatchStatementRequest>()
    myBatchStatementList.add(statementRequestRec1)
    myBatchStatementList.add(statementRequestRec2)
    myBatchStatementList.add(statementRequestRec3)

    val batchRequest = BatchExecuteStatementRequest {
        statements = myBatchStatementList
    }

    ddb.batchExecuteStatement(batchRequest)
    println("Deleted three movies using a batch command.")
}

suspend fun deleteTablePartiQLBatch(tableNameVal: String) {

    val request = DeleteTableRequest {
        tableName = tableNameVal
    }
}

```

```
DynamoDbClient { region = "us-east-1" }.use { ddb ->
    ddb.deleteTable(request)
    println("$tableNameVal was deleted")
}
}
```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for Kotlin API reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
namespace DynamoDb\PartiQL_Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\DynamoDBAttribute;

class GettingStartedWithPartiQLBatch
{
    public function run()
    {
        echo("-----\n");
        print("Welcome to the Amazon DynamoDB - PartiQL getting started demo using
PHP!\n");
        echo("-----\n");

        $uuid = uniqid();
        $service = new DynamoDb\DynamoDBService();

        $tableName = "partiql_demo_table_$uuid";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitUntil("TableExists", ['TableName' =>
$tableName]);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }
        $key = [
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [

```

```

        'S' => $movieName,
    ],
],
];
list($statement, $parameters) = $service-
>buildStatementAndParameters("INSERT", $tableName, $key);
$service->insertItemByPartiQLBatch($statement, $parameters);

echo "How would you rate the movie from 1-10?\n";
$rating = 0;
while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 || $rating > 10) {
    $rating = testable_readline("Rating (1-10): ");
}
echo "What was the movie about?\n";
while (empty($plot)) {
    $plot = testable_readline("Plot summary: ");
}
$attributes = [
    new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
    new DynamoDBAttribute('plot', 'S', 'RANGE', $plot),
];

list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
$service->updateItemByPartiQLBatch($statement, $parameters);
echo "Movie added and updated.\n";

$batch = json_decode(loadMovieData());

$service->writeBatch($tableName, $batch);

$movie = $service->getItemByPartiQLBatch($tableName, [$key]);
echo "\nThe movie {$movie['Responses'][0]['Item']['title']['S']} was released in {$movie['Responses'][0]['Item']['year']['N']}.\\n";
echo "What rating would you like to give {$movie['Responses'][0]['Item']['title']['S']}?\\n";
$rating = 0;
while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 || $rating > 10) {
    $rating = testable_readline("Rating (1-10): ");
}
$attributes = [
    new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
    new DynamoDBAttribute('plot', 'S', 'RANGE', $plot)
];
list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
$service->updateItemByPartiQLBatch($statement, $parameters);

$movie = $service->getItemByPartiQLBatch($tableName, [$key]);
echo "Okay, you have rated {$movie['Responses'][0]['Item']['title']['S']} as a {$movie['Responses'][0]['Item']['rating']['N']}\\n";

$service->deleteItemByPartiQLBatch($statement, $parameters);
echo "But, bad news, this was a trap. That movie has now been deleted because of your rating...harsh.\\n";

echo "That's okay though. The book was better. Now, for something lighter, in what year were you born?\\n";
$birthYear = "not a number";
while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
    $birthYear = testable_readline("Birth year: ");
}
$birthKey = [
    'Key' => [

```

```

        'year' => [
            'N' => "$birthYear",
        ],
    ],
];
$result = $service->query($tableName, $birthKey);
$marshal = new Marshaler();
echo "Here are the movies in our collection released the year you were
born:\n";
$oops = "Oops! There were no movies released in that year (that we know
of).\n";
$display = "";
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    $display .= $movie['title'] . "\n";
}
echo ($display) ?: $oops;

$yearsKey = [
    'Key' => [
        'year' => [
            'N' => [
                'minRange' => 1990,
                'maxRange' => 1999,
            ],
        ],
    ],
];
$filter = "year between 1990 and 1999";
echo "\nHere's a list of all the movies released in the 90s:\n";
$result = $service->scan($tableName, $yearsKey, $filter);
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    echo $movie['title'] . "\n";
}

echo "\nCleaning up this demo by deleting table $tableName...\n";
bservice->deleteTable($tableName);
}

public function insertItemByPartiQLBatch(string $statement, array $parameters)
{
    $this->dynamoDbClient->batchExecuteStatement([
        'Statements' => [
            [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ],
        ],
    ]);
}

public function getItemByPartiQLBatch(string $tableName, array $keys): Result
{
    $statements = [];
    foreach ($keys as $key) {
        list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);
        $statements[] = [
            'Statement' => "$statement",
            'Parameters' => $parameters,
        ];
    }
}

return $this->dynamoDbClient->batchExecuteStatement([

```

```

        'Statements' => $statements,
    ]);
}

public function updateItemByPartiQLBatch(string $statement, array $parameters)
{
    $this->dynamoDbClient->batchExecuteStatement([
        'Statements' => [
            [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ],
        ],
    ]);
}

public function deleteItemByPartiQLBatch(string $statement, array $parameters)
{
    $this->dynamoDbClient->batchExecuteStatement([
        'Statements' => [
            [
                'Statement' => "$statement",
                'Parameters' => $parameters,
            ],
        ],
    ]);
}

```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a class that can run batches of PartiQL statements.

```

from datetime import datetime
from decimal import Decimal
import logging
from pprint import pprint

import boto3
from botocore.exceptions import ClientError

from scaffold import Scaffold

logger = logging.getLogger(__name__)

class PartiQLBatchWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource

    def run_partiql(self, statements, param_list):

```

```

"""
Runs a PartiQL statement. A Boto3 resource is used even though
`execute_statement` is called on the underlying `client` object because the
resource transforms input and output from plain old Python objects (POPOs)
to
the DynamoDB format. If you create the client directly, you must do these
transforms yourself.

:param statements: The batch of PartiQL statements.
:param param_list: The batch of PartiQL parameters that are associated with
                   each statement. This list must be in the same order as
the
                   statements.
:return: The responses returned from running the statements, if any.
"""
try:
    output = self.dyn_resource.meta.client.batch_execute_statement(
        Statements=[{
            'Statement': statement, 'Parameters': params
        } for statement, params in zip(statements, param_list)])
except ClientError as err:
    if err.response['Error']['Code'] == 'ResourceNotFoundException':
        logger.error(
            "Couldn't execute batch of PartiQL statements because the table"
            "does not exist.")
    else:
        logger.error(
            "Couldn't execute batch of PartiQL statements. Here's why: %s",
            err.response['Error']['Code'], err.response['Error']
            ['Message'])
        raise
else:
    return output

```

Run a scenario that creates a table and runs PartiQL queries in batches.

```

def run_scenario(scaffold, wrapper, table_name):
    logging.basicConfig(level=logging.INFO, format='%(levelname)s: %(message)s')

    print('*'*88)
    print("Welcome to the Amazon DynamoDB PartiQL batch statement demo.")
    print('*'*88)

    print(f"Creating table '{table_name}' for the demo...")
    scaffold.create_table(table_name)
    print('*'*88)

    movie_data = [
        {
            'title': f"House PartiQL",
            'year': datetime.now().year - 5,
            'info': {
                'plot': "Wacky high jinks result from querying a mysterious database.",
                'rating': Decimal('8.5')}},
        {
            'title': f"House PartiQL 2",
            'year': datetime.now().year - 3,
            'info': {
                'plot': "Moderate high jinks result from querying another mysterious
database.",
                'rating': Decimal('6.5')}},
        {
            'title': f"House PartiQL 3",
            'year': datetime.now().year - 1,
            'info': {

```

```

        'plot': "Tepid high jinks result from querying yet another mysterious
database.",

        'rating': Decimal('2.5')}]

print(f"Inserting a batch of movies into table '{table_name}'.")
statements = [
    f"INSERT INTO \\"{table_name}\\" "
    f"VALUE {{'title': ?, 'year': ?, 'info': ?}}] * len(movie_data)
params = [list(movie.values()) for movie in movie_data]
wrapper.run_partiql(statements, params)
print("Success!")
print('*'*88)

print(f"Getting data for a batch of movies.")
statements = [
    f"SELECT * FROM \\"{table_name}\\" WHERE title=? AND year=?"] *
len(movie_data)
params = [[movie['title'], movie['year']] for movie in movie_data]
output = wrapper.run_partiql(statements, params)
for item in output['Responses']:
    print(f"\n{item['Item']['title']}, {item['Item']['year']}")
    pprint(item['Item'])
print('*'*88)

ratings = [Decimal('7.7'), Decimal('5.5'), Decimal('1.3')]
print(f"Updating a batch of movies with new ratings.")
statements = [
    f"UPDATE \\"{table_name}\\" SET info.rating=? "
    f"WHERE title=? AND year=?"] * len(movie_data)
params = [
    [rating, movie['title'], movie['year']] for rating, movie in zip(ratings,
movie_data)]
wrapper.run_partiql(statements, params)
print("Success!")
print('*'*88)

print(f"Getting projected data from the table to verify our update.")
output = wrapper.dyn_resource.meta.client.execute_statement(
    Statement=f'SELECT title, info.rating FROM "{table_name}"')
pprint(output['Items'])
print('*'*88)

print(f"Deleting a batch of movies from the table.")
statements = [
    f"DELETE FROM \\"{table_name}\\" WHERE title=? AND year=?"] * len(movie_data)
params = [[movie['title'], movie['year']] for movie in movie_data]
wrapper.run_partiql(statements, params)
print("Success!")
print('*'*88)

print(f"Deleting table '{table_name}'...")
scaffold.delete_table()
print('*'*88)

print("\nThanks for watching!")
print('*'*88)

if __name__ == '__main__':
    try:
        dyn_res = boto3.resource('dynamodb')
        scaffold = Scaffold(dyn_res)
        movies = PartiQLBatchWrapper(dyn_res)
        run_scenario(scaffold, movies, 'doc-example-table-partiql-movies')
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")

```

- For API details, see [BatchExecuteStatement](#) in *AWS SDK for Python (Boto3) API Reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Query a DynamoDB table using PartiQL and an AWS SDK

The following code examples show how to:

- Get an item by running a SELECT statement.
- Add an item by running an INSERT statement.
- Update an item by running an UPDATE statement.
- Delete an item by running a DELETE statement.

.NET

### AWS SDK for .NET

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
namespace PartiQL_Basics_Scenario
{
    public class PartiQLMethods
    {
        private static readonly AmazonDynamoDBClient Client = new
AmazonDynamoDBClient();

        ///<summary>
        /// Inserts movies imported from a JSON file into the movie table by
        /// using an Amazon DynamoDB PartiQL INSERT statement.
        ///</summary>
        ///<param name="tableName">The name of the table where the movie
        /// information will be inserted.</param>
        ///<param name="movieFileName">The name of the JSON file that contains
        /// movie information.</param>
        ///<returns>A Boolean value that indicates the success or failure of
        /// the insert operation.</returns>
        public static async Task<bool> InsertMovies(string tableName, string
movieFileName)
        {
            // Get the list of movies from the JSON file.
            var movies = ImportMovies(movieFileName);

            var success = false;

            if (movies is not null)
            {
                // Insert the movies in a batch using PartiQL. Because the
                // batch can contain a maximum of 25 items, insert 25 movies
                // at a time.
                string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?,
'year': ?}}";
            }
        }
}
```

```

var statements = new List<BatchStatementRequest>();

try
{
    for (var indexOffset = 0; indexOffset < 250; indexOffset += 25)
    {
        for (var i = indexOffset; i < indexOffset + 25; i++)
        {
            statements.Add(new BatchStatementRequest
            {
                Statement = insertBatch,
                Parameters = new List<AttributeValue>
                {
                    new AttributeValue { S = movies[i].Title },
                    new AttributeValue { N =
movies[i].Year.ToString() },
                },
            });
        }
    }

    var response = await Client.BatchExecuteStatementAsync(new
BatchExecuteStatementRequest
{
    Statements = statements,
});

    // Wait between batches for movies to be successfully
added.
    System.Threading.Thread.Sleep(3000);

    success = response.HttpStatusCode ==
System.Net.HttpStatusCode.OK;

    // Clear the list of statements for the next batch.
    statements.Clear();
}
}
catch (AmazonDynamoDBException ex)
{
    Console.WriteLine(ex.Message);
}
}

return success;
}

/// <summary>
/// Loads the contents of a JSON file into a list of movies to be
/// added to the DynamoDB table.
/// </summary>
/// <param name="movieFileName">The full path to the JSON file.</param>
/// <returns>A generic list of movie objects.</returns>
public static List<Movie> ImportMovies(string movieFileName)
{
    if (!File.Exists(movieFileName))
    {
        return null;
    }

    using var sr = new StreamReader(movieFileName);
    string json = sr.ReadToEnd();
    var allMovies = JsonConvert.DeserializeObject<List<Movie>>(json);

    if (allMovies is not null)
    {
        // Return the first 250 entries.
    }
}

```

```

        return allMovies.GetRange(0, 250);
    }
    else
    {
        return null;
    }
}

/// <summary>
/// Uses a PartiQL SELECT statement to retrieve a single movie from the
/// movie database.
/// </summary>
/// <param name="tableName">The name of the movie table.</param>
/// <param name="movieTitle">The title of the movie to retrieve.</param>
/// <returns>A list of movie data. If no movie matches the supplied
/// title, the list is empty.</returns>
public static async Task<List<Dictionary<string,AttributeValue>>>
GetSingleMovie(string tableName, string movieTitle)
{
    string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
    var parameters = new List<AttributeValue>
    {
        new AttributeValue { S = movieTitle },
    };

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = selectSingle,
    Parameters = parameters,
});

    return response.Items;
}

/// <summary>
/// Retrieve multiple movies by year using a SELECT statement.
/// </summary>
/// <param name="tableName">The name of the movie table.</param>
/// <param name="year">The year the movies were released.</param>
/// <returns></returns>
public static async Task<List<Dictionary<string,AttributeValue>>>
GetMovies(string tableName, int year)
{
    string selectSingle = $"SELECT * FROM {tableName} WHERE year = ?";
    var parameters = new List<AttributeValue>
    {
        new AttributeValue { N = year.ToString() },
    };

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = selectSingle,
    Parameters = parameters,
});

    return response.Items;
}

/// <summary>

```

```

    ///> Inserts a single movie into the movies table.
    ///</summary>
    ///<param name="tableName">The name of the table.</param>
    ///<param name="movieTitle">The title of the movie to insert.</param>
    ///<param name="year">The year that the movie was released.</param>
    ///<returns>A Boolean value that indicates the success or failure of
    ///the INSERT operation.</returns>
    public static async Task<bool> InsertSingleMovie(string tableName, string
movieTitle, int year)
    {
        string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?, 'year': ?}}";

        var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
        {
            Statement = insertBatch,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
                new AttributeValue { N = year.ToString() },
            },
        });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    ///<summary>
    ///<param name="tableName">the name of the table.</param>
    ///<param name="producer">The name of the producer.</param>
    ///<param name="movieTitle">The movie title.</param>
    ///<param name="year">The year the movie was released.</param>
    ///<returns>A Boolean value that indicates the success of the
    ///UPDATE operation.</returns>
    public static async Task<bool> UpdateSingleMovie(string tableName, string
producer, string movieTitle, int year)
    {
        string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

        var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
        {
            Statement = insertSingle,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = producer },
                new AttributeValue { S = movieTitle },
                new AttributeValue { N = year.ToString() },
            },
        });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    ///<summary>
    ///<param name="tableName">The name of the table.</param>

```

```

    /// <param name="movieTitle">The title of the movie to delete.</param>
    /// <param name="year">The year that the movie was released.</param>
    /// <returns>A Boolean value that indicates the success of the
    /// DELETE operation.</returns>
    public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
    {
        var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";
        var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
        {
            Statement = deleteSingle,
            Parameters = new List<AttributeValue>
            {
                new AttributeValue { S = movieTitle },
                new AttributeValue { N = year.ToString() },
            },
        });
        return response.HttpStatusCode == System.Net.HttpStatusCode.OK;
    }

    /// <summary>
    /// Displays the list of movies returned from a database query.
    /// </summary>
    /// <param name="items">The list of movie information to display.</param>
    private static void DisplayMovies(List<Dictionary<string,AttributeValue>>
items)
    {
        if (items.Count > 0)
        {
            Console.WriteLine($"Found {items.Count} movies.");
            items.ForEach(item =>
Console.WriteLine($"{item["year"].N}\t{item["title"].S}"));
        }
        else
        {
            Console.WriteLine($"Didn't find a movie that matched the supplied
criteria.");
        }
    }

}

    /// <summary>
    /// Uses a PartiQL SELECT statement to retrieve a single movie from the
    /// movie database.
    /// </summary>
    /// <param name="tableName">The name of the movie table.</param>
    /// <param name="movieTitle">The title of the movie to retrieve.</param>
    /// <returns>A list of movie data. If no movie matches the supplied
    /// title, the list is empty.</returns>
    public static async Task<List<Dictionary<string,AttributeValue>>>
GetSingleMovie(string tableName, string movieTitle)
    {
        string selectSingle = $"SELECT * FROM {tableName} WHERE title = ?";
        var parameters = new List<AttributeValue>
        {
            new AttributeValue { S = movieTitle },

```

```

    };

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = selectSingle,
    Parameters = parameters,
});

return response.Items;
}

/// <summary>
/// Inserts a single movie into the movies table.
/// </summary>
/// <param name="tableName">The name of the table.</param>
/// <param name="movieTitle">The title of the movie to insert.</param>
/// <param name="year">The year that the movie was released.</param>
/// <returns>A Boolean value that indicates the success or failure of
/// the INSERT operation.</returns>
public static async Task<bool> InsertSingleMovie(string tableName, string
movieTitle, int year)
{
    string insertBatch = $"INSERT INTO {tableName} VALUE {{'title': ?, 'year': ?}}";

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = insertBatch,
    Parameters = new List<AttributeValue>
    {
        new AttributeValue { S = movieTitle },
        new AttributeValue { N = year.ToString() },
    },
});
}

return response.StatusCode == System.Net.HttpStatusCode.OK;
}

/// <summary>
/// Updates a single movie in the table, adding information for the
/// producer.
/// </summary>
/// <param name="tableName">the name of the table.</param>
/// <param name="producer">The name of the producer.</param>
/// <param name="movieTitle">The movie title.</param>
/// <param name="year">The year the movie was released.</param>
/// <returns>A Boolean value that indicates the success of the
/// UPDATE operation.</returns>
public static async Task<bool> UpdateSingleMovie(string tableName, string
producer, string movieTitle, int year)
{
    string insertSingle = $"UPDATE {tableName} SET Producer=? WHERE title
= ? AND year = ?";

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = insertSingle,
    Parameters = new List<AttributeValue>
    {
}
}

```

```

        new AttributeValue { S = producer },
        new AttributeValue { S = movieTitle },
        new AttributeValue { N = year.ToString() },
    },
});

return response.StatusCode == System.Net.HttpStatusCode.OK;
}

/// <summary>
/// Deletes a single movie from the table.
/// </summary>
/// <param name="tableName">The name of the table.</param>
/// <param name="movieTitle">The title of the movie to delete.</param>
/// <param name="year">The year that the movie was released.</param>
/// <returns>A Boolean value that indicates the success of the
/// DELETE operation.</returns>
public static async Task<bool> DeleteSingleMovie(string tableName, string
movieTitle, int year)
{
    var deleteSingle = $"DELETE FROM {tableName} WHERE title = ? AND year
= ?";

    var response = await Client.ExecuteStatementAsync(new
ExecuteStatementRequest
{
    Statement = deleteSingle,
    Parameters = new List<AttributeValue>
    {
        new AttributeValue { S = movieTitle },
        new AttributeValue { N = year.ToString() },
    },
});

    return response.StatusCode == System.Net.HttpStatusCode.OK;
}

```

- For API details, see [ExecuteStatement](#) in *AWS SDK for .NET API Reference*.

Go

## SDK for Go V2

### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a struct that is a receiver for methods that can run PartiQL statements.

```

// PartiQLRunner encapsulates the Amazon DynamoDB service actions used in the
// PartiQL examples. It contains a DynamoDB service client that is used to act on
// the
// specified table.
type PartiQLRunner struct {
    DynamoDbClient *dynamodb.Client
    TableName      string
}

```

```

// AddMovie runs a PartiQL INSERT statement to add a movie to the DynamoDB table.
func (runner PartiQLRunner) AddMovie(movie Movie) error {
    params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year,
    movie.Info})
    if err != nil {
        panic(err)
    }
    _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
            fmt.Sprintf("INSERT INTO \"%v\" VALUE {'title': ?, 'year': ?, 'info': ?}",
            runner.TableName)),
        Parameters: params,
    })
    if err != nil {
        log.Printf("Couldn't insert an item with PartiQL. Here's why: %v\n", err)
    }
    return err
}

// GetMovie runs a PartiQL SELECT statement to get a movie from the DynamoDB table
// by
// title and year.
func (runner PartiQLRunner) GetMovie(title string, year int) (Movie, error) {
    var movie Movie
    params, err := attributevalue.MarshalList([]interface{}{title, year})
    if err != nil {
        panic(err)
    }
    response, err := runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
            fmt.Sprintf("SELECT * FROM \"%v\" WHERE title=? AND year=?",
            runner.TableName)),
        Parameters: params,
    })
    if err != nil {
        log.Printf("Couldn't get info about %v. Here's why: %v\n", title, err)
    } else {
        err = attributevalue.UnmarshalMap(response.Items[0], &movie)
        if err != nil {
            log.Printf("Couldn't unmarshal response. Here's why: %v\n", err)
        }
    }
    return movie, err
}

// UpdateMovie runs a PartiQL UPDATE statement to update the rating of a movie that
// already exists in the DynamoDB table.
func (runner PartiQLRunner) UpdateMovie(movie Movie, rating float64) error {
    params, err := attributevalue.MarshalList([]interface{}{rating, movie.Title,
    movie.Year})
    if err != nil {
        panic(err)
    }
    _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
    &dynamodb.ExecuteStatementInput{
        Statement: aws.String(
            fmt.Sprintf("UPDATE \"%v\" SET info.rating=? WHERE title=? AND year=?",
            runner.TableName)),
        Parameters: params,
    })
}

```

```

if err != nil {
    log.Printf("Couldn't update movie %v. Here's why: %v\n", movie.Title, err)
}
return err
}

// DeleteMovie runs a PartiQL DELETE statement to remove a movie from the DynamoDB
// table.
func (runner PartiQLRunner) DeleteMovie(movie Movie) error {
    params, err := attributevalue.MarshalList([]interface{}{movie.Title, movie.Year})
    if err != nil {
        panic(err)
    }
    _, err = runner.DynamoDbClient.ExecuteStatement(context.TODO(),
        &dynamodb.ExecuteStatementInput{
            Statement: aws.String(
                fmt.Sprintf("DELETE FROM \"%v\" WHERE title=? AND year=?",
                    runner.TableName)),
            Parameters: params,
        })
    if err != nil {
        log.Printf("Couldn't delete %v from the table. Here's why: %v\n", movie.Title,
            err)
    }
    return err
}

```

Run a scenario that creates a table and runs PartiQL queries.

```

// RunPartiQLSingleScenario shows you how to use the AWS SDK for Go
// to use PartiQL to query a table that stores data about movies.
//
// * Use PartiQL statements to add, get, update, and delete data for individual
//   movies.
//
// This example creates an Amazon DynamoDB service client from the specified
// sdkConfig so that
// you can replace it with a mocked or stubbed config for unit testing.
//
// This example creates and deletes a DynamoDB table to use during the scenario.
func RunPartiQLSingleScenario(sdkConfig aws.Config, tableName string) {
    defer func() {
        if r := recover(); r != nil {
            fmt.Printf("Something went wrong with the demo.")
        }
    }()

    log.Println(strings.Repeat("-", 88))
    log.Println("Welcome to the Amazon DynamoDB PartiQL single action demo.")
    log.Println(strings.Repeat("-", 88))

    tableBasics := actions.TableBasics{
        DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
        TableName:      tableName,
    }
    runner := actions.PartiQLRunner{
        DynamoDbClient: dynamodb.NewFromConfig(sdkConfig),
        TableName:      tableName,
    }
}

```

```

exists, err := tableBasics.TableExists()
if err != nil {
    panic(err)
}
if !exists {
    log.Printf("Creating table %v...\n", tableName)
    _, err = tableBasics.CreateMovieTable()
    if err != nil {
        panic(err)
    } else {
        log.Printf("Created table %v.\n", tableName)
    }
} else {
    log.Printf("Table %v already exists.\n", tableName)
}
log.Println(strings.Repeat("-", 88))

currentYear, _, _ := time.Now().Date()
customMovie := actions.Movie{
    Title: "24 Hour PartiQL People",
    Year: currentYear,
    Info: map[string]interface{}{
        "plot": "A group of data developers discover a new query language they can't
stop using.",
        "rating": 9.9,
    },
}

log.Printf("Inserting movie '%v' released in %v.", customMovie.Title,
customMovie.Year)
err = runner.AddMovie(customMovie)
if err == nil {
    log.Printf("Added %v to the movie table.\n", customMovie.Title)
}
log.Println(strings.Repeat("-", 88))

log.Printf("Getting data for movie '%v' released in %v.", customMovie.Title,
customMovie.Year)
movie, err := runner.GetMovie(customMovie.Title, customMovie.Year)
if err == nil {
    log.Println(movie)
}
log.Println(strings.Repeat("-", 88))

newRating := 6.6
log.Printf("Updating movie '%v' with a rating of %v.", customMovie.Title,
newRating)
err = runner.UpdateMovie(customMovie, newRating)
if err == nil {
    log.Printf("Updated %v with a new rating.\n", customMovie.Title)
}
log.Println(strings.Repeat("-", 88))

log.Printf("Getting data again to verify the update.")
movie, err = runner.GetMovie(customMovie.Title, customMovie.Year)
if err == nil {
    log.Println(movie)
}
log.Println(strings.Repeat("-", 88))

log.Printf("Deleting movie '%v'.\n", customMovie.Title)
err = runner.DeleteMovie(customMovie)
if err == nil {
    log.Printf("Deleted %v.\n", customMovie.Title)
}

```

```
    err = tableBasics.DeleteTable()
    if err == nil {
        log.Printf("Deleted table %v.\n", tableBasics.TableName)
    }

    log.Println(strings.Repeat("-", 88))
    log.Println("Thanks for watching!")
    log.Println(strings.Repeat("-", 88))
}
```

- For API details, see [ExecuteStatement](#) in *AWS SDK for Go API Reference*.

## Java

### SDK for Java 2.x

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```
public class ScenarioPartiQ {

    public static void main(String [] args) throws IOException {

        final String usage = "\n" +
            "Usage:\n" +
            "      <fileName>\n\n" +
            "Where:\n" +
            "      fileName - The path to the moviedata.json file that you can
download from the Amazon DynamoDB Developer Guide.\n" ;

        if (args.length != 1) {
            System.out.println(usage);
            System.exit(1);
        }

        String fileName = args[0];
        String tableName = "MoviesPartiQ";
        ProfileCredentialsProvider credentialsProvider =
ProfileCredentialsProvider.create();
        Region region = Region.US_EAST_1;
        DynamoDbClient ddb = DynamoDbClient.builder()
            .credentialsProvider(credentialsProvider)
            .region(region)
            .build();

        System.out.println("***** Creating an Amazon DynamoDB table named
MoviesPartiQ with a key named year and a sort key named title.");
        createTable(ddb, tableName);

        System.out.println("***** Loading data into the MoviesPartiQ table.");
        loadData(ddb, fileName);

        System.out.println("***** Getting data from the MoviesPartiQ table.");
        getItem(ddb);

        System.out.println("***** Putting a record into the MoviesPartiQ table.");
        putRecord(ddb);

        System.out.println("***** Updating a record.");
        updateTableItem(ddb);
```

```

System.out.println("***** Querying the movies released in 2013.");
queryTable(ddb);

System.out.println("***** Deleting the Amazon DynamoDB table.");
deleteDynamoDBTable(ddb, tableName);
ddb.close();
}

public static void createTable(DynamoDbClient ddb, String tableName) {
    DynamoDbWaiter dbWaiter = ddb.waiter();
    ArrayList<AttributeDefinition> attributeDefinitions = new ArrayList<>();

    // Define attributes.
    attributeDefinitions.add(AttributeDefinition.builder()
        .attributeName("year")
        .attributeType("N")
        .build());

    attributeDefinitions.add(AttributeDefinition.builder()
        .attributeName("title")
        .attributeType("S")
        .build());

    ArrayList<KeySchemaElement> tableKey = new ArrayList<>();
    KeySchemaElement key = KeySchemaElement.builder()
        .attributeName("year")
        .keyType(KeyType.HASH)
        .build();

    KeySchemaElement key2 = KeySchemaElement.builder()
        .attributeName("title")
        .keyType(KeyType.RANGE) // Sort
        .build();

    // Add KeySchemaElement objects to the list.
    tableKey.add(key);
    tableKey.add(key2);

    CreateTableRequest request = CreateTableRequest.builder()
        .keySchema(tableKey)
        .provisionedThroughput(ProvisionedThroughput.builder()
            .readCapacityUnits(new Long(10))
            .writeCapacityUnits(new Long(10))
            .build())
        .attributeDefinitions(attributeDefinitions)
        .tableName(tableName)
        .build();

    try {
        CreateTableResponse response = ddb.createTable(request);
        DescribeTableRequest tableRequest = DescribeTableRequest.builder()
            .tableName(tableName)
            .build();

        // Wait until the Amazon DynamoDB table is created.
        WaiterResponse<DescribeTableResponse> waiterResponse =
        dbWaiter.waitUntilTableExists(tableRequest);
        waiterResponse.matched().response().ifPresent(System.out::println);
        String newTable = response.tableDescription().tableName();
        System.out.println("The " +newTable + " was successfully created.");

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
}

```

```

// Load data into the table.
public static void loadData(DynamoDbClient ddb, String fileName) throws
IOException {

    String sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?,
'title' : ?, 'info' : ?}";
    JsonParser parser = new JsonFactory().createParser(new File(fileName));
    com.fasterxml.jackson.databind.JsonNode rootNode = new
ObjectMapper().readTree(parser);
    Iterator<JsonNode> iter = rootNode.iterator();
    ObjectNode currentNode;
    int t = 0 ;
    List<AttributeValue> parameters = new ArrayList<>();
    while (iter.hasNext()) {

        // Add 200 movies to the table.
        if (t == 200)
            break ;
        currentNode = (ObjectNode) iter.next();

        int year = currentNode.path("year").asInt();
        String title = currentNode.path("title").asText();
        String info = currentNode.path("info").toString();

        AttributeValue att1 = AttributeValue.builder()
            .n(String.valueOf(year))
            .build();

        AttributeValue att2 = AttributeValue.builder()
            .s(title)
            .build();

        AttributeValue att3 = AttributeValue.builder()
            .s(info)
            .build();

        parameters.add(att1);
        parameters.add(att2);
        parameters.add(att3);

        // Insert the movie into the Amazon DynamoDB table.
        executeStatementRequest(ddb, sqlStatement, parameters);
        System.out.println("Added Movie " +title);

        parameters.remove(att1);
        parameters.remove(att2);
        parameters.remove(att3);
        t++;
    }
}

public static void getItem(DynamoDbClient ddb) {

    String sqlStatement = "SELECT * FROM MoviesPartiQ where year=? and
title=?";
    List<AttributeValue> parameters = new ArrayList<>();
    AttributeValue att1 = AttributeValue.builder()
        .n("2012")
        .build();

    AttributeValue att2 = AttributeValue.builder()
        .s("The Perks of Being a Wallflower")
        .build();

    parameters.add(att1);
}

```

```

        parameters.add(att2);

        try {
            ExecuteStatementResponse response = executeStatementRequest(ddb,
sqlStatement, parameters);
            System.out.println("ExecuteStatement successful: "+
response.toString());

        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void putRecord(DynamoDbClient ddb) {

        String sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?:,
'title' : ?, 'info' : ?}";
        try {
            List<AttributeValue> parameters = new ArrayList<>();

            AttributeValue att1 = AttributeValue.builder()
                .n(String.valueOf("2020"))
                .build();

            AttributeValue att2 = AttributeValue.builder()
                .s("My Movie")
                .build();

            AttributeValue att3 = AttributeValue.builder()
                .s("No Information")
                .build();

            parameters.add(att1);
            parameters.add(att2);
            parameters.add(att3);

            executeStatementRequest(ddb, sqlStatement, parameters);
            System.out.println("Added new movie.");
        } catch (DynamoDbException e) {
            System.err.println(e.getMessage());
            System.exit(1);
        }
    }

    public static void updateTableItem(DynamoDbClient ddb){

        String sqlStatement = "UPDATE MoviesPartiQ SET info = 'directors\':
[\"Merian C. Cooper\", \"Ernest B. Schoedsack\"] where year=? and title=?";
        List<AttributeValue> parameters = new ArrayList<>();
        AttributeValue att1 = AttributeValue.builder()
            .n(String.valueOf("2013"))
            .build();

        AttributeValue att2 = AttributeValue.builder()
            .s("The East")
            .build();

        parameters.add(att1);
        parameters.add(att2);

        try {
            executeStatementRequest(ddb, sqlStatement, parameters);
        } catch (DynamoDbException e) {
    
```

```

        System.err.println(e.getMessage());
        System.exit(1);
    }
    System.out.println("Item was updated!");
}

// Query the table where the year is 2013.
public static void queryTable(DynamoDbClient ddb) {
    String sqlStatement = "SELECT * FROM MoviesPartiQ WHERE year = ? ORDER BY
year";
    try {

        List<AttributeValue> parameters = new ArrayList<>();
        AttributeValue att1 = AttributeValue.builder()
            .n(String.valueOf("2013"))
            .build();
        parameters.add(att1);

        // Get items in the table and write out the ID value.
        ExecuteStatementResponse response = executeStatementRequest(ddb,
sqlStatement, parameters);
        System.out.println("ExecuteStatement successful: "+
response.toString());

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
}

public static void deleteDynamoDBTable(DynamoDbClient ddb, String tableName) {

    DeleteTableRequest request = DeleteTableRequest.builder()
        .tableName(tableName)
        .build();

    try {
        ddb.deleteTable(request);

    } catch (DynamoDbException e) {
        System.err.println(e.getMessage());
        System.exit(1);
    }
    System.out.println(tableName +" was successfully deleted!");
}

private static ExecuteStatementResponse executeStatementRequest(DynamoDbClient
ddb, String statement, List<AttributeValue> parameters ) {
    ExecuteStatementRequest request = ExecuteStatementRequest.builder()
        .statement(statement)
        .parameters(parameters)
        .build();

    return ddb.executeStatement(request);
}

private static void processResults(ExecuteStatementResponse
executeStatementResult) {
    System.out.println("ExecuteStatement successful: "+
executeStatementResult.toString());
}
}

```

- For API details, see [ExecuteStatement](#) in *AWS SDK for Java 2.x API Reference*.

## JavaScript

### SDK for JavaScript V3

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create the client.

```
// Create the DynamoDB service client module using ES6 syntax.
import { DynamoDBClient } from "@aws-sdk/client-dynamodb";
// Set the AWS Region.
export const REGION = "eu-west-1"; // For example, "us-east-1".
// Create an Amazon DynamoDB service client object.
export const ddbClient = new DynamoDBClient({ region: REGION });
```

Create the document client.

```
// Create a service client module using ES6 syntax.
import { DynamoDBDocumentClient } from "@aws-sdk/lib-dynamodb";
import { ddbClient } from "./ddbClient.js";
// Set the AWS Region.
const REGION = "eu-west-1"; // For example, "us-east-1".

const marshallOptions = {
    // Whether to automatically convert empty strings, blobs, and sets to `null`.
    convertEmptyValues: false, // false, by default.
    // Whether to remove undefined values while marshalling.
    removeUndefinedValues: false, // false, by default.
    // Whether to convert typeof object to map attribute.
    convertClassInstanceToMap: false, // false, by default.
};

const unmarshallOptions = {
    // Whether to return numbers as a string instead of converting them to native
    // JavaScript numbers.
    wrapNumbers: false, // false, by default.
};

const translateConfig = { marshallOptions, unmarshallOptions };

// Create the DynamoDB document client.
const ddbDocClient = DynamoDBDocumentClient.from(ddbClient, translateConfig);

export { ddbDocClient };
```

Query single items.

```
/*
import fs from "fs";
// A practical functional library used to split the data into segments.
import * as R from "ramda";
import { ddbClient } from "../libs/ddbClient.js";
import { ddbDocClient } from "../libs/ddbDocClient.js";
import { BatchWriteCommand } from "@aws-sdk/lib-dynamodb";
import {
    CreateTableCommand,
    ExecuteStatementCommand,
} from "@aws-sdk/client-dynamodb";
if (process.argv.length < 6) {
```

```

        console.log(
            "Usage: node partiQL_basics.js <tableName> <movieYear1> <movieTitle1>
<producer1>\n" +
            "Example: node partiQL_basics.js Movies 2006 'The Departed' 'New View Films'"
        );
    }

    // Helper function to delay running the code while the AWS service calls wait for
    // responses.
    function wait(ms) {
        var start = Date.now();
        var end = start;
        while (end < start + ms) {
            end = Date.now();
        }
    }

    const tableName = process.argv[2];
    const movieTitle1 = process.argv[3];
    const movieYear1 = process.argv[4];
    const producer1 = process.argv[5];

    export const run = async (tableName, movieYear1, movieTitle1, producer1) => {
        try {
            console.log("Creating table ...");
            // Set the parameters.
            const params = {
                AttributeDefinitions: [
                    {
                        AttributeName: "title",
                        AttributeType: "S",
                    },
                    {
                        AttributeName: "year",
                        AttributeType: "N",
                    },
                ],
                KeySchema: [
                    {
                        AttributeName: "title",
                        KeyType: "HASH",
                    },
                    {
                        AttributeName: "year",
                        KeyType: "RANGE",
                    },
                ],
                ProvisionedThroughput: {
                    ReadCapacityUnits: 5,
                    WriteCapacityUnits: 5,
                },
                TableName: tableName,
            };
            const data = await ddbClient.send(new CreateTableCommand(params));
            console.log("Waiting for table to be created...");
            wait(10000);
            console.log(
                "Table created. Table name is ",
                data.TableDescription.TableName
            );
        } catch {
            // Before you run this example, download 'movies.json' from https://
            // docs.aws.amazon.com/amazondynamodb/latest/developerguide/GettingStarted.Js.02.html,
            // and put it in the same folder as the example.
            // Get the movie data parse to convert into a JSON object.
            const allMovies = JSON.parse(fs.readFileSync("moviedata.json", "utf8"));
        }
    }
}

```

```

// Split the table into segments of 25.
const dataSegments = R.splitEvery(25, allMovies);
// Loop batch write operation 10 times to upload 250 items.
console.log("Writing movies in batch to table...");
for (let i = 0; i < 10; i++) {
    const segment = dataSegments[i];
    for (let j = 0; j < 25; j++) {
        const params = {
            RequestItems: [
                [tableName]: [
                    {
                        // Destination Amazon DynamoDB table name.
                        PutRequest: {
                            Item: {
                                year: segment[j].year,
                                title: segment[j].title,
                                info: segment[j].info,
                            },
                        },
                    ],
                ],
            ],
        };
        const data = ddbDocClient.send(new BatchWriteCommand(params));
    }
}
wait(20000);
console.log("Success, movies written to table.");
try {
    const params = {
        Statement: "SELECT * FROM " + tableName + " where title=?",
        Parameters: [{ S: movieTitle1 }],
    };
    console.log("Getting movie....");

    console.log("Statement", params.Statement);
    const data = await ddbDocClient.send(
        new ExecuteStatementCommand(params)
    );
    for (let i = 0; i < data.Items.length; i++) {
        console.log(
            "Success. The query return the following data. Item " + i,
            data.Items[i].year,
            data.Items[i].title,
            data.Items[i].info
        );
    }
    try {
        const params = {
            Statement: "DELETE FROM " + tableName + " where title=? and year=?",
            Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
        };
        const data = await ddbDocClient.send(
            new ExecuteStatementCommand(params)
        );
        console.log("Success. Item deleted.");
        try {
            const params = {
                Statement:
                    "INSERT INTO " + tableName + " value {'title':?, 'year':?}",
                Parameters: [{ S: movieTitle1 }, { N: movieYear1 }],
            };
            const data = await ddbDocClient.send(
                new ExecuteStatementCommand(params)
            );
            console.log("Success. Item added.");
        }
    }
}

```

```

try {
    const params = {
        Statement:
            "UPDATE " +
            tableName +
            " SET Producer=? where title=? and year=?",
        Parameters: [
            { S: producer1 },
            { S: movieTitle1 },
            { N: movieYear1 },
        ],
    };

    console.log("Updating a single movie...");
    const data = await ddbDocClient.send(
        new ExecuteStatementCommand(params)
    );
    console.log("Success. Item updated.");
    return "Run successfully"; // For unit tests.
} catch (err) {
    console.log("Error updating item. ", err);
}
} catch (err) {
    console.log("Error adding items to table. ", err);
}
} catch (err) {
    console.log("Error deleting movie. ", err);
}
} catch (err) {
    console.log("Error getting movie. ", err);
}
} catch (err) {
    console.log("Error adding movies by batch. ", err);
}
} catch (err) {
    console.log("Error creating table. ", err);
}
};

run(tableName, movieYear1, movieTitle1, producer1);

```

- For API details, see [ExecuteStatement](#) in *AWS SDK for JavaScript API Reference*.

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

suspend fun main(args: Array<String>) {

    val usage = """
        Usage:
            <fileName>

        Where:
            fileName - The path to the moviedata.json you can download from the
            Amazon DynamoDB Developer Guide.
    
```

```

"""
if (args.size != 1) {
    println(usage)
    exitProcess(1)
}

val ddb = DynamoDbClient { region = "us-east-1" }
val tableName = "MoviesPartiQ"

// Get the moviedata.json from the Amazon DynamoDB Developer Guide.
val fileName = args[0]
println("Creating an Amazon DynamoDB table named MoviesPartiQ with a key named id and a sort key named title.")
createTablePartiQL(ddb, tableName, "year")
loadDataPartiQL(ddb, fileName)

println("***** Getting data from the MoviesPartiQ table.")
getMoviePartiQL(ddb)

println("***** Putting a record into the MoviesPartiQ table.")
putRecordPartiQL(ddb)

println("***** Updating a record.")
updateTableItemPartiQL(ddb)

println("***** Querying the movies released in 2013.")
queryTablePartiQL(ddb)

println("***** Deleting the MoviesPartiQ table.")
deleteTablePartiQL(tableName)
}

suspend fun createTablePartiQL(ddb: DynamoDbClient, tableNameVal: String, key: String) {

    val attDef = AttributeDefinition {
        attributeName = key
        attributeType = ScalarAttributeType.N
    }

    val attDef1 = AttributeDefinition {
        attributeName = "title"
        attributeType = ScalarAttributeType.S
    }

    val keySchemaVal = KeySchemaElement {
        attributeName = key
        keyType = KeyType.Hash
    }

    val keySchemaVal1 = KeySchemaElement {
        attributeName = "title"
        keyType = KeyType.Range
    }

    val provisionedVal = ProvisionedThroughput {
        readCapacityUnits = 10
        writeCapacityUnits = 10
    }

    val request = CreateTableRequest {
        attributeDefinitions = listOf(attDef, attDef1)
        keySchema = listOf(keySchemaVal, keySchemaVal1)
        provisionedThroughput = provisionedVal
        tableName = tableNameVal
    }
}

```

```

        }

        val response = ddb.createTable(request)
        ddb.waitUntilTableExists { // suspend call
            tableName = tableNameVal
        }
        println("The table was successfully created
        ${response.tableDescription?.tableArn}")
    }

suspend fun loadDataPartiQL(ddb: DynamoDbClient, fileName: String) {
    val sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?, 'title' : ?, 'info' : ?}"
    val parser = JsonFactory().createParser(File(fileName))
    val rootNode = ObjectMapper().readTree<JsonNode>(parser)
    val iter: Iterator<JsonNode> = rootNode.iterator()
    var currentNode: ObjectNode
    var t = 0

    while (iter.hasNext()) {

        if (t == 200)
            break

        currentNode = iter.next() as ObjectNode
        val year = currentNode.path("year").asInt()
        val title = currentNode.path("title").asText()
        val info = currentNode.path("info").toString()

        val parameters: MutableList<AttributeValue> = ArrayList<AttributeValue>()
        parameters.add(AttributeValue.N(year.toString()))
        parameters.add(AttributeValue.S(title))
        parameters.add(AttributeValue.S(info))

        executeStatementPartiQL(ddb, sqlStatement, parameters)
        println("Added Movie $title")
        parameters.clear()
        t++
    }
}

suspend fun getMoviePartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "SELECT * FROM MoviesPartiQ where year=? and title=?"
    val parameters: MutableList<AttributeValue> = ArrayList<AttributeValue>()
    parameters.add(AttributeValue.N("2012"))
    parameters.add(AttributeValue.S("The Perks of Being a Wallflower"))
    val response = executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("ExecuteStatement successful: $response")
}

suspend fun putRecordPartiQL(ddb: DynamoDbClient) {

    val sqlStatement = "INSERT INTO MoviesPartiQ VALUE {'year':?, 'title' : ?, 'info' : ?}"
    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
    parameters.add(AttributeValue.N("2020"))
    parameters.add(AttributeValue.S("My Movie"))
    parameters.add(AttributeValue.S("No Info"))
    executeStatementPartiQL(ddb, sqlStatement, parameters)
    println("Added new movie.")
}

suspend fun updateTableItemPartiQL(ddb: DynamoDbClient) {
    val sqlStatement = "UPDATE MoviesPartiQ SET info = 'directors\":[\"Merian C. Cooper\", \"Ernest B. Schoedsack\"]' where year=? and title=?"
    val parameters: MutableList<AttributeValue> = java.util.ArrayList()
}

```

```

        parameters.add(AttributeValue.N("2013"))
        parameters.add(AttributeValue.S("The East"))
        executeStatementPartiQL(ddb, sqlStatement, parameters)
        println("Item was updated!")
    }

    // Query the table where the year is 2013.
    suspend fun queryTablePartiQL(ddb: DynamoDbClient) {
        val sqlStatement = "SELECT * FROM MoviesPartiQ WHERE year = ?"

        val parameters: MutableList<AttributeValue> = java.util.ArrayList()
        parameters.add(AttributeValue.N("2013"))
        val response = executeStatementPartiQL(ddb, sqlStatement, parameters)
        println("ExecuteStatement successful: $response")
    }

    suspend fun deleteTablePartiQL(tableNameVal: String) {

        val request = DeleteTableRequest {
            tableName = tableNameVal
        }

        DynamoDbClient { region = "us-east-1" }.use { ddb ->
            ddb.deleteTable(request)
            println("$tableNameVal was deleted")
        }
    }

    suspend fun executeStatementPartiQL(
        ddb: DynamoDbClient,
        statementVal: String,
        parametersVal: List<AttributeValue>
    ): ExecuteStatementResponse {

        val request = ExecuteStatementRequest {
            statement = statementVal
            parameters = parametersVal
        }

        return ddb.executeStatement(request)
    }
}

```

- For API details, see [ExecuteStatement](#) in *AWS SDK for Kotlin API reference*.

## PHP

### SDK for PHP

#### Tip

To learn how to set up and run this example, see [GitHub](#).

```

namespace DynamoDb\PartiQL_Basics;

use Aws\DynamoDb\Marshaler;
use DynamoDb;
use DynamoDb\AttributeValue;

class GettingStartedWithPartiQL
{
    public function run()
    {
        echo("-----\n");

```

```

        print("Welcome to the Amazon DynamoDB - PartiQL getting started demo using
PHP!\n");
        echo("-----\n");

        $uuid = uniqid();
        $service = new DynamoDb\DynamoDBService();

        $tableName = "partiql_demo_table_{$uuid}";
        $service->createTable(
            $tableName,
            [
                new DynamoDBAttribute('year', 'N', 'HASH'),
                new DynamoDBAttribute('title', 'S', 'RANGE')
            ]
        );

        echo "Waiting for table...";
        $service->dynamoDbClient->waitForTable($tableName);
        echo "table $tableName found!\n";

        echo "What's the name of the last movie you watched?\n";
        while (empty($movieName)) {
            $movieName = testable_readline("Movie name: ");
        }
        echo "And what year was it released?\n";
        $movieYear = "year";
        while (!is_numeric($movieYear) || intval($movieYear) != $movieYear) {
            $movieYear = testable_readline("Year released: ");
        }
        $key = [
            'Item' => [
                'year' => [
                    'N' => "$movieYear",
                ],
                'title' => [
                    'S' => $movieName,
                ],
            ],
        ];
        list($statement, $parameters) = $service-
>buildStatementAndParameters("INSERT", $tableName, $key);
        $service->insertItemByPartiQL($statement, $parameters);

        echo "How would you rate the movie from 1-10?\n";
        $rating = 0;
        while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 ||
$rating > 10) {
            $rating = testable_readline("Rating (1-10): ");
        }
        echo "What was the movie about?\n";
        while (empty($plot)) {
            $plot = testable_readline("Plot summary: ");
        }
        $attributes = [
            new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
            new DynamoDBAttribute('plot', 'S', 'RANGE', $plot),
        ];

        list($statement, $parameters) = $service-
>buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
        $service->updateItemByPartiQL($statement, $parameters);
        echo "Movie added and updated.\n";
    }
}

```

```

$batch = json_decode(loadMovieData());

$service->writeBatch($tableName, $batch);

$movie = $service->getItemByPartiQL($tableName, $key);
echo "\nThe movie {$movie['Items'][0]['title']['S']} was released in
{$movie['Items'][0]['year']['N']}.\n";
echo "What rating would you like to give {$movie['Items'][0]['title']
['S']}?\n";
$rating = 0;
while (!is_numeric($rating) || intval($rating) != $rating || $rating < 1 || $rating > 10) {
    $rating = testable_readline("Rating (1-10): ");
}
$attributes = [
    new DynamoDBAttribute('rating', 'N', 'HASH', $rating),
    new DynamoDBAttribute('plot', 'S', 'RANGE', $plot)
];
list($statement, $parameters) = $service->buildStatementAndParameters("UPDATE", $tableName, $key, $attributes);
$service->updateItemByPartiQL($statement, $parameters);

$movie = $service->getItemByPartiQL($tableName, $key);
echo "Okay, you have rated {$movie['Items'][0]['title']['S']} as a
{$movie['Items'][0]['rating']['N']}.\n";

$service->deleteItemByPartiQL($statement, $parameters);
echo "But, bad news, this was a trap. That movie has now been deleted
because of your rating...harsh.\n";

echo "That's okay though. The book was better. Now, for something lighter,
in what year were you born?\n";
$birthYear = "not a number";
while (!is_numeric($birthYear) || $birthYear >= date("Y")) {
    $birthYear = testable_readline("Birth year: ");
}
$birthKey = [
    'Key' => [
        'year' => [
            'N' => "$birthYear",
        ],
    ],
];
$result = $service->query($tableName, $birthKey);
$marshal = new Marshaler();
echo "Here are the movies in our collection released the year you were
born:\n";
$oops = "Oops! There were no movies released in that year (that we know
of).\n";
$display = "";
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    $display .= $movie['title'] . "\n";
}
echo ($display) ?: $oops;

$yearsKey = [
    'Key' => [
        'year' => [
            'N' => [
                'minRange' => 1990,
                'maxRange' => 1999,
            ],
        ],
    ],
];

```

```

$filter = "year between 1990 and 1999";
echo "\nHere's a list of all the movies released in the 90s:\n";
$result = $service->scan($tableName, $yearsKey, $filter);
foreach ($result['Items'] as $movie) {
    $movie = $marshal->unmarshalItem($movie);
    echo $movie['title'] . "\n";
}

echo "\nCleaning up this demo by deleting table $tableName...\n";
$service->deleteTable($tableName);
}

public function insertItemByPartiQL(string $statement, array $parameters)
{
    $this->dynamoDbClient->executeStatement([
        'Statement' => "$statement",
        'Parameters' => $parameters,
    ]);
}

public function getItemByPartiQL(string $tableName, array $key): Result
{
    list($statement, $parameters) = $this-
>buildStatementAndParameters("SELECT", $tableName, $key['Item']);

    return $this->dynamoDbClient->executeStatement([
        'Parameters' => $parameters,
        'Statement' => $statement,
    ]);
}

public function updateItemByPartiQL(string $statement, array $parameters)
{
    $this->dynamoDbClient->executeStatement([
        'Statement' => $statement,
        'Parameters' => $parameters,
    ]);
}

public function deleteItemByPartiQL(string $statement, array $parameters)
{
    $this->dynamoDbClient->executeStatement([
        'Statement' => $statement,
        'Parameters' => $parameters,
    ]);
}

```

- For API details, see [ExecuteStatement](#) in *AWS SDK for PHP API Reference*.

## Python

### SDK for Python (Boto3)

#### Tip

To learn how to set up and run this example, see [GitHub](#).

Create a class that can run PartiQL statements.

```

from datetime import datetime
from decimal import Decimal
import logging

```

```

from pprint import pprint

import boto3
from botocore.exceptions import ClientError

from scaffold import Scaffold

logger = logging.getLogger(__name__)

class PartiQLWrapper:
    """
    Encapsulates a DynamoDB resource to run PartiQL statements.
    """
    def __init__(self, dyn_resource):
        """
        :param dyn_resource: A Boto3 DynamoDB resource.
        """
        self.dyn_resource = dyn_resource

    def run_partiql(self, statement, params):
        """
        Runs a PartiQL statement. A Boto3 resource is used even though
        `execute_statement` is called on the underlying `client` object because the
        resource transforms input and output from plain old Python objects (POPOs)
        to
        the DynamoDB format. If you create the client directly, you must do these
        transforms yourself.

        :param statement: The PartiQL statement.
        :param params: The list of PartiQL parameters. These are applied to the
                      statement in the order they are listed.
        :return: The items returned from the statement, if any.
        """
        try:
            output = self.dyn_resource.meta.client.execute_statement(
                Statement=statement, Parameters=params)
        except ClientError as err:
            if err.response['Error']['Code'] == 'ResourceNotFoundException':
                logger.error(
                    "Couldn't execute PartiQL '%s' because the table does not
exist.", statement)
            else:
                logger.error(
                    "Couldn't execute PartiQL '%s'. Here's why: %s: %s", statement,
                    err.response['Error']['Code'], err.response['Error']
                ['Message'])
            raise
        else:
            return output

```

Run a scenario that creates a table and runs PartiQL queries.

```

def run_scenario(scaffold, wrapper, table_name):
    logging.basicConfig(level=logging.INFO, format='%(levelname)s: %(message)s')

    print('*'*88)
    print("Welcome to the Amazon DynamoDB PartiQL single statement demo.")
    print('*'*88)

    print(f"Creating table '{table_name}' for the demo...")
    scaffold.create_table(table_name)
    print('*'*88)

```

```

        title = "24 Hour PartiQL People"
        year = datetime.now().year
        plot = "A group of data developers discover a new query language they can't
stop using."
        rating = Decimal('9.9')

        print(f"Inserting movie '{title}' released in {year}.")
        wrapper.run_partiql(
            f"INSERT INTO \"\{table_name\}\" VALUE {{'title': ?, 'year': ?, 'info': ?}}",
            [title, year, {'plot': plot, 'rating': rating}])
        print("Success!")
        print('*'*88)

        print(f"Getting data for movie '{title}' released in {year}.")
        output = wrapper.run_partiql(
            f"SELECT * FROM \"\{table_name\}\" WHERE title=? AND year=?", [title, year])
        for item in output['Items']:
            print(f"\n{item['title']}, {item['year']}")
            pprint(output['Items'])
        print('*'*88)

        rating = Decimal('2.4')
        print(f"Updating movie '{title}' with a rating of {float(rating)}.")
        wrapper.run_partiql(
            f"UPDATE \"\{table_name\}\" SET info.rating=? WHERE title=? AND year=?",
            [rating, title, year])
        print("Success!")
        print('*'*88)

        print(f"Getting data again to verify our update.")
        output = wrapper.run_partiql(
            f"SELECT * FROM \"\{table_name\}\" WHERE title=? AND year=?", [title, year])
        for item in output['Items']:
            print(f"\n{item['title']}, {item['year']}")
            pprint(output['Items'])
        print('*'*88)

        print(f"Deleting movie '{title}' released in {year}.")
        wrapper.run_partiql(
            f"DELETE FROM \"\{table_name\}\" WHERE title=? AND year=?", [title, year])
        print("Success!")
        print('*'*88)

        print(f"Deleting table '{table_name}'...")
        scaffold.delete_table()
        print('*'*88)

        print("\nThanks for watching!")
        print('*'*88)

if __name__ == '__main__':
    try:
        dyn_res = boto3.resource('dynamodb')
        scaffold = Scaffold(dyn_res)
        movies = PartiQLWrapper(dyn_res)
        run_scenario(scaffold, movies, 'doc-example-table-partiql-movies')
    except Exception as e:
        print(f"Something went wrong with the demo! Here's what: {e}")

```

- For API details, see [ExecuteStatement](#) in *AWS SDK for Python (Boto3) API Reference*.

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Cross-service examples for DynamoDB using AWS SDKs

The following sample applications use AWS SDKs to combine DynamoDB with other AWS services. Each example includes a link to GitHub, where you can find instructions on how to set up and run the application.

### Examples

- [Build an application to submit data to a DynamoDB table \(p. 1050\)](#)
- [Create an API Gateway REST API to track COVID-19 data \(p. 1051\)](#)
- [Create a messenger application with Step Functions \(p. 1052\)](#)
- [Create a dynamic web application to track DynamoDB data \(p. 1053\)](#)
- [Create a websocket chat application with API Gateway \(p. 1054\)](#)
- [Detect PPE in images with Amazon Rekognition using an AWS SDK \(p. 1055\)](#)
- [Invoke a Lambda function from a browser \(p. 1056\)](#)
- [Save EXIF and other image information using an AWS SDK \(p. 1056\)](#)
- [Use API Gateway to invoke a Lambda function \(p. 1057\)](#)
- [Use Step Functions to invoke Lambda functions \(p. 1058\)](#)
- [Use scheduled events to invoke a Lambda function \(p. 1059\)](#)

## Build an application to submit data to a DynamoDB table

The following code examples show how to build an application that submits data to an Amazon DynamoDB table and notifies you when a user updates the table.

Java

### SDK for Java 2.x

Shows how to create a dynamic web application that submits data using the Amazon DynamoDB Java API and sends a text message using the Amazon Simple Notification Service Java API.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

### Services used in this example

- DynamoDB
- Amazon SNS

## JavaScript

### SDK for JavaScript V3

This example shows how to build an app that enables users to submit data to an Amazon DynamoDB table, and send a text message to the administrator using Amazon Simple Notification Service (Amazon SNS).

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

This example is also available in the [AWS SDK for JavaScript v3 developer guide](#).

#### Services used in this example

- DynamoDB
- Amazon SNS

## Kotlin

### SDK for Kotlin

#### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

Shows how to create a native Android application that submits data using the Amazon DynamoDB Kotlin API and sends a text message using the Amazon SNS Kotlin API.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Amazon SNS

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Create an API Gateway REST API to track COVID-19 data

The following code example shows how to create a REST API that simulates a system to track daily cases of COVID-19 in the United States, using fictional data.

## Python

### SDK for Python (Boto3)

Shows how to use AWS Chalice with the AWS SDK for Python (Boto3) to create a serverless REST API that uses Amazon API Gateway, AWS Lambda, and Amazon DynamoDB. The REST API simulates a system that tracks daily cases of COVID-19 in the United States, using fictional data. Learn how to:

- Use AWS Chalice to define routes in Lambda functions that are called to handle REST requests that come through API Gateway.

- Use Lambda functions to retrieve and store data in a DynamoDB table to serve REST requests.
- Define table structure and security role resources in an AWS CloudFormation template.
- Use AWS Chalice and CloudFormation to package and deploy all necessary resources.
- Use CloudFormation to clean up all created resources.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- API Gateway
- AWS CloudFormation
- DynamoDB
- Lambda

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Create a messenger application with Step Functions

The following code example shows how to create an AWS Step Functions messenger application that retrieves message records from a database table.

Python

#### SDK for Python (Boto3)

Shows how to use the AWS SDK for Python (Boto3) with AWS Step Functions to create a messenger application that retrieves message records from an Amazon DynamoDB table and sends them with Amazon Simple Queue Service (Amazon SQS). The state machine integrates with an AWS Lambda function to scan the database for unsent messages.

- Create a state machine that retrieves and updates message records from an Amazon DynamoDB table.
- Update the state machine definition to also send messages to Amazon Simple Queue Service (Amazon SQS).
- Start and stop state machine runs.
- Connect to Lambda, DynamoDB, and Amazon SQS from a state machine by using service integrations.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Lambda
- Amazon SQS
- Step Functions

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

# Create a dynamic web application to track DynamoDB data

The following code examples show how to create a web application that tracks and reports on work items.

.NET

## AWS SDK for .NET

Shows how to use the Amazon DynamoDB .NET API to create a dynamic web application that tracks DynamoDB work data.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

### Services used in this example

- DynamoDB
- Amazon SES

Java

## SDK for Java 2.x

Shows how to use the Amazon DynamoDB API to create a dynamic web application that tracks DynamoDB work data.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

### Services used in this example

- DynamoDB
- Amazon SES

JavaScript

## SDK for JavaScript V3

Shows how to use the Amazon DynamoDB API to create a dynamic web application that tracks DynamoDB work data.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

### Services used in this example

- DynamoDB
- Amazon SES

Kotlin

## SDK for Kotlin

### Note

This is prerelease documentation for a feature in preview release. It is subject to change.

Shows how to use the Amazon DynamoDB API to create a dynamic web application that tracks DynamoDB work data.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

### Services used in this example

- DynamoDB
- Amazon SES

Python

#### SDK for Python (Boto3)

Shows how to use the AWS SDK for Python (Boto3) to create a web application that tracks work items in Amazon DynamoDB and emails reports by using Amazon Simple Email Service (Amazon SES). This example uses the Flask web framework to host a local website and render templated web pages.

- Integrate a Flask web application with AWS services.
- List, add, update, and delete items in a DynamoDB table.
- Send an email report of filtered work items using Amazon SES.
- Make AWS requests with an AWS Identity and Access Management (IAM) role that restricts permissions.
- Deploy and manage example resources with the included AWS CloudFormation script.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

### Services used in this example

- DynamoDB
- Amazon SES

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Create a websocket chat application with API Gateway

The following code example shows how to create a chat application that is served by a websocket API built on Amazon API Gateway.

Python

#### SDK for Python (Boto3)

Shows how to use the AWS SDK for Python (Boto3) with Amazon API Gateway V2 to create a websocket API that integrates with AWS Lambda and Amazon DynamoDB.

- Create a websocket API served by API Gateway.
- Define a Lambda handler that stores connections in DynamoDB and posts messages to other chat participants.

- Connect to the websocket chat application and send messages with the Websockets package.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- API Gateway
- DynamoDB
- Lambda

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Detect PPE in images with Amazon Rekognition using an AWS SDK

The following code examples show how to build an app that uses Amazon Rekognition to detect Personal Protective Equipment (PPE) in images.

Java

#### SDK for Java 2.x

Shows how to create an AWS Lambda function that detects images with Personal Protective Equipment.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

JavaScript

#### SDK for JavaScript V3

Shows how to use Amazon Rekognition with the AWS SDK for JavaScript to create an application to detect personal protective equipment (PPE) in images located in an Amazon Simple Storage Service (Amazon S3) bucket. The app saves the results to an Amazon DynamoDB table, and sends the admin an email notification with the results using Amazon Simple Email Service (Amazon SES).

Learn how to:

- Create an unauthenticated user using Amazon Cognito.
- Analyze images for PPE using Amazon Rekognition.
- Verify an email address for Amazon SES.
- Update a DynamoDB table with results.
- Send an email notification using Amazon SES.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Amazon Rekognition
- Amazon S3
- Amazon SES

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Invoke a Lambda function from a browser

The following code example shows how to invoke an AWS Lambda function from a browser.

JavaScript

#### SDK for JavaScript V2

You can create a browser-based application that uses an AWS Lambda function to update an Amazon DynamoDB table with user selections.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Lambda

#### SDK for JavaScript V3

You can create a browser-based application that uses an AWS Lambda function to update an Amazon DynamoDB table with user selections. This app uses AWS SDK for JavaScript v3.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Lambda

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Save EXIF and other image information using an AWS SDK

The following code example shows how to:

- Get EXIF information from a a JPG, JPEG, or PNG file.

- Upload the image file to an Amazon Simple Storage Service (Amazon S3) bucket.
- Use Amazon Rekognition (Amazon Rekognition) to identify the three top attributes (labels in Amazon Rekognition) in the file.
- Add the EXIF and label information to a Amazon DynamoDB (DynamoDB) table in the Region.

Rust

#### SDK for Rust

##### Note

This documentation is for an SDK in preview release. The SDK is subject to change and should not be used in production.

Get EXIF information from a JPG, JPEG, or PNG file, upload the image file to an Amazon Simple Storage Service bucket, use Amazon Rekognition to identify the three top attributes (*labels* in Amazon Rekognition) in the file, and add the EXIF and label information to a Amazon DynamoDB table in the Region.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Amazon Rekognition
- Amazon S3

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Use API Gateway to invoke a Lambda function

The following code examples show how to create an AWS Lambda function invoked by Amazon API Gateway.

Java

#### SDK for Java 2.x

Shows how to create an AWS Lambda function by using the Lambda Java runtime API. This example invokes different AWS services to perform a specific use case. This example demonstrates how to create a Lambda function invoked by Amazon API Gateway that scans an Amazon DynamoDB table for work anniversaries and uses Amazon Simple Notification Service (Amazon SNS) to send a text message to your employees that congratulates them at their one year anniversary date.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

JavaScript

### SDK for JavaScript V3

Shows how to create an AWS Lambda function by using the Lambda JavaScript runtime API. This example invokes different AWS services to perform a specific use case. This example demonstrates how to create a Lambda function invoked by Amazon API Gateway that scans an Amazon DynamoDB table for work anniversaries and uses Amazon Simple Notification Service (Amazon SNS) to send a text message to your employees that congratulates them at their one year anniversary date.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

This example is also available in the [AWS SDK for JavaScript v3 developer guide](#).

#### Services used in this example

- API Gateway
- DynamoDB
- Lambda
- Amazon SNS

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Use Step Functions to invoke Lambda functions

The following code examples show how to create an AWS Step Functions state machine that invokes AWS Lambda functions in sequence.

Java

### SDK for Java 2.x

Shows how to create an AWS serverless workflow by using AWS Step Functions and the AWS SDK for Java 2.x. Each workflow step is implemented using an AWS Lambda function.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

#### Services used in this example

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

JavaScript

### SDK for JavaScript V3

Shows how to create an AWS serverless workflow by using AWS Step Functions and the AWS SDK for JavaScript. Each workflow step is implemented using an AWS Lambda function.

Lambda is a compute service that enables you to run code without provisioning or managing servers. Step Functions is a serverless orchestration service that lets you combine Lambda functions and other AWS services to build business-critical applications.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

This example is also available in the [AWS SDK for JavaScript v3 developer guide](#).

### Services used in this example

- DynamoDB
- Lambda
- Amazon SES
- Step Functions

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

## Use scheduled events to invoke a Lambda function

The following code examples show how to create an AWS Lambda function invoked by an Amazon EventBridge scheduled event.

Java

### SDK for Java 2.x

Shows how to create an Amazon EventBridge scheduled event that invokes an AWS Lambda function. Configure EventBridge to use a cron expression to schedule when the Lambda function is invoked. In this example, you create a Lambda function by using the Lambda Java runtime API. This example invokes different AWS services to perform a specific use case. This example demonstrates how to create an app that sends a mobile text message to your employees that congratulates them at the one year anniversary date.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

### Services used in this example

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

JavaScript

### SDK for JavaScript V3

Shows how to create an Amazon EventBridge scheduled event that invokes an AWS Lambda function. Configure EventBridge to use a cron expression to schedule when the Lambda function is invoked. In this example, you create a Lambda function by using the Lambda JavaScript runtime API. This example invokes different AWS services to perform a specific use case. This example demonstrates how to create an app that sends a mobile text message to your employees that congratulates them at the one year anniversary date.

For complete source code and instructions on how to set up and run, see the full example on [GitHub](#).

This example is also available in the [AWS SDK for JavaScript v3 developer guide](#).

### Services used in this example

- DynamoDB
- EventBridge
- Lambda
- Amazon SNS

For a complete list of AWS SDK developer guides and code examples, see [Using DynamoDB with an AWS SDK \(p. 152\)](#). This topic also includes information about getting started and details about previous SDK versions.

# Security and compliance in Amazon DynamoDB

Cloud security at AWS is the highest priority. As an AWS customer, you benefit from a data center and network architecture that is built to meet the requirements of the most security-sensitive organizations.

Security is a shared responsibility between AWS and you. The [shared responsibility model](#) describes this as security of the cloud and security *in the cloud*:

- **Security of the cloud** – AWS is responsible for protecting the infrastructure that runs AWS services in the AWS Cloud. AWS also provides you with services that you can use securely. The effectiveness of our security is regularly tested and verified by third-party auditors as part of the [AWS compliance programs](#). To learn about the compliance programs that apply to DynamoDB, see [AWS Services in Scope by Compliance Program](#).
- **Security in the cloud** – Your responsibility is determined by the AWS service that you use. You are also responsible for other factors including the sensitivity of your data, your organization's requirements, and applicable laws and regulations.

This documentation will help you understand how to apply the shared responsibility model when using DynamoDB. The following topics show you how to configure DynamoDB to meet your security and compliance objectives. You'll also learn how to use other AWS services that can help you to monitor and secure your DynamoDB resources.

## Topics

- [Data protection in DynamoDB \(p. 1061\)](#)
- [Identity and access management \(p. 1070\)](#)
- [Compliance validation by industry for DynamoDB \(p. 1100\)](#)
- [Resilience and disaster recovery in Amazon DynamoDB \(p. 1101\)](#)
- [Infrastructure security in Amazon DynamoDB \(p. 1101\)](#)
- [Configuration and vulnerability analysis in Amazon DynamoDB \(p. 1107\)](#)
- [Security best practices for Amazon DynamoDB \(p. 1108\)](#)

## Data protection in DynamoDB

Amazon DynamoDB provides a highly durable storage infrastructure designed for mission-critical and primary data storage. Data is redundantly stored on multiple devices across multiple facilities in an Amazon DynamoDB Region.

DynamoDB protects user data stored at rest and also data in transit between on-premises clients and DynamoDB, and between DynamoDB and other AWS resources within the same AWS Region.

## Topics

- [DynamoDB encryption at rest \(p. 1062\)](#)
- [Data protection in DynamoDB Accelerator \(p. 1069\)](#)

- [Internetwork traffic privacy \(p. 1069\)](#)

## DynamoDB encryption at rest

All user data stored in Amazon DynamoDB is fully encrypted at rest. DynamoDB encryption at rest provides enhanced security by encrypting all your data at rest using encryption keys stored in [AWS Key Management Service \(AWS KMS\)](#). This functionality helps reduce the operational burden and complexity involved in protecting sensitive data. With encryption at rest, you can build security-sensitive applications that meet strict encryption compliance and regulatory requirements.

DynamoDB encryption at rest provides an additional layer of data protection by securing your data in an encrypted table—including its primary key, local and global secondary indexes, streams, global tables, backups, and DynamoDB Accelerator (DAX) clusters whenever the data is stored in durable media. Organizational policies, industry or government regulations, and compliance requirements often require the use of encryption at rest to increase the data security of your applications.

Encryption at rest integrates with AWS KMS for managing the encryption key that is used to encrypt your tables. For more information, see [AWS Key Management Service concepts](#) in the [AWS Key Management Service Developer Guide](#).

When creating a new table, you can choose one of the following AWS KMS keys to encrypt your table:

- AWS owned key – Default encryption type. The key is owned by DynamoDB (no additional charge).
- AWS managed key – The key is stored in your account and is managed by AWS KMS (AWS KMS charges apply).
- Customer managed key – The key is stored in your account and is created, owned, and managed by you. You have full control over the KMS key (AWS KMS charges apply).

### Note

When creating a new DAX cluster with encryption at rest enabled, an AWS managed key will be used to encrypt data at rest in the cluster.

When you access an encrypted table, DynamoDB decrypts the table data transparently. You can switch between the AWS owned key, AWS managed key, and customer managed key at any given time. You don't have to change any code or applications to use or manage encrypted tables. DynamoDB continues to deliver the same single-digit millisecond latency that you have come to expect, and all DynamoDB queries work seamlessly on your encrypted data.

You can specify an encryption key when you create a new table or switch the encryption keys on an existing table by using the AWS Management Console, AWS Command Line Interface (AWS CLI), or the Amazon DynamoDB API. To learn how, see [Managing encrypted tables in DynamoDB \(p. 1065\)](#).

Encryption at rest using the AWS owned key is offered at no additional charge. However, AWS KMS charges apply for an AWS managed key and for a customer managed key. For more information about pricing, see [AWS KMS pricing](#).

DynamoDB encryption at rest is available in all AWS Regions, including the AWS China (Beijing) and AWS China (Ningxia) Regions and the AWS GovCloud (US) Regions. For more information, see [Encryption at rest: How it works \(p. 1062\)](#) and [DynamoDB encryption at rest usage notes \(p. 1064\)](#).

## Encryption at rest: How it works

Amazon DynamoDB encryption at rest encrypts your data using 256-bit Advanced Encryption Standard (AES-256), which helps secure your data from unauthorized access to the underlying storage.

Encryption at rest integrates with AWS Key Management Service (AWS KMS) for managing the encryption key that is used to encrypt your tables.

When creating a new table or switching the encryption keys on an existing table, you can choose one of the following AWS KMS keys:

- AWS owned key – Default encryption type. The key is owned by DynamoDB (no additional charge).
- AWS managed key – The key is stored in your account and is managed by AWS KMS (AWS KMS charges apply).
- Customer managed key – The key is stored in your account and is created, owned, and managed by you. You have full control over the KMS key (AWS KMS charges apply).

## AWS owned keys

AWS owned keys are not stored in your AWS account. They are part of a collection of KMS keys that AWS owns and manages for use in multiple AWS accounts. AWS services can use AWS owned keys to protect your data.

You cannot view, manage, or use AWS owned keys, or audit their use. However, you do not need to do any work or change any programs to protect the keys that encrypt your data.

You are not charged a monthly fee or a usage fee for use of AWS owned keys, and they do not count against AWS KMS quotas for your account.

## AWS managed keys

AWS managed keys are KMS keys in your account that are created, managed, and used on your behalf by an AWS service that is integrated with AWS KMS. You can view the AWS managed keys in your account, view their key policies, and audit their use in AWS CloudTrail logs. However, you cannot manage these KMS keys or change their permissions.

Encryption at rest automatically integrates with AWS KMS for managing the AWS managed key for DynamoDB (`aws/dynamodb`) that is used to encrypt your tables. If an AWS managed key doesn't exist when you create your encrypted DynamoDB table, AWS KMS automatically creates a new key for you. This key is used with encrypted tables that are created in the future. AWS KMS combines secure, highly available hardware and software to provide a key management system scaled for the cloud.

For more information about managing permissions of the AWS managed key, see [Authorizing use of the AWS managed key](#) in the *AWS Key Management Service Developer Guide*.

## Customer managed keys

Customer managed keys are KMS keys in your AWS account that you create, own, and manage. You have full control over these KMS keys, including establishing and maintaining their key policies, IAM policies, and grants; enabling and disabling them; rotating their cryptographic material; adding tags; creating aliases that refer to them; and scheduling them for deletion. For more information about managing permissions of a customer managed key, see [Customer managed key policy](#).

When you specify a customer managed key as the table-level encryption key, the DynamoDB table, local and global secondary indexes, and streams are encrypted with the same customer managed key. On-demand backups are encrypted with the table-level encryption key that is specified at the time the backup is created. Updating the table-level encryption key does not change the encryption key that is associated with existing on-demand backups.

Setting the state of the customer managed key to disabled or scheduling it for deletion prevents all users and the DynamoDB service from being able to encrypt or decrypt data and to perform read and write operations on the table. DynamoDB must have access to your encryption key to ensure that you can continue to access your table and to prevent data loss.

If you disable your customer managed key or schedule it for deletion, your table status becomes **Inaccessible**. To ensure that you can continue working with the table, you must provide DynamoDB

access to the specified encryption key within seven days. As soon as the service detects that your encryption key is inaccessible, DynamoDB sends you an email notification to alert you.

**Note**

- If your customer managed key remains inaccessible to the DynamoDB service for longer than seven days, the table is archived and can no longer be accessed. DynamoDB creates an on-demand backup of your table, and you are billed for it. You can use this on-demand backup to restore your data to a new table. To initiate the restore, the last customer managed key on the table must be enabled, and DynamoDB must have access to it.
- If your customer managed key that was used to encrypt a global table replica is inaccessible DynamoDB will remove this replica from the replication group. The replica will not be deleted and replication will stop from and to this region, 20 hours after detecting the customer managed key as inaccessible.

## Notes on using AWS managed keys

Amazon DynamoDB can't read your table data unless it has access to the KMS key stored in your AWS KMS account. DynamoDB uses envelope encryption and key hierarchy to encrypt data. Your AWS KMS encryption key is used to encrypt the root key of this key hierarchy. For more information, see [Envelope encryption](#) in the *AWS Key Management Service Developer Guide*.

You can use AWS CloudTrail and Amazon CloudWatch Logs to track the requests that DynamoDB sends to AWS KMS on your behalf. For more information, see [Monitoring DynamoDB interaction with AWS KMS](#) in the *AWS Key Management Service Developer Guide*.

DynamoDB doesn't call AWS KMS for every DynamoDB operation. The key is refreshed once every 5 minutes per client connection with active traffic.

Ensure that you have configured the SDK to reuse connections. Otherwise, you will experience latencies from DynamoDB having to reestablish new AWS KMS cache entries for each DynamoDB operation. In addition, you might potentially have to face higher AWS KMS and CloudTrail costs. For example, to do this using the Node.js SDK, you can create a new HTTPS agent with `keepAlive` turned on. For more information, see [Configuring maxSockets in Node.js](#) in the *AWS SDK for JavaScript Developer Guide*.

## DynamoDB encryption at rest usage notes

Consider the following when you are using encryption at rest in Amazon DynamoDB.

### All table data is encrypted

Server-side encryption at rest is enabled on all DynamoDB table data and cannot be disabled. You cannot encrypt only a subset of items in a table. DynamoDB has encrypted all existing tables that were previously unencrypted by using the AWS owned key.

Encryption at rest only encrypts data while it is static (at rest) on a persistent storage media. If data security is a concern for data in transit or data in use, you might need to take additional measures:

- Data in transit: All your data in DynamoDB is encrypted in transit (except the data in DAX). By default, communications to and from DynamoDB use the HTTPS protocol, which protects network traffic by using Secure Sockets Layer (SSL)/Transport Layer Security (TLS) encryption.
- Data in use: Protect your data before sending it to DynamoDB using client-side encryption. For more information, see [Client-side and server-side encryption](#) in the *Amazon DynamoDB Encryption Client Developer Guide*.

You can use streams with encrypted tables. DynamoDB streams are always encrypted with a table-level encryption key. For more information, see [Change data capture for DynamoDB Streams \(p. 598\)](#).

DynamoDB backups are encrypted, and the table that is restored from a backup also has encryption enabled. You can use the AWS owned key, AWS managed key, or customer managed key to encrypt your backup data. For more information, see [Using On-Demand backup and restore for DynamoDB \(p. 629\)](#).

Local secondary indexes and global secondary indexes are encrypted using the same key as the base table.

## Encryption types

### Note

Customer Managed Key (CMK) is not supported in Global Table Version 2017. If you want to use a CMK in a DynamoDB Global Table, you need to upgrade the table to Global Table Version 2019 and then enable it.

On the AWS Management Console, the encryption type is `KMS` when you use the AWS managed key or customer managed key to encrypt your data. The encryption type is `DEFAULT` when you use the AWS owned key. In the Amazon DynamoDB API, the encryption type is `KMS` when you use the AWS managed key or customer managed key. In the absence of encryption type, your data is encrypted using the AWS owned key. You can switch between the AWS owned key, AWS managed key, and customer managed key at any given time. You can use the console, the AWS Command Line Interface (AWS CLI), or the Amazon DynamoDB API to switch the encryption keys.

Note the following limitations when using customer managed keys:

- You cannot use a customer managed key with DynamoDB Accelerator (DAX) clusters. For more information, see [DAX encryption at rest \(p. 744\)](#).
- You can use a customer managed key to encrypt tables that use transactions. However, to ensure durability for propagation of transactions, a copy of the transaction request is temporarily stored by the service and encrypted using an AWS owned key. Committed data in your tables and secondary indexes is always encrypted at rest using your customer managed key.
- You can use a customer managed key to encrypt tables that use Contributor Insights. However, data that is transmitted to Amazon CloudWatch is encrypted with an AWS owned key.
- When you transition to a new customer managed key, be sure to keep the original key enabled until the process is complete. AWS will still need the original key to decrypt the data before encrypting it with the new key. The process will be complete when the table's `SSEDescription` Status is `ENABLED` and the `KMSMasterKeyArn` of the new customer managed key is displayed. At this point the original key can be disabled or scheduled for deletion.
- Once the new customer managed key is displayed, the table and any new on-demand backups are encrypted with the new key.
- Any existing on-demand backups remain encrypted with the customer managed key that was used when those backups were created. You will need that same key to restore those backups. You can identify the key for the period when each backup was created by using the `DescribeBackup` API to view that backup's `SSEDescription`.
- If you disable your customer managed key or schedule it for deletion, any data in DynamoDB Streams is still subject to a 24-hour lifetime. Any unretrieved activity data is eligible for trimming when it is older than 24 hours.
- If you disable your customer managed key or schedule it for deletion, Time to Live (TTL) deletes continue for 30 minutes. These TTL deletes continue to be emitted to DynamoDB Streams and are subject to the standard trimming/retention interval.

## Managing encrypted tables in DynamoDB

You can use the AWS Management Console or the AWS Command Line Interface (AWS CLI) to specify the encryption key on new tables and update the encryption keys on existing tables in Amazon DynamoDB.

## Topics

- [Specifying the encryption key for a new table \(p. 1066\)](#)
- [Updating an encryption key \(p. 1068\)](#)

## Specifying the encryption key for a new table

Follow these steps to specify the encryption key on a new table using the Amazon DynamoDB console or the AWS CLI.

### Creating an encrypted table (console)

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose **Create Table**. For the **Table name**, enter **Music**. For the primary key, enter **Artist**, and for the sort key, enter **SongTitle**, both as strings.
4. In **Settings**, make sure that **Customize settings** is selected.

#### Note

If **Use default settings** is selected, tables are encrypted at rest with the AWS owned key at no additional cost.

5. Under **Encryption at rest**, choose an encryption type:
  - **Owned by Amazon DynamoDB.** The AWS KMS key is owned and managed by DynamoDB. You are not charged an additional fee for using this key.
  - **AWS managed key** Key alias: aws/dynamodb. The key is stored in your account and is managed by AWS Key Management Service (AWS KMS). AWS KMS charges apply.
  - **Stored in your account, and owned and managed by you.** The key is stored in your account and is managed by AWS Key Management Service (AWS KMS). AWS KMS charges apply.

#### Note

If you select to own and manage your own key, make sure the KMS Key Policy is appropriately set. For more information see [Key policy for a customer managed key](#).

6. Choose **Create table** to create the encrypted table. To confirm the encryption type, select the table details on the **Overview** tab and review the **Additional details** section.

### Creating an encrypted table (AWS CLI)

Use the AWS CLI to create a table with the default AWS owned key, the AWS managed key, or a customer managed key for Amazon DynamoDB.

#### To create an encrypted table with the default AWS owned key

- Create the encrypted **Music** table as follows.

```
aws dynamodb create-table \
  --table-name Music \
  --attribute-definitions \
    AttributeName=Artist,AttributeType=S \
    AttributeName=SongTitle,AttributeType=S \
  --key-schema \
    AttributeName=Artist,KeyType=HASH \
    AttributeName=SongTitle,KeyType=RANGE \
  --provisioned-throughput \
    ReadCapacityUnits=10,WriteCapacityUnits=5
```

**Note**

This table is now encrypted using the default AWS owned key in the DynamoDB service account.

**To create an encrypted table with the AWS managed key for DynamoDB**

- Create the encrypted Music table as follows.

```
aws dynamodb create-table \
    --table-name Music \
    --attribute-definitions \
        AttributeName=Artist,AttributeType=S \
        AttributeName=SongTitle,AttributeType=S \
    --key-schema \
        AttributeName=Artist,KeyType=HASH \
        AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput \
        ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --sse-specification Enabled=true,SSEType=KMS
```

The SSEDescription status of the table description is set to ENABLED and the SSEType is KMS.

```
"SSEDescription": {
    "SSEType": "KMS",
    "Status": "ENABLED",
    "KMSMasterKeyArn": "arn:aws:kms:us-east-1:123456789012:key/abcd1234-abcd-1234-a123-
ab1234a1b234",
}
```

**To create an encrypted table with a customer managed key for DynamoDB**

- Create the encrypted Music table as follows.

```
aws dynamodb create-table \
    --table-name Music \
    --attribute-definitions \
        AttributeName=Artist,AttributeType=S \
        AttributeName=SongTitle,AttributeType=S \
    --key-schema \
        AttributeName=Artist,KeyType=HASH \
        AttributeName=SongTitle,KeyType=RANGE \
    --provisioned-throughput \
        ReadCapacityUnits=10,WriteCapacityUnits=5 \
    --sse-specification Enabled=true,SSEType=KMS,KMSMasterKeyId=abcd1234-abcd-1234-a123-
ab1234a1b234
```

The SSEDescription status of the table description is set to ENABLED and the SSEType is KMS.

```
"SSEDescription": {
    "SSEType": "KMS",
    "Status": "ENABLED",
    "KMSMasterKeyArn": "arn:aws:kms:us-east-1:123456789012:key/abcd1234-abcd-1234-a123-
ab1234a1b234",
}
```

## Updating an encryption key

You can also use the DynamoDB console or the AWS CLI to update the encryption keys of an existing table between an AWS owned key, AWS managed key, and customer managed key at any time.

### Updating an encryption key (console)

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the table that you want to update.
4. Select the **Actions** dropdown, and then select the **Update settings** option.
5. Go to the **Additional settings** tab.
6. Under **Encryption**, choose **Manage encryption**.
7. Choose an encryption type:
  - **Owned by Amazon DynamoDB.** The AWS KMS key is owned and managed by DynamoDB. You are not charged an additional fee for using this key.
  - **AWS managed key** Key alias: aws/dynamodb. The key is stored in your account and is managed by AWS Key Management Service. (AWS KMS). AWS KMS charges apply.
  - **Stored in your account, and owned and managed by you.** The key is stored in your account and is managed by AWS Key Management Service. (AWS KMS). AWS KMS charges apply.

#### Note

If you select to own and manage your own key, make sure the KMS Key Policy is appropriately set. For more information see [Key policy for a customer managed key](#).

Then choose **Save** to update the encrypted table. To confirm the encryption type, check the table details under the **Overview** tab.

### Updating an encryption key (AWS CLI)

The following examples show how to update an encrypted table using the AWS CLI.

#### To update an encrypted table with the default AWS owned key

- Update the encrypted Music table, as in the following example.

```
aws dynamodb update-table \
--table-name Music \
--sse-specification Enabled=false
```

#### Note

This table is now encrypted using the default AWS owned key in the DynamoDB service account.

#### To update an encrypted table with the AWS managed key for DynamoDB

- Update the encrypted Music table, as in the following example.

```
aws dynamodb update-table \
--table-name Music \
--sse-specification Enabled=true
```

The SSEDescription status of the table description is set to `ENABLED` and the SSEType is `KMS`.

```
"SSEDescription": {  
    "SSEType": "KMS",  
    "Status": "ENABLED",  
    "KMSMasterKeyArn": "arn:aws:kms:us-east-1:123456789012:key/abcd1234-abcd-1234-a123-  
ab1234a1b234",  
}
```

### To update an encrypted table with a customer managed key for DynamoDB

- Update the encrypted `Music` table, as in the following example.

```
aws dynamodb update-table \  
    --table-name Music \  
    --sse-specification Enabled=true,SSEType=KMS,KMSMasterKeyId=abcd1234-abcd-1234-a123-  
ab1234a1b234
```

The SSEDescription status of the table description is set to `ENABLED` and the SSEType is `KMS`.

```
"SSEDescription": {  
    "SSEType": "KMS",  
    "Status": "ENABLED",  
    "KMSMasterKeyArn": "arn:aws:kms:us-east-1:123456789012:key/abcd1234-abcd-1234-a123-  
ab1234a1b234",  
}
```

## Data protection in DynamoDB Accelerator

Amazon DynamoDB Accelerator (DAX) encryption at rest provides an additional layer of data protection by helping secure your data from unauthorized access to the underlying storage. Organizational policies, industry or government regulations, and compliance requirements might require the use of encryption at rest to protect your data. You can use encryption to increase the data security of your applications that are deployed in the cloud.

For more information about data protection in DAX, see [DAX encryption at rest \(p. 744\)](#).

## Internet traffic privacy

Connections are protected both between Amazon DynamoDB and on-premises applications and between DynamoDB and other AWS resources within the same AWS Region.

### Traffic between service and on-premises clients and applications

You have two connectivity options between your private network and AWS:

- An AWS Site-to-Site VPN connection. For more information, see [What is AWS Site-to-Site VPN?](#) in the [AWS Site-to-Site VPN User Guide](#).
- An AWS Direct Connect connection. For more information, see [What is AWS Direct Connect?](#) in the [AWS Direct Connect User Guide](#).

Access to DynamoDB via the network is through AWS published APIs. Clients must support Transport Layer Security (TLS) 1.0. We recommend TLS 1.2 or above. Clients must also support cipher suites

with Perfect Forward Secrecy (PFS), such as Ephemeral Diffie-Hellman (DHE) or Elliptic Curve Diffie-Hellman Ephemeral (ECDHE). Most modern systems such as Java 7 and later support these modes. Additionally, you must sign requests using an access key ID and a secret access key that are associated with an IAM principal, or you can use the [AWS Security Token Service \(STS\)](#) to generate temporary security credentials to sign requests.

## Traffic between AWS resources in the same Region

An Amazon Virtual Private Cloud (Amazon VPC) endpoint for DynamoDB is a logical entity within a VPC that allows connectivity only to DynamoDB. The Amazon VPC routes requests to DynamoDB and routes responses back to the VPC. For more information, see [VPC endpoints](#) in the *Amazon VPC User Guide*. For example policies that you can use to control access from VPC endpoints, see [Using IAM policies to control access to DynamoDB](#).

# Identity and access management

IAM administrators control who can be authenticated (signed in) and authorized (have permissions) to use Amazon DynamoDB resources. You can use AWS Identity and Access Management (IAM) to manage access permissions and implement security policies for both Amazon DynamoDB and DynamoDB Accelerator (DAX).

## Topics

- [Identity and access management in Amazon DynamoDB \(p. 1070\)](#)
- [Identity and access management in DynamoDB Accelerator \(p. 1100\)](#)

## Identity and access management in Amazon DynamoDB

Access to Amazon DynamoDB requires credentials. Those credentials must have permissions to access AWS resources, such as an Amazon DynamoDB table or an Amazon Elastic Compute Cloud (Amazon EC2) instance. The following sections provide details on how you can use [AWS Identity and Access Management \(IAM\)](#) and DynamoDB to help secure access to your resources.

- [Authentication \(p. 1070\)](#)
- [Access control \(p. 1071\)](#)

## Authentication

You can access AWS as any of the following types of identities:

- **AWS account root user**

When you create an AWS account, you begin with one sign-in identity that has complete access to all AWS services and resources in the account. This identity is called the AWS account *root user* and is accessed by signing in with the email address and password that you used to create the account. We strongly recommend that you do not use the root user for your everyday tasks. Safeguard your root user credentials and use them to perform the tasks that only the root user can perform. For the complete list of tasks that require you to sign in as the root user, see [Tasks that require root user credentials](#) in the *AWS General Reference*.

- **IAM users and groups**

An [IAM user](#) is an identity within your AWS account that has specific permissions for a single person or application. An IAM user can have long-term credentials such as a user name and password or a set of access keys. To learn how to generate access keys, see [Managing access keys for IAM users](#) in the *IAM User Guide*. When you generate access keys for an IAM user, make sure you view and securely save the key pair. You cannot recover the secret access key in the future. Instead, you must generate a new access key pair.

An [IAM group](#) is an identity that specifies a collection of IAM users. You can't sign in as a group. You can use groups to specify permissions for multiple users at a time. Groups make permissions easier to manage for large sets of users. For example, you could have a group named *IAMAdmins* and give that group permissions to administer IAM resources.

Users are different from roles. A user is uniquely associated with one person or application, but a role is intended to be assumable by anyone who needs it. Users have permanent long-term credentials, but roles provide temporary credentials. To learn more, see [When to create an IAM user \(instead of a role\)](#) in the *IAM User Guide*.

- **IAM role**

An [IAM role](#) is an IAM identity that you can create in your account that has specific permissions. An IAM role is similar to an IAM user in that it is an AWS identity with permissions policies that determine what the identity can and cannot do in AWS. However, instead of being uniquely associated with one person, a role is intended to be assumable by anyone who needs it. Also, a role does not have standard long-term credentials such as a password or access keys associated with it. Instead, when you assume a role, it provides you with temporary security credentials for your role session. IAM roles with temporary credentials are useful in the following situations:

- **Federated user access** – Instead of creating an IAM user, you can use existing identities from AWS Directory Service, your enterprise user directory, a web identity provider, or the IAM Identity Center identity store. These identities are known as *federated identities*. To assign permissions to federated identities, you can create a role and define permissions for the role. When an external identity authenticates, the identity is associated with the role and is granted the permissions that are defined by it. If you use IAM Identity Center, you configure a permission set. IAM Identity Center correlates the permission set to a role in IAM to control what your identities can access after they authenticate. For more information about identity federation, see [Creating a role for a third-party Identity Provider](#) in the *IAM User Guide*. For more information about IAM Identity Center, see [What is IAM Identity Center?](#) in the *AWS IAM Identity Center (successor to AWS Single Sign-On) User Guide*.
- **AWS service access** – A service role is an [IAM role](#) that a service assumes to perform actions on your behalf. An IAM administrator can create, modify, and delete a service role from within IAM. For more information, see [Creating a role to delegate permissions to an AWS service](#) in the *IAM User Guide*.
- **Applications running on Amazon EC2** – You can use an IAM role to manage temporary credentials for applications that are running on an EC2 instance and making AWS CLI or AWS API requests. This is preferable to storing access keys within the EC2 instance. To assign an AWS role to an EC2 instance and make it available to all of its applications, you create an instance profile that is attached to the instance. An instance profile contains the role and enables programs that are running on the EC2 instance to get temporary credentials. For more information, see [Using an IAM role to grant permissions to applications running on Amazon EC2 instances](#) in the *IAM User Guide*.

## Access control

You can have valid credentials to authenticate your requests, but unless you have permissions you cannot create or access Amazon DynamoDB resources. For example, you must have permissions to create an Amazon DynamoDB table.

The following sections describe how to manage permissions for Amazon DynamoDB. We recommend that you read the overview first.

- Overview of managing access (p. 1072)
- Using identity-based policies (IAM Policies) (p. 1075)
- DynamoDB API permissions reference (p. 1084)
- Using conditions (p. 1085)

## Overview of managing access permissions to your Amazon DynamoDB Resources

Every AWS resource is owned by an AWS account, and permissions to create or access a resource are governed by permissions policies. An account administrator can attach permissions policies to IAM identities (that is, users, groups, and roles), and some services (such as AWS Lambda) also support attaching permissions policies to resources.

### Note

An *account administrator* (or administrator user) is a user with administrator privileges. For more information, see [IAM Best Practices](#) in the *IAM User Guide*.

When granting permissions, you decide who is getting the permissions, the resources they get permissions for, and the specific actions that you want to allow on those resources.

### Topics

- [DynamoDB resources and operations \(p. 1072\)](#)
- [Understanding resource ownership \(p. 1072\)](#)
- [Managing access to resources \(p. 1073\)](#)
- [Specifying policy elements: Actions, effects, and principals \(p. 1074\)](#)
- [Specifying conditions in a policy \(p. 1075\)](#)

## DynamoDB resources and operations

In DynamoDB, the primary resources are *tables*. DynamoDB also supports additional resource types, *indexes*, and *streams*. However, you can create indexes and streams only in the context of an existing DynamoDB table. These are referred to as *subresources*.

These resources and subresources have unique Amazon Resource Names (ARNs) associated with them, as shown in the following table.

Resource Type	ARN Format
Table	<code>arn:aws:dynamodb:<i>region</i>:<i>account-id</i>:table/<i>table-name</i></code>
Index	<code>arn:aws:dynamodb:<i>region</i>:<i>account-id</i>:table/<i>table-name</i>/index/<i>index-name</i></code>
Stream	<code>arn:aws:dynamodb:<i>region</i>:<i>account-id</i>:table/<i>table-name</i>/stream/<i>stream-label</i></code>

DynamoDB provides a set of operations to work with DynamoDB resources. For a list of available operations, see [Amazon DynamoDB Actions](#).

## Understanding resource ownership

The AWS account owns the resources that are created in the account, regardless of who created the resources. Specifically, the resource owner is the AWS account of the [principal entity](#) (that is, the AWS

account root user, an IAM user, or an IAM role) that authenticates the resource creation request. The following examples illustrate how this works:

- If you use your AWS account root user credentials to create a table, your AWS account is the owner of the resource (in DynamoDB, the resource is a table).
- If you create an IAM user in your AWS account and grant permissions to create a table to that user, the user can create a table. However, your AWS account, to which the user belongs, owns the table resource.
- If you create an IAM role in your AWS account with permissions to create a table, anyone who can assume the role can create a table. Your AWS account, to which the role belongs, owns the table resource.

## Managing access to resources

A *permissions policy* describes who has access to what. The following section explains the available options for creating permissions policies.

### Note

This section discusses using IAM in the context of DynamoDB. It doesn't provide detailed information about the IAM service. For complete IAM documentation, see [What Is IAM?](#) in the *IAM User Guide*. For information about IAM policy syntax and descriptions, see [AWS IAM Policy Reference](#) in the *IAM User Guide*.

Policies attached to an IAM identity are referred to as *identity-based* policies (IAM policies). Policies attached to a resource are referred to as *resource-based* policies. DynamoDB supports only identity-based policies (IAM policies).

### Topics

- [Identity-based policies \(IAM policies\) \(p. 1073\)](#)
- [Resource-based policies \(p. 1074\)](#)

## Identity-based policies (IAM policies)

You can attach policies to IAM identities. For example, you can do the following:

- **Attach a permissions policy to a user or a group in your account** – To grant a user permissions to create an Amazon DynamoDB resource, such as a table, you can attach a permissions policy to a user or group that the user belongs to.
- **Attach a permissions policy to a role (grant cross-account permissions)** – You can attach an identity-based permissions policy to an IAM role to grant cross-account permissions. For example, the administrator in account A can create a role to grant cross-account permissions to another AWS account (for example, account B) or an AWS service as follows:
  1. Account A administrator creates an IAM role and attaches a permissions policy to the role that grants permissions on resources in account A.
  2. Account A administrator attaches a trust policy to the role identifying account B as the principal who can assume the role.
  3. Account B administrator can then delegate permissions to assume the role to any users in account B. Doing this allows users in account B to create or access resources in account A. The principal in the trust policy can also be an AWS service principal if you want to grant an AWS service permissions to assume the role.

For more information about using IAM to delegate permissions, see [Access Management](#) in the *IAM User Guide*.

The following is an example policy that grants permissions for one DynamoDB action (`dynamodb:ListTables`). The wildcard character (\*) in the Resource value means that you can use this action to obtain the names of all the tables owned by the AWS account in the current AWS Region.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "ListTables",  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:ListTables"  
            ],  
            "Resource": "*"  
        }  
    ]  
}
```

For more information about using identity-based policies with DynamoDB, see [Using identity-based policies \(IAM policies\) with Amazon DynamoDB \(p. 1075\)](#). For more information about users, groups, roles, and permissions, see [Identities \(Users, Groups, and Roles\)](#) in the *IAM User Guide*.

### Resource-based policies

Other services, such as Amazon S3, also support resource-based permissions policies. For example, you can attach a policy to an S3 bucket to manage access permissions to that bucket. DynamoDB doesn't support resource-based policies.

## Specifying policy elements: Actions, effects, and principals

For each DynamoDB resource, the service defines a set of API operations. To grant permissions for these API operations, DynamoDB defines a set of actions that you can specify in a policy. Some API operations can require permissions for more than one action in order to perform the API operation. For more information about resources and API operations, see [DynamoDB resources and operations \(p. 1072\)](#) and [DynamoDB Actions](#).

The following are the most basic policy elements:

- **Resource** – You use an Amazon Resource Name (ARN) to identify the resource that the policy applies to. For more information, see [DynamoDB resources and operations \(p. 1072\)](#).
- **Action** – You use action keywords to identify resource operations that you want to allow or deny. For example, `dynamodb:Query` allows the user permissions to perform the DynamoDB `Query` operation.
- **Effect** – You specify the effect, either allow or deny, when the user requests the specific action. If you don't explicitly grant access to (allow) a resource, access is implicitly denied. You can also explicitly deny access to a resource, which you might do to make sure that a user cannot access it, even if a different policy grants access.
- **Principal** – In identity-based policies (IAM policies), the user that the policy is attached to is the implicit principal. For resource-based policies, you specify the user, account, service, or other entity that you want to receive permissions (applies to resource-based policies only). DynamoDB doesn't support resource-based policies.

To learn more about IAM policy syntax and descriptions, see [AWS IAM Policy Reference](#) in the *IAM User Guide*.

For a list showing all of the Amazon DynamoDB API operations and the resources that they apply to, see [DynamoDB API permissions: Actions, resources, and conditions reference \(p. 1084\)](#).

## Specifying conditions in a policy

When you grant permissions, you can use the access policy language to specify the conditions when a policy should take effect. For example, you might want a policy to be applied only after a specific date. For more information about specifying conditions in a policy language, see [Condition](#) in the *IAM User Guide*.

To express conditions, you use predefined condition keys. There are AWS-wide condition keys and DynamoDB-specific keys that you can use as appropriate. For a complete list of AWS-wide keys, see [Available Keys for Conditions](#) in the *IAM User Guide*. For a complete list of DynamoDB-specific keys, see [Using IAM policy conditions for fine-grained access control \(p. 1085\)](#).

## Using identity-based policies (IAM policies) with Amazon DynamoDB

This topic covers using identity-based AWS Identity and Access Management (IAM) policies with Amazon DynamoDB and provides examples. The examples show how an account administrator can attach permissions policies to IAM identities (users, groups, and roles) and thereby grant permissions to perform operations on Amazon DynamoDB resources.

### Important

We recommend that you first review the introductory topics that explain the basic concepts and options available to manage access to your DynamoDB resources. For more information, see [Overview of managing access permissions to your Amazon DynamoDB Resources \(p. 1072\)](#).

The sections in this topic cover the following:

- [IAM permissions required to use the Amazon DynamoDB console \(p. 1076\)](#)
- [AWS managed \(predefined\) IAM policies for Amazon DynamoDB \(p. 1076\)](#)
- [Customer managed policy examples \(p. 1076\)](#)

The following is an example of a permissions policy.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "DescribeQueryScanBooksTable",  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:DescribeTable",  
                "dynamodb:Query",  
                "dynamodb:Scan"  
            ],  
            "Resource": "arn:aws:dynamodb:us-west-2:account-id:table/Books"  
        }  
    ]  
}
```

The preceding policy has one statement that grants permissions for three DynamoDB actions (`dynamodb:DescribeTable`, `dynamodb:Query`, and `dynamodb:Scan`) on a table in the `us-west-2` AWS Region, which is owned by the AWS account specified by `account-id`. The *Amazon Resource Name (ARN)* in the `Resource` value specifies the table that the permissions apply to.

## IAM permissions required to use the Amazon DynamoDB console

To work with the DynamoDB console, a user must have a minimum set of permissions that allow the user to work with their AWS account's DynamoDB resources. In addition to these DynamoDB permissions, the console requires permissions:

- Amazon CloudWatch permissions to display metrics and graphs.
- AWS Data Pipeline permissions to export and import DynamoDB data.
- AWS Identity and Access Management permissions to access roles necessary for exports and imports.
- Amazon Simple Notification Service permissions to notify you whenever a CloudWatch alarm is triggered.
- AWS Lambda permissions to process DynamoDB Streams records.

If you create an IAM policy that is more restrictive than the minimum required permissions, the console won't function as intended for users with that IAM policy. To ensure that those users can still use the DynamoDB console, also attach the [AmazonDynamoDBReadOnlyAccess](#) AWS managed policy to the user, as described in [AWS managed \(predefined\) IAM policies for Amazon DynamoDB \(p. 1076\)](#).

You don't need to allow minimum console permissions for users who are making calls only to the AWS CLI or the Amazon DynamoDB API.

## AWS managed (predefined) IAM policies for Amazon DynamoDB

AWS addresses some common use cases by providing standalone IAM policies that are created and administered by AWS. These AWS managed policies grant necessary permissions for common use cases so that you can avoid having to investigate which permissions are needed. For more information, see [AWS Managed Policies](#) in the *IAM User Guide*.

The following AWS managed policies, which you can attach to users in your account, are specific to DynamoDB and are grouped by use-case scenario:

- **AmazonDynamoDBReadOnlyAccess** – Grants read-only access to DynamoDB resources through the AWS Management Console.
- **AmazonDynamoDBFullAccess** – Grants full access to DynamoDB resources through the AWS Management Console.

You can review these AWS managed permissions policies by signing in to the IAM console and searching for specific policies there.

**Important**

The best practice is to create custom IAM policies that grant [least-privilege](#) to the IAM users, roles, or groups that require them.

## Customer managed policy examples

In this section, you can find policy examples that grant permissions for various DynamoDB actions. These policies work when you use AWS SDKs or the AWS CLI. When you use the console, you need to grant additional permissions that are specific to the console. For more information, see [IAM permissions required to use the Amazon DynamoDB console \(p. 1076\)](#).

**Note**

All of the following policy examples use one of the AWS Regions and contain fictitious account IDs and table names.

Examples:

- [IAM policy to grant permissions to all DynamoDB actions on a table \(p. 1077\)](#)

- [IAM policy to grant read-only permissions on items in a DynamoDB table \(p. 1077\)](#)
- [IAM policy to grant access to a specific DynamoDB table and its indexes \(p. 1078\)](#)
- [IAM policy to read, write, update, and delete access on a DynamoDB table \(p. 1078\)](#)
- [IAM policy to separate DynamoDB environments in the same AWS account \(p. 1079\)](#)
- [IAM policy to prevent the purchase of DynamoDB reserved capacity \(p. 1081\)](#)
- [IAM policy to grant read access for a DynamoDB stream only \(not for the table\) \(p. 1082\)](#)
- [IAM policy to allow an AWS Lambda function to access DynamoDB stream records \(p. 1083\)](#)
- [IAM policy for read and write access to a DynamoDB Accelerator \(DAX\) cluster \(p. 1084\)](#)

The *IAM User Guide*, includes [three additional DynamoDB examples](#):

- [Amazon DynamoDB: Allows Access to a Specific Table](#)
- [Amazon DynamoDB: Allows Access to Specific Columns](#)
- [Amazon DynamoDB: Allows Row-Level Access to DynamoDB Based on an Amazon Cognito ID](#)

## IAM policy to grant permissions to all DynamoDB actions on a table

The following policy grants permissions for *all* DynamoDB actions on a table called Books. The resource ARN specified in the Resource identifies a table in a specific AWS Region. If you replace the table name Books in the Resource ARN with a wildcard character (\*), *all* DynamoDB actions are allowed on *all* tables in the account. Carefully consider the possible security implications before using a wildcard character on this or any IAM policy.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AllAPIActionsOnBooks",
            "Effect": "Allow",
            "Action": "dynamodb:*",
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
        }
    ]
}
```

### Note

This is an example of using a wildcard character (\*) to allow *all* actions, including administration, data operations, monitoring, and purchase of DynamoDB reserved capacity. Instead, it is a best practice to explicitly specify each action to be granted and only what that user, role, or group needs.

## IAM policy to grant read-only permissions on items in a DynamoDB table

The following permissions policy grants permissions for the `GetItem`, `BatchGetItem`, `Scan`, `Query`, and `ConditionCheckItem` DynamoDB actions only, and as a result, sets read-only access on the Books table.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "ReadOnlyAPIActionsOnBooks",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Scan",
                "dynamodb:Query",
                "dynamodb:ConditionCheckItem"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
        }
    ]
}
```

```

        "dynamodb:BatchGetItem",
        "dynamodb:Scan",
        "dynamodb:Query",
        "dynamodb:ConditionCheckItem"
    ],
    "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
}
]
}

```

## IAM policy to grant access to a specific DynamoDB table and its indexes

The following policy grants permissions for data modification actions on a DynamoDB table called Books and all of that table's indexes. For more information about how indexes work, see [Improving data access with secondary indexes \(p. 497\)](#).

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AccessTableAllIndexesOnBooks",
            "Effect": "Allow",
            "Action": [
                "dynamodb:PutItem",
                "dynamodb:UpdateItem",
                "dynamodb:DeleteItem",
                "dynamodb:BatchWriteItem",
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Scan",
                "dynamodb:Query",
                "dynamodb:ConditionCheckItem"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/Books",
                "arn:aws:dynamodb:us-west-2:123456789012:table/Books/index/*"
            ]
        }
    ]
}

```

## IAM policy to read, write, update, and delete access on a DynamoDB table

Use this policy if you need to allow your application to create, read, update, and delete data in Amazon DynamoDB tables, indexes, and streams. Substitute the AWS Region name, your account ID, and the table name or wildcard character (\*) where appropriate.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "DynamoDBIndexAndStreamAccess",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetShardIterator",
                "dynamodb:Scan",
                "dynamodb:Query",
                "dynamodb:DescribeStream",
                "dynamodb:GetRecords",
                "dynamodb>ListStreams"
            ],
            "Resource": [

```

```

        "arn:aws:dynamodb:us-west-2:123456789012:table/Books/index/*",
        "arn:aws:dynamodb:us-west-2:123456789012:table/Books/stream/*"
    ],
},
{
    "Sid": "DynamoDBTableAccess",
    "Effect": "Allow",
    "Action": [
        "dynamodb:BatchGetItem",
        "dynamodb:BatchWriteItem",
        "dynamodb:ConditionCheckItem",
        "dynamodb:PutItem",
        "dynamodb:DescribeTable",
        "dynamodb:DeleteItem",
        "dynamodb:GetItem",
        "dynamodb:Scan",
        "dynamodb:Query",
        "dynamodb:UpdateItem"
    ],
    "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books"
},
{
    "Sid": "DynamoDBDescribeLimitsAccess",
    "Effect": "Allow",
    "Action": "dynamodb:DescribeLimits",
    "Resource": [
        "arn:aws:dynamodb:us-west-2:123456789012:table/Books",
        "arn:aws:dynamodb:us-west-2:123456789012:table/Books/index/*"
    ]
}
]
}

```

To expand this policy to cover all DynamoDB tables in all AWS Regions for this account, use a wildcard (\*) for the Region and table name. For example:

```

"Resource": [
    "arn:aws:dynamodb:*:123456789012:table/*",
    "arn:aws:dynamodb:*:123456789012:table/*/*index/*"
]

```

## IAM policy to separate DynamoDB environments in the same AWS account

Suppose that you have separate environments where each environment maintains its own version of a table named `ProductCatalog`. If you create two `ProductCatalog` tables in the same AWS account, work in one environment might affect the other environment because of the way that permissions are set up. For example, quotas on the number of concurrent control plane operations (such as `CreateTable`) are set at the AWS account level.

As a result, each action in one environment reduces the number of operations available in the other environment. There is also a risk that the code in one environment might accidentally access tables in the other environment.

### Note

If you want to separate production and test workloads to help control an event's potential "blast radius," the best practice is to create separate AWS accounts for test and production workloads. For more information, see [AWS Account Management and Separation](#).

Suppose further that you have two developers, Amit and Alice, who are testing the `ProductCatalog` table. Instead of each developer requiring a separate AWS account, your developers can share the same test AWS account. In this test account, you can create a copy of the same table for each developer to work on, such as `Alice_ProductCatalog` and `Amit_ProductCatalog`. In this case, you can create

IAM users Alice and Amit in the AWS account that you created for the test environment. You then can grant permissions to these users to perform DynamoDB actions on the tables that they own.

To grant these IAM user permissions, you can do either of the following:

- Create a separate policy for each user, and then attach each policy to its user separately. For example, you can attach the following policy to user Alice to allow her access to DynamoDB actions on the Alice\_ProductCatalog table:

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AllAPIActionsOnAliceTable",
            "Effect": "Allow",
            "Action": [
                "dynamodb>DeleteItem",
                "dynamodb>DescribeContributorInsights",
                "dynamodb>RestoreTableToPointInTime",
                "dynamodb>ListTagsOfResource",
                "dynamodb>CreateTableReplica",
                "dynamodb>UpdateContributorInsights",
                "dynamodb>CreateBackup",
                "dynamodb>DeleteTable",
                "dynamodb>UpdateTableReplicaAutoScaling",
                "dynamodb>UpdateContinuousBackups",
                "dynamodb>TagResource",
                "dynamodb>DescribeTable",
                "dynamodb>GetItem",
                "dynamodb>DescribeContinuousBackups",
                "dynamodb>BatchGetItem",
                "dynamodb>UpdateTimeToLive",
                "dynamodb>BatchWriteItem",
                "dynamodb>ConditionCheckItem",
                "dynamodb>UntagResource",
                "dynamodb>PutItem",
                "dynamodb>Scan",
                "dynamodb>Query",
                "dynamodb>UpdateItem",
                "dynamodb>DeleteTableReplica",
                "dynamodb>DescribeTimeToLive",
                "dynamodb>RestoreTableFromBackup",
                "dynamodb>UpdateTable",
                "dynamodb>DescribeTableReplicaAutoScaling",
                "dynamodb>GetShardIterator",
                "dynamodb>DescribeStream",
                "dynamodb>GetRecords",
                "dynamodb>DescribeLimits",
                "dynamodb>ListStreams"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/
Alice_ProductCatalog/*"
        }
    ]
}
```

Then, you can create a similar policy with a different resource (the Amit\_ProductCatalog table) for user Amit.

- Instead of attaching policies to individual users, you can use IAM policy variables to write a single policy and attach it to a group. You need to create a group and, for this example, add both users Alice and Amit to the group. The following example grants permissions to perform all DynamoDB actions on the \${aws:username}\_ProductCatalog table. The policy variable \${aws:username} is replaced

by the requester's user name when the policy is evaluated. For example, if Alice sends a request to add an item, the action is allowed only if Alice is adding items to the `Alice_ProductCatalog` table.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "ActionsOnUserSpecificTable",
            "Effect": "Allow",
            "Action": [
                "dynamodb:PutItem",
                "dynamodb:UpdateItem",
                "dynamodb>DeleteItem",
                "dynamodb:BatchWriteItem",
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Scan",
                "dynamodb:Query",
                "dynamodb:ConditionCheckItem"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/
${aws:username}_ProductCatalog"
        },
        {
            "Sid": "AdditionalPrivileges",
            "Effect": "Allow",
            "Action": [
                "dynamodb>ListTables",
                "dynamodb:DescribeTable",
                "dynamodb:DescribeContributorInsights"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/*"
        }
    ]
}
```

### Note

When using IAM policy variables, you must explicitly specify the 2012-10-17 version of the IAM policy language in the policy. The default version of the IAM policy language (2008-10-17) does not support policy variables.

Instead of identifying a specific table as a resource as you normally would, you could use a wildcard character (\*) to grant permissions on all tables where the table name is prefixed with the IAM user that is making the request, as shown in the following example.

```
"Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/${aws:username}_*"
```

## IAM policy to prevent the purchase of DynamoDB reserved capacity

With Amazon DynamoDB reserved capacity, you pay a one-time, upfront fee and commit to paying for a minimum usage level at significant savings over a period of time. You can use the AWS Management Console to view and purchase reserved capacity. However, you might not want all of the users in your organization to be able to purchase reserved capacity. For more information about reserved capacity, see [Amazon DynamoDB pricing](#).

DynamoDB provides the following API operations for controlling access to reserved capacity management:

- `dynamodb:DescribeReservedCapacity` – Returns the reserved capacity purchases that are currently in effect.

- `dynamodb:DescribeReservedCapacityOfferings` – Returns details about the reserved capacity plans that are currently offered by AWS.
- `dynamodb:PurchaseReservedCapacityOfferings` – Performs an actual purchase of reserved capacity.

The AWS Management Console uses these API actions to display reserved capacity information and make purchases. You cannot call these operations from an application program because they can be accessed only from the console. However, you can allow or deny access to these operations in an IAM permissions policy.

The following policy allows users to view reserved capacity purchases and offerings by using the AWS Management Console — but new purchases are denied.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AllowReservedCapacityDescriptions",
            "Effect": "Allow",
            "Action": [
                "dynamodb:DescribeReservedCapacity",
                "dynamodb:DescribeReservedCapacityOfferings"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:/*"
        },
        {
            "Sid": "DenyReservedCapacityPurchases",
            "Effect": "Deny",
            "Action": "dynamodb:PurchaseReservedCapacityOfferings",
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:/*"
        }
    ]
}
```

Note that this policy uses the wildcard character (\*) to allow describe permissions for all, and to deny the purchase of DynamoDB reserved capacity for all.

## IAM policy to grant read access for a DynamoDB stream only (not for the table)

When you enable DynamoDB Streams on a table, information is captured about every modification to items in the table. For more information, see [Change data capture for DynamoDB Streams \(p. 598\)](#).

In some cases, you might want to prevent an application from reading data from a DynamoDB table, but still allow access to that table's streams. For example, you can configure AWS Lambda to poll a stream and invoke a Lambda function when item updates are detected, and then perform additional processing.

The following actions are available for controlling access to DynamoDB streams:

- `dynamodb:DescribeStream`
- `dynamodb:GetRecords`
- `dynamodb:GetShardIterator`
- `dynamodb>ListStreams`

The following example policy grants users permissions to access the streams of a table named `GameScores`. The wildcard character (\*) in the ARN matches any stream associated with that table.

```
{
```

```

    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AccessGameScoresStreamOnly",
            "Effect": "Allow",
            "Action": [
                "dynamodb:DescribeStream",
                "dynamodb:GetRecords",
                "dynamodb:GetShardIterator",
                "dynamodb>ListStreams"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores/stream/*"
        }
    ]
}

```

Note that this policy grants access to the GameScores table's streams, but not to the table itself.

### IAM policy to allow an AWS Lambda function to access DynamoDB stream records

If you want certain actions to be performed based on events in a DynamoDB stream, you can write an AWS Lambda function that is triggered by these events. A Lambda function such as this needs permissions to read data from a DynamoDB stream. For more information about using Lambda with DynamoDB Streams, see [DynamoDB Streams and AWS Lambda triggers \(p. 621\)](#).

To grant permissions to Lambda, use the permissions policy that is associated with the Lambda function's IAM role (also known as an execution role). Specify this policy when you create the Lambda function.

For example, you can associate the following permissions policy with an execution role to grant Lambda permissions to perform the DynamoDB Streams actions listed.

```

{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AllowLambdaFunctionInvocation",
            "Effect": "Allow",
            "Action": [
                "lambda:InvokeFunction"
            ],
            "Resource": [
                "*"
            ]
        },
        {
            "Sid": "APIAccessForDynamoDBStreams",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetRecords",
                "dynamodb:GetShardIterator",
                "dynamodb:DescribeStream",
                "dynamodb>ListStreams"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores/stream/*"
        }
    ]
}

```

For more information, see [AWS Lambda permissions](#) in the *AWS Lambda Developer Guide*.

## IAM policy for read and write access to a DynamoDB Accelerator (DAX) cluster

The following policy allows read, write, update, and delete access to a DynamoDB Accelerator (DAX) cluster, but not to the associated DynamoDB table. To use this policy, substitute the AWS Region name, your account ID, and the name of your DAX cluster.

### Note

This policy gives access to DAX cluster, but not to the associated DynamoDB table. Make sure that your DAX cluster has the correct policy to perform these same operations on the DynamoDB table on your behalf.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "AmazonDynamoDBDAXDataOperations",  
            "Effect": "Allow",  
            "Action": [  
                "dax:GetItem",  
                "dax:PutItem",  
                "dax:ConditionCheckItem",  
                "dax:BatchGetItem",  
                "dax:BatchWriteItem",  
                "dax:DeleteItem",  
                "dax:Query",  
                "dax:UpdateItem",  
                "dax:Scan"  
            ],  
            "Resource": "arn:aws:dax:eu-west-1:123456789012:cache/MyDAXCluster"  
        }  
    ]  
}
```

To expand this policy to cover DAX access for all AWS Regions for an account, use a wildcard character (\*) for the Region name.

```
"Resource": "arn:aws:dax:*:123456789012:cache/MyDAXCluster"
```

## DynamoDB API permissions: Actions, resources, and conditions reference

When you are setting up [Access control \(p. 1071\)](#) and writing a permissions policy that you can attach to an IAM identity (identity-based policies), you can use the list of [Actions, resources, and condition keys for Amazon DynamoDB](#) in the *IAM User Guide* as a reference. The page lists each DynamoDB API operation, the corresponding actions for which you can grant permissions to perform the action, and the AWS resource for which you can grant the permissions. You specify the actions in the policy's `Action` field, and you specify the resource value in the policy's `Resource` field.

You can use AWS-wide condition keys in your DynamoDB policies to express conditions. For a complete list of AWS-wide keys, see the [IAM JSON policy elements reference](#) in the *IAM User Guide*.

In addition to the AWS-wide condition keys, DynamoDB has its own specific keys that you can use in conditions. For more information, see [Using IAM policy conditions for fine-grained access control \(p. 1085\)](#).

### Related topics

- [Access control \(p. 1071\)](#)

- Using IAM policy conditions for fine-grained access control (p. 1085)

## Using IAM policy conditions for fine-grained access control

When you grant permissions in DynamoDB, you can specify conditions that determine how a permissions policy takes effect.

### Overview

In DynamoDB, you have the option to specify conditions when granting permissions using an IAM policy (see [Access control \(p. 1071\)](#)). For example, you can:

- Grant permissions to allow users read-only access to certain items and attributes in a table or a secondary index.
- Grant permissions to allow users write-only access to certain attributes in a table, based upon the identity of that user.

In DynamoDB, you can specify conditions in an IAM policy using condition keys, as illustrated in the use case in the following section.


#### Note

Some AWS services also support tag-based conditions; however, DynamoDB does not.


### Permissions use case

In addition to controlling access to DynamoDB API actions, you can also control access to individual data items and attributes. For example, you can do the following:

- Grant permissions on a table, but restrict access to specific items in that table based on certain primary key values. An example might be a social networking app for games, where all users' saved game data is stored in a single table, but no users can access data items that they do not own, as shown in the following illustration:



- Hide information so that only a subset of attributes is visible to the user. An example might be an app that displays flight data for nearby airports, based on the user's location. Airline names, arrival and departure times, and flight numbers are all displayed. However, attributes such as pilot names or the number of passengers are hidden, as shown in the following illustration:



To implement this kind of fine-grained access control, you write an IAM permissions policy that specifies conditions for accessing security credentials and the associated permissions. You then apply the policy to IAM users, groups, or roles that you create using the IAM console. Your IAM policy can restrict access to individual items in a table, access to the attributes in those items, or both at the same time.

You can optionally use web identity federation to control access by users who are authenticated by Login with Amazon, Facebook, or Google. For more information, see [Using web identity federation \(p. 1094\)](#).

You use the IAM Condition element to implement a fine-grained access control policy. By adding a Condition element to a permissions policy, you can allow or deny access to items and attributes in DynamoDB tables and indexes, based upon your particular business requirements.

As an example, consider a mobile gaming app that lets players select from and play a variety of different games. The app uses a DynamoDB table named GameScores to keep track of high scores and other user data. Each item in the table is uniquely identified by a user ID and the name of the game that the user played. The GameScores table has a primary key consisting of a partition key (`UserID`) and sort key (`GameTitle`). Users only have access to game data associated with their user ID. A user who wants to play a game must belong to an IAM role named GameRole, which has a security policy attached to it.

To manage user permissions in this app, you could write a permissions policy such as the following:

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AllowAccessToOnlyItemsMatchingUserID",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Query",
                "dynamodb:PutItem",
                "dynamodb:UpdateItem",
                "dynamodb:DeleteItem",
                "dynamodb:BatchWriteItem"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores"
            ],
            "Condition": {

```

```
        "ForAllValues:StringEquals": {
            "dynamodb:LeadingKeys": [
                "${www.amazon.com:user_id}"
            ],
            "dynamodb:Attributes": [
                "UserId",
                "GameTitle",
                "Wins",
                "Losses",
                "TopScore",
                "TopScoreDateTime"
            ]
        },
        "StringEqualsIfExists": {
            "dynamodb:Select": "SPECIFIC_ATTRIBUTES"
        }
    }
}
```

In addition to granting permissions for specific DynamoDB actions (`Action` element) on the `GameScores` table (`Resource` element), the `Condition` element uses the following condition keys specific to DynamoDB that limit the permissions as follows:

- **dynamodb:LeadingKeys** – This condition key allows users to access only the items where the partition key value matches their user ID. This ID, \${www.amazon.com:user\_id}, is a substitution variable. For more information about substitution variables, see [Using web identity federation \(p. 1094\)](#).
  - **dynamodb:Attributes** – This condition key limits access to the specified attributes so that only the actions listed in the permissions policy can return values for these attributes. In addition, the `StringEqualsIfExists` clause ensures that the app must always provide a list of specific attributes to act upon and that the app can't request all attributes.

When an IAM policy is evaluated, the result is always either true (access is allowed) or false (access is denied). If any part of the Condition element is false, the entire policy evaluates to false and access is denied.

## **Important**

If you use `dynamodb:Attributes`, you must specify the names of all of the primary key and index key attributes for the table and any secondary indexes that are listed in the policy. Otherwise, DynamoDB can't use these key attributes to perform the requested action.

IAM policy documents can contain only the following Unicode characters: horizontal tab (U+0009), linefeed (U+000A), carriage return (U+000D), and characters in the range U+0020 to U+00FF.

## Specifying conditions: Using condition keys

AWS provides a set of predefined condition keys (AWS-wide condition keys) for all AWS services that support IAM for access control. For example, you can use the `aws:SourceIp` condition key to check the requester's IP address before allowing an action to be performed. For more information and a list of the AWS-wide keys, see [Available Keys for Conditions](#) in the IAM User Guide.

The following table shows the DynamoDB service-specific condition keys that apply to DynamoDB.

DynamoDB Condition Key	Description
dynamodb:LeadingKeys	Represents the first key attribute of a table—in other words, the partition key. The key name <code>LeadingKeys</code> is plural, even if the key is used with

DynamoDB Condition Key	Description
	single-item actions. In addition, you must use the <code>ForAllValues</code> modifier when using <code>LeadingKeys</code> in a condition.
<code>dynamodb:Select</code>	Represents the <code>Select</code> parameter of a <code>Query</code> or <code>Scan</code> request. <code>Select</code> can be any of the following values: <ul style="list-style-type: none"> <li>• <code>ALL_ATTRIBUTES</code></li> <li>• <code>ALL_PROJECTED_ATTRIBUTES</code></li> <li>• <code>SPECIFIC_ATTRIBUTES</code></li> <li>• <code>COUNT</code></li> </ul>
<code>dynamodb:Attributes</code>	Represents a list of the attribute names in a request, or the attributes that are returned from a request. <code>Attributes</code> values are named the same way and have the same meaning as the parameters for certain DynamoDB API actions, as shown following: <ul style="list-style-type: none"> <li>• <code>AttributesToGet</code> Used by: <code>BatchGetItem</code>, <code>.GetItem</code>, <code>Query</code>, <code>Scan</code></li> <li>• <code>AttributeUpdates</code> Used by: <code>UpdateItem</code></li> <li>• <code>Expected</code> Used by: <code>DeleteItem</code>, <code>PutItem</code>, <code>UpdateItem</code></li> <li>• <code>Item</code> Used by: <code>PutItem</code></li> <li>• <code>ScanFilter</code> Used by: <code>Scan</code></li> </ul>
<code>dynamodb:ReturnValues</code>	Represents the <code>ReturnValues</code> parameter of a request. <code>ReturnValues</code> can be any of the following values: <ul style="list-style-type: none"> <li>• <code>ALL_OLD</code></li> <li>• <code>UPDATED_OLD</code></li> <li>• <code>ALL_NEW</code></li> <li>• <code>UPDATED_NEW</code></li> <li>• <code>NONE</code></li> </ul>
<code>dynamodb:ReturnConsumedCapacity</code>	Represents the <code>ReturnConsumedCapacity</code> parameter of a request. <code>ReturnConsumedCapacity</code> can be one of the following values: <ul style="list-style-type: none"> <li>• <code>TOTAL</code></li> <li>• <code>NONE</code></li> </ul>

## Limiting user access

Many IAM permissions policies allow users to access only those items in a table where the partition key value matches the user identifier. For example, the game app preceding limits access in this way so that users can only access game data that is associated with their user ID. The IAM substitution variables  `${www.amazon.com:user_id}`,  `${graph.facebook.com:id}`, and

`#{accounts.google.com:sub}` contain user identifiers for Login with Amazon, Facebook, and Google. To learn how an application logs in to one of these identity providers and obtains these identifiers, see [Using web identity federation \(p. 1094\)](#).

**Note**

Each of the examples in the following section sets the `Effect` clause to `Allow` and specifies only the actions, resources, and parameters that are allowed. Access is permitted only to what is explicitly listed in the IAM policy.

In some cases, it is possible to rewrite these policies so that they are deny-based (that is, setting the `Effect` clause to `Deny` and inverting all of the logic in the policy). However, we recommend that you avoid using deny-based policies with DynamoDB because they are difficult to write correctly, compared to allow-based policies. In addition, future changes to the DynamoDB API (or changes to existing API inputs) can render a deny-based policy ineffective.

### Example policies: Using conditions for fine-grained access control

This section shows several policies for implementing fine-grained access control on DynamoDB tables and indexes.

**Note**

All examples use the us-west-2 Region and contain fictitious account IDs.

#### 1: Grant permissions that limit access to items with a specific partition key value

The following permissions policy grants permissions that allow a set of DynamoDB actions on the `GamesScore` table. It uses the `dynamodb:LeadingKeys` condition key to limit user actions only on the items whose `UserID` partition key value matches the Login with Amazon unique user ID for this app.

**Important**

The list of actions does not include permissions for `Scan` because `Scan` returns all items regardless of the leading keys.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "FullAccessToUserItems",  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:GetItem",  
                "dynamodb:BatchGetItem",  
                "dynamodb:Query",  
                "dynamodb:PutItem",  
                "dynamodb:UpdateItem",  
                "dynamodb:DeleteItem",  
                "dynamodb:BatchWriteItem"  
            ],  
            "Resource": [  
                "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores"  
            ],  
            "Condition": {  
                "ForAllValues:StringEquals": {  
                    "dynamodb:LeadingKeys": [  
                        "${www.amazon.com:user_id}"  
                    ]  
                }  
            }  
        }  
    ]  
}
```

**Note**

When using policy variables, you must explicitly specify version 2012-10-17 in the policy. The default version of the access policy language, 2008-10-17, does not support policy variables.

To implement read-only access, you can remove any actions that can modify the data. In the following policy, only those actions that provide read-only access are included in the condition.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "ReadOnlyAccessToUserItems",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:BatchGetItem",
                "dynamodb:Query"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores"
            ],
            "Condition": {
                "ForAllValues:StringEquals": {
                    "dynamodb:LeadingKeys": [
                        "${www.amazon.com:user_id}"
                    ]
                }
            }
        }
    ]
}
```

**Important**

If you use `dynamodb:Attributes`, you must specify the names of all of the primary key and index key attributes, for the table and any secondary indexes that are listed in the policy. Otherwise, DynamoDB can't use these key attributes to perform the requested action.

## 2: Grant permissions that limit access to specific attributes in a table

The following permissions policy allows access to only two specific attributes in a table by adding the `dynamodb:Attributes` condition key. These attributes can be read, written, or evaluated in a conditional write or scan filter.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "LimitAccessToSpecificAttributes",
            "Effect": "Allow",
            "Action": [
                "dynamodb:UpdateItem",
                "dynamodb:GetItem",
                "dynamodb:Query",
                "dynamodb:BatchGetItem",
                "dynamodb:Scan"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores"
            ],
            "Condition": {
                "ForAllValues:StringEquals": {
                    "dynamodb:Attributes": [

```

```

        "UserId",
        "TopScore"
    ],
},
"StringEqualsIfExists": {
    "dynamodb:Select": "SPECIFIC_ATTRIBUTES",
    "dynamodb:ReturnValues": [
        "NONE",
        "UPDATED_OLD",
        "UPDATED_NEW"
    ]
}
}
]
}
}
```

### Note

The policy takes an *allow list* approach, which allows access to a named set of attributes. You can write an equivalent policy that denies access to other attributes instead. We don't recommend this *deny list* approach. Users can determine the names of these denied attributes by follow the *principle of least privilege*, as explained in Wikipedia at [http://en.wikipedia.org/wiki/Principle\\_of\\_least\\_privilege](http://en.wikipedia.org/wiki/Principle_of_least_privilege), and use an *allow list* approach to enumerate all of the allowed values, rather than specifying the denied attributes.

This policy doesn't permit `PutItem`, `DeleteItem`, or `BatchWriteItem`. These actions always replace the entire previous item, which would allow users to delete the previous values for attributes that they are not allowed to access.

The `StringEqualsIfExists` clause in the permissions policy ensures the following:

- If the user specifies the `Select` parameter, then its value must be `SPECIFIC_ATTRIBUTES`. This requirement prevents the API action from returning any attributes that aren't allowed, such as from an index projection.
- If the user specifies the `ReturnValues` parameter, then its value must be `NONE`, `UPDATED_OLD`, or `UPDATED_NEW`. This is required because the `UpdateItem` action also performs implicit read operations to check whether an item exists before replacing it, and so that previous attribute values can be returned if requested. Restricting `ReturnValues` in this way ensures that users can only read or write the allowed attributes.
- The `StringEqualsIfExists` clause assures that only one of these parameters — `Select` or `ReturnValues` — can be used per request, in the context of the allowed actions.

The following are some variations on this policy:

- To allow only read actions, you can remove `UpdateItem` from the list of allowed actions. Because none of the remaining actions accept `ReturnValues`, you can remove `ReturnValues` from the condition. You can also change `StringEqualsIfExists` to `StringEquals` because the `Select` parameter always has a value (`ALL_ATTRIBUTES`, unless otherwise specified).
- To allow only write actions, you can remove everything except `UpdateItem` from the list of allowed actions. Because `UpdateItem` does not use the `Select` parameter, you can remove `Select` from the condition. You must also change `StringEqualsIfExists` to `StringEquals` because the `ReturnValues` parameter always has a value (`NONE` unless otherwise specified).
- To allow all attributes whose name matches a pattern, use `StringLike` instead of `StringEquals`, and use a multi-character pattern match wildcard character (\*).

### 3: Grant permissions to prevent updates on certain attributes

The following permissions policy limits user access to updating only the specific attributes identified by the dynamodb:Attributes condition key. The StringNotLike condition prevents an application from updating the attributes specified using the dynamodb:Attributes condition key.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "PreventUpdatesOnCertainAttributes",
            "Effect": "Allow",
            "Action": [
                "dynamodb:UpdateItem"
            ],
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
            "Condition": {
                "ForAllValues:StringNotLike": {
                    "dynamodb:Attributes": [
                        "FreeGamesAvailable",
                        "BossLevelUnlocked"
                    ]
                },
                "StringEquals": {
                    "dynamodb:ReturnValues": [
                        "NONE",
                        "UPDATED_OLD",
                        "UPDATED_NEW"
                    ]
                }
            }
        }
    ]
}
```

Note the following:

- The `UpdateItem` action, like other write actions, requires read access to the items so that it can return values before and after the update. In the policy, you limit the action to accessing only the attributes that are allowed to be updated by specifying the `dynamodb:ReturnValues` condition key. The condition key restricts `ReturnValues` in the request to specify only `NONE`, `UPDATED_OLD`, or `UPDATED_NEW` and doesn't include `ALL_OLD` or `ALL_NEW`.
- The `PutItem` and `DeleteItem` actions replace an entire item, and thus allows applications to modify any attributes. So when limiting an application to updating only specific attributes, you should not grant permission for these APIs.

### 4: Grant permissions to query only projected attributes in an index

The following permissions policy allows queries on a secondary index (`TopScoreDateTimeIndex`) by using the `dynamodb:Attributes` condition key. The policy also limits queries to requesting only specific attributes that have been projected into the index.

To require the application to specify a list of attributes in the query, the policy also specifies the `dynamodb:Select` condition key to require that the `Select` parameter of the DynamoDB `Query` action is `SPECIFIC_ATTRIBUTES`. The list of attributes is limited to a specific list that is provided using the `dynamodb:Attributes` condition key.

```
{
    "Version": "2012-10-17",
    "Statement": [
```

```
{
    "Sid": "QueryOnlyProjectedIndexAttributes",
    "Effect": "Allow",
    "Action": [
        "dynamodb:Query"
    ],
    "Resource": [
        "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores/index/
TopScoreDateTimeIndex"
    ],
    "Condition": {
        "ForAllValues:StringEquals": {
            "dynamodb:Attributes": [
                "TopScoreDateTime",
                "GameTitle",
                "Wins",
                "Losses",
                "Attempts"
            ]
        },
        "StringEquals": {
            "dynamodb:Select": "SPECIFIC_ATTRIBUTES"
        }
    }
}
]
```

The following permissions policy is similar, but the query must request all of the attributes that have been projected into the index.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "QueryAllIndexAttributes",
            "Effect": "Allow",
            "Action": [
                "dynamodb:Query"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores/index/
TopScoreDateTimeIndex"
            ],
            "Condition": {
                "StringEquals": {
                    "dynamodb:Select": "ALL_PROJECTED_ATTRIBUTES"
                }
            }
        }
    ]
}
```

## 5: Grant permissions to limit access to certain attributes and partition key values

The following permissions policy allows specific DynamoDB actions (specified in the Action element) on a table and a table index (specified in the Resource element). The policy uses the dynamodb:LeadingKeys condition key to restrict permissions to only the items whose partition key value matches the user's Facebook ID.

```
{
    "Version": "2012-10-17",
```

```

"Statement": [
    {
        "Sid": "LimitAccessToCertainAttributesAndKeyValues",
        "Effect": "Allow",
        "Action": [
            "dynamodb:UpdateItem",
            "dynamodb:GetItem",
            "dynamodb:Query",
            "dynamodb:BatchGetItem"
        ],
        "Resource": [
            "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores",
            "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores/index/
TopScoreDateTimeIndex"
        ],
        "Condition": {
            "ForAllValues:StringEquals": {
                "dynamodb:LeadingKeys": [
                    "${graph.facebook.com:id}"
                ],
                "dynamodb:Attributes": [
                    "attribute-A",
                    "attribute-B"
                ]
            },
            "StringEqualsIfExists": {
                "dynamodb:Select": "SPECIFIC_ATTRIBUTES",
                "dynamodb:ReturnValues": [
                    "NONE",
                    "UPDATED_OLD",
                    "UPDATED_NEW"
                ]
            }
        }
    }
]
}

```

Note the following:

- Write actions allowed by the policy (UpdateItem) can only modify attribute-A or attribute-B.
- Because the policy allows UpdateItem, an application can insert new items, and the hidden attributes will be null in the new items. If these attributes are projected into TopScoreDateTimeIndex, the policy has the added benefit of preventing queries that cause fetches from the table.
- Applications cannot read any attributes other than those listed in dynamodb:Attributes. With this policy in place, an application must set the Select parameter to SPECIFIC\_ATTRIBUTES in read requests, and only attributes in the allow list can be requested. For write requests, the application cannot set ReturnValues to ALL\_OLD or ALL\_NEW and it cannot perform conditional write operations based on any other attributes.

## Related topics

- [Access control \(p. 1071\)](#)
- [DynamoDB API permissions: Actions, resources, and conditions reference \(p. 1084\)](#)

## Using web identity federation

If you are writing an application targeted at large numbers of users, you can optionally use *web identity federation* for authentication and authorization. Web identity federation removes the need for creating

individual IAM users. Instead, users can sign in to an identity provider and then obtain temporary security credentials from AWS Security Token Service (AWS STS). The app can then use these credentials to access AWS services.

Web identity federation supports the following identity providers:

- Login with Amazon
- Facebook
- Google

## Additional resources for web identity federation

The following resources can help you learn more about web identity federation:

- The post [Web Identity Federation using the AWS SDK for .NET](#) on the AWS Developer blog walks through how to use web identity federation with Facebook. It includes code snippets in C# that show how to assume an IAM role with web identity and how to use temporary security credentials to access an AWS resource.
- The [AWS Mobile SDK for iOS](#) and the [AWS Mobile SDK for Android](#) contain sample apps. They include code that shows how to invoke the identity providers, and then how to use the information from these providers to get and use temporary security credentials.
- The article [Web Identity Federation with Mobile Applications](#) discusses web identity federation and shows an example of how to use web identity federation to access an AWS resource.

## Example policy for web identity federation

To show how you can use web identity federation with DynamoDB, revisit the *GameScores* table that was introduced in [Using IAM policy conditions for fine-grained access control \(p. 1085\)](#). Here is the primary key for *GameScores*.


Table Name	Primary Key Type	Partition Key Name and Type	Sort Key Name and Type
<u>GameScores</u> ( <u>UserId</u> , <u>GameTitle</u> , ...)	Composite	Attribute Name: UserId Type: String	Attribute Name: GameTitle Type: String

Now suppose that a mobile gaming app uses this table, and that app needs to support thousands, or even millions, of users. At this scale, it becomes very difficult to manage individual app users, and to guarantee that each user can only access their own data in the *GameScores* table. Fortunately, many users already have accounts with a third-party identity provider, such as Facebook, Google, or Login with Amazon. So it makes sense to use one of these providers for authentication tasks.

To do this using web identity federation, the app developer must register the app with an identity provider (such as Login with Amazon) and obtain a unique app ID. Next, the developer needs to create an IAM role. (For this example, this role is named *GameRole*.) The role must have an IAM policy document attached to it, specifying the conditions under which the app can access *GameScores* table.

When a user wants to play a game, they sign in to their Login with Amazon account from within the gaming app. The app then calls AWS Security Token Service (AWS STS), providing the Login with Amazon app ID and requesting membership in *GameRole*. AWS STS returns temporary AWS credentials to the app and allows it to access the *GameScores* table, subject to the *GameRole* policy document.

The following diagram shows how these pieces fit together.



### Web identity federation overview

1. The app calls a third-party identity provider to authenticate the user and the app. The identity provider returns a web identity token to the app.
2. The app calls AWS STS and passes the web identity token as input. AWS STS authorizes the app and gives it temporary AWS access credentials. The app is allowed to assume an IAM role (*GameRole*) and access AWS resources in accordance with the role's security policy.
3. The app calls DynamoDB to access the *GameScores* table. Because it has assumed the *GameRole*, the app is subject to the security policy associated with that role. The policy document prevents the app from accessing data that does not belong to the user.

Once again, here is the security policy for *GameRole* that was shown in [Using IAM policy conditions for fine-grained access control \(p. 1085\)](#):

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "AllowAccessToOnlyItemsMatchingUserID",
            "Effect": "Allow",
            "Action": [
                "dynamodb:GetItem",
                "dynamodb:Query"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-east-1:123456789012:table/GameScores/*"
            ],
            "Condition": {
                "StringEquals": {
                    "dynamodb:userId": "#userId"
                }
            }
        }
    ]
}
```

```

        "dynamodb:BatchGetItem",
        "dynamodb:Query",
        "dynamodb:PutItem",
        "dynamodb:UpdateItem",
        "dynamodb:DeleteItem",
        "dynamodb:BatchWriteItem"
    ],
    "Resource": [
        "arn:aws:dynamodb:us-west-2:123456789012:table/GameScores"
    ],
    "Condition": {
        "ForAllValues:StringEquals": {
            "dynamodb:LeadingKeys": [
                "${www.amazon.com:user_id}"
            ],
            "dynamodb:Attributes": [
                "UserId",
                "GameTitle",
                "Wins",
                "Losses",
                "TopScore",
                "TopScoreDateTime"
            ]
        },
        "StringEqualsIfExists": {
            "dynamodb:Select": "SPECIFIC_ATTRIBUTES"
        }
    }
}
]
}
}

```

The **Condition** clause determines which items in *GameScores* are visible to the app. It does this by comparing the Login with Amazon ID to the *UserId* partition key values in *GameScores*. Only the items belonging to the current user can be processed using one of DynamoDB actions that are listed in this policy. Other items in the table cannot be accessed. Furthermore, only the specific attributes listed in the policy can be accessed.

## Preparing to use web identity federation

If you are an application developer and want to use web identity federation for your app, follow these steps:

- Sign up as a developer with a third-party identity provider.** The following external links provide information about signing up with supported identity providers:
  - [Login with Amazon Developer Center](#)
  - [Registration](#) on the Facebook site
  - [Using OAuth 2.0 to Access Google APIs](#) on the Google site
- Register your app with the identity provider.** When you do this, the provider gives you an ID that's unique to your app. If you want your app to work with multiple identity providers, you need to obtain an app ID from each provider.
- Create one or more IAM roles.** You need one role for each identity provider for each app. For example, you might create a role that can be assumed by an app where the user signed in using Login with Amazon, a second role for the same app where the user has signed in using Facebook, and a third role for the app where users sign in using Google.

As part of the role creation process, you need to attach an IAM policy to the role. Your policy document should define the DynamoDB resources required by your app, and the permissions for accessing those resources.

For more information, see [About Web Identity Federation](#) in *IAM User Guide*.

**Note**

As an alternative to AWS Security Token Service, you can use Amazon Cognito. Amazon Cognito is the preferred service for managing temporary credentials for mobile apps. For more information, see the following pages:

- [How to Authenticate Users \(AWS Mobile SDK for iOS\)](#)
- [How to Authenticate Users \(AWS Mobile SDK for Android\)](#)

### Generating an IAM policy using the DynamoDB console

The DynamoDB console can help you create an IAM policy for use with web identity federation. To do this, you choose a DynamoDB table and specify the identity provider, actions, and attributes to be included in the policy. The DynamoDB console then generates a policy that you can attach to an IAM role.

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane, choose **Tables**.
3. In the list of tables, choose the table for which you want to create the IAM policy.
4. Choose the **Access control** tab.
5. Choose the identity provider, actions, and attributes for the policy.  
  
When the settings are as you want them, click **Create policy**. The generated policy appears.
6. Click **Attach policy instructions**, and follow the steps required to attach the generated policy to an IAM role.

### Writing your app to use web identity federation

To use web identity federation, your app must assume the IAM role that you created. From that point on, the app honors the access policy that you attached to the role.

At runtime, if your app uses web identity federation, it must follow these steps:

1. **Authenticate with a third-party identity provider.** Your app must call the identity provider using an interface that they provide. The exact way in which you authenticate the user depends on the provider and on what platform your app is running. Typically, if the user is not already signed in, the identity provider takes care of displaying a sign-in page for that provider.

After the identity provider authenticates the user, the provider returns a web identity token to your app. The format of this token depends on the provider, but is typically a very long string of characters.

2. **Obtain temporary AWS security credentials.** To do this, your app sends a `AssumeRoleWithWebIdentity` request to AWS Security Token Service (AWS STS). This request contains the following:
  - The web identity token from the previous step
  - The app ID from the identity provider
  - The Amazon Resource Name (ARN) of the IAM role that you created for this identity provider for this app

AWS STS returns a set of AWS security credentials that expire after a certain amount of time (3,600 seconds, by default).

The following is a sample request and response from a `AssumeRoleWithWebIdentity` action in AWS STS. The web identity token was obtained from the Login with Amazon identity provider.

```
GET / HTTP/1.1
Host: sts.amazonaws.com
Content-Type: application/json; charset=utf-8
URL: https://sts.amazonaws.com/?ProviderId=www.amazon.com
&DurationSeconds=900&Action=AssumeRoleWithWebIdentity
&Version=2011-06-15&RoleSessionName=web-identity-federation
&RoleArn=arn:aws:iam::123456789012:role/GameRole
&WebIdentityToken=Atza|IQEBLjAsAhQluyKqyBiYZ8-kclvGTYM81e...(remaining characters
omitted)
```

```
<AssumeRoleWithWebIdentityResponse
  xmlns="https://sts.amazonaws.com/doc/2011-06-15/">
  <AssumeRoleWithWebIdentityResult>
    <SubjectFromWebIdentityToken>amzn1.account.AGJZDKHJKAUUSW6C44CHPEXAMPLE</
  SubjectFromWebIdentityToken>
    <Credentials>
      <SessionToken>AQoDYXdzEMf//////////wEa8AP6nNDwcSLnf+cHupC...(remaining characters
omitted)</SessionToken>
      <SecretAccessKey>8Jhi60+EWUUbbUShTESjTxqQtM8UKvsM6XAjdA==</SecretAccessKey>
      <Expiration>2013-10-01T22:14:35Z</Expiration>
      <AccessKeyId>06198791C436IEXAMPLE</AccessKeyId>
    </Credentials>
    <AssumedRoleUser>
      <Arn>arn:aws:sts::123456789012:assumed-role/GameRole/web-identity-federation</Arn>
      <AssumedRoleId>AROAJU4SA2VW5S2RF2YMG:web-identity-federation</AssumedRoleId>
    </AssumedRoleUser>
  </AssumeRoleWithWebIdentityResult>
  <ResponseMetadata>
    <RequestId>c265ac8e-2ae4-11e3-8775-6969323a932d</RequestId>
  </ResponseMetadata>
</AssumeRoleWithWebIdentityResponse>
```

- 3. Access AWS resources.** The response from AWS STS contains information that your app requires in order to access DynamoDB resources:

- The `AccessKeyId`, `SecretAccessKey`, and `SessionToken` fields contain security credentials that are valid for this user and this app only.
- The `Expiration` field signifies the time limit for these credentials, after which they are no longer valid.
- The `AssumedRoleId` field contains the name of a session-specific IAM role that has been assumed by the app. The app honors the access controls in the IAM policy document for the duration of this session.
- The `SubjectFromWebIdentityToken` field contains the unique ID that appears in an IAM policy variable for this particular identity provider. The following are the IAM policy variables for supported providers, and some example values for them:

Policy Variable	Example Value
<code>#{www.amazon.com:user_id}</code>	amzn1.account.AGJZDKHJKAUUSW6C44CHPEXAMPLE
<code>#{graph.facebook.com:id}</code>	123456789
<code>#{accounts.google.com:sub}</code>	123456789012345678901

For example IAM policies where these policy variables are used, see [Example policies: Using conditions for fine-grained access control \(p. 1089\)](#).

For more information about how AWS STS generates temporary access credentials, see [Requesting Temporary Security Credentials in IAM User Guide](#).

## Identity and access management in DynamoDB Accelerator

DynamoDB Accelerator (DAX) is designed to work together with DynamoDB, to seamlessly add a caching layer to your applications. However, DAX and DynamoDB have separate access control mechanisms. Both services use AWS Identity and Access Management (IAM) to implement their respective security policies, but the security models for DAX and DynamoDB are different.

For more information about Identity and Access Management in DAX, see [DAX access control \(p. 734\)](#).

## Compliance validation by industry for DynamoDB

The security and compliance of DynamoDB is assessed by third-party auditors as part of multiple AWS compliance programs, including the following:

- System and Organization Controls (SOC)
- Payment Card Industry (PCI)
- Federal Risk and Authorization Management Program (FedRAMP)
- Health Insurance Portability and Accountability Act (HIPAA)

AWS provides a frequently updated list of AWS services in scope of specific compliance programs at [AWS Services in Scope by Compliance Program](#).

Third-party audit reports are available for you to download using AWS Artifact. For more information, see [Downloading Reports in AWS Artifact](#).

For more information about AWS compliance programs, see [AWS Compliance Programs](#).

Your compliance responsibility when using DynamoDB is determined by the sensitivity of your data, your organization's compliance objectives, and applicable laws and regulations. If your use of DynamoDB is subject to compliance with standards like HIPAA, PCI, or FedRAMP, AWS provides resources to help:

- [Security and Compliance Quick Start Guides](#) – Deployment guides that discuss architectural considerations and provide steps for deploying security- and compliance-focused baseline environments on AWS.
- [Architecting for HIPAA Security and Compliance Whitepaper](#) – A whitepaper that describes how companies can use AWS to create HIPAA-compliant applications.
- [AWS Compliance Resources](#) – A collection of workbooks and guides that might apply to your industry and location.
- [AWS Config](#) – A service that assesses how well your resource configurations comply with internal practices, industry guidelines, and regulations.
- [AWS Security Hub](#) – A comprehensive view of your security state within AWS that helps you check your compliance with security industry standards and best practices.

# Resilience and disaster recovery in Amazon DynamoDB

The AWS global infrastructure is built around AWS Regions and Availability Zones. AWS Regions provide multiple physically separated and isolated Availability Zones, which are connected with low-latency, high-throughput, and highly redundant networking. With Availability Zones, you can design and operate applications and databases that automatically fail over between Availability Zones without interruption. Availability Zones are more highly available, fault tolerant, and scalable than traditional single or multiple data center infrastructures.

If you need to replicate your data or applications over greater geographic distances, use AWS Local Regions. An AWS Local Region is a single data center designed to complement an existing AWS Region. Like all AWS Regions, AWS Local Regions are completely isolated from other AWS Regions.

For more information about AWS Regions and Availability Zones, see [AWS global infrastructure](#).

In addition to the AWS global infrastructure, Amazon DynamoDB offers several features to help support your data resiliency and backup needs.

## On-demand backup and restore

DynamoDB provides on-demand backup capability. It allows you to create full backups of your tables for long-term retention and archival. For more information, see [On-Demand backup and restore for DynamoDB](#).

## Point-in-time recovery

Point-in-time recovery helps protect your DynamoDB tables from accidental write or delete operations. With point in time recovery, you don't have to worry about creating, maintaining, or scheduling on-demand backups. For more information, see [Point-in-time recovery for DynamoDB](#).

# Infrastructure security in Amazon DynamoDB

As a managed service, Amazon DynamoDB is protected by the AWS global network security procedures that are described in the [Amazon web services: Overview of security processes](#) whitepaper.

You use AWS published API calls to access DynamoDB through the network. Clients must support TLS (Transport Layer Security) 1.0. We recommend TLS 1.2 or later. Clients must also support cipher suites with perfect forward secrecy (PFS) such as Ephemeral Diffie-Hellman (DHE) or Elliptic Curve Diffie-Hellman Ephemeral (ECDHE). Most modern systems such as Java 7 and later support these modes. Additionally, requests must be signed using an access key ID and a secret access key that is associated with an IAM principal. Or you can use the [AWS Security Token Service](#) (AWS STS) to generate temporary security credentials to sign requests.

You can also use a virtual private cloud (VPC) endpoint for DynamoDB to enable Amazon EC2 instances in your VPC to use their private IP addresses to access DynamoDB with no exposure to the public internet. For more information, see [Using Amazon VPC endpoints to access DynamoDB \(p. 1101\)](#).

## Using Amazon VPC endpoints to access DynamoDB

For security reasons, many AWS customers run their applications within an Amazon Virtual Private Cloud environment (Amazon VPC). With Amazon VPC, you can launch Amazon EC2 instances into a virtual private cloud, which is logically isolated from other networks—including the public internet. With an

Amazon VPC, you have control over its IP address range, subnets, routing tables, network gateways, and security settings.


**Note**

If you created your AWS account after December 4, 2013, then you already have a default VPC in each AWS Region. A default VPC is ready for you to use—you can immediately start using it without having to perform any additional configuration steps.

For more information, see [Default VPC and Default Subnets](#) in the *Amazon VPC User Guide*.

To access the public internet, your VPC must have an internet gateway—a virtual router that connects your VPC to the internet. This allows applications running on Amazon EC2 in your VPC to access internet resources, such as Amazon DynamoDB.

By default, communications to and from DynamoDB use the HTTPS protocol, which protects network traffic by using SSL/TLS encryption. The following diagram shows how an EC2 instance in a VPC accesses DynamoDB:




Many customers have legitimate privacy and security concerns about sending and receiving data across the public internet. You can address these concerns by using a virtual private network (VPN) to route all DynamoDB network traffic through your own corporate network infrastructure. However, this approach can introduce bandwidth and availability challenges.

VPC endpoints for DynamoDB can alleviate these challenges. A *VPC endpoint* for DynamoDB enables Amazon EC2 instances in your VPC to use their private IP addresses to access DynamoDB with no exposure to the public internet. Your EC2 instances do not require public IP addresses, and you don't need an internet gateway, a NAT device, or a virtual private gateway in your VPC. You use endpoint policies to control access to DynamoDB. Traffic between your VPC and the AWS service does not leave the Amazon network.

When you create a VPC endpoint for DynamoDB, any requests to a DynamoDB endpoint within the Region (for example, `dynamodb.us-west-2.amazonaws.com`) are routed to a private DynamoDB endpoint within the Amazon network. You don't need to modify your applications running on EC2 instances in your VPC. The endpoint name remains the same, but the route to DynamoDB stays entirely within the Amazon network, and does not access the public internet.

The following diagram shows how an EC2 instance in a VPC can use a VPC endpoint to access DynamoDB.



For more information, see [the section called “Tutorial: Using a VPC endpoint for DynamoDB” \(p. 1103\)](#).

## Tutorial: Using a VPC endpoint for DynamoDB

This section walks you through setting up and using a VPC endpoint for DynamoDB.

### Topics

- [Step 1: Launch an Amazon EC2 instance \(p. 1103\)](#)
- [Step 2: Configure your Amazon EC2 instance \(p. 1104\)](#)
- [Step 3: Create a VPC endpoint for DynamoDB \(p. 1105\)](#)
- [Step 4: \(Optional\) Clean up \(p. 1106\)](#)

### Step 1: Launch an Amazon EC2 instance

In this step, you launch an Amazon EC2 instance in your default Amazon VPC. You can then create and use a VPC endpoint for DynamoDB.

1. Open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.
2. Choose **Launch Instance** and do the following:
  - Step 1: Choose an Amazon Machine Image (AMI)
    - At the top of the list of AMIs, go to **Amazon Linux AMI** and choose **Select**.

#### Step 2: Choose an Instance Type

- At the top of the list of instance types, choose **t2.micro**.
- Choose **Next: Configure Instance Details**.

#### Step 3: Configure Instance Details

- Go to **Network** and choose your default VPC.

Choose **Next: Add Storage**.

Step 4: Add Storage

- Skip this step by choosing **Next: Tag Instance**.

Step 5: Tag Instance

- Skip this step by choosing **Next: Configure Security Group**.

Step 6: Configure Security Group

- Choose **Select an existing security group**.
- In the list of security groups, choose **default**. This is the default security group for your VPC.
- Choose **Next: Review and Launch**.

Step 7: Review Instance Launch

- Choose **Launch**.

3. In the **Select an existing key pair or create a new key pair** window, do one of the following:
  - If you do not have an Amazon EC2 key pair, choose **Create a new key pair** and follow the instructions. You will be asked to download a private key file (.pem file); you will need this file later when you log in to your Amazon EC2 instance.
  - If you already have an existing Amazon EC2 key pair, go to **Select a key pair** and choose your key pair from the list. You must already have the private key file (.pem file) available in order to log in to your Amazon EC2 instance.
4. When you have configured your key pair, choose **Launch Instances**.
5. Return to the Amazon EC2 console home page and choose the instance that you launched. In the lower pane, on the **Description** tab, find the **Public DNS** for your instance. For example: ec2-00-00-00-00.us-east-1.compute.amazonaws.com.

Make a note of this public DNS name, because you will need it in the next step in this tutorial ([Step 2: Configure your Amazon EC2 instance \(p. 1104\)](#)).

#### Note

It will take a few minutes for your Amazon EC2 instance to become available. Before you go on to the next step, ensure that the **Instance State** is **running** and that all of its **Status Checks** have passed.

## Step 2: Configure your Amazon EC2 instance

When your Amazon EC2 instance is available, you will be able to log into it and prepare it for first use.

#### Note

The following steps assume that you are connecting to your Amazon EC2 instance from a computer running Linux. For other ways to connect, see [Connect to Your Linux Instance](#) in the Amazon EC2 User Guide for Linux Instances.

1. You will need to authorize inbound SSH traffic to your Amazon EC2 instance. To do this, you will create a new EC2 security group, and then assign the security group to your EC2 instance.
  - a. In the navigation pane, choose **Security Groups**.

- b. Choose **Create Security Group**. In the **Create Security Group** window, do the following:
  - **Security group name**—type a name for your security group. For example: my-ssh-access
  - **Description**—type a short description for the security group.
  - **VPC**—choose your default VPC.
  - In the **Security group rules** section, choose **Add Rule** and do the following:
    - **Type**—choose SSH.
    - **Source**—choose My IP.

When the settings are as you want them, choose **Create**.

- c. In the navigation pane, choose **Instances**.
- d. Choose the Amazon EC2 instance that you launched in [Step 1: Launch an Amazon EC2 instance \(p. 1103\)](#).
- e. Choose **Actions --> Networking --> Change Security Groups**.
- f. In the **Change Security Groups**, select the security group that you created earlier in this procedure (for example: my-ssh-access). The existing default security group should also be selected. When the settings are as you want them, choose **Assign Security Groups**.

2. Use the ssh command to log in to your Amazon EC2 instance, as in the following example.

```
ssh -i my-keypair.pem ec2-user@public-dns-name
```

You will need to specify your private key file (.pem file) and the public DNS name of your instance. (See [Step 1: Launch an Amazon EC2 instance \(p. 1103\)](#)).

The login ID is ec2-user. No password is required.

3. Configure your AWS credentials, as shown following. Enter your AWS access key ID, secret key, and default Region name when prompted.

```
aws configure

AWS Access Key ID [None]: AKIAIOSFODNN7EXAMPLE
AWS Secret Access Key [None]: wJalrXUtnFEMI/K7MDENG/bPxRfiCYEXAMPLEKEY
Default region name [None]: us-east-1
Default output format [None]:
```

You are now ready to create a VPC endpoint for DynamoDB.

### Step 3: Create a VPC endpoint for DynamoDB

In this step, you will create a VPC endpoint for DynamoDB and test it to make sure that it works.

1. Before you begin, verify that you can communicate with DynamoDB using its public endpoint.

```
aws dynamodb list-tables
```

The output will show a list of DynamoDB tables that you currently own. (If you don't have any tables, the list will be empty.).

2. Verify that DynamoDB is an available service for creating VPC endpoints in the current AWS Region. (The command is shown in bold text, followed by example output.)

```
aws ec2 describe-vpc-endpoints API Version: 2012-08-10
1105
```

```
{  
    "ServiceNames": [  
        "com.amazonaws.us-east-1.s3",  
        "com.amazonaws.us-east-1.dynamodb"  
    ]  
}
```

In the example output, DynamoDB is one of the services available, so you can proceed with creating a VPC endpoint for it.

3. Determine your VPC identifier.

```
aws ec2 describe-vpcs  
  
{  
    "vpcs": [  
        {  
            "VpcId": "vpc-0bbc736e",  
            "InstanceTenancy": "default",  
            "State": "available",  
            "DhcpOptionsId": "dopt-8454b7e1",  
            "CidrBlock": "172.31.0.0/16",  
            "IsDefault": true  
        }  
    ]  
}
```

In the example output, the VPC ID is vpc-0bbc736e.

4. Create the VPC endpoint. For the `--vpc-id` parameter, specify the VPC ID from the previous step. Use the `--route-table-ids` parameter to associate the endpoint with your route tables.

```
aws ec2 create-vpc-endpoint --vpc-id vpc-0bbc736e --service-name com.amazonaws.us-east-1.dynamodb --route-table-ids rtb-11aa22bb  
  
{  
    "VpcEndpoint": {  
        "PolicyDocument": "{\"Version\":\"2008-10-17\", \"Statement\":[{\"Effect\":\"Allow\", \"Principal\":\"*\", \"Action\":\"*\", \"Resource\":\"*\"}]}",  
        "VpcId": "vpc-0bbc736e",  
        "State": "available",  
        "ServiceName": "com.amazonaws.us-east-1.dynamodb",  
        "RouteTableIds": [  
            "rtb-11aa22bb"  
        ],  
        "VpcEndpointId": "vpce-9b15e2f2",  
        "CreationTimestamp": "2017-07-26T22:00:14Z"  
    }  
}
```

5. Verify that you can access DynamoDB through the VPC endpoint.

```
aws dynamodb list-tables
```

If you want, you can try some other AWS CLI commands for DynamoDB. For more information, see the [AWS CLI Command Reference](#).

## Step 4: (Optional) Clean up

If you want to delete the resources you have created in this tutorial, follow these procedures:

### To remove your VPC endpoint for DynamoDB

1. Log in to your Amazon EC2 instance.
2. Determine the VPC endpoint ID.

```
aws ec2 describe-vpc-endpoints

{
    "VpcEndpoint": {
        "PolicyDocument": "{\"Version\":\"2008-10-17\", \"Statement\":[{\"Effect\": \"Allow\", \"Principal\":\"*\", \"Action\":\"*\", \"Resource\":\"*\"}]}",
        "VpcId": "vpc-0bbc736e",
        "State": "available",
        "ServiceName": "com.amazonaws.us-east-1.dynamodb",
        "RouteTableIds": [],
        "VpcEndpointId": "vpce-9b15e2f2",
        "CreationTimestamp": "2017-07-26T22:00:14Z"
    }
}
```

In the example output, the VPC endpoint ID is `vpce-9b15e2f2`.

3. Delete the VPC endpoint.

```
aws ec2 delete-vpc-endpoints --vpc-endpoint-ids vpce-9b15e2f2

{
    "Unsuccessful": []
}
```

The empty array [ ] indicates success (there were no unsuccessful requests).

### To terminate your Amazon EC2 instance

1. Open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.
2. In the navigation pane, choose **Instances**.
3. Choose your Amazon EC2 instance.
4. Choose **Actions, Instance State, Terminate**.
5. In the confirmation window, choose **Yes, Terminate**.

## Configuration and vulnerability analysis in Amazon DynamoDB

AWS handles basic security tasks like guest operating system (OS) and database patching, firewall configuration, and disaster recovery. These procedures have been reviewed and certified by the appropriate third parties. For more details, see the following resources:

- [Compliance validation for Amazon DynamoDB](#)
- [Shared responsibility model](#)
- [Amazon Web Services: Overview of security processes](#)(whitepaper)

The following security best practices also address configuration and vulnerability analysis in Amazon DynamoDB:

- Monitor DynamoDB compliance with AWS Config Rules
- Monitor DynamoDB configuration with AWS Config

## Security best practices for Amazon DynamoDB

Amazon DynamoDB provides a number of security features to consider as you develop and implement your own security policies. The following best practices are general guidelines and don't represent a complete security solution. Because these best practices might not be appropriate or sufficient for your environment, treat them as helpful considerations rather than prescriptions.

### Topics

- [DynamoDB preventative security best practices \(p. 1108\)](#)
- [DynamoDB detective security best practices \(p. 1109\)](#)

## DynamoDB preventative security best practices

The following best practices can help you anticipate and prevent security incidents in Amazon DynamoDB.

### Encryption at rest

DynamoDB encrypts at rest all user data stored in tables, indexes, streams, and backups using encryption keys stored in [AWS Key Management Service \(AWS KMS\)](#). This provides an additional layer of data protection by securing your data from unauthorized access to the underlying storage .

You can specify whether DynamoDB should use an AWS owned key (default encryption type), an AWS managed key, or a customer managed key to encrypt user data. For more information, see [Amazon DynamoDB Encryption at Rest](#).

### Use IAM roles to authenticate access to DynamoDB

For users, applications, and other AWS services to access DynamoDB, they must include valid AWS credentials in their AWS API requests. You should not store AWS credentials directly in the application or EC2 instance. These are long-term credentials that are not automatically rotated, and therefore could have significant business impact if they are compromised. An IAM role enables you to obtain temporary access keys that can be used to access AWS services and resources.

For more information, see [Authentication](#).

### Use IAM policies for DynamoDB base authorization

When granting permissions, you decide who is getting them, which DynamoDB APIs they are getting permissions for, and the specific actions you want to allow on those resources. Implementing least privilege is key in reducing security risk and the impact that can result from errors or malicious intent.

Attach permissions policies to IAM identities (that is, users, groups, and roles) and thereby grant permissions to perform operations on DynamoDB resources.

You can do this by using the following:

- [AWS Managed \(predefined\) policies](#)
- [Customer managed policies](#)

### Use IAM policy conditions for fine-grained access control

When you grant permissions in DynamoDB, you can specify conditions that determine how a permissions policy takes effect. Implementing least privilege is key in reducing security risk and the impact that can result from errors or malicious intent.

You can specify conditions when granting permissions using an IAM policy. For example, you can do the following:

- Grant permissions to allow users read-only access to certain items and attributes in a table or a secondary index.
- Grant permissions to allow users write-only access to certain attributes in a table, based upon the identity of that user.

For more information, see [Using IAM Policy Conditions for Fine-Grained Access Control](#).

#### Use a VPC endpoint and policies to access DynamoDB

If you only require access to DynamoDB from within a virtual private cloud (VPC), you should use a VPC endpoint to limit access from only the required VPC. Doing this prevents that traffic from traversing the open internet and being subject to that environment.

Using a VPC endpoint for DynamoDB allows you to control and limit access using the following:

- VPC endpoint policies – These policies are applied on the DynamoDB VPC endpoint. They allow you to control and limit API access to the DynamoDB table.
- IAM policies – By using the `aws:sourceVpce` condition on policies attached to IAM users, groups, or roles, you can enforce that all access to the DynamoDB table is via the specified VPC endpoint.

For more information, see [Endpoints for Amazon DynamoDB](#).

#### Consider client-side encryption

If you store sensitive or confidential data in DynamoDB, you might want to encrypt that data as close as possible to its origin so that your data is protected throughout its lifecycle. Encrypting your sensitive data in transit and at rest helps ensure that your plaintext data isn't available to any third party.

The [Amazon DynamoDB Encryption Client](#) is a software library that helps you protect your table data before you send it to DynamoDB.

At the core of the DynamoDB Encryption Client is an item encryptor that encrypts, signs, verifies, and decrypts table items. It takes in information about your table items and instructions about which items to encrypt and sign. It gets the encryption materials and instructions on how to use them from a cryptographic material provider that you select and configure.

## DynamoDB detective security best practices

The following best practices for Amazon DynamoDB can help you detect potential security weaknesses and incidents.

#### Use AWS CloudTrail to monitor AWS managed KMS key usage

If you are using an [AWS managed key](#) for encryption at rest, usage of this key is logged into AWS CloudTrail. CloudTrail provides visibility into user activity by recording actions taken on your account. CloudTrail records important information about each action, including who made the request, the services used, the actions performed, parameters for the actions, and the response elements returned by the AWS service. This information helps you track changes made to your AWS resources and troubleshoot operational issues. CloudTrail makes it easier to ensure compliance with internal policies and regulatory standards.

You can use CloudTrail to audit key usage. CloudTrail creates log files that contain a history of AWS API calls and related events for your account. These log files include all AWS KMS API requests made using the AWS Management Console, AWS SDKs, and command line tools, in addition to those made through integrated AWS services. You can use these log files to get information about when the KMS key was used, the operation that was requested, the identity of the requester, the IP address that

the request came from, and so on. For more information, see [Logging AWS KMS API Calls with AWS CloudTrail](#) and the [AWS CloudTrail User Guide](#).

### Monitor DynamoDB operations using CloudTrail

CloudTrail can monitor both control plane events and data plane events. Control plane operations let you create and manage DynamoDB tables. They also let you work with indexes, streams, and other objects that are dependent on tables. Data plane operations let you perform create, read, update, and delete (also called *CRUD*) actions on data in a table. Some data plane operations also let you read data from a secondary index. To enable logging of data plane events in CloudTrail, you'll need to enable logging of data plane API activity in CloudTrail. See [Logging data events for trails](#) for more information.

When activity occurs in DynamoDB, that activity is recorded in a CloudTrail event along with other AWS service events in the event history. For more information, see [Logging DynamoDB Operations by Using AWS CloudTrail](#). You can view, search, and download recent events in your AWS account. For more information, see [Viewing Events with CloudTrail Event History](#) in the *AWS CloudTrail User Guide*.

For an ongoing record of events in your AWS account, including events for DynamoDB, create a [trail](#). A trail enables CloudTrail to deliver log files to an Amazon Simple Storage Service (Amazon S3) bucket. By default, when you create a trail on the console, the trail applies to all AWS Regions. The trail logs events from all Regions in the AWS partition and delivers the log files to the S3 bucket that you specify. Additionally, you can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs.

### Use DynamoDB Streams to monitor data plane operations

DynamoDB is integrated with AWS Lambda so that you can create triggers—pieces of code that automatically respond to events in DynamoDB Streams. With triggers, you can build applications that react to data modifications in DynamoDB tables.

If you enable DynamoDB Streams on a table, you can associate the stream Amazon Resource Name (ARN) with a Lambda function that you write. Immediately after an item in the table is modified, a new record appears in the table's stream. AWS Lambda polls the stream and invokes your Lambda function synchronously when it detects new stream records. The Lambda function can perform any actions that you specify, such as sending a notification or initiating a workflow.

For an example, see [Tutorial: Using AWS Lambda with Amazon DynamoDB Streams](#). This example receives a DynamoDB event input, processes the messages that it contains, and writes some of the incoming event data to Amazon CloudWatch Logs.

### Monitor DynamoDB configuration with AWS Config

Using [AWS Config](#), you can continuously monitor and record configuration changes of your AWS resources. You can also use AWS Config to inventory your AWS resources. When a change from a previous state is detected, an Amazon Simple Notification Service (Amazon SNS) notification can be delivered for you to review and take action. Follow the guidance in [Setting Up AWS Config with the Console](#), ensuring that DynamoDB resource types are included.

You can configure AWS Config to stream configuration changes and notifications to an Amazon SNS topic. For example, when a resource is updated, you can get a notification sent to your email, so that you can view the changes. You can also be notified when AWS Config evaluates your custom or managed rules against your resources.

For an example, see [Notifications that AWS Config Sends to an Amazon SNS topic](#) in the *AWS Config Developer Guide*.

### Monitor DynamoDB compliance with AWS Config rules

AWS Config continuously tracks the configuration changes that occur among your resources. It checks whether these changes violate any of the conditions in your rules. If a resource violates a rule, AWS Config flags the resource and the rule as noncompliant.

By using AWS Config to evaluate your resource configurations, you can assess how well your resource configurations comply with internal practices, industry guidelines, and regulations. AWS Config provides [AWS managed rules](#), which are predefined, customizable rules that AWS Config uses to evaluate whether your AWS resources comply with common best practices.

#### Tag your DynamoDB resources for identification and automation

You can assign metadata to your AWS resources in the form of tags. Each tag is a simple label consisting of a customer-defined key and an optional value that can make it easier to manage, search for, and filter resources.

Tagging allows for grouped controls to be implemented. Although there are no inherent types of tags, they enable you to categorize resources by purpose, owner, environment, or other criteria. The following are some examples:

- Security – Used to determine requirements such as encryption.
- Confidentiality – An identifier for the specific data-confidentiality level a resource supports.
- Environment – Used to distinguish between development, test, and production infrastructure.

For more information, see [AWS Tagging Strategies](#) and [Tagging for DynamoDB](#).

# Monitoring and logging

Monitoring is an important part of maintaining the reliability, availability, and performance of DynamoDB and your AWS solutions. You should collect monitoring data from all of the parts of your AWS solution so that you can more easily debug a multi-point failure if one occurs. AWS provides several tools for monitoring your DynamoDB resources and responding to potential incidents:

## Topics

- [Logging and monitoring in DynamoDB \(p. 1112\)](#)
- [Logging and monitoring in DynamoDB Accelerator \(p. 1149\)](#)
- [Analyzing data access using CloudWatch contributor insights for DynamoDB \(p. 1149\)](#)

## Logging and monitoring in DynamoDB

Monitoring is an important part of maintaining the reliability, availability, and performance of DynamoDB and your AWS solutions. You should collect monitoring data from all parts of your AWS solution so that you can more easily debug a multi-point failure, if one occurs. Before you start monitoring DynamoDB, you should create a monitoring plan that includes answers to the following questions:

- What are your monitoring goals?
- What resources will you monitor?
- How often will you monitor these resources?
- What monitoring tools will you use?
- Who will perform the monitoring tasks?
- Who should be notified when something goes wrong?

The next step is to establish a baseline for normal DynamoDB performance in your environment, by measuring performance at various times and under different load conditions. As you monitor DynamoDB, you should consider storing historical monitoring data. This stored data will give you a baseline from which to compare current performance data, identify normal performance patterns and performance anomalies, and devise methods to address issues.

To establish a baseline you should, at a minimum, monitor the following items:

- The number of read or write capacity units consumed over the specified time period, so you can track how much of your provisioned throughput is used.
- Requests that exceeded a table's provisioned write or read capacity during the specified time period, so you can determine which requests exceed the provisioned throughput quotas of a table.
- System errors, so you can determine if any requests resulted in an error.

## Topics

- [Monitoring tools \(p. 1113\)](#)
- [Monitoring with Amazon CloudWatch \(p. 1114\)](#)
- [Logging DynamoDB operations by using AWS CloudTrail \(p. 1133\)](#)

## Monitoring tools

AWS provides tools that you can use to monitor DynamoDB. You can configure some of these tools to do the monitoring for you; some require manual intervention. We recommend that you automate monitoring tasks as much as possible.

### Automated monitoring tools

You can use the following automated monitoring tools to watch DynamoDB and report when something is wrong:

- **Amazon CloudWatch Alarms** – Watch a single metric over a time period that you specify, and perform one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The action is a notification sent to an Amazon Simple Notification Service (Amazon SNS) topic or Amazon EC2 Auto Scaling policy. CloudWatch alarms do not invoke actions simply because they are in a particular state; the state must have changed and been maintained for a specified number of periods. For more information, see [Monitoring with Amazon CloudWatch \(p. 1114\)](#).
- **Amazon CloudWatch Logs** – Monitor, store, and access your log files from AWS CloudTrail or other sources. For more information, see [Monitoring Log Files](#) in the *Amazon CloudWatch User Guide*.
- **Amazon CloudWatch Events** – Match events and route them to one or more target functions or streams to make changes, capture state information, and take corrective action. For more information, see [What is Amazon CloudWatch Events](#) in the *Amazon CloudWatch User Guide*.
- **AWS CloudTrail Log Monitoring** – Share log files between accounts, monitor CloudTrail log files in real time by sending them to CloudWatch Logs, write log processing applications in Java, and validate that your log files have not changed after delivery by CloudTrail. For more information, see [Working with CloudTrail Log Files](#) in the *AWS CloudTrail User Guide*.

### Manual monitoring tools

Another important part of monitoring DynamoDB involves manually monitoring those items that the CloudWatch alarms don't cover. The DynamoDB, CloudWatch, Trusted Advisor, and other AWS console dashboards provide an at-a-glance view of the state of your AWS environment. We recommend that you also check the log files on Amazon DynamoDB.

- DynamoDB dashboard shows:
  - Recent alerts
  - Total capacity
  - Service health
- CloudWatch home page shows:
  - Current alarms and status
  - Graphs of alarms and resources
  - Service health status

In addition, you can use CloudWatch to do the following:

- Create [customized dashboards](#) to monitor the services you care about
- Graph metric data to troubleshoot issues and discover trends
- Search and browse all of your AWS resource metrics
- Create and edit alarms to be notified of problems

# Monitoring with Amazon CloudWatch

You can monitor Amazon DynamoDB using CloudWatch, which collects and processes raw data from DynamoDB into readable, near real-time metrics. These statistics are retained for a period of time, so that you can access historical information for a better perspective on how your web application or service is performing. By default, DynamoDB metric data is sent to CloudWatch automatically. For more information, see [What is Amazon CloudWatch?](#) and [Metrics retention](#) in the *Amazon CloudWatch User Guide*.

## Topics

- [DynamoDB Metrics and dimensions \(p. 1114\)](#)
- [How do I use DynamoDB metrics? \(p. 1130\)](#)
- [Creating CloudWatch alarms to monitor DynamoDB \(p. 1131\)](#)

## DynamoDB Metrics and dimensions

When you interact with DynamoDB, it sends the following metrics and dimensions to CloudWatch. You can use the following procedures to view the metrics for DynamoDB.

### To view metrics (console)

Metrics are grouped first by the service namespace, and then by the various dimension combinations within each namespace.

1. Open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>.
2. In the navigation pane, choose **Metrics**.

#### Note

You can also select **Usage** namespace to view DynamoDB usage metrics. For more information about usage metrics, see [AWS usage metrics](#).

3. Select the **DynamoDB** namespace.

### To view metrics (CLI)

- At a command prompt, use the following command:

```
aws cloudwatch list-metrics --namespace "AWS/DynamoDB"
```

## Viewing metrics and dimensions

CloudWatch displays the following metrics for DynamoDB:

### DynamoDB metrics

#### Note

Amazon CloudWatch aggregates these metrics at one-minute intervals:

- ConditionalCheckFailedRequests
- ConsumedReadCapacityUnits
- ConsumedWriteCapacityUnits
- ReadThrottleEvents

- `ReturnedBytes`
- `ReturnedItemCount`
- `ReturnedRecordsCount`
- `SuccessfulRequestLatency`
- `SystemErrors`
- `TimeToLiveDeletedItemCount`
- `ThrottledRequests`
- `TransactionConflict`
- `UserErrors`
- `WriteThrottleEvents`

For all other DynamoDB metrics, the aggregation granularity is five minutes.

Not all statistics, such as *Average* or *Sum*, are applicable for every metric. However, all of these values are available through the Amazon DynamoDB console, or by using the CloudWatch console, AWS CLI, or AWS SDKs for all metrics.

In the following list, each metric has a set of valid statistics that are applicable to that metric.

#### List of Available Metrics

- [AccountMaxReads \(p. 1116\)](#)
- [AccountMaxTableLevelReads \(p. 1116\)](#)
- [AccountMaxTableLevelWrites \(p. 1116\)](#)
- [AccountMaxWrites \(p. 1116\)](#)
- [AccountProvisionedReadCapacityUtilization \(p. 1117\)](#)
- [AccountProvisionedWriteCapacityUtilization \(p. 1117\)](#)
- [AgeOfOldestUnreplicatedRecord \(p. 1117\)](#)
- [ConditionalCheckFailedRequests \(p. 1117\)](#)
- [ConsumedChangeDataCaptureUnits \(p. 1118\)](#)
- [ConsumedReadCapacityUnits \(p. 1118\)](#)
- [ConsumedWriteCapacityUnits \(p. 1119\)](#)
- [FailedToReplicateRecordCount \(p. 1119\)](#)
- [MaxProvisionedTableReadCapacityUtilization \(p. 1120\)](#)
- [MaxProvisionedTableWriteCapacityUtilization \(p. 1120\)](#)
- [OnlineIndexConsumedWriteCapacity \(p. 1120\)](#)
- [OnlineIndexPercentageProgress \(p. 1121\)](#)
- [OnlineIndexThrottleEvents \(p. 1121\)](#)
- [PendingReplicationCount \(p. 1122\)](#)
- [ProvisionedReadCapacityUnits \(p. 1122\)](#)
- [ProvisionedWriteCapacityUnits \(p. 1122\)](#)
- [ReadThrottleEvents \(p. 1123\)](#)
- [ReplicationLatency \(p. 1123\)](#)
- [ReturnedBytes \(p. 1123\)](#)
- [ReturnedItemCount \(p. 1124\)](#)
- [ReturnedRecordsCount \(p. 1124\)](#)
- [SuccessfulRequestLatency \(p. 1124\)](#)

- [SystemErrors \(p. 1125\)](#)
- [TimeToLiveDeletedItemCount \(p. 1125\)](#)
- [ThrottledPutRecordCount \(p. 1125\)](#)
- [ThrottledRequests \(p. 1126\)](#)
- [TransactionConflict \(p. 1126\)](#)
- [UserErrors \(p. 1127\)](#)
- [WriteThrottleEvents \(p. 1127\)](#)

### [AccountMaxReads](#)

The maximum number of read capacity units that can be used by an account. This limit does not apply to on-demand tables or global secondary indexes.

Units: Count

Valid Statistics:

- Maximum – The maximum number of read capacity units that can be used by an account.

### [AccountMaxTableLevelReads](#)

The maximum number of read capacity units that can be used by a table or global secondary index of an account. For on-demand tables this limit caps the maximum read request units a table or a global secondary index can use.

Units: Count

Valid Statistics:

- Maximum – The maximum number of read capacity units that can be used by a table or global secondary index of the account.

### [AccountMaxTableLevelWrites](#)

The maximum number of write capacity units that can be used by a table or global secondary index of an account. For on-demand tables this limit caps the maximum write request units a table or a global secondary index can use.

Units: Count

Valid Statistics:

- Maximum – The maximum number of write capacity units that can be used by a table or global secondary index of the account.

### [AccountMaxWrites](#)

The maximum number of write capacity units that can be used by an account. This limit does not apply to on-demand tables or global secondary indexes.

Units: Count

Valid Statistics:

- Maximum – The maximum number of write capacity units that can be used by an account.

## [AccountProvisionedReadCapacityUtilization](#)

The percentage of provisioned read capacity units utilized by an account.

Units: Percent

Valid Statistics:

- **Maximum** – The maximum percentage of provisioned read capacity units utilized by the account.
- **Minimum** – The minimum percentage of provisioned read capacity units utilized by the account.
- **Average** – The average percentage of provisioned read capacity units utilized by the account. The metric is published for five-minute intervals. Therefore, if you rapidly adjust the provisioned read capacity units, this statistic might not reflect the true average.

## [AccountProvisionedWriteCapacityUtilization](#)

The percentage of provisioned write capacity units utilized by an account.

Units: Percent

Valid Statistics:

- **Maximum** – The maximum percentage of provisioned write capacity units utilized by the account.
- **Minimum** – The minimum percentage of provisioned write capacity units utilized by the account.
- **Average** – The average percentage of provisioned write capacity units utilized by the account. The metric is published for five-minute intervals. Therefore, if you rapidly adjust the provisioned write capacity units, this statistic might not reflect the true average.

## [AgeOfOldestUnreplicatedRecord](#)

The elapsed time since a record yet to be replicated to the Kinesis data stream first appeared in the DynamoDB table.

Units: Milliseconds

Dimensions: TableName, DelegatedOperation

Valid Statistics:

- **Maximum**.
- **Minimum**.
- **Average**.

## [ConditionalCheckFailedRequests](#)

The number of failed attempts to perform conditional writes. The PutItem, UpdateItem, and DeleteItem operations let you provide a logical condition that must evaluate to true before the operation can proceed. If this condition evaluates to false, ConditionalCheckFailedRequests is incremented by one. ConditionalCheckFailedRequests is also incremented by one for PartiQL Update and Delete statements where a logical condition is provided and that condition evaluates to false.

### Note

A failed conditional write will result in an HTTP 400 error (Bad Request). These events are reflected in the ConditionalCheckFailedRequests metric, but not in the UserErrors metric.

Units: Count

Dimensions: TableName

Valid Statistics:

- Minimum
- Maximum
- Average
- SampleCount
- Sum

### ConsumedChangeDataCaptureUnits

The number of consumed change data capture units.

Units: Count

Dimensions: TableName, DelegatedOperation

Valid Statistics:

- Minimum
- Maximum
- Average

### ConsumedReadCapacityUnits

The number of read capacity units consumed over the specified time period, so you can track how much of your provisioned throughput is used. You can retrieve the total consumed read capacity for a table and all of its global secondary indexes, or for a particular global secondary index. For more information, see [Read/Write Capacity Mode](#).

The TableName dimension returns the ConsumedReadCapacityUnits for the table, but not for any global secondary indexes. To view ConsumedReadCapacityUnits for a global secondary index, you must specify both TableName and GlobalSecondaryIndexName.

#### Note

Use the Sum statistic to calculate the consumed throughput. For example, get the Sum value over a span of one minute, and divide it by the number of seconds in a minute (60) to calculate the average ConsumedReadCapacityUnits per second (recognizing that this average does not highlight any large but brief spikes in read activity that occurred during that minute). You can compare the calculated value to the provisioned throughput value that you provide DynamoDB.

Units: Count

Dimensions: TableName, GlobalSecondaryIndexName

Valid Statistics:

- Minimum – The minimum number of read capacity units consumed by any individual request to the table or index.
- Maximum – The maximum number of read capacity units consumed by any individual request to the table or index.
- Average – The average per-request read capacity consumed.

**Note**

The Average value is influenced by periods of inactivity where the sample value will be zero.

- Sum – The total read capacity units consumed. This is the most useful statistic for the ConsumedReadCapacityUnits metric.
- SampleCount – The number of read requests to DynamoDB, even if no read capacity was consumed.

**Note**

The SampleCount value is influenced by periods of inactivity where the sample value will be zero.

### ConsumedWriteCapacityUnits

The number of write capacity units consumed over the specified time period, so you can track how much of your provisioned throughput is used. You can retrieve the total consumed write capacity for a table and all of its global secondary indexes, or for a particular global secondary index. For more information, see [Read/Write Capacity Mode](#).

The TableName dimension returns the ConsumedWriteCapacityUnits for the table, but not for any global secondary indexes. To view ConsumedWriteCapacityUnits for a global secondary index, you must specify both TableName and GlobalSecondaryIndexName.

**Note**

Use the Sum statistic to calculate the consumed throughput. For example, get the Sum value over a span of one minute, and divide it by the number of seconds in a minute (60) to calculate the average ConsumedWriteCapacityUnits per second (recognizing that this average does not highlight any large but brief spikes in write activity that occurred during that minute).

You can compare the calculated value to the provisioned throughput value that you provide DynamoDB.

Units: Count

Dimensions: TableName, GlobalSecondaryIndexName

Valid Statistics:

- Minimum – The minimum number of write capacity units consumed by any individual request to the table or index.
- Maximum – The maximum number of write capacity units consumed by any individual request to the table or index.
- Average – The average per-request write capacity consumed.

**Note**

The Average value is influenced by periods of inactivity where the sample value will be zero.

- Sum – The total write capacity units consumed. This is the most useful statistic for the ConsumedWriteCapacityUnits metric.
- SampleCount – The number of write requests to DynamoDB, even if no write capacity was consumed.

**Note**

The SampleCount value is influenced by periods of inactivity where the sample value will be zero.

### FailedToReplicateRecordCount

The number of records that DynamoDB failed to replicate to your Kinesis data stream.

Units: Count

Dimensions: `TableName`, `DelegatedOperation`

Valid Statistics:

- `Minimum`
- `Maximum`
- `Average`
- `SampleCount`

### [MaxProvisionedTableReadCapacityUtilization](#)

The percentage of provisioned read capacity utilized by the highest provisioned read table or global secondary index of an account.

Units: `Percent`

Valid Statistics:

- `Maximum` – The maximum percentage of provisioned read capacity units utilized by the highest provisioned read table or global secondary index of an account.
- `Minimum` – The minimum percentage of provisioned read capacity units utilized by the highest provisioned read table or global secondary index of an account.
- `Average` – The average percentage of provisioned read capacity units utilized by the highest provisioned read table or global secondary index of the account. The metric is published for five-minute intervals. Therefore, if you rapidly adjust the provisioned read capacity units, this statistic might not reflect the true average.

### [MaxProvisionedTableWriteCapacityUtilization](#)

The percentage of provisioned write capacity utilized by the highest provisioned write table or global secondary index of an account.

Units: `Percent`

Valid Statistics:

- `Maximum` – The maximum percentage of provisioned write capacity units utilized by the highest provisioned write table or global secondary index of an account.
- `Minimum` – The minimum percentage of provisioned write capacity units utilized by the highest provisioned write table or global secondary index of an account.
- `Average` – The average percentage of provisioned write capacity units utilized by the highest provisioned write table or global secondary index of the account. The metric is published for five-minute intervals. Therefore, if you rapidly adjust the provisioned write capacity units, this statistic might not reflect the true average.

### [OnlineIndexConsumedWriteCapacity](#)

The number of write capacity units consumed when adding a new global secondary index to a table. If the write capacity of the index is too low, incoming write activity during the backfill phase might be throttled. This can increase the time it takes to create the index. You should monitor this statistic while the index is being built to determine whether the write capacity of the index is underprovisioned.

You can adjust the write capacity of the index using the `UpdateTable` operation, even while the index is still being built.

The `ConsumedWriteCapacityUnits` metric for the index does not include the write throughput consumed during index creation.

Units: Count

Dimensions: `TableName`, `GlobalSecondaryIndexName`

Valid Statistics:

- Minimum
- Maximum
- Average
- SampleCount
- Sum

### [OnlineIndexPercentageProgress](#)

The percentage of completion when a new global secondary index is being added to a table. DynamoDB must first allocate resources for the new index, and then backfill attributes from the table into the index. For large tables, this process might take a long time. You should monitor this statistic to view the relative progress as DynamoDB builds the index.

Units: Count

Dimensions: `TableName`, `GlobalSecondaryIndexName`

Valid Statistics:

- Minimum
- Maximum
- Average
- SampleCount
- Sum

### [OnlineIndexThrottleEvents](#)

The number of write throttle events that occur when adding a new global secondary index to a table. These events indicate that the index creation will take longer to complete, because incoming write activity is exceeding the provisioned write throughput of the index.

You can adjust the write capacity of the index using the `UpdateTable` operation, even while the index is still being built.

The `WriteThrottleEvents` metric for the index does not include any throttle events that occur during index creation.

Units: Count

Dimensions: `TableName`, `GlobalSecondaryIndexName`

Valid Statistics:

- Minimum
- Maximum

- Average
- SampleCount
- Sum

### PendingReplicationCount

Metric for [Version 2017.11.29 \(p. 319\)](#). It shows the number of item updates that are written to one replica table, but that have not yet been written to another replica in the global table.

Units: Count

Dimensions: TableName, ReceivingRegion

Valid Statistics:

- Average
- Sample Count
- Sum

### ProvisionedReadCapacityUnits

The number of provisioned read capacity units for a table or a global secondary index. The TableName dimension returns the ProvisionedReadCapacityUnits for the table, but not for any global secondary indexes. To view ProvisionedReadCapacityUnits for a global secondary index, you must specify both TableName and GlobalSecondaryIndexName.

Units:Count

Dimensions: TableName, GlobalSecondaryIndexName

Valid Statistics:

- Minimum – The lowest setting for provisioned read capacity. If you use UpdateTable to increase read capacity, this metric shows the lowest value of provisioned ReadCapacityUnits during this time period.
- Maximum – The highest setting for provisioned read capacity. If you use UpdateTable to decrease read capacity, this metric shows the highest value of provisioned ReadCapacityUnits during this time period.
- Average – The average provisioned read capacity. The ProvisionedReadCapacityUnits metric is published at five-minute intervals. Therefore, if you rapidly adjust the provisioned read capacity units, this statistic might not reflect the true average.

### ProvisionedWriteCapacityUnits

The number of provisioned write capacity units for a table or a global secondary index.

The TableName dimension returns the ProvisionedWriteCapacityUnits for the table, but not for any global secondary indexes. To view ProvisionedWriteCapacityUnits for a global secondary index, you must specify both TableName and GlobalSecondaryIndexName.

Units: Count

Dimensions: TableName, GlobalSecondaryIndexName

Valid Statistics:

- **Minimum** – The lowest setting for provisioned write capacity. If you use `UpdateTable` to increase write capacity, this metric shows the lowest value of provisioned `WriteCapacityUnits` during this time period.
- **Maximum** – The highest setting for provisioned write capacity. If you use `UpdateTable` to decrease write capacity, this metric shows the highest value of provisioned `WriteCapacityUnits` during this time period.
- **Average** – The average provisioned write capacity. The `ProvisionedWriteCapacityUnits` metric is published at five-minute intervals. Therefore, if you rapidly adjust the provisioned write capacity units, this statistic might not reflect the true average.

### ReadThrottleEvents

Requests to DynamoDB that exceed the provisioned read capacity units for a table or a global secondary index.

A single request can result in multiple events. For example, a `BatchGetItem` that reads 10 items is processed as 10 `GetItem` events. For each event, `ReadThrottleEvents` is incremented by one if that event is throttled. The `ThrottledRequests` metric for the entire `BatchGetItem` is not incremented unless *all* 10 of the `GetItem` events are throttled.

The `TableName` dimension returns the `ReadThrottleEvents` for the table, but not for any global secondary indexes. To view `ReadThrottleEvents` for a global secondary index, you must specify both `TableName` and `GlobalSecondaryIndexName`.

Units: Count

Dimensions: `TableName`, `GlobalSecondaryIndexName`

Valid Statistics:

- `SampleCount`
- `Sum`

### ReplicationLatency

(This metric is for DynamoDB global tables.) The elapsed time between an updated item appearing in the DynamoDB stream for one replica table, and that item appearing in another replica in the global table.

Units: Milliseconds

Dimensions: `TableName`, `ReceivingRegion`

Valid Statistics:

- `Average`
- `Minimum`
- `Maximum`

### ReturnedBytes

The number of bytes returned by `GetRecords` operations (Amazon DynamoDB Streams) during the specified time period.

Units: Bytes

Dimensions: `Operation`, `StreamLabel`, `TableName`

Valid Statistics:

- Minimum
- Maximum
- Average
- SampleCount
- Sum

### ReturnedItemCount

The number of items returned by `Query`, `Scan` or `ExecuteStatement` (select) operations during the specified time period.

The number of items *returned* is not necessarily the same as the number of items that were evaluated. For example, suppose that you requested a Scan on a table or an index that had 100 items, but specified a `FilterExpression` that narrowed the results so that only 15 items were returned. In this case, the response from Scan would contain a `ScanCount` of 100 and a `Count` of 15 returned items.

Units: Count

Dimensions: TableName, Operation

Valid Statistics:

- Minimum
- Maximum
- Average
- SampleCount
- Sum

### ReturnedRecordsCount

The number of stream records returned by `GetRecords` operations (Amazon DynamoDB Streams) during the specified time period.

Units: Count

Dimensions: Operation, StreamLabel, TableName

Valid Statistics:

- Minimum
- Maximum
- Average
- SampleCount
- Sum

### SuccessfulRequestLatency

The successful requests to DynamoDB or Amazon DynamoDB Streams during the specified time period. `SuccessfulRequestLatency` can provide two different kinds of information:

- The elapsed time for successful requests (`Minimum`, `Maximum`, `Sum`, or `Average`).

- The number of successful requests (`SampleCount`).

`SuccessfulRequestLatency` reflects activity only within DynamoDB or Amazon DynamoDB Streams, and does not take into account network latency or client-side activity.

Units: Milliseconds

Dimensions: `TableName`, `Operation`

Valid Statistics:

- `Minimum`
- `Maximum`
- `Average`
- `SampleCount`

### SystemErrors

The requests to DynamoDB or Amazon DynamoDB Streams that generate an HTTP 500 status code during the specified time period. An HTTP 500 usually indicates an internal service error.

Units: Count

Dimensions: `TableName`, `Operation`

Valid Statistics:

- `Sum`
- `SampleCount`

### TimeToLiveDeletedItemCount

The number of items deleted by Time to Live (TTL) during the specified time period. This metric helps you monitor the rate of TTL deletions on your table.

Units: Count

Dimensions: `TableName`

Valid Statistics:

- `Sum`

### ThrottledPutRecordCount

The number of records that were throttled by your Kinesis data stream due to insufficient Kinesis Data Streams capacity.

Units: Count

Dimensions: `TableName`, `DelegatedOperation`

Valid Statistics:

- `Minimum`
- `Maximum`

- Average
- SampleCount

### ThrottledRequests

Requests to DynamoDB that exceed the provisioned throughput limits on a resource (such as a table or an index).

`ThrottledRequests` is incremented by one if any event within a request exceeds a provisioned throughput limit. For example, if you update an item in a table with global secondary indexes, there are multiple events—a write to the table, and a write to each index. If one or more of these events are throttled, then `ThrottledRequests` is incremented by one.

#### Note

In a batch request (`BatchGetItem` or `BatchWriteItem`), `ThrottledRequests` is incremented only if *every* request in the batch is throttled.

If any individual request within the batch is throttled, one of the following metrics is incremented:

- `ReadThrottleEvents` – For a throttled `GetItem` event within `BatchGetItem`.
- `WriteThrottleEvents` – For a throttled `PutItem` or `DeleteItem` event within `BatchWriteItem`.

To gain insight into which event is throttling a request, compare `ThrottledRequests` with the `ReadThrottleEvents` and `WriteThrottleEvents` for the table and its indexes.

#### Note

A throttled request will result in an HTTP 400 status code. All such events are reflected in the `ThrottledRequests` metric, but not in the `UserErrors` metric.

Units: Count

Dimensions: `TableName`, `Operation`

Valid Statistics:

- Sum
- SampleCount

### TransactionConflict

Rejected item-level requests due to transactional conflicts between concurrent requests on the same items. For more information, see [Transaction Conflict Handling in DynamoDB](#).

Units: Count

Dimensions: `TableName`

Valid Statistics:

- Sum – The number of rejected item-level requests due to transaction conflicts.

#### Note

If multiple item-level requests within a call to `TransactWriteItems` or `TransactGetItems` were rejected, `Sum` is incremented by one for each item-level `Put`, `Update`, `Delete`, or `Get` request.

- SampleCount – The number of rejected requests due to transaction conflicts.

### Note

If multiple item-level requests within a call to `TransactWriteItems` or `TransactGetItems` are rejected, `SampleCount` is only incremented by one.

- `Min` – The minimum number of rejected item-level requests within a call to `TransactWriteItems`, `TransactGetItems`, `PutItem`, `UpdateItem`, or `DeleteItem`.
- `Max` – The maximum number of rejected item-level requests within a call to `TransactWriteItems`, `TransactGetItems`, `PutItem`, `UpdateItem`, or `DeleteItem`.
- `Average` – The average number of rejected item-level requests within a call to `TransactWriteItems`, `TransactGetItems`, `PutItem`, `UpdateItem`, or `DeleteItem`.

### UserErrors

Requests to DynamoDB or Amazon DynamoDB Streams that generate an HTTP 400 status code during the specified time period. An HTTP 400 usually indicates a client-side error, such as an invalid combination of parameters, an attempt to update a nonexistent table, or an incorrect request signature.

All such events are reflected in the `UserErrors` metric, except for the following:

- `ProvisionedThroughputExceededException` – See the `ThrottledRequests` metric in this section.
- `ConditionalCheckFailedException` – See the `ConditionalCheckFailedRequests` metric in this section.

`UserErrors` represents the aggregate of HTTP 400 errors for DynamoDB or Amazon DynamoDB Streams requests for the current AWS Region and the current AWS account.

Units: Count

Valid Statistics:

- `Sum`
- `SampleCount`

### WriteThrottleEvents

Requests to DynamoDB that exceed the provisioned write capacity units for a table or a global secondary index.

A single request can result in multiple events. For example, a `PutItem` request on a table with three global secondary indexes would result in four events—the table write, and each of the three index writes. For each event, the `WriteThrottleEvents` metric is incremented by one if that event is throttled. For single `PutItem` requests, if any of the events are throttled, `ThrottledRequests` is also incremented by one. For `BatchWriteItem`, the `ThrottledRequests` metric for the entire `BatchWriteItem` is not incremented unless all of the individual `PutItem` or `DeleteItem` events are throttled.

The `TableName` dimension returns the `WriteThrottleEvents` for the table, but not for any global secondary indexes. To view `WriteThrottleEvents` for a global secondary index, you must specify both `TableName` and `GlobalSecondaryIndexName`.

Units: Count

Dimensions: `TableName`, `GlobalSecondaryIndexName`

Valid Statistics:

- `Sum`

- [SampleCount](#)

### Usage metrics

Usage metrics in CloudWatch allow you to proactively manage usage by visualizing metrics in the CloudWatch console, creating custom dashboards, detecting changes in activity with CloudWatch anomaly detection, and configuring alarms that alert you when usage approaches a threshold.

DynamoDB also integrates these usage metrics with Service Quotas. You can use CloudWatch to manage your account's use of your service quotas. For more information, see [Visualizing your service quotas and setting alarms](#)

#### List of Available Usage Metrics

- [AccountProvisionedWriteCapacityUnits \(p. 1128\)](#)
- [AccountProvisionedReadCapacityUnits \(p. 1128\)](#)
- [TableCount \(p. 1128\)](#)

### [AccountProvisionedWriteCapacityUnits](#)

The sum of write capacity units provisioned for all tables and global secondary indexes of an account.

Units: Count

Valid Statistics:

- **Minimum** – The lowest number of provisioned write capacity units during a time period.
- **Maximum** – The highest number of provisioned write capacity units during a time period.
- **Average** - The average number provisioned write capacity units account during a time period.

This metric is published at five-minute intervals. Therefore, if you rapidly adjust the provisioned write capacity units, this statistic might not reflect the true average.

### [AccountProvisionedReadCapacityUnits](#)

The sum of read capacity units provisioned for all tables and global secondary indexes of an account.

Units: Count

Valid Statistics:

- **Minimum** – The lowest number of provisioned read capacity units during a time period.
- **Maximum** – The highest number of provisioned read capacity units during a time period.
- **Average** - The average number provisioned read capacity units account during a time period.

This metric is published at five-minute intervals. Therefore, if you rapidly adjust the provisioned read capacity units, this statistic might not reflect the true average.

### [TableCount](#)

The number of active tables of an account.

Units: Count

Valid Statistics:

- **Minimum** – The lowest number of tables during a time period.
- **Maximum** – The highest number of tables during a time period.
- **Average** - The average number tables during a time period.

## Understanding metrics and dimensions for DynamoDB

The metrics for DynamoDB are qualified by the values for the account, table name, global secondary index name, or operation. You can use the CloudWatch console to retrieve DynamoDB data along any of the dimensions in the table below.

### List of Available Dimensions

- [DelegatedOperation \(p. 1129\)](#)
- [GlobalSecondaryIndexName \(p. 1129\)](#)
- [Operation \(p. 1129\)](#)
- [OperationType \(p. 1130\)](#)
- [Verb \(p. 1130\)](#)
- [ReceivingRegion \(p. 1130\)](#)
- [StreamLabel \(p. 1130\)](#)
- [TableName \(p. 1130\)](#)

### [DelegatedOperation](#)

This dimension limits the data to operations DynamoDB performs on your behalf. The following operations are captured:

- Change data capture for Kinesis Data Streams.

### [GlobalSecondaryIndexName](#)

This dimension limits the data to a global secondary index on a table. If you specify `GlobalSecondaryIndexName`, you must also specify `TableName`.

### [Operation](#)

This dimension limits the data to one of the following DynamoDB operations:

- [PutItem](#)
- [DeleteItem](#)
- [UpdateItem](#)
- [GetItem](#)
- [BatchGetItem](#)
- [Scan](#)
- [Query](#)
- [BatchWriteItem](#)
- [TransactWriteItems](#)
- [TransactGetItems](#)
- [ExecuteTransaction](#)
- [BatchExecuteStatement](#)
- [ExecuteStatement](#)

In addition, you can limit the data to the following Amazon DynamoDB Streams operation:

- `GetRecords`

### OperationType

This dimension limits the data to one of the following operation types:

- `Read`
- `Write`

This dimension is emitted for `ExecuteTransaction` and `BatchExecuteStatement` requests.

### Verb

This dimension limits the data to one of the following DynamoDB PartiQL verbs:

- `Insert: PartiQLInsert`
- `Select: PartiQLSelect`
- `Update: PartiQLUpdate`
- `Delete: PartiQLDelete`

This dimension is emitted for the `ExecuteStatement` operation.

### ReceivingRegion

This dimension limits the data to a particular AWS region. It is used with metrics originating from replica tables within a DynamoDB global table.

### StreamLabel

This dimension limits the data to a specific stream label. It is used with metrics originating from Amazon DynamoDB Streams `GetRecords` operations.

### TableName

This dimension limits the data to a specific table. This value can be any table name in the current region and the current AWS account.

## How do I use DynamoDB metrics?

The metrics reported by DynamoDB provide information that you can analyze in different ways. The following list shows some common uses for the metrics. These are suggestions to get you started, not a comprehensive list.

How can I?	Relevant metrics
How can I monitor the rate of TTL deletions on my table?	You can monitor <code>TimeToLiveDeletedItemCount</code> over the specified time period, to track the rate of TTL deletions on your table. For an example of a server-less application using the <code>TimeToLiveDeletedItemCount</code> metric, see <a href="#">Automatically archive items to S3 using DynamoDB time to live (TTL) with AWS Lambda and Amazon Kinesis Data Firehose</a> .

How can I?	Relevant metrics
How can I determine how much of my provisioned throughput is being used?	You can monitor ConsumedReadCapacityUnits or ConsumedWriteCapacityUnits over the specified time period, to track how much of your provisioned throughput is being used.
How can I determine which requests exceed the provisioned throughput quotas of a table?	ThrottledRequests is incremented by one if any event within a request exceeds a provisioned throughput quota. Then, to gain insight into which event is throttling a request, compare ThrottledRequests with the ReadThrottleEvents and WriteThrottleEvents metrics for the table and its indexes.
How can I determine if any system errors occurred?	<p>You can monitor SystemErrors to determine if any requests resulted in an HTTP 500 (server error) code. Typically, this metric should be equal to zero. If it isn't, then you might want to investigate.</p> <p><b>Note</b>            You might encounter internal server errors while working with items. These are expected during the lifetime of a table. Any failed requests can be retried immediately.</p>

## Creating CloudWatch alarms to monitor DynamoDB

You can create a CloudWatch alarm that sends an Amazon SNS message when the alarm changes state. An alarm watches a single metric over a time period you specify, and performs one or more actions based on the value of the metric relative to a given threshold over a number of time periods. The action is a notification sent to an Amazon SNS topic or Auto Scaling policy. Alarms invoke actions for sustained state changes only. CloudWatch alarms do not invoke actions simply because they are in a particular state; the state must have changed and been maintained for a specified number of periods.

**Note**

You must specify all the required dimensions when creating your CloudWatch alarm, since CloudWatch will not aggregate metrics for a missing dimension. Creating a CloudWatch alarm with a missing dimension will not result in an error, when creating the alarm.

For a list of supported metrics and their required dimensions in DynamoDB, see [Viewing metrics and dimensions \(p. 1114\)](#).

### How can I be notified before I consume my entire read capacity?

1. Create an Amazon SNS topic, `arn:aws:sns:us-east-1:123456789012:capacity-alarm`.  
 For more information, see [Set up Amazon Simple Notification Service](#).
2. Create the alarm. In this example, we assume a provisioned capacity of five read capacity units.

```
aws cloudwatch put-metric-alarm \
    --alarm-name ReadCapacityUnitsLimitAlarm \
    --alarm-description "Alarm when read capacity reaches 80% of my provisioned read capacity" \
    --namespace AWS/DynamoDB \
    --metric-name ConsumedReadCapacityUnits \
    --dimensions Name=TableName,Value=myTable \
    --statistic Sum \
    --threshold 240 \
    --comparison-operator GreaterThanOrEqualToThreshold \
    --period 60 \
    --evaluation-periods 1 \
```

```
--alarm-actions arn:aws:sns:us-east-1:123456789012:capacity-alarm
```

3. Test the alarm.

```
aws cloudwatch set-alarm-state --alarm-name ReadCapacityUnitsLimitAlarm --state-reason "initializing" --state-value OK
```

```
aws cloudwatch set-alarm-state --alarm-name ReadCapacityUnitsLimitAlarm --state-reason "initializing" --state-value ALARM
```

**Note**

The alarm is activated whenever the consumed read capacity is at least 4 units per second (80% of provisioned read capacity of 5) for 1 minute (60 seconds). So the threshold is 240 read capacity units (4 units/sec \* 60 seconds). Any time the read capacity is updated you should update the alarm calculations appropriately. You can avoid this process by creating alarms through the DynamoDB Console. In this way, the alarms are automatically updated for you.

## How can I be notified if any requests exceed the provisioned throughput quotas of a table?

1. Create an Amazon SNS topic, `arn:aws:sns:us-east-1:123456789012:requests-exceeding-throughput`.

For more information, see [Set up Amazon Simple Notification Service](#).

2. Create the alarm.

```
aws cloudwatch put-metric-alarm \
--alarm-name RequestsExceedingThroughputAlarm \
--alarm-description "Alarm when my requests are exceeding provisioned throughput
quotas of a table" \
--namespace AWS/DynamoDB \
--metric-name ThrottledRequests \
--dimensions Name=TableName,Value=myTable Name=Operation,Value=aDynamoDBOperation \
--statistic Sum \
--threshold 0 \
--comparison-operator GreaterThanThreshold \
--period 300 \
--unit Count \
--evaluation-periods 1 \
--alarm-actions arn:aws:sns:us-east-1:123456789012:requests-exceeding-throughput
```

3. Test the alarm.

```
aws cloudwatch set-alarm-state --alarm-name RequestsExceedingThroughputAlarm --state-
reason "initializing" --state-value OK
```

```
aws cloudwatch set-alarm-state --alarm-name RequestsExceedingThroughputAlarm --state-
reason "initializing" --state-value ALARM
```

## How can I be notified if any system errors occurred?

1. Create an Amazon SNS topic, `arn:aws:sns:us-east-1:123456789012:notify-on-system-errors`.

For more information, see [Set up Amazon Simple Notification Service](#).

2. Create the alarm.

```
aws cloudwatch put-metric-alarm \
--alarm-name SystemErrorsAlarm \
--alarm-description "Alarm when system errors occur" \
--namespace AWS/DynamoDB \
--metric-name SystemErrors \
--dimensions Name=TableName,Value=myTable Name=Operation,Value=aDynamoDBOperation \
--statistic Sum \
--threshold 0 \
--comparison-operator GreaterThanThreshold \
--period 60 \
--unit Count \
--evaluation-periods 1 \
--alarm-actions arn:aws:sns:us-east-1:123456789012:notify-on-system-errors
```

3. Test the alarm.

```
aws cloudwatch set-alarm-state --alarm-name SystemErrorsAlarm --state-reason
"initializing" --state-value OK
```

```
aws cloudwatch set-alarm-state --alarm-name SystemErrorsAlarm --state-reason
"initializing" --state-value ALARM
```

## Logging DynamoDB operations by using AWS CloudTrail

DynamoDB is integrated with AWS CloudTrail, a service that provides a record of actions taken by a user, role, or an AWS service in DynamoDB. CloudTrail captures all API calls for DynamoDB as events. The calls captured include calls from the DynamoDB console and code calls to the DynamoDB API operations, using both PartiQL and the classic API. If you create a trail, you can enable continuous delivery of CloudTrail events to an Amazon S3 bucket, including events for DynamoDB. If you don't configure a trail, you can still view the most recent events in the CloudTrail console in **Event history**. Using the information collected by CloudTrail, you can determine the request that was made to DynamoDB, the IP address from which the request was made, who made the request, when it was made, and additional details.

For robust monitoring and alerting, you can also integrate CloudTrail events with [Amazon CloudWatch Logs](#). To enhance your analysis of DynamoDB service activity and identify changes in activities for an AWS account, you can query AWS CloudTrail logs using [Amazon Athena](#). For example, you can use queries to identify trends and further isolate activity by attributes such as source IP address or user.

To learn more about CloudTrail, including how to configure and enable it, see the [AWS CloudTrail User Guide](#).

### Topics

- [DynamoDB information in CloudTrail \(p. 1133\)](#)
- [Understanding DynamoDB log file entries \(p. 1136\)](#)

## DynamoDB information in CloudTrail

CloudTrail is enabled on your AWS account when you create the account. When supported event activity occurs in DynamoDB, that activity is recorded in a CloudTrail event along with other AWS service events

in **Event history**. You can view, search, and download recent events in your AWS account. For more information, see [Viewing events with CloudTrail event history](#).

For an ongoing record of events in your AWS account, including events for DynamoDB, create a trail. A *trail* enables CloudTrail to deliver log files to an Amazon S3 bucket. By default, when you create a trail in the console, the trail applies to all AWS Regions. The trail logs events from all Regions in the AWS partition and delivers the log files to the Amazon S3 bucket that you specify. Additionally, you can configure other AWS services to further analyze and act upon the event data collected in CloudTrail logs. For more information, see the following:

- [Overview for creating a trail](#)
- [CloudTrail supported services and integrations](#)
- [Configuring Amazon SNS notifications for CloudTrail](#)
- [Receiving CloudTrail log files from multiple regions](#) and [Receiving CloudTrail log files from multiple accounts](#)

## Control plane events in CloudTrail

The following API actions are logged by default as events in CloudTrail files:

### Amazon DynamoDB

- [CreateBackup](#)
- [CreateGlobalTable](#)
- [CreateTable](#)
- [DeleteBackup](#)
- [DeleteTable](#)
- [DescribeBackup](#)
- [DescribeContinuousBackups](#)
- [DescribeGlobalTable](#)
- [DescribeLimits](#)
- [DescribeTable](#)
- [DescribeTimeToLive](#)
- [ListBackups](#)
- [ListTables](#)
- [ListTagsOfResource](#)
- [ListGlobalTables](#)
- [RestoreTableFromBackup](#)
- [RestoreTableToPointInTime](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateGlobalTable](#)
- [UpdateTable](#)
- [UpdateTimeToLive](#)
- [DescribeReservedCapacity \(p. 1081\)](#)
- [DescribeReservedCapacityOfferings \(p. 1081\)](#)

- [PurchaseReservedCapacityOfferings \(p. 1081\)](#)
- [DescribeScalableTargets](#)
- [RegisterScalableTarget](#)

### DynamoDB Streams

- [DescribeStream](#)
- [ListStreams](#)

### DynamoDB Accelerator (DAX)

- [CreateCluster](#)
- [CreateParameterGroup](#)
- [CreateSubnetGroup](#)
- [DecreaseReplicationFactor](#)
- [DeleteCluster](#)
- [DeleteParameterGroup](#)
- [DeleteSubnetGroup](#)
- [DescribeClusters](#)
- [DescribeDefaultParameters](#)
- [DescribeEvents](#)
- [DescribeParameterGroups](#)
- [DescribeParameters](#)
- [DescribeSubnetGroups](#)
- [IncreaseReplicationFactor](#)
- [ListTags](#)
- [RebootNode](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateCluster](#)
- [UpdateParameterGroup](#)
- [UpdateSubnetGroup](#)

### DynamoDB data plane events in CloudTrail

To enable logging of the following API actions in CloudTrail files, you'll need to enable logging of data plane API activity in CloudTrail. See [Logging data events for trails](#) for more information.

Data plane events can be filtered by resource type for granular control over which DynamoDB API calls you want to selectively log and pay for in CloudTrail. For example, by specifying `AWS::DynamoDB::Stream` as a resource type, you can log only calls to the DynamoDB Streams APIs, enabling you to identify security issues while controlling costs. For more information, see [DataResource](#) in the CloudTrail [AWS CloudTrail API reference](#).

### Amazon DynamoDB

- [BatchExecuteStatement](#)

- [BatchGetItem](#)
- [BatchWriteItem](#)
- [DeleteItem](#)
- [ExecuteStatement](#)
- [ExecuteTransaction](#)
- [GetItem](#)
- [PutItem](#)
- [Query](#)
- [Scan](#)
- [TransactGetItems](#)
- [TransactWriteItems](#)
- [UpdateItem](#)

**Note**

DynamoDB Time to Live data plane actions are not logged by CloudTrail

**DynamoDB Streams**

- [GetRecords](#)
- [GetShardIterator](#)

## Understanding DynamoDB log file entries

A trail is a configuration that enables delivery of events as log files to an Amazon S3 bucket that you specify. CloudTrail log files contain one or more log entries. An event represents a single request from any source and includes information about the requested action, the date and time of the action, request parameters, and so on.

Every event or log entry contains information about who generated the request. The identity information helps you determine the following:

- Whether the request was made with root or AWS Identity and Access Management (IAM) user credentials.
- Whether the request was made with temporary security credentials for a role or federated user.
- Whether the request was made by another AWS service.

**Note**

Non key attribute values will be redacted in the CloudTrail logs of actions using the PartiQL API, and will not appear in logs of actions using the classic API.

For more information, see the [CloudTrail userIdentity element](#).

The following examples demonstrate CloudTrail logs of these event types:

**Amazon DynamoDB**

- [UpdateTable \(p. 1137\)](#)
- [DeleteTable \(p. 1138\)](#)
- [CreateCluster \(p. 1139\)](#)

- [PutItem \(Successful\) \(p. 1140\)](#)
- [UpdateItem \(Unsuccessful\) \(p. 1141\)](#)
- [TransactWriteItems \(Successful\) \(p. 1142\)](#)
- [TransactWriteItems \(With TransactionCanceledException\) \(p. 1144\)](#)
- [ExecuteStatement \(p. 1146\)](#)
- [BatchExecuteStatement \(p. 1147\)](#)

## DynamoDB Streams

- [GetRecords \(p. 1148\)](#)

## UpdateTable

```
{  
    "Records": [  
        {  
            "eventVersion": "1.03",  
            "userIdentity": {  
                "type": "AssumedRole",  
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",  
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",  
                "accountId": "111122223333",  
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",  
                "sessionContext": {  
                    "attributes": {  
                        "mfaAuthenticated": "false",  
                        "creationDate": "2015-05-28T18:06:01Z"  
                    },  
                    "sessionIssuer": {  
                        "type": "Role",  
                        "principalId": "AKIAI44QH8DHBEXAMPLE",  
                        "arn": "arn:aws:iam::444455556666:role/admin-role",  
                        "accountId": "444455556666",  
                        "userName": "bob"  
                    }  
                }  
            },  
            "eventTime": "2015-05-04T02:14:52Z",  
            "eventSource": "dynamodb.amazonaws.com",  
            "eventName": "UpdateTable",  
            "awsRegion": "us-west-2",  
            "sourceIPAddress": "192.0.2.0",  
            "userAgent": "console.aws.amazon.com",  
            "requestParameters": {  
                "provisionedThroughput": {  
                    "writeCapacityUnits": 25,  
                    "readCapacityUnits": 25  
                }  
            },  
            "responseElements": {  
                "tableDescription": {  
                    "tableName": "Music",  
                    "attributeDefinitions": [  
                        {  
                            "attributeType": "S",  
                            "attributeName": "Artist"  
                        },  
                        {  
                            "attributeType": "S",  
                            "attributeName": "SongTitle"  
                        }  
                    ]  
                }  
            }  
        }  
    ]  
}
```

```

        }
    ],
    "itemCount": 0,
    "provisionedThroughput": {
        "writeCapacityUnits": 10,
        "numberOfDecreasesToday": 0,
        "readCapacityUnits": 10,
        "lastIncreaseDateTime": "May 3, 2015 11:34:14 PM"
    },
    "creationDateTime": "May 3, 2015 11:34:14 PM",
    "keySchema": [
        {
            "attributeName": "Artist",
            "keyType": "HASH"
        },
        {
            "attributeName": "SongTitle",
            "keyType": "RANGE"
        }
    ],
    "tableStatus": "UPDATING",
    "tableSizeBytes": 0
},
{
    "requestID": "AALNP0J2L244N5O15PKISJ1KUFVV4KQNSO5AEMVJF66Q9ASUAAJG",
    "eventID": "eb834e01-f168-435f-92c0-c36278378b6e",
    "eventType": "AwsApiCall",
    "apiVersion": "2012-08-10",
    "recipientAccountId": "111122223333"
}
]
}

```

## DeleteTable

```
{
    "Records": [
        {
            "eventVersion": "1.03",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "attributes": {
                        "mfaAuthenticated": "false",
                        "creationDate": "2015-05-28T18:06:01Z"
                    },
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    }
                }
            },
            "eventTime": "2015-05-04T13:38:20Z",
            "eventSource": "dynamodb.amazonaws.com",
            "eventName": "DeleteTable",
            "awsRegion": "us-west-2",
            "sourceIPAddress": "192.0.2.0",
            "userAgent": "AmazonDynamoDB"
        }
    ]
}
```

```

        "userAgent": "console.aws.amazon.com",
        "requestParameters": {
            "tableName": "Music"
        },
        "responseElements": {
            "tableDescription": {
                "tableName": "Music",
                "itemCount": 0,
                "provisionedThroughput": {
                    "writeCapacityUnits": 25,
                    "numberOfDecreasesToday": 0,
                    "readCapacityUnits": 25
                },
                "tableStatus": "DELETING",
                "tableSizeBytes": 0
            }
        },
        "requestID": "4KBNVRGD25RG1KEO9UT4V3FQDJVV4KQNSO5AEMVJF66Q9ASUAAJG",
        "eventID": "a954451c-c2fc-4561-8aea-7a30ba1fdf52",
        "eventType": "AwsApiCall",
        "apiVersion": "2012-08-10",
        "recipientAccountId": "111122223333"
    }
}
]
}
}

```

## CreateCluster

```

{
    "Records": [
        {
            "eventVersion": "1.05",
            "userIdentity": {
                "type": "IAMUser",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "userName": "bob"
            },
            "eventTime": "2019-12-17T23:17:34Z",
            "eventSource": "dax.amazonaws.com",
            "eventName": "CreateCluster",
            "awsRegion": "us-west-2",
            "sourceIPAddress": "192.0.2.0",
            "userAgent": "aws-cli/1.16.304 Python/3.6.9
Linux/4.9.184-0.1.ac.235.83.329.metal1.x86_64 botocore/1.13.40",
            "requestParameters": {
                "sS ES Specification": {
                    "enabled": true
                },
                "clusterName": "daxcluster",
                "nodeType": "dax.r4.large",
                "replicationFactor": 3,
                "iamRoleArn": "arn:aws:iam::111122223333:role/
DAXServiceRoleForDynamoDBAccess"
            },
            "responseElements": {
                "cluster": {
                    "securityGroups": [
                        {
                            "securityGroupIdentifier": "sg-1af6e36e",
                            "status": "active"
                        }
                    ]
                }
            }
        }
    ]
}
}

```

```

        ],
        "parameterGroup": {
            "nodeIdsToReboot": [],
            "parameterGroupName": "default.dax1.0",
            "parameterApplyStatus": "in-sync"
        },
        "clusterDiscoveryEndpoint": {
            "port": 8111
        },
        "clusterArn": "arn:aws:dax:us-west-2:111122223333:cache/daxcluster",
        "status": "creating",
        "subnetGroup": "default",
        "sSDescription": {
            "status": "ENABLED",
            "kMSMasterKeyArn": "arn:aws:kms:us-
west-2:111122223333:key/764898e4-adb1-46d6-a762-e2f4225b4fc4"
        },
        "iamRoleArn": "arn:aws:iam::111122223333:role/
DAXServiceRoleForDynamoDBAccess",
        "clusterName": "daxcluster",
        "activeNodes": 0,
        "totalNodes": 3,
        "preferredMaintenanceWindow": "thu:13:00-thu:14:00",
        "nodeType": "dax.r4.large"
    }
},
"requestID": "585adc5f-ad05-4e27-8804-70ba1315f8fd",
"eventID": "29158945-28da-4e32-88e1-56d1b90c1a0c",
"eventType": "AwsApiCall",
"recipientAccountId": "111122223333"
}
]
}

```

## PutItem (Successful)

```
{
    "Records": [
        {
            "eventVersion": "1.06",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "attributes": {
                        "mfaAuthenticated": "false",
                        "creationDate": "2015-05-28T18:06:01Z"
                    },
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    }
                }
            },
            "eventTime": "2019-01-19T15:41:54Z",
            "eventSource": "dynamodb.amazonaws.com",
            "eventName": "PutItem",
            "awsRegion": "us-west-2",
            "eventVersion": "1.06"
        }
    ]
}
```

```

    "sourceIPAddress": "192.0.2.0",
    "userAgent": "aws-cli/1.15.64 Python/2.7.16 Darwin/17.7.0 botocore/1.10.63",
    "requestParameters": {
        "tableName": "Music",
        "key": {
            "Artist": "No One You Know",
            "SongTitle": "Scared of My Shadow"
        },
        "item": [
            "Artist",
            "SongTitle",
            "AlbumTitle"
        ],
        "returnConsumedCapacity": "TOTAL"
    },
    "responseElements": null,
    "requestID": "4KBNVRGD25RG1KEO9UT4V3FQDJVV4KQNSO5AEMVJF66Q9ASUAAJG",
    "eventID": "a954451c-c2fc-4561-8aea-7a30ba1fdf52",
    "readOnly": false,
    "resources": [
        {
            "accountId": "111122223333",
            "type": "AWS::DynamoDB::Table",
            "ARN": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
        }
    ],
    "eventType": "AwsApiCall",
    "apiVersion": "2012-08-10",
    "managementEvent": false,
    "recipientAccountId": "111122223333",
    "eventCategory": "Data"
}
]
}

```

## UpdateItem (Unsuccessful)

```
{
    "Records": [
        {
            "eventVersion": "1.07",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    },
                    "attributes": {
                        "creationDate": "2020-09-03T22:14:13Z",
                        "mfaAuthenticated": "false"
                    }
                }
            },
            "eventTime": "2020-09-03T22:27:15Z",
            "eventSource": "dynamodb.amazonaws.com",
            "eventName": "UpdateItem",
            "awsRegion": "us-east-1"
        }
    ]
}
```

```

    "awsRegion": "us-west-2",
    "sourceIPAddress": "192.0.2.0",
    "userAgent": "aws-cli/1.15.64 Python/2.7.16 Darwin/17.7.0 botocore/1.10.63",
    "errorCode": "ConditionalCheckFailedException",
    "errorMessage": "The conditional request failed",
    "requestParameters": {
        "tableName": "Music",
        "key": {
            "Artist": "No One You Know",
            "SongTitle": "Call Me Today"
        },
        "updateExpression": "SET #Y = :y, #AT = :t",
        "expressionAttributeNames": {
            "#Y": "Year",
            "#AT": "AlbumTitle"
        },
        "conditionExpression": "attribute_not_exists(#Y)",
        "returnConsumedCapacity": "TOTAL"
    },
    "responseElements": null,
    "requestID": "4KBNVRGD25RG1KEO9UT4V3FQDJVV4KQNSO5AEMVJF66Q9ASUAAJG",
    "eventID": "a954451c-c2fc-4561-8aea-7a30ba1fdf52",
    "readOnly": false,
    "resources": [
        {
            "accountId": "111122223333",
            "type": "AWS::DynamoDB::Table",
            "ARN": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
        }
    ],
    "eventType": "AwsApiCall",
    "apiVersion": "2012-08-10",
    "managementEvent": false,
    "recipientAccountId": "111122223333",
    "eventCategory": "Data"
}
]
}

```

## TransactWriteItems (Successful)

```

{
    "Records": [
        {
            "eventVersion": "1.07",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    },
                    "attributes": {
                        "creationDate": "2020-09-03T22:14:13Z",
                        "mfaAuthenticated": "false"
                    }
                }
            }
        }
    ]
}

```

```
},
"eventTime": "2020-09-03T21:48:12Z",
"eventSource": "dynamodb.amazonaws.com",
"eventName": "TransactWriteItems",
"awsRegion": "us-west-1",
"sourceIPAddress": "192.0.2.0",
"userAgent": "aws-cli/1.15.64 Python/2.7.16 Darwin/17.7.0 botocore/1.10.63",
"requestParameters": {
    "requestItems": [
        {
            "operation": "Put",
            "tableName": "Music",
            "key": {
                "Artist": "No One You Know",
                "SongTitle": "Call Me Today"
            },
            "items": [
                "Artist",
                "SongTitle",
                "AlbumTitle"
            ],
            "conditionExpression": "#AT = :A",
            "expressionAttributeNames": {
                "#AT": "AlbumTitle"
            },
            "returnValuesOnConditionCheckFailure": "ALL_OLD"
        },
        {
            "operation": "Update",
            "tableName": "Music",
            "key": {
                "Artist": "No One You Know",
                "SongTitle": "Call Me Tomorrow"
            },
            "updateExpression": "SET #AT = :newval",
            "ConditionExpression": "attribute_not_exists(Rating)",
            "ExpressionAttributeNames": {
                "#AT": "AlbumTitle"
            },
            "returnValuesOnConditionCheckFailure": "ALL_OLD"
        },
        {
            "operation": "Delete",
            "TableName": "Music",
            "key": {
                "Artist": "No One You Know",
                "SongTitle": "Call Me Yesterday"
            },
            "conditionExpression": "#P between :lo and :hi",
            "expressionAttributeNames": {
                "#P": "Price"
            },
            "ReturnValuesOnConditionCheckFailure": "ALL_OLD"
        },
        {
            "operation": "ConditionCheck",
            "TableName": "Music",
            "Key": {
                "Artist": "No One You Know",
                "SongTitle": "Call Me Now"
            },
            "ConditionExpression": "#P between :lo and :hi",
            "ExpressionAttributeNames": {
                "#P": "Price"
            },
            "ReturnValuesOnConditionCheckFailure": "ALL_OLD"
        }
    ]
}
```

```

        }
    ],
    "returnConsumedCapacity": "TOTAL",
    "returnItemCollectionMetrics": "SIZE"
},
"responseElements": null,
"requestID": "45EN320M6TQSMV2MI65O4L5TNFVV4KQNSO5AEMVJF66Q9ASUAAJG",
"eventID": "4f1cc78b-5c94-4174-a6ad-3ee78605381c",
"readOnly": false,
"resources": [
{
    "accountId": "111122223333",
    "type": "AWS::DynamoDB::Table",
    "ARN": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
}
],
"eventType": "AwsApiCall",
"apiVersion": "2012-08-10",
"managementEvent": false,
"recipientAccountId": "111122223333",
"eventCategory": "Data"
}
]
}

```

### TransactWriteItems (With TransactionCanceledException)

```
{
    "Records": [
        {
            "eventVersion": "1.06",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    },
                    "attributes": {
                        "creationDate": "2020-09-03T22:14:13Z",
                        "mfaAuthenticated": "false"
                    }
                }
            },
            "eventTime": "2019-02-01T00:42:34Z",
            "eventSource": "dynamodb.amazonaws.com",
            "eventName": "TransactWriteItems",
            "awsRegion": "us-west-2",
            "sourceIPAddress": "192.0.2.0",
            "userAgent": "aws-cli/1.16.93 Python/3.4.7
Linux/4.9.119-0.1.ac.277.71.329.metal1.x86_64 botocore/1.12.83",
            "errorCode": "TransactionCanceledException",
            "errorMessage": "Transaction cancelled, please refer cancellation reasons for
specific reasons [ConditionalCheckFailed, None]",
            "requestParameters": {
                "requestItems": [
                    {

```

```

        "operation": "Put",
        "tableName": "Music",
        "key": {
            "Artist": "No One You Know",
            "SongTitle": "Call Me Today"
        },
        "items": [
            "Artist",
            "SongTitle",
            "AlbumTitle"
        ],
        "conditionExpression": "#AT = :A",
        "expressionAttributeNames": {
            "#AT": "AlbumTitle"
        },
        "returnValuesOnConditionCheckFailure": "ALL_OLD"
    },
    {
        "operation": "Update",
        "tableName": "Music",
        "key": {
            "Artist": "No One You Know",
            "SongTitle": "Call Me Tomorrow"
        },
        "updateExpression": "SET #AT = :newval",
        "ConditionExpression": "attribute_not_exists(Rating)",
        "ExpressionAttributeNames": {
            "#AT": "AlbumTitle"
        },
        "returnValuesOnConditionCheckFailure": "ALL_OLD"
    },
    {
        "operation": "Delete",
        "TableName": "Music",
        "key": {
            "Artist": "No One You Know",
            "SongTitle": "Call Me Yesterday"
        },
        "conditionExpression": "#P between :lo and :hi",
        "expressionAttributeNames": {
            "#P": "Price"
        },
        "ReturnValuesOnConditionCheckFailure": "ALL_OLD"
    },
    {
        "operation": "ConditionCheck",
        "TableName": "Music",
        "Key": {
            "Artist": "No One You Know",
            "SongTitle": "Call Me Now"
        },
        "ConditionExpression": "#P between :lo and :hi",
        "ExpressionAttributeNames": {
            "#P": "Price"
        },
        "ReturnValuesOnConditionCheckFailure": "ALL_OLD"
    }
],
"returnConsumedCapacity": "TOTAL",
"returnItemCollectionMetrics": "SIZE"
},
"responseElements": null,
"requestID": "A0GTQEKLBB9VD8E05REA5A3E1VVV4KQNSO5AEMVJF66Q9ASUAAJG",
"eventID": "43e437b5-908a-46af-84e6-e27fffb9c5cd",
"readOnly": false,
"resources": [

```

```

        {
            "accountId": "111122223333",
            "type": "AWS::DynamoDB::Table",
            "ARN": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
        }
    ],
    "eventType": "AwsApiCall",
    "apiVersion": "2012-08-10",
    "managementEvent": false,
    "recipientAccountId": "111122223333",
    "eventCategory": "Data"
}
]
}

```

## ExecuteStatement

```

{
    "Records": [
        {
            "eventVersion": "1.08",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    },
                    "attributes": {
                        "creationDate": "2020-09-03T22:14:13Z",
                        "mfaAuthenticated": "false"
                    }
                }
            },
            "eventTime": "2021-03-03T23:06:45Z",
            "eventSource": "dynamodb.amazonaws.com",
            "eventName": "ExecuteStatement",
            "awsRegion": "us-west-2",
            "sourceIPAddress": "192.0.2.0",
            "userAgent": "aws-cli/1.19.7 Python/3.6.13
Linux/4.9.230-0.1.ac.223.84.332.metal1.x86_64 botocore/1.20.7",
            "requestParameters": {
                "statement": "SELECT * FROM Music WHERE Artist = 'No One You Know' AND
SongTitle = 'Call Me Today' AND nonKeyAttr = ****(Redacted)"
            },
            "responseElements": null,
            "requestID": "V7G2KCSFLP830RB7MMFG6RIAD3VV4KQNSO5AEMVJF66Q9ASUAAJG",
            "eventID": "0b5c4779-e169-4227-a1de-6ed01dd18ac7",
            "readOnly": false,
            "resources": [
                {
                    "accountId": "111122223333",
                    "type": "AWS::DynamoDB::Table",
                    "ARN": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
                }
            ],
            "eventType": "AwsApiCall",

```

```

        "apiVersion": "2012-08-10",
        "managementEvent": false,
        "recipientAccountId": "111122223333",
        "eventCategory": "Data"
    }
]
}

```

## BatchExecuteStatement

```

{
    "Records": [
        {
            "eventVersion": "1.08",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    },
                    "attributes": {
                        "creationDate": "2020-09-03T22:14:13Z",
                        "mfaAuthenticated": "false"
                    }
                }
            },
            "eventTime": "2021-03-03T23:24:48Z",
            "eventSource": "dynamodb.amazonaws.com",
            "eventName": "BatchExecuteStatement",
            "awsRegion": "us-west-2",
            "sourceIPAddress": "192.0.2.0",
            "userAgent": "aws-cli/1.19.7 Python/3.6.13
Linux/4.9.230-0.1.ac.223.84.332.metal1.x86_64 botocore/1.20.7",
            "requestParameters": {
                "requestItems": [
                    {
                        "statement": "UPDATE Music SET Album = ***(***) WHERE Artist = 'No One You Know' AND SongTitle = 'Call Me Today'"
                    },
                    {
                        "statement": "INSERT INTO Music VALUE {'Artist' : ***(***) , 'SongTitle' : ***(***) , 'Album' : ***(***)}"
                    }
                ]
            },
            "responseElements": null,
            "requestID": "23PE7ED291UD65P9SMS6TISNVBVV4KQNSO5AEMVJF66Q9ASUAAJG",
            "eventID": "f863f966-b741-4c36-b15e-f867e829035a",
            "readOnly": false,
            "resources": [
                {
                    "accountId": "111122223333",
                    "type": "AWS::DynamoDB::Table",
                    "ARN": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
                }
            ],
        }
    ]
}

```

```

        "eventType": "AwsApiCall",
        "apiVersion": "2012-08-10",
        "managementEvent": false,
        "recipientAccountId": "111122223333",
        "eventCategory": "Data"
    }
]
}

```

## GetRecords

```

{
    "Records": [
        {
            "eventVersion": "1.08",
            "userIdentity": {
                "type": "AssumedRole",
                "principalId": "AKIAIOSFODNN7EXAMPLE:bob",
                "arn": "arn:aws:sts::111122223333:assumed-role/users/bob",
                "accountId": "111122223333",
                "accessKeyId": "AKIAIOSFODNN7EXAMPLE",
                "sessionContext": {
                    "sessionIssuer": {
                        "type": "Role",
                        "principalId": "AKIAI44QH8DHBEXAMPLE",
                        "arn": "arn:aws:iam::444455556666:role/admin-role",
                        "accountId": "444455556666",
                        "userName": "bob"
                    },
                    "attributes": {
                        "creationDate": "2020-09-03T22:14:13Z",
                        "mfaAuthenticated": "false"
                    }
                }
            },
            "eventTime": "2021-04-15T04:15:02Z",
            "eventSource": "dynamodb.amazonaws.com",
            "eventName": "GetRecords",
            "awsRegion": "us-west-2",
            "sourceIPAddress": "192.0.2.0",
            "userAgent": "aws-cli/1.19.50 Python/3.6.13
Linux/4.9.230-0.1.ac.224.84.332.metal1.x86_64 botocore/1.20.50",
            "requestParameters": {
                "shardIterator": "arn:aws:dynamodb:us-west-2:123456789012:table/
Music/stream/2021-04-15T04:02:47.428|1|AAAAAAAAAAH7HF3xwDQHBrvk2UBZ1PKh8bX3F
+JeH0rFwHCE7dz4VGv1ZoJ5bMxQwkmerA3wzCTL+zSseGldSxNJP14EwrjLNvDNoZeRSJ/
n6xc3I4NYOptR4zR8d7VrjMAD6h5nR12NtxGIgJ/dVsUpluWsHyCW3PPbKsMlJSruVRWoitRhSd3S6s1EWEPB0bDC7+
+iSH5mXrCHOnvyezQKlqNshTSPZ5jWwqRj2VNSXCMTGXv9P01/U0bpOUI2cuRTchgpSe3ur2sQrRj3KlbmIyCz7P
+h3CYlugafi8fQ5kipDSkESkIWS605ejzibWKg/3izms1eVIm/
zLfdEihCY7G8fpHUSLX5JAk3ab68aUXGSFZLONntgNihQkcMo00/
mJlaIgkEdBqyqvZ01vtKUBH5YonIrZqSUhv8Coc+mh24v0g1YI+SPIXlr
+Ln154BG6AjrmascjHACVXoPDxPsXSJXC4c9HjoC3YSskCPV7uWi0f65/
n7JAT3cskc2ISaLHwYzJPaMBSftxOgeRLm3BnisL32nT8uTj2gF/
PUrEjdyoqTX7EerQpcaekXmOgay5Kh8n4T2uPdM83f356vRpar/
DDp8pLFD0ddb6Yvz7zU2zGdAvTod3ISc1GpTcqjRxaMh1BVzy1TnI9Cs
+7fxMdUF6xYScjR2725icFBNIojSFVDmsfHabXaCEpmeuXzsLbp5CjcPAHa66R8mQ5tSoFjrzOEzeB4uconEXAMPLE=="
            },
            "responseElements": null,
            "requestID": "1M0U1Q80P4LDPT7A7N1A758N2VVV4KQNSO5AEMVJF66Q9EXAMPLE",
            "eventID": "09a634f2-da7d-4c9e-a259-54aceexample",
            "readOnly": true,
            "resources": [
                {
                    "accountId": "111122223333",

```

```
        "type": "AWS::DynamoDB::Table",
        "ARN": "arn:aws:dynamodb:us-west-2:123456789012:table/Music"
    },
    "eventType": "AwsApiCall",
    "apiVersion": "2012-08-10",
    "managementEvent": false,
    "recipientAccountId": "111122223333",
    "eventCategory": "Data"
}
]
```

## Logging and monitoring in DynamoDB Accelerator

Monitoring is an important part of maintaining the reliability, availability, and performance of Amazon DynamoDB Accelerator (DAX) and your AWS solutions. You should collect monitoring data from all parts of your AWS solution so that you can more easily debug a multi-point failure, if one occurs.

For more information about logging and monitoring in DAX, see [Monitoring DAX \(p. 718\)](#).

## Analyzing data access using CloudWatch contributor insights for DynamoDB

Amazon CloudWatch Contributor Insights for Amazon DynamoDB is a diagnostic tool for identifying the most frequently accessed and throttled keys in your table or index at a glance. This tool uses [CloudWatch contributor insights](#).

By enabling CloudWatch Contributor Insights for DynamoDB on a table or global secondary index, you can view the most accessed and throttled items in those resources.

### Note

CloudWatch charges apply for Contributor Insights for DynamoDB. For more information about pricing, see [Amazon CloudWatch pricing](#).

### Topics

- [CloudWatch contributor insights for DynamoDB: How it works \(p. 1149\)](#)
- [Getting started with CloudWatch contributor insights for DynamoDB \(p. 1153\)](#)
- [Using IAM with CloudWatch contributor insights for DynamoDB \(p. 1157\)](#)

## CloudWatch contributor insights for DynamoDB: How it works

Amazon DynamoDB integrates with [Amazon CloudWatch Contributor Insights](#) to provide information about the most accessed and throttled items in a table or global secondary index. DynamoDB delivers this information to you via CloudWatch Contributor Insights [rules](#), [reports](#), and graphs of report data.

For more information about CloudWatch Contributor Insights, see [Using Contributor Insights to Analyze High-Cardinality Data](#) in the [Amazon CloudWatch User Guide](#).

The following sections describe the core concepts and behavior of CloudWatch Contributor Insights for DynamoDB.

#### Topics

- [CloudWatch contributor insights for DynamoDB rules \(p. 1150\)](#)
- [Understanding CloudWatch contributor insights for DynamoDB graphs \(p. 1151\)](#)
- [Interactions with other DynamoDB features \(p. 1152\)](#)
- [CloudWatch contributor insights for DynamoDB billing \(p. 1153\)](#)

## CloudWatch contributor insights for DynamoDB rules

When you enable CloudWatch Contributor Insights for DynamoDB on a table or global secondary index, DynamoDB creates the following [rules](#) on your behalf:

- **Most accessed items (partition key)** — Identifies the partition keys of the most accessed items in your table or global secondary index.

CloudWatch rule name format: `DynamoDBContributorInsights-PKC-[resource_name]-[creationtimestamp]`

- **Most throttled keys (partition key)** — Identifies the partition keys of the most throttled items in your table or global secondary index.

CloudWatch rule name format: `DynamoDBContributorInsights-PKT-[resource_name]-[creationtimestamp]`

If your table or global secondary index has a sort key, DynamoDB also creates the following rules specific to sort keys:

- **Most accessed keys (partition and sort keys)** — Identifies the partition and sort keys of the most accessed items in your table or global secondary index.

CloudWatch rule name format: `DynamoDBContributorInsights-SKC-[resource_name]-[creationtimestamp]`

- **Most throttled keys (partition and sort keys)** — Identifies the partition and sort keys of the most throttled items in your table or global secondary index.

CloudWatch rule name format: `DynamoDBContributorInsights-SKT-[resource_name]-[creationtimestamp]`

#### Note

- You can't use the CloudWatch console or APIs to directly modify or delete the rules created by CloudWatch Contributor Insights for DynamoDB. Disabling CloudWatch Contributor Insights for DynamoDB on a table or global secondary index automatically deletes the rules created for that table or global secondary index.
- When you use the [GetInsightRuleReport](#) operation with CloudWatch Contributor Insights rules that are created by DynamoDB, only `MaxContributorValue` and `Maximum` return useful statistics. The other statistics in this list don't return meaningful values.

You can create CloudWatch Alarms using the CloudWatch Contributor Insights for DynamoDB [rules](#). This allows you to be notified when any item exceed or meets a specific threshold for `ConsumedThroughputUnits` or `ThrottleCount`. For more information, see [Setting an Alarm on Contributor Insights Metric Data](#).

## Understanding CloudWatch contributor insights for DynamoDB graphs

CloudWatch Contributor Insights for DynamoDB displays two types of graphs on both the DynamoDB and CloudWatch consoles: *Most Accessed Items* and *Most Throttled Items*.

### Most accessed items

Use this graph to identify the most accessed items in the table or global secondary index. The graph displays `ConsumedThroughputUnits` on the y-axis and time on the x-axis. Each of the top N keys is displayed in its own color, with a legend displayed below the x-axis.

DynamoDB measures key access frequency by using `ConsumedThroughputUnits`, which measures combined read and write traffic. `ConsumedThroughputUnits` is defined as the following:

- Provisioned —  $(3 \times \text{consumed write capacity units}) + \text{consumed read capacity units}$
- On-demand —  $(3 \times \text{write request units}) + \text{read request units}$

On the DynamoDB console, each data point in the graph represents the maximum of `ConsumedThroughputUnits` over a 1-minute period. For example, a graph value of 180,000 `ConsumedThroughputUnits` indicates that the item was accessed continuously at the per-item maximum throughput of 1,000 write request units or 3,000 read request units for a 60-second span within that 1-minute period (3,000 x 60 seconds). In other words, the graphed values represent the highest-traffic minute within each 1-minute period. You can change the time granularity of the `ConsumedThroughputUnits` metric (for example, to view 5-minute metrics instead of 1-minute) on the CloudWatch console.

If you see several closely clustered lines without any obvious outliers, it indicates that your workload is relatively balanced across items over the given time window. If you see isolated points in the graph instead of connected lines, it indicates an item that was frequently accessed only for a brief period.

If your table or global secondary index has a sort key, DynamoDB creates two graphs: one for the most accessed partition keys and one for the most accessed partition + sort key pairs. You can see traffic at the partition key level in the partition key-only graph. You can see traffic at the item level in the partition + sort key graphs.

### Most throttled items

Use this graph to identify the most throttled items in the table or global secondary index. The graph displays `ThrottleCount` on the y-axis and time on the x-axis. Each of the top N keys is displayed in its own color, with a legend displayed below the x-axis.

DynamoDB measures throttle frequency using `ThrottleCount`, which is the count of `ProvisionedThroughputExceededException`, `ThrottlingException`, and `RequestLimitExceeded` errors.

Write throttling caused by insufficient write capacity for a global secondary index is not measured. You can use the *Most Accessed Items* graph of the global secondary index to identify imbalanced access patterns that may cause write throttling. For more information, see [Provisioned Throughput Considerations for Global Secondary Indexes](#).

On the DynamoDB console, each data point in the graph represents the count of throttle events over a 1-minute period.

If you see no data in this graph, it indicates that your requests are not being throttled. If you see isolated points in the graph instead of connected lines, it indicates that an item was frequently throttled for a brief period.

If your table or global secondary index has a sort key, DynamoDB creates two graphs: one for most throttled partition keys and one for most throttled partition + sort key pairs. You can see throttle count at the partition key level in the partition key-only graph, and throttle count at the item-level in the partition + sort key graphs.

## Report examples

The following are examples of the reports generated for a table with both a partition key and a sort key.



## Interactions with other DynamoDB features

The following sections describe how CloudWatch Contributor Insights for DynamoDB behaves and interacts with several other features in DynamoDB.

### Global tables

CloudWatch Contributor Insights for DynamoDB monitors global table replicas as distinct tables. The Contributor Insights graphs for a replica in one AWS Region might not show the same patterns as another Region. This is because write data is replicated across all replicas in a global table, but each replica can serve Region-bound read traffic.

### DynamoDB Accelerator (DAX)

CloudWatch Contributor Insights for DynamoDB doesn't show DAX cache responses. It only shows responses to accessing a table or a global secondary index.

### Encryption at rest

CloudWatch Contributor Insights for DynamoDB doesn't affect how encryption works in DynamoDB. The primary key data that is published in CloudWatch is encrypted with the AWS owned key. However, DynamoDB also supports the AWS managed key and a customer managed key.

CloudWatch Contributor Insights for DynamoDB graphs display the partition key and sort key (if applicable) of frequently accessed items and frequently throttled items in plaintext. If you require the use of AWS Key Management Service (KMS) to encrypt this table's partition key and sort key data with an AWS managed key or customer managed key, you should not enable CloudWatch Contributor Insights for DynamoDB for this table.

If you require your primary key data to be encrypted with the AWS managed key or a customer managed key, you should not enable CloudWatch Contributor Insights for DynamoDB for that table.

### Fine-grained access control

CloudWatch Contributor Insights for DynamoDB doesn't function differently for tables with fine-grained access control (FGAC). In other words, any user who has the appropriate CloudWatch permissions can view FGAC-protected primary keys in CloudWatch Contributor Insights graphs.

If the table's primary key contains FGAC-protected data that you don't want published to CloudWatch, you should not enable CloudWatch Contributor Insights for DynamoDB for that table.

### Access control

You control access to CloudWatch Contributor Insights for DynamoDB using AWS Identity and Access Management (IAM) by limiting DynamoDB control plane permissions and CloudWatch data plane permissions. For more information see, [Using IAM with CloudWatch Contributor Insights for DynamoDB](#).

## CloudWatch contributor insights for DynamoDB billing

Charges for CloudWatch Contributor Insights for DynamoDB appear in the [CloudWatch](#) section of your monthly bill. These charges are calculated based on the number of DynamoDB events that are processed. For tables and global secondary indexes with CloudWatch Contributor Insights for DynamoDB enabled, each item that is written or read via a [data plane](#) operation represents one event.

If a table or global secondary index includes a sort key, each item that is read or written represents two events. This is because DynamoDB is identifying top contributors from separate time series: one for partitions keys only, and one for partition and sort key pairs.

For example, assume that your application performs the following DynamoDB operations: a `GetItem`, a `PutItem`, and a `BatchWriteItem` that puts five items

- If your table or global secondary index has only a partition key, it results in 7 events (1 for the `GetItem`, 1 for the `PutItem`, and 5 for the `BatchWriteItem`).
- If your table or global secondary index has a partition key and sort key, it results in 14 events (2 for the `GetItem`, 2 for the `PutItem`, and 10 for the `BatchWriteItem`).
- A `Query` operation always results in 1 event, regardless of the number of items returned.

Unlike other DynamoDB features, CloudWatch Contributor Insights for DynamoDB billing *does not* vary based on the following:

- The [capacity mode](#) (provisioned vs. on-demand)
- Whether you perform read or write requests
- The size (KB) of the items read or written

## Getting started with CloudWatch contributor insights for DynamoDB

This section describes how to use Amazon CloudWatch Contributor Insights with the Amazon DynamoDB console or the AWS Command Line Interface (AWS CLI).


In the following examples, you use the DynamoDB table that is defined in the [Getting started with DynamoDB tutorial](#).

### Topics


- [Using contributor insights \(console\) \(p. 1154\)](#)
- [Using contributor insights \(AWS CLI\) \(p. 1157\)](#)

## Using contributor insights (console)

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Tables**.
3. Choose the **Music** table.
4. Choose the **Contributor Insights** tab.
5. Choose **Manage Contributor Insights**.




6. In the **Manage Contributor Insights** dialog box, under **Contributor Insights Status**, choose **Enabled** for both the **Music** base table and the **AlbumTitle-index** global secondary index. Then choose **Confirm**.




If the operation fails, see [DescribeContributorInsightsFailureException](#) in the *Amazon DynamoDB API Reference* for possible reasons.

**7. Choose View in DynamoDB.**



**8. The Contributor Insights graphs are now visible on the **Contributor Insights** tab for the **Music** table.**




## Creating CloudWatch alarms

Follow these steps to create a CloudWatch alarm and be notified when any partition key consumes more than 50,000 `ConsumedThroughputUnits`.


1. Sign in to the AWS Management Console and open the CloudWatch console at <https://console.aws.amazon.com/cloudwatch/>
2. In the navigation pane on the left side of the console, choose **Contributor Insights**.
3. Choose the **DynamoDBContributorInsights-PKC-Music** rule.
4. Choose the **Actions** drop down.
5. Choose **View in metrics**.
6. Choose **Max Contributor Value**.

**Note**

Only `Max Contributor Value` and `Maximum` return useful statistics. The other statistics in this list don't return meaningful values.



**7. On the Actions column, Choose Create Alarm.**



**8. Enter a value of 50000 for threshold and choose Next.**

**9. See [Using Amazon CloudWatch alarms](#) for details on how to configure the notification for the alarm.**

## Using contributor insights (AWS CLI)

1. Enable CloudWatch Contributor Insights for DynamoDB on the `Music` base table.

```
aws dynamodb update-contributor-insights --table-name Music --contributor-insights-action=ENABLE
```

2. Enable Contributor Insights for DynamoDB on the `AlbumTitle-index` global secondary index.

```
aws dynamodb update-contributor-insights --table-name Music --index-name AlbumTitle-index --contributor-insights-action=ENABLE
```

3. Get the status and rules for the `Music` table and all its indexes.

```
aws dynamodb describe-contributor-insights --table-name Music
```

4. Disable CloudWatch Contributor Insights for DynamoDB on the `AlbumTitle-index` global secondary index.

```
aws dynamodb update-contributor-insights --table-name Music --index-name AlbumTitle-index --contributor-insights-action=DISABLE
```

5. Get the status of the `Music` table and all its indexes.

```
aws dynamodb list-contributor-insights --table-name Music
```

## Using IAM with CloudWatch contributor insights for DynamoDB

The first time that you enable Amazon CloudWatch Contributor Insights for Amazon DynamoDB, DynamoDB automatically creates an AWS Identity and Access Management (IAM) service-linked role for you. This role, `AWSServiceRoleForDynamoDBCloudWatchContributorInsights`, allows DynamoDB to manage CloudWatch Contributor Insights rules on your behalf. Don't delete this service-linked role. If you delete it, all your managed rules will no longer be cleaned up when you delete your table or global secondary index.

For more information about service-linked roles, see [Using service-linked roles](#) in the *IAM User Guide*.

The following permissions are required:

- To enable or disable CloudWatch Contributor Insights for DynamoDB, you must have `dynamodb:UpdateContributorInsights` permission on the table or index.
- To view CloudWatch Contributor Insights for DynamoDB graphs, you must have `cloudwatch:GetInsightRuleReport` permission.
- To describe CloudWatch Contributor Insights for DynamoDB for a given DynamoDB table or index, you must have `dynamodb:DescribeContributorInsights` permission.
- To list CloudWatch Contributor Insights for DynamoDB statuses for each table and global secondary index, you must have `dynamodb>ListContributorInsights` permission.

## Example: Enable or disable CloudWatch contributor insights for DynamoDB

The following IAM policy grants permissions to enable or disable CloudWatch Contributor Insights for DynamoDB.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": "iam:CreateServiceLinkedRole",  
            "Resource": "arn:aws:iam::*:role/aws-service-role/  
contributorinsights.dynamodb.amazonaws.com/  
AWSServiceRoleForDynamoDBCloudWatchContributorInsights",  
            "Condition": {"StringLike": {"iam:AWSServiceName":  
"contributorinsights.dynamodb.amazonaws.com"}}  
        },  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:UpdateContributorInsights"  
            ],  
            "Resource": "arn:aws:dynamodb:*:*:table/*"  
        }  
    ]  
}
```

For tables encrypted by KMS key, the user needs to have kms:Decrypt permissions in order to update Contributor Insights.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": "iam:CreateServiceLinkedRole",  
            "Resource": "arn:aws:iam::*:role/aws-service-role/  
contributorinsights.dynamodb.amazonaws.com/  
AWSServiceRoleForDynamoDBCloudWatchContributorInsights",  
            "Condition": {"StringLike": {"iam:AWSServiceName":  
"contributorinsights.dynamodb.amazonaws.com"}}  
        },  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:UpdateContributorInsights"  
            ],  
            "Resource": "arn:aws:dynamodb:*:*:table/*"  
        },  
        {  
            "Effect": "Allow",  
            "Resource": "arn:aws:kms:*:*:key/*",  
            "Action": [  
                "kms:Decrypt"  
            ],  
        }  
    ]  
}
```

## Example: Retrieve CloudWatch contributor insights rule report

The following IAM policy grants permissions to retrieve CloudWatch Contributor Insights rule report.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "cloudwatch:GetInsightRuleReport"  
            ],  
            "Resource": "arn:aws:cloudwatch:*:*:insight-rule/DynamoDBContributorInsights*"  
        }  
    ]  
}
```

## Example: Selectively apply CloudWatch contributor insights for DynamoDB permissions based on resource

The following IAM policy grants permissions to allow the `ListContributorInsights` and `DescribeContributorInsights` actions and denies the `UpdateContributorInsights` action for a specific global secondary index.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb>ListContributorInsights",  
                "dynamodb:DescribeContributorInsights"  
            ],  
            "Resource": "*"  
        },  
        {  
            "Effect": "Deny",  
            "Action": [  
                "dynamodb:UpdateContributorInsights"  
            ],  
            "Resource": "arn:aws:dynamodb:us-west-2:123456789012:table/Books/index/Author-  
index"  
        }  
    ]  
}
```

## Using service-linked roles for CloudWatch Contributor Insights for DynamoDB

CloudWatch Contributor Insights for DynamoDB uses AWS Identity and Access Management (IAM) [service-linked roles](#). A service-linked role is a unique type of IAM role that is linked directly to CloudWatch Contributor Insights for DynamoDB. Service-linked roles are predefined by CloudWatch Contributor Insights for DynamoDB and include all the permissions that the service requires to call other AWS services on your behalf.

A service-linked role makes setting up CloudWatch Contributor Insights for DynamoDB easier because you don't have to manually add the necessary permissions. CloudWatch Contributor Insights for DynamoDB defines the permissions of its service-linked roles, and unless defined otherwise, only

CloudWatch Contributor Insights for DynamoDB can assume its roles. The defined permissions include the trust policy and the permissions policy, and that permissions policy cannot be attached to any other IAM entity.

For information about other services that support service-linked roles, see [AWS Services That Work with IAM](#) and look for the services that have **Yes** in the **Service-Linked Role** column. Choose a **Yes** with a link to view the service-linked role documentation for that service.

## Service-linked role permissions for CloudWatch Contributor Insights for DynamoDB

CloudWatch Contributor Insights for DynamoDB uses the service-linked role named **AWSServiceRoleForDynamoDBCloudWatchContributorInsights**. The purpose of the service-linked role is to allow Amazon DynamoDB to manage Amazon CloudWatch Contributor Insights rules created for DynamoDB tables and global secondary indexes, on your behalf.

The **AWSServiceRoleForDynamoDBCloudWatchContributorInsights** service-linked role trusts the following services to assume the role:

- `contributorinsights.dynamodb.amazonaws.com`

The role permissions policy allows CloudWatch Contributor Insights for DynamoDB to complete the following actions on the specified resources:

- Action: `Create and manage Insight Rules on DynamoDBContributorInsights`

You must configure permissions to allow an IAM entity (such as a user, group, or role) to create, edit, or delete a service-linked role. For more information, see [Service-Linked Role Permissions](#) in the *IAM User Guide*.

## Creating a service-linked role for CloudWatch Contributor Insights for DynamoDB

You don't need to manually create a service-linked role. When you enable Contributor Insights in the AWS Management Console, the AWS CLI, or the AWS API, CloudWatch Contributor Insights for DynamoDB creates the service-linked role for you.

If you delete this service-linked role, and then need to create it again, you can use the same process to recreate the role in your account. When you enable Contributor Insights, CloudWatch Contributor Insights for DynamoDB creates the service-linked role for you again.

## Editing a service-linked role for CloudWatch Contributor Insights for DynamoDB

CloudWatch Contributor Insights for DynamoDB does not allow you to edit the **AWSServiceRoleForDynamoDBCloudWatchContributorInsights** service-linked role. After you create a service-linked role, you cannot change the name of the role because various entities might reference the role. However, you can edit the description of the role using IAM. For more information, see [Editing a Service-Linked Role](#) in the *IAM User Guide*.

## Deleting a service-linked role for CloudWatch Contributor Insights for DynamoDB

You don't need to manually delete the **AWSServiceRoleForDynamoDBCloudWatchContributorInsights** role. When you disable Contributor Insights in the AWS Management Console, the AWS CLI, or the AWS API, CloudWatch Contributor Insights for DynamoDB cleans up the resources.

You can also use the IAM console, the AWS CLI or the AWS API to manually delete the service-linked role. To do this, you must first manually clean up the resources for your service-linked role and then you can manually delete it.

**Note**

If the CloudWatch Contributor Insights for DynamoDB service is using the role when you try to delete the resources, then the deletion might fail. If that happens, wait for a few minutes and try the operation again.

**To manually delete the service-linked role using IAM**

Use the IAM console, the AWS CLI, or the AWS API to delete the `AWSServiceRoleForDynamoDBCloudWatchContributorInsights` service-linked role. For more information, see [Deleting a Service-Linked Role](#) in the *IAM User Guide*.

# Best practices for designing and architecting with DynamoDB

Use this section to quickly find recommendations for maximizing performance and minimizing throughput costs when working with Amazon DynamoDB.

## Contents

- [NoSQL design for DynamoDB \(p. 1163\)](#)
  - Differences between relational data design and NoSQL (p. 1163)
  - Two key concepts for NoSQL design (p. 1164)
  - Approaching NoSQL design (p. 1164)
- [Best practices for designing and using partition keys effectively \(p. 1165\)](#)
  - Using burst capacity effectively (p. 1165)
  - Understanding DynamoDB adaptive capacity (p. 1165)
    - Boost throughput capacity to high-traffic partitions (p. 1166)
    - Isolate frequently accessed items (p. 1166)
  - Designing partition keys to distribute your workload evenly (p. 1167)
  - Using write sharding to distribute workloads evenly (p. 1167)
    - Sharding using random suffixes (p. 1168)
    - Sharding using calculated suffixes (p. 1168)
  - Distributing write activity efficiently during data upload (p. 1168)
- [Best practices for using sort keys to organize data \(p. 1169\)](#)
  - Using sort keys for version control (p. 1170)
- [Best practices for using secondary indexes in DynamoDB \(p. 1171\)](#)
  - General guidelines for secondary indexes in DynamoDB (p. 1171)
    - Use indexes efficiently (p. 1172)
    - Choose projections carefully (p. 1172)
    - Optimize frequent queries to avoid fetches (p. 1172)
    - Be aware of item-collection size limits when creating local secondary indexes (p. 1173)
  - Take advantage of sparse indexes (p. 1173)
    - Examples of sparse indexes in DynamoDB (p. 1173)
  - Using Global Secondary Indexes for materialized aggregation queries (p. 1174)
  - Overloading Global Secondary Indexes (p. 1175)
  - Using Global Secondary Index write sharding for selective table queries (p. 1176)
  - Using Global Secondary Indexes to create an eventually consistent replica (p. 1177)
- [Best practices for storing large items and attributes \(p. 1178\)](#)
  - Compressing large attribute values (p. 1178)
  - Storing large attribute values in Amazon S3 (p. 1178)
- [Best practices for handling time series data in DynamoDB \(p. 1179\)](#)
  - Design pattern for time series data (p. 1179)

- Time series table examples (p. 1179)
- Best practices for managing many-to-many relationships (p. 1180)
  - Adjacency list design pattern (p. 1180)
  - Materialized graph pattern (p. 1181)
- Best practices for implementing a hybrid database system (p. 1184)
  - If you don't want to migrate everything to DynamoDB (p. 1184)
  - How a hybrid system can be implemented (p. 1185)
- Best practices for modeling relational data in DynamoDB (p. 1185)
  - First steps for modeling relational data in DynamoDB (p. 1187)
  - Example of modeling relational data in DynamoDB (p. 1188)
- Best practices for querying and scanning data (p. 1191)
  - Performance considerations for scans (p. 1191)
  - Avoiding sudden spikes in read activity (p. 1191)
  - Taking advantage of parallel scans (p. 1194)
    - Choosing TotalSegments (p. 1194)

## NoSQL design for DynamoDB

NoSQL database systems like Amazon DynamoDB use alternative models for data management, such as key-value pairs or document storage. When you switch from a relational database management system to a NoSQL database system like DynamoDB, it's important to understand the key differences and specific design approaches.

### Topics

- Differences between relational data design and NoSQL (p. 1163)
- Two key concepts for NoSQL design (p. 1164)
- Approaching NoSQL design (p. 1164)

## Differences between relational data design and NoSQL

Relational database systems (RDBMS) and NoSQL databases have different strengths and weaknesses:

- In RDBMS, data can be queried flexibly, but queries are relatively expensive and don't scale well in high-traffic situations (see [First steps for modeling relational data in DynamoDB \(p. 1187\)](#)).
- In a NoSQL database such as DynamoDB, data can be queried efficiently in a limited number of ways, outside of which queries can be expensive and slow.

These differences make database design different between the two systems:

- In RDBMS, you design for flexibility without worrying about implementation details or performance. Query optimization generally doesn't affect schema design, but normalization is important.
- In DynamoDB, you design your schema specifically to make the most common and important queries as fast and as inexpensive as possible. Your data structures are tailored to the specific requirements of your business use cases.

## Two key concepts for NoSQL design

NoSQL design requires a different mindset than RDBMS design. For an RDBMS, you can go ahead and create a normalized data model without thinking about access patterns. You can then extend it later when new questions and query requirements arise. You can organize each type of data into its own table.

### How NoSQL design is different

- By contrast, you shouldn't start designing your schema for DynamoDB until you know the questions it will need to answer. Understanding the business problems and the application use cases up front is essential.
- You should maintain as few tables as possible in a DynamoDB application. Having fewer tables keeps things more scalable, requires less permissions management, and reduces overhead for your DynamoDB application. It can also help keep backup costs lower overall.

## Approaching NoSQL design

*The first step in designing your DynamoDB application is to identify the specific query patterns that the system must satisfy.*

In particular, it is important to understand three fundamental properties of your application's access patterns before you begin:

- **Data size:** Knowing how much data will be stored and requested at one time will help determine the most effective way to partition the data.
- **Data shape:** Instead of reshaping data when a query is processed (as an RDBMS system does), a NoSQL database organizes data so that its shape in the database corresponds with what will be queried. This is a key factor in increasing speed and scalability.
- **Data velocity:** DynamoDB scales by increasing the number of physical partitions that are available to process queries, and by efficiently distributing data across those partitions. Knowing in advance what the peak query loads will be might help determine how to partition data to best use I/O capacity.

After you identify specific query requirements, you can organize data according to general principles that govern performance:

- **Keep related data together.** Research on routing-table optimization 20 years ago found that "locality of reference" was the single most important factor in speeding up response time: keeping related data together in one place. This is equally true in NoSQL systems today, where keeping related data in close proximity has a major impact on cost and performance. Instead of distributing related data items across multiple tables, you should keep related items in your NoSQL system as close together as possible.

As a general rule, you should maintain as few tables as possible in a DynamoDB application.

Exceptions are cases where high-volume time series data are involved, or datasets that have very different access patterns. A single table with inverted indexes can usually enable simple queries to create and retrieve the complex hierarchical data structures required by your application.

- **Use sort order.** Related items can be grouped together and queried efficiently if their key design causes them to sort together. This is an important NoSQL design strategy.
- **Distribute queries.** It is also important that a high volume of queries not be focused on one part of the database, where they can exceed I/O capacity. Instead, you should design data keys to distribute traffic evenly across partitions as much as possible, avoiding "hot spots."
- **Use global secondary indexes.** By creating specific global secondary indexes, you can enable different queries than your main table can support, and that are still fast and relatively inexpensive.

These general principles translate into some common design patterns that you can use to model data efficiently in DynamoDB.

## Best practices for designing and using partition keys effectively

The primary key that uniquely identifies each item in an Amazon DynamoDB table can be simple (a partition key only) or composite (a partition key combined with a sort key).

Generally speaking, you should design your application for uniform activity across all logical partition keys in the table and its secondary indexes. You can determine the access patterns that your application requires, and read and write units that each table and secondary index requires.

By default, every partition in the table will strive to deliver the full capacity of 3,000 RCU and 1,000 WCU. The total throughput across all partitions in the table may be constrained by the provisioned throughput in provisioned mode, or by the table level throughput limit in on-demand mode. See [Service Quotas](#) for more information.

### Topics

- [Using burst capacity effectively \(p. 1165\)](#)
- [Understanding DynamoDB adaptive capacity \(p. 1165\)](#)
- [Designing partition keys to distribute your workload evenly \(p. 1167\)](#)
- [Using write sharding to distribute workloads evenly \(p. 1167\)](#)
- [Distributing write activity efficiently during data upload \(p. 1168\)](#)

## Using burst capacity effectively

DynamoDB provides some flexibility for your throughput provisioning with *burst capacity*. Whenever you're not fully using your available throughput, DynamoDB reserves a portion of that unused capacity for later *bursts* of throughput to handle usage spikes.

DynamoDB currently retains up to 5 minutes (300 seconds) of unused read and write capacity. During an occasional burst of read or write activity, these extra capacity units can be consumed quickly—even faster than the per-second provisioned throughput capacity that you've defined for your table.

DynamoDB can also consume burst capacity for background maintenance and other tasks without prior notice.

Note that these burst capacity details might change in the future.

## Understanding DynamoDB adaptive capacity

*Adaptive capacity* is a feature that enables DynamoDB to run imbalanced workloads indefinitely. It minimizes throttling due to throughput exceptions. It also helps you reduce costs by enabling you to provision only the throughput capacity that you need.

Adaptive capacity is enabled automatically for every DynamoDB table, at no additional cost. You don't need to explicitly enable or disable it.

### Topics

- [Boost throughput capacity to high-traffic partitions \(p. 1166\)](#)

- [Isolate frequently accessed items \(p. 1166\)](#)


## Boost throughput capacity to high-traffic partitions

It's not always possible to distribute read and write activity evenly. When data access is imbalanced, a "hot" partition can receive a higher volume of read and write traffic compared to other partitions. As read and write operations on a partition are managed independently, throttling will occur if a single partition receives more than 3000 read operation or more than 1000 write operations.

To better accommodate uneven access patterns, DynamoDB adaptive capacity enables your application to continue reading and writing to hot partitions without being throttled, provided that traffic does not exceed your table's total provisioned capacity or the partition maximum capacity. Adaptive capacity works by automatically and instantly increasing throughput capacity for partitions that receive more traffic.

The following diagram illustrates how adaptive capacity works. The example table is provisioned with 400 WCUs evenly shared across four partitions, allowing each partition to sustain up to 100 WCUs per second. Partitions 1, 2, and 3 each receives write traffic of 50 WCU/sec. Partition 4 receives 150 WCU/sec. This hot partition can accept write traffic while it still has unused burst capacity, but eventually it throttles traffic that exceeds 100 WCU/sec.

DynamoDB adaptive capacity responds by increasing partition 4's capacity so that it can sustain the higher workload of 150 WCU/sec without being throttled.



## Isolate frequently accessed items

If your application drives disproportionately high traffic to one or more items, adaptive capacity rebalances your partitions such that frequently accessed items don't reside on the same partition. This isolation of frequently accessed items reduces the likelihood of request throttling due to your workload exceeding the throughput quota on a single partition. You can also break up an item collection into segments by sort key, as long as the item collection isn't traffic that is tracked by a monotonic increase or decrease of the sort key.

If your application drives consistently high traffic to a single item, adaptive capacity might rebalance your data so that a partition contains only that single, frequently accessed item. In this case, DynamoDB can deliver throughput up to the partition maximum of 3,000 RCU and 1,000 WCUs to that single item's primary key. Adaptive capacity will not split item collections across multiple partitions of the table when there is a [local secondary index](#) on the table.

### Note

This isolation functionality is not available for tables using [Provisioned Read/Write Capacity Mode](#) that have enabled [DynamoDB Streams](#).

## Designing partition keys to distribute your workload evenly

The partition key portion of a table's primary key determines the logical partitions in which a table's data is stored. This in turn affects the underlying physical partitions. A partition key design that doesn't distribute I/O requests evenly can create "hot" partitions that result in throttling and use your provisioned I/O capacity inefficiently.

The optimal usage of a table's provisioned throughput depends not only on the workload patterns of individual items, but also on the partition key design. This doesn't mean that you must access all partition key values to achieve an efficient throughput level, or even that the percentage of accessed partition key values must be high. It does mean that the more distinct partition key values that your workload accesses, the more those requests will be spread across the partitioned space. In general, you will use your provisioned throughput more efficiently as the ratio of partition key values accessed to the total number of partition key values increases.

The following is a comparison of the provisioned throughput efficiency of some common partition key schemas.

Partition key value	Uniformity
User ID, where the application has many users.	Good
Status code, where there are only a few possible status codes.	Bad
Item creation date, rounded to the nearest time period (for example, day, hour, or minute).	Bad
Device ID, where each device accesses data at relatively similar intervals.	Good
Device ID, where even if there are many devices being tracked, one is by far more popular than all the others.	Bad

If a single table has only a small number of partition key values, consider distributing your write operations across more distinct partition key values. In other words, structure the primary key elements to avoid one "hot" (heavily requested) partition key value that slows overall performance.

For example, consider a table with a composite primary key. The partition key represents the item's creation date, rounded to the nearest day. The sort key is an item identifier. On a given day, say 2014-07-09, **all** of the new items are written to that single partition key value (and corresponding physical partition).

If the table fits entirely into a single partition (considering growth of your data over time), and if your application's read and write throughput requirements don't exceed the read and write capabilities of a single partition, your application won't encounter any unexpected throttling as a result of partitioning.

## Using write sharding to distribute workloads evenly

One way to better distribute writes across a partition key space in Amazon DynamoDB is to expand the space. You can do this in several different ways. You can add a random number to the partition key values to distribute the items among partitions. Or you can use a number that is calculated based on something that you're querying on.

## Sharding using random suffixes

One strategy for distributing loads more evenly across a partition key space is to add a random number to the end of the partition key values. Then you randomize the writes across the larger space.

For example, for a partition key that represents today's date, you might choose a random number between 1 and 200 and concatenate it as a suffix to the date. This yields partition key values like 2014-07-09.1, 2014-07-09.2, and so on, through 2014-07-09.200. Because you are randomizing the partition key, the writes to the table on each day are spread evenly across multiple partitions. This results in better parallelism and higher overall throughput.

However, to read all the items for a given day, you would have to query the items for all the suffixes and then merge the results. For example, you would first issue a `Query` request for the partition key value 2014-07-09.1. Then issue another `Query` for 2014-07-09.2, and so on, through 2014-07-09.200. Finally, your application would have to merge the results from all those `Query` requests.

## Sharding using calculated suffixes

A randomizing strategy can greatly improve write throughput. But it's difficult to read a specific item because you don't know which suffix value was used when writing the item. To make it easier to read individual items, you can use a different strategy. Instead of using a random number to distribute the items among partitions, use a number that you can calculate based upon something that you want to query on.

Consider the previous example, in which a table uses today's date in the partition key. Now suppose that each item has an accessible `OrderId` attribute, and that you most often need to find items by order ID in addition to date. Before your application writes the item to the table, it could calculate a hash suffix based on the order ID and append it to the partition key date. The calculation might generate a number between 1 and 200 that is fairly evenly distributed, similar to what the random strategy produces.

A simple calculation would likely suffice, such as the product of the UTF-8 code point values for the characters in the order ID, modulo 200, + 1. The partition key value would then be the date concatenated with the calculation result.

With this strategy, the writes are spread evenly across the partition key values, and thus across the physical partitions. You can easily perform a `GetItem` operation for a particular item and date because you can calculate the partition key value for a specific `OrderId` value.

To read all the items for a given day, you still must `query` each of the 2014-07-09.N keys (where N is 1–200), and your application then has to merge all the results. The benefit is that you avoid having a single "hot" partition key value taking all of the workload.

### Note

For a more efficient strategy specifically designed to handle high-volume time series data, see [Time series data \(p. 1179\)](#).

## Distributing write activity efficiently during data upload

Typically, when you load data from other data sources, Amazon DynamoDB partitions your table data on multiple servers. You get better performance if you upload data to all the allocated servers simultaneously.

For example, suppose that you want to upload user messages to a DynamoDB table that uses a composite primary key with `UserID` as the partition key and `MessageID` as the sort key.

When you upload the data, one approach you can take is to upload all message items for each user, one user after another:

UserID	MessageID
U1	1
U1	2
U1	...
U1	... up to 100
U2	1
U2	2
U2	...
U2	... up to 200

The problem in this case is that you are not distributing your write requests to DynamoDB across your partition key values. You are taking one partition key value at a time and uploading all of its items before going to the next partition key value and doing the same.

Behind the scenes, DynamoDB is partitioning the data in your table across multiple servers. To fully use all the throughput capacity that is provisioned for the table, you must distribute your workload across your partition key values. By directing an uneven amount of upload work toward items that all have the same partition key value, you are not fully using all the resources that DynamoDB has provisioned for your table.

You can distribute your upload work by using the sort key to load one item from each partition key value, then another item from each partition key value, and so on:

UserID	MessageID
U1	1
U2	1
U3	1
...	...
U1	2
U2	2
U3	2
...	...

Every upload in this sequence uses a different partition key value, keeping more DynamoDB servers busy simultaneously and improving your throughput performance.

## Best practices for using sort keys to organize data

In an Amazon DynamoDB table, the primary key that uniquely identifies each item in the table can be composed not only of a partition key, but also of a sort key.

Well-designed sort keys have two key benefits:

- They gather related information together in one place where it can be queried efficiently. Careful design of the sort key lets you retrieve commonly needed groups of related items using range queries with operators such as `begins_with`, `between`, `>`, `<`, and so on.
- Composite sort keys let you define hierarchical (one-to-many) relationships in your data that you can query at any level of the hierarchy.

For example, in a table listing geographical locations, you might structure the sort key as follows.

[country]#[region]#[state]#[county]#[city]#[neighborhood]

This would let you make efficient range queries for a list of locations at any one of these levels of aggregation, from country, to a neighborhood, and everything in between.

## Using sort keys for version control

Many applications need to maintain a history of item-level revisions for audit or compliance purposes and to be able to retrieve the most recent version easily. There is an effective design pattern that accomplishes this using sort key prefixes:

- For each new item, create two copies of the item: One copy should have a version-number prefix of zero (such as `v0_`) at the beginning of the sort key, and one should have a version-number prefix of one (such as `v1_`).
- Every time the item is updated, use the next higher version-prefix in the sort key of the updated version, and copy the updated contents into the item with version-prefix zero. This means that the latest version of any item can be located easily using the zero prefix.

For example, a parts manufacturer might use a schema like the one illustrated below.

Primary Key		Data-Item Attributes...							
Partition Key	Sort Key (varies)	Attribute 1		Attribute 2		Attribute 3		Attribute 4	...
Equipment_1	Details	Name:	Biphasic Cardiometer (equipment name)	Factory_ID:	S14_Tukwilla (factory where manufactured)	Line_ID	R_7 (assembly-line ID)		
	v0_Audit	Auditor:	Padma (name of the auditor)	Latest:	3 (most recent audit version)	Time:	2018-04-15T11:00 (audit date and time)	Result	Passed (audit result)
	v1_Audit	Auditor:	Rick (name of the auditor)	Time:	2018-03-14T11:00 (audit date and time)	Result	Open (audit result)	Report:	0943922EKG14 (detailed problem report in S3)
	v2_Audit	Auditor:	George (name of the auditor)	Time:	2018-03-18T11:00 (audit date and time)	Result	Open (audit result)	Report:	0943923EKG15 (detailed problem report in S3)
	v3_Audit	Auditor:	Padma (name of the auditor)	Time:	2018-04-15T11:00 (audit date and time)	Result	Passed (audit result)	Report:	x792 (pass confirmation report)

The `Equipment_1` item goes through a sequence of audits by various auditors. The results of each new audit are captured in a new item in the table, starting with version number one, and then incrementing the number for each successive revision.

When each new revision is added, the application layer replaces the contents of the zero-version item (having sort key equal to `v0_Audit`) with the contents of the new revision.

Whenever the application needs to retrieve for the most recent audit status, it can query for the sort key prefix of `v0_`.

If the application needs to retrieve the entire revision history, it can query all the items under the item's partition key and filter out the `v0_` item.

This design also works for audits across multiple parts of a piece of equipment, if you include the individual part-IDs in the sort key after the sort key prefix.

## Best practices for using secondary indexes in DynamoDB

Secondary indexes are often essential to support the query patterns that your application requires. At the same time, overusing secondary indexes or using them inefficiently can add cost and reduce performance unnecessarily.

### Contents

- [General guidelines for secondary indexes in DynamoDB \(p. 1171\)](#)
  - [Use indexes efficiently \(p. 1172\)](#)
  - [Choose projections carefully \(p. 1172\)](#)
  - [Optimize frequent queries to avoid fetches \(p. 1172\)](#)
  - [Be aware of item-collection size limits when creating local secondary indexes \(p. 1173\)](#)
- [Take advantage of sparse indexes \(p. 1173\)](#)
  - [Examples of sparse indexes in DynamoDB \(p. 1173\)](#)
- [Using Global Secondary Indexes for materialized aggregation queries \(p. 1174\)](#)
- [Overloading Global Secondary Indexes \(p. 1175\)](#)
- [Using Global Secondary Index write sharding for selective table queries \(p. 1176\)](#)
- [Using Global Secondary Indexes to create an eventually consistent replica \(p. 1177\)](#)

## General guidelines for secondary indexes in DynamoDB

Amazon DynamoDB supports two types of secondary indexes:

- **Global secondary index**—An index with a partition key and a sort key that can be different from those on the base table. A global secondary index is considered "global" because queries on the index can span all of the data in the base table, across all partitions. A global secondary index has no size limitations and has its own provisioned throughput settings for read and write activity that are separate from those of the table.
- **Local secondary index**—An index that has the same partition key as the base table, but a different sort key. A local secondary index is "local" in the sense that every partition of a local secondary index is scoped to a base table partition that has the same partition key value. As a result, the total size of indexed items for any one partition key value can't exceed 10 GB. Also, a local secondary index shares provisioned throughput settings for read and write activity with the table it is indexing.

Each table in DynamoDB can have up to 20 global secondary indexes (default quota) and 5 local secondary indexes.

For more information about the differences between global secondary indexes and local secondary indexes, see [Improving data access with secondary indexes \(p. 497\)](#).

In general, you should use global secondary indexes rather than local secondary indexes. The exception is when you need strong consistency in your query results, which a local secondary index can provide but a global secondary index cannot (global secondary index queries only support eventual consistency).

The following are some general principles and design patterns to keep in mind when creating indexes in DynamoDB:

#### Topics

- [Use indexes efficiently \(p. 1172\)](#)
- [Choose projections carefully \(p. 1172\)](#)
- [Optimize frequent queries to avoid fetches \(p. 1172\)](#)
- [Be aware of item-collection size limits when creating local secondary indexes \(p. 1173\)](#)

## Use indexes efficiently

**Keep the number of indexes to a minimum.** Don't create secondary indexes on attributes that you don't query often. Indexes that are seldom used contribute to increased storage and I/O costs without improving application performance.

## Choose projections carefully

Because secondary indexes consume storage and provisioned throughput, you should keep the size of the index as small as possible. Also, the smaller the index, the greater the performance advantage compared to querying the full table. If your queries usually return only a small subset of attributes, and the total size of those attributes is much smaller than the whole item, project only the attributes that you regularly request.

If you expect a lot of write activity on a table compared to reads, follow these best practices:

- Consider projecting fewer attributes to minimize the size of items written to the index. However, this only applies if the size of projected attributes would otherwise be larger than a single write capacity unit (1 KB). For example, if the size of an index entry is only 200 bytes, DynamoDB rounds this up to 1 KB. In other words, as long as the index items are small, you can project more attributes at no extra cost.
- Avoid projecting attributes that you know will rarely be needed in queries. Every time you update an attribute that is projected in an index, you incur the extra cost of updating the index as well. You can still retrieve non-projected attributes in a `Query` at a higher provisioned throughput cost, but the query cost may be significantly lower than the cost of updating the index frequently.
- Specify `ALL` only if you want your queries to return the entire table item sorted by a different sort key. Projecting all attributes eliminates the need for table fetches, but in most cases, it doubles your costs for storage and write activity.

Balance the need to keep your indexes as small as possible against the need to keep fetches to a minimum, as explained in the next section.

## Optimize frequent queries to avoid fetches

To get the fastest queries with the lowest possible latency, project all the attributes that you expect those queries to return. In particular, if you query a local secondary index for attributes that are not projected, DynamoDB automatically fetches those attributes from the table, which requires reading the entire item from the table. This introduces latency and additional I/O operations that you can avoid.

Keep in mind that "occasional" queries can often turn into "essential" queries. If there are attributes that you don't intend to project because you anticipate querying them only occasionally, consider whether circumstances might change and you might regret not projecting those attributes after all.

For more information about table fetches, see [Provisioned throughput considerations for Local Secondary Indexes \(p. 546\)](#).

## Be aware of item-collection size limits when creating local secondary indexes

An *item collection* is all the items in a table and its local secondary indexes that have the same partition key. No item collection can exceed 10 GB, so it's possible to run out of space for a particular partition key value.

When you add or update a table item, DynamoDB updates all local secondary indexes that are affected. If the indexed attributes are defined in the table, the local secondary indexes grow too.

When you create a local secondary index, think about how much data will be written to it, and how many of those data items will have the same partition key value. If you expect that the sum of table and index items for a particular partition key value might exceed 10 GB, consider whether you should avoid creating the index.

If you can't avoid creating the local secondary index, you must anticipate the item collection size limit and take action before you exceed it. For strategies on working within the limit and taking corrective action, see [Item collection size limit \(p. 550\)](#).

## Take advantage of sparse indexes

For any item in a table, DynamoDB writes a corresponding index entry **only if the index sort key value is present in the item**. If the sort key doesn't appear in every table item, the index is said to be *sparse*.

Sparse indexes are useful for queries over a small subsection of a table. For example, suppose that you have a table where you store all your customer orders, with the following key attributes:

- Partition key: `CustomerId`
- Sort key: `OrderId`

To track open orders, you can insert an attribute named `isOpen` in order items that have not already shipped. Then when the order ships, you can delete the attribute. If you then create an index on `CustomerId` (partition key) and `isOpen` (sort key), only those orders with `isOpen` defined appear in it. When you have thousands of orders of which only a small number are open, it's faster and less expensive to query that index for open orders than to scan the entire table.

Instead of using a type of attribute like `isOpen`, you could use an attribute with a value that results in a useful sort order in the index. For example, you could use an `OrderOpenDate` attribute set to the date on which each order was placed, and then delete it after the order is fulfilled. That way, when you query the sparse index, the items are returned sorted by the date on which each order was placed.

## Examples of sparse indexes in DynamoDB

Global secondary indexes are sparse by default. When you create a global secondary index, you specify a partition key and optionally a sort key. Only items in the base table that contain those attributes appear in the index.

By designing a global secondary index to be sparse, you can provision it with lower write throughput than that of the base table, while still achieving excellent performance.

For example, a gaming application might track all scores of every user, but generally only needs to query a few high scores. The following design handles this scenario efficiently:

Table	Primary Key		Data Attributes...			
	Partition Key	Sort Key				
	Player_ID	Game_ID	Attribute 1		Attribute 2	
Rick	Game_1	Score:	36,750	Date:	2017-11-14	
		(game score)		(date of game)		
		Score:	69,450	Date:	2017-12-31	
Padma	Game_2	(game score)		(date of game)		
		Score:	135,900	Date:	2018-01-19	Award: Champ
		(game score)		(date of game)		(type of award)
Padma	Game_4	Score:	25,350	Date:	2018-01-27	
		(game score)		(date of game)		
		Score:	69,450	Date:	2018-01-19	
Padma	Game_5	(game score)		(date of game)		
		Score:	147,300	Date:	2018-02-02	Award: Champ
		(game score)		(date of game)		(type of award)
Padma	Game_6	Score:	169,100	Date:	2018-03-10	Award: Champ
		(game score)		(date of game)		(type of award)
		Score:	169,100	Date:	2018-03-10	

Here, Rick has played three games and achieved Champ status in one of them. Padma has played four games and achieved Champ status in two of them. Notice that the Award attribute is present only in items where the user achieved an award. The associated global secondary index looks like the following:

GSI	Primary Key		Projected Attributes...		
	Partition Key				
	Award	Player_ID	Game_ID	Score	Date
Champ	Champ	Rick	Game_3	135,900	2018-01-19
		Padma	Game_6	147,300	2018-02-02
		Padma	Game_7	169,100	2018-03-10

The global secondary index contains only the high scores that are frequently queried, which are a small subset of the items in the base table.

## Using Global Secondary Indexes for materialized aggregation queries

Maintaining near real-time aggregations and key metrics on top of rapidly changing data is becoming increasingly valuable to businesses for making rapid decisions. For example, a music library might want to showcase its most downloaded songs in near-real time.

Consider the following music library table layout:

Music Library Table

Primary Key		Data-Item Attributes...							
Partition Key	Sort Key	Attribute 1		Attribute 2		Attribute 3			
Song-129 <i>(song ID)</i>	Details	Title:	Wild Love <i>(song title)</i>	Artist:	Argyboots <i>(artist or band name)</i>	Downloads:	15,314,822 <i>(lifetime total downloads)</i>		
		GSI Primary Key		GSI Secondary Key					
	Month-2018-01	Month:	2018-01 <i>(download month)</i>	MonthTotal:		1,746,992 <i>(month total downloads)</i>			
		Dld-9349823681	Time: 2018-01-01T00:00:07 <i>(download timestamp)</i>						
		Dld-9349823682	Time: 2018-01-01T00:00:07 <i>(download timestamp)</i>						
		Dld-9349823683	Time: 2018-01-01T00:00:07 <i>(download timestamp)</i>						

The table in this example stores songs with the `songID` as the partition key. You can enable Amazon DynamoDB Streams on this table and attach a Lambda function to the streams so that as each song is downloaded, an entry is added to the table with `Partition-Key=SongID` and `Sort-Key=DownloadID`. As these updates are made, they trigger a Lambda function in DynamoDB Streams. The Lambda function can aggregate and group the downloads by `songID` and update the top-level item, `Partition-Key=songID`, and `Sort-Key=Month`. Keep in mind that if a lambda execution fails just after writing the new aggregated value, it may be retried and aggregate the value more than once, leaving you with an approximate value.

To read the updates in near-real time, with single-digit millisecond latency, use the global secondary index with query conditions `Month=2018-01`, `ScanIndexForward=False`, `Limit=1`.

Another key optimization used here is that the global secondary index is a sparse index and is available only on the items that need to be queried to retrieve the data in real time. The global secondary index can serve additional workflows that need information on the top 10 songs that were popular, or any song downloaded in that month.

## Overloading Global Secondary Indexes

Although Amazon DynamoDB has a default quota of 20 global secondary indexes per table, in practice, you can index across far more than 20 data fields. As opposed to a table in a relational database management system (RDBMS), in which the schema is uniform, a table in DynamoDB can hold many different kinds of data items at one time. In addition, the same attribute in different items can contain entirely different kinds of information.

Consider the following example of a DynamoDB table layout that saves a variety of different kinds of data.

Primary Key		Data-Item Attributes...				
Partition Key	Sort Key	Attribute 1		Attribute 2		...
HR-974 <i>(employee ID)</i>	Employee_Name	Data:	Murphy, John <i>(employee name)</i>	Start:	2008-11-08 <i>(start date)</i>	...etc.
	YYYY-Q1	Data:	\$5,477 <i>(order totals in USD)</i>	Name:	Murphy, John <i>(employee name)</i>	
	HR_confidential	Data:	2008-11-08 <i>(hire date)</i>	Name:	Murphy, John <i>(employee name)</i>	...etc.
	Warehouse_01	Data:	Murphy, John <i>(employee name)</i>			
	v0_Job_title	Data:	Operator-1 <i>(job title)</i>	Start:	2008-11-08 <i>(start date)</i>	...etc.
	v1_Job_title	Data:	Operator-2 <i>(job title)</i>	Start:	2016-11-04 <i>(start date)</i>	...etc.
	v2_Job_title	Data:	Supervisor-1 <i>(job title)</i>	Start:	2017-11-01 <i>(start date)</i>	...etc.

The Data attribute, which is common to all the items, has different content depending on its parent item. If you create a global secondary index for the table that uses the table's sort key as its partition key and the Data attribute as its sort key, you can make a variety of different queries using that single global secondary index. These queries might include the following:

- Look up an employee by name in the global secondary index, using Employee\_Name as the partition key value and the employee's name (for example Murphy, John) as the sort key value.
- Use the global secondary index to find all employees working in a particular warehouse by searching on a warehouse ID (such as Warehouse\_01).
- Get a list of recent hires, querying the global secondary index on HR\_confidential as a partition key value and using a range of dates in the sort key value.

## Using Global Secondary Index write sharding for selective table queries

Applications frequently need to identify a small subset of items in an Amazon DynamoDB table that meet a certain condition. When these items are distributed randomly across the partition keys of the table, you could resort to a table scan to retrieve them. This option can be expensive, but it works well when a large number of items on the table meet the search condition. However, when the key space is large and the search condition is very selective, this strategy can cause a lot of unnecessary processing.

To enable selective queries across the entire key space, you can use write sharding by adding an attribute containing a (0–N) value to every item that you will use for the global secondary index partition key.

The following is an example of a schema that uses this in a Critical-Event workflow:

Table	Primary Key <i>Partition Key</i>	Data Attributes...						
		Attribute 1		Attribute 2		Attribute 3		Attribute 4
Event	EID_12345	Time: <i>(event timestamp)</i>	2018-02-07T08:42:40	State: <i>(event state)</i>	INFO	GSI PK: <i>(random: 0-N)</i> <i>(random GSI-PK value)</i>	GSI SK: <i>INFO#2018-02-07T08:42:40</i> <i>(composite state-time)</i>	...etc.
	EID_12346	Time: <i>(event timestamp)</i>	2018-02-07T08:32:40	State: <i>(event state)</i>	CRITICAL	GSI PK: <i>(random: 0-N)</i> <i>(random GSI-PK value)</i>	GSI SK: <i>CRITICAL#2018-02-07T08:32:40</i> <i>(composite state-time)</i>	...etc.
	EID_12347	Time: <i>(event timestamp)</i>	2018-02-07T08:22:40	State: <i>(event state)</i>	WARN	GSI PK: <i>(random: 0-N)</i> <i>(random GSI-PK value)</i>	GSI SK: <i>WARN#2018-02-07T08:22:40</i> <i>(composite state-time)</i>	...etc.
	EID_12348	Time: <i>(event timestamp)</i>	2018-02-07T08:12:40	State: <i>(event state)</i>	INFO	GSI PK: <i>(random: 0-N)</i> <i>(random GSI-PK value)</i>	GSI SK: <i>INFO#2018-02-07T08:12:40</i> <i>(composite state-time)</i>	...etc.

GSI	Primary Key		Data Attributes...	
	Partition Key	Sort Key	...	
	GSI PK	GSI SK	...	
	[0-N]	INFO#2018-02-07T08:42:40 <i>(composite state-time)</i>	...etc.	
	[0-N]	CRITICAL#2018-02-07T08:32:40 <i>(composite state-time)</i>	...etc.	
	[0-N]	WARN#2018-02-07T08:22:40 <i>(composite state-time)</i>	...etc.	
	[0-N]	INFO#2018-02-07T08:12:40 <i>(composite state-time)</i>	...etc.	

Using this schema design, the event items are distributed across 0–N partitions on the GSI, allowing a scatter read using a sort condition on the composite key to retrieve all items with a given state during a specified time period.

This schema pattern delivers a highly selective result set at minimal cost, without requiring a table scan.

## Using Global Secondary Indexes to create an eventually consistent replica

You can use a global secondary index to create an eventually consistent replica of a table. Creating a replica can allow you to do the following:

- **Set different provisioned read capacity for different readers.** For example, suppose that you have two applications: One application handles high-priority queries and needs the highest levels of read performance, whereas the other handles low-priority queries that can tolerate throttling of read activity.

If both of these applications read from the same table, a heavy read load from the low-priority application could consume all the available read capacity for the table. This would throttle the high-priority application's read activity.

Instead, you can create a replica through a global secondary index whose read capacity you can set separate from that of the table itself. You can then have your low-priority app query the replica instead of the table.

- **Eliminate reads from a table entirely.** For example, you might have an application that captures a high volume of clickstream activity from a website, and you don't want to risk having reads interfere with that. You can isolate this table and prevent reads by other applications (see [Using IAM policy](#))

[conditions for fine-grained access control \(p. 1085\)](#)), while letting other applications read a replica created using a global secondary index.

To create a replica, set up a global secondary index that has the same key schema as the parent table, with some or all of the non-key attributes projected into it. In applications, you can direct some or all read activity to this global secondary index rather than to the parent table. You can then adjust the provisioned read capacity of the global secondary index to handle those reads without changing the parent table's provisioned read capacity.

There is always a short propagation delay between a write to the parent table and the time when the written data appears in the index. In other words, your applications should take into account that the global secondary index replica is only *eventually consistent* with the parent table.

You can create multiple global secondary index replicas to support different read patterns. When you create the replicas, project only the attributes that each read pattern actually requires. An application can then consume less provisioned read capacity to obtain only the data it needs rather than having to read the item from the parent table. This optimization can result in significant cost savings over time.

## Best practices for storing large items and attributes

Amazon DynamoDB currently limits the size of each item that you store in a table (see [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#)). If your application needs to store more data in an item than the DynamoDB size limit permits, you can try compressing one or more large attributes or breaking the item into multiple items (efficiently indexed by sort keys). You can also store the item as an object in Amazon Simple Storage Service (Amazon S3) and store the Amazon S3 object identifier in your DynamoDB item.

### Compressing large attribute values

Compressing large attribute values can let them fit within item limits in DynamoDB and reduce your storage costs. Compression algorithms such as GZIP or LZO produce binary output that you can then store in a `Binary` attribute type.

For example, the `Reply` table in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section stores messages written by forum users. These user replies might consist of long strings of text, which makes them excellent candidates for compression.

For sample code that demonstrates how to compress such messages in DynamoDB, see the following:

- [Example: Handling binary type attributes using the AWS SDK for Java document API \(p. 400\)](#)
- [Example: Handling binary type attributes using the AWS SDK for .NET low-level API \(p. 424\)](#)

### Storing large attribute values in Amazon S3

As mentioned previously, you can also use Amazon S3 to store large attribute values that cannot fit in a DynamoDB item. You can store them as an object in Amazon S3 and then store the object identifier in your DynamoDB item.

You can also use the object metadata support in Amazon S3 to provide a link back to the parent item in DynamoDB. Store the primary key value of the item as Amazon S3 metadata of the object in Amazon S3. Doing this often helps with maintenance of the Amazon S3 objects.

For example, consider the [ProductCatalog table](#) in the [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#) section. Items in this table store information about item price, description, book authors, and dimensions for other products. If you wanted to store an image of each product that was too large to fit in an item, you could store the images in Amazon S3 instead of in DynamoDB.

When implementing this strategy, keep the following in mind:

- DynamoDB doesn't support transactions that cross Amazon S3 and DynamoDB. Therefore, your application must deal with any failures, which could include cleaning up orphaned Amazon S3 objects.
- Amazon S3 limits the length of object identifiers. So you must organize your data in a way that doesn't generate excessively long object identifiers or violate other Amazon S3 constraints.

For more information about how to use Amazon S3, see the [Amazon Simple Storage Service User Guide](#).

## Best practices for handling time series data in DynamoDB

General design principles in Amazon DynamoDB recommend that you keep the number of tables you use to a minimum. For most applications, a single table is all you need. However, for time series data, you can often best handle it by using one table per application per period.

### Design pattern for time series data

Consider a typical time series scenario, where you want to track a high volume of events. Your write access pattern is that all the events being recorded have today's date. Your read access pattern might be to read today's events most frequently, yesterday's events much less frequently, and then older events very little at all. One way to handle this is by building the current date and time into the primary key.

The following design pattern often handles this kind of scenario effectively:

- Create one table per period, provisioned with the required read and write capacity and the required indexes.
- Before the end of each period, prebuild the table for the next period. Just as the current period ends, direct event traffic to the new table. You can assign names to these tables that specify the periods they have recorded.
- As soon as a table is no longer being written to, reduce its provisioned write capacity to a lower value (for example, 1 WCU), and provision whatever read capacity is appropriate. Reduce the provisioned read capacity of earlier tables as they age. You might choose to archive or delete the tables whose contents are rarely or never needed.

The idea is to allocate the required resources for the current period that will experience the highest volume of traffic and scale down provisioning for older tables that are not used actively, therefore saving costs. Depending on your business needs, you might consider write sharding to distribute traffic evenly to the logical partition key. For more information, see [Using write sharding to distribute workloads evenly \(p. 1167\)](#).

### Time series table examples

The following is a time series data example in which the current table is provisioned at a higher read/write capacity and the older tables are scaled down because they are accessed infrequently.

Current table		Promised at: WCU=750 and RCU=100	
Primary Key		Attributes	
Partition key	Sort key	Attribute 1	
2018-01-13	00:00:00:002	17.173 WC	713 items
2018-01-13	00:00:00:003	14.479 WC	713 items
2018-01-13	00:00:00:005	17.479 WC	708 items
2018-01-13	00:00:00:007	18.173 WC	674 items
***	***	***	***

Previous table		Promised at: WCU=111 and RCU=100	
Primary Key		Attributes	
Partition key	Sort key	Attribute 1	
2018-01-13	00:00:00:002	14.479 WC	712 items
2018-01-14	00:00:00:003	14.479 WC	818 items
2018-01-14	00:00:00:004	14.479 WC	818 items
2018-01-14	00:00:00:006	18.173 WC	822 items
***	***	***	***

Older table		Promised at: WCU=111 and RCU=100	
Primary Key		Attributes	
Partition key	Sort key	Attribute 1	
2018-01-10	00:00:00:001	13.448 WC	406 items
2018-01-10	00:00:00:002	13.532 WC	409 items
2018-01-10	00:00:00:003	13.532 WC	409 items
2018-01-10	00:00:00:005	18.173 WC	426 items
***	***	***	***

## Best practices for managing many-to-many relationships

Adjacency lists are a design pattern that is useful for modeling many-to-many relationships in Amazon DynamoDB. More generally, they provide a way to represent graph data (nodes and edges) in DynamoDB.

### Adjacency list design pattern

When different entities of an application have a many-to-many relationship between them, the relationship can be modeled as an adjacency list. In this pattern, all top-level entities (synonymous to nodes in the graph model) are represented using the partition key. Any relationships with other entities (edges in a graph) are represented as an item within the partition by setting the value of the sort key to the target entity ID (target node).

The advantages of this pattern include minimal data duplication and simplified query patterns to find all entities (nodes) related to a target entity (having an edge to a target node).

A real-world example where this pattern has been useful is an invoicing system where invoices contain multiple bills. One bill can belong in multiple invoices. The partition key in this example is either an `InvoiceID` or a `BillID`. `BillID` partitions have all attributes specific to bills. `InvoiceID` partitions have an item storing invoice-specific attributes, and an item for each `BillID` that rolls up to the invoice.

The schema looks like the following.

Table	Primary Key		Data Attributes...		
	Partition Key	Sort Key (and GSI PK)			
Invoice-92551	Inv_ID:	Invoice-92551 <i>(invoice ID)</i>	Dated:	2018-02-07 <i>(date created)</i>	More attributes of this invoice...
	Bill_ID:	Bill-4224663 <i>(bill ID)</i>	Dated:	2017-12-03 <i>(date created)</i>	Attributes of this bill <i>in this invoice..</i>
	Bill_ID:	Bill-4224687 <i>(bill ID)</i>	Dated:	2018-01-09 <i>(date created)</i>	Attributes of this bill <i>in this invoice..</i>
Invoice-92552	Inv_ID:	Invoice-92552 <i>(invoice ID)</i>	Dated:	2018-03-04 <i>(date created)</i>	More attributes of this invoice...
	Bill_ID:	Bill-4224687 <i>(bill ID)</i>	Dated:	2018-01-09 <i>(date created)</i>	Attributes of this bill <i>in this invoice..</i>
Bill-4224663	Bill_ID:	Bill-4224663 <i>(bill ID)</i>	Dated:	2017-12-03 <i>(date created)</i>	More attributes of this bill...
	Bill_ID:	Bill-4224687 <i>(bill ID)</i>	Dated:	2018-01-09 <i>(date created)</i>	More attributes of this bill...

Using the preceding schema, you can see that all bills for an invoice can be queried using the primary key on the table. To look up all invoices that contain a part of a bill, create a global secondary index on the table's sort key.

The projections for the global secondary index look like the following.

GSI	Primary Key	Projected Attributes...	
	Partition Key		
Bill-4224663	Bill_ID:	Bill-4224663 <i>(table primary key)</i>	Attributes of this bill...
	Inv_ID:	Invoice-92551 <i>(table primary key)</i>	Attributes of this bill <i>in this invoice</i> ..
Bill-4224687	Bill_ID:	Bill-4224687 <i>(table primary key)</i>	Attributes of this bill...
	Inv_ID:	Invoice-92551 <i>(table primary key)</i>	Attributes of this bill <i>in this invoice</i> ..
	Inv_ID:	Invoice-92552 <i>(table primary key)</i>	Attributes of this bill <i>in this invoice</i> ..
Invoice-92551	Inv_ID:	Invoice-92551 <i>(table primary key)</i>	Attributes of this invoice...
Invoice-92552	Inv_ID:	Invoice-92552 <i>(table primary key)</i>	Attributes of this invoice...

## Materialized graph pattern

Many applications are built around understanding rankings across peers, common relationships between entities, neighbor entity state, and other types of graph style workflows. For these types of applications, consider the following schema design pattern.

PK (NodeId)	Primary Key		Attributes			
	SK (TypeTarget, GSI 2 SK)		Data	GSI PK	Graph Projections	
1	DATE 2 BIRTH		1980-12-19	Hash(Person.Data)	...	
	PERSON 1		Data (GSI1 SK)	GSI PK		
	PERSON 5 FRIEND		John Doe	Hash(Person.Data)		
	PLACE 4 BIRTH		Data	GSI PK		
	SKILL 6		Jane Smith	Hash(Person.Data)		
	DATE 2		Data	GSI PK		
	PLACE 3		USA Texas Austin	Hash(Person.Data)		
	PLACE 4		Data	GSI PK		
	DATE 2 BIRTH		Java Developer Senior	Hash(Person.Data)		
	PERSON 5		Data	GSI PK		
5	PERSON 1 FRIEND		1980-12-19	0	...	
	PLACE 3 BIRTH		Data	GSI PK		
	SKILL 7		UK England London	0		
	SKILL 6		Data	GSI PK		
	SKILL 7		USA Texas Austin	0		
	DATE 2		Data	GSI PK		
	PLACE 3		Jane Smith	Hash(Person.Data)		
	PLACE 4		Data	GSI PK		
	SKILL 6		John Doe	Hash(Person.Data)		
	SKILL 7		Data	GSI PK		
GSI 1	Primary Key		Attributes			
	GSI 1 SK (Data)		NodeID	TypeTarget	Graph Projections	
	1980-12-19		2	DATE 2	...	
			NodeID	TypeTarget		
			1	DATE 2 BIRTH		
			NodeID			
			5			
	Guitar		NodeID	TypeTarget		
			7	SKILL 7		
			NodeID			
	Guitar Advanced		5			
			NodeID	TypeTarget		
			5	Person 5		
			NodeID	TypeTarget		
	Jane Smith		1	Person 5 FRIEND		
			NodeID	TypeTarget		
			6	SKILL 6		
	Java Developer		NodeID			
			1			
			NodeID	TypeTarget		
	Java Developer Senior		6	SKILL 6		
			NodeID			
			1			
	John Doe		NodeID	TypeTarget		
			1	Person 1		
			NodeID	TypeTarget		
	UK England London		5	Person 1 FRIEND		
			NodeID	TypeTarget		
			3	PLACE 3		
	USA Texas Austin		NodeID	TypeTarget		
			1	PLACE 3 BIRTH		
			NodeID	TypeTarget		
			4	PLACE 4		
			NodeID	TypeTarget		
			5	PLACE 4 BIRTH		

GSI PK	Primary Key GSI 2 SK (TypeTarget)	Attributes			
		NodeID	Data	Graph Projections	
GSI 2	DATE 2	2	1980-12-19	O-N	
	DATE 2 BIRTH	1			
	PERSON 1	1	John Doe		
	PERSON 1 FRIEND	5			
	PERSON 5	5	Jane Smith		
	PERSON 5 FRIEND	1			
	PLACE 3	3	UK England London		
	PLACE 3 BIRTH	5			
	PLACE 4	4	USA texas Austin		
	PLACE 4 BIRTH	1			
	SKILL 6	6	Java Developer	...	
		NodeID	Data		
		1	Java Developer Senior		
		7	Guitar		
	SKILL 7	NodeID	Data		
		5	Guitar Advanced		

The preceding schema shows a graph data structure that is defined by a set of data partitions containing the items that define the edges and nodes of the graph. Edge items contain a `Type` and a `Target` attribute. These attributes are used as part of a composite key name "TypeTarget" to identify the item in a partition in the primary table or in a second global secondary index.


The first global secondary index is built on the `Data` attribute. This attribute uses global secondary index-overloading as described earlier to index several different attribute types, namely Dates, Names, Places, and Skills. Here, one global secondary index is effectively indexing four different attributes.

As you insert items into the table, you can use an intelligent sharding strategy to distribute item sets with large aggregations (birthdate, skill) across as many logical partitions on the global secondary indexes as are needed to avoid hot read/write problems.

The result of this combination of design patterns is a solid datastore for highly efficient real-time graph workflows. These workflows can provide high-performance neighbor entity state and edge aggregation queries for recommendation engines, social-networking applications, node rankings, subtree aggregations, and other common graph use cases.

If your use case isn't sensitive to real-time data consistency, you can use a scheduled Amazon EMR process to populate edges with relevant graph summary aggregations for your workflows. If your application doesn't need to know immediately when an edge is added to the graph, you can use a scheduled process to aggregate results.

To maintain some level of consistency, the design could include Amazon DynamoDB Streams and AWS Lambda to process edge updates. It could also use an Amazon EMR job to validate results on a regular interval. This approach is illustrated by the following diagram. It is commonly used in social networking applications, where the cost of a real-time query is high and the need to immediately know individual user updates is low.



IT service-management (ITSM) and security applications generally need to respond in real time to entity state changes composed of complex edge aggregations. Such applications need a system that can support real-time multiple node aggregations of second- and third-level relationships, or complex edge traversals. If your use case requires these types of real-time graph query workflows, we recommend that you consider using [Amazon Neptune](#) to manage these workflows.

## Best practices for implementing a hybrid database system

In some circumstances, migrating from one or more relational database management systems (RDBMS) to Amazon DynamoDB might not be advantageous. In these cases, it might be preferable to create a hybrid system.

### If you don't want to migrate everything to DynamoDB

For example, some organizations have large investments in the code that produces a multitude of reports needed for accounting and operations. The time it takes to generate a report is not important to them. The flexibility of a relational system is well suited to this kind of task, and re-creating all those reports in a NoSQL context might be prohibitively difficult.


Some organizations also maintain a variety of legacy relational systems that they have acquired or inherited over decades. Migrating data from these systems might be too risky and expensive to justify the effort.

However, the same organizations may now find that their operations depend on high-traffic customer-facing websites, where millisecond response is essential. Relational systems can't scale to meet this requirement except at huge (and often unacceptable) expense.

In these situations, the answer might be to create a hybrid system, in which DynamoDB creates a materialized view of data stored in one or more relational systems and handles high-traffic requests against this view. This type of system can potentially reduce costs by eliminating server hardware, maintenance, and RDBMS licenses that were previously needed to handle customer-facing traffic.

## How a hybrid system can be implemented

DynamoDB can take advantage of DynamoDB Streams and AWS Lambda to integrate seamlessly with one or more existing relational database systems:



A system that integrates DynamoDB Streams and AWS Lambda can provide several advantages:

- It can operate as a persisted cache of materialized views.
- It can be set up to fill gradually with data as that data is queried for, and as data is modified in the SQL system. This means that the entire view does not need to be pre-populated. This in turn means that provisioned throughput capacity is more likely to be used efficiently.
- It has low administrative costs and is highly available and reliable.

For this kind of integration to be implemented, essentially three kinds of interoperation must be provided.




1. **Fill the DynamoDB cache incrementally.** When an item is queried, look for it first in DynamoDB. If it is not there, look for it in the SQL system, and load it into DynamoDB.
2. **Write through a DynamoDB cache.** When a customer changes a value in DynamoDB, a Lambda function is triggered to write the new data back to the SQL system.
3. **Update DynamoDB from the SQL system.** When internal processes such as inventory management or pricing change a value in the SQL system, a stored procedure is triggered to propagate the change to the DynamoDB materialized view.

These operations are straightforward, and not all of them are needed for every scenario.

A hybrid solution can also be useful when you want to rely primarily on DynamoDB, but you also want to maintain a small relational system for one-time queries, or for operations that need special security or that are not time-critical.

## Best practices for modeling relational data in DynamoDB

Traditional relational database management system (RDBMS) platforms store data in a normalized relational structure. This structure reduces hierarchical data structures to a set of common elements that are stored across multiple tables. The following schema is an example of a generic order-entry application with supporting HR schema backing the operational and business support systems of a theoretical manufacturer.



RDBMS platforms use an ad hoc query language (generally a flavor of SQL) to generate or materialize views of the normalized data to support application-layer access patterns.

For example, to generate a list of purchase order items sorted by the quantity in stock at all warehouses that can ship each item, you could issue the following query against the preceding schema.

```
SELECT * FROM Orders
INNER JOIN Order_Items ON Orders.Order_ID = Order_Items.Order_ID
INNER JOIN Products ON Products.Product_ID = Order_Items.Product_ID
INNER JOIN Inventories ON Products.Product_ID = Inventories.Product_ID
ORDER BY Quantity_on_Hand DESC
```

One-time queries of this kind provide a flexible API for accessing data, but they require a significant amount of processing. You must often query the data from multiple locations, and the results must be assembled for presentation. The preceding query initiates complex queries across a number of tables and then sorts and integrates the resulting data.

Another factor that can slow down RDBMS systems is the need to support an ACID-compliant transaction framework. The hierarchical data structures used by most online transaction processing (OLTP) applications must be broken down and distributed across multiple logical tables when they are stored in an RDBMS. Therefore, an ACID-compliant transaction framework is necessary to avoid race conditions that could occur if an application tries to read an object that is in the process of being written. Such a transaction framework necessarily adds significant overhead to the write process.

These two factors are the primary barriers to scale for traditional RDBMS platforms. It remains to be seen whether the NewSQL community can be successful in delivering a distributed RDBMS solution. But it is unlikely that even that would resolve the two limitations described earlier. No matter how the solution is delivered, the processing costs of normalization and ACID transactions must remain significant.

For this reason, when your business requires low-latency response to high-traffic queries, taking advantage of a NoSQL system generally makes technical and economic sense. Amazon DynamoDB helps solve the problems that limit relational system scalability by avoiding them.

A relational database system does not scale well for the following reasons:

- It normalizes data and stores it on multiple tables that require multiple queries to write to disk.
- It generally incurs the performance costs of an ACID-compliant transaction system.
- It uses expensive joins to reassemble required views of query results.

DynamoDB scales well for these reasons:

- Schema flexibility lets DynamoDB store complex hierarchical data within a single item.
- Composite key design lets it store related items close together on the same table.

Queries against the data store become much simpler, often in the following form:

```
SELECT * FROM Table_X WHERE Attribute_Y = "somevalue"
```

DynamoDB does far less work to return the requested data compared to the RDBMS in the earlier example.

## First steps for modeling relational data in DynamoDB

### Important

NoSQL design requires a different mindset than RDBMS design. For an RDBMS, you can create a normalized data model without thinking about access patterns. You can then extend it later when new questions and query requirements arise. By contrast, in Amazon DynamoDB, you shouldn't start designing your schema until you know the questions that it needs to answer. Understanding the business problems and the application use cases up front is absolutely essential.

To start designing a DynamoDB table that will scale efficiently, you must take several steps first to identify the access patterns that are required by the operations and business support systems (OSS/BSS) that it needs to support:

- For new applications, review user stories about activities and objectives. Document the various use cases you identify, and analyze the access patterns that they require.
- For existing applications, analyze query logs to find out how people are currently using the system and what the key access patterns are.

After completing this process, you should end up with a list that might look something like the following.

Most Common/Import Access Patterns in Our Organization	
1	Look up employee details by employee ID
2	Query employee details by employee name
3	Find an employee's phone number(s)
4	Find a customer's phone number(s)
5	Get orders for a given customer within a given date range
6	Show all open orders within a given date range across all customers
7	See all employees hired recently
8	Find all employees working in a given warehouse
9	Get all items on order for a given product
10	Get current inventories for a given product at all warehouses
11	Get customers by account representative
12	Get orders by account representative and date
13	Get all items on order for a given product
14	Get all employees with a given job title
15	Get inventory by product and warehouse
16	Get total product inventory
17	Get account representatives ranked by order total and sales period

In a real application, your list might be much longer. But this collection represents the range of query pattern complexity that you might find in a production environment.

A common approach to DynamoDB schema design is to identify application layer entities and use denormalization and composite key aggregation to reduce query complexity.

In DynamoDB, this means using composite sort keys, overloaded global secondary indexes, partitioned tables/indexes, and other design patterns. You can use these elements to structure the data so that an application can retrieve whatever it needs for a given access pattern using a single query on a table or index. The primary pattern that you can use to model the normalized schema shown in [Relational modeling \(p. 1185\)](#) is the adjacency list pattern. Other patterns used in this design can include global secondary index write sharding, global secondary index overloading, composite keys, and materialized aggregations.

**Important**

In general, you should maintain as few tables as possible in a DynamoDB application. Exceptions include cases where high-volume time series data are involved, or datasets that have very different access patterns. A single table with inverted indexes can usually enable simple queries to create and retrieve the complex hierarchical data structures required by your application.

## Example of modeling relational data in DynamoDB

This example describes how to model relational data in Amazon DynamoDB. A DynamoDB table design corresponds to the relational order entry schema that is shown in [Relational modeling \(p. 1185\)](#). It

follows the [Adjacency list design pattern \(p. 1180\)](#), which is a common way to represent relational data structures in DynamoDB.

The design pattern requires you to define a set of entity types that usually correlate to the various tables in the relational schema. Entity items are then added to the table using a compound (partition and sort) primary key. The partition key of these entity items is the attribute that uniquely identifies the item and is referred to generically on all items as **PK**. The sort key attribute contains an attribute value that you can use for an inverted index or global secondary index. It is generically referred to as **SK**.

You define the following entities, which support the relational order entry schema.

1. HR-Employee - PK: EmployeeID, SK: Employee Name
  2. HR-Region - PK: RegionID, SK: Region Name
  3. HR-Country - PK: CountryId, SK: Country Name
  4. HR-Location - PK: LocationID, SK: Country Name
  5. HR-Job - PK: JobID, SK: Job Title
  6. HR-Department - PK: DepartmentID, SK: DepartmentID
  7. OE-Customer - PK: CustomerID, SK: AccountRepID
  8. OE-Order - PK OrderID, SK: CustomerID
  9. OE-Product - PK: ProductID, SK: Product Name
- 10OE-Warehouse - PK: WarehouseID, SK: Region Name

After adding these entity items to the table, you can define the relationships between them by adding edge items to the entity item partitions. The following table demonstrates this step.

In this example, the `Employee`, `Order`, and `Product` Entity partitions on the table have additional edge items that contain pointers to other entity items on the table. Next, define a few global secondary indexes (GSIs) to support all the access patterns defined previously. The entity items don't all use the same type of value for the primary key or the sort key attribute. All that is required is to have the primary key and sort key attributes present to be inserted on the table.

The fact that some of these entities use proper names and others use other entity IDs as sort key values allows the same global secondary index to support multiple types of queries. This technique is called *GSI overloading*. It effectively eliminates the default limit of 20 global secondary indexes for tables that contain multiple item types. This is shown in the following diagram as *GSI 1*.

GSI 2 is designed to support a fairly common application access pattern, which is to get all the items on the table that have a certain state. For a large table with an uneven distribution of items across available states, this access pattern can result in a hot key, unless the items are distributed across more than one logical partition that can be queried in parallel. This design pattern is called *write sharding*.

To accomplish this for GSI 2, the application adds the GSI 2 primary key attribute to every Order item. It populates that with a random number in a range of 0–N, where N can generically be calculated using the following formula, unless there is a specific reason to do otherwise.

```
ItemsPerRCU = 4KB / AvgItemSize
PartitionMaxReadRate = 3K * ItemsPerRCU
N = MaxRequiredIO / PartitionMaxReadRate
```

For example, assume that you expect the following:

- Up to 2 million orders will be in the system, growing to 3 million in 5 years.

- Up to 20 percent of these orders will be in an OPEN state at any given time.
- The average order record is around 100 bytes, with three OrderItem records in the order partition that are around 50 bytes each, giving you an average order entity size of 250 bytes.

For that table, the N factor calculation would look like the following.

```
ItemsPerRCU = 4KB / 250B = 16
PartitionMaxReadRate = 3K * 16 = 48K
N = (0.2 * 3M) / 48K = 13
```

In this case, you need to distribute all the orders across at least 13 logical partitions on GSI 2 to ensure that a read of all `Order` items with an OPEN status doesn't cause a hot partition on the physical storage layer. It is a good practice to pad this number to allow for anomalies in the dataset. So a model using  $N = 15$  is probably fine. As mentioned earlier, you do this by adding the random 0–N value to the GSI 2 PK attribute of each `Order` and `OrderItem` record that is inserted on the table.

This breakdown assumes that the access pattern that requires gathering all OPEN invoices occurs relatively infrequently so that you can use burst capacity to fulfill the request. You can query the following global secondary index using a State and Date Range Sort Key condition to produce a subset or all Orders in a given state as needed.

In this example, the items are randomly distributed across the 15 logical partitions. This structure works because the access pattern requires a large number of items to be retrieved. Therefore, it's unlikely that any of the 15 threads will return empty result sets that could potentially represent wasted capacity. A query always uses 1 read capacity unit (RCU) or 1 write capacity unit (WCU), even if nothing is returned or no data is written.

If the access pattern requires a high velocity query on this global secondary index that returns a sparse result set, it's probably better to use a hash algorithm to distribute the items rather than a random pattern. In this case, you might select an attribute that is known when the query is run at runtime and hash that attribute into a 0–14 key space when the items are inserted. Then they can be efficiently read from the global secondary index.

Finally, you can revisit the access patterns that were defined earlier. Following is the list of access patterns and the query conditions that you will use with the new DynamoDB version of the application to accommodate them.

	<b>Access patterns</b>	<b>Query conditions</b>
1	Look up Employee Details by Employee ID	Primary Key on table, ID="HR-EMPLOYEE"
2	Query Employee Details by Employee Name	Use GSI-1, PK="Employee Name"
3	Get an employee's current job details only	Primary Key on table, PK=HR-EMPLOYEE-1, SK starts with "v0"
4	Get Orders for a customer for a date range	Use GSI-1, PK=CUSTOMER1, SK="STATUS-DATE", for each StatusCode
5	Show all Orders in OPEN status for a date range across all customers	Use GSI-2, PK=query in parallel for the range [0..N], SK between OPEN-Date1 and OPEN-Date2

	<b>Access patterns</b>	<b>Query conditions</b>
6	All Employees hired recently	Use GSI-1, PK="HR-CONFIDENTIAL", SK > date1
7	Find all Employees in specific Warehouse	Use GSI-1, PK=WAREHOUSE1
8	Get all Orderitems for a Product including warehouse location inventories	Use GSI-1, PK=PRODUCT1
9	Get customers by Account Rep	Use GSI-1, PK=ACCOUNT-REP
10	Get orders by Account Rep and date	Use GSI-1, PK=ACCOUNT-REP, SK="STATUS-DATE", for each StatusCode
11	Get all employees with specific Job Title	Use GSI-1, PK=v0-JOBTITLE
12	Get inventory by Product and Warehouse	Primary Key on table, PK=OE-PRODUCT1,SK=PRODUCT1
13	Get total product inventory	Primary Key on table, PK=OE-PRODUCT1,SK=PRODUCT1
14	Get Account Reps ranked by Order Total and Sales Period	Use GSI-1, PK=YYYY-Q1, scanIndexForward=False

## Best practices for querying and scanning data

This section covers some best practices for using `Query` and `Scan` operations in Amazon DynamoDB.

### Performance considerations for scans

In general, `Scan` operations are less efficient than other operations in DynamoDB. A `Scan` operation always scans the entire table or secondary index. It then filters out values to provide the result you want, essentially adding the extra step of removing data from the result set.

If possible, you should avoid using a `Scan` operation on a large table or index with a filter that removes many results. Also, as a table or index grows, the `Scan` operation slows. The `Scan` operation examines every item for the requested values and can use up the provisioned throughput for a large table or index in a single operation. For faster response times, design your tables and indexes so that your applications can use `Query` instead of `Scan`. (For tables, you can also consider using the `GetItem` and `BatchGetItem` APIs.)

Alternatively, design your application to use `Scan` operations in a way that minimizes the impact on your request rate.

### Avoiding sudden spikes in read activity


When you create a table, you set its read and write capacity unit requirements. For reads, the capacity units are expressed as the number of strongly consistent 4 KB data read requests per second. For eventually consistent reads, a read capacity unit is two 4 KB read requests per second. A `Scan` operation

performs eventually consistent reads by default, and it can return up to 1 MB (one page) of data. Therefore, a single Scan request can consume  $(1 \text{ MB page size} / 4 \text{ KB item size}) / 2$  (eventually consistent reads) = 128 read operations. If you request strongly consistent reads instead, the Scan operation would consume twice as much provisioned throughput—256 read operations.

This represents a sudden spike in usage, compared to the configured read capacity for the table. This usage of capacity units by a scan prevents other potentially more important requests for the same table from using the available capacity units. As a result, you likely get a ProvisionedThroughputExceeded exception for those requests.

The problem is not just the sudden increase in capacity units that the Scan uses. The scan is also likely to consume all of its capacity units from the same partition because the scan requests read items that are next to each other on the partition. This means that the request is hitting the same partition, causing all of its capacity units to be consumed, and throttling other requests to that partition. If the request to read data is spread across multiple partitions, the operation would not throttle a specific partition.


The following diagram illustrates the impact of a sudden spike of capacity unit usage by Query and Scan operations, and its impact on your other requests against the same table.




1. Good: Even distribution of requests and size




2. Not as Good: Frequent requests in bursts



3. Bad: A few random large requests



4. Bad: Large scan operations



As illustrated here, the usage spike can impact the table's provisioned throughput in several ways:

1. Good: Even distribution of requests and size
2. Not as good: Frequent requests in bursts
3. Bad: A few random large requests
4. Bad: Large scan operations

Instead of using a large Scan operation, you can use the following techniques to minimize the impact of a scan on a table's provisioned throughput.

- **Reduce page size**

Because a Scan operation reads an entire page (by default, 1 MB), you can reduce the impact of the scan operation by setting a smaller page size. The Scan operation provides a *Limit* parameter that you can use to set the page size for your request. Each Query or Scan request that has a smaller page size uses fewer read operations and creates a "pause" between each request. For example, suppose that each item is 4 KB and you set the page size to 40 items. A Query request would then consume only 20 eventually consistent read operations or 40 strongly consistent read operations. A larger number of smaller Query or Scan operations would allow your other critical requests to succeed without throttling.

- **Isolate scan operations**

DynamoDB is designed for easy scalability. As a result, an application can create tables for distinct purposes, possibly even duplicating content across several tables. You want to perform scans on a table that is not taking "mission-critical" traffic. Some applications handle this load by rotating traffic hourly between two tables—one for critical traffic, and one for bookkeeping. Other applications can do this by performing every write on two tables: a "mission-critical" table, and a "shadow" table.

Configure your application to retry any request that receives a response code that indicates you have exceeded your provisioned throughput. Or, increase the provisioned throughput for your table using the `UpdateTable` operation. If you have temporary spikes in your workload that cause your throughput to exceed, occasionally, beyond the provisioned level, retry the request with exponential backoff. For more information about implementing exponential backoff, see [Error retries and exponential backoff \(p. 168\)](#).

## Taking advantage of parallel scans

Many applications can benefit from using parallel Scan operations rather than sequential scans. For example, an application that processes a large table of historical data can perform a parallel scan much faster than a sequential one. Multiple worker threads in a background "sweeper" process could scan a table at a low priority without affecting production traffic. In each of these examples, a parallel Scan is used in such a way that it does not starve other applications of provisioned throughput resources.

Although parallel scans can be beneficial, they can place a heavy demand on provisioned throughput. With a parallel scan, your application has multiple workers that are all running Scan operations concurrently. This can quickly consume all of your table's provisioned read capacity. In that case, other applications that need to access the table might be throttled.

A parallel scan can be the right choice if the following conditions are met:

- The table size is 20 GB or larger.
- The table's provisioned read throughput is not being fully used.
- Sequential Scan operations are too slow.

## Choosing TotalSegments

The best setting for `TotalSegments` depends on your specific data, the table's provisioned throughput settings, and your performance requirements. You might need to experiment to get it right. We recommend that you begin with a simple ratio, such as one segment per 2 GB of data. For example, for a 30 GB table, you could set `TotalSegments` to 15 (30 GB / 2 GB). Your application would then use 15 workers, with each worker scanning a different segment.

You can also choose a value for `TotalSegments` that is based on client resources. You can set `TotalSegments` to any number from 1 to 1000000, and DynamoDB lets you scan that number of

segments. For example, if your client limits the number of threads that can run concurrently, you can gradually increase `TotalSegments` until you get the best `Scan` performance with your application.

Monitor your parallel scans to optimize your provisioned throughput use, while also making sure that your other applications aren't starved of resources. Increase the value for `TotalSegments` if you don't consume all of your provisioned throughput but still experience throttling in your `Scan` requests. Reduce the value for `TotalSegments` if the `Scan` requests consume more provisioned throughput than you want to use.

# DynamoDB integration with other AWS services

Amazon DynamoDB is integrated with other AWS services, letting you automate repeating tasks or build applications that span multiple services. For example:

## Topics

- [Configuring AWS credentials in your files using Amazon Cognito \(p. 1196\)](#)
- [Loading data from DynamoDB into Amazon Redshift \(p. 1198\)](#)
- [Processing DynamoDB data with Apache Hive on Amazon EMR \(p. 1199\)](#)
- [Integrating with Amazon S3 \(p. 1223\)](#)

## Configuring AWS credentials in your files using Amazon Cognito

The recommended way to obtain AWS credentials for your web and mobile applications is to use Amazon Cognito. Amazon Cognito helps you avoid hardcoding your AWS credentials on your files. It uses AWS Identity and Access Management (IAM) roles to generate temporary credentials for your application's authenticated and unauthenticated users.

For example, to configure your JavaScript files to use an Amazon Cognito unauthenticated role to access the Amazon DynamoDB web service, do the following.

### To configure credentials to integrate with Amazon Cognito

1. Create an Amazon Cognito identity pool that allows unauthenticated identities.

```
aws cognito-identity create-identity-pool \
--identity-pool-name DynamoPool \
--allow-unauthenticated-identities \
--output json
{
  "IdentityPoolId": "us-west-2:12345678-1ab2-123a-1234-a12345ab12",
  "AllowUnauthenticatedIdentities": true,
  "IdentityPoolName": "DynamoPool"
}
```

2. Copy the following policy into a file named `myCognitoPolicy.json`. Replace the identity pool ID (`us-west-2:12345678-1ab2-123a-1234-a12345ab12`) with your own `IdentityPoolId` obtained in the previous step.

```
{
  "Version": "2012-10-17",
  "Statement": [
    {
      "Effect": "Allow",
      "Action": "dynamodb:DescribeTable",
      "Resource": "arn:aws:dynamodb:us-west-2:12345678-1ab2-123a-1234-a12345ab12:table/MyTable"
    }
  ]
}
```

```

    "Effect": "Allow",
    "Principal": {
        "Federated": "cognito-identity.amazonaws.com"
    },
    "Action": "sts:AssumeRoleWithWebIdentity",
    "Condition": {
        "StringEquals": {
            "cognito-identity.amazonaws.com:aud": "us-west-2:12345678-1ab2-123a-1234-
a12345ab12"
        },
        "ForAnyValue:StringLike": {
            "cognito-identity.amazonaws.com:amr": "unauthenticated"
        }
    }
}
]
}
}

```

3. Create an IAM role that assumes the previous policy. In this way, Amazon Cognito becomes a trusted entity that can assume the Cognito\_DynamoPoolUnauth role.

```
aws iam create-role --role-name Cognito_DynamoPoolUnauth \
--assume-role-policy-document file://PathToFile/myCognitoPolicy.json --output json
```

4. Grant the Cognito\_DynamoPoolUnauth role full access to DynamoDB by attaching a managed policy (AmazonDynamoDBFullAccess).

```
aws iam attach-role-policy --policy-arn arn:aws:iam::aws:policy/
AmazonDynamoDBFullAccess \
--role-name Cognito_DynamoPoolUnauth
```

**Note**

Alternatively, you can grant fine-grained access to DynamoDB. For more information, see [Using IAM policy conditions for fine-grained access control](#).

5. Obtain and copy the IAM role Amazon Resource Name (ARN).

```
aws iam get-role --role-name Cognito_DynamoPoolUnauth --output json
```

6. Add the Cognito\_DynamoPoolUnauth role to the DynamoPool identity pool. The format to specify is KeyName=string, where KeyName is unauthenticated and the string is the role ARN obtained in the previous step.

```
aws cognito-identity set-identity-pool-roles \
--identity-pool-id "us-west-2:12345678-1ab2-123a-1234-a12345ab12" \
--roles unauthenticated=arn:aws:iam::123456789012:role/Cognito_DynamoPoolUnauth --
output json
```

7. Specify the Amazon Cognito credentials in your files. Modify the IdentityPoolId and RoleArn accordingly.

```
AWS.config.credentials = new AWS.CognitoIdentityCredentials({
IdentityPoolId: "us-west-2:12345678-1ab2-123a-1234-a12345ab12",
RoleArn: "arn:aws:iam::123456789012:role/Cognito_DynamoPoolUnauth"
});
```

You can now run your JavaScript programs against the DynamoDB web service using Amazon Cognito credentials. For more information, see [Setting credentials in a web browser](#) in the *AWS SDK for JavaScript Getting Started Guide*.

# Loading data from DynamoDB into Amazon Redshift

Amazon Redshift complements Amazon DynamoDB with advanced business intelligence capabilities and a powerful SQL-based interface. When you copy data from a DynamoDB table into Amazon Redshift, you can perform complex data analysis queries on that data, including joins with other tables in your Amazon Redshift cluster.

In terms of provisioned throughput, a copy operation from a DynamoDB table counts against that table's read capacity. After the data is copied, your SQL queries in Amazon Redshift do not affect DynamoDB in any way. This is because your queries act upon a copy of the data from DynamoDB, rather than upon DynamoDB itself.

Before you can load data from a DynamoDB table, you must first create an Amazon Redshift table to serve as the destination for the data. Keep in mind that you are copying data from a NoSQL environment into a SQL environment, and that there are certain rules in one environment that do not apply in the other. Here are some of the differences to consider:

- DynamoDB table names can contain up to 255 characters, including '.' (dot) and '-' (dash) characters, and are case-sensitive. Amazon Redshift table names are limited to 127 characters, cannot contain dots or dashes and are not case-sensitive. In addition, table names cannot conflict with any Amazon Redshift reserved words.
- DynamoDB does not support the SQL concept of NULL. You need to specify how Amazon Redshift interprets empty or blank attribute values in DynamoDB, treating them either as NULLs or as empty fields.
- DynamoDB data types do not correspond directly with those of Amazon Redshift. You need to ensure that each column in the Amazon Redshift table is of the correct data type and size to accommodate the data from DynamoDB.

Here is an example COPY command from Amazon Redshift SQL:

```
copy favoritemovies from 'dynamodb://my-favorite-movies-table'
credentials 'aws_access_key_id=<Your-Access-Key-ID>;aws_secret_access_key=<Your-Secret-
Access-Key>'
readratio 50;
```

In this example, the source table in DynamoDB is `my-favorite-movies-table`. The target table in Amazon Redshift is `favoritemovies`. The `readratio 50` clause regulates the percentage of provisioned throughput that is consumed; in this case, the COPY command will use no more than 50 percent of the read capacity units provisioned for `my-favorite-movies-table`. We highly recommend setting this ratio to a value less than the average unused provisioned throughput.

For detailed instructions on loading data from DynamoDB into Amazon Redshift, refer to the following sections in the [Amazon Redshift Database Developer Guide](#):

- [Loading data from a DynamoDB table](#)
- [The COPY command](#)
- [COPY examples](#)

# Processing DynamoDB data with Apache Hive on Amazon EMR

Amazon DynamoDB is integrated with Apache Hive, a data warehousing application that runs on Amazon EMR. Hive can read and write data in DynamoDB tables, allowing you to:

- Query live DynamoDB data using a SQL-like language (HiveQL).
- Copy data from a DynamoDB table to an Amazon S3 bucket, and vice-versa.
- Copy data from a DynamoDB table into Hadoop Distributed File System (HDFS), and vice-versa.
- Perform join operations on DynamoDB tables.

## Topics

- [Overview \(p. 1199\)](#)
- [Tutorial: Working with Amazon DynamoDB and Apache Hive \(p. 1200\)](#)
- [Creating an external table in Hive \(p. 1206\)](#)
- [Processing HiveQL statements \(p. 1208\)](#)
- [Querying data in DynamoDB \(p. 1209\)](#)
- [Copying data to and from Amazon DynamoDB \(p. 1210\)](#)
- [Performance tuning \(p. 1220\)](#)

## Overview

Amazon EMR is a service that makes it easy to quickly and cost-effectively process vast amounts of data. To use Amazon EMR, you launch a managed cluster of Amazon EC2 instances running the Hadoop open source framework. *Hadoop* is a distributed application that implements the MapReduce algorithm, where a task is mapped to multiple nodes in the cluster. Each node processes its designated work, in parallel with the other nodes. Finally, the outputs are reduced on a single node, yielding the final result.

You can choose to launch your Amazon EMR cluster so that it is persistent or transient:

- A *persistent* cluster runs until you shut it down. Persistent clusters are ideal for data analysis, data warehousing, or any other interactive use.
- A *transient* cluster runs long enough to process a job flow, and then shuts down automatically. Transient clusters are ideal for periodic processing tasks, such as running scripts.

For information about Amazon EMR architecture and administration, see the [Amazon EMR Management Guide](#).

When you launch an Amazon EMR cluster, you specify the initial number and type of Amazon EC2 instances. You also specify other distributed applications (in addition to Hadoop itself) that you want to run on the cluster. These applications include Hue, Mahout, Pig, Spark, and more.

For information about applications for Amazon EMR, see the [Amazon EMR Release Guide](#).

Depending on the cluster configuration, you might have one or more of the following node types:

- Leader node — Manages the cluster, coordinating the distribution of the MapReduce executable and subsets of the raw data, to the core and task instance groups. It also tracks the status of each task performed and monitors the health of the instance groups. There is only one leader node in a cluster.

- Core nodes — Runs MapReduce tasks and stores data using the Hadoop Distributed File System (HDFS).
- Task nodes (optional) — Runs MapReduce tasks.

## Tutorial: Working with Amazon DynamoDB and Apache Hive

In this tutorial, you will launch an Amazon EMR cluster, and then use Apache Hive to process data stored in a DynamoDB table.

*Hive* is a data warehouse application for Hadoop that allows you to process and analyze data from multiple sources. Hive provides a SQL-like language, *HiveQL*, that lets you work with data stored locally in the Amazon EMR cluster or in an external data source (such as Amazon DynamoDB).

For more information, see to the [Hive Tutorial](#).

### Topics

- [Before you begin \(p. 1200\)](#)
- [Step 1: Create an Amazon EC2 key pair \(p. 1200\)](#)
- [Step 2: Launch an Amazon EMR cluster \(p. 1201\)](#)
- [Step 3: Connect to the Leader node \(p. 1202\)](#)
- [Step 4: Load data into HDFS \(p. 1202\)](#)
- [Step 5: Copy data to DynamoDB \(p. 1204\)](#)
- [Step 6: Query the data in the DynamoDB table \(p. 1205\)](#)
- [Step 7: \(Optional\) clean up \(p. 1205\)](#)

## Before you begin

For this tutorial, you will need the following:

- An AWS account. If you do not have one, see [Signing up for AWS \(p. 58\)](#).
- An SSH client (Secure Shell). You use the SSH client to connect to the leader node of the Amazon EMR cluster and run interactive commands. SSH clients are available by default on most Linux, Unix, and Mac OS X installations. Windows users can download and install the [PuTTY](#) client, which has SSH support.

### Next step

#### [Step 1: Create an Amazon EC2 key pair \(p. 1200\)](#)

## Step 1: Create an Amazon EC2 key pair

In this step, you will create the Amazon EC2 key pair you need to connect to an Amazon EMR leader node and run Hive commands.

1. Sign in to the AWS Management Console and open the Amazon EC2 console at <https://console.aws.amazon.com/ec2/>.
2. Choose a region (for example, `us West (Oregon)`). This should be the same region in which your DynamoDB table is located.

3. In the navigation pane, choose **Key Pairs**.
4. Choose **Create Key Pair**.
5. In **Key pair name**, type a name for your key pair (for example, `mykeypair`), and then choose **Create**.
6. Download the private key file. The file name will end with `.pem` (such as `mykeypair.pem`). Keep this private key file in a safe place. You will need it to access any Amazon EMR cluster that you launch with this key pair.

**Important**

If you lose the key pair, you cannot connect to the leader node of your Amazon EMR cluster.

For more information about key pairs, see [Amazon EC2 Key Pairs](#) in the *Amazon EC2 User Guide for Linux Instances*.

**Next step**

[Step 2: Launch an Amazon EMR cluster \(p. 1201\)](#)

## Step 2: Launch an Amazon EMR cluster

In this step, you will configure and launch an Amazon EMR cluster. Hive and a storage handler for DynamoDB will already be installed on the cluster.

1. Open the Amazon EMR console at <https://console.aws.amazon.com/elasticmapreduce/>.
2. Choose **Create Cluster**.
3. On the **Create Cluster - Quick Options** page, do the following:
  - a. In **Cluster name**, type a name for your cluster (for example: `My EMR cluster`).
  - b. In **EC2 key pair**, choose the key pair you created earlier.

Leave the other settings at their defaults.
4. Choose **Create cluster**.

It will take several minutes to launch your cluster. You can use the **Cluster Details** page in the Amazon EMR console to monitor its progress.

When the status changes to `Waiting`, the cluster is ready for use.

## Cluster log files and Amazon S3

An Amazon EMR cluster generates log files that contain information about the cluster status and debugging information. The default settings for **Create Cluster - Quick Options** include setting up Amazon EMR logging.

If one does not already exist, the AWS Management Console creates an Amazon S3 bucket. The bucket name is `aws-logs-account-id-region`, where `account-id` is your AWS account number and `region` is the region in which you launched the cluster (for example, `aws-logs-123456789012-us-west-2`).

**Note**

You can use the Amazon S3 console to view the log files. For more information, see [View Log Files](#) in the *Amazon EMR Management Guide*.

You can use this bucket for purposes in addition to logging. For example, you can use the bucket as a location for storing a Hive script or as a destination when exporting data from Amazon DynamoDB to Amazon S3.

**Next step**

[Step 3: Connect to the Leader node \(p. 1202\)](#)

## Step 3: Connect to the Leader node

When the status of your Amazon EMR cluster changes to **Waiting**, you will be able to connect to the leader node using SSH and perform command line operations.

1. In the Amazon EMR console, choose your cluster's name to view its status.
2. On the **Cluster Details** page, find the **Leader public DNS** field. This is the public DNS name for the leader node of your Amazon EMR cluster.
3. To the right of the DNS name, choose the **SSH** link.
4. Follow the instructions in [Connect to the Leader Node Using SSH](#).

Depending on your operating system, choose the **Windows** tab or the **Mac/Linux** tab, and follow the instructions for connecting to the leader node.

After you connect to the leader node using either SSH or PuTTY, you should see a command prompt similar to the following:

```
[hadoop@ip-192-0-2-0 ~]$
```

**Next step**

[Step 4: Load data into HDFS \(p. 1202\)](#)

## Step 4: Load data into HDFS

In this step, you will copy a data file into Hadoop Distributed File System (HDFS), and then create an external Hive table that maps to the data file.

### Download the sample data

1. Download the sample data archive (`features.zip`):

```
wget https://docs.aws.amazon.com/amazondynamodb/latest/developerguide/samples/features.zip
```

2. Extract the `features.txt` file from the archive:

```
unzip features.zip
```

3. View the first few lines of the `features.txt` file:

```
head features.txt
```

The result should look similar to this:

```
1535908|Big Run|Stream|WV|38.6370428|-80.8595469|794
875609|Constable Hook|Cape|NJ|40.657881|-74.0990309|7
1217998|Gooseberry Island|Island|RI|41.4534361|-71.3253284|10
26603|Boone Moore Spring|Spring|AZ|34.0895692|-111.410065|3681
1506738|Missouri Flat|Flat|WA|46.7634987|-117.0346113|2605
```

```
1181348|Minnow Run|Stream|PA|40.0820178|-79.3800349|1558
1288759|Hunting Creek|Stream|TN|36.343969|-83.8029682|1024
533060|Big Charles Bayou|Bay|LA|29.6046517|-91.9828654|0
829689|Greenwood Creek|Stream|NE|41.596086|-103.0499296|3671
541692|Button Willow Island|Island|LA|31.9579389|-93.0648847|98
```

The `features.txt` file contains a subset of data from the United States Board on Geographic Names ([http://geonames.usgs.gov/domestic/download\\_data.htm](http://geonames.usgs.gov/domestic/download_data.htm)). The fields in each line represent the following:

- Feature ID (unique identifier)
- Name
- Class (lake; forest; stream; and so on)
- State
- Latitude (degrees)
- Longitude (degrees)
- Height (in feet)

4. At the command prompt, enter the following command:

```
hive
```

The command prompt changes to this: `hive>`

5. Enter the following HiveQL statement to create a native Hive table:

```
CREATE TABLE hive_features
  (feature_id          BIGINT,
   feature_name        STRING ,
   feature_class       STRING ,
   state_alpha         STRING,
   prim_lat_dec       DOUBLE ,
   prim_long_dec      DOUBLE ,
   elev_in_ft          BIGINT)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY '|'
LINES TERMINATED BY '\n';
```

6. Enter the following HiveQL statement to load the table with data:

```
LOAD DATA
LOCAL
INPATH './features.txt'
OVERWRITE
INTO TABLE hive_features;
```

7. You now have a native Hive table populated with data from the `features.txt` file. To verify, enter the following HiveQL statement:

```
SELECT state_alpha, COUNT(*)
FROM hive_features
GROUP BY state_alpha;
```

The output should show a list of states and the number of geographic features in each.

## Next step

[Step 5: Copy data to DynamoDB \(p. 1204\)](#)

## Step 5: Copy data to DynamoDB

In this step, you will copy data from the Hive table (`hive_features`) to a new table in DynamoDB.

1. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. Choose **Create Table**.
3. On the **Create DynamoDB table** page, do the following:
  - a. In **Table**, type **Features**.
  - b. For **Primary key**, in the **Partition key** field, type `id`. Set the data type to **Number**.

Clear **Use Default Settings**. For **Provisioned Capacity**, type the following:

- **Read Capacity Units**—10
- **Write Capacity Units**—10

Choose **Create**.

4. At the Hive prompt, enter the following HiveQL statement:

```
CREATE EXTERNAL TABLE ddb_features
  (feature_id      BIGINT,
   feature_name    STRING,
   feature_class   STRING,
   state_alpha     STRING,
   prim_lat_dec   DOUBLE,
   prim_long_dec  DOUBLE,
   elev_in_ft      BIGINT)
STORED BY 'org.apache.hadoop.hive.dynamodb.DynamoDBStorageHandler'
TBLPROPERTIES(
  "dynamodb.table.name" = "Features",
  "dynamodb.column.mapping"="feature_id:Id,feature_name:Name,feature_class:Class,state_alpha:State,p");

```

You have now established a mapping between Hive and the Features table in DynamoDB.

5. Enter the following HiveQL statement to import data to DynamoDB:

```
INSERT OVERWRITE TABLE ddb_features
SELECT
  feature_id,
  feature_name,
  feature_class,
  state_alpha,
  prim_lat_dec,
  prim_long_dec,
  elev_in_ft
FROM hive_features;
```

Hive will submit a MapReduce job, which will be processed by your Amazon EMR cluster. It will take several minutes to complete the job.

6. Verify that the data has been loaded into DynamoDB:
  - a. In the DynamoDB console navigation pane, choose **Tables**.
  - b. Choose the **Features** table, and then choose the **Items** tab to view the data.

**Next step**

[Step 6: Query the data in the DynamoDB table \(p. 1205\)](#)

## Step 6: Query the data in the DynamoDB table

In this step, you will use HiveQL to query the Features table in DynamoDB. Try the following Hive queries:

1. All of the feature types (`feature_class`) in alphabetical order:

```
SELECT DISTINCT feature_class
FROM ddb_features
ORDER BY feature_class;
```

2. All of the lakes that begin with the letter "M":

```
SELECT feature_name, state_alpha
FROM ddb_features
WHERE feature_class = 'Lake'
AND feature_name LIKE 'M%'
ORDER BY feature_name;
```

3. States with at least three features higher than a mile (5,280 feet):

```
SELECT state_alpha, feature_class, COUNT(*)
FROM ddb_features
WHERE elev_in_ft > 5280
GROUP by state_alpha, feature_class
HAVING COUNT(*) >= 3
ORDER BY state_alpha, feature_class;
```

### Next step

[Step 7: \(Optional\) clean up \(p. 1205\)](#)

## Step 7: (Optional) clean up

Now that you have completed the tutorial, you can continue reading this section to learn more about working with DynamoDB data in Amazon EMR. You might decide to keep your Amazon EMR cluster up and running while you do this.

If you don't need the cluster anymore, you should terminate it and remove any associated resources. This will help you avoid being charged for resources you don't need.

1. Terminate the Amazon EMR cluster:
  - a. Open the Amazon EMR console at <https://console.aws.amazon.com/elasticmapreduce/>.
  - b. Choose the Amazon EMR cluster, choose **Terminate**, and then confirm.
2. Delete the Features table in DynamoDB:
  - a. Open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
  - b. In the navigation pane, choose **Tables**.
  - c. Choose the Features table. From the **Actions** menu, choose **Delete Table**.
3. Delete the Amazon S3 bucket containing the Amazon EMR log files:
  - a. Open the Amazon S3 console at <https://console.aws.amazon.com/s3/>.
  - b. From the list of buckets, choose `aws-logs- accountID-region`, where `accountID` is your AWS account number and `region` is the region in which you launched the cluster.

- c. From the **Action** menu, choose **Delete**.

## Creating an external table in Hive

In [Tutorial: Working with Amazon DynamoDB and Apache Hive \(p. 1200\)](#), you created an external Hive table that mapped to a DynamoDB table. When you issued HiveQL statements against the external table, the read and write operations were passed through to the DynamoDB table.

You can think of an external table as a pointer to a data source that is managed and stored elsewhere. In this case, the underlying data source is a DynamoDB table. (The table must already exist. You cannot create, update, or delete a DynamoDB table from within Hive.) You use the `CREATE EXTERNAL TABLE` statement to create the external table. After that, you can use HiveQL to work with data in DynamoDB, as if that data were stored locally within Hive.

### Note

You can use `INSERT` statements to insert data into an external table and `SELECT` statements to select data from it. However, you cannot use `UPDATE` or `DELETE` statements to manipulate data in the table.

If you no longer need the external table, you can remove it using the `DROP TABLE` statement. In this case, `DROP TABLE` only removes the external table in Hive. It does not affect the underlying DynamoDB table or any of its data.

### Topics

- [CREATE EXTERNAL TABLE syntax \(p. 1206\)](#)
- [Data type mappings \(p. 1207\)](#)

## CREATE EXTERNAL TABLE syntax

The following shows the HiveQL syntax for creating an external Hive table that maps to a DynamoDB table:

```
CREATE EXTERNAL TABLE hive_table
  (hive_column1_name hive_column1_datatype, hive_column2_name hive_column2_datatype...)
STORED BY 'org.apache.hadoop.hive.dynamodb.DynamoDBStorageHandler'
TBLPROPERTIES (
    "dynamodb.table.name" = "dynamodb_table",
    "dynamodb.column.mapping" =
    "hive_column1_name:dynamodb_attribute1_name,hive_column2_name:dynamodb_attribute2_name..."
);
```

Line 1 is the start of the `CREATE EXTERNAL TABLE` statement, where you provide the name of the Hive table (*hive\_table*) you want to create.

Line 2 specifies the columns and data types for *hive\_table*. You need to define columns and data types that correspond to the attributes in the DynamoDB table.

Line 3 is the `STORED BY` clause, where you specify a class that handles data management between the Hive and the DynamoDB table. For DynamoDB, `STORED BY` should be set to `'org.apache.hadoop.hive.dynamodb.DynamoDBStorageHandler'`.

Line 4 is the start of the `TBLPROPERTIES` clause, where you define the following parameters for `DynamoDBStorageHandler`:

- `dynamodb.table.name`—the name of the DynamoDB table.

- `dynamodb.column.mapping`—pairs of column names in the Hive table and their corresponding attributes in the DynamoDB table. Each pair is of the form `hive_column_name:dynamodb_attribute_name`, and the pairs are separated by commas.

Note the following:

- The name of the Hive table name does not have to be the same as the DynamoDB table name.
- The Hive table column names do not have to be the same as those in the DynamoDB table.
- The table specified by `dynamodb.table.name` must exist in DynamoDB.
- For `dynamodb.column.mapping`:
  - You must map the key schema attributes for the DynamoDB table. This includes the partition key and the sort key (if present).
  - You do not have to map the non-key attributes of the DynamoDB table. However, you will not see any data from those attributes when you query the Hive table.
  - If the data types of a Hive table column and a DynamoDB attribute are incompatible, you will see `NULL` in these columns when you query the Hive table.

**Note**

The `CREATE EXTERNAL TABLE` statement does not perform any validation on the `TBLPROPERTIES` clause. The values you provide for `dynamodb.table.name` and `dynamodb.column.mapping` are only evaluated by the `DynamoDBStorageHandler` class when you attempt to access the table.

## Data type mappings

The following table shows DynamoDB data types and compatible Hive data types:

DynamoDB Data Type	Hive Data Type
String	STRING
Number	BIGINT or DOUBLE
Binary	BINARY
String Set	ARRAY<STRING>
Number Set	ARRAY<BIGINT> or ARRAY<DOUBLE>
Binary Set	ARRAY<BINARY>

**Note**

The following DynamoDB data types are not supported by the `DynamoDBStorageHandler` class, so they cannot be used with `dynamodb.column.mapping`:

- Map
- List
- Boolean
- Null

If you want to map a DynamoDB attribute of type Number, you must choose an appropriate Hive type:

- The Hive `BIGINT` type is for 8-byte signed integers. It is the same as the `long` data type in Java.
- The Hive `DOUBLE` type is for 8-bit double precision floating point numbers. It is the same as the `double` type in Java.

If you have numeric data stored in DynamoDB that has a higher precision than the Hive data type you choose, then accessing the DynamoDB data could cause a loss of precision.

If you export data of type Binary from DynamoDB to (Amazon S3) or HDFS, the data is stored as a Base64-encoded string. If you import data from Amazon S3 or HDFS into the DynamoDB Binary type, you must ensure the data is encoded as a Base64 string.

## Processing HiveQL statements

Hive is an application that runs on Hadoop, which is a batch-oriented framework for running MapReduce jobs. When you issue a HiveQL statement, Hive determines whether it can return the results immediately or whether it must submit a MapReduce job.

For example, consider the `ddb_features` table (from [Tutorial: Working with Amazon DynamoDB and Apache Hive \(p. 1200\)](#)). The following Hive query prints state abbreviations and the number of summits in each:

```
SELECT state_alpha, count(*)
FROM ddb_features
WHERE feature_class = 'Summit'
GROUP BY state_alpha;
```

Hive does not return the results immediately. Instead, it submits a MapReduce job, which is processed by the Hadoop framework. Hive will wait until the job is complete before it shows the results from the query:

```
AK 2
AL 2
AR 2
AZ 3
CA 7
CO 2
CT 2
ID 1
KS 1
ME 2
MI 1
MT 3
NC 1
NE 1
NM 1
NY 2
OR 5
PA 1
TN 1
TX 1
UT 4
VA 1
VT 2
WA 2
WY 3
Time taken: 8.753 seconds, Fetched: 25 row(s)
```

## Monitoring and canceling jobs

When Hive launches a Hadoop job, it prints output from that job. The job completion status is updated as the job progresses. In some cases, the status might not be updated for a long time. (This can happen when you are querying a large DynamoDB table that has a low provisioned read capacity setting.)

If you need to cancel the job before it is complete, you can type **Ctrl+C** at any time.

## Querying data in DynamoDB

The following examples show some ways that you can use HiveQL to query data stored in DynamoDB.

These examples refer to the *ddb\_features* table in the tutorial ([Step 5: Copy data to DynamoDB \(p. 1204\)](#)).

### Topics

- [Using aggregate functions \(p. 1209\)](#)
- [Using the GROUP BY and HAVING clauses \(p. 1209\)](#)
- [Joining two DynamoDB tables \(p. 1209\)](#)
- [Joining tables from different sources \(p. 1210\)](#)

## Using aggregate functions

HiveQL provides built-in functions for summarizing data values. For example, you can use the `MAX` function to find the largest value for a selected column. The following example returns the elevation of the highest feature in the state of Colorado.

```
SELECT MAX(elev_in_ft)
FROM ddb_features
WHERE state_alpha = 'CO';
```

## Using the GROUP BY and HAVING clauses

You can use the `GROUP BY` clause to collect data across multiple records. This is often used with an aggregate function such as `SUM`, `COUNT`, `MIN`, or `MAX`. You can also use the `HAVING` clause to discard any results that do not meet certain criteria.

The following example returns a list of the highest elevations from states that have more than five features in the *ddb\_features* table.

```
SELECT state_alpha, max(elev_in_ft)
FROM ddb_features
GROUP BY state_alpha
HAVING count(*) >= 5;
```

## Joining two DynamoDB tables

The following example maps another Hive table (*east\_coast\_states*) to a table in DynamoDB. The `SELECT` statement is a join across these two tables. The join is computed on the cluster and returned. The join does not take place in DynamoDB.

Consider a DynamoDB table named *EastCoastStates* that contains the following data:

StateName	StateAbbrev
-----------	-------------

Maine	ME
New Hampshire	NH
Massachusetts	MA
Rhode Island	RI
Connecticut	CT
New York	NY
New Jersey	NJ
Delaware	DE
Maryland	MD
Virginia	VA
North Carolina	NC
South Carolina	SC
Georgia	GA
Florida	FL

Let's assume the table is available as a Hive external table named `east_coast_states`:

```
CREATE EXTERNAL TABLE ddb_east_coast_states (state_name STRING, state_alpha STRING)
STORED BY 'org.apache.hadoop.hive.dynamodb.DynamoDBStorageHandler'
TBLPROPERTIES ("dynamodb.table.name" = "EastCoastStates",
"dynamodb.column.mapping" = "state_name:StateName,state_alpha:StateAbbrev");
```

The following join returns the states on the East Coast of the United States that have at least three features:

```
SELECT ecs.state_name, f.feature_class, COUNT(*)
FROM ddb_east_coast_states ecs
JOIN ddb_features f ON ecs.state_alpha = f.state_alpha
GROUP BY ecs.state_name, f.feature_class
HAVING COUNT(*) >= 3;
```

## Joining tables from different sources

In the following example, `s3_east_coast_states` is a Hive table associated with a CSV file stored in Amazon S3. The `ddb_features` table is associated with data in DynamoDB. The following example joins these two tables, returning the geographic features from states whose names begin with "New."

```
create external table s3_east_coast_states (state_name STRING, state_alpha STRING)
ROW FORMAT DELIMITED FIELDS TERMINATED BY ','
LOCATION 's3://<bucketname>/path/<subpath>/';
```

```
SELECT ecs.state_name, f.feature_name, f.feature_class
FROM s3_east_coast_states ecs
JOIN ddb_features f
ON ecs.state_alpha = f.state_alpha
WHERE ecs.state_name LIKE 'New%';
```

## Copying data to and from Amazon DynamoDB

In the [Tutorial: Working with Amazon DynamoDB and Apache Hive \(p. 1200\)](#), you copied data from a native Hive table into an external DynamoDB table, and then queried the external DynamoDB table. The table is external because it exists outside of Hive. Even if you drop the Hive table that maps to it, the table in DynamoDB is not affected.

Hive is an excellent solution for copying data among DynamoDB tables, Amazon S3 buckets, native Hive tables, and Hadoop Distributed File System (HDFS). This section provides examples of these operations.

### Topics

- [Copying data between DynamoDB and a native Hive table \(p. 1211\)](#)
- [Copying data between DynamoDB and Amazon S3 \(p. 1211\)](#)
- [Copying data between DynamoDB and HDFS \(p. 1215\)](#)
- [Using data compression \(p. 1219\)](#)
- [Reading non-printable UTF-8 character data \(p. 1219\)](#)

## Copying data between DynamoDB and a native Hive table

If you have data in a DynamoDB table, you can copy the data to a native Hive table. This will give you a snapshot of the data, as of the time you copied it.

You might decide to do this if you need to perform many HiveQL queries, but do not want to consume provisioned throughput capacity from DynamoDB. Because the data in the native Hive table is a copy of the data from DynamoDB, and not "live" data, your queries should not expect that the data is up-to-date.

### Note

The examples in this section are written with the assumption you followed the steps in [Tutorial: Working with Amazon DynamoDB and Apache Hive \(p. 1200\)](#) and have an external table in DynamoDB named *ddb\_features*.

### Example From DynamoDB to native Hive table

You can create a native Hive table and populate it with data from *ddb\_features*, like this:

```
CREATE TABLE features_snapshot AS
SELECT * FROM ddb_features;
```

You can then refresh the data at any time:

```
INSERT OVERWRITE TABLE features_snapshot
SELECT * FROM ddb_features;
```

In these examples, the subquery `SELECT * FROM ddb_features` will retrieve all of the data from *ddb\_features*. If you only want to copy a subset of the data, you can use a `WHERE` clause in the subquery.

The following example creates a native Hive table, containing only some of the attributes for lakes and summits:

```
CREATE TABLE lakes_and_summits AS
SELECT feature_name, feature_class, state_alpha
FROM ddb_features
WHERE feature_class IN ('Lake','Summit');
```

### Example From native Hive table to DynamoDB

Use the following HiveQL statement to copy the data from the native Hive table to *ddb\_features*:

```
INSERT OVERWRITE TABLE ddb_features
SELECT * FROM features_snapshot;
```

## Copying data between DynamoDB and Amazon S3

If you have data in a DynamoDB table, you can use Hive to copy the data to an Amazon S3 bucket.

You might do this if you want to create an archive of data in your DynamoDB table. For example, suppose you have a test environment where you need to work with a baseline set of test data in

DynamoDB. You can copy the baseline data to an Amazon S3 bucket, and then run your tests. Afterward, you can reset the test environment by restoring the baseline data from the Amazon S3 bucket to DynamoDB.

If you worked through [Tutorial: Working with Amazon DynamoDB and Apache Hive \(p. 1200\)](#), then you already have an Amazon S3 bucket that contains your Amazon EMR logs. You can use this bucket for the examples in this section, if you know the root path for the bucket:

1. Open the Amazon EMR console at <https://console.aws.amazon.com/elasticmapreduce/>.
2. For **Name**, choose your cluster.
3. The URI is listed in **Log URI** under **Configuration Details**.
4. Make a note of the root path of the bucket. The naming convention is:

`s3://aws-logs-accountID-region`

where `accountID` is your AWS account ID and region is the AWS region for the bucket.

#### Note

For these examples, we will use a subpath within the bucket, as in this example:

`s3://aws-logs-123456789012-us-west-2/hive-test`

The following procedures are written with the assumption you followed the steps in the tutorial and have an external table in DynamoDB named `ddb_features`.

#### Topics

- [Copying data using the Hive default format \(p. 1212\)](#)
- [Copying data with a user-specified format \(p. 1213\)](#)
- [Copying data without a column mapping \(p. 1214\)](#)
- [Viewing the data in Amazon S3 \(p. 1215\)](#)

## Copying data using the Hive default format

### Example From DynamoDB to Amazon S3

Use an `INSERT OVERWRITE` statement to write directly to Amazon S3.

```
INSERT OVERWRITE DIRECTORY 's3://aws-logs-123456789012-us-west-2/hive-test'  
SELECT * FROM ddb_features;
```

The data file in Amazon S3 looks like this:

```
920709^ASoldiers Farewell Hill^ASummit^ANM^A32.3564729^A-108.33004616135  
1178153^AJones Run^AStream^APA^A41.2120086^A-79.25920781260  
253838^ASentinel Dome^ASummit^ACA^A37.7229821^A-119.584338133  
264054^ANeversweet Gulch^AValley^ACA^A41.6565269^A-122.83614322900  
115905^AChacaloochee Bay^ABay^AAL^A30.6979676^A-87.97388530
```

Each field is separated by an SOH character (start of heading, 0x01). In the file, SOH appears as `^A`.

### Example From Amazon S3 to DynamoDB

1. Create an external table pointing to the unformatted data in Amazon S3.

```
CREATE EXTERNAL TABLE s3_features_unformatted
```

```
(feature_id      BIGINT,  
 feature_name    STRING ,  
 feature_class   STRING ,  
 state_alpha     STRING,  
 prim_lat_dec   DOUBLE ,  
 prim_long_dec  DOUBLE ,  
 elev_in_ft     BIGINT)  
LOCATION 's3://aws-logs-123456789012-us-west-2/hive-test';
```

2. Copy the data to DynamoDB.

```
INSERT OVERWRITE TABLE ddb_features  
SELECT * FROM s3_features_unformatted;
```

## Copying data with a user-specified format

If you want to specify your own field separator character, you can create an external table that maps to the Amazon S3 bucket. You might use this technique for creating data files with comma-separated values (CSV).

### Example From DynamoDB to Amazon S3

1. Create a Hive external table that maps to Amazon S3. When you do this, ensure that the data types are consistent with those of the DynamoDB external table.

```
CREATE EXTERNAL TABLE s3_features_csv  
(feature_id      BIGINT,  
 feature_name    STRING,  
 feature_class   STRING,  
 state_alpha     STRING,  
 prim_lat_dec   DOUBLE,  
 prim_long_dec  DOUBLE,  
 elev_in_ft     BIGINT)  
ROW FORMAT DELIMITED  
FIELDS TERMINATED BY ','  
LOCATION 's3://aws-logs-123456789012-us-west-2/hive-test';
```

2. Copy the data from DynamoDB.

```
INSERT OVERWRITE TABLE s3_features_csv  
SELECT * FROM ddb_features;
```

The data file in Amazon S3 looks like this:

```
920709,Soldiers Farewell Hill,Summit,NM,32.3564729,-108.3300461,6135  
1178153,Jones Run,Stream,PA,41.2120086,-79.2592078,1260  
253838,Sentinel Dome,Summit,CA,37.7229821,-119.58433,8133  
264054,Neversweet Gulch,Valley,CA,41.6565269,-122.8361432,2900  
115905,Chacaloochee Bay,Bay,AL,30.6979676,-87.9738853,0
```

### Example From Amazon S3 to DynamoDB

With a single HiveQL statement, you can populate the DynamoDB table using the data from Amazon S3:

```
INSERT OVERWRITE TABLE ddb_features  
SELECT * FROM s3_features_csv;
```

## Copying data without a column mapping

You can copy data from DynamoDB in a raw format and write it to Amazon S3 without specifying any data types or column mapping. You can use this method to create an archive of DynamoDB data and store it in Amazon S3.

### Note

If your DynamoDB table contains attributes of type Map, List, Boolean or Null, then this is the only way you can use Hive to copy data from DynamoDB to Amazon S3.

### Example From DynamoDB to Amazon S3

1. Create an external table associated with your DynamoDB table. (There is no dynamodb.column.mapping in this HiveQL statement.)

```
CREATE EXTERNAL TABLE ddb_features_no_mapping
  (item MAP<STRING, STRING>)
STORED BY 'org.apache.hadoop.hive.dynamodb.DynamoDBStorageHandler'
TBLPROPERTIES ("dynamodb.table.name" = "Features");
```

2. Create another external table associated with your Amazon S3 bucket.

```
CREATE EXTERNAL TABLE s3_features_no_mapping
  (item MAP<STRING, STRING>)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY '\t'
LINES TERMINATED BY '\n'
LOCATION 's3://aws-logs-123456789012-us-west-2/hive-test';
```

3. Copy the data from DynamoDB to Amazon S3.

```
INSERT OVERWRITE TABLE s3_features_no_mapping
SELECT * FROM ddb_features_no_mapping;
```

The data file in Amazon S3 looks like this:

```
Name^C{"s":"Soldiers Farewell
Hill"}^BState^C{"s":"NM"}^BClass^C{"s":"Summit"}^BElevation^C{"n":6135}^BLatitude^C{"n":32.3564729}
Name^C{"s":"Jones
Run"}^BState^C{"s":"PA"}^BClass^C{"s":Stream"}^BElevation^C{"n":1260}^BLatitude^C{"n":41.2120086}
Name^C{"s":"Sentinel
Dome"}^BState^C{"s":CA"}^BClass^C{"s":Summit"}^BElevation^C{"n":8133}^BLatitude^C{"n":37.7229821}
Name^C{"s":"Neversweet
Gulch"}^BState^C{"s":CA"}^BClass^C{"s":Valley"}^BElevation^C{"n":2900}^BLatitude^C{"n":41.6565269}
Name^C{"s":"Chacaloochee
Bay"}^BState^C{"s":AL"}^BClass^C{"s":Bay"}^BElevation^C{"n":0}^BLatitude^C{"n":30.6979676}^BId^C
```

Each field begins with an STX character (start of text, 0x02) and ends with an ETX character (end of text, 0x03). In the file, STX appears as ^B and ETX appears as ^C.

### Example From Amazon S3 to DynamoDB

With a single HiveQL statement, you can populate the DynamoDB table using the data from Amazon S3:

```
INSERT OVERWRITE TABLE ddb_features_no_mapping
SELECT * FROM s3_features_no_mapping;
```

## Viewing the data in Amazon S3

If you use SSH to connect to the leader node, you can use the AWS Command Line Interface (AWS CLI) to access the data that Hive wrote to Amazon S3.

The following steps are written with the assumption you have copied data from DynamoDB to Amazon S3 using one of the procedures in this section.

1. If you are currently at the Hive command prompt, exit to the Linux command prompt.

```
hive> exit;
```

2. List the contents of the `hive-test` directory in your Amazon S3 bucket. (This is where Hive copied the data from DynamoDB.)

```
aws s3 ls s3://aws-logs-123456789012-us-west-2/hive-test/
```

The response should look similar to this:

```
2016-11-01 23:19:54 81983 000000_0
```

The file name (`000000_0`) is system-generated.

3. (Optional) You can copy the data file from Amazon S3 to the local file system on the leader node. After you do this, you can use standard Linux command line utilities to work with the data in the file.

```
aws s3 cp s3://aws-logs-123456789012-us-west-2/hive-test/000000_0 .
```

The response should look similar to this:

```
download: s3://aws-logs-123456789012-us-west-2/hive-test/000000_0
to ./000000_0
```

**Note**

The local file system on the leader node has limited capacity. Do not use this command with files that are larger than the available space in the local file system.

## Copying data between DynamoDB and HDFS

If you have data in a DynamoDB table, you can use Hive to copy the data to the Hadoop Distributed File System (HDFS).

You might do this if you are running a MapReduce job that requires data from DynamoDB. If you copy the data from DynamoDB into HDFS, Hadoop can process it, using all of the available nodes in the Amazon EMR cluster in parallel. When the MapReduce job is complete, you can then write the results from HDFS to DDB.

In the following examples, Hive will read from and write to the following HDFS directory: `/user/hadoop/hive-test`

**Note**

The examples in this section are written with the assumption you followed the steps in [Tutorial: Working with Amazon DynamoDB and Apache Hive \(p. 1200\)](#) and you have an external table in DynamoDB named `ddb_features`.

### Topics

- [Copying data using the Hive default format \(p. 1216\)](#)
- [Copying data with a user-specified format \(p. 1216\)](#)

- [Copying data without a column mapping \(p. 1217\)](#)
- [Accessing the data in HDFS \(p. 1218\)](#)

## Copying data using the Hive default format

### Example From DynamoDB to HDFS

Use an `INSERT OVERWRITE` statement to write directly to HDFS.

```
INSERT OVERWRITE DIRECTORY 'hdfs:///user/hadoop/hive-test'  
SELECT * FROM ddb_features;
```

The data file in HDFS looks like this:

```
920709^ASoldiers Farewell Hill^ASummit^ANM^A32.3564729^A-108.33004616135  
1178153^AJones Run^AStream^APA^A41.2120086^A-79.25920781260  
253838^ASentinel Dome^ASummit^ACA^A37.7229821^A-119.584338133  
264054^ANeversweet Gulch^AValley^ACA^A41.6565269^A-122.83614322900  
115905^AChacaloochee Bay^ABay^AAL^A30.6979676^A-87.97388530
```

Each field is separated by an SOH character (start of heading, 0x01). In the file, SOH appears as ^A.

### Example From HDFS to DynamoDB

1. Create an external table that maps to the unformatted data in HDFS.

```
CREATE EXTERNAL TABLE hdfs_features_unformatted  
(feature_id      BIGINT,  
 feature_name    STRING ,  
 feature_class   STRING ,  
 state_alpha     STRING,  
 prim_lat_dec   DOUBLE ,  
 prim_long_dec  DOUBLE ,  
 elev_in_ft     BIGINT)  
LOCATION 'hdfs:///user/hadoop/hive-test';
```

2. Copy the data to DynamoDB.

```
INSERT OVERWRITE TABLE ddb_features  
SELECT * FROM hdfs_features_unformatted;
```

## Copying data with a user-specified format

If you want to use a different field separator character, you can create an external table that maps to the HDFS directory. You might use this technique for creating data files with comma-separated values (CSV).

### Example From DynamoDB to HDFS

1. Create a Hive external table that maps to HDFS. When you do this, ensure that the data types are consistent with those of the DynamoDB external table.

```
CREATE EXTERNAL TABLE hdfs_features_csv  
(feature_id      BIGINT,  
 feature_name    STRING ,  
 feature_class   STRING ,  
 state_alpha     STRING ,
```

```

    prim_lat_dec      DOUBLE ,
    prim_long_dec    DOUBLE ,
    elev_in_ft       BIGINT)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY ','
LOCATION 'hdfs:///user/hadoop/hive-test';

```

2. Copy the data from DynamoDB.

```

INSERT OVERWRITE TABLE hdfs_features_csv
SELECT * FROM ddb_features;

```

The data file in HDFS looks like this:

```

920709,Soldiers Farewell Hill,Summit,NM,32.3564729,-108.3300461,6135
1178153,Jones Run,Stream,PA,41.2120086,-79.2592078,1260
253838,Sentinel Dome,Summit,CA,37.7229821,-119.58433,8133
264054,Neversweet Gulch,Valley,CA,41.6565269,-122.8361432,2900
115905,Chacaloochee Bay,Bay,AL,30.6979676,-87.9738853,0

```

### **Example From HDFS to DynamoDB**

With a single HiveQL statement, you can populate the DynamoDB table using the data from HDFS:

```

INSERT OVERWRITE TABLE ddb_features
SELECT * FROM hdfs_features_csv;

```

### **Copying data without a column mapping**

You can copy data from DynamoDB in a raw format and write it to HDFS without specifying any data types or column mapping. You can use this method to create an archive of DynamoDB data and store it in HDFS.

#### **Note**

If your DynamoDB table contains attributes of type Map, List, Boolean or Null, then this is the only way you can use Hive to copy data from DynamoDB to HDFS.

### **Example From DynamoDB to HDFS**

1. Create an external table associated with your DynamoDB table. (There is no dynamodb.column.mapping in this HiveQL statement.)

```

CREATE EXTERNAL TABLE ddb_features_no_mapping
(item MAP<STRING, STRING>)
STORED BY 'org.apache.hadoop.hive.dynamodb.DynamoDBStorageHandler'
TBLPROPERTIES ("dynamodb.table.name" = "Features");

```

2. Create another external table associated with your HDFS directory.

```

CREATE EXTERNAL TABLE hdfs_features_no_mapping
(item MAP<STRING, STRING>)
ROW FORMAT DELIMITED
FIELDS TERMINATED BY '\t'
LINES TERMINATED BY '\n'
LOCATION 'hdfs:///user/hadoop/hive-test';

```

3. Copy the data from DynamoDB to HDFS.

```
INSERT OVERWRITE TABLE hdfs_features_no_mapping
SELECT * FROM ddb_features_no_mapping;
```

The data file in HDFS looks like this:

```
Name^C{"s":"Soldiers Farewell
Hill"}^BState^C{"s":"NM"}^BClass^C{"s":"Summit"}^BElevation^C{"n":6135}^BLatitude^C{"n":32.3564729}
Name^C{"s":"Jones
Run"}^BState^C{"s":"PA"}^BClass^C{"s":"Stream"}^BElevation^C{"n":1260}^BLatitude^C{"n":41.2120086}
Name^C{"s":"Sentinel
Dome"}^BState^C{"s":"CA"}^BClass^C{"s":"Summit"}^BElevation^C{"n":8133}^BLatitude^C{"n":37.7229821}
Name^C{"s":"Neversweet
Gulch"}^BState^C{"s":"CA"}^BClass^C{"s":"Valley"}^BElevation^C{"n":2900}^BLatitude^C{"n":41.6565269}
Name^C{"s":"Chacaloochee
Bay"}^BState^C{"s":"AL"}^BClass^C{"s":Bay"}^BElevation^C{"n":0}^BLatitude^C{"n":30.6979676}^BId^C
```

Each field begins with an STX character (start of text, 0x02) and ends with an ETX character (end of text, 0x03). In the file, STX appears as ^B and ETX appears as ^C.

### Example From HDFS to DynamoDB

With a single HiveQL statement, you can populate the DynamoDB table using the data from HDFS:

```
INSERT OVERWRITE TABLE ddb_features_no_mapping
SELECT * FROM hdfs_features_no_mapping;
```

### Accessing the data in HDFS

HDFS is a distributed file system, accessible to all of the nodes in the Amazon EMR cluster. If you use SSH to connect to the leader node, you can use command line tools to access the data that Hive wrote to HDFS.

HDFS is not the same thing as the local file system on the leader node. You cannot work with files and directories in HDFS using standard Linux commands (such as `cat`, `cp`, `mv`, or `rm`). Instead, you perform these tasks using the `hadoop fs` command.

The following steps are written with the assumption you have copied data from DynamoDB to HDFS using one of the procedures in this section.

1. If you are currently at the Hive command prompt, exit to the Linux command prompt.

```
hive> exit;
```

2. List the contents of the `/user/hadoop/hive-test` directory in HDFS. (This is where Hive copied the data from DynamoDB.)

```
hadoop fs -ls /user/hadoop/hive-test
```

The response should look similar to this:

```
Found 1 items
-rw-r--r-- 1 hadoop hadoop 29504 2016-06-08 23:40 /user/hadoop/hive-test/000000_0
```

The file name (`000000_0`) is system-generated.

3. View the contents of the file:

```
hadoop fs -cat /user/hadoop/hive-test/000000_0
```

**Note**

In this example, the file is relatively small (approximately 29 KB). Be careful when you use this command with files that are very large or contain non-printable characters.

4. (Optional) You can copy the data file from HDFS to the local file system on the leader node. After you do this, you can use standard Linux command line utilities to work with the data in the file.

```
hadoop fs -get /user/hadoop/hive-test/000000_0
```

This command will not overwrite the file.

**Note**

The local file system on the leader node has limited capacity. Do not use this command with files that are larger than the available space in the local file system.

## Using data compression

When you use Hive to copy data among different data sources, you can request on-the-fly data compression. Hive provides several compression codecs. You can choose one during your Hive session. When you do this, the data is compressed in the specified format.

The following example compresses data using the Lempel-Ziv-Oberhumer (LZO) algorithm.

```
SET hive.exec.compress.output=true;
SET io.seqfile.compression.type=BLOCK;
SET mapred.output.compression.codec = com.hadoop.compression.lzo.LzopCodec;

CREATE EXTERNAL TABLE lzo_compression_table (line STRING)
ROW FORMAT DELIMITED FIELDS TERMINATED BY '\t' LINES TERMINATED BY '\n'
LOCATION 's3://bucketname/path/subpath/';

INSERT OVERWRITE TABLE lzo_compression_table SELECT *
FROM hiveTableName;
```

The resulting file in Amazon S3 will have a system-generated name with .lzo at the end (for example, 8d436957-57ba-4af7-840c-96c2fc7bb6f5-000000.lzo).

The available compression codecs are:

- org.apache.hadoop.io.compress.GzipCodec
- org.apache.hadoop.io.compress.DefaultCodec
- com.hadoop.compression.lzo.LzoCodec
- com.hadoop.compression.lzo.LzopCodec
- org.apache.hadoop.io.compress.BZip2Codec
- org.apache.hadoop.io.compress.SnappyCodec

## Reading non-printable UTF-8 character data

To read and write non-printable UTF-8 character data, you can use the STORED AS SEQUENCEFILE clause when you create a Hive table. A SequenceFile is a Hadoop binary file format. You need to use Hadoop to read this file. The following example shows how to export data from DynamoDB into Amazon S3. You can use this functionality to handle non-printable UTF-8 encoded characters.

```
CREATE EXTERNAL TABLE s3_export(a_col string, b_col bigint, c_col array<string>)
STORED AS SEQUENCEFILE
LOCATION 's3://bucketname/path/subpath/';

INSERT OVERWRITE TABLE s3_export SELECT *
FROM hiveTableName;
```

## Performance tuning

When you create a Hive external table that maps to a DynamoDB table, you do not consume any read or write capacity from DynamoDB. However, read and write activity on the Hive table (such as `INSERT` or `SELECT`) translates directly into read and write operations on the underlying DynamoDB table.

Apache Hive on Amazon EMR implements its own logic for balancing the I/O load on the DynamoDB table and seeks to minimize the possibility of exceeding the table's provisioned throughput. At the end of each Hive query, Amazon EMR returns runtime metrics, including the number of times your provisioned throughput was exceeded. You can use this information, together with CloudWatch metrics on your DynamoDB table, to improve performance in subsequent requests.

The Amazon EMR console provides basic monitoring tools for your cluster. For more information, see [View and Monitor a Cluster](#) in the *Amazon EMR Management Guide*.

You can also monitor your cluster and Hadoop jobs using web-based tools, such as Hue, Ganglia, and the Hadoop web interface. For more information, see [View Web Interfaces Hosted on Amazon EMR Clusters](#) in the *Amazon EMR Management Guide*.

This section describes steps you can take to performance-tune Hive operations on external DynamoDB tables.

### Topics

- [DynamoDB provisioned throughput \(p. 1220\)](#)
- [Adjusting the mappers \(p. 1222\)](#)
- [Additional topics \(p. 1223\)](#)

## DynamoDB provisioned throughput

When you issue HiveQL statements against the external DynamoDB table, the `DynamoDBStorageHandler` class makes the appropriate low-level DynamoDB API requests, which consume provisioned throughput. If there is not enough read or write capacity on the DynamoDB table, the request will be throttled, resulting in slow HiveQL performance. For this reason, you should ensure that the table has enough throughput capacity.

For example, suppose that you have provisioned 100 read capacity units for your DynamoDB table. This will let you read 409,600 bytes per second (100 × 4 KB read capacity unit size). Now suppose that the table contains 20 GB of data (21,474,836,480 bytes) and you want to use the `SELECT` statement to select all of the data using HiveQL. You can estimate how long the query will take to run like this:

$$21,474,836,480 / 409,600 = 52,429 \text{ seconds} = 14.56 \text{ hours}$$

In this scenario, the DynamoDB table is a bottleneck. It won't help to add more Amazon EMR nodes, because the Hive throughput is constrained to only 409,600 bytes per second. The only way to decrease the time required for the `SELECT` statement is to increase the provisioned read capacity of the DynamoDB table.

You can perform a similar calculation to estimate how long it would take to bulk-load data into a Hive external table mapped to a DynamoDB table. Determine the total number of bytes in the data you want

to load, and then divide it by the size of one DynamoDB write capacity unit (1 KB). This will yield the number of seconds it will take to load the table.

You should regularly monitor the CloudWatch metrics for your table. For a quick overview in the DynamoDB console, choose your table and then choose the **Metrics** tab. From here, you can view read and write capacity units consumed and read and write requests that have been throttled.

## Read capacity

Amazon EMR manages the request load against your DynamoDB table, according to the table's provisioned throughput settings. However, if you notice a large number of ProvisionedThroughputExceeded messages in the job output, you can adjust the default read rate. To do this, you can modify the dynamodb.throughput.read.percent configuration variable. You can use the SET command to set this variable at the Hive command prompt:

```
SET dynamodb.throughput.read.percent=1.0;
```

This variable persists for the current Hive session only. If you exit Hive and return to it later, dynamodb.throughput.read.percent will return to its default value.

The value of dynamodb.throughput.read.percent can be between 0.1 and 1.5, inclusively. 0.5 represents the default read rate, meaning that Hive will attempt to consume half of the read capacity of the table. If you increase the value above 0.5, Hive will increase the request rate; decreasing the value below 0.5 decreases the read request rate. (The actual read rate will vary, depending on factors such as whether there is a uniform key distribution in the DynamoDB table.)

If you notice that Hive is frequently depleting the provisioned read capacity of the table, or if your read requests are being throttled too much, try reducing dynamodb.throughput.read.percent below 0.5. If you have sufficient read capacity in the table and want more responsive HiveQL operations, you can set the value above 0.5.

## Write capacity

Amazon EMR manages the request load against your DynamoDB table, according to the table's provisioned throughput settings. However, if you notice a large number of ProvisionedThroughputExceeded messages in the job output, you can adjust the default write rate. To do this, you can modify the dynamodb.throughput.write.percent configuration variable. You can use the SET command to set this variable at the Hive command prompt:

```
SET dynamodb.throughput.write.percent=1.0;
```

This variable persists for the current Hive session only. If you exit Hive and return to it later, dynamodb.throughput.write.percent will return to its default value.

The value of dynamodb.throughput.write.percent can be between 0.1 and 1.5, inclusively. 0.5 represents the default write rate, meaning that Hive will attempt to consume half of the write capacity of the table. If you increase the value above 0.5, Hive will increase the request rate; decreasing the value below 0.5 decreases the write request rate. (The actual write rate will vary, depending on factors such as whether there is a uniform key distribution in the DynamoDB table.)

If you notice that Hive is frequently depleting the provisioned write capacity of the table, or if your write requests are being throttled too much, try reducing dynamodb.throughput.write.percent below 0.5. If you have sufficient capacity in the table and want more responsive HiveQL operations, you can set the value above 0.5.

When you write data to DynamoDB using Hive, ensure that the number of write capacity units is greater than the number of mappers in the cluster. For example, consider an Amazon EMR cluster consisting of

10 *m1.xlarge* nodes. The *m1.xlarge* node type provides 8 mapper tasks, so the cluster would have a total of 80 mappers ( $10 \times 8$ ). If your DynamoDB table has fewer than 80 write capacity units, then a Hive write operation could consume all of the write throughput for that table.

To determine the number of mappers for Amazon EMR node types, see [Task Configuration](#) in the *Amazon EMR Developer Guide*.

For more information on mappers, see [Adjusting the mappers \(p. 1222\)](#).

## Adjusting the mappers

When Hive launches a Hadoop job, the job is processed by one or more mapper tasks. Assuming that your DynamoDB table has sufficient throughput capacity, you can modify the number of mappers in the cluster, potentially improving performance.

### Note

The number of mapper tasks used in a Hadoop job are influenced by *input splits*, where Hadoop subdivides the data into logical blocks. If Hadoop does not perform enough input splits, then your write operations might not be able to consume all the write throughput available in the DynamoDB table.

### Increasing the number of mappers

Each mapper in an Amazon EMR has a maximum read rate of 1 MiB per second. The number of mappers in a cluster depends on the size of the nodes in your cluster. (For information about node sizes and the number of mappers per node, see [Task Configuration](#) in the *Amazon EMR Developer Guide*.)

If your DynamoDB table has ample throughput capacity for reads, you can try increasing the number of mappers by doing one of the following:

- Increase the size of the nodes in your cluster. For example, if your cluster is using *m1.large* nodes (three mappers per node), you can try upgrading to *m1.xlarge* nodes (eight mappers per node).
- Increase the number of nodes in your cluster. For example, if you have three-node cluster of *m1.xlarge* nodes, you have a total of 24 mappers available. If you were to double the size of the cluster, with the same type of node, you would have 48 mappers.

You can use the AWS Management Console to manage the size or the number of nodes in your cluster. (You might need to restart the cluster for these changes to take effect.)

Another way to increase the number of mappers is to modify the `mapred.tasktracker.map.tasks.maximum` Hadoop configuration parameter. (This is a Hadoop parameter, not a Hive parameter. You cannot modify it interactively from the command prompt.). If you increase the value of `mapred.tasktracker.map.tasks.maximum`, you can increase the number of mappers without increasing the size or number of nodes. However, it is possible for the cluster nodes to run out of memory if you set the value too high.

You set the value for `mapred.tasktracker.map.tasks.maximum` as a bootstrap action when you first launch your Amazon EMR cluster. For more information, see [\(Optional\) Create Bootstrap Actions to Install Additional Software](#) in the *Amazon EMR Management Guide*.

### Decreasing the number of mappers

If you use the `SELECT` statement to select data from an external Hive table that maps to DynamoDB, the Hadoop job can use as many tasks as necessary, up to the maximum number of mappers in the cluster. In this scenario, it is possible that a long-running Hive query can consume all of the provisioned read capacity of the DynamoDB table, negatively impacting other users.

You can use the `dynamodb.max.map.tasks` parameter to set an upper limit for map tasks:

```
SET dynamodb.max.map.tasks=1
```

This value must be equal to or greater than 1. When Hive processes your query, the resulting Hadoop job will use no more than `dynamodb.max.map.tasks` when reading from the DynamoDB table.

## Additional topics

The following are some more ways to tune applications that use Hive to access DynamoDB.

### Retry duration

By default, Hive will rerun a Hadoop job if it has not returned any results from DynamoDB within two minutes. You can adjust this interval by modifying the `dynamodb.retry.duration` parameter:

```
SET dynamodb.retry.duration=2;
```

The value must be a nonzero integer, representing the number of minutes in the retry interval. The default for `dynamodb.retry.duration` is 2 (minutes).

### Parallel data requests

Multiple data requests, either from more than one user or more than one application to a single table can drain read provisioned throughput and slow performance.

### Process duration

Data consistency in DynamoDB depends on the order of read and write operations on each node. While a Hive query is in progress, another application might load new data into the DynamoDB table or modify or delete existing data. In this case, the results of the Hive query might not reflect changes made to the data while the query was running.

### Request time

Scheduling Hive queries that access a DynamoDB table when there is lower demand on the DynamoDB table improves performance. For example, if most of your application's users live in San Francisco, you might choose to export daily data at 4:00 A.M. PST when the majority of users are asleep and not updating records in your DynamoDB database.

# Integrating with Amazon S3

Amazon DynamoDB import and export capabilities provide a simple and efficient way to move data between Amazon S3 and DynamoDB tables without writing any code.

DynamoDB import and export features help you move, transform, and copy DynamoDB table accounts, or AWS. You can import from your S3 sources, and you can export your DynamoDB table data to Amazon S3 and use AWS services such as Athena, Amazon SageMaker, and AWS Lake Formation to analyze your data and extract actionable insights. You can also import data directly into new DynamoDB tables to build new applications with single-digit millisecond performance at scale, facilitate data sharing between tables and accounts, and simplify your disaster recovery and business continuity plans.

### Topics

- [DynamoDB data import from Amazon S3: how it works \(p. 1224\)](#)
- [DynamoDB data export to Amazon S3: how it works \(p. 1234\)](#)

## DynamoDB data import from Amazon S3: how it works

To import data into DynamoDB, your data must be in an Amazon S3 bucket in CSV, DynamoDB JSON, or Amazon Ion format. Data can be compressed in ZSTD or GZIP format, or can be directly imported in uncompressed form. Source data can either be a single Amazon S3 object or multiple Amazon S3 objects that use the same prefix.

Your data will be imported into a new DynamoDB table, which will be created when you initiate the import request. You can create this table with secondary indexes, then query and update your data across all primary and secondary indexes as soon as the import is complete. You can also add a global table replica after the import is complete.

### Note

During the Amazon S3 import process, DynamoDB creates a new target table that will be imported into.

Import from Amazon S3 does not consume write capacity on the new table, so you do not need to provision any extra capacity for importing data into DynamoDB. Data import pricing is based on the uncompressed size of the source data in Amazon S3, that is processed as a result of the import. Items that are processed but fail to load into the table due to formatting or other inconsistencies in the source data are also billed as part of the import process. See [Amazon DynamoDB pricing](#) for details.

You can import data from an Amazon S3 bucket owned by a different account if you have the correct permissions to read from that specific bucket. The new table may also be in a different Region from the source Amazon S3 bucket. For more information, see [Amazon Simple Storage Service setup and permissions](#).

Import times are directly related to your data's characteristics in Amazon S3. This includes data size, data format, compression scheme, uniformity of data distribution, number of Amazon S3 objects, and other related variables. In particular, data sets with uniformly distributed keys will be faster to import than skewed data sets. For example, if your secondary index's key is using the month of the year for partitioning, and all your data is from the month of December, then importing this data may take significantly longer.

The attributes associated with keys are expected to be unique on the base table. If they are not unique, the import will overwrite any existing item with matching keys. In such cases, the number of items processed in import table description will not match the number of items in the target table. For example, if the primary key is the month and multiple items are set to the month of September, each new item will overwrite the previously written items and only one item with the month (primary key) set to September will remain.

AWS CloudTrail logs all console and API actions for table import. For more information, see [Logging DynamoDB operations by using AWS CloudTrail \(p. 1133\)](#).

### Topics

- [Requesting a table import in DynamoDB \(p. 1224\)](#)
- [Amazon S3 import formats for DynamoDB \(p. 1228\)](#)
- [Import format quotas and validation \(p. 1230\)](#)

## Requesting a table import in DynamoDB

DynamoDB import allows you to import data from an Amazon S3 bucket to a new DynamoDB table. You can request a table import using the [DynamoDB console](#), the [CLI \(p. 61\)](#), [CloudFormation](#) or the [DynamoDB API](#).

If you want to use the AWS CLI, you must configure it first. For more information, see [Accessing DynamoDB \(p. 60\)](#).

**Note**

The Import Table feature interacts with multiple different AWS Services such as Amazon S3 and CloudWatch. Before you begin an import, make sure that the user or role that invokes the import APIs has permissions to all services and resources the feature depends on. For more information on errors and troubleshooting, see [Import format quotas and validation \(p. 1230\)](#)

**Topics**

- [Setting up IAM permissions \(p. 1225\)](#)
- [Requesting an import using the AWS Management Console \(p. 1226\)](#)
- [Getting details about past imports in the AWS Management Console \(p. 1227\)](#)
- [Requesting an import using the AWS CLI \(p. 1227\)](#)
- [Getting details about past imports in the AWS CLI \(p. 1227\)](#)

## Setting up IAM permissions

You can import data from any Amazon S3 bucket you have permission to read from. The source bucket does not need to be in the same Region or have the same owner as the source table. Your AWS Identity and Access Management (IAM) must include the relevant actions on the source Amazon S3 bucket, and required CloudWatch permissions for providing debugging information. An example policy is shown below.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "AllowDynamoDBImportAction",  
            "Effect": "Allow",  
            "Action": [  
                "dynamodb:ImportTable",  
                "dynamodb:DescribeImport",  
                "dynamodb>ListImports"  
            ],  
            "Resource": "arn:aws:dynamodb:us-east-1:111122223333:table/my-table"  
        },  
        {  
            "Sid": "AllowS3Access",  
            "Effect": "Allow",  
            "Action": [  
                "s3:GetObject",  
                "s3>ListBucket"  
            ],  
            "Resource": "arn:aws:s3:::your-bucket/*"  
        },  
        {  
            "Sid": "AllowCloudwatchAccess",  
            "Effect": "Allow",  
            "Action": [  
                "logs>CreateLogGroup",  
                "logs>CreateLogStream",  
                "logs>DescribeLogGroups",  
                "logs>DescribeLogStreams",  
                "logs>PutLogEvents",  
                "logs>PutRetentionPolicy"  
            ],  
            "Resource": "arn:aws:logs:us-east-1:111122223333:log-group:/aws-dynamodb/*"  
        }  
    ]  
}
```

}

## Amazon S3 permissions

When starting an import on an Amazon S3 bucket source that is owned by another account, ensure that the role or user has access to the Amazon S3 objects. You can check that by executing an Amazon S3 GetObject command and using the credentials. When using the API, the Amazon S3 bucket owner parameter defaults to the current user's account ID. For cross account imports, ensure that this parameter is correctly populated with the bucket owner's account ID. The following code is an example Amazon S3 bucket policy in the source account.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {"Sid": "ExampleStatement",  
            "Effect": "Allow",  
            "Principal": {"AWS": "arn:aws:iam::123456789012:user/Dave"},  
            "Action": [  
                "s3:GetObject",  
                "s3>ListBucket"  
            ],  
            "Resource": "arn:aws:s3:::awsexamplebucket1/*"  
        }  
    ]  
}
```

## KMS

When creating the new table for import, if you select an encryption at rest key that is not owned by DynamoDB then you must provide the AWS KMS permissions required to operate a DynamoDB table encrypted with CM-CMK. For more information see [Authorizing use of your AWS KMS key](#). If the Amazon S3 objects are encrypted with SSE-KMS, ensure that the role or user initiating the import has access to decrypt using the AWS KMS key. This feature does not support SSE-C encrypted Amazon S3 objects.

## CloudWatch permissions

The role or user that is initiating the import will need create and manage permissions for the log group and log streams associated with the import.

## Requesting an import using the AWS Management Console

The following example demonstrates how to use the DynamoDB console to import existing data to a new table named `MusicCollection`.

### To request a table import

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Import from S3**.
3. On the page that appears, select **Import from S3**.
4. Choose **Import from S3**.
5. Enter the Amazon S3 source URL.

If the source bucket is owned by your account, you can find it by using the **Browse S3** button. Alternately, you can enter the URL of the bucket in the `s3://bucket/prefix` format. The `prefix` is an Amazon S3 key prefix that is either the Amazon S3 object name that you want to import, or the key prefix shared by all the Amazon S3 objects that you want to import.

6. Specify if you are the **S3 bucket owner**. If the source bucket is owned by a different account, select **A different AWS account**. Then enter the account ID of the bucket owner.
7. Under **Import file compression**, select either **No compression**, **GZIP** or **ZSTD** as appropriate.
8. Select the appropriate Import file format. The options are **DynamoDB JSON**, **Amazon Ion** or **CSV**. If you select **CSV**, you will have two additional options: **CSV header** and **CSV delimiter character**.

For **CSV header**, choose if the header will either be taken from the first line of the file or be customized. If you select **Customize your headers**, you can specify the header values you want to import with. CSV Headers specified by this method are case-sensitive and are expected to contain the keys of the target table.

- For **CSV delimiter character**, you set the character which will separate items. Comma is selected by default. If you select **Custom delimiter character**, the delimiter must match the regex pattern: [ , ; : | \t ].
9. Select the **Next** button and select the options for the new table that will be created to store your data.

**Note**

Primary Key and Sort Key must match the attributes in the file, or the import will fail. The attributes are case sensitive.

10. Select **Next** again to review your import options, then click **Import** to begin the import task. You will first see your new table listed in the "Tables" with the status "Creating". At this time the table is not accessible.
11. Once the import completes, the status will show as "Active" and you can start using the table.

## Getting details about past imports in the AWS Management Console

You can find information about import tasks you've run in the past by clicking **Import from S3** in the navigation sidebar, then selecting the **Imports** tab. The import panel contains a list of all imports you've created in the past 90 days. Selecting the ARN of a task listed in the Imports tab will retrieve information about that import, including any advanced configuration settings you chose.

## Requesting an import using the AWS CLI

The following example imports CSV formatted data from an S3 bucket called `bucket` with a prefix of `prefix` to a new table called `target-table`.

```
aws dynamodb import-table --s3-bucket-source S3Bucket=bucket,S3KeyPrefix=prefix \
    --input-format CSV --table-creation-parameters '{"TableName":"target-
    table","KeySchema": \
        [{"AttributeName":"hk","KeyType":"HASH"}],"AttributeDefinitions": \
        [{"AttributeName":"hk","AttributeType":"S"}],"BillingMode":"PAY_PER_REQUEST"}' \
    --input-format-options '{"Csv": {"HeaderList": ["hk", "title", "artist",
    "year_of_release"]}, "Delimiter": ";"}}
```

**Note**

If you choose to encrypt your import using a key protected by AWS Key Management Service (AWS KMS), the key must be in the same Region as the destination Amazon S3 bucket.

## Getting details about past imports in the AWS CLI

You can find information about import tasks you've run in the past by using the `list-imports` command. This command returns a list of all imports you've created in the past 90 days. Note that although import task metadata expires after 90 days and jobs older than that are no longer found on this list, DynamoDB does not delete any of the objects in your Amazon S3 bucket or the table created during import.

```
aws dynamodb list-imports
```

To retrieve detailed information about a specific import task, including any advanced configuration settings, use the `describe-import` command.

```
aws dynamodb describe-import \
--import-arn arn:aws:dynamodb:us-east-1:123456789012:table/ProductCatalog/exp
```

## Amazon S3 import formats for DynamoDB

DynamoDB can import data in three formats: CSV, DynamoDB JSON, and Amazon Ion.

### Topics

- [CSV \(p. 1228\)](#)
- [DynamoDB Json \(p. 1228\)](#)
- [Amazon Ion \(p. 1229\)](#)

### CSV

A file in CSV format consists of multiple items delimited by newlines. By default, DynamoDB interprets the first line of an import file as the header and expects columns to be delimited by commas. You can also define headers that will be applied, as long as they match the number of columns in the file. If you define headers explicitly, the first line of the file will be imported as values.

#### Note

When importing from CSV files, all columns other than the hash range and keys of your base table and secondary indexes are imported as DynamoDB strings.

### DynamoDB Json

A file in DynamoDB JSON format consists of multiple Item objects. Each individual object is in DynamoDB's standard marshalled JSON format, and newlines are used as item delimiters. As an added feature, exports from point in time are supported as an import source by default.

#### Note

In the following example, a single item from a file in DynamoDB JSON format has been formatted on multiple lines for the sake of readability.

```
{
  "Item": {
    "Authors": {
      "SS": [
        "Author1",
        "Author2"
      ]
    },
    "Dimensions": {
      "S": "8.5 x 11.0 x 1.5"
    },
    "ISBN": {
      "S": "333-333333333"
    },
    "Id": {
      "N": "103"
    },
    "InPublication": {
      "BOOL": false
    }
  }
}
```

```

    "PageCount":{  
        "N":"600"  
    },  
    "Price":{  
        "N":"2000"  
    },  
    "ProductCategory":{  
        "S":"Book"  
    },  
    "Title":{  
        "S":"Book 103 Title"  
    }  
}  

}

```

## Amazon Ion

[Amazon Ion](#) is a richly-typed, self-describing, hierarchical data serialization format built to address rapid development, decoupling, and efficiency challenges faced every day while engineering large-scale, service-oriented architectures.

When you import data in Ion format, the Ion datatypes are mapped to DynamoDB datatypes in the new DynamoDB table.

	<b>Ion to DynamoDB datatype conversion</b>	<b>B</b>
1	Ion Data Type	DynamoDB Representation
2	string	String (s)
3	bool	Boolean (BOOL)
4	decimal	Number (N)
5	blob	Binary (B)
6	list (with type annotation \$dynamodb_SS, \$dynamodb_NS, or \$dynamodb_BS)	Set (SS, NS, BS)
7	list	List
8	struct	Map

Items in an Ion file are delimited by newlines. Each line begins with an Ion version marker, followed by an item in Ion format.

### Note

In the following example, an item from an Ion-formatted file has been formatted on multiple lines for the sake of readability.

```
$ion_1_0 {  
    Item:{  
        Authors:$dynamodb_SS:[ "Author1", "Author2" ],  
        Dimensions:"8.5 x 11.0 x 1.5",  
        ISBN:"333-333333333",  
        Id:103.,  
        InPublication:false,  
    }  
}
```

```
    PageCount:6d2,  
    Price:2d3,  
    ProductCategory:"Book",  
    Title:"Book 103 Title"  
}  
}
```

## Import format quotas and validation

### Import quotas

DynamoDB Import from Amazon S3 can support up to 50 concurrent import jobs with a total import source object size of 15TB at a time in us-east-1, us-west-2, and eu-west-1 regions. In all other regions, up to 50 concurrent import tasks with a total size of 1TB is supported. Each import job can take up to 5000 Amazon S3 objects in all regions. For more details on DynamoDB limits, see [Service Quotas](#).

### Validation errors

During the import process, DynamoDB may encounter errors while parsing your data. For each error, DynamoDB emits a CloudWatch log and keeps a count of the total number of errors encountered. If the Amazon S3 object itself is malformed or if its contents cannot form a DynamoDB item, then we may skip processing the remaining portion of the object.

There are three categories of import errors: API validation errors, data validation errors, and configuration errors.

#### API validation errors

API validation errors are item-level errors from the sync API. Common causes are permissions issues, missing required parameters and parameter validation failures. Details on why the API call failed are contained in the exceptions thrown by the `ImportTable` request.

#### Data validation errors

Data validation errors can occur at either the item level or file level. During import, items are validated based on DynamoDB rules before importing into the target table. When an item fails validation and is not imported, the import job skips over that item and continues on with the next item. At the end of job, the import status is set to FAILED with a `FailureCode`, `ItemValidationError` and the `FailureMessage` "Some of the items failed validation checks and were not imported. Please check CloudWatch error logs for more details."

Common causes for data validation errors include objects being unparsable, objects being in the incorrect format (input specifies DYNAMODB\_JSON but the object is not in DYNAMODB\_JSON), and schema mismatch with specified source table keys.

#### Configuration errors

Configuration errors are typically workflow errors due to permission validation. The Import workflow checks some permissions after accepting the request. If there are issues calling any of the required dependencies like Amazon S3 or CloudWatch the process marks the import status as FAILED. The `failureCode` and `failureMessage` point to the reason for failure. Where applicable, the failure message also contains the request id that you can use to investigate the reason for failure in CloudTrail.

Common configuration errors include having the wrong URL for the Amazon S3 bucket, and not having permission to access the Amazon S3 bucket, CloudWatch Logs, and AWS KMS keys used to decrypt the Amazon S3 object.

### Validating source Amazon S3 objects

In order to validate source S3 objects, take the following steps.

1. Validate the data format and compression type

- Make sure that all matching Amazon S3 objects under the specified prefix have the same format (DYNAMODB\_JSON, DYNAMODB\_ION, CSV)
- Make sure that all matching Amazon S3 objects under the specified prefix are compressed the same way (GZIP, ZSTD, NONE)

**Note**

The Amazon S3 objects do not need to have the corresponding extension (.csv / .json / .ion / .gz / .zstd etc) as the input format specified in ImportTable call takes precedence.

2. Validate that the import data conforms to the desired table schema

- Make sure that each item in the source data has the primary key. A sort key is optional for imports.
- Make sure that the attribute type associated with the primary key and any sort key matches the attribute type in the Table and the GSI schema, as specified in table creation parameters

## Troubleshooting

### CloudWatch logs

For Import jobs that fail, detailed error messages are posted to CloudWatch logs. To access these logs, first retrieve the ImportArn from the output and describe-import using this command:

```
aws dynamodb describe-import --import-arn arn:aws:dynamodb:us-east-1:ACCOUNT:table/target-table/import/01658528578619-c4d4e311}
```

Example output:

```
aws dynamodb describe-import --import-arn "arn:aws:dynamodb:us-east-1:531234567890:table/target-table/import/01658528578619-c4d4e311"
{
    "ImportTableDescription": {
        "ImportArn": "arn:aws:dynamodb:us-east-1:ACCOUNT:table/target-table/import/01658528578619-c4d4e311",
        "ImportStatus": "FAILED",
        "TableArn": "arn:aws:dynamodb:us-east-1:ACCOUNT:table/target-table",
        "TableId": "7b7ecc22-302f-4039-8ea9-8e7c3eb2bcb8",
        "ClientToken": "30f8891c-e478-47f4-af4a-67a5c3b595e3",
        "S3BucketSource": {
            "S3BucketOwner": "ACCOUNT",
            "S3Bucket": "my-import-source",
            "S3KeyPrefix": "import-test"
        },
        "ErrorCount": 1,
        "CloudWatchLogGroupArn": "arn:aws:logs:us-east-1:ACCOUNT:log-group:/aws-dynamodb/imports:*",
        "InputFormat": "CSV",
        "InputCompressionType": "NONE",
        "TableCreationParameters": {
            "TableName": "target-table",
            "AttributeDefinitions": [
                {
                    "AttributeName": "pk",
                    "AttributeType": "S"
                }
            ],
            "KeySchema": [
                {

```

```

        "AttributeName": "pk",
        "KeyType": "HASH"
    }
],
"BillingMode": "PAY_PER_REQUEST"
},
"StartTime": 1658528578.619,
"EndTime": 1658528750.628,
"ProcessedSizeBytes": 70,
"ProcessedItemCount": 1,
"ImportedItemCount": 0,
"FailureCode": "ItemValidationException",
"FailureMessage": "Some of the items failed validation checks and were not imported. Please check CloudWatch error logs for more details."
}
}

```

Retrieve the log group and the import id from the above response and use it to retrieve the error logs. The import ID is the last path element of the ImportArn field. The log group name is /aws-dynamodb/imports. The error log stream name is import-id/error. For this example, it would be 01658528578619-c4d4e311/error.

### Missing the key pk in the item

If the source S3 object does not contain the primary key that was provided as a parameter, the import will fail. For example, when you define the primary key for the import as column name "pk".

```

aws dynamodb import-table --s3-bucket-source S3Bucket=my-import-source,S3KeyPrefix=import-test.csv \
    --input-format CSV --table-creation-parameters '{"TableName":"target-table","KeySchema": \
        [{"AttributeName":"pk","KeyType":"HASH"}],"AttributeDefinitions": \
        [{"AttributeName":"pk","AttributeType":"S"}],"BillingMode":"PAY_PER_REQUEST"}'

```

The column "pk" is missing from the the source object import-test.csv which has the following contents:

```

title,artist,year_of_release
The Dark Side of the Moon,Pink Floyd,1973

```

This import will fail due to item validation error because of the missing primary key in the data source.

Example CloudWatch error log:

```

aws logs get-log-events --log-group-name /aws-dynamodb/imports --log-stream-name
01658528578619-c4d4e311/error
{
"events": [
{
"timestamp": 1658528745319,
"message": "{\"itemS3Pointer\":{\"bucket\":\"my-import-source\",\"key\":\"import-test.csv\"},\"itemIndex\":0,\"importArn\":\"arn:aws:dynamodb:us-east-1:531234567890:table/target-table/import/01658528578619-c4d4e311\",\"errorMessages\":[\"One or more parameter values were invalid: Missing the key pk in the item\"]}",
"ingestionTime": 1658528745414
},
{"nextForwardToken": "f/36986426953797707963335499204463414460239026137054642176/s",
"nextBackwardToken": "b/36986426953797707963335499204463414460239026137054642176/s"
}
]

```

This error log indicates that "One or more parameter values were invalid: Missing the key pk in the item". Since this import job failed, the table "target-table" now exists and is empty because no items were imported. The first item was processed and the object failed Item Validation.

To fix the issue, first delete "target-table" if it is no longer needed. Then either use a primary key column name that exists in the source object, or update the source data to:

```
pk,title,artist,year_of_release
Albums::Rock::Classic::1973::AlbumId::ALB25,The Dark Side of the Moon,Pink Floyd,1973
```

### Target table exists

When you start an import job and receive a response as follows:

```
An error occurred (ResourceInUseException) when calling the ImportTable operation: Table already exists: target-table
```

To fix this error, you will need to choose a table name that doesn't already exist and retry the import.

### The specified bucket does not exist

If the source bucket does not exist, the import will fail and log the error message details in CloudWatch.

Example describe import:

```
aws dynamodb --endpoint-url $ENDPOINT describe-import --import-arn "arn:aws:dynamodb:us-east-1:531234567890:table/target-table/import/01658530687105-e6035287"
{
  "ImportTableDescription": {
    "ImportArn": "arn:aws:dynamodb:us-east-1:ACCOUNT:table/target-table/import/01658530687105-e6035287",
    "ImportStatus": "FAILED",
    "TableArn": "arn:aws:dynamodb:us-east-1:ACCOUNT:table/target-table",
    "TableId": "e1215a82-b8d1-45a8-b2e2-14b9dd8eb99c",
    "ClientToken": "3048e16a-069b-47a6-9dfb-9c259fd2fb6f",
    "S3BucketSource": {
      "S3BucketOwner": "531234567890",
      "S3Bucket": "BUCKET_DOES_NOT_EXIST",
      "S3KeyPrefix": "import-test"
    },
    "ErrorCount": 0,
    "CloudWatchLogGroupArn": "arn:aws:logs:us-east-1:ACCOUNT:log-group:/aws-dynamodb/imports:*",
    "InputFormat": "CSV",
    "InputCompressionType": "NONE",
    "TableCreationParameters": {
      "TableName": "target-table",
      "AttributeDefinitions": [
        {
          "AttributeName": "pk",
          "AttributeType": "S"
        }
      ],
      "KeySchema": [
        {
          "AttributeName": "pk",
          "KeyType": "HASH"
        }
      ],
      "BillingMode": "PAY_PER_REQUEST"
    },
    "StartTime": 1658530687.105,
```

```
"EndTime": 1658530701.873,  
"ProcessedSizeBytes": 0,  
"ProcessedItemCount": 0,  
"ImportedItemCount": 0,  
"FailureCode": "S3NoSuchBucket",  
"FailureMessage": "The specified bucket does not exist (Service: Amazon S3; Status Code:  
404; Error Code: NoSuchBucket; Request ID: Q4W6QYYFDWY6WAKH; S3 Extended Request ID:  
ObgSlLeIMJp0qHLRX2C5Sy7n+8g6iGPwy7ixg7eEeTuEkg/+chU/JF+RbliWytMlkUlUcuCLTrI=; Proxy:  
null)"  
}  
}
```

The `FailureCode` is `S3NoSuchBucket`, with `FailureMessage` containing details such as request id and the service that threw the error. Since the error was caught before the data was imported into the table, a new DynamoDB table is not created. In some cases, when these errors are encountered after the data import has started, the table with partially imported data is retained.

To fix this error, make sure that the source Amazon S3 bucket exists and then restart the import process.

## DynamoDB data export to Amazon S3: how it works

Using DynamoDB table export, you can export data from an Amazon DynamoDB table from any time within your point-in-time recovery window to an Amazon S3 bucket. Exporting a DynamoDB table to an S3 bucket enables you to perform analytics and complex queries on your data using other AWS services such as Athena, AWS Glue, and Lake Formation. DynamoDB table export is a fully managed solution for exporting DynamoDB tables at scale, and is much faster than other workarounds involving table scans.

Exporting a table does not consume read capacity on the table, and has no impact on table performance and availability. You can export table data to an S3 bucket owned by another AWS account, and to a different Region than the one your table is in. Your data is always encrypted end-to-end.

You can export a DynamoDB table using the AWS Management Console, the AWS Command Line Interface, or the DynamoDB API. For more information, see [Requesting a table export in DynamoDB \(p. 1235\)](#).

For more information about AWS Region availability and pricing, see [Amazon DynamoDB pricing](#).

To export data from an Amazon DynamoDB table to an Amazon S3 bucket, point-in-time recovery (PITR) must be enabled on the source table. You can export table data from any point in time within the PITR window, up to 35 days. For more information, see [Point-in-time recovery for DynamoDB \(p. 649\)](#).

Exporting a table does not consume read capacity on the table, and has no impact on table performance and availability. You can export table data to an S3 bucket owned by another AWS account, and to a different Region than the one your table is in. Your data is always encrypted at rest and in transit.

You can choose to export your data in either DynamoDB JSON format or Amazon Ion text format. For more information about export formats, see [Data objects \(p. 1239\)](#).

You can export data to an S3 bucket owned by a different account if you have the correct permissions to write to that bucket. The destination bucket may be in a different region from the source table. For more information, see [Amazon S3 setup and permissions \(p. 1235\)](#).

Up to 300 export tasks, or up to 100 TB of table size, can be exported concurrently.

The request time and the time of the last update included in the data lake export request may vary within a one-minute time window. For example, if you submit the request at 2:25 PM, the output is guaranteed to contain all data committed to the table up to 2:24, and data committed after 2:26 will not be included. The output may or may not contain data modifications made between 2:24 and 2:26. Exported data is also not transactionally consistent.

AWS CloudTrail logs all console and API actions for table export to enable logging, continuous monitoring, and auditing. For more information, see [Logging DynamoDB operations by using AWS CloudTrail \(p. 1133\)](#).

DynamoDB table export is designed to be faster than exporting a table using a table scan. However, the exact time it takes for the export to complete depends on how large the table is and how uniformly the table data is distributed. If your use case involves real-time analytics, you can use Amazon Kinesis Data Streams. For more information, see the [Amazon Kinesis Data Streams Developer Guide](#).

For more information about Amazon S3, see the [Amazon Simple Storage Service User Guide](#).

#### Topics

- [Requesting a table export in DynamoDB \(p. 1235\)](#)
- [DynamoDB table export output format \(p. 1238\)](#)
- [Using DynamoDB table exports with other AWS services \(p. 1241\)](#)

## Requesting a table export in DynamoDB

DynamoDB table exports allow you to export table data to an Amazon S3 bucket, enabling you to perform analytics and complex queries on your data using other AWS services such as Athena, AWS Glue, and Lake Formation. You can request a table export using the AWS Management Console, the AWS CLI, or the DynamoDB API.

If you want to use the AWS CLI, you must configure it first. For more information, see [Accessing DynamoDB \(p. 60\)](#).

#### Topics

- [Amazon S3 setup and permissions \(p. 1235\)](#)
- [Requesting an export using the AWS Management Console \(p. 1236\)](#)
- [Getting details about past exports in the AWS Management Console \(p. 1237\)](#)
- [Requesting an export using the AWS CLI \(p. 1237\)](#)
- [Getting details about past exports in the AWS CLI \(p. 1237\)](#)

## Amazon S3 setup and permissions

You can export your table data to any Amazon S3 bucket you have permission to write to. The destination bucket does not need to be in the same Region or have the same owner as the source table. Your AWS Identity and Access Management (IAM) policy should allow the s3:AbortMultipartUpload, s3:PutObject, and s3:PutObjectAcl actions, in addition to the dynamodb:ExportTableToPointInTime permission, as shown in the following example.

#### Note

To export to a cross-account Amazon S3 bucket through the DynamoDB AWS Management Console, DynamoDB will need s3>ListBucket permissions for that bucket. The DynamoDB AWS Management Console will check for these permissions before allowing the export to start.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "AllowDynamoDBExportAction",  
            "Effect": "Allow",  
            "Action": "dynamodb:ExportTableToPointInTime",  
            "Resource": "arn:aws:dynamodb:us-east-1:111122223333:table/my-table"  
        },
```

```
{  
    "Sid": "AllowWriteToDestinationBucket",  
    "Effect": "Allow",  
    "Action": [  
        "s3:AbortMultipartUpload",  
        "s3:PutObject",  
        "s3:PutObjectAcl"  
    ],  
    "Resource": "arn:aws:s3:::your-bucket/*"  
}  
}  
}
```

The following code is an example S3 bucket policy (in the target account).

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Sid": "ExampleStatement",  
            "Effect": "Allow",  
            "Principal": {  
                "AWS": "arn:aws:iam::123456789012:user/Dave"  
            },  
            "Action": [  
                "s3:AbortMultipartUpload",  
                "s3:PutObject",  
                "s3:PutObjectAcl"  
            ],  
            "Resource": "arn:aws:s3:::awsexamplebucket1/*"  
        }  
    ]  
}
```

Revoking these permissions while an export is in progress will result in partial files.

## Requesting an export using the AWS Management Console

The following example demonstrates how to use the DynamoDB console to export an existing table named `MusicCollection`.

### Note

This procedure assumes that you have enabled point-in-time recovery. To enable it for the `MusicCollection` table, on the table's **Overview** tab, in the **Table details** section, choose **Enable for Point-in-time recovery**.

### To request a table export

1. Sign in to the AWS Management Console and open the DynamoDB console at <https://console.aws.amazon.com/dynamodb/>.
2. In the navigation pane on the left side of the console, choose **Exports to S3**.
3. Choose **Export to S3**.
4. Choose a source table and destination S3 bucket. If the destination bucket is owned by your account, you can use the **Browse S3** button to find it. Otherwise, enter the URL of the bucket using the `s3://bucketname/prefix` format. The `prefix` is an optional folder to help keep your destination bucket organized.
5. By default, your table will be exported in DynamoDB JSON format from the latest restorable time in the point in time recovery window and encrypted using an Amazon S3 key (SSE-S3). If you want to change these settings, expand the **Additional settings** section of the page and enter your desired export settings.

**Note**

If you choose to encrypt your export using a key protected by AWS Key Management Service (AWS KMS), the key must be in the same Region as the destination S3 bucket.

6. Click the **Export** button to begin the export.

## Getting details about past exports in the AWS Management Console

You can find information about export tasks you've run in the past by clicking **Streams and exports** in the navigation sidebar, then selecting the **Exports** tab. This tab contains a list of all exports you've created in the past 90 days. Selecting the ARN of a task listed in the Exports tab will retrieve information about that export, including any advanced configuration settings you chose. Note that although export task metadata expires after 90 days and jobs older than that are no longer found in this list, the objects in your S3 bucket remain as long as their bucket policies allow. DynamoDB never deletes any of the objects it creates in your S3 bucket during an export.

## Requesting an export using the AWS CLI

The following example shows how to use the AWS CLI to export an existing table named `MusicCollection` to an S3 bucket called `ddb-export-musiccollection`.

**Note**

This procedure assumes that you have enabled point-in-time recovery. To enable it for the `MusicCollection` table, run the following command.

```
aws dynamodb update-continuous-backups \
    --table-name MusicCollection \
    --point-in-time-recovery-specification PointInTimeRecoveryEnabled=True
```

The following command exports the `MusicCollection` to an S3 bucket called `ddb-export-musiccollection` with a prefix of `2020-Nov`. Table data will be exported in DynamoDB JSON format from a specific time within the point in time recovery window and encrypted using an Amazon S3 key (SSE-S3).

```
aws dynamodb export-table-to-point-in-time \
    --table-arn arn:aws:dynamodb:us-west-2:123456789012:table/MusicCollection \
    --s3-bucket ddb-export-musiccollection \
    --s3-prefix 2020-Nov \
    --export-format DYNAMODB_JSON \
    --export-time 1604632434 \
    --s3-sse-algorithm AES256
```

**Note**

If you choose to encrypt your export using a key protected by AWS Key Management Service (AWS KMS), the key must be in the same Region as the destination S3 bucket.

## Getting details about past exports in the AWS CLI

You can find information about export tasks you've run in the past by using the `list-exports` command. This command returns a list of all exports you've created in the past 90 days. Note that although export task metadata expires after 90 days and jobs older than that are no longer returned by the `list-exports` command, the objects in your S3 bucket remain as long as their bucket policies allow. DynamoDB never deletes any of the objects it creates in your S3 bucket during an export.

In the following example, we use the optional `table-arn` parameter to list only exports of a specific table.

```
aws dynamodb list-exports \
```

```
--table-arn arn:aws:dynamodb:us-east-1:123456789012:table/ProductCatalog
```

To retrieve detailed information about a specific export task, including any advanced configuration settings, use the `describe-export` command.

```
aws dynamodb describe-export \
  --export-arn arn:aws:dynamodb:us-east-1:123456789012:table/ProductCatalog/
  export/01234567890123-a1b2c3d4
```

## DynamoDB table export output format

A DynamoDB table export includes two manifest files in addition to the files containing your table data. These files are all saved in the Amazon S3 bucket that you specify in your [export request \(p. 1235\)](#). The following sections describe the format and contents of each output object.

### Topics

- [Manifest files \(p. 1238\)](#)
- [Data objects \(p. 1239\)](#)

## Manifest files

DynamoDB creates two manifest files, along with their checksum files, in the specified S3 bucket for each export request.

```
export-prefix/AWSDynoDB/ExportId/manifest-summary.json
export-prefix/AWSDynoDB/ExportId/manifest-summary.checksum
export-prefix/AWSDynoDB/ExportId/manifest-files.json
export-prefix/AWSDynoDB/ExportId/manifest-files.checksum
```

You choose an `export-prefix` when you request a table export. This helps you keep files in the destination S3 bucket organized. The `ExportId` is a unique token to ensure that multiple exports to the same S3 bucket and `export-prefix` don't overwrite each other.

### Note

DynamoDB also creates an empty file named `_started` in the same directory as the manifest files. This file verifies that the destination bucket is writable and that the export has begun. It can safely be deleted.

### The summary manifest

The `manifest-summary.json` file contains summary information about the export job. Its format is as follows:

```
{
  "version": "2020-06-30",
  "exportArn": "arn:aws:dynamodb:us-east-1:123456789012:table/ProductCatalog/
  export/01234567890123-a1b2c3d4",
  "startTime": "2020-11-04T07:28:34.028Z",
  "endTime": "2020-11-04T07:33:43.897Z",
  "tableArn": "arn:aws:dynamodb:us-east-1:123456789012:table/ProductCatalog",
  "tableId": "12345a12-abcd-123a-ab12-1234abc12345",
  "exportTime": "2020-11-04T07:28:34.028Z",
  "s3Bucket": "ddb-productcatalog-export",
  "s3Prefix": "2020-Nov",
  "s3SseAlgorithm": "AES256",
  "s3SseKmsKeyId": null,
  "manifestFilesS3Key": "AWSDynoDB/01345678901234-abc12345/manifest-files.json",
```

```
        "billedSizeBytes": 0,  
        "itemCount": 8,  
        "outputFormat": "DYNAMODB_JSON"  
    }  
}
```

## The files manifest

The `manifest-files.json` file contains information about the files that contain your exported table data. The file is in [JSON lines](#) format, meaning that newlines are used as item delimiters. In the following example, the details of one data file from a files manifest are formatted on multiple lines for the sake of readability.

```
{  
  "itemCount": 8,  
  "md5Checksum": "sQMSpEILNgoQmarvDFonGQ==",  
  "etag": "af83d6f217c19b8b0fff8023d8ca4716-1",  
  "dataFileS3Key": "AWSDynamoDB/1111111111111111-22222222/data/33334444EXAMPLE.json.gz"  
}
```

## Data objects

DynamoDB can export your table data in two formats: DynamoDB JSON and Amazon Ion. Regardless of the format you choose, your data will be written to multiple compressed files named by the keys found in the `manifest-files.json` file.

```
export-prefix/AWSDynoDB/ExportId/data/bafybeiczss3yxay3o4abnabb.json.gz  
export-prefix/AWSDynoDB/ExportId/data/gkes5o3lnrhznhyax3hxvya.json.gz
```

## DynamoDB JSON

A table export in DynamoDB JSON format consists of multiple `Item` objects. Each individual object is in DynamoDB's standard marshalled JSON format.

When creating custom parsers for DynamoDB JSON export data, keep in mind that the format is [JSON lines](#). This means that newlines are used as item delimiters. Many AWS services, such as Athena and AWS Glue, will parse this format automatically.

In the following example, a single item from a DynamoDB JSON export has been formatted on multiple lines for the sake of readability.

```
{
    "Item": {
        "Authors": {
            "SS": [
                "Author1",
                "Author2"
            ]
        },
        "Dimensions": {
            "S": "8.5 x 11.0 x 1.5"
        },
        "ISBN": {
            "S": "333-3333333333"
        },
        "Id": {
            "N": "103"
        },
        "InPublication": {
            "BOOL": false
        }
    }
}
```

```

    "PageCount":{  
        "N":"600"  
    },  
    "Price":{  
        "N":"2000"  
    },  
    "ProductCategory":{  
        "S":"Book"  
    },  
    "Title":{  
        "S":"Book 103 Title"  
    }  
}  

}

```

### Amazon Ion

**Amazon ion** is a richly-typed, self-describing, hierarchical data serialization format built to address rapid development, decoupling, and efficiency challenges faced every day while engineering large-scale, service-oriented architectures. DynamoDB supports exporting table data in Ion's [text format](#), which is a superset of JSON.

When you export a table to Ion format, the DynamoDB datatypes used in the table are mapped to [Ion datatypes](#). DynamoDB sets use [Ion type annotations](#) to disambiguate the datatype used in the source table.

### DynamoDB to ion datatype conversion

DynamoDB data type	Ion representation
String (S)	string
Boolean (BOOL)	bool
Number (N)	decimal
Binary (B)	blob
Set (SS, NS, BS)	list (with type annotation \$dynamodb_SS, \$dynamodb_NS, or \$dynamodb_BS)
List	list
Map	struct

Items in an Ion export are delimited by newlines. Each line begins with an Ion version marker, followed by an item in Ion format. In the following example, an item from an Ion export has been formatted on multiple lines for the sake of readability.

```
$ion_1_0 {  
    Item:{  
        Authors:$dynamodb_SS:[ "Author1", "Author2" ],  
        Dimensions:"8.5 x 11.0 x 1.5",  
        ISBN:"333-333333333",  
        Id:103.,  
        InPublication:false,  
        PageCount:6d2,  
        Price:2d3,  
        ProductCategory:"Book",  
        Title:"Book 103 Title"  
    }  
}
```

}

## Using DynamoDB table exports with other AWS services

Once your DynamoDB table data is exported to Amazon S3, you can process it from a variety of other AWS services. The following sections detail some of the options for querying your exported data.

### Using exports with Amazon Athena

Amazon Athena is an interactive query service that makes it easy to analyze data in Amazon S3 using standard SQL. Athena is serverless, so there is no infrastructure to manage and you pay only for the queries that you run. For more information, see the [Amazon Athena User Guide](#).

### Using exports with AWS Glue

AWS Glue is a fully managed extract, transform, and load (ETL) service that makes it easy to load your data for analytics. You can create and run an ETL job with a few clicks in the AWS Glue visual editor. You simply point AWS Glue to your data and AWS Glue discovers your data and stores the associated metadata (such as table definition and schema) in the AWS Glue Data Catalog. Once catalogued, your data is immediately searchable, queryable, and available for ETL. For more information, see the [AWS Glue Developer Guide](#).

### Using exports with AWS Lake Formation

AWS Lake Formation makes it easy to set up a secure data lake in days. A data lake is a centralized, curated, and secured repository that stores all your data, both in its original form and prepared for analysis. A data lake enables you to break down data silos and combine different types of analytics to gain insights and guide better business decisions.

Creating a data lake with Lake Formation is as simple as defining data sources and what data access and security policies you want to apply. Lake Formation then helps you collect and catalog data from databases and object storage, move the data into your new Amazon S3 data lake, clean and classify your data using machine learning algorithms, and secure access to your sensitive data. For more information, see the [AWS Lake Formation Developer Guide](#).

# Service, account, and table quotas in Amazon DynamoDB

This section describes current quotas, formerly referred to as limits, within Amazon DynamoDB. Each quota applies on a per-Region basis unless otherwise specified.

## Topics

- [Read/write capacity mode and throughput \(p. 1242\)](#)
- [Tables \(p. 1244\)](#)
- [Global tables \(p. 1245\)](#)
- [Secondary indexes \(p. 1245\)](#)
- [Partition keys and sort keys \(p. 1246\)](#)
- [Naming rules \(p. 1246\)](#)
- [Data types \(p. 1247\)](#)
- [Items \(p. 1247\)](#)
- [Attributes \(p. 1248\)](#)
- [Expression parameters \(p. 1248\)](#)
- [DynamoDB transactions \(p. 1249\)](#)
- [DynamoDB Streams \(p. 1249\)](#)
- [DynamoDB Accelerator \(DAX\) \(p. 1250\)](#)
- [API-specific limits \(p. 1250\)](#)
- [DynamoDB encryption at rest \(p. 1251\)](#)
- [Table export to Amazon S3 \(p. 1252\)](#)

## Read/write capacity mode and throughput

You can switch between read/write capacity modes once every 24 hours.

### Capacity unit sizes (for provisioned tables)

One read capacity unit = one strongly consistent read per second, or two eventually consistent reads per second, for items up to 4 KB in size.

One write capacity unit = one write per second, for items up to 1 KB in size.

Transactional read requests require two read capacity units to perform one read per second for items up to 4 KB.

Transactional write requests require two write capacity units to perform one write per second for items up to 1 KB.

### Request unit sizes (for on-demand tables)

One read request unit = one strongly consistent read, or two eventually consistent reads, for items up to 4 KB in size.

One write request unit = one write, for items up to 1 KB in size.

Transactional read requests require two read request units to perform one read for items up to 4 KB.

Transactional write requests require two write request units to perform one write for items up to 1 KB.

## Throughput default quotas

AWS places some default quotas on the throughput your account can provision and consume in a Region.

The account-level read throughput and account-level write throughput quotas apply at the account level. These account-level quotas apply to the sum of the provisioned throughput capacity for all your account's tables and global secondary indexes in a given Region. All the account's available throughput can be provisioned for a single table or across multiple tables. These quotas only apply to tables using the provisioned capacity mode.

The table-level read throughput and table-level write throughput quotas apply at a table level. These table-level quotas apply to tables that use the provisioned capacity mode as well as tables that use the on-demand capacity mode. These table-level quotas apply to the sum of a table's throughput together with the throughput of all of its global secondary indexes.

Below are the throughput quotas that apply on your account, by default.

	On-Demand	Provisioned	Adjustable
Per table	40,000 read request units and 40,000 write request units	40,000 read capacity units and 40,000 write capacity units	Yes
Per account	Not applicable	80,000 read capacity units and 80,000 write capacity units	Yes
Minimum throughput for any table or global secondary index	Not applicable	1 read capacity unit and 1 write capacity unit	Yes

You can use the [Service Quotas console](#), the [AWS API](#) and the [AWS CLI](#) to request quota increases for the adjustable quotas when needed.

For your account-level throughput quotas, you can use the [Service Quotas console](#), the [AWS CloudWatch console](#), the [AWS API](#) and the [AWS CLI](#) to create CloudWatch alarms and be notified automatically when your current usage reaches a specified percentage of your applied quota values. Using CloudWatch you can also monitor your usage by looking at the `AccountProvisionedReadCapacityUnits` and `AccountProvisionedWriteCapacityUnits` AWS usage metrics. To learn more about usage metrics, see [AWS usage metrics](#).

## Increasing or decreasing throughput (for provisioned tables)

### Increasing provisioned throughput

You can increase `ReadCapacityUnits` or `WriteCapacityUnits` as often as necessary, using the AWS Management Console or the `UpdateTable` operation. In a single call, you can increase the provisioned

throughput for a table, for any global secondary indexes on that table, or for any combination of these. The new settings do not take effect until the `UpdateTable` operation is complete.

You can't exceed your per-account quotas when you add provisioned capacity, and DynamoDB doesn't allow you to increase provisioned capacity very rapidly. Aside from these restrictions, you can increase the provisioned capacity for your tables as high as you need. For more information about per-account quotas, see the preceding section, [Throughput default quotas \(p. 1243\)](#).

## Decreasing provisioned throughput

For every table and global secondary index in an `UpdateTable` operation, you can decrease `ReadCapacityUnits` or `WriteCapacityUnits` (or both). The new settings don't take effect until the `UpdateTable` operation is complete.

There is a default quota on the number of provisioned capacity decreases you can perform on your DynamoDB table per day. A day is defined according to Universal Time Coordinated (UTC). On a given day, you can start by performing up to four decreases within one hour as long as you have not performed any other decreases yet during that day. Subsequently, you can perform one additional decrease per hour as long as there was no decreases in the preceding hour. This effectively brings the maximum number of decreases in a day to 27 times (4 decreases in the first hour, and 1 decrease for each of the subsequent 1-hour windows in a day).

You can use the [Service Quotas console](#), the [AWS API](#) and the [AWS CLI](#) to request quota increases, when needed.

### Important

Table and global secondary index decrease limits are decoupled, so any global secondary indexes for a particular table have their own decrease limits. However, if a single request decreases the throughput for a table and a global secondary index, it is rejected if either exceeds the current limits. Requests are not partially processed.

### Example

In the first 4 hours of a day, a table with a global secondary index can be modified as follows:

- Decrease the table's `WriteCapacityUnits` or `ReadCapacityUnits` (or both) four times.
- Decrease the `WriteCapacityUnits` or `ReadCapacityUnits` (or both) of the global secondary index four times.

At the end of that same day, the table and the global secondary index throughput can potentially be decreased a total of 27 times each.

# Tables

## Table size

There is no practical limit on a table's size. Tables are unconstrained in terms of the number of items or the number of bytes.

## Maximum number of tables per account per region

For any AWS account, there is an initial quota of 2,500 tables per AWS Region.

You can use the [Service Quotas console](#), the [AWS API](#) and the [AWS CLI](#) to view the default and applied quota values for the maximum number of tables for in your account, and to request quota increases, when needed. You can also request quota increases by cutting a ticket to [AWS support](#)

Using the [Service Quotas console](#), the [AWS API](#) and the [AWS CLI](#) you can create CloudWatch alarms to get notified automatically when your current usage reaches a specified percentage of your current quota. Using CloudWatch you can also monitor your usage by looking at the `TableCount` AWS usage metrics. To learn more about usage metrics, see [AWS usage metrics](#).

## Global tables

AWS places some default quotas on the throughput you can provision or utilize when using global tables.

	On-Demand	Provisioned
Per table	40,000 read request units and 40,000 write request units	40,000 read capacity units and 40,000 write capacity units
Per table, per destination Region, per day	10 TB for all source tables to which a replica was added for this destination Region	10 TB for all source tables to which a replica was added for this destination Region

If you are adding a replica for a table that is configured to use more than 40,000 write capacity units (WCU), you must request a service quota increase for your add replica WCU quota. To request a service quota increase see <https://aws.amazon.com/support>.

If you are adding a replica or replicas to one destination Region within a 24-hour period with a combined total greater than 10TB, you must request a service quota increase for your add replica data backfill quota.

Transactional operations provide atomicity, consistency, isolation, and durability (ACID) guarantees only within the AWS Region where the write is made originally. Transactions are not supported across Regions in global tables. For example, suppose that you have a global table with replicas in the US East (Ohio) and US West (Oregon) Regions and you perform a `TransactWriteItems` operation in the US East (N. Virginia) Region. In this case, you might observe partially completed transactions in the US West (Oregon) Region as changes are replicated. Changes are replicated to other Regions only after they have been committed in the source Region.

## Secondary indexes

### Secondary indexes per table

You can define a maximum of 5 local secondary indexes.

There is a default quota of 20 global secondary indexes per table. You can use the [Service Quotas console](#), the [AWS API](#) and the [AWS CLI](#) to check the global secondary indexes per table default and current quotas that apply for your account, and to request quota increases, when needed. You can also request quota increases by cutting a ticket to <https://aws.amazon.com/support>.

You can create or delete only one global secondary index per `UpdateTable` operation.

### Projected Secondary Index attributes per table

You can project a total of up to 100 attributes into all of a table's local and global secondary indexes. This only applies to user-specified projected attributes.

In a `CreateTable` operation, if you specify a `ProjectionType` of `INCLUDE`, the total count of attributes specified in `NonKeyAttributes`, summed across all of the secondary indexes, must not exceed 100. If you project the same attribute name into two different indexes, this counts as two distinct attributes when determining the total.

This limit does not apply for secondary indexes with a `ProjectionType` of `KEYS_ONLY` or `ALL`.

## Partition keys and sort keys

### Partition key length

The minimum length of a partition key value is 1 byte. The maximum length is 2048 bytes.

### Partition key values

There is no practical limit on the number of distinct partition key values, for tables or for secondary indexes.

### Sort key length

The minimum length of a sort key value is 1 byte. The maximum length is 1024 bytes.

### Sort key values

In general, there is no practical limit on the number of distinct sort key values per partition key value.

The exception is for tables with secondary indexes. With a local secondary index, there is a limit on item collection sizes: For every distinct partition key value, the total sizes of all table and index items cannot exceed 10 GB. This might constrain the number of sort keys per partition key value. For more information, see [Item collection size limit \(p. 550\)](#).

## Naming rules

### Table names and Secondary Index names

Names for tables and secondary indexes must be at least 3 characters long, but no greater than 255 characters long. The following are the allowed characters:

- A–Z
- a–z
- 0–9
- \_ (underscore)
- – (hyphen)
- . (dot)

### Attribute names

In general, an attribute name must be at least one character long, but no greater than 64 KB long.

The following are the exceptions. These attribute names must be no greater than 255 characters long:

- Secondary index partition key names.
  - Secondary index sort key names.
  - The names of any user-specified projected attributes (applicable only to local secondary indexes). In a `CreateTable` operation, if you specify a `ProjectionType` of `INCLUDE`, the names of the attributes in the `NonKeyAttributes` parameter are length-restricted. The `KEYS_ONLY` and `ALL` projection types are not affected.

These attribute names must be encoded using UTF-8, and the total size of each name (after encoding) cannot exceed 255 bytes.

# Data types

# String

The length of a String is constrained by the maximum item size of 400 KB.

Strings are Unicode with UTF-8 binary encoding. Because UTF-8 is a variable width encoding, DynamoDB determines the length of a String using its UTF-8 bytes.

## Number

A Number can have up to 38 digits of precision, and can be positive, negative, or zero.



DynamoDB uses JSON strings to represent Number data in requests and replies. For more information, see [DynamoDB low-level API \(p. 159\)](#).

If number precision is important, you should pass numbers to DynamoDB using strings that you convert from a number type.

# Binary

The length of a Binary is constrained by the maximum item size of 400 KB.

Applications that work with Binary attributes must encode the data in base64 format before sending it to DynamoDB. Upon receipt of the data, DynamoDB decodes it into an unsigned byte array and uses that as the length of the attribute.

# Items

## Item size

The maximum item size in DynamoDB is 400 KB, which includes both attribute name binary length (UTF-8 length) and attribute value lengths (again binary length). The attribute name counts towards the size limit.

For example, consider an item with two attributes: one attribute named "shirt-color" with value "R" and another attribute named "shirt-size" with value "M". The total size of that item is 23 bytes.

## Item size for tables with Local Secondary Indexes

For each local secondary index on a table, there is a 400 KB limit on the total of the following:

- The size of an item's data in the table.
- The size of the local secondary index entry corresponding to that item, including its key values and projected attributes.

## Attributes

### Attribute name-value pairs per item

The cumulative size of attributes per item must fit within the maximum DynamoDB item size (400 KB).

### Number of values in list, map, or set

There is no limit on the number of values in a List, a Map, or a Set, as long as the item containing the values fits within the 400 KB item size limit.

### Attribute values

Empty String and Binary attribute values are allowed, if the attribute is not used as a key attribute for a table or index. Empty String and Binary values are allowed inside Set, List, and Map types. An attribute value cannot be an empty Set (String Set, Number Set, or Binary Set). However, empty Lists and Maps are allowed.

### Nested attribute depth

DynamoDB supports nested attributes up to 32 levels deep.

## Expression parameters

Expression parameters include `ProjectionExpression`, `ConditionExpression`, `UpdateExpression`, and `FilterExpression`.

### Lengths

The maximum length of any expression string is 4 KB. For example, the size of the `ConditionExpression` `a=b` is 3 bytes.

The maximum length of any single expression attribute name or expression attribute value is 255 bytes. For example, `#name` is 5 bytes; `:val1` is 4 bytes.

The maximum length of all substitution variables in an expression is 2 MB. This is the sum of the lengths of all `ExpressionAttributeNames` and `ExpressionAttributeValues`.

## Operators and operands

The maximum number of operators or functions allowed in an `UpdateExpression` is 300. For example, the `UpdateExpression` `SET a = :val1 + :val2 + :val3` contains two "+" operators.

The maximum number of operands for the `IN` comparator is 100.

## Reserved words

DynamoDB does not prevent you from using names that conflict with reserved words. (For a complete list, see [Reserved words in DynamoDB \(p. 1310\)](#).)

However, if you use a reserved word in an expression parameter, you must also specify `ExpressionAttributeNames`. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#).

## DynamoDB transactions

DynamoDB transactional API operations have the following constraints:

- A transaction cannot contain more than 25 unique items.
- A transaction cannot contain more than 4 MB of data.
- No two actions in a transaction can work against the same item in the same table. For example, you cannot both `ConditionCheck` and `Update` the same item in one transaction.
- A transaction cannot operate on tables in more than one AWS account or Region.
- Transactional operations provide atomicity, consistency, isolation, and durability (ACID) guarantees only within the AWS Region where the write is made originally. Transactions are not supported across Regions in global tables. For example, suppose that you have a global table with replicas in the US East (Ohio) and US West (Oregon) Regions and you perform a `TransactWriteItems` operation in the US East (N. Virginia) Region. In this case, you might observe partially completed transactions in the US West (Oregon) Region as changes are replicated. Changes are replicated to other Regions only after they have been committed in the source Region.

## DynamoDB Streams

### Simultaneous readers of a shard in DynamoDB Streams

For single-Region tables that are not global tables, you can design for up to two processes to read from the same DynamoDB Streams shard at the same time. Exceeding this limit can result in request throttling. For global tables, we recommend you limit the number of simultaneous readers to one to avoid request throttling.

### Maximum write capacity for a table with DynamoDB Streams enabled

AWS places some default quotas on the write capacity for DynamoDB tables with DynamoDB Streams enabled. These default quotas are applicable only for tables in provisioned read/write capacity mode. The following are throughput quotas that apply to your account by default.

- US East (N. Virginia), US East (Ohio), US West (N. California), US West (Oregon), South America (São Paulo), Europe (Frankfurt), Europe (Ireland), Asia Pacific (Tokyo), Asia Pacific (Seoul), Asia Pacific (Singapore), Asia Pacific (Sydney), China (Beijing) Regions:
  - Per table – 40,000 write capacity units

- All other Regions:
  - Per table – 10,000 write capacity units

You can use the [Service Quotas console](#), the [AWS API](#) and the [AWS CLI](#) to check the maximum write capacity for a table with DynamoDB Streams enabled default and current quotas that apply on your account, and to request quota increases, when needed. You can also request quota increases by cutting a ticket to [AWS support](#).

**Note**

The provisioned throughput quotas also apply for DynamoDB tables with DynamoDB Streams enabled. When you request a quota increase on the write capacity for a table with Streams enabled, make sure you also request an increase of the provisioned throughput capacity for this table. For more information, see [Throughput Default Quotas](#). Other quotas also apply when processing higher throughput DynamoDB Streams. For more information, see [Amazon DynamoDB Streams API reference guide](#).

## DynamoDB Accelerator (DAX)

### AWS region availability

For a list of AWS Regions in which DAX is available, see [DynamoDB Accelerator \(DAX\)](#) in the *AWS General Reference*.

### Nodes

A DAX cluster consists of exactly one primary node, and between zero and ten read replica nodes.

The total number of nodes (per AWS account) cannot exceed 50 in a single AWS Region.

### Parameter groups

You can create up to 20 DAX parameter groups per Region.

### Subnet groups

You can create up to 50 DAX subnet groups per Region.

Within a subnet group, you can define up to 20 subnets.

## API-specific limits

### `CreateTable/UpdateTable/DeleteTable`

In general, you can have up to 500 `CreateTable`, `UpdateTable`, and `DeleteTable` requests running simultaneously in any combination. As a result, the total number of tables in the `CREATING`, `UPDATING`, or `DELETING` state cannot exceed 500.

You can use the [Service Quotas console](#), the [AWS API](#) and the [AWS CLI](#) to view default and applied quota values for concurrent control plane operations, and request quota increases, when needed. You can also request quota increases by cutting a ticket to [AWS support](#)

#### **BatchGetItem**

A single `BatchGetItem` operation can retrieve a maximum of 100 items. The total size of all the items retrieved cannot exceed 16 MB.

#### **BatchWriteItem**

A single `BatchWriteItem` operation can contain up to 25 `PutItem` or `DeleteItem` requests. The total size of all the items written cannot exceed 16 MB.

#### **DescribeTableReplicaAutoScaling**

`DescribeTableReplicaAutoScaling` method supports only 10 requests per second.

#### **DescribeLimits**

`DescribeLimits` should be called only periodically. You can expect throttling errors if you call it more than once in a minute.

#### **DescribeContributorInsights/ListContributorInsights/UpdateContributorInsights**

`DescribeContributorInsights`, `ListContributorInsights` and `UpdateContributorInsights` should be called only periodically. DynamoDB supports up to five requests per second for each of these APIs.

#### **Query**

The result set from a `Query` is limited to 1 MB per call. You can use the `LastEvaluatedKey` from the query response to retrieve more results.

#### **Scan**

The result set from a `Scan` is limited to 1 MB per call. You can use the `LastEvaluatedKey` from the scan response to retrieve more results.

#### **UpdateTableReplicaAutoScaling**

`UpdateTableReplicaAutoScaling` method supports only ten requests per second.

## DynamoDB encryption at rest

You can switch between an AWS owned key, an AWS managed key, and a customer managed key up to four times, anytime per 24-hour window, on a per table basis, starting from when the table was created. If there was no change in the past six hours, an additional change is allowed. This effectively brings the maximum number of changes in a day to eight (four changes in the first six hours, and one change for each of the subsequent six hour windows in a day).

You can switch encryption keys to use an AWS owned key as often as necessary, even if the above quota has been exhausted.

These are the quotas unless you request a higher amount. To request a service quota increase, see <https://aws.amazon.com/support>.

## Table export to Amazon S3

Up to 300 export tasks, or up to 100 TB of table size, can be exported concurrently.

# Low-level API reference

The [Amazon DynamoDB API reference](#) contains a complete list of operations supported by:

- [DynamoDB](#).
- [DynamoDB Streams](#).
- [DynamoDB Accelerator \(DAX\)](#).

# DynamoDB Appendix

## Topics

- [Troubleshooting SSL/TLS connection establishment issues \(p. 1254\)](#)
- [Example tables and data \(p. 1256\)](#)
- [Creating example tables and uploading data \(p. 1265\)](#)
- [DynamoDB example application using the AWS SDK for Python \(Boto\): Tic-tac-toe \(p. 1281\)](#)
- [Exporting and importing DynamoDB data using AWS Data Pipeline \(p. 1300\)](#)
- [Amazon DynamoDB Storage Backend for Titan \(p. 1309\)](#)
- [Reserved words in DynamoDB \(p. 1310\)](#)
- [Legacy conditional parameters \(p. 1318\)](#)
- [Previous low-level API version \(2011-12-05\) \(p. 1336\)](#)
- [AWS SDK for Java 1.x examples \(p. 1399\)](#)

## Troubleshooting SSL/TLS connection establishment issues

Amazon DynamoDB is in the process of moving our endpoints to secure certificates signed by the Amazon Trust Services (ATS) Certificate Authority instead of third-party Certificate Authority. In December 2017, we launched the EU-WEST-3 (Paris) Region with the secure certificates issued by the Amazon Trust Services. All new regions launched after December 2017 have endpoints with the certificates issued by the Amazon Trust Services. This guide shows you how to validate and troubleshoot SSL/TLS connection issues.

## Testing your application or service

Most AWS SDKs and Command Line Interfaces (CLIs) support the Amazon Trust Services Certificate Authority. If you are using a version of the AWS SDK for Python or CLI released before October 29, 2013, you must upgrade. The .NET, Java, PHP, Go, JavaScript, and C++ SDKs and CLIs do not bundle any certificates, their certificates come from the underlying operating system. The Ruby SDK has included at least one of the required CAs since June 10, 2015. Before that date, the Ruby V2 SDK did not bundle certificates. If you use an unsupported, custom, or modified version of the AWS SDK, or if you use custom trust store, you might not have the support needed for Amazon Trust Services Certificate Authority.

To validate access to DynamoDB endpoints, you will need to develop a test that accesses DynamoDB API or DynamoDB Streams API in the EU-WEST-3 region and validate that the TLS handshake succeeds. The specific endpoints you will need to access in such test are:

- DynamoDB: <https://dynamodb.eu-west-3.amazonaws.com>
- DynamoDB Streams: <https://streams.dynamodb.eu-west-3.amazonaws.com>

If your application does not support Amazon Trust Services Certificate Authority you will see one of the following failures:

- SSL/TLS Negotiation errors
- A long delay before your software receives an error indicating SSL/TLS negotiation failure. The delay time depends on the retry strategy and timeout configuration of your client.

## Testing your client browser

To verify that your browser can connect to Amazon DynamoDB, open the following URL: <https://dynamodb.eu-west-3.amazonaws.com>. If the test is successful, you will see a message like this:

```
healthy: dynamodb.eu-west-3.amazonaws.com
```

If the test is unsuccessful, it will display an error similar to this: <https://untrusted-root.badssl.com/>.

## Updating your software application client

Applications accessing DynamoDB or DynamoDB Streams API endpoints (whether through browsers or programmatically) will need to update the trusted CA list on the client machines if they do not already support any of the following CAs:

- Amazon Root CA 1
- Starfield Services Root Certificate Authority - G2
- Starfield Class 2 Certification Authority

If the clients already trust ANY of the above three CAs then these will trust certificates used by DynamoDB and no action is required. However, if your clients do not already trust any of the above CAs, the HTTPS connections to the DynamoDB or DynamoDB Streams APIs will fail. For more information, please visit this blog post: <https://aws.amazon.com/blogs/security/how-to-prepare-for-aws-move-to-its-own-certificate-authority/>.

## Updating your client browser

You can update the certificate bundle in your browser simply by updating your browser. Instructions for the most common browsers can be found on the browsers' websites:

- Chrome: <https://support.google.com/chrome/answer/95414?hl=en>
- Firefox: <https://support.mozilla.org/en-US/kb/update-firefox-latest-version>
- Safari: <https://support.apple.com/en-us/HT204416>
- Internet Explorer: <https://support.microsoft.com/en-us/help/17295/windows-internet-explorer-which-version#ie=other>

## Manually updating your certificate bundle

If you cannot access the DynamoDB API or DynamoDB Streams API then you need to update your certificate bundle. To do this, you need to import at least one of the required CAs. You can find these at <https://www.amazontrust.com/repository/>.

The following operating systems and programming languages support Amazon Trust Services certificates:

- Microsoft Windows versions that have January 2005 or later updates installed, Windows Vista, Windows 7, Windows Server 2008, and newer versions.
- MacOS X 10.4 with Java for MacOS X 10.4 Release 5, MacOS X 10.5 and newer versions.
- Red Hat Enterprise Linux 5 (March 2007), Linux 6, and Linux 7 and CentOS 5, CentOS 6, and CentOS 7
- Ubuntu 8.10
- Debian 5.0

- Amazon Linux (all versions)
- Java 1.4.2\_12, Java 5 update 2, and all newer versions, including Java 6, Java 7, and Java 8

If you are still unable to connect please consult your software documentation, OS Vendor or contact AWS Support <https://aws.amazon.com/support> for further assistance.

## Example tables and data

The *Amazon DynamoDB Developer Guide* uses sample tables to illustrate various aspects of DynamoDB.

Table name	Primary key
<i>ProductCatalog</i>	Simple primary key: <ul style="list-style-type: none"><li>• <code>Id</code> (Number)</li></ul>
<i>Forum</i>	Simple primary key: <ul style="list-style-type: none"><li>• <code>Name</code> (String)</li></ul>
<i>Thread</i>	Composite primary key: <ul style="list-style-type: none"><li>• <code>ForumName</code> (String)</li><li>• <code>Subject</code> (String)</li></ul>
<i>Reply</i>	Composite primary key: <ul style="list-style-type: none"><li>• <code>Id</code> (String)</li><li>• <code>ReplyDateTime</code> (String)</li></ul>

The *Reply* table has a global secondary index named *PostedBy-Message-Index*. This index will facilitate queries on two non-key attributes of the *Reply* table.

Index name	Primary key
<i>PostedBy-Message-Index</i>	Composite primary key: <ul style="list-style-type: none"><li>• <code>PostedBy</code> (String)</li><li>• <code>Message</code> (String)</li></ul>

For more information about these tables, see [Use case 1: Product catalog \(p. 269\)](#) and [Use case 2: Forum application \(p. 269\)](#).

## Sample data files

### Topics

- [ProductCatalog sample data \(p. 1257\)](#)
- [Forum sample data \(p. 1261\)](#)
- [Thread sample data \(p. 1262\)](#)
- [Reply sample data \(p. 1264\)](#)

The following sections show the sample data files that are used for loading the *ProductCatalog*, *Forum*, *Thread* and *Reply* tables.

Each data file contains multiple `PutRequest` elements, each of which contain a single item. These `PutRequest` elements are used as input to the `BatchWriteItem` operation, using the AWS Command Line Interface (AWS CLI).

For more information, see [Step 2: Load data into tables \(p. 271\)](#) in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#).

## ProductCatalog sample data

```
{  
    "ProductCatalog": [  
        {  
            "PutRequest": {  
                "Item": {  
                    "Id": {  
                        "N": "101"  
                    },  
                    "Title": {  
                        "S": "Book 101 Title"  
                    },  
                    "ISBN": {  
                        "S": "111-1111111111"  
                    },  
                    "Authors": {  
                        "L": [  
                            {  
                                "S": "Author1"  
                            }  
                        ]  
                    },  
                    "Price": {  
                        "N": "2"  
                    },  
                    "Dimensions": {  
                        "S": "8.5 x 11.0 x 0.5"  
                    },  
                    "PageCount": {  
                        "N": "500"  
                    },  
                    "InPublication": {  
                        "BOOL": true  
                    },  
                    "ProductCategory": {  
                        "S": "Book"  
                    }  
                }  
            }  
        },  
        {  
            "PutRequest": {  
                "Item": {  
                    "Id": {  
                        "N": "102"  
                    },  
                    "Title": {  
                        "S": "Book 102 Title"  
                    },  
                    "ISBN": {  
                        "S": "222-2222222222"  
                    },  
                    "Authors": {  
                }  
            }  
        }  
    ]  
}
```

```
"L": [
    {
        "S": "Author1"
    },
    {
        "S": "Author2"
    }
]
},
"Price": {
    "N": "20"
},
"Dimensions": {
    "S": "8.5 x 11.0 x 0.8"
},
"PageCount": {
    "N": "600"
},
"InPublication": {
    "BOOL": true
},
"ProductCategory": {
    "S": "Book"
}
}
}
},
{
    "PutRequest": {
        "Item": {
            "Id": {
                "N": "103"
            },
            "Title": {
                "S": "Book 103 Title"
            },
            "ISBN": {
                "S": "333-3333333333"
            },
            "Authors": {
                "L": [
                    {
                        "S": "Author1"
                    },
                    {
                        "S": "Author2"
                    }
                ]
            },
            "Price": {
                "N": "2000"
            },
            "Dimensions": {
                "S": "8.5 x 11.0 x 1.5"
            },
            "PageCount": {
                "N": "600"
            },
            "InPublication": {
                "BOOL": false
            },
            "ProductCategory": {
                "S": "Book"
            }
        }
    }
}
```

```
},
{
    "PutRequest": {
        "Item": {
            "Id": {
                "N": "201"
            },
            "Title": {
                "S": "18-Bike-201"
            },
            "Description": {
                "S": "201 Description"
            },
            "BicycleType": {
                "S": "Road"
            },
            "Brand": {
                "S": "Mountain A"
            },
            "Price": {
                "N": "100"
            },
            "Color": {
                "L": [
                    {
                        "S": "Red"
                    },
                    {
                        "S": "Black"
                    }
                ]
            },
            "ProductCategory": {
                "S": "Bicycle"
            }
        }
    }
},
{
    "PutRequest": {
        "Item": {
            "Id": {
                "N": "202"
            },
            "Title": {
                "S": "21-Bike-202"
            },
            "Description": {
                "S": "202 Description"
            },
            "BicycleType": {
                "S": "Road"
            },
            "Brand": {
                "S": "Brand-Company A"
            },
            "Price": {
                "N": "200"
            },
            "Color": {
                "L": [
                    {
                        "S": "Green"
                    },
                    {
                        "S": "Black"
                    }
                ]
            }
        }
    }
}
```

```
        }
    ],
},
"ProductCategory": {
    "S": "Bicycle"
}
}
},
{
    "PutRequest": {
        "Item": {
            "Id": {
                "N": "203"
            },
            "Title": {
                "S": "19-Bike-203"
            },
            "Description": {
                "S": "203 Description"
            },
            "BicycleType": {
                "S": "Road"
            },
            "Brand": {
                "S": "Brand-Company B"
            },
            "Price": {
                "N": "300"
            },
            "Color": {
                "L": [
                    {
                        "S": "Red"
                    },
                    {
                        "S": "Green"
                    },
                    {
                        "S": "Black"
                    }
                ]
            },
            "ProductCategory": {
                "S": "Bicycle"
            }
        }
    }
},
{
    "PutRequest": {
        "Item": {
            "Id": {
                "N": "204"
            },
            "Title": {
                "S": "18-Bike-204"
            },
            "Description": {
                "S": "204 Description"
            },
            "BicycleType": {
                "S": "Mountain"
            },
            "Brand": {
                "S": "Brand-Company B"
            }
        }
    }
}
```

```

        },
        "Price": {
            "N": "400"
        },
        "Color": {
            "L": [
                {
                    "S": "Red"
                }
            ]
        },
        "ProductCategory": {
            "S": "Bicycle"
        }
    }
},
{
    "PutRequest": {
        "Item": {
            "Id": {
                "N": "205"
            },
            "Title": {
                "S": "18-Bike-204"
            },
            "Description": {
                "S": "205 Description"
            },
            "BicycleType": {
                "S": "Hybrid"
            },
            "Brand": {
                "S": "Brand-Company C"
            },
            "Price": {
                "N": "500"
            },
            "Color": {
                "L": [
                    {
                        "S": "Red"
                    },
                    {
                        "S": "Black"
                    }
                ]
            },
            "ProductCategory": {
                "S": "Bicycle"
            }
        }
    }
}
]
}

```

## Forum sample data

```
{
    "Forum": [
        {
            "PutRequest": {
                "Item": {

```

```

        "Name": {"S":"Amazon DynamoDB"},  

        "Category": {"S":"Amazon Web Services"},  

        "Threads": {"N":"2"},  

        "Messages": {"N":"4"},  

        "Views": {"N":"1000"}  

    }  

}  

},  

{  

    "PutRequest": {  

        "Item": {  

            "Name": {"S":"Amazon S3"},  

            "Category": {"S":"Amazon Web Services"}  

        }  

    }  

}  

]  

}

```

## Thread sample data

```

{
    "Thread": [
        {
            "PutRequest": {
                "Item": {
                    "ForumName": {
                        "S": "Amazon DynamoDB"
                    },
                    "Subject": {
                        "S": "DynamoDB Thread 1"
                    },
                    "Message": {
                        "S": "DynamoDB thread 1 message"
                    },
                    "LastPostedBy": {
                        "S": "User A"
                    },
                    "LastPostedDateTime": {
                        "S": "2015-09-22T19:58:22.514Z"
                    },
                    "Views": {
                        "N": "0"
                    },
                    "Replies": {
                        "N": "0"
                    },
                    "Answered": {
                        "N": "0"
                    },
                    "Tags": {
                        "L": [
                            {
                                "S": "index"
                            },
                            {
                                "S": "primarykey"
                            },
                            {
                                "S": "table"
                            }
                        ]
                    }
                }
            }
        }
    ]
}

```

```
        }
    },
{
    "PutRequest": {
        "Item": {
            "ForumName": {
                "S": "Amazon DynamoDB"
            },
            "Subject": {
                "S": "DynamoDB Thread 2"
            },
            "Message": {
                "S": "DynamoDB thread 2 message"
            },
            "LastPostedBy": {
                "S": "User A"
            },
            "LastPostedDateTime": {
                "S": "2015-09-15T19:58:22.514Z"
            },
            "Views": {
                "N": "3"
            },
            "Replies": {
                "N": "0"
            },
            "Answered": {
                "N": "0"
            },
            "Tags": {
                "L": [
                    {
                        "S": "items"
                    },
                    {
                        "S": "attributes"
                    },
                    {
                        "S": "throughput"
                    }
                ]
            }
        }
    },
{
    "PutRequest": {
        "Item": {
            "ForumName": {
                "S": "Amazon S3"
            },
            "Subject": {
                "S": "S3 Thread 1"
            },
            "Message": {
                "S": "S3 thread 1 message"
            },
            "LastPostedBy": {
                "S": "User A"
            },
            "LastPostedDateTime": {
                "S": "2015-09-29T19:58:22.514Z"
            },
            "Views": {
                "N": "0"
            }
        }
    }
}
```

```
        "Replies": {
            "N": "0"
        },
        "Answered": {
            "N": "0"
        },
        "Tags": [
            {
                "L": [
                    {
                        "S": "largeobjects"
                    },
                    {
                        "S": "multipart upload"
                    }
                ]
            }
        ]
    }
}
```

## Reply sample data

```
{
    "Reply": [
        {
            "PutRequest": {
                "Item": {
                    "Id": {
                        "S": "Amazon DynamoDB#DynamoDB Thread 1"
                    },
                    "ReplyDateTime": {
                        "S": "2015-09-15T19:58:22.947Z"
                    },
                    "Message": {
                        "S": "DynamoDB Thread 1 Reply 1 text"
                    },
                    "PostedBy": {
                        "S": "User A"
                    }
                }
            }
        },
        {
            "PutRequest": {
                "Item": {
                    "Id": {
                        "S": "Amazon DynamoDB#DynamoDB Thread 1"
                    },
                    "ReplyDateTime": {
                        "S": "2015-09-22T19:58:22.947Z"
                    },
                    "Message": {
                        "S": "DynamoDB Thread 1 Reply 2 text"
                    },
                    "PostedBy": {
                        "S": "User B"
                    }
                }
            }
        },
        {
            "PutRequest": {
```

```
        "Item": {
            "Id": {
                "S": "Amazon DynamoDB#DynamoDB Thread 2"
            },
            "ReplyDateTime": {
                "S": "2015-09-29T19:58:22.947Z"
            },
            "Message": {
                "S": "DynamoDB Thread 2 Reply 1 text"
            },
            "PostedBy": {
                "S": "User A"
            }
        }
    }
},
{
    "PutRequest": {
        "Item": {
            "Id": {
                "S": "Amazon DynamoDB#DynamoDB Thread 2"
            },
            "ReplyDateTime": {
                "S": "2015-10-05T19:58:22.947Z"
            },
            "Message": {
                "S": "DynamoDB Thread 2 Reply 2 text"
            },
            "PostedBy": {
                "S": "User A"
            }
        }
    }
}
]
```

## Creating example tables and uploading data

### Topics

- [Creating example tables and uploading data using the AWS SDK for Java \(p. 1265\)](#)
- [Creating example tables and uploading data using the AWS SDK for .NET \(p. 1272\)](#)

In [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#), you first create tables using the DynamoDB console and then use the AWS CLI to add data to the tables. This appendix provides code to both create the tables and add data programmatically.

## Creating example tables and uploading data using the AWS SDK for Java

The following Java code example creates tables and uploads data to the tables. The resulting table structure and data is shown in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#). For step-by-step instructions to run this code using Eclipse, see [Java code examples \(p. 274\)](#).

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 */
```

```

/*
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

package com.amazonaws.codesamples;

import java.text.SimpleDateFormat;
import java.util.ArrayList;
import java.util.Arrays;
import java.util.Date;
import java.util.HashSet;
import java.util.TimeZone;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Item;
import com.amazonaws.services.dynamodbv2.document.Table;
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;
import com.amazonaws.services.dynamodbv2.model.CreateTableRequest;
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;
import com.amazonaws.services.dynamodbv2.model.KeyType;
import com.amazonaws.services.dynamodbv2.model.LocalSecondaryIndex;
import com.amazonaws.services.dynamodbv2.model.Projection;
import com.amazonaws.services.dynamodbv2.model.ProjectionType;
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;

public class CreateTablesLoadData {

    static AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();
    static DynamoDB dynamoDB = new DynamoDB(client);

    static SimpleDateFormat dateFormatter = new SimpleDateFormat("yyyy-MM-
dd'T'HH:mm:ss.SSS'Z'");

    static String productCatalogTableName = "ProductCatalog";
    static String forumTableName = "Forum";
    static String threadTableName = "Thread";
    static String replyTableName = "Reply";

    public static void main(String[] args) throws Exception {

        try {

            deleteTable(productCatalogTableName);
            deleteTable(forumTableName);
            deleteTable(threadTableName);
            deleteTable(replyTableName);

            // Parameter1: table name
            // Parameter2: reads per second
            // Parameter3: writes per second
            // Parameter4/5: partition key and data type
            // Parameter6/7: sort key and data type (if applicable)

            createTable(productCatalogTableName, 10L, 5L, "Id", "N");
            createTable(forumTableName, 10L, 5L, "Name", "S");
        }
    }
}

```

```

        createTable(threadTableName, 10L, 5L, "ForumName", "S", "Subject", "S");
        createTable(replyTableName, 10L, 5L, "Id", "S", "ReplyDateTime", "S");

        loadSampleProducts(productCatalogTableName);
        loadSampleForums(forumTableName);
        loadSampleThreads(threadTableName);
        loadSampleReplies(replyTableName);

    }
    catch (Exception e) {
        System.err.println("Program failed:");
        System.err.println(e.getMessage());
    }
    System.out.println("Success.");
}

private static void deleteTable(String tableName) {
    Table table = dynamoDB.getTable(tableName);
    try {
        System.out.println("Issuing DeleteTable request for " + tableName);
        table.delete();
        System.out.println("Waiting for " + tableName + " to be deleted...this may take
a while...");
        table.waitForDelete();

    }
    catch (Exception e) {
        System.err.println("DeleteTable request failed for " + tableName);
        System.err.println(e.getMessage());
    }
}

private static void createTable(String tableName, long readCapacityUnits, long
writeCapacityUnits,
        String partitionKeyName, String partitionKeyType) {

    createTable(tableName, readCapacityUnits, writeCapacityUnits, partitionKeyName,
partitionKeyType, null, null);
}

private static void createTable(String tableName, long readCapacityUnits, long
writeCapacityUnits,
        String partitionKeyName, String partitionKeyType, String sortKeyName, String
sortKeyType) {

    try {

        ArrayList<KeySchemaElement> keySchema = new ArrayList<KeySchemaElement>();
        keySchema.add(new
KeySchemaElement().withAttributeName(partitionKeyName).withKeyType(KeyType.HASH)); // Partition

        // key

        ArrayList<AttributeDefinition> attributeDefinitions = new
ArrayList<AttributeDefinition>();
        attributeDefinitions
            .add(new
AttributeDefinition().withAttributeName(partitionKeyName).withAttributeType(partitionKeyType));

        if (sortKeyName != null) {
            keySchema.add(new
KeySchemaElement().withAttributeName(sortKeyName).withKeyType(KeyType.RANGE)); // Sort

            // key
            attributeDefinitions
    }
}

```

```

        .add(new
AttributeDefinition().withAttributeName(sortKeyName).withAttributeType(sortKeyType));
    }

    CreateTableRequest request = new
CreateTableRequest().withTableName(tableName).withKeySchema(keySchema)
        .withProvisionedThroughput(new
ProvisionedThroughput().withReadCapacityUnits(readCapacityUnits)
        .withWriteCapacityUnits(writeCapacityUnits));

    // If this is the Reply table, define a local secondary index
    if (replyTableName.equals(tableName)) {

        attributeDefinitions
            .add(new
AttributeDefinition().withAttributeName("PostedBy").withAttributeType("S"));

        ArrayList<LocalSecondaryIndex> localSecondaryIndexes = new
ArrayList<LocalSecondaryIndex>();
        localSecondaryIndexes.add(new
LocalSecondaryIndex().withIndexName("PostedBy-Index")
            .withKeySchema(new
KeySchemaElement().withAttributeName(partitionKeyName).withKeyType(KeyType.HASH), // Partition

                // key
                new
KeySchemaElement().withAttributeName("PostedBy").withKeyType(KeyType.RANGE)) // Sort

            // key
            .withProjection(new
Projection().withProjectionType(ProjectionType.KEYS_ONLY)));

        request.setLocalSecondaryIndexes(localSecondaryIndexes);
    }

    request.setAttributeDefinitions(attributeDefinitions);

    System.out.println("Issuing CreateTable request for " + tableName);
    Table table = dynamoDB.createTable(request);
    System.out.println("Waiting for " + tableName + " to be created...this may take
a while...");
    table.waitForActive();

}

catch (Exception e) {
    System.err.println("CreateTable request failed for " + tableName);
    System.err.println(e.getMessage());
}
}

private static void loadSampleProducts(String tableName) {

    Table table = dynamoDB.getTable(tableName);

    try {

        System.out.println("Adding data to " + tableName);

        Item item = new Item().withPrimaryKey("Id", 101).withString("Title", "Book 101
Title")
            .withString("ISBN", "111-1111111111")
            .withStringSet("Authors", new
HashSet<String>(Arrays.asList("Author1"))).withNumber("Price", 2)
            .withString("Dimensions", "8.5 x 11.0 x 0.5").withNumber("PageCount", 500)
            .withBoolean("InPublication", true).withString("ProductCategory", "Book");
    }
}
```

```

        table.putItem(item);

        item = new Item().withPrimaryKey("Id", 102).withString("Title", "Book 102
Title")
            .withString("ISBN", "222-222222222")
            .withStringSet("Authors", new HashSet<String>(Arrays.asList("Author1",
"Author2")))
            .withNumber("Price", 20).withString("Dimensions", "8.5 x 11.0 x
0.8").withNumber("PageCount", 600)
            .withBoolean("InPublication", true).withString("ProductCategory", "Book");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", 103).withString("Title", "Book 103
Title")
            .withString("ISBN", "333-333333333")
            .withStringSet("Authors", new HashSet<String>(Arrays.asList("Author1",
"Author2")))
            // Intentional. Later we'll run Scan to find price error. Find
            // items > 1000 in price.
            .withNumber("Price", 2000).withString("Dimensions", "8.5 x 11.0 x
1.5").withNumber("PageCount", 600)
            .withBoolean("InPublication", false).withString("ProductCategory", "Book");
        table.putItem(item);

        // Add bikes.

        item = new Item().withPrimaryKey("Id", 201).withString("Title", "18-Bike-201")
            // Size, followed by some title.
            .withString("Description", "201 Description").withString("BicycleType",
"Road")
            .withString("Brand", "Mountain A")
            // Trek, Specialized.
            .withNumber("Price", 100).withStringSet("Color", new
HashSet<String>(Arrays.asList("Red", "Black")))
            .withString("ProductCategory", "Bicycle");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", 202).withString("Title", "21-Bike-202")
            .withString("Description", "202 Description").withString("BicycleType",
"Road")
            .withString("Brand", "Brand-Company A").withNumber("Price", 200)
            .withStringSet("Color", new HashSet<String>(Arrays.asList("Green",
"Black")))
            .withString("ProductCategory", "Bicycle");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", 203).withString("Title", "19-Bike-203")
            .withString("Description", "203 Description").withString("BicycleType",
"Road")
            .withString("Brand", "Brand-Company B").withNumber("Price", 300)
            .withStringSet("Color", new HashSet<String>(Arrays.asList("Red", "Green",
"Black")))
            .withString("ProductCategory", "Bicycle");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", 204).withString("Title", "18-Bike-204")
            .withString("Description", "204 Description").withString("BicycleType",
"Mountain")
            .withString("Brand", "Brand-Company B").withNumber("Price", 400)
            .withStringSet("Color", new HashSet<String>(Arrays.asList("Red")))
            .withString("ProductCategory", "Bicycle");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", 205).withString("Title", "20-Bike-205")
            .withString("Description", "205 Description").withString("BicycleType",
"Hybrid")
    
```

```

        .withString("Brand", "Brand-Company C").withNumber("Price", 500)
        .withStringSet("Color", new HashSet<String>(Arrays.asList("Red", "Black")));
        .withString("ProductCategory", "Bicycle");
    table.putItem(item);

}

catch (Exception e) {
    System.err.println("Failed to create item in " + tableName);
    System.err.println(e.getMessage());
}

}

private static void loadSampleForums(String tableName) {

    Table table = dynamoDB.getTable(tableName);

    try {

        System.out.println("Adding data to " + tableName);

        Item item = new Item().withPrimaryKey("Name", "Amazon DynamoDB")
            .withString("Category", "Amazon Web Services").withNumber("Threads",
2).withNumber("Messages", 4)
            .withNumber("Views", 1000);
        table.putItem(item);

        item = new Item().withPrimaryKey("Name", "Amazon S3").withString("Category",
"Amazon Web Services")
            .withNumber("Threads", 0);
        table.putItem(item);

    }
    catch (Exception e) {
        System.err.println("Failed to create item in " + tableName);
        System.err.println(e.getMessage());
    }
}

private static void loadSampleThreads(String tableName) {
    try {
        long time1 = (new Date()).getTime() - (7 * 24 * 60 * 60 * 1000); // 7
        // days
        // ago
        long time2 = (new Date()).getTime() - (14 * 24 * 60 * 60 * 1000); // 14
        // days
        // ago
        long time3 = (new Date()).getTime() - (21 * 24 * 60 * 60 * 1000); // 21
        // days
        // ago

        Date date1 = new Date();
        date1.setTime(time1);

        Date date2 = new Date();
        date2.setTime(time2);

        Date date3 = new Date();
        date3.setTime(time3);

        dateFormatter.setTimeZone(TimeZone.getTimeZone("UTC"));

        Table table = dynamoDB.getTable(tableName);

        System.out.println("Adding data to " + tableName);
    }
}

```

```

        Item item = new Item().withPrimaryKey("ForumName", "Amazon DynamoDB")
            .withString("Subject", "DynamoDB Thread 1").withString("Message", "DynamoDB
thread 1 message")
            .withString("LastPostedBy", "User A").withString("LastPostedDateTime",
dateFormatter.format(date2))
            .withNumber("Views", 0).withNumber("Replies", 0).withNumber("Answered", 0)
            .withStringSet("Tags", new HashSet<String>(Arrays.asList("index",
"primarykey", "table")));
        table.putItem(item);

        item = new Item().withPrimaryKey("ForumName", "Amazon
DynamoDB").withString("Subject", "DynamoDB Thread 2")
            .withString("Message", "DynamoDB thread 2
message").withString("LastPostedBy", "User A")
            .withString("LastPostedDateTime",
dateFormatter.format(date3)).withNumber("Views", 0)
            .withNumber("Replies", 0).withNumber("Answered", 0)
            .withStringSet("Tags", new HashSet<String>(Arrays.asList("index",
"partitionkey", "sortkey")));
        table.putItem(item);

        item = new Item().withPrimaryKey("ForumName", "Amazon
S3").withString("Subject", "S3 Thread 1")
            .withString("Message", "S3 Thread 3 message").withString("LastPostedBy",
"User A")
            .withString("LastPostedDateTime",
dateFormatter.format(date1)).withNumber("Views", 0)
            .withNumber("Replies", 0).withNumber("Answered", 0)
            .withStringSet("Tags", new HashSet<String>(Arrays.asList("largeobjects",
"multipart upload")));
        table.putItem(item);

    }
    catch (Exception e) {
        System.err.println("Failed to create item in " + tableName);
        System.err.println(e.getMessage());
    }
}

private static void loadSampleReplies(String tableName) {
    try {
        // 1 day ago
        long time0 = (new Date()).getTime() - (1 * 24 * 60 * 60 * 1000);
        // 7 days ago
        long time1 = (new Date()).getTime() - (7 * 24 * 60 * 60 * 1000);
        // 14 days ago
        long time2 = (new Date()).getTime() - (14 * 24 * 60 * 60 * 1000);
        // 21 days ago
        long time3 = (new Date()).getTime() - (21 * 24 * 60 * 60 * 1000);

        Date date0 = new Date();
        date0.setTime(time0);

        Date date1 = new Date();
        date1.setTime(time1);

        Date date2 = new Date();
        date2.setTime(time2);

        Date date3 = new Date();
        date3.setTime(time3);

        dateFormatter.setTimeZone(TimeZone.getTimeZone("UTC"));

        Table table = dynamoDB.getTable(tableName);
    }
}

```

```

        System.out.println("Adding data to " + tableName);

        // Add threads.

        Item item = new Item().withPrimaryKey("Id", "Amazon DynamoDB#DynamoDB Thread
1")
            .withString("ReplyDateTime", (dateFormatter.format(date3)))
            .withString("Message", "DynamoDB Thread 1 Reply 1
text").withString("PostedBy", "User A");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", "Amazon DynamoDB#DynamoDB Thread 1")
            .withString("ReplyDateTime", dateFormatter.format(date2))
            .withString("Message", "DynamoDB Thread 1 Reply 2
text").withString("PostedBy", "User B");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", "Amazon DynamoDB#DynamoDB Thread 2")
            .withString("ReplyDateTime", dateFormatter.format(date1))
            .withString("Message", "DynamoDB Thread 2 Reply 1
text").withString("PostedBy", "User A");
        table.putItem(item);

        item = new Item().withPrimaryKey("Id", "Amazon DynamoDB#DynamoDB Thread 2")
            .withString("ReplyDateTime", dateFormatter.format(date0))
            .withString("Message", "DynamoDB Thread 2 Reply 2
text").withString("PostedBy", "User A");
        table.putItem(item);

    }
    catch (Exception e) {
        System.err.println("Failed to create item in " + tableName);
        System.err.println(e.getMessage());
    }
}
}

```

## Creating example tables and uploading data using the AWS SDK for .NET

The following C# code example creates tables and uploads data to the tables. The resulting table structure and data is shown in [Creating tables and loading data for code examples in DynamoDB \(p. 269\)](#). For step-by-step instructions to run this code in Visual Studio, see [.NET code examples \(p. 276\)](#).

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */

```

```

using System;
using System.Collections.Generic;
using Amazon.DynamoDBv2;
using Amazon.DynamoDBv2.DocumentModel;
using Amazon.DynamoDBv2.Model;
using Amazon.Runtime;
using Amazon.SecurityToken;

namespace com.amazonaws.codesamples
{
    class CreateTablesLoadData
    {
        private static AmazonDynamoDBClient client = new AmazonDynamoDBClient();

        static void Main(string[] args)
        {
            try
            {
                //DeleteAllTables(client);
                DeleteTable("ProductCatalog");
                DeleteTable("Forum");
                DeleteTable("Thread");
                DeleteTable("Reply");

                // Create tables (using the AWS SDK for .NET low-level API).
                CreateTableProductCatalog();
                CreateTableForum();
                CreateTableThread(); // ForumTitle, Subject */
                CreateTableReply();

                // Load data (using the .NET SDK document API)
                LoadSampleProducts();
                LoadSampleForums();
                LoadSampleThreads();
                LoadSampleReplies();
                Console.WriteLine("Sample complete!");
                Console.WriteLine("Press ENTER to continue");
                Console.ReadLine();
            }
            catch (AmazonServiceException e) { Console.WriteLine(e.Message); }
            catch (Exception e) { Console.WriteLine(e.Message); }
        }

        private static void DeleteTable(string tableName)
        {
            try
            {
                var deleteTableResponse = client.DeleteTable(new DeleteTableRequest()
                {
                    TableName = tableName
                });
                WaitTillTableDeleted(client, tableName, deleteTableResponse);
            }
            catch (ResourceNotFoundException)
            {
                // There is no such table.
            }
        }

        private static void CreateTableProductCatalog()
        {
            string tableName = "ProductCatalog";

            var response = client.CreateTable(new CreateTableRequest()
            {
                TableName = tableName,

```

```

        AttributeDefinitions = new List<AttributeDefinition>()
        {
            new AttributeDefinition
            {
                AttributeName = "Id",
                AttributeType = "N"
            }
        },
        KeySchema = new List<KeySchemaElement>()
        {
            new KeySchemaElement
            {
                AttributeName = "Id",
                KeyType = "HASH"
            }
        },
        ProvisionedThroughput = new ProvisionedThroughput
        {
            ReadCapacityUnits = 10,
            WriteCapacityUnits = 5
        }
    });
}

WaitTillTableCreated(client, tableName, response);
}

private static void CreateTableForum()
{
    string tableName = "Forum";

    var response = client.CreateTable(new CreateTableRequest
    {
        TableName = tableName,
        AttributeDefinitions = new List<AttributeDefinition>()
        {
            new AttributeDefinition
            {
                AttributeName = "Name",
                AttributeType = "S"
            }
        },
        KeySchema = new List<KeySchemaElement>()
        {
            new KeySchemaElement
            {
                AttributeName = "Name", // forum Title
                KeyType = "HASH"
            }
        },
        ProvisionedThroughput = new ProvisionedThroughput
        {
            ReadCapacityUnits = 10,
            WriteCapacityUnits = 5
        }
    });

    WaitTillTableCreated(client, tableName, response);
}

private static void CreateTableThread()
{
    string tableName = "Thread";

    var response = client.CreateTable(new CreateTableRequest
    {
        TableName = tableName,

```

```

        AttributeDefinitions = new List<AttributeDefinition>()
        {
            new AttributeDefinition
            {
                AttributeName = "ForumName", // Hash attribute
                AttributeType = "S"
            },
            new AttributeDefinition
            {
                AttributeName = "Subject",
                AttributeType = "S"
            }
        },
        KeySchema = new List<KeySchemaElement>()
        {
            new KeySchemaElement
            {
                AttributeName = "ForumName", // Hash attribute
                KeyType = "HASH"
            },
            new KeySchemaElement
            {
                AttributeName = "Subject", // Range attribute
                KeyType = "RANGE"
            }
        },
        ProvisionedThroughput = new ProvisionedThroughput
        {
            ReadCapacityUnits = 10,
            WriteCapacityUnits = 5
        }
    });

    WaitTillTableCreated(client, tableName, response);
}

private static void CreateTableReply()
{
    string tableName = "Reply";
    var response = client.CreateTable(new CreateTableRequest
    {
        TableName = tableName,
        AttributeDefinitions = new List<AttributeDefinition>()
        {
            new AttributeDefinition
            {
                AttributeName = "Id",
                AttributeType = "S"
            },
            new AttributeDefinition
            {
                AttributeName = "ReplyDateTime",
                AttributeType = "S"
            },
            new AttributeDefinition
            {
                AttributeName = "PostedBy",
                AttributeType = "S"
            }
        },
        KeySchema = new List<KeySchemaElement>()
        {
            new KeySchemaElement()
            {
                AttributeName = "Id",
                KeyType = "HASH"
            }
        }
    });
}

```

```

        },
        new KeySchemaElement()
        {
            AttributeName = "ReplyDateTime",
            KeyType = "RANGE"
        }
    },
    LocalSecondaryIndexes = new List<LocalSecondaryIndex>()
    {
        new LocalSecondaryIndex()
        {
            IndexName = "PostedBy_index",

            KeySchema = new List<KeySchemaElement>() {
                new KeySchemaElement() {
                    AttributeName = "Id", KeyType = "HASH"
                },
                new KeySchemaElement() {
                    AttributeName = "PostedBy", KeyType = "RANGE"
                }
            },
            Projection = new Projection() {
                ProjectionType = ProjectionType.KEYS_ONLY
            }
        }
    },
    ProvisionedThroughput = new ProvisionedThroughput
    {
        ReadCapacityUnits = 10,
        WriteCapacityUnits = 5
    }
});
WaitTillTableCreated(client, tableName, response);
}

private static void WaitTillTableCreated(AmazonDynamoDBClient client, string
tableName,
                                         CreateTableResponse response)
{
    var tableDescription = response.TableDescription;
    string status = tableDescription.TableStatus;

    Console.WriteLine(tableName + " - " + status);

    // Let us wait until table is created. Call DescribeTable.
    while (status != "ACTIVE")
    {
        System.Threading.Thread.Sleep(5000); // Wait 5 seconds.
        try
        {
            var res = client.DescribeTable(new DescribeTableRequest
            {
                TableName = tableName
            });
            Console.WriteLine("Table name: {0}, status: {1}", res.Table.TableName,
                             res.Table.TableStatus);
            status = res.Table.TableStatus;
        }
        // Try-catch to handle potential eventual-consistency issue.
        catch (ResourceNotFoundException)
        {
        }
    }
}
}

```

```

        private static void WaitTillTableDeleted(AmazonDynamoDBClient client, string
tableName,
                                         DeleteTableResponse response)
{
    var tableDescription = response.TableDescription;

    string status = tableDescription.TableStatus;

    Console.WriteLine(tableName + " - " + status);

    // Let us wait until table is created. Call DescribeTable
    try
    {
        while (status == "DELETING")
        {
            System.Threading.Thread.Sleep(5000); // wait 5 seconds

            var res = client.DescribeTable(new DescribeTableRequest
            {
                TableName = tableName
            });
            Console.WriteLine("Table name: {0}, status: {1}", res.Table.TableName,
                             res.Table.TableStatus);
            status = res.Table.TableStatus;
        }
    }
    catch (ResourceNotFoundException)
    {
        // Table deleted.
    }
}

private static void LoadSampleProducts()
{
    Table productCatalogTable = Table.LoadTable(client, "ProductCatalog");
    // ***** Add Books *****
    var book1 = new Document();
    book1["Id"] = 101;
    book1["Title"] = "Book 101 Title";
    book1["ISBN"] = "111-1111111111";
    book1["Authors"] = new List<string> { "Author 1" };
    book1["Price"] = -2; // *** Intentional value. Later used to illustrate scan.
    book1["Dimensions"] = "8.5 x 11.0 x 0.5";
    book1["PageCount"] = 500;
    book1["InPublication"] = true;
    book1["ProductCategory"] = "Book";
    productCatalogTable.PutItem(book1);

    var book2 = new Document();

    book2["Id"] = 102;
    book2["Title"] = "Book 102 Title";
    book2["ISBN"] = "222-2222222222";
    book2["Authors"] = new List<string> { "Author 1", "Author 2" }; ;
    book2["Price"] = 20;
    book2["Dimensions"] = "8.5 x 11.0 x 0.8";
    book2["PageCount"] = 600;
    book2["InPublication"] = true;
    book2["ProductCategory"] = "Book";
    productCatalogTable.PutItem(book2);

    var book3 = new Document();
    book3["Id"] = 103;
    book3["Title"] = "Book 103 Title";
    book3["ISBN"] = "333-3333333333";
}

```

```

book3["Authors"] = new List<string> { "Author 1", "Author2", "Author 3" }; ;
book3["Price"] = 2000;
book3["Dimensions"] = "8.5 x 11.0 x 1.5";
book3["PageCount"] = 700;
book3["InPublication"] = false;
book3["ProductCategory"] = "Book";
productCatalogTable.PutItem(book3);

// ***** Add bikes. *****
var bicycle1 = new Document();
bicycle1["Id"] = 201;
bicycle1["Title"] = "18-Bike 201"; // size, followed by some title.
bicycle1["Description"] = "201 description";
bicycle1["BicycleType"] = "Road";
bicycle1["Brand"] = "Brand-Company A"; // Trek, Specialized.
bicycle1["Price"] = 100;
bicycle1["Color"] = new List<string> { "Red", "Black" };
bicycle1["ProductCategory"] = "Bike";
productCatalogTable.PutItem(bicycle1);

var bicycle2 = new Document();
bicycle2["Id"] = 202;
bicycle2["Title"] = "21-Bike 202Brand-Company A";
bicycle2["Description"] = "202 description";
bicycle2["BicycleType"] = "Road";
bicycle2["Brand"] = "";
bicycle2["Price"] = 200;
bicycle2["Color"] = new List<string> { "Green", "Black" };
bicycle2["ProductCategory"] = "Bicycle";
productCatalogTable.PutItem(bicycle2);

var bicycle3 = new Document();
bicycle3["Id"] = 203;
bicycle3["Title"] = "19-Bike 203";
bicycle3["Description"] = "203 description";
bicycle3["BicycleType"] = "Road";
bicycle3["Brand"] = "Brand-Company B";
bicycle3["Price"] = 300;
bicycle3["Color"] = new List<string> { "Red", "Green", "Black" };
bicycle3["ProductCategory"] = "Bike";
productCatalogTable.PutItem(bicycle3);

var bicycle4 = new Document();
bicycle4["Id"] = 204;
bicycle4["Title"] = "18-Bike 204";
bicycle4["Description"] = "204 description";
bicycle4["BicycleType"] = "Mountain";
bicycle4["Brand"] = "Brand-Company B";
bicycle4["Price"] = 400;
bicycle4["Color"] = new List<string> { "Red" };
bicycle4["ProductCategory"] = "Bike";
productCatalogTable.PutItem(bicycle4);

var bicycle5 = new Document();
bicycle5["Id"] = 205;
bicycle5["Title"] = "20-Title 205";
bicycle5["Description"] = "205 description";
bicycle5["BicycleType"] = "Hybrid";
bicycle5["Brand"] = "Brand-Company C";
bicycle5["Price"] = 500;
bicycle5["Color"] = new List<string> { "Red", "Black" };
bicycle5["ProductCategory"] = "Bike";
productCatalogTable.PutItem(bicycle5);
}

private static void LoadSampleForums()

```

```

    {
        Table forumTable = Table.LoadTable(client, "Forum");

        var forum1 = new Document();
        forum1["Name"] = "Amazon DynamoDB"; // PK
        forum1["Category"] = "Amazon Web Services";
        forum1["Threads"] = 2;
        forum1["Messages"] = 4;
        forum1["Views"] = 1000;

        forumTable.PutItem(forum1);

        var forum2 = new Document();
        forum2["Name"] = "Amazon S3"; // PK
        forum2["Category"] = "Amazon Web Services";
        forum2["Threads"] = 1;

        forumTable.PutItem(forum2);
    }

    private static void LoadSampleThreads()
    {
        Table threadTable = Table.LoadTable(client, "Thread");

        // Thread 1.
        var thread1 = new Document();
        thread1["ForumName"] = "Amazon DynamoDB"; // Hash attribute.
        thread1["Subject"] = "DynamoDB Thread 1"; // Range attribute.
        thread1["Message"] = "DynamoDB thread 1 message text";
        thread1["LastPostedBy"] = "User A";
        thread1["LastPostedDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(14, 0, 0));
        thread1["Views"] = 0;
        thread1["Replies"] = 0;
        thread1["Answered"] = false;
        thread1["Tags"] = new List<string> { "index", "primarykey", "table" };

        threadTable.PutItem(thread1);

        // Thread 2.
        var thread2 = new Document();
        thread2["ForumName"] = "Amazon DynamoDB"; // Hash attribute.
        thread2["Subject"] = "DynamoDB Thread 2"; // Range attribute.
        thread2["Message"] = "DynamoDB thread 2 message text";
        thread2["LastPostedBy"] = "User A";
        thread2["LastPostedDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(21, 0, 0));
        thread2["Views"] = 0;
        thread2["Replies"] = 0;
        thread2["Answered"] = false;
        thread2["Tags"] = new List<string> { "index", "primarykey", "rangekey" };

        threadTable.PutItem(thread2);

        // Thread 3.
        var thread3 = new Document();
        thread3["ForumName"] = "Amazon S3"; // Hash attribute.
        thread3["Subject"] = "S3 Thread 1"; // Range attribute.
        thread3["Message"] = "S3 thread 3 message text";
        thread3["LastPostedBy"] = "User A";
        thread3["LastPostedDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(7, 0, 0));
        thread3["Views"] = 0;
        thread3["Replies"] = 0;
        thread3["Answered"] = false;
        thread3["Tags"] = new List<string> { "largeobjects", "multipart upload" };
    }

```

```

        threadTable.PutItem(thread3);
    }

    private static void LoadSampleReplies()
    {
        Table replyTable = Table.LoadTable(client, "Reply");

        // Reply 1 - thread 1.
        var thread1Reply1 = new Document();
        thread1Reply1["Id"] = "Amazon DynamoDB#DynamoDB Thread 1"; // Hash attribute.
        thread1Reply1["ReplyDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(21, 0, 0)); // Range attribute.
        thread1Reply1["Message"] = "DynamoDB Thread 1 Reply 1 text";
        thread1Reply1["PostedBy"] = "User A";

        replyTable.PutItem(thread1Reply1);

        // Reply 2 - thread 1.
        var thread1Reply2 = new Document();
        thread1Reply2["Id"] = "Amazon DynamoDB#DynamoDB Thread 1"; // Hash attribute.
        thread1Reply2["ReplyDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(14, 0, 0)); // Range attribute.
        thread1Reply2["Message"] = "DynamoDB Thread 1 Reply 2 text";
        thread1Reply2["PostedBy"] = "User B";

        replyTable.PutItem(thread1Reply2);

        // Reply 3 - thread 1.
        var thread1Reply3 = new Document();
        thread1Reply3["Id"] = "Amazon DynamoDB#DynamoDB Thread 1"; // Hash attribute.
        thread1Reply3["ReplyDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(7, 0, 0, 0)); // Range attribute.
        thread1Reply3["Message"] = "DynamoDB Thread 1 Reply 3 text";
        thread1Reply3["PostedBy"] = "User B";

        replyTable.PutItem(thread1Reply3);

        // Reply 1 - thread 2.
        var thread2Reply1 = new Document();
        thread2Reply1["Id"] = "Amazon DynamoDB#DynamoDB Thread 2"; // Hash attribute.
        thread2Reply1["ReplyDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(7, 0, 0, 0)); // Range attribute.
        thread2Reply1["Message"] = "DynamoDB Thread 2 Reply 1 text";
        thread2Reply1["PostedBy"] = "User A";

        replyTable.PutItem(thread2Reply1);

        // Reply 2 - thread 2.
        var thread2Reply2 = new Document();
        thread2Reply2["Id"] = "Amazon DynamoDB#DynamoDB Thread 2"; // Hash attribute.
        thread2Reply2["ReplyDateTime"] = DateTime.UtcNow.Subtract(new TimeSpan(1, 0, 0, 0)); // Range attribute.
        thread2Reply2["Message"] = "DynamoDB Thread 2 Reply 2 text";
        thread2Reply2["PostedBy"] = "User A";

        replyTable.PutItem(thread2Reply2);
    }
}
}

```

# DynamoDB example application using the AWS SDK for Python (Boto): Tic-tac-toe

## Topics

- [Step 1: Deploy and test locally \(p. 1281\)](#)
- [Step 2: Examine the data model and implementation details \(p. 1285\)](#)
- [Step 3: Deploy in production using the DynamoDB service \(p. 1293\)](#)
- [Step 4: Clean up resources \(p. 1299\)](#)

The Tic-Tac-Toe game is an example web application built on Amazon DynamoDB. The application uses the AWS SDK for Python (Boto) to make the necessary DynamoDB calls to store game data in a DynamoDB table, and the Python web framework Flask to illustrate end-to-end application development in DynamoDB, including how to model data. It also demonstrates best practices when it comes to modeling data in DynamoDB, including the table you create for the game application, the primary key you define, additional indexes you need based on your query requirements, and the use of concatenated value attributes.

You play the Tic-Tac-Toe application on the web as follows:

1. You log in to the application home page.
2. You then invite another user to play the game as your opponent.

Until another user accepts your invitation, the game status remains as `PENDING`. After an opponent accepts the invite, the game status changes to `IN_PROGRESS`.

3. The game begins after the opponent logs in and accepts the invite.
4. The application stores all game moves and status information in a DynamoDB table.
5. The game ends with a win or a draw, which sets the game status to `FINISHED`.

The end-to-end application building exercise is described in steps:

- **[Step 1: Deploy and test locally \(p. 1281\)](#)** – In this section, you download, deploy, and test the application on your local computer. You will create the required tables in the downloadable version of DynamoDB.
- **[Step 2: Examine the data model and implementation details \(p. 1285\)](#)** – This section first describes in detail the data model, including the indexes and the use of the concatenated value attribute. Then the section explains how the application works.
- **[Step 3: Deploy in production using the DynamoDB service \(p. 1293\)](#)** – This section focuses on deployment considerations in production. In this step, you create a table using the Amazon DynamoDB service and deploy the application using AWS Elastic Beanstalk. When you have the application in production, you also grant appropriate permissions so the application can access the DynamoDB table. The instructions in this section walk you through the end-to-end production deployment.
- **[Step 4: Clean up resources \(p. 1299\)](#)** – This section highlights areas that are not covered by this example. The section also provides steps for you to remove the AWS resources you created in the preceding steps so that you avoid incurring any charges.

## Step 1: Deploy and test locally

### Topics

- [1.1: Download and install the required packages \(p. 1282\)](#)

- [1.2: Test the game application \(p. 1282\)](#)

In this step you download, deploy, and test the Tic-Tac-Toe game application on your local computer. Instead of using the Amazon DynamoDB web service, you will download DynamoDB to your computer, and create the required table there.

## 1.1: Download and install the required packages

You will need the following to test this application locally:

- Python
- Flask (a microframework for Python)
- AWS SDK for Python (Boto)
- DynamoDB running on your computer
- Git

To get these tools, do the following:

1. Install Python. For step-by-step instructions, see [Download Python](#).

The Tic-Tac-Toe application has been tested using Python version 2.7.

2. Install Flask and AWS SDK for Python (Boto) using the Python Package Installer (PIP):

- Install PIP.

For instructions, see [Install PIP](#). On the installation page, choose the **get-pip.py** link, and then save the file. Then open a command terminal as an administrator, and enter the following at the command prompt.

```
python.exe get-pip.py
```

On Linux, you don't specify the .exe extension. You only specify `python get-pip.py`.

- Using PIP, install the Flask and Boto packages using the following code.

```
pip install Flask
pip install boto
pip install configparser
```

3. Download DynamoDB to your computer. For instructions on how to run it, see [Setting up DynamoDB local \(downloadable version\) \(p. 51\)](#).

4. Download the Tic-Tac-Toe application:

- a. Install Git. For instructions, see [git downloads](#).
- b. Run the following code to download the application.

```
git clone https://github.com/awslabs/dynamodb-tictactoe-example-app.git
```

## 1.2: Test the game application

To test the Tic-Tac-Toe application, you need to run DynamoDB locally on your computer.

### To run the tic-tac-toe application

1. Start DynamoDB.

2. Start the web server for the Tic-Tac-Toe application.

To do so, open a command terminal, navigate to the folder where you downloaded the Tic-Tac-Toe application, and run the application locally using the following code.


```
python.exe application.py --mode local --serverPort 5000 --port 8000
```

On Linux, you don't specify the .exe extension.

3. Open your web browser, and enter the following.

```
http://localhost:5000/
```

The browser shows the home page.




4. Enter **user1** in the **Log in** box to log in as user1.

**Note**

This example application does not perform any user authentication. The user ID is only used to identify players. If two players log in with the same alias, the application works as if you are playing in two different browsers.

5. If this is your first time playing the game, a page appears requesting you to create the required table (Games) in DynamoDB. Choose **CREATE TABLE**.



6. Choose **CREATE** to create the first tic-tac-toe game.
7. Enter **user2** in the **Choose an Opponent** box, and choose **Create Game!**



Doing this creates the game by adding an item in the Games table. It sets the game status to PENDING.


8. Open another browser window, and enter the following.

```
http://localhost:5000/
```


The browser passes information through cookies, so you should use incognito mode or private browsing so that your cookies don't carry over.

9. Log in as user2.

A page appears that shows a pending invitation from user1.



10. Choose **accept** to accept the invitation.



The game page appears with an empty tic-tac-toe grid. The page also shows relevant game information such as the game ID, whose turn it is, and game status.

#### 11. Play the game.

For each user move, the web service sends a request to DynamoDB to conditionally update the game item in the Games table. For example, the conditions ensure that the move is valid, the square that the user chose is available, and that it was the turn of the user who made the move. For a valid move, the update operation adds a new attribute corresponding to the selection on the board. The update operation also sets the value of the existing attribute to the user who can make the next move.

On the game page, the application makes asynchronous JavaScript calls every second, for up to 5 minutes, to check if the game state in DynamoDB has changed. If it has, the application updates the page with new information. After 5 minutes, the application stops making the requests, and you need to refresh the page to get updated information.

## Step 2: Examine the data model and implementation details

### Topics

- [2.1: Basic data model \(p. 1285\)](#)
- [2.2: Application in action \(code walkthrough\) \(p. 1288\)](#)

## 2.1: Basic data model

This example application highlights the following DynamoDB data model concepts:

- **Table** – In DynamoDB, a table is a collection of items (that is, records), and each item is a collection of name-value pairs called attributes.

In this Tic-Tac-Toe example, the application stores all game data in a table, Games. The application creates one item in the table per game and stores all game data as attributes. A tic-tac-toe game can have up to nine moves. Because DynamoDB tables do not have a schema in cases where only the primary key is the required attribute, the application can store varying number of attributes per game item.

The Games table has a simple primary key made of one attribute, GameId, of string type. The application assigns a unique ID to each game. For more information on DynamoDB primary keys, see [Primary key \(p. 6\)](#).

When a user initiates a tic-tac-toe game by inviting another user to play, the application creates a new item in the Games table with attributes storing game metadata, such as the following:

- HostId, the user who initiated the game.
- Opponent, the user who was invited to play.
- The user whose turn it is to play. The user who initiated the game plays first.
- The user who uses the O symbol on the board. The user who initiates the games uses the O symbol.

In addition, the application creates a StatusDate concatenated attribute, marking the initial game state as PENDING. The following screenshot shows an example item as it appears in the DynamoDB console:

Attribute	Type	Value
GameId (Hash Key)	String	"6ffd7f5-e293-4b4a-bacf-6ddde49ef0ae"
HostId	String	"user1"
O	String	"user1"
Opponent	String	"user2"
StatusDate	String	"PENDING_2014-07-06 21:28:02.354807"
Turn	String	"user1"

As the game progresses, the application adds one attribute to the table for each game move. The attribute name is the board position, for example TopLeft or BottomRight. For example, a move might have a TopLeft attribute with the value O, a TopRight attribute with the value O, and a BottomRight attribute with the value X. The attribute value is either O or X, depending on which user made the move. For example, consider the following board.



- Concatenated value attributes** – The StatusDate attribute illustrates a concatenated value attribute. In this approach, instead of creating separate attributes to store game status (PENDING, IN\_PROGRESS, and FINISHED) and date (when the last move was made), you combine them as single attribute, for example IN\_PROGRESS\_2014-04-30 10:20:32.

The application then uses the StatusDate attribute in creating secondary indexes by specifying StatusDate as a sort key for the index. The benefit of using the StatusDate concatenated value attribute is further illustrated in the indexes discussed next.

- Global secondary indexes** – You can use the table's primary key, GameId, to efficiently query the table to find a game item. To query the table on attributes other than the primary key attributes, DynamoDB supports the creation of secondary indexes. In this example application, you build the following two secondary indexes:

Local Secondary Indexes															
Index Name	Hash Key	Range Key	Projected Attributes	Index Size (Bytes)*	Item Count*										
This table has no local secondary indexes.															
Global Secondary Indexes															
Index Name	Hash Key	Range Key	Projected Attributes	Status	Read Capacity Units	Write Capacity Units	Last Decrease Time	Last Increase Time	Index Size (Bytes)*	Item Count*					
hostStatusDate	HostId (String)	StatusDate (String)	All	Active	20	20		Sat May 31 10:35:42 GMT-700 2014	20305	125					
oppStatusDate	Opponent (String)	StatusDate (String)	All	Active	20	20		Sat May 31 10:35:42 GMT-700 2014	20305	125					

- HostId-StatusDate-index.** This index has HostId as a partition key and StatusDate as a sort key. You can use this index to query on HostId, for example to find games hosted by a particular user.
- OpponentId-StatusDate-index.** This index has OpponentId as a partition key and StatusDate as a sort key. You can use this index to query on Opponent, for example to find games where a particular user is the opponent.

These indexes are called global secondary indexes because the partition key in these indexes is not the same the partition key (GameId), used in the primary key of the table.

Note that both the indexes specify StatusDate as a sort key. Doing this enables the following:

- You can query using the `BEGINS_WITH` comparison operator. For example, you can find all games with the `IN_PROGRESS` attribute hosted by a particular user. In this case, the `BEGINS_WITH` operator checks for the `StatusDate` value that begins with `IN_PROGRESS`.
- DynamoDB stores the items in the index in sorted order, by sort key value. So if all status prefixes are the same (for example, `IN_PROGRESS`), the ISO format used for the date part will have items sorted from oldest to the newest. This approach enables certain queries to be performed efficiently, for example the following:
  - Retrieve up to 10 of the most recent `IN_PROGRESS` games hosted by the user who is logged in. For this query, you specify the `HostId-StatusDate-index` index.
  - Retrieve up to 10 of the most recent `IN_PROGRESS` games where the user logged in is the opponent. For this query, you specify the `OpponentId-StatusDate-index` index.

For more information about secondary indexes, see [Improving data access with secondary indexes \(p. 497\)](#).

## 2.2: Application in action (code walkthrough)

This application has two main pages:

- **Home page** – This page provides the user a simple login, a **CREATE** button to create a new tic-tac-toe game, a list of games in progress, game history, and any active pending game invitations.

The home page is not refreshed automatically; you must refresh the page to refresh the lists.


- **Game page** – This page shows the tic-tac-toe grid where users play.

The application updates the game page automatically every second. The JavaScript in your browser calls the Python web server every second to query the Games table whether the game items in the table have changed. If they have, JavaScript triggers a page refresh so that the user sees the updated board.

Let us see in detail how the application works.

### Home page

After the user logs in, the application displays the following three lists of information.



- **Invitations** – This list shows up to the 10 most recent invitations from others that are pending acceptance by the user who is logged in. In the preceding screenshot, user1 has invitations from user5 and user2 pending.
- **Games in-progress** – This list shows up to the 10 most recent games that are in progress. These are games that the user is actively playing, which have the status IN\_PROGRESS. In the screenshot, user1 is actively playing a tic-tac-toe game with user3 and user4.
- **Recent history** – This list shows up to the 10 most recent games that the user finished, which have the status FINISHED. In game shown in the screenshot, user1 has previously played with user2. For each completed game, the list shows the game result.

In the code, the index function (in application.py) makes the following three calls to retrieve game status information:

```
inviteGames      = controller.getGameInvites(session["username"])
inProgressGames = controller.getGamesWithStatus(session["username"], "IN_PROGRESS")
finishedGames   = controller.getGamesWithStatus(session["username"], "FINISHED")
```

Each of these calls returns a list of items from DynamoDB that are wrapped by the Game objects. It is easy to extract data from these objects in the view. The index function passes these object lists to the view to render the HTML.

```
return render_template("index.html",
                      user=session["username"],
                      invites=inviteGames,
                      inprogress=inProgressGames,
                      finished=finishedGames)
```

The Tic-Tac-Toe application defines the Game class primarily to store game data retrieved from DynamoDB. These functions return lists of Game objects that enable you to isolate the rest of the application from code related to Amazon DynamoDB items. Thus, these functions help you decouple your application code from the details of the data store layer.

The architectural pattern described here is also referred as the model-view-controller (MVC) UI pattern. In this case, the Game object instances (representing data) are the model, and the HTML page is the view. The controller is divided into two files. The application.py file has the controller logic for the Flask framework, and the business logic is isolated in the gameController.py file. That is, the application stores everything that has to do with DynamoDB SDK in its own separate file in the dynamodb folder.

Let us review the three functions and how they query the Games table using global secondary indexes to retrieve relevant data.

### Using getGameInvites to get the list of pending game invitations

The getGameInvites function retrieves the list of the 10 most recent pending invitations. These games have been created by users, but the opponents have not accepted the game invitations. For these games, the status remains PENDING until the opponent accepts the invite. If the opponent declines the invite, the application removes the corresponding item from the table.

The function specifies the query as follows:

- It specifies the OpponentId-StatusDate-index index to use with the following index key values and comparison operators:
  - The partition key is OpponentId and takes the index key **user ID**.
  - The sort key is StatusDate and takes the comparison operator and index key value beginswith="PENDING\_".

You use the `OpponentId-StatusDate-index` index to retrieve games to which the logged-in user is invited—that is, where the logged-in user is the opponent.

- The query limits the result to 10 items.

```
gameInvitesIndex = self.cm.getGamesTable().query(  
    Opponent__eq=user,  
    StatusDate__beginswith="PENDING_",  
    index="OpponentId-StatusDate-index",  
    limit=10)
```

In the index, for each `OpponentId` (the partition key) DynamoDB keeps items sorted by `StatusDate` (the sort key). Therefore, the games that the query returns will be the 10 most recent games.

### Using `getGamesWithStatus` to get the list of games with a specific status

After an opponent accepts a game invitation, the game status changes to `IN_PROGRESS`. After the game completes, the status changes to `FINISHED`.

Queries to find games that are either in progress or finished are the same except for the different status value. Therefore, the application defines the `getGamesWithStatus` function, which takes the status value as a parameter.

```
inProgressGames = controller.getGamesWithStatus(session["username"], "IN_PROGRESS")  
finishedGames = controller.getGamesWithStatus(session["username"], "FINISHED")
```

The following section discusses in-progress games, but the same description also applies to finished games.

A list of in-progress games for a given user includes both the following:

- In-progress games hosted by the user
- In-progress games where the user is the opponent

The `getGamesWithStatus` function runs the following two queries, each time using the appropriate secondary index.

- The function queries the `Games` table using the `HostId-StatusDate-index` index. For the index, the query specifies primary key values—both the partition key (`HostId`) and sort key (`StatusDate`) values, along with comparison operators.

```
hostGamesInProgress = self.cm.getGamesTable().query(HostId__eq=user,  
    StatusDate__beginswith=status,  
    index="HostId-StatusDate-index",  
    limit=10)
```

Note the Python syntax for comparison operators:

- `HostId__eq=user` specifies the equality comparison operator.
- `StatusDate__beginswith=status` specifies the `BEGINS_WITH` comparison operator.
- The function queries the `Games` table using the `OpponentId-StatusDate-index` index.

```
oppGamesInProgress = self.cm.getGamesTable().query(Opponent__eq=user,  
    StatusDate__beginswith=status,  
    index="OpponentId-StatusDate-index",  
    limit=10)
```


```
limit=10)
```

- The function then combines the two lists, sorts, and for the first 0 to 10 items creates a list of the Game objects and returns the list to the calling function (that is, the index).

```
games = self.mergeQueries(hostGamesInProgress,  
                           oppGamesInProgress)  
return games
```

## Game page

The game page is where the user plays tic-tac-toe games. It shows the game grid along with game-relevant information. The following screenshot shows an example game in progress:



The application displays the game page in the following situations:

- The user creates a game inviting another user to play.

In this case, the page shows the user as host and the game status as PENDING, waiting for the opponent to accept.

- The user accepts one of the pending invitations on the home page.

In this case, the page shows the user as the opponent and game status as IN\_PROGRESS.

A user selection on the board generates a form POST request to the application. That is, Flask calls the `selectSquare` function (in `application.py`) with the HTML form data. This function, in turn, calls the `updateBoardAndTurn` function (in `gameController.py`) to update the game item as follows:

- It adds a new attribute specific to the move.
- It updates the `Turn` attribute value to the user whose turn is next.

```
controller.updateBoardAndTurn(item, value, session["username"])
```

The function returns true if the item update was successful; otherwise, it returns false. Note the following about the `updateBoardAndTurn` function:

- The function calls the `update_item` function of the SDK for Python to make a finite set of updates to an existing item. The function maps to the `UpdateItem` operation in DynamoDB. For more information, see [UpdateItem](#).

**Note**

The difference between the `UpdateItem` and `PutItem` operations is that `PutItem` replaces the entire item. For more information, see [PutItem](#).

For the `update_item` call, the code identifies the following:

- The primary key of the Games table (that is, `ItemId`).

```
key = { "GameId" : { "S" : gameId } }
```

- The new attribute to add, specific to the current user move, and its value (for example, `TopLeft="X"`).

```
attributeUpdates = {
    position : {
        "Action" : "PUT",
        "Value" : { "S" : representation }
    }
}
```

- Conditions that must be true for the update to take place:

- The game must be in progress. That is, the `StatusDate` attribute value must begin with `IN_PROGRESS`.
- The current turn must be a valid user turn as specified by the `Turn` attribute.
- The square that the user chose must be available. That is, the attribute corresponding to the square must not exist.

```
expectations = {"StatusDate" : {"AttributeValueList": [{"S" : "IN_PROGRESS_"}],
    "ComparisonOperator": "BEGINS_WITH"},
    "Turn" : {"Value" : {"S" : current_player}},
    position : {"Exists" : False}}
```

Now the function calls `update_item` to update the item.

```
self.cm.db.update_item("Games", key=key,
    attribute_updates=attributeUpdates,
    expected=expectations)
```

After the function returns, the `selectSquare` function calls `redirect`, as shown in the following example.

```
redirect("/game="+gameId)
```

This call causes the browser to refresh. As part of this refresh, the application checks to see if the game has ended in a win or draw. If it has, the application updates the game item accordingly.

## Step 3: Deploy in production using the DynamoDB service

### Topics

- [3.1: Create an IAM role for Amazon EC2 \(p. 1294\)](#)
- [3.2: Create the games table in Amazon DynamoDB \(p. 1294\)](#)
- [3.3: Bundle and deploy the tic-tac-toe application code \(p. 1294\)](#)
- [3.4: Set up the AWS Elastic Beanstalk environment \(p. 1295\)](#)

In the preceding sections, you deployed and tested the Tic-Tac-Toe application locally on your computer using DynamoDB Local. Now, you deploy the application in production as follows:

- Deploy the application using AWS Elastic Beanstalk, an easy-to-use service for deploying and scaling web applications and services. For more information, see [Deploying a flask application to AWS Elastic Beanstalk](#).

Elastic Beanstalk launches one or more Amazon Elastic Compute Cloud (Amazon EC2) instances, which you configure through Elastic Beanstalk, on which your Tic-Tac-Toe application will run.

- Using the Amazon DynamoDB service, create a Games table that exists on AWS rather than locally on your computer.

In addition, you also have to configure permissions. Any AWS resources you create, such as the Games table in DynamoDB, are private by default. Only the resource owner, that is the AWS account that created the Games table, can access this table. Thus, by default your Tic-Tac-Toe application cannot update the Games table.

To grant necessary permissions, you create an AWS Identity and Access Management (IAM) role and grant this role permissions to access the Games table. Your Amazon EC2 instance first assumes this role. In response, AWS returns temporary security credentials that the Amazon EC2 instance can use to update the Games table on behalf of the Tic-Tac-Toe application. When you configure your Elastic Beanstalk application, you specify the IAM role that the Amazon EC2 instance or instances can assume. For more information about IAM roles, see [IAM roles for amazon EC2](#) in the *Amazon EC2 User Guide for Linux Instances*.

### Note

Before you create Amazon EC2 instances for the Tic-Tac-Toe application, you must first decide the AWS Region where you want Elastic Beanstalk to create the instances. After you create the Elastic Beanstalk application, you provide the same Region name and endpoint in a configuration file. The Tic-Tac-Toe application uses information in this file to create the Games table and send subsequent requests in a specific AWS Region. Both the DynamoDB Games table and the Amazon EC2 instances that Elastic Beanstalk launches must be in the same Region. For a list of available Regions, see [Amazon DynamoDB](#) in the *Amazon Web Services General Reference*.

In summary, you do the following to deploy the Tic-Tac-Toe application in production:

1. Create an IAM role using the IAM service. You attach a policy to this role granting permissions for DynamoDB actions to access the Games table.
2. Bundle the Tic-Tac-Toe application code and a configuration file, and create a .zip file. You use this .zip file to give the Tic-Tac-Toe application code to Elastic Beanstalk to put on your servers. For more information about creating a bundle, see [Creating an application source bundle](#) in the *AWS Elastic Beanstalk Developer Guide*.

In the configuration file (`beanstalk.config`), you provide AWS Region and endpoint information. The Tic-Tac-Toe application uses this information to determine which DynamoDB Region to talk to.

3. Set up the Elastic Beanstalk environment. Elastic Beanstalk launches an Amazon EC2 instance or instances and deploys your Tic-Tac-Toe application bundle on them. After the Elastic Beanstalk environment is ready, you provide the configuration file name by adding the `CONFIG_FILE` environment variable.
4. Create the DynamoDB table. Using the Amazon DynamoDB service, you create the Games table on AWS, rather than locally on your computer. Remember, this table has a simple primary key made of the `GameId` partition key of string type.
5. Test the game in production.

### 3.1: Create an IAM role for Amazon EC2

Creating an IAM role of the **Amazon EC2** type allows the Amazon EC2 instance that is running your Tic-Tac-Toe application to assume the correct role and make application requests to access the Games table. When creating the role, choose the **Custom Policy** option and copy and paste the following policy.

```
{  
    "Version": "2012-10-17",  
    "Statement": [  
        {  
            "Action": [  
                "dynamodb>ListTables"  
            ],  
            "Effect": "Allow",  
            "Resource": "*"  
        },  
        {  
            "Action": [  
                "dynamodb:*"  
            ],  
            "Effect": "Allow",  
            "Resource": [  
                "arn:aws:dynamodb:us-west-2:922852403271:table/Games",  
                "arn:aws:dynamodb:us-west-2:922852403271:table/Games/index/*"  
            ]  
        }  
    ]  
}
```

For further instructions, see [Creating a role for an AWS service \(AWS Management Console\)](#) in the *IAM User Guide*.

### 3.2: Create the games table in Amazon DynamoDB

The Games table in DynamoDB stores game data. If the table does not exist, the application creates the table for you. In this case, let the application create the Games table.

### 3.3: Bundle and deploy the tic-tac-toe application code

If you followed this example's steps, then you already have the downloaded the Tic-Tac-Toe application. If not, download the application and extract all the files to a folder on your local computer. For instructions, see [Step 1: Deploy and test locally \(p. 1281\)](#).

After you extract all files, you will have a code folder. To hand off this folder to Elastic Beanstalk, you bundle the contents of this folder as a `.zip` file. First, you add a configuration file to that folder. Your application uses the Region and endpoint information to create a DynamoDB table in the specified Region and make subsequent table operation requests using the specified endpoint.

1. Switch to the folder where you downloaded the Tic-Tac-Toe application.

2. In the root folder of the application, create a text file named `beanstalk.config` with the following content.

```
[dynamodb]
region=<AWS region>
endpoint=<DynamoDB endpoint>
```

For example, you might use the following content.

```
[dynamodb]
region=us-west-2
endpoint=dynamodb.us-west-2.amazonaws.com
```

For a list of available Regions, see [Amazon DynamoDB](#) in the *Amazon Web Services General Reference*.

**Important**

The Region specified in the configuration file is the location where the Tic-Tac-Toe application creates the Games table in DynamoDB. You must create the Elastic Beanstalk application discussed in the next section in the same Region.

**Note**

When you create your Elastic Beanstalk application, you request to launch an environment where you can choose the environment type. To test the Tic-Tac-Toe example application, you can choose the **Single Instance** environment type, skip the following, and go to the next step.

However, the **Load balancing, autoscaling** environment type provides a highly available and scalable environment, something you should consider when you create and deploy other applications. If you choose this environment type, you also need to generate a UUID and add it to the configuration file, as shown following.

```
[dynamodb]
region=us-west-2
endpoint=dynamodb.us-west-2.amazonaws.com
[flask]
secret_key= 284e784d-1a25-4a19-92bf-8eeb7a9example
```

In client-server communication, when the server sends a response, for security's sake the server sends a signed cookie that the client sends back to the server in the next request. When there is only one server, the server can locally generate an encryption key when it starts. When there are many servers, they all need to know the same encryption key; otherwise, they won't be able to read cookies set by the peer servers. By adding `secret_key` to the configuration file, you tell all servers to use this encryption key.

3. Zip the content of the root folder of the application (which includes the `beanstalk.config` file)—for example, `TicTacToe.zip`.
4. Upload the `.zip` file to an Amazon Simple Storage Service (Amazon S3) bucket. In the next section, you provide this `.zip` file to Elastic Beanstalk to upload on the server or servers.

For instructions on how to upload to an Amazon S3 bucket, see [Create a bucket](#) and [Add an object to a bucket](#) in the *Amazon Simple Storage Service User Guide*.

## 3.4: Set up the AWS Elastic Beanstalk environment

In this step, you create an Elastic Beanstalk application, which is a collection of components including environments. For this example, you launch one Amazon EC2 instance to deploy and run your Tic-Tac-Toe application.

1. Enter the following custom URL to set up an Elastic Beanstalk console to set up the environment.


```
https://console.aws.amazon.com/elasticbeanstalk/?region=<AWS-Region>#/newApplication  
?applicationName=TicTacToe<your-name>  
&solutionStackName=Python  
&sourceBundleUrl=https://s3.amazonaws.com/<bucket-name>/TicTacToe.zip  
&environmentType=SingleInstance  
&instanceType=t1.micro
```

For more information about custom URLs, see [Constructing a Launch Now URL](#) in the *AWS Elastic Beanstalk Developer Guide*. For the URL, note the following:

- You must provide an AWS Region name (the same as the one you provided in the configuration file), an Amazon S3 bucket name, and the object name.
- For testing, the URL requests the **SingleInstance** environment type, and **t1.micro** as the instance type.
- The application name must be unique. Thus, in the preceding URL, we suggest you prepend your name to the `applicationName`.

Doing this opens the Elastic Beanstalk console. In some cases, you might need to sign in.


2. In the Elastic Beanstalk console, choose **Review and Launch**, and then choose **Launch**.
3. Note the URL for future reference. This URL opens your Tic-Tac-Toe application home page.



4. Configure the Tic-Tac-Toe application so it knows the location of the configuration file.

After Elastic Beanstalk creates the application, choose **Configuration**.

- a. Choose the gear icon next to **Software Configuration**, as shown in the following screenshot.



- At the end of the **Environment Properties** section, enter **CONFIG\_FILE** and its value **beanstalk.config**, and then choose **Save**.

It might take a few minutes for this environment update to complete.

PARAM3 A predefined environment property that will be available to your running application.	<input type="text"/>
PARAM4 A predefined environment property that will be available to your running application.	<input type="text"/>
PARAM5 A predefined environment property that will be available to your running application.	<input type="text"/>
<b>CONFIG_FILE</b>	<b>beanstalk.config</b> <input type="button" value="+"/>


[Cancel](#) [Save](#)

After the update completes, you can play the game.


- In the browser, enter the URL you copied in the previous step, as shown in the following example.

`http://<open-name>.elasticbeanstalk.com`

Doing this opens the application home page.



6. Log in as testuser1, and choose **CREATE** to start a new tic-tac-toe game.
7. Enter **testuser2** in the **Choose an Opponent** box.




8. Open another browser window.

Make sure that you clear all cookies in your browser window so you won't be logged in as same user.


9. Enter the same URL to open the application home page, as shown in the following example.

```
http://<env-name>.elasticbeanstalk.com
```

10. Log in as testuser2.
11. For the invitation from testuser1 in the list of pending invitations, choose **accept**.



12. Now the game page appears.



Both testuser1 and testuser2 can play the game. For each move, the application saves the move in the corresponding item in the Games table.

## Step 4: Clean up resources

Now you have completed the Tic-Tac-Toe application deployment and testing. The application covers end-to-end web application development on Amazon DynamoDB, except for user authentication. The application uses the login information on the home page only to add a player name when creating a game. In a production application, you would add the necessary code to perform user login and authentication.

If you are done testing, you can remove the resources you created to test the Tic-Tac-Toe application to avoid incurring any charges.

#### To remove the resources you created

1. Remove the Games table that you created in DynamoDB.
2. Terminate the Elastic Beanstalk environment to free up the Amazon EC2 instances.
3. Delete the IAM role that you created.
4. Remove the object that you created in Amazon S3.

## Exporting and importing DynamoDB data using AWS Data Pipeline

You can use AWS Data Pipeline to export data from a DynamoDB table to a file in an Amazon S3 bucket. You can also use the console to import data from Amazon S3 into a DynamoDB table, in the same AWS region or in a different region.

#### Note

DynamoDB Console now supports its own Export to Amazon S3 flow, however it is not compatible with AWS Data Pipeline import flow. For more information, see [DynamoDB data export to Amazon S3: how it works \(p. 1234\)](#) and the blog post [Export Amazon DynamoDB table data to your data lake in Amazon S3, no code writing required](#).


The ability to export and import data is useful in many scenarios. For example, suppose you want to maintain a baseline set of data, for testing purposes. You could put the baseline data into a DynamoDB table and export it to Amazon S3. Then, after you run an application that modifies the test data, you could "reset" the data set by importing the baseline from Amazon S3 back into the DynamoDB table. Another example involves accidental deletion of data, or even an accidental `DeleteTable` operation. In these cases, you could restore the data from a previous export file in Amazon S3. You can even copy data from a DynamoDB table in one AWS region, store the data in Amazon S3, and then import the data from Amazon S3 to an identical DynamoDB table in a second region. Applications in the second region could then access their nearest DynamoDB endpoint and work with their own copy of the data, with reduced network latency.

#### Important


DynamoDB Backup and Restore is a fully managed feature. You can back up tables from a few megabytes to hundreds of terabytes of data, with no impact on the performance and availability of your production applications. You can restore your table with a single click in the AWS Management Console or a single API call. We highly recommend that you use DynamoDB's native backup and restore feature instead of using AWS Data Pipeline. For more information, see [Using On-Demand backup and restore for DynamoDB \(p. 629\)](#).

The following diagram shows an overview of exporting and importing DynamoDB data using AWS Data Pipeline.

## Exporting Data from DynamoDB to Amazon S3



## Importing Data from Amazon S3 to DynamoDB



To export a DynamoDB table, you use the AWS Data Pipeline console to create a new pipeline. The pipeline launches an Amazon EMR cluster to perform the actual export. Amazon EMR reads the data from DynamoDB, and writes the data to an export file in an Amazon S3 bucket.

The process is similar for an import, except that the data is read from the Amazon S3 bucket and written to the DynamoDB table.

**Important**

When you export or import DynamoDB data, you will incur additional costs for the underlying AWS services that are used:

- **AWS Data Pipeline**— manages the import/export workflow for you.
- **Amazon S3**— contains the data that you export from DynamoDB, or import into DynamoDB.
- **Amazon EMR**— runs a managed Hadoop cluster to perform reads and writes between DynamoDB to Amazon S3. The cluster configuration is one `m3.xlarge` instance leader node and one `m3.xlarge` instance core node.

For more information see [AWS Data Pipeline pricing](#), [Amazon EMR pricing](#), and [Amazon S3 pricing](#).

## Prerequisites to export and import data

When you use AWS Data Pipeline for exporting and importing data, you must specify the actions that the pipeline is allowed to perform, and which resources the pipeline can consume. The permitted actions and resources are defined using AWS Identity and Access Management (IAM) roles.

You can also control access by creating IAM policies and attaching them to IAM users, roles or groups. These policies let you specify which users are allowed to import and export your DynamoDB data.

**Important**

The IAM user that performs the exports and imports must have an *active* AWS Access Key Id and Secret Key. For more information, see [Administering access keys for IAM users](#) in the *IAM User Guide*.

## Creating IAM roles for AWS Data Pipeline

In order to use AWS Data Pipeline, the following IAM roles must be present in your AWS account:

- **DataPipelineDefaultRole** — the actions that your pipeline can take on your behalf.
- **DataPipelineDefaultResourceRole** — the AWS resources that the pipeline will provision on your behalf. For exporting and importing DynamoDB data, these resources include an Amazon EMR cluster and the Amazon EC2 instances associated with that cluster.

If you have never used AWS Data Pipeline before, you will need to create *DataPipelineDefaultRole* and *DataPipelineDefaultResourceRole* yourself. Once you have created these roles, you can use them any time you want to export or import DynamoDB data.

**Note**

If you have previously used the AWS Data Pipeline console to create a pipeline, then *DataPipelineDefaultRole* and *DataPipelineDefaultResourceRole* were created for you at that time. No further action is required; you can skip this section and begin creating pipelines using the DynamoDB console. For more information, see [Exporting data from DynamoDB to Amazon S3 \(p. 1306\)](#) and [Importing data from Amazon S3 to DynamoDB \(p. 1307\)](#).

1. Sign in to the AWS Management Console and open the IAM console at <https://console.aws.amazon.com/iam/>.

2. From the IAM Console Dashboard, click **Roles**.
3. Click **Create Role** and do the following:
  - a. In the **AWS Service** trusted entity, choose **Data Pipeline**.
  - b. In the **Select your use case** panel, choose **Data Pipeline** and then choose **Next:Permissions**.
  - c. Notice that the **AWSDataPipelineRole** policy is automatically attached. Choose **Next:Review**.
  - d. In the **Role name** field, type **DataPipelineDefaultRole** as the role name and choose **Create role**.
4. Click **Create Role** and do the following:
  - a. In the **AWS Service** trusted entity, choose **Data Pipeline**.
  - b. In the **Select your use case** panel, choose **EC2 Role for Data Pipeline** and then choose **Next:Permissions**.
  - c. Notice that the **AmazonEC2RoleForDataPipelineRole** policy is automatically attached. Choose **Next:Review**.
  - d. In the **Role name** field, type **DataPipelineDefaultResourceRole** as the role name and choose **Create role**.

Now that you have created these roles, you can begin creating pipelines using the DynamoDB console. For more information, see [Exporting data from DynamoDB to Amazon S3 \(p. 1306\)](#) and [Importing data from Amazon S3 to DynamoDB \(p. 1307\)](#).

## Granting IAM users and groups permission to perform export and import tasks

If you want to allow other IAM users, roles or groups to export and import your DynamoDB table data, you can create an IAM policy and attach it to the users or groups that you designate. The policy contains only the necessary permissions for performing these tasks.

### Granting full access

The following procedure describes how to attach the AWS managed policies `AmazonDynamoDBFullAccess`, `AWSDataPipeline_FullAccess` and an Amazon EMR inline policy to an IAM user. These managed policies provides full access to AWS Data Pipeline and to DynamoDB resources, and used with the Amazon EMR inline policy, allow the user to perform the actions described in this documentation.

#### Note

To limit the scope of the suggested permissions, the inline policy above is enforcing the usage of the tag `dynamodb:datipeline`. If you want to utilize this documentation without this limitation, you can remove the `Condition` section of the suggested policy.

1. Sign in to the AWS Management Console and open the IAM console at <https://console.aws.amazon.com/iam/>.
2. From the IAM Console Dashboard, click **Users** and select the user you want to modify.
3. In the **Permissions** tab, click **Add Policy**.
4. In the **Attach permissions** panel, click **Attach existing policies directly**.
5. Select both `AmazonDynamoDBFullAccess` and `AWSDataPipeline_FullAccess` and click **Next:Review**.
6. Click **Add permissions**.
7. Back on **Permissions** tab, click **Add inline policy**.
8. In the **Create a policy** page, click **JSON** tab.
9. Paste the content below.

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Sid": "EMR",
            "Effect": "Allow",
            "Action": [
                "elasticmapreduce:DescribeStep",
                "elasticmapreduce:DescribeCluster",
                "elasticmapreduce:RunJobFlow",
                "elasticmapreduce:TerminateJobFlows"
            ],
            "Resource": "*",
            "Condition": {
                "Null": {
                    "elasticmapreduce:RequestTag/dynamodbdatipeline": "false"
                }
            }
        }
    ]
}
```

10. Click **Review policy**.
11. Type `EMRforDynamoDBDataPipeline` on the name field.
12. Click **Create policy**.

**Note**

You can use a similar procedure to attach this managed policy to a role or group, rather than to a user.

## Restricting access to particular DynamoDB tables

If you want to restrict access so that a user can only export or import a subset of your tables, you will need to create a customized IAM policy document. You can use the process described on [Granting full access \(p. 1303\)](#) as a starting point for your custom policy, and then modify the policy so that a user can only work with the tables that you specify.

For example, suppose that you want to allow an IAM user to export and import only the *Forum*, *Thread*, and *Reply* tables. This procedure describes how to create a custom policy so that a user can work with those tables, but no others.

1. Sign in to the AWS Management Console and open the IAM console at <https://console.aws.amazon.com/iam/>.
2. From the IAM Console Dashboard, click **Policies** and then click **Create Policy**.
3. In the **Create Policy** panel, go to **Copy an AWS Managed Policy** and click **Select**.
4. In the **Copy an AWS Managed Policy** panel, go to `AmazonDynamoDBFullAccess` and click **Select**.
5. In the **Review Policy** panel, do the following:
  - a. Review the autogenerated **Policy Name** and **Description**. If you want, you can modify these values.
  - b. In the **Policy Document** text box, edit the policy to restrict access to specific tables. By default, the policy permits all DynamoDB actions on all of your tables:

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Action": [
                "dynamodb:DescribeTable"
            ],
            "Resource": [
                "arn:aws:dynamodb:us-east-1:123456789012:table/Forum"
            ],
            "Effect": "Allow"
        }
    ]
}
```

```

    "Action": [
        "cloudwatch:DeleteAlarms",
        "cloudwatch:DescribeAlarmHistory",
        "cloudwatch:DescribeAlarms",
        "cloudwatch:DescribeAlarmsForMetric",
        "cloudwatch:GetMetricStatistics",
        "cloudwatch>ListMetrics",
        "cloudwatch:PutMetricAlarm",
        "dynamodb:*",
        "sns>CreateTopic",
        "sns>DeleteTopic",
        "sns>ListSubscriptions",
        "sns>ListSubscriptionsByTopic",
        "sns>ListTopics",
        "sns:Subscribe",
        "sns:Unsubscribe"
    ],
    "Effect": "Allow",
    "Resource": "*",
    "Sid": "DDBConsole"
},
...remainder of document omitted...

```

To restrict the policy, first remove the following line:

```
"dynamodb:*
```

Next, construct a new Action that allows access to only the *Forum*, *Thread* and *Reply* tables:

```
{
    "Action": [
        "dynamodb:*
```

#### Note

Replace `us-west-2` with the region in which your DynamoDB tables reside. Replace `123456789012` with your AWS account number.

Finally, add the new Action to the policy document:

```
{
    "Version": "2012-10-17",
    "Statement": [
        {
            "Action": [
                "dynamodb:*
```

```
},
{
  "Action": [
    "cloudwatch:DeleteAlarms",
    "cloudwatch:DescribeAlarmHistory",
    "cloudwatch:DescribeAlarms",
    "cloudwatch:DescribeAlarmsForMetric",
    "cloudwatch:GetMetricStatistics",
    "cloudwatch>ListMetrics",
    "cloudwatch:PutMetricAlarm",
    "sns>CreateTopic",
    "sns>DeleteTopic",
    "sns>ListSubscriptions",
    "sns>ListSubscriptionsByTopic",
    "sns>ListTopics",
    "sns:Subscribe",
    "sns:Unsubscribe"
  ],
  "Effect": "Allow",
  "Resource": "*",
  "Sid": "DDBConsole"
},
...remainder of document omitted...
```

- When the policy settings are as you want them, click **Create Policy**.

After you have created the policy, you can attach it to an IAM user.

- From the IAM Console Dashboard, click **Users** and select the user you want to modify.
- In the **Permissions** tab, click **Attach Policy**.
- In the **Attach Policy** panel, select the name of your policy and click **Attach Policy**.

**Note**

You can use a similar procedure to attach your policy to a role or group, rather than to a user.

## Exporting data from DynamoDB to Amazon S3

This section describes how to export data from one or more DynamoDB tables to an Amazon S3 bucket. You need to create the Amazon S3 bucket before you can perform the export.

**Important**

If you have never used AWS Data Pipeline before, you will need to set up two IAM roles before following this procedure. For more information, see [Creating IAM roles for AWS Data Pipeline \(p. 1302\)](#).

- Sign in to the AWS Management Console and open the AWS Data Pipeline console at <https://console.aws.amazon.com/datapipeline/>.
- If you do not already have any pipelines in the current AWS region, choose **Get started now**.

Otherwise, if you already have at least one pipeline, choose **Create new pipeline**.

- On the **Create Pipeline** page, do the following:
  - In the **Name** field, type a name for your pipeline. For example: `MyDynamoDBExportPipeline`.
  - For the **Source** parameter, select **Build using a template**. From the drop-down template list, choose **Export DynamoDB table to S3**.
  - In the **Source DynamoDB table name** field, type the name of the DynamoDB table that you want to export.

- d. In the **Output S3 Folder** text box, enter an Amazon S3 URI where the export file will be written. For example: s3://mybucket(exports

The format of this URI is s3://*bucketname*/*folder* where:

- *bucketname* is the name of your Amazon S3 bucket.
- *folder* is the name of a folder within that bucket. If the folder does not exist, it will be created automatically. If you do not specify a name for the folder, a name will be assigned for it in the form s3://*bucketname*/*region*/*tablename*.

- e. In the **S3 location for logs** text box, enter an Amazon S3 URI where the log file for the export will be written. For example: s3://mybucket/logs/

The URI format for **S3 Log Folder** is the same as for **Output S3 Folder**. The URI must resolve to a folder; log files cannot be written to the top level of the S3 bucket.

4. Add a tag with the Key dynamodbdatapipeline and the Value true.
5. When the settings are as you want them, click **Activate**.

Your pipeline will now be created; this process can take several minutes to complete. You can monitor the progress in the AWS Data Pipeline console.

When the export has finished, you can go to the [Amazon S3 console](#) to view your export file. The output file name is an identifier value with no extension, such as this example: ae10f955-fb2f-4790-9b11-fbfea01a871e\_000000. The internal format of this file is described at [Verify data export file](#) in the [AWS Data Pipeline Developer Guide](#).

## Importing data from Amazon S3 to DynamoDB

This section assumes that you have already exported data from a DynamoDB table, and that the export file has been written to your Amazon S3 bucket. The internal format of this file is described at [Verify data export file](#) in the [AWS Data Pipeline Developer Guide](#). Note that this is the *only* file format that DynamoDB can import using AWS Data Pipeline.

We will use the term *source table* for the original table from which the data was exported, and *destination table* for the table that will receive the imported data. You can import data from an export file in Amazon S3, provided that all of the following are true:

- The destination table already exists. (The import process will not create the table for you.)
- The destination table has the same key schema as the source table.

The destination table does not have to be empty. However, the import process will replace any data items in the table that have the same keys as the items in the export file. For example, suppose you have a *Customer* table with a key of *CustomerId*, and that there are only three items in the table (*CustomerId* 1, 2, and 3). If your export file also contains data items for *CustomerId* 1, 2, and 3, the items in the destination table will be replaced with those from the export file. If the export file also contains a data item for *CustomerId* 4, then that item will be added to the table.

The destination table can be in a different AWS region. For example, suppose you have a *Customer* table in the US West (Oregon) region and export its data to Amazon S3. You could then import that data into an identical *Customer* table in the Europe (Ireland) region. This is referred to as a *cross-region* export and import. For a list of AWS regions, go to [Regions and endpoints](#) in the [AWS General Reference](#).

Note that the AWS Management Console lets you export multiple source tables at once. However, you can only import one table at a time.

1. Sign in to the AWS Management Console and open the AWS Data Pipeline console at <https://console.aws.amazon.com/datapipeline/>.

2. (Optional) If you want to perform a cross region import, go to the upper right corner of the window and choose the destination region.
3. Choose **Create new pipeline**.
4. On the **Create Pipeline** page, do the following:
  - a. In the **Name** field, type a name for your pipeline. For example: `MyDynamoDBImportPipeline`.
  - b. For the **Source** parameter, select **Build using a template**. From the drop-down template list, choose **Import DynamoDB backup data from S3**.
  - c. In the **Input S3 Folder** text box, enter an Amazon S3 URI where the export file can be found. For example: `s3://mybucket/exports`

The format of this URI is `s3://bucketname/folder` where:

- `bucketname` is the name of your Amazon S3 bucket.
- `folder` is the name of the folder that contains the export file.

The import job will expect to find a file at the specified Amazon S3 location. The internal format of the file is described at [Verify data export file](#) in the *AWS Data Pipeline Developer Guide*.

- d. In the **Target DynamoDB table name** field, type the name of the DynamoDB table into which you want to import the data.
- e. In the **S3 location for logs** text box, enter an Amazon S3 URI where the log file for the import will be written. For example: `s3://mybucket/logs/`

The URI format for **S3 Log Folder** is the same as for **Output S3 Folder**. The URI must resolve to a folder; log files cannot be written to the top level of the S3 bucket.

- f. Add a tag with the Key `dynamodbdatapipeline` and the Value `true`.
5. When the settings are as you want them, click **Activate**.

Your pipeline will now be created; this process can take several minutes to complete. The import job will begin immediately after the pipeline has been created.

## Troubleshooting

This section covers some basic failure modes and troubleshooting for DynamoDB exports.

If an error occurs during an export or import, the pipeline status in the AWS Data Pipeline console will display as `ERROR`. If this happens, click the name of the failed pipeline to go to its detail page. This will show details about all of the steps in the pipeline, and the status of each one. In particular, examine any execution stack traces that you see.

Finally, go to your Amazon S3 bucket and look for any export or import log files that were written there.

The following are some common issues that may cause a pipeline to fail, along with corrective actions. To diagnose your pipeline, compare the errors you have seen with the issues noted below.

- For an import, ensure that the destination table already exists, and the destination table has the same key schema as the source table. These conditions must be met, or the import will fail.
- Ensure that the pipeline has the tag `dynamodbdatapipeline`; otherwise, the Amazon EMR API calls will not succeed.
- Ensure that the Amazon S3 bucket you specified has been created, and that you have read and write permissions on it.
- The pipeline might have exceeded its execution timeout. (You set this parameter when you created the pipeline.) For example, you might have set the execution timeout for 1 hour, but the export job might

have required more time than this. Try deleting and then re-creating the pipeline, but with a longer execution timeout interval this time.

- Update the manifest file if you restore from a Amazon S3 bucket that is not the original bucket that the export was performed with (contains a copy of the export).
- You might not have the correct permissions for performing an export or import. For more information, see [Prerequisites to export and import data \(p. 1302\)](#).
- You might have reached a resource quota in your AWS account, such as the maximum number of Amazon EC2 instances or the maximum number of AWS Data Pipeline pipelines. For more information, including how to request increases in these quotas, see [AWS service quotas](#) in the *AWS General Reference*.

**Note**

For more details on troubleshooting a pipeline, go to [Troubleshooting](#) in the *AWS Data Pipeline Developer Guide*.

## Predefined templates for AWS Data Pipeline and DynamoDB

If you would like a deeper understanding of how AWS Data Pipeline works, we recommend that you consult the *AWS Data Pipeline Developer Guide*. This guide contains step-by-step tutorials for creating and working with pipelines; you can use these tutorials as starting points for creating your own pipelines. We recommend that you read the AWS Data Pipeline tutorial, which walks you through the steps required to create an import and export pipeline that you can customize for your requirements. See [Tutorial: Amazon DynamoDB import and export using AWS Data Pipeline](#) in the *AWS Data Pipeline Developer Guide*.

AWS Data Pipeline offers several templates for creating pipelines; the following templates are relevant to DynamoDB.

### Exporting data between DynamoDB and Amazon S3

**Note**

DynamoDB Console now supports its own Export to Amazon S3 flow, however it is not compatible with AWS Data Pipeline import flow. For more information, see [DynamoDB data export to Amazon S3: how it works \(p. 1234\)](#) and the blog post [Export Amazon DynamoDB table data to your data lake in Amazon S3, no code writing required](#).

The AWS Data Pipeline console provides two predefined templates for exporting data between DynamoDB and Amazon S3. For more information about these templates, see the following sections of the *AWS Data Pipeline Developer Guide*:

- [Export DynamoDB to Amazon S3](#)
- [Export Amazon S3 to DynamoDB](#)

## Amazon DynamoDB Storage Backend for Titan

The DynamoDB Storage Backend for Titan project has been superseded by the Amazon DynamoDB Storage Backend for JanusGraph, which is available on [GitHub](#).

For up-to-date instructions on the DynamoDB Storage Backend for JanusGraph, see the [README.md](#) file.

## Reserved words in DynamoDB

The following keywords are reserved for use by DynamoDB. Do not use any of these words as attribute names in expressions. This list is not case-sensitive.

If you need to write an expression containing an attribute name that conflicts with a DynamoDB reserved word, you can define an expression attribute name to use in the place of the reserved word. For more information, see [Expression attribute names in DynamoDB \(p. 358\)](#).

```
ABORT
ABSOLUTE
ACTION
ADD
AFTER
AGENT
AGGREGATE
ALL
ALLOCATE
ALTER
ANALYZE
AND
ANY
ARCHIVE
ARE
ARRAY
AS
ASC
ASCII
ASENSITIVE
ASSERTION
ASYMMETRIC
AT
ATOMIC
ATTACH
ATTRIBUTE
AUTH
AUTHORIZATION
AUTHORIZE
AUTO
AVG
BACK
BACKUP
BASE
BATCH
BEFORE
BEGIN
BETWEEN
BIGINT
BINARY
BIT
BLOB
BLOCK
BOOLEAN
BOTH
BREADTH
BUCKET
BULK
BY
BYTE
CALL
CALLED
CALLING
```

CAPACITY
CASCADE
CASCADED
CASE
CAST
CATALOG
CHAR
CHARACTER
CHECK
CLASS
CLOB
CLOSE
CLUSTER
CLUSTERED
CLUSTERING
CLUSTERS
COALESCE
COLLATE
COLLATION
COLLECTION
COLUMN
COLUMNS
COMBINE
COMMENT
COMMIT
COMPACT
COMPILE
COMPRESS
CONDITION
CONFLICT
CONNECT
CONNECTION
CONSISTENCY
CONSISTENT
CONSTRAINT
CONSTRAINTS
CONSTRUCTOR
CONSUMED
CONTINUE
CONVERT
COPY
CORRESPONDING
COUNT
COUNTER
CREATE
CROSS
CUBE
CURRENT
CURSOR
CYCLE
DATA
DATABASE
DATE
DATETIME
DAY
DEALLOCATE
DEC
DECIMAL
DECLARE
DEFAULT
DEFERRABLE
DEFERRED
DEFINE
DEFINED
DEFINITION
DELETE

```
DELIMITED
DEPTH
DEREF
DESC
DESCRIBE
DESCRIPTOR
DETACH
DETERMINISTIC
DIAGNOSTICS
DIRECTORIES
DISABLE
DISCONNECT
DISTINCT
DISTRIBUTE
DO
DOMAIN
DOUBLE
DROP
DUMP
DURATION
DYNAMIC
EACH
ELEMENT
ELSE
ELSEIF
EMPTY
ENABLE
END
EQUAL
EQUALS
ERROR
ESCAPE
ESCAPED
EVAL
EVALUATE
EXCEEDED
EXCEPT
EXCEPTION
EXCEPTIONS
EXCLUSIVE
EXEC
EXECUTE
EXISTS
EXIT
EXPLAIN
EXPLODE
EXPORT
EXPRESSION
EXTENDED
EXTERNAL
EXTRACT
FAIL
FALSE
FAMILY
FETCH
FIELDS
FILE
FILTER
FILTERING
FINAL
FINISH
FIRST
FIXED
FLATTEN
FLOAT
FOR
```

FORCE
FOREIGN
FORMAT
FORWARD
FOUND
FREE
FROM
FULL
FUNCTION
FUNCTIONS
GENERAL
GENERATE
GET
GLOB
GLOBAL
GO
GOTO
GRANT
GREATER
GROUP
GROUPING
HANDLER
HASH
HAVE
HAVING
HEAP
HIDDEN
HOLD
HOUR
IDENTIFIED
IDENTITY
IF
IGNORE
IMMEDIATE
IMPORT
IN
INCLUDING
INCLUSIVE
INCREMENT
INCREMENTAL
INDEX
INDEXED
INDEXES
INDICATOR
INFINITE
INITIALLY
INLINE
INNER
INNTER
INOUT
INPUT
INSENSITIVE
INSERT
INSTEAD
INT
INTEGER
INTERSECT
INTERVAL
INTO
INVALIDATE
IS
ISOLATION
ITEM
ITEMS
ITERATE
JOIN

KEY
KEYS
LAG
LANGUAGE
LARGE
LAST
LATERAL
LEAD
LEADING
LEAVE
LEFT
LENGTH
LESS
LEVEL
LIKE
LIMIT
LIMITED
LINES
LIST
LOAD
LOCAL
LOCALTIME
LOCALTIMESTAMP
LOCATION
LOCATOR
LOCK
LOCKS
LOG
LOGED
LONG
LOOP
LOWER
MAP
MATCH
MATERIALIZED
MAX
MAXLEN
MEMBER
MERGE
METHOD
METRICS
MIN
MINUS
MINUTE
MISSING
MOD
MODE
MODIFIES
MODIFY
MODULE
MONTH
MULTI
MULTiset
NAME
NAMES
NATIONAL
NATURAL
NCHAR
NCLOB
NEW
NEXT
NO
NONE
NOT
NULL
NULLIF

NUMBER
NUMERIC
OBJECT
OF
OFFLINE
OFFSET
OLD
ON
ONLINE
ONLY
OPAQUE
OPEN
OPERATOR
OPTION
OR
ORDER
ORDINALITY
OTHER
OTHERS
OUT
OUTER
OUTPUT
OVER
OVERLAPS
OVERRIDE
OWNER
PAD
PARALLEL
PARAMETER
PARAMETERS
PARTIAL
PARTITION
PARTITIONED
PARTITIONS
PATH
PERCENT
PERCENTILE
PERMISSION
PERMISSIONS
PIPE
PIPELINED
PLAN
POOL
POSITION
PRECISION
PREPARE
PRESERVE
PRIMARY
PRIOR
PRIVATE
PRIVILEGES
PROCEDURE
PROCESSED
PROJECT
PROJECTION
PROPERTY
PROVISIONING
PUBLIC
PUT
QUERY
QUIT
QUORUM
RAISE
RANDOM
RANGE
RANK

```
RAW
READ
READS
REAL
REBUILD
RECORD
RECURSIVE
REDUCE
REF
REFERENCE
REFERENCES
REFERENCING
REGEXP
REGION
REINDEX
RELATIVE
RELEASE
REMAINDER
RENAME
REPEAT
REPLACE
REQUEST
RESET
RESIGNAL
RESOURCE
RESPONSE
RESTORE
RESTRICT
RESULT
RETURN
RETURNING
RETURNS
REVERSE
REVOKE
RIGHT
ROLE
ROLES
ROLLBACK
ROLLUP
ROUTINE
ROW
ROWS
RULE
RULES
SAMPLE
SATISFIES
SAVE
SAVEPOINT
SCAN
SCHEMA
SCOPE
SCROLL
SEARCH
SECOND
SECTION
SEGMENT
SEGMENTS
SELECT
SELF
SEMI
SENSITIVE
SEPARATE
SEQUENCE
SERIALIZABLE
SESSION
SET
```

SETS
SHARD
SHARE
SHARED
SHORT
SHOW
SIGNAL
SIMILAR
SIZE
SKEWED
SMALLINT
SNAPSHOT
SOME
SOURCE
SPACE
SPACES
SPARSE
SPECIFIC
SPECIFICTYPE
SPLIT
SQL
SQLCODE
SQLERROR
SQLEXCEPTION
SQLSTATE
SQLWARNING
START
STATE
STATIC
STATUS
STORAGE
STORE
STORED
STREAM
STRING
STRUCT
STYLE
SUB
SUBMULTISET
SUBPARTITION
SUBSTRING
SUBTYPE
SUM
SUPER
SYMMETRIC
SYNONYM
SYSTEM
TABLE
TABLESAMPLE
TEMP
TEMPORARY
TERMINATED
TEXT
THAN
THEN
THROUGHPUT
TIME
TIMESTAMP
TIMEZONE
TINYINT
TO
TOKEN
TOTAL
TOUCH
TRAILING
TRANSACTION

```
TRANSFORM
TRANSLATE
TRANSLATION
TREAT
TRIGGER
TRIM
TRUE
TRUNCATE
TTL
TUPLE
TYPE
UNDER
UNDO
UNION
UNIQUE
UNIT
UNKNOWN
UNLOGGED
UNNEST
UNPROCESSED
UNSIGNED
UNTIL
UPDATE
UPPER
URL
USAGE
USE
USER
USERS
USING
UUID
VACUUM
VALUE
VALUED
VALUES
VARCHAR
VARIABLE
VARIANCE
VARINT
VARYING
VIEW
VIEWS
VIRTUAL
VOID
WAIT
WHEN
WHENEVER
WHERE
WHILE
WINDOW
WITH
WITHIN
WITHOUT
WORK
WRAPPED
WRITE
YEAR
ZONE
```

## Legacy conditional parameters

This section compares the legacy conditional parameters with expression parameters in DynamoDB.

### **Important**

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

Additionally, DynamoDB does not allow mixing legacy conditional parameters and expression parameters in a single call. For example, calling the `Query` operation with `AttributesToGet` and `ConditionExpression` will result in an error.

The following table shows the DynamoDB APIs that still support these legacy parameters, and which expression parameter to use instead. This table can be helpful if you are considering updating your applications so that they use expression parameters instead.

If you use this API...	With these legacy parameters...	Use this expression parameter instead
<code>BatchGetItem</code>	<code>AttributesToGet</code>	<code>ProjectionExpression</code>
<code>DeleteItem</code>	<code>Expected</code>	<code>ConditionExpression</code>
<code>GetItem</code>	<code>AttributesToGet</code>	<code>ProjectionExpression</code>
<code>PutItem</code>	<code>Expected</code>	<code>ConditionExpression</code>
<code>Query</code>	<code>AttributesToGet</code>	<code>ProjectionExpression</code>
	<code>KeyConditions</code>	<code>KeyConditionExpression</code>
	<code>QueryFilter</code>	<code>FilterExpression</code>
<code>Scan</code>	<code>AttributesToGet</code>	<code>ProjectionExpression</code>
	<code>ScanFilter</code>	<code>FilterExpression</code>
<code>UpdateItem</code>	<code>AttributeUpdates</code>	<code>UpdateExpression</code>
	<code>Expected</code>	<code>ConditionExpression</code>

The following sections provide more information about legacy conditional parameters.

### **Topics**

- [AttributesToGet \(p. 1319\)](#)
- [AttributeUpdates \(p. 1320\)](#)
- [ConditionalOperator \(p. 1322\)](#)
- [Expected \(p. 1322\)](#)
- [KeyConditions \(p. 1326\)](#)
- [QueryFilter \(p. 1328\)](#)
- [ScanFilter \(p. 1329\)](#)
- [Writing conditions with legacy parameters \(p. 1330\)](#)

## AttributesToGet

### **Note**

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

`AttributesToGet` is an array of one or more attributes to retrieve from DynamoDB. If no attribute names are provided, then all attributes will be returned. If any of the requested attributes are not found, they will not appear in the result.

`AttributesToGet` allows you to retrieve attributes of type List or Map; however, it cannot retrieve individual elements within a List or a Map.

Note that `AttributesToGet` has no effect on provisioned throughput consumption. DynamoDB determines capacity units consumed based on item size, not on the amount of data that is returned to an application.

## Use *ProjectionExpression* instead

Suppose you wanted to retrieve an item from the `Music` table, but that you only wanted to return some of the attributes. You could use a `GetItem` request with an `AttributesToGet` parameter, as in this AWS CLI example:

```
aws dynamodb get-item \  
  --table-name Music \  
  --attributes-to-get '["Artist", "Genre"]' \  
  --key '{  
    "Artist": {"S": "No One You Know"},  
    "SongTitle": {"S": "Call Me Today"}  
}'
```

But you could use a `ProjectionExpression` instead:

```
aws dynamodb get-item \  
  --table-name Music \  
  --projection-expression "Artist, Genre" \  
  --key '{  
    "Artist": {"S": "No One You Know"},  
    "SongTitle": {"S": "Call Me Today"}  
}'
```

## AttributeUpdates

### Note

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

In an `UpdateItem` operation, `AttributeUpdates` are the names of attributes to be modified, the action to perform on each, and the new value for each. If you are updating an attribute that is an index key attribute for any indexes on that table, the attribute type must match the index key type defined in the `AttributesDefinition` of the table description. You can use `UpdateItem` to update any non-key attributes.

Attribute values cannot be null. String and Binary type attributes must have lengths greater than zero. Set type attributes must not be empty. Requests with empty values will be rejected with a `ValidationException` exception.

Each `AttributeUpdates` element consists of an attribute name to modify, along with the following:

- `Value` - The new value, if applicable, for this attribute.
- `Action` - A value that specifies how to perform the update. This action is only valid for an existing attribute whose data type is Number or is a set; do not use `ADD` for other data types.

If an item with the specified primary key is found in the table, the following values perform the following actions:

- **PUT** - Adds the specified attribute to the item. If the attribute already exists, it is replaced by the new value.
- **DELETE** - Removes the attribute and its value, if no value is specified for **DELETE**. The data type of the specified value must match the existing value's data type.

If a set of values is specified, then those values are subtracted from the old set. For example, if the attribute value was the set [a, b, c] and the **DELETE** action specifies [a, c], then the final attribute value is [b]. Specifying an empty set is an error.

- **ADD** - Adds the specified value to the item, if the attribute does not already exist. If the attribute does exist, then the behavior of **ADD** depends on the data type of the attribute:
  - If the existing attribute is a number, and if **Value** is also a number, then **Value** is mathematically added to the existing attribute. If **Value** is a negative number, then it is subtracted from the existing attribute.

#### **Note**

If you use **ADD** to increment or decrement a number value for an item that doesn't exist before the update, DynamoDB uses 0 as the initial value.

Similarly, if you use **ADD** for an existing item to increment or decrement an attribute value that doesn't exist before the update, DynamoDB uses 0 as the initial value. For example, suppose that the item you want to update doesn't have an attribute named *itemcount*, but you decide to **ADD** the number 3 to this attribute anyway. DynamoDB will create the *itemcount* attribute, set its initial value to 0, and finally add 3 to it. The result will be a new *itemcount* attribute, with a value of 3.

- If the existing data type is a set, and if **Value** is also a set, then **Value** is appended to the existing set. For example, if the attribute value is the set [1, 2], and the **ADD** action specified [3], then the final attribute value is [1, 2, 3]. An error occurs if an **ADD** action is specified for a set attribute and the attribute type specified does not match the existing set type.

Both sets must have the same primitive data type. For example, if the existing data type is a set of strings, **Value** must also be a set of strings.

If no item with the specified key is found in the table, the following values perform the following actions:

- **PUT** - Causes DynamoDB to create a new item with the specified primary key, and then adds the attribute.
- **DELETE** - Nothing happens, because attributes cannot be deleted from a nonexistent item. The operation succeeds, but DynamoDB does not create a new item.
- **ADD** - Causes DynamoDB to create an item with the supplied primary key and number (or set of numbers) for the attribute value. The only data types allowed are Number and Number Set.

If you provide any attributes that are part of an index key, then the data types for those attributes must match those of the schema in the table's attribute definition.

## Use *UpdateExpression* instead

Suppose you wanted to modify an item in the *Music* table. You could use an **UpdateItem** request with an **AttributeUpdates** parameter, as in this AWS CLI example:

```
aws dynamodb update-item \
--table-name Music \
--key '{
    "SongTitle": {"S": "Call Me Today"}, 
    "Artist": {"S": "No One You Know"}
```

```
}' \
--attribute-updates '{
    "Genre": {
        "Action": "PUT",
        "Value": {"S":"Rock"}
    }
}'
```

But you could use a `UpdateExpression` instead:

```
aws dynamodb update-item \
    --table-name Music \
    --key '{
        "SongTitle": {"S":"Call Me Today"},
        "Artist": {"S":"No One You Know"}
    }' \
    --update-expression 'SET Genre = :g' \
    --expression-attribute-values '{
        ":g": {"S":"Rock"}
    }'
```

For more information about updating attributes, see [Update an item in a DynamoDB table \(p. 113\)](#).

## ConditionalOperator

### Note

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

A logical operator to apply to the conditions in a `Expected`, `QueryFilter` or `ScanFilter` map:

- AND - If all of the conditions evaluate to true, then the entire map evaluates to true.
- OR - If at least one of the conditions evaluate to true, then the entire map evaluates to true.

If you omit `ConditionalOperator`, then AND is the default.

The operation will succeed only if the entire map evaluates to true.

### Note

This parameter does not support attributes of type List or Map.

## Expected

### Note

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

`Expected` is a conditional block for an `UpdateItem` operation. `Expected` is a map of attribute/condition pairs. Each element of the map consists of an attribute name, a comparison operator, and one or more values. DynamoDB compares the attribute with the value(s) you supplied, using the comparison operator. For each `Expected` element, the result of the evaluation is either true or false.

If you specify more than one element in the `Expected` map, then by default all of the conditions must evaluate to true. In other words, the conditions are ANDed together. (You can use the `ConditionalOperator` parameter to OR the conditions instead. If you do this, then at least one of the conditions must evaluate to true, rather than all of them.)

If the `Expected` map evaluates to true, then the conditional operation succeeds; otherwise, it fails.

Expected contains the following:

- **AttributeValueList** - One or more values to evaluate against the supplied attribute. The number of values in the list depends on the **ComparisonOperator** being used.

For type Number, value comparisons are numeric.

String value comparisons for greater than, equals, or less than are based on Unicode with UTF-8 binary encoding. For example, a is greater than A, and a is greater than B.

For type Binary, DynamoDB treats each byte of the binary data as unsigned when it compares binary values.

- **ComparisonOperator** - A comparator for evaluating attributes in the **AttributeValueList**. When performing the comparison, DynamoDB uses strongly consistent reads.

The following comparison operators are available:

**EQ** | **NE** | **LE** | **LT** | **GE** | **GT** | **NOT\_NULL** | **NULL** | **CONTAINS** | **NOT\_CONTAINS** |  
**BEGINS\_WITH** | **IN** | **BETWEEN**

The following are descriptions of each comparison operator.

- **EQ** : Equal. EQ is supported for all datatypes, including lists and maps.

**AttributeValueList** can contain only one **AttributeValue** element of type String, Number, Binary, String Set, Number Set, or Binary Set. If an item contains an **AttributeValue** element of a different type than the one provided in the request, the value does not match. For example, {"S": "6"} does not equal {"N": "6"}. Also, {"N": "6"} does not equal {"NS": ["6", "2", "1"]}.

- **NE** : Not equal. NE is supported for all datatypes, including lists and maps.

**AttributeValueList** can contain only one **AttributeValue** of type String, Number, Binary, String Set, Number Set, or Binary Set. If an item contains an **AttributeValue** of a different type than the one provided in the request, the value does not match. For example, {"S": "6"} does not equal {"N": "6"}. Also, {"N": "6"} does not equal {"NS": ["6", "2", "1"]}.

- **LE** : Less than or equal.

**AttributeValueList** can contain only one **AttributeValue** element of type String, Number, or Binary (not a set type). If an item contains an **AttributeValue** element of a different type than the one provided in the request, the value does not match. For example, {"S": "6"} does not equal {"N": "6"}. Also, {"N": "6"} does not compare to {"NS": ["6", "2", "1"]}.

- **LT** : Less than.

**AttributeValueList** can contain only one **AttributeValue** of type String, Number, or Binary (not a set type). If an item contains an **AttributeValue** element of a different type than the one provided in the request, the value does not match. For example, {"S": "6"} does not equal {"N": "6"}. Also, {"N": "6"} does not compare to {"NS": ["6", "2", "1"]}.

- **GE** : Greater than or equal.

**AttributeValueList** can contain only one **AttributeValue** element of type String, Number, or Binary (not a set type). If an item contains an **AttributeValue** element of a different type than the one provided in the request, the value does not match. For example, {"S": "6"} does not equal {"N": "6"}. Also, {"N": "6"} does not compare to {"NS": ["6", "2", "1"]}.

- **GT** : Greater than.

**AttributeValueList** can contain only one **AttributeValue** element of type String, Number, or Binary (not a set type). If an item contains an **AttributeValue** element of a different type than

the one provided in the request, the value does not match. For example, `{ "S" : "6" }` does not equal `{ "N" : "6" }`. Also, `{ "N" : "6" }` does not compare to `{ "NS" : [ "6", "2", "1" ] }`.

- `NOT_NULL` : The attribute exists. `NOT_NULL` is supported for all datatypes, including lists and maps.

**Note**

This operator tests for the existence of an attribute, not its data type. If the data type of attribute "a" is null, and you evaluate it using `NOT_NULL`, the result is a Boolean `true`.

This result is because the attribute "a" exists; its data type is not relevant to the `NOT_NULL` comparison operator.

- `NONE` : The attribute does not exist. `NONE` is supported for all datatypes, including lists and maps.

**Note**

This operator tests for the nonexistence of an attribute, not its data type. If the data type of attribute "a" is null, and you evaluate it using `NONE`, the result is a Boolean `false`. This is because the attribute "a" exists; its data type is not relevant to the `NONE` comparison operator.

- `CONTAINS` : Checks for a subsequence, or value in a set.

`AttributeValueList` can contain only one `AttributeValue` element of type String, Number, or Binary (not a set type). If the target attribute of the comparison is of type String, then the operator checks for a substring match. If the target attribute of the comparison is of type Binary, then the operator looks for a subsequence of the target that matches the input. If the target attribute of the comparison is a set ("SS", "NS", or "BS"), then the operator evaluates to true if it finds an exact match with any member of the set.

`CONTAINS` is supported for lists: When evaluating `"a CONTAINS b"`, "a" can be a list; however, "b" cannot be a set, a map, or a list.

- `NOT_CONTAINS` : Checks for absence of a subsequence, or absence of a value in a set.

`AttributeValueList` can contain only one `AttributeValue` element of type String, Number, or Binary (not a set type). If the target attribute of the comparison is a String, then the operator checks for the absence of a substring match. If the target attribute of the comparison is Binary, then the operator checks for the absence of a subsequence of the target that matches the input. If the target attribute of the comparison is a set ("SS", "NS", or "BS"), then the operator evaluates to true if it does not find an exact match with any member of the set.

`NOT_CONTAINS` is supported for lists: When evaluating `"a NOT CONTAINS b"`, "a" can be a list; however, "b" cannot be a set, a map, or a list.

- `BEGINS_WITH` : Checks for a prefix.

`AttributeValueList` can contain only one `AttributeValue` of type String or Binary (not a Number or a set type). The target attribute of the comparison must be of type String or Binary (not a Number or a set type).

- `IN` : Checks for matching elements within two sets.

`AttributeValueList` can contain one or more `AttributeValue` elements of type String, Number, or Binary (not a set type). These attributes are compared against an existing set type attribute of an item. If any elements of the input set are present in the item attribute, the expression evaluates to true.

- `BETWEEN` : Greater than or equal to the first value, and less than or equal to the second value.

`AttributeValueList` must contain two `AttributeValue` elements of the same type, either String, Number, or Binary (not a set type). A target attribute matches if the target value is greater than, or equal to, the first element and less than, or equal to, the second element. If an item contains an `AttributeValue` element of a different type than the one provided in the request, the value does not match. For example, `{ "S" : "6" }` does not compare to `{ "N" : "6" }`. Also, `{ "N" : "6" }` does not compare to `{ "NS" : [ "6", "2", "1" ] }`.

The following parameters can be used instead of `AttributeValueList` and `ComparisonOperator`:

- `Value` - A value for DynamoDB to compare with an attribute.
- `Exists` - A Boolean value that causes DynamoDB to evaluate the value before attempting the conditional operation:
  - If `Exists` is `true`, DynamoDB will check to see if that attribute value already exists in the table. If it is found, then the condition evaluates to true; otherwise the condition evaluate to false.
  - If `Exists` is `false`, DynamoDB assumes that the attribute value does not exist in the table. If in fact the value does not exist, then the assumption is valid and the condition evaluates to true. If the value is found, despite the assumption that it does not exist, the condition evaluates to false.

Note that the default value for `Exists` is `true`.

The `Value` and `Exists` parameters are incompatible with `AttributeValueList` and `ComparisonOperator`. Note that if you use both sets of parameters at once, DynamoDB will return a `ValidationException` exception.

**Note**

This parameter does not support attributes of type List or Map.

## Use *ConditionExpression* instead

Suppose you wanted to modify an item in the `Music` table, but only if a certain condition was true. You could use an `UpdateItem` request with an `Expected` parameter, as in this AWS CLI example:

```
aws dynamodb update-item \
  --table-name Music \
  --key '{
    "Artist": {"S":"No One You Know"},
    "SongTitle": {"S":"Call Me Today"}
}' \
  --attribute-updates '{
    "Price": {
        "Action": "PUT",
        "Value": {"N":"1.98"}
    }
}' \
  --expected '{
    "Price": {
        "ComparisonOperator": "LE",
        "AttributeValueList": [ {"N":"2.00"} ]
    }
}'
```

But you could use a `ConditionExpression` instead:

```
aws dynamodb update-item \
  --table-name Music \
  --key '{
    "Artist": {"S":"No One You Know"},
    "SongTitle": {"S":"Call Me Today"}
}' \
  --update-expression 'SET Price = :p1' \
  --condition-expression 'Price <= :p2' \
  --expression-attribute-values '{
    ":p1": {"N":"1.98"},
    ":p2": {"N":"2.00"}
}'
```

## KeyConditions

### Note

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

**KeyConditions** are the selection criteria for a `Query` operation. For a query on a table, you can have conditions only on the table primary key attributes. You must provide the partition key name and value as an `EQ` condition. You can optionally provide a second condition, referring to the sort key.

### Note

If you don't provide a sort key condition, all of the items that match the partition key will be retrieved. If a `FilterExpression` or `QueryFilter` is present, it will be applied after the items are retrieved.

For a query on an index, you can have conditions only on the index key attributes. You must provide the index partition key name and value as an `EQ` condition. You can optionally provide a second condition, referring to the index sort key.

Each `KeyConditions` element consists of an attribute name to compare, along with the following:

- `AttributeValueList` - One or more values to evaluate against the supplied attribute. The number of values in the list depends on the `ComparisonOperator` being used.

For type `Number`, value comparisons are numeric.

String value comparisons for greater than, equals, or less than are based on Unicode with UTF-8 binary encoding. For example, `a` is greater than `A`, and `a` is greater than `B`.

For `Binary`, DynamoDB treats each byte of the binary data as `unsigned` when it compares binary values.

- `ComparisonOperator` - A comparator for evaluating attributes, for example, equals, greater than, less than, and so on.

For `KeyConditions`, only the following comparison operators are supported:

`EQ` | `LE` | `LT` | `GE` | `GT` | `BEGINS_WITH` | `BETWEEN`

The following are descriptions of these comparison operators.

- `EQ` : Equal.

`AttributeValueList` can contain only one `AttributeValue` of type `String`, `Number`, or `Binary` (not a set type). If an item contains an `AttributeValue` element of a different type than the one specified in the request, the value does not match. For example, `{"S": "6"}` does not equal `{"N": "6"}`. Also, `{"N": "6"}` does not equal `{"NS": ["6", "2", "1"]}`.

- `LE` : Less than or equal.

`AttributeValueList` can contain only one `AttributeValue` element of type `String`, `Number`, or `Binary` (not a set type). If an item contains an `AttributeValue` element of a different type than the one provided in the request, the value does not match. For example, `{"S": "6"}` does not equal `{"N": "6"}`. Also, `{"N": "6"}` does not compare to `{"NS": ["6", "2", "1"]}`.

- `LT` : Less than.

`AttributeValueList` can contain only one `AttributeValue` of type `String`, `Number`, or `Binary` (not a set type). If an item contains an `AttributeValue` element of a different type than the one provided in the request, the value does not match. For example, `{"S": "6"}` does not equal `{"N": "6"}`. Also, `{"N": "6"}` does not compare to `{"NS": ["6", "2", "1"]}`.

- `GE` : Greater than or equal.

`AttributeValueList` can contain only one `AttributeValue` element of type String, Number, or Binary (not a set type). If an item contains an `AttributeValue` element of a different type than the one provided in the request, the value does not match. For example, `{"S": "6"}` does not equal `{"N": "6"}`. Also, `{"N": "6"}` does not compare to `{"NS": ["6", "2", "1"]}`.

- `GT` : Greater than.

`AttributeValueList` can contain only one `AttributeValue` element of type String, Number, or Binary (not a set type). If an item contains an `AttributeValue` element of a different type than the one provided in the request, the value does not match. For example, `{"S": "6"}` does not equal `{"N": "6"}`. Also, `{"N": "6"}` does not compare to `{"NS": ["6", "2", "1"]}`.

- `BEGINS_WITH` : Checks for a prefix.

`AttributeValueList` can contain only one `AttributeValue` of type String or Binary (not a Number or a set type). The target attribute of the comparison must be of type String or Binary (not a Number or a set type).

- `BETWEEN` : Greater than or equal to the first value, and less than or equal to the second value.

`AttributeValueList` must contain two `AttributeValue` elements of the same type, either String, Number, or Binary (not a set type). A target attribute matches if the target value is greater than, or equal to, the first element and less than, or equal to, the second element. If an item contains an `AttributeValue` element of a different type than the one provided in the request, the value does not match. For example, `{"S": "6"}` does not compare to `{"N": "6"}`. Also, `{"N": "6"}` does not compare to `{"NS": ["6", "2", "1"]}`

## Use `KeyConditionExpression` instead

Suppose you wanted to retrieve several items with the same partition key from the *Music* table. You could use a `Query` request with a `KeyConditions` parameter, as in this AWS CLI example:

```
aws dynamodb query \
--table-name Music \
--key-conditions '{
    "Artist": {
        "ComparisonOperator": "EQ",
        "AttributeValueList": [ {"S": "No One You Know"} ]
    },
    "SongTitle": {
        "ComparisonOperator": "BETWEEN",
        "AttributeValueList": [ {"S": "A"}, {"S": "M"} ]
    }
}'
```

But you could use a `KeyConditionExpression` instead:

```
aws dynamodb query \
--table-name Music \
--key-condition-expression 'Artist = :a AND SongTitle BETWEEN :t1 AND :t2' \
--expression-attribute-values '{
    ":a": {"S": "No One You Know"},
    ":t1": {"S": "A"},
    ":t2": {"S": "M"}
}'
```

## QueryFilter

### Note

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

In a `Query` operation, `QueryFilter` is a condition that evaluates the query results after the items are read and returns only the desired values.

This parameter does not support attributes of type List or Map.

### Note

A `QueryFilter` is applied after the items have already been read; the process of filtering does not consume any additional read capacity units.

If you provide more than one condition in the `QueryFilter` map, then by default all of the conditions must evaluate to true. In other words, the conditions are ANDed together. (You can use the [ConditionalOperator \(p. 1322\)](#) parameter to OR the conditions instead. If you do this, then at least one of the conditions must evaluate to true, rather than all of them.)

Note that `QueryFilter` does not allow key attributes. You cannot define a filter condition on a partition key or a sort key.

Each `QueryFilter` element consists of an attribute name to compare, along with the following:

- `AttributeValueList` - One or more values to evaluate against the supplied attribute. The number of values in the list depends on the operator specified in `ComparisonOperator`.

For type Number, value comparisons are numeric.

String value comparisons for greater than, equals, or less than are based on UTF-8 binary encoding. For example, a is greater than A, and a is greater than B.

For type Binary, DynamoDB treats each byte of the binary data as unsigned when it compares binary values.

For information on specifying data types in JSON, see [DynamoDB low-level API \(p. 159\)](#).

- `ComparisonOperator` - A comparator for evaluating attributes. For example, equals, greater than, less than, etc.

The following comparison operators are available:

`EQ | NE | LE | LT | GE | GT | NOT_NULL | NULL | CONTAINS | NOT_CONTAINS |  
BEGINS_WITH | IN | BETWEEN`

## Use *FilterExpression* instead

Suppose you wanted to query the `Music` table and apply a condition to the matching items. You could use a `Query` request with a `QueryFilter` parameter, as in this AWS CLI example:

```
aws dynamodb query \  
--table-name Music \  
--key-conditions '{  
    "Artist": {  
        "ComparisonOperator": "EQ",  
        "AttributeValueList": [ {"S": "No One You Know"} ]  
    }  
}'
```

```

        }
    }' \
--query-filter '{
    "Price": {
        "ComparisonOperator": "GT",
        "AttributeValueList": [ {"N": "1.00"} ]
    }
}'
```

But you could use a `FilterExpression` instead:

```

aws dynamodb query \
--table-name Music \
--key-condition-expression 'Artist = :a' \
--filter-expression 'Price > :p' \
--expression-attribute-values '{
    ":p": {"N": "1.00"},
    ":a": {"S": "No One You Know"}
}'
```

## ScanFilter

### Note

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

In a Scan operation, `ScanFilter` is a condition that evaluates the scan results and returns only the desired values.

### Note

This parameter does not support attributes of type List or Map.

If you specify more than one condition in the `ScanFilter` map, then by default all of the conditions must evaluate to true. In other words, the conditions are ANDed together. (You can use the [ConditionalOperator \(p. 1322\)](#) parameter to OR the conditions instead. If you do this, then at least one of the conditions must evaluate to true, rather than all of them.)

Each `ScanFilter` element consists of an attribute name to compare, along with the following:

- `AttributeValueList` - One or more values to evaluate against the supplied attribute. The number of values in the list depends on the operator specified in `ComparisonOperator`.

For type Number, value comparisons are numeric.

String value comparisons for greater than, equals, or less than are based on UTF-8 binary encoding. For example, a is greater than A, and a is greater than B.

For Binary, DynamoDB treats each byte of the binary data as unsigned when it compares binary values.

For information on specifying data types in JSON, see [DynamoDB low-level API \(p. 159\)](#).

- `ComparisonOperator` - A comparator for evaluating attributes. For example, equals, greater than, less than, etc.

The following comparison operators are available:

`EQ | NE | LE | LT | GE | GT | NOT_NULL | NULL | CONTAINS | NOT_CONTAINS |  
BEGINS_WITH | IN | BETWEEN`

## Use `FilterExpression` instead

Suppose you wanted to scan the `Music` table and apply a condition to the matching items. You could use a Scan request with a `ScanFilter` parameter, as in this AWS CLI example:

```
aws dynamodb scan \  
  --table-name Music \  
  --scan-filter '{  
    "Genre":{  
      "AttributeValueList": [ {"S":"Rock"} ],  
      "ComparisonOperator": "EQ"  
    }  
}'
```

But you could use a `FilterExpression` instead:

```
aws dynamodb scan \  
  --table-name Music \  
  --filter-expression 'Genre = :g' \  
  --expression-attribute-values '{  
    ":g": {"S":"Rock"}  
}'
```

## Writing conditions with legacy parameters

### Note

With the introduction of expression parameters, several older parameters have been deprecated. New applications should not use these legacy parameters, but should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

The following section describes how to write conditions for use with legacy parameters, such as `Expected`, `QueryFilter`, and `ScanFilter`.

### Note

New applications should use expression parameters instead. For more information, see [Using expressions in DynamoDB \(p. 354\)](#).

## Simple conditions

With attribute values, you can write conditions for comparisons against table attributes. A condition always evaluates to true or false, and consists of:

- `ComparisonOperator` — greater than, less than, equal to, and so on.
- `AttributeValueList` (optional) — attribute value(s) to compare against. Depending on the `ComparisonOperator` being used, the `AttributeValueList` might contain one, two, or more values; or it might not be present at all.

The following sections describe the various comparison operators, along with examples of how to use them in conditions.

## Comparison operators with no attribute values

- `NOT_NULL` - true if an attribute exists.
- `NULL` - true if an attribute does not exist.

Use these operators to check whether an attribute exists, or doesn't exist. Because there is no value to compare against, do not specify `AttributeValueList`.

### Example

The following expression evaluates to true if the *Dimensions* attribute exists.

```
...
    "Dimensions": {
        ComparisonOperator: "NOT_NULL"
    }
...
```

## Comparison operators with one attribute value

- **EQ** - true if an attribute is equal to a value.

`AttributeValueList` can contain only one value of type String, Number, Binary, String Set, Number Set, or Binary Set. If an item contains a value of a different type than the one specified in the request, the value does not match. For example, the string "3" is not equal to the number 3. Also, the number 3 is not equal to the number set [3, 2, 1].

- **NE** - true if an attribute is not equal to a value.

`AttributeValueList` can contain only one value of type String, Number, Binary, String Set, Number Set, or Binary Set. If an item contains a value of a different type than the one specified in the request, the value does not match.

- **LE** - true if an attribute is less than or equal to a value.

`AttributeValueList` can contain only one value of type String, Number, or Binary (not a set). If an item contains an `AttributeValue` of a different type than the one specified in the request, the value does not match.

- **LT** - true if an attribute is less than a value.

`AttributeValueList` can contain only one value of type String, Number, or Binary (not a set). If an item contains a value of a different type than the one specified in the request, the value does not match.

- **GE** - true if an attribute is greater than or equal to a value.

`AttributeValueList` can contain only one value of type String, Number, or Binary (not a set). If an item contains a value of a different type than the one specified in the request, the value does not match.

- **GT** - true if an attribute is greater than a value.

`AttributeValueList` can contain only one value of type String, Number, or Binary (not a set). If an item contains a value of a different type than the one specified in the request, the value does not match.

- **CONTAINS** - true if a value is present within a set, or if one value contains another.

`AttributeValueList` can contain only one value of type String, Number, or Binary (not a set). If the target attribute of the comparison is a String, then the operator checks for a substring match. If the target attribute of the comparison is Binary, then the operator looks for a subsequence of the target that matches the input. If the target attribute of the comparison is a set, then the operator evaluates to true if it finds an exact match with any member of the set.

- **NOT\_CONTAINS** - true if a value is *not* present within a set, or if one value does not contain another value.

`AttributeValueList` can contain only one value of type String, Number, or Binary (not a set). If the target attribute of the comparison is a String, then the operator checks for the absence of a substring match. If the target attribute of the comparison is Binary, then the operator checks for the absence of

a subsequence of the target that matches the input. If the target attribute of the comparison is a set, then the operator evaluates to true if it *does not* find an exact match with any member of the set.

- **BEGINS\_WITH** - true if the first few characters of an attribute match the provided value. Do not use this operator for comparing numbers.

`AttributeValueList` can contain only one value of type String or Binary (not a Number or a set). The target attribute of the comparison must be a String or Binary (not a Number or a set).

Use these operators to compare an attribute with a value. You must specify an `AttributeValueList` consisting of a single value. For most of the operators, this value must be a scalar; however, the `EQ` and `NE` operators also support sets.

### Examples

The following expressions evaluate to true if:

- A product's price is greater than 100.

```
...
    "Price": {
        ComparisonOperator: "GT",
        AttributeValueList: [ {"N":"100"} ]
    }
...
```

- A product category begins with "Bo".

```
...
    "ProductCategory": {
        ComparisonOperator: "BEGINS_WITH",
        AttributeValueList: [ {"S":"Bo"} ]
    }
...
```

- A product is available in either red, green, or black:

```
...
    "Color": {
        ComparisonOperator: "EQ",
        AttributeValueList: [
            [ {"S":"Black"}, {"S":"Red"}, {"S":"Green"} ]
        ]
    }
...
```

#### Note

When comparing set data types, the order of the elements does not matter. DynamoDB will return only the items with the same set of values, regardless of the order in which you specify them in your request.

## Comparison operators with two attribute values

- **BETWEEN** - true if a value is between a lower bound and an upper bound, endpoints inclusive.

`AttributeValueList` must contain two elements of the same type, either String, Number, or Binary (not a set). A target attribute matches if the target value is greater than, or equal to, the first element and less than, or equal to, the second element. If an item contains a value of a different type than the one specified in the request, the value does not match.

Use this operator to determine if an attribute value is within a range. The `AttributeValueList` must contain two scalar elements of the same type - String, Number, or Binary.

#### Example

The following expression evaluates to true if a product's price is between 100 and 200.

```

...
    "Price": {
        ComparisonOperator: "BETWEEN",
        AttributeValueList: [ {"N":"100"}, {"N":"200"} ]
    }
...

```

### Comparison operators with *n* attribute values

- `IN` - true if a value is equal to any of the values in an enumerated list. Only scalar values are supported in the list, not sets. The target attribute must be of the same type and exact value in order to match.

`AttributeValueList` can contain one or more elements of type String, Number, or Binary (not a set). These attributes are compared against an existing non-set type attribute of an item. If *any* elements of the input set are present in the item attribute, the expression evaluates to true.

`AttributeValueList` can contain one or more values of type String, Number, or Binary (not a set). The target attribute of the comparison must be of the same type and exact value to match. A String never matches a String set.

Use this operator to determine whether the supplied value is within an enumerated list. You can specify any number of scalar values in `AttributeValueList`, but they all must be of the same data type.

#### Example

The following expression evaluates to true if the value for `Id` is 201, 203, or 205.

```

...
    "Id": {
        ComparisonOperator: "IN",
        AttributeValueList: [ {"N":"201"}, {"N":"203"}, {"N":"205"} ]
    }
...

```

### Using multiple conditions

DynamoDB lets you combine multiple conditions to form complex expressions. You do this by providing at least two expressions, with an optional [ConditionalOperator \(p. 1322\)](#).

By default, when you specify more than one condition, *all* of the conditions must evaluate to true in order for the entire expression to evaluate to true. In other words, an implicit AND operation takes place.

#### Example

The following expression evaluates to true if a product is a book which has at least 600 pages. Both of the conditions must evaluate to true, since they are implicitly ANDed together.

```

...
    "ProductCategory": {
        ComparisonOperator: "EQ",
        AttributeValueList: [ {"S":"Book"} ]
    },
    "PageCount": {

```

```

        ComparisonOperator: "GE",
        AttributeValueList: [ {"N":600} ]
    }
...

```

You can use [ConditionalOperator \(p. 1322\)](#) to clarify that an *AND* operation will take place. The following example behaves in the same manner as the previous one.

```

...
    "ConditionalOperator" : "AND",
    "ProductCategory": {
        "ComparisonOperator": "EQ",
        "AttributeValueList": [ {"N":"Book"} ]
    },
    "PageCount": {
        "ComparisonOperator": "GE",
        "AttributeValueList": [ {"N":600} ]
    }
...

```

You can also set `ConditionalOperator` to *OR*, which means that *at least one* of the conditions must evaluate to true.

### Example

The following expression evaluates to true if a product is a mountain bike, if it is a particular brand name, or if its price is greater than 100.

```

...
    ConditionalOperator : "OR",
    "BicycleType": {
        "ComparisonOperator": "EQ",
        "AttributeValueList": [ {"S":"Mountain"} ]
    },
    "Brand": {
        "ComparisonOperator": "EQ",
        "AttributeValueList": [ {"S":"Brand-Company A"} ]
    },
    "Price": {
        "ComparisonOperator": "GT",
        "AttributeValueList": [ {"N":100} ]
    }
...

```

### Note

In a complex expression, the conditions are processed in order, from the first condition to the last.

You cannot use both AND and OR in a single expression.

## Other conditional operators

In previous releases of DynamoDB, the `Expected` parameter behaved differently for conditional writes. Each item in the `Expected` map represented an attribute name for DynamoDB to check, along with the following:

- `Value` — a value to compare against the attribute.
- `Exists` — determine whether the value exists prior to attempting the operation.

The `Value` and `Exists` options continue to be supported in DynamoDB; however, they only let you test for an equality condition, or whether an attribute exists. We recommend that you use

`ComparisonOperator` and `AttributeValueList` instead, because these options let you construct a much wider range of conditions.

### Example

A `DeleteItem` can check to see whether a book is no longer in publication, and only delete it if this condition is true. Here is an AWS CLI example using a legacy condition:

```
aws dynamodb delete-item \
    --table-name ProductCatalog \
    --key '{
        "Id": {"N":"600"}
    }' \
    --expected '{
        "InPublication": {
            "Exists": true,
            "Value": {"BOOL":false}
        }
}'
```

The following example does the same thing, but does not use a legacy condition:

```
aws dynamodb delete-item \
    --table-name ProductCatalog \
    --key '{
        "Id": {"N":"600"}
    }' \
    --expected '{
        "InPublication": {
            "ComparisonOperator": "EQ",
            "AttributeValueList": [ {"BOOL":false} ]
        }
}'
```

### Example

A `PutItem` operation can protect against overwriting an existing item with the same primary key attributes. Here is an example using a legacy condition:

```
aws dynamodb put-item \
    --table-name ProductCatalog \
    --item '{
        "Id": {"N":"500"},
        "Title": {"S":"Book 500 Title"}
    }' \
    --expected '{
        "Id": { "Exists": false }
    }'
```

The following example does the same thing, but does not use a legacy condition:

```
aws dynamodb put-item \
    --table-name ProductCatalog \
    --item '{
        "Id": {"N":"500"},
        "Title": {"S":"Book 500 Title"}
    }' \
    --expected '{
        "Id": { "ComparisonOperator": "NULL" }
    }'
```

}

**Note**

For conditions in the `Expected` map, do not use the legacy `Value` and `Exists` options together with `ComparisonOperator` and `AttributeValueList`. If you do this, your conditional write will fail.

## Previous low-level API version (2011-12-05)

This section documents the operations available in the previous DynamoDB low-level API version (2011-12-05). This version of the low-level API is maintained for backward compatibility with existing applications.

New applications should use the current API version (2012-08-10). For more information, see [Low-level API reference \(p. 1253\)](#).

**Note**

We recommend that you migrate your applications to the latest API version (2012-08-10), since new DynamoDB features will not be backported to the previous API version.

**Topics**

- [BatchGetItem \(p. 1336\)](#)
- [BatchWriteItem \(p. 1341\)](#)
- [CreateTable \(p. 1346\)](#)
- [DeleteItem \(p. 1351\)](#)
- [DeleteTable \(p. 1355\)](#)
- [DescribeTables \(p. 1358\)](#)
- [.GetItem \(p. 1361\)](#)
- [ListTables \(p. 1364\)](#)
- [PutItem \(p. 1366\)](#)
- [Query \(p. 1371\)](#)
- [Scan \(p. 1380\)](#)
- [UpdateItem \(p. 1390\)](#)
- [UpdateTable \(p. 1396\)](#)

## BatchGetItem

**Important**

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

### Description

The `BatchGetItem` operation returns the attributes for multiple items from multiple tables using their primary keys. The maximum number of items that can be retrieved for a single operation is 100. Also, the number of items retrieved is constrained by a 1 MB size limit. If the response size limit is exceeded or a partial result is returned because the table's provisioned throughput is exceeded, or because of an internal processing failure, DynamoDB returns an `UnprocessedKeys` value so you can retry the operation starting with the next item to get. DynamoDB automatically adjusts the number of items returned per page to enforce this limit. For example, even if you ask to retrieve 100 items, but each individual item is 50 KB in size, the system returns 20 items and an appropriate `UnprocessedKeys`

value so you can get the next page of results. If desired, your application can include its own logic to assemble the pages of results into one set.

If no items could be processed because of insufficient provisioned throughput on each of the tables involved in the request, DynamoDB returns a `ProvisionedThroughputExceeded` exception.

#### Note

By default, `BatchGetItem` performs eventually consistent reads on every table in the request. You can set the `ConsistentRead` parameter to `true`, on a per-table basis, if you want consistent reads instead.

`BatchGetItem` fetches items in parallel to minimize response latencies.

When designing your application, keep in mind that DynamoDB does not guarantee how attributes are ordered in the returned response. Include the primary key values in the `AttributesToGet` for the items in your request to help parse the response by item.

If the requested items do not exist, nothing is returned in the response for those items. Requests for non-existent items consume the minimum read capacity units according to the type of read.

For more information, see [DynamoDB Item sizes and formats \(p. 290\)](#).

## Requests

### Syntax

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.BatchGetItem
content-type: application/x-amz-json-1.0

{"RequestItems":
  {"Table1":
    {"Keys":
      [{"HashKeyElement": {"S": "KeyValue1"}, "RangeKeyElement": {"N": "KeyValue2"}},
       {"HashKeyElement": {"S": "KeyValue3"}, "RangeKeyElement": {"N": "KeyValue4"}},
       {"HashKeyElement": {"S": "KeyValue5"}, "RangeKeyElement": {"N": "KeyValue6"}},
      "AttributesToGet": ["AttributeName1", "AttributeName2", "AttributeName3"]},
     "Table2":
      {"Keys":
        [{"HashKeyElement": {"S": "KeyValue4"}},
         {"HashKeyElement": {"S": "KeyValue5"}},
        "AttributesToGet": ["AttributeName4", "AttributeName5", "AttributeName6"]}
      }
    }
}
```

Name	Description	Required
<code>RequestItems</code>	A container of the table name and corresponding items to get by primary key. While requesting items, each table name can be invoked only once per operation.  Type: String  Default: None	Yes
<code>Table</code>	The name of the table containing the items to get. The entry is simply a string	Yes

Name	Description	Required
	<p>specifying an existing table with no label.</p> <p>Type: String</p> <p>Default: None</p>	
Table:Keys	<p>The primary key values that define the items in the specified table. For more information about primary keys, see <a href="#">Primary key (p. 6)</a>.</p> <p>Type: Keys</p>	Yes
Table:AttributesToGet	<p>Array of Attribute names within the specified table. If attribute names are not specified then all attributes will be returned. If some attributes are not found, they will not appear in the result.</p> <p>Type: Array</p>	No
Table:ConsistentRead	<p>If set to true, then a consistent read is issued, otherwise eventually consistent is used.</p> <p>Type: Boolean</p>	No

## Responses

### Syntax

```

HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 855

{"Responses":
  {"Table1":
    {"Items":
      [{"AttributeName1": {"S": "AttributeValue"}, "AttributeName2": {"N": "AttributeValue"}, "AttributeName3": {"SS": ["AttributeValue", "AttributeValue", "AttributeValue"]}}, {"AttributeName1": {"S": "AttributeValue"}, "AttributeName2": {"S": "AttributeValue"}, "AttributeName3": {"NS": ["AttributeValue", "AttributeValue", "AttributeValue"]}}], "ConsumedCapacityUnits":1},
   "Table2":
    {"Items":
      [{"AttributeName1": {"S": "AttributeValue"}, "AttributeName2": {"N": "AttributeValue"}, "AttributeName3": {"SS": ["AttributeValue", "AttributeValue", "AttributeValue"]}}]
    }
  }
}

```

```
{
    "AttributeName1": {"S": "AttributeValue"},  

    "AttributeName2": {"S": "AttributeValue"},  

    "AttributeName3": {"NS": ["AttributeValue", "AttributeValue", "AttributeValue"]}  

    ]},  

    "ConsumedCapacityUnits":1}  

},  

"UnprocessedKeys":  

{ "Table3":  

{ "Keys":  

[ { "HashKeyElement": {"S": "KeyValue1"}, "RangeKeyElement": {"N": "KeyValue2"} },  

{ "HashKeyElement": {"S": "KeyValue3"}, "RangeKeyElement": {"N": "KeyValue4"} },  

{ "HashKeyElement": {"S": "KeyValue5"}, "RangeKeyElement": {"N": "KeyValue6"} } ],  

"AttributesToGet": ["AttributeName1", "AttributeName2", "AttributeName3"]  

}  

}
}
```

Name	Description
Responses	Table names and the respective item attributes from the tables.  Type: Map
Table	The name of the table containing the items. The entry is simply a string specifying the table with no label.  Type: String
Items	Container for the attribute names and values meeting the operation parameters.  Type: Map of attribute names to and their data types and values.
ConsumedCapacityUnits	The number of read capacity units consumed, for each table. This value shows the number applied toward your provisioned throughput. Requests for non-existent items consume the minimum read capacity units, depending on the type of read. For more information see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a> .  Type: Number
UnprocessedKeys	Contains an array of tables and their respective keys that were not processed with the current response, possibly due to reaching a limit on the response size. The UnprocessedKeys value is in the same form as a RequestItems parameter (so the value can be provided directly to a subsequent BatchGetItem operation). For more information, see the above RequestItems parameter.  Type: Array
UnprocessedKeys: Table: Keys	The primary key attribute values that define the items and the attributes associated with the items. For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .

Name	Description
	Type: Array of attribute name-value pairs.
UnprocessedKeys: Table: AttributesToGet	Attribute names within the specified table. If attribute names are not specified then all attributes will be returned. If some attributes are not found, they will not appear in the result.
	Type: Array of attribute names.
UnprocessedKeys: Table: ConsistentRead	If set to true, then a consistent read is used for the specified table, otherwise an eventually consistent read is used.
	Type: Boolean.

## Special errors

Error	Description
ProvisionedThroughputExceededException	Your maximum allowed provisioned throughput has been exceeded.

## Examples

The following examples show an HTTP POST request and response using the BatchGetItem operation. For examples using the AWS SDK, see [Working with items and attributes \(p. 344\)](#).

### Sample request

The following sample requests attributes from two different tables.

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.BatchGetItem
content-type: application/x-amz-json-1.0
content-length: 409

{"RequestItems":
    {"comp1":
        {"Keys":
            [{"HashKeyElement": {"S": "Casey"}, "RangeKeyElement": {"N": "1319509152"}},
             {"HashKeyElement": {"S": "Dave"}, "RangeKeyElement": {"N": "1319509155"}},
             {"HashKeyElement": {"S": "Riley"}, "RangeKeyElement": {"N": "1319509158"}],
            "AttributesToGet": ["user", "status"]},
         "comp2":
        {"Keys":
            [{"HashKeyElement": {"S": "Julie"}, "RangeKeyElement": {"S": "Mingus"}}],
            "AttributesToGet": ["user", "friends"]}
    }
}
```

### Sample response

The following sample is the response.

```
HTTP/1.1 200 OK
x-amzn-RequestId: GTPQVRM4VJS792J1UFJTKUBVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 373
Date: Fri, 02 Sep 2011 23:07:39 GMT

{"Responses": {
    "comp1": {
        "Items": [
            {"status":{"S":"online"}, "user":{"S":"Casey"}},
            {"status":{"S":"working"}, "user":{"S":"Riley"}},
            {"status":{"S":"running"}, "user":{"S":"Dave"}},
            "ConsumedCapacityUnits":1.5,
        ],
        "comp2": {
            "Items": [
                {"friends":{"SS":["Elisabeth", "Peter"]}, "user":{"S":"Mingus"}},
                {"friends":{"SS":["Dave", "Peter"]}, "user":{"S":"Julie"}},
                "ConsumedCapacityUnits":1
            ],
            "UnprocessedKeys":{}
        }
    }
}
```

## BatchWriteItem

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

This operation enables you to put or delete several items across multiple tables in a single call.

To upload one item, you can use `PutItem`, and to delete one item, you can use `DeleteItem`. However, when you want to upload or delete large amounts of data, such as uploading large amounts of data from Amazon EMR (Amazon EMR) or migrating data from another database in to DynamoDB, `BatchWriteItem` offers an efficient alternative.

If you use languages such as Java, you can use threads to upload items in parallel. This adds complexity in your application to handle the threads. Other languages don't support threading. For example, if you are using PHP, you must upload or delete items one at a time. In both situations, `BatchWriteItem` provides an alternative where the specified put and delete operations are processed in parallel, giving you the power of the thread pool approach without having to introduce complexity in your application.

Note that each individual put and delete specified in a `BatchWriteItem` operation costs the same in terms of consumed capacity units. However, because `BatchWriteItem` performs the specified operations in parallel, you get lower latency. Delete operations on non-existent items consume 1 write capacity unit. For more information about consumed capacity units, see [Working with tables and data in DynamoDB \(p. 279\)](#).

When using `BatchWriteItem`, note the following limitations:

- **Maximum operations in a single request**—You can specify a total of up to 25 put or delete operations; however, the total request size cannot exceed 1 MB (the HTTP payload).
- You can use the `BatchWriteItem` operation only to put and delete items. You cannot use it to update existing items.
- **Not an atomic operation**—Individual operations specified in a `BatchWriteItem` are atomic; however `BatchWriteItem` as a whole is a "best-effort" operation and not an atomic operation. That is,

in a `BatchWriteItem` request, some operations might succeed and others might fail. The failed operations are returned in an `UnprocessedItems` field in the response. Some of these failures might be because you exceeded the provisioned throughput configured for the table or a transient failure such as a network error. You can investigate and optionally resend the requests. Typically, you call `BatchWriteItem` in a loop and in each iteration check for unprocessed items, and submit a new `BatchWriteItem` request with those unprocessed items.

- **Does not return any items**—The `BatchWriteItem` is designed for uploading large amounts of data efficiently. It does not provide some of the sophistication offered by `PutItem` and `DeleteItem`. For example, `DeleteItem` supports the `ReturnValues` field in your request body to request the deleted item in the response. The `BatchWriteItem` operation does not return any items in the response.
- Unlike `PutItem` and `DeleteItem`, `BatchWriteItem` does not allow you to specify conditions on individual write requests in the operation.
- Attribute values must not be null; string and binary type attributes must have lengths greater than zero; and set type attributes must not be empty. Requests that have empty values will be rejected with a `ValidationException`.

DynamoDB rejects the entire batch write operation if any one of the following is true:

- If one or more tables specified in the `BatchWriteItem` request does not exist.
- If primary key attributes specified on an item in the request does not match the corresponding table's primary key schema.
- If you try to perform multiple operations on the same item in the same `BatchWriteItem` request. For example, you cannot put and delete the same item in the same `BatchWriteItem` request.
- If the total request size exceeds the 1 MB request size (the HTTP payload) limit.
- If any individual item in a batch exceeds the 64 KB item size limit.

## Requests

### Syntax

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.BatchGetItem
content-type: application/x-amz-json-1.0

{
    "RequestItems" : RequestItems
}

RequestItems
{
    "TableName1" : [ Request, Request, ... ],
    "TableName2" : [ Request, Request, ... ],
    ...
}

Request ::= 
PutRequest | DeleteRequest

PutRequest ::= 
{
    "PutRequest" : {
        "Item" : {
            "Attribute-Name1" : Attribute-Value,
            "Attribute-Name2" : Attribute-Value,
            ...
        }
    }
}
```

```

        }
    }

DeleteRequest ::= 
{
    "DeleteRequest" : {
        "Key" : PrimaryKey-Value
    }
}

PrimaryKey-Value ::= HashTypePK | HashAndRangeTypePK

HashTypePK ::=
{
    "HashKeyElement" : Attribute-Value
}

HashAndRangeTypePK
{
    "HashKeyElement" : Attribute-Value,
    "RangeKeyElement" : Attribute-Value,
}

Attribute-Value ::= String | Numeric | Binary | StringSet | NumericSet | BinarySet

Numeric ::=
{
    "N": "Number"
}

String ::=
{
    "S": "String"
}

Binary ::=
{
    "B": "Base64 encoded binary data"
}

StringSet ::=
{
    "SS": [ "String1", "String2", ... ]
}

NumberSet ::=
{
    "NS": [ "Number1", "Number2", ... ]
}

BinarySet ::=
{
    "BS": [ "Binary1", "Binary2", ... ]
}

```

In the request body, the `RequestItems` JSON object describes the operations that you want to perform. The operations are grouped by tables. You can use `BatchWriteItem` to update or delete several items across multiple tables. For each specific write request, you must identify the type of request (`PutItem`, `DeleteItem`) followed by detail information about the operation.

- For a `PutRequest`, you provide the item, that is, a list of attributes and their values.
- For a `DeleteRequest`, you provide the primary key name and value.

## Responses

### Syntax

The following is the syntax of the JSON body returned in the response.

```
{  
    "Responses" : ConsumedCapacityUnitsByTable  
    "UnprocessedItems" : RequestItems  
}  
  
ConsumedCapacityUnitsByTable  
{  
    "TableName1" : { "ConsumedCapacityUnits" : NumericValue },  
    "TableName2" : { "ConsumedCapacityUnits" : NumericValue },  
    ...  
}  
  
RequestItems  
This syntax is identical to the one described in the JSON syntax in the request.
```

## Special errors

No errors specific to this operation.

## Examples

The following example shows an HTTP POST request and the response of a `BatchWriteItem` operation. The request specifies the following operations on the Reply and the Thread tables:

- Put an item and delete an item from the Reply table
- Put an item into the Thread table

For examples using the AWS SDK, see [Working with items and attributes \(p. 344\)](#).

### Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.BatchGetItem  
content-type: application/x-amz-json-1.0  
  
{  
    "RequestItems":{  
        "Reply": [  
            {  
                "PutRequest":{  
                    "Item":{  
                        "ReplyDateTime":{  
                            "S":"2012-04-03T11:04:47.034Z"  
                        },  
                        "Id":{  
                            "S":"DynamoDB#DynamoDB Thread 5"  
                        }  
                    }  
                }  
            },  
            {  
                "DeleteRequest":{  
                    "Key":{  
                        "Id":{  
                            "S":"DynamoDB#DynamoDB Thread 5"  
                        }  
                    }  
                }  
            }  
        ]  
    }  
}
```

```

        "Key": {
            "HashKeyElement": {
                "S": "DynamoDB#DynamoDB Thread 4"
            },
            "RangeKeyElement": {
                "S": "oops - accidental row"
            }
        }
    },
    "Thread": [
        {
            "PutRequest": {
                "Item": {
                    "ForumName": {
                        "S": "DynamoDB"
                    },
                    "Subject": {
                        "S": "DynamoDB Thread 5"
                    }
                }
            }
        }
    ]
}

```

## Sample response

The following example response shows a put operation on both the Thread and Reply tables succeeded and a delete operation on the Reply table failed (for reasons such as throttling that is caused when you exceed the provisioned throughput on the table). Note the following in the JSON response:

- The `Responses` object shows one capacity unit was consumed on both the Thread and Reply tables as a result of the successful put operation on each of these tables.
- The `UnprocessedItems` object shows the unsuccessful delete operation on the Reply table. You can then issue a new `BatchWriteItem` call to address these unprocessed requests.

```

HTTP/1.1 200 OK
x-amzn-RequestId: G8M9ANLOE5QA26AEUHJKJE0ASBVV4KQNSO5AEMVJF66Q9ASUAAJG
Content-Type: application/x-amz-json-1.0
Content-Length: 536
Date: Thu, 05 Apr 2012 18:22:09 GMT

{
    "Responses": {
        "Thread": {
            "ConsumedCapacityUnits": 1.0
        },
        "Reply": {
            "ConsumedCapacityUnits": 1.0
        }
    },
    "UnprocessedItems": {
        "Reply": [
            {
                "DeleteRequest": {
                    "Key": {
                        "HashKeyElement": {
                            "S": "DynamoDB#DynamoDB Thread 4"
                        },

```

```

        "RangeKeyElement":{  

            "S":"oops - accidental row"  

        }  

    }  

}  

}  

}
}
```

## CreateTable

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

The `CreateTable` operation adds a new table to your account.

The table name must be unique among those associated with the AWS Account issuing the request, and the AWS region that receives the request (such as `dynamodb.us-west-2.amazonaws.com`). Each DynamoDB endpoint is entirely independent. For example, if you have two tables called "MyTable," one in `dynamodb.us-west-2.amazonaws.com` and one in `dynamodb.us-west-1.amazonaws.com`, they are completely independent and do not share any data.

The `CreateTable` operation triggers an asynchronous workflow to begin creating the table. DynamoDB immediately returns the state of the table (`CREATING`) until the table is in the `ACTIVE` state. Once the table is in the `ACTIVE` state, you can perform data plane operations.

Use the [DescribeTables \(p. 1358\)](#) operation to check the status of the table.

## Requests

### Syntax

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.CreateTable  
content-type: application/x-amz-json-1.0  
  
{"TableName":"Table1",  
 "KeySchema":  
     {"HashKeyElement": {"AttributeName": "AttributeName1", "AttributeType": "S"},  
      "RangeKeyElement": {"AttributeName": "AttributeName2", "AttributeType": "N"}},  
 "ProvisionedThroughput": {"ReadCapacityUnits": 5, "WriteCapacityUnits": 10}  
}
```

Name	Description	Required
TableName	<p>The name of the table to create.</p> <p>Allowed characters are a-z, A-Z, 0-9, '_' (underscore), '-' (dash), and '.' (dot). Names can be between 3 and 255 characters long.</p>	Yes

Name	Description	Required
	Type: String	
KeySchema	<p>The primary key (simple or composite) structure for the table. A name-value pair for the <code>HashKeyElement</code> is required, and a name-value pair for the <code>RangeKeyElement</code> is optional (only required for composite primary keys). For more information about primary keys, see <a href="#">Primary key (p. 6)</a>.</p> <p>Primary key element names can be between 1 and 255 characters long with no character restrictions.</p> <p>Possible values for the <code>AttributeType</code> are "S" (string), "N" (numeric), or "B" (binary).</p> <p>Type: Map of <code>HashKeyElement</code>, or <code>HashKeyElement</code> and <code>RangeKeyElement</code> for a composite primary key.</p>	Yes
ProvisionedThroughput	<p>New throughput for the specified table, consisting of values for <code>ReadCapacityUnits</code> and <code>WriteCapacityUnits</code>. For details, see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a>.</p> <p><b>Note</b> For current maximum/minimum values, see <a href="#">Service, account, and table quotas in Amazon DynamoDB (p. 1242)</a>.</p> <p>Type: Array</p>	Yes

Name	Description	Required
ProvisionedThroughput: ReadCapacityUnits	<p>Sets the minimum number of consistent ReadCapacityUnits consumed per second for the specified table before DynamoDB balances the load with other operations.</p> <p>Eventually consistent read operations require less effort than a consistent read operation, so a setting of 50 consistent ReadCapacityUnits per second provides 100 eventually consistent ReadCapacityUnits per second.</p> <p>Type: Number</p>	Yes
ProvisionedThroughput: WriteCapacityUnits	<p>Sets the minimum number of WriteCapacityUnits consumed per second for the specified table before DynamoDB balances the load with other operations.</p> <p>Type: Number</p>	Yes

## Responses

### Syntax

```

HTTP/1.1 200 OK
x-amzn-RequestId: CSOC7TJPLR0OKIRLG0HVAICUFVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 311
Date: Tue, 12 Jul 2011 21:31:03 GMT

{
    "TableDescription": {
        "CreationDateTime": 1.310506263362E9,
        "KeySchema": [
            {"HashKeyElement": {"AttributeName": "AttributeName1", "AttributeType": "S"}, "RangeKeyElement": {"AttributeName": "AttributeName2", "AttributeType": "N"}},
            {"ProvisionedThroughput": {"ReadCapacityUnits": 5, "WriteCapacityUnits": 10}, "TableName": "Table1", "TableStatus": "CREATING"}
        ]
    }
}

```

Name	Description
TableDescription	A container for the table properties.

Name	Description
<code>CreationDateTime</code>	Date when the table was created in <a href="#">UNIX epoch time</a> .  Type: Number
<code>KeySchema</code>	The primary key (simple or composite) structure for the table. A name-value pair for the <code>HashKeyElement</code> is required, and a name-value pair for the <code>RangeKeyElement</code> is optional (only required for composite primary keys). For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .  Type: Map of <code>HashKeyElement</code> , or <code>HashKeyElement</code> and <code>RangeKeyElement</code> for a composite primary key.
<code>ProvisionedThroughput</code>	Throughput for the specified table, consisting of values for <code>ReadCapacityUnits</code> and <code>WriteCapacityUnits</code> . See <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a> .  Type: Array
<code>ProvisionedThroughput</code> <code>:ReadCapacityUnits</code>	The minimum number of <code>ReadCapacityUnits</code> consumed per second before DynamoDB balances the load with other operations  Type: Number
<code>ProvisionedThroughput</code> <code>:WriteCapacityUnits</code>	The minimum number of <code>ReadCapacityUnits</code> consumed per second before <code>WriteCapacityUnits</code> balances the load with other operations  Type: Number
<code>TableName</code>	The name of the created table.  Type: String
<code>TableStatus</code>	The current state of the table ( <code>CREATING</code> ). Once the table is in the <code>ACTIVE</code> state, you can put data in it.  Use the <a href="#">DescribeTables (p. 1358)</a> API to check the status of the table.  Type: String

## Special errors

Error	Description
ResourceInUseException	Attempt to recreate an already existing table.
LimitExceededException	The number of simultaneous table requests (cumulative number of tables in the CREATING, DELETING or UPDATING state) exceeds the maximum allowed.  <b>Note</b> For current maximum/minimum values, see <a href="#">Service, account, and table quotas in Amazon DynamoDB (p. 1242)</a> .

## Examples

The following example creates a table with a composite primary key containing a string and a number. For examples using the AWS SDK, see [Working with tables and data in DynamoDB \(p. 279\)](#).

### Sample request

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.CreateTable
content-type: application/x-amz-json-1.0

{"TableName": "comp-table",
 "KeySchema":
    {"HashKeyElement": {"AttributeName": "user", "AttributeType": "S"},
     "RangeKeyElement": {"AttributeName": "time", "AttributeType": "N"}},
 "ProvisionedThroughput": {"ReadCapacityUnits": 5, "WriteCapacityUnits": 10}
}
```

### Sample response

```
HTTP/1.1 200 OK
x-amzn-RequestId: CSOC7TJPLR00OKIRLGOHVAICUFVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 311
Date: Tue, 12 Jul 2011 21:31:03 GMT

{"TableDescription":
    {"CreationDateTime": 1.310506263362E9,
     "KeySchema":
        {"HashKeyElement": {"AttributeName": "user", "AttributeType": "S"},
         "RangeKeyElement": {"AttributeName": "time", "AttributeType": "N"}},
     "ProvisionedThroughput": {"ReadCapacityUnits": 5, "WriteCapacityUnits": 10},
     "TableName": "comp-table",
     "TableStatus": "CREATING"
   }
}
```

## Related actions

- [DescribeTables \(p. 1358\)](#)
- [DeleteTable \(p. 1355\)](#)

## DeleteItem

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

Deletes a single item in a table by primary key. You can perform a conditional delete operation that deletes the item if it exists, or if it has an expected attribute value.

### Note

If you specify `DeleteItem` without attributes or values, all the attributes for the item are deleted.

Unless you specify conditions, the `DeleteItem` is an idempotent operation; running it multiple times on the same item or attribute does *not* result in an error response.

Conditional deletes are useful for only deleting items and attributes if specific conditions are met. If the conditions are met, DynamoDB performs the delete. Otherwise, the item is not deleted.

You can perform the expected conditional check on one attribute per operation.

## Requests

### Syntax

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.DeleteItem  
content-type: application/x-amz-json-1.0  
  
{ "TableName": "Table1",  
  "Key":  
    { "HashKeyElement": { "S": "AttributeValue1" }, "RangeKeyElement":  
      { "N": "AttributeValue2" } },  
    "Expected": { "AttributeName3": { "Value": { "S": "AttributeValue3" } } },  
    "ReturnValues": "ALL_OLD"  
}
```

Name	Description	Required
TableName	The name of the table containing the item to delete.  Type: String	Yes
Key	The primary key that defines the item. For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .	Yes

Name	Description	Required
	Type: Map of HashKeyElement to its value and RangeKeyElement to its value.	
Expected	<p>Designates an attribute for a conditional delete. The <code>Expected</code> parameter allows you to provide an attribute name, and whether or not DynamoDB should check to see if the attribute has a particular value before deleting it.</p> <p>Type: Map of attribute names.</p>	No
Expected:AttributeName	<p>The name of the attribute for the conditional put.</p> <p>Type: String</p>	No

Name	Description	Required
Expected:AttributeName: ExpectedAttributeValue	<p>Use this parameter to specify whether or not a value already exists for the attribute name-value pair.</p> <p>The following JSON notation deletes the item if the "Color" attribute doesn't exist for that item:</p> <pre>"Expected" : {"Color":{"Exists":false}}</pre> <p>The following JSON notation checks to see if the attribute with name "Color" has an existing value of "Yellow" before deleting the item:</p> <pre>"Expected" : {"Color":{"Exists":true}, {"Value":{"S":"Yellow"}}}</pre> <p>By default, if you use the <code>Expected</code> parameter and provide a <code>Value</code>, DynamoDB assumes the attribute exists and has a current value to be replaced. So you don't have to specify <code>{"Exists":true}</code>, because it is implied. You can shorten the request to:</p> <pre>"Expected" : {"Color":{"Value":{"S":"Yellow"}}}</pre> <p><b>Note</b>  If you specify <code>{"Exists":true}</code> without an attribute value to check, DynamoDB returns an error.</p>	No

Name	Description	Required
ReturnValues	<p>Use this parameter if you want to get the attribute name-value pairs before they were deleted. Possible parameter values are <code>NONE</code> (default) or <code>ALL_OLD</code>. If <code>ALL_OLD</code> is specified, the content of the old item is returned. If this parameter is not provided or is <code>NONE</code>, nothing is returned.</p> <p>Type: String</p>	No

## Responses

### Syntax

```

HTTP/1.1 200 OK
x-amzn-RequestId: CSOC7TJPLR00OKIRLGOHVAICUFVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 353
Date: Tue, 12 Jul 2011 21:31:03 GMT

{
    "Attributes": [
        {"AttributeName3": {"S": ["AttributeValue3", "AttributeValue4", "AttributeValue5"]}},
        {"AttributeName2": {"S": "AttributeValue2"}},
        {"AttributeName1": {"N": "AttributeValue1"}}
    ],
    "ConsumedCapacityUnits": 1
}

```

Name	Description
Attributes	<p>If the <code>ReturnValues</code> parameter is provided as <code>ALL_OLD</code> in the request, DynamoDB returns an array of attribute name-value pairs (essentially, the deleted item). Otherwise, the response contains an empty set.</p> <p>Type: Array of attribute name-value pairs.</p>
ConsumedCapacityUnits	<p>The number of write capacity units consumed by the operation. This value shows the number applied toward your provisioned throughput. Delete requests on non-existent items consume 1 write capacity unit. For more information see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a>.</p> <p>Type: Number</p>

## Special errors

Error	Description
ConditionalCheckFailedException	Conditional check failed. An expected attribute value was not found.

## Examples

### Sample request

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.DeleteItem  
content-type: application/x-amz-json-1.0  
  
{"TableName":"comp-table",  
 "Key":  
     {"HashKeyElement":{"S":"Mingus"}, "RangeKeyElement":{"N":"200"}},  
 "Expected":  
     {"status":{"Value":{"S":"shopping"}},  
 "ReturnValues":"ALL_OLD"  
}
```

### Sample response

```
HTTP/1.1 200 OK  
x-amzn-RequestId: U9809LI6BBFJA5N2ROTBOP017JVV4KQNSO5AEMVJF66Q9ASUAAJG  
content-type: application/x-amz-json-1.0  
content-length: 353  
Date: Tue, 12 Jul 2011 22:31:23 GMT  
  
{"Attributes":  
    {"friends":{"SS":["Dooley", "Ben", "Daisy"]},  
     "status":{"S":"shopping"},  
     "time":{"N":"200"},  
     "user":{"S":"Mingus"}  
},  
"ConsumedCapacityUnits":1  
}
```

## Related actions

- [PutItem \(p. 1366\)](#)

## DeleteTable

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

The `DeleteTable` operation deletes a table and all of its items. After a `DeleteTable` request, the specified table is in the `DELETING` state until DynamoDB completes the deletion. If the table is in the `ACTIVE` state, you can delete it. If a table is in `CREATING` or `UPDATING` states, then DynamoDB returns a `ResourceInUseException` error. If the specified table does not exist, DynamoDB returns a `ResourceNotFoundException`. If table is already in the `DELETING` state, no error is returned.

### Note

DynamoDB might continue to accept data plane operation requests, such as `GetItem` and `PutItem`, on a table in the `DELETING` state until the table deletion is complete.

Tables are unique among those associated with the AWS Account issuing the request, and the AWS region that receives the request (such as `dynamodb.us-west-1.amazonaws.com`). Each DynamoDB endpoint is entirely independent. For example, if you have two tables called "MyTable," one in `dynamodb.us-west-2.amazonaws.com` and one in `dynamodb.us-west-1.amazonaws.com`, they are completely independent and do not share any data; deleting one does not delete the other.

Use the [DescribeTables \(p. 1358\)](#) operation to check the status of the table.

## Requests

### Syntax

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.DeleteTable
content-type: application/x-amz-json-1.0

{"TableName": "Table1"}
```

Name	Description	Required
TableName	The name of the table to delete.  Type: String	Yes

## Responses

### Syntax

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4HONCKIVH1BFUDQ1U68CTG3N27VV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 311
Date: Sun, 14 Aug 2011 22:56:22 GMT

{"TableDescription":
  {"CreationDateTime": 1.313362508446E9,
   "KeySchema": [
     {"HashKeyElement": {"AttributeName": "user", "AttributeType": "S"},
      "RangeKeyElement": {"AttributeName": "time", "AttributeType": "N"}},
     {"ProvisionedThroughput": {"ReadCapacityUnits": 10, "WriteCapacityUnits": 10},
      "TableName": "Table1"},
```

```

        "TableStatus": "DELETING"
    }
}

```

Name	Description
TableDescription	A container for the table properties.
CreationDateTime	Date when the table was created.  Type: Number
KeySchema	The primary key (simple or composite) structure for the table. A name-value pair for the HashKeyElement is required, and a name-value pair for the RangeKeyElement is optional (only required for composite primary keys). For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .  Type: Map of HashKeyElement, or HashKeyElement and RangeKeyElement for a composite primary key.
ProvisionedThroughput	Throughput for the specified table, consisting of values for ReadCapacityUnits and WriteCapacityUnits. See <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a> .
ProvisionedThroughput: ReadCapacityUnits	The minimum number of ReadCapacityUnits consumed per second for the specified table before DynamoDB balances the load with other operations.  Type: Number
ProvisionedThroughput: WriteCapacityUnits	The minimum number of WriteCapacityUnits consumed per second for the specified table before DynamoDB balances the load with other operations.  Type: Number
TableName	The name of the deleted table.  Type: String
TableStatus	The current state of the table (DELETING). Once the table is deleted, subsequent requests for the table return resource not found.  Use the <a href="#">DescribeTables (p. 1358)</a> operation to check the status of the table.  Type: String

## Special errors

Error	Description
ResourceInUseException	Table is in state CREATING or UPDATING and can't be deleted.

## Examples

### Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.DeleteTable
content-type: application/x-amz-json-1.0
content-length: 40

{"TableName":"favorite-movies-table"}
```

### Sample response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 4HONCKIVH1BFUDQ1U68CTG3N27VV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 160
Date: Sun, 14 Aug 2011 17:20:03 GMT

{"TableDescription":
    {"CreationDateTime":1.313362508446E9,
     "KeySchema":
        {"HashKeyElement":{"AttributeName":"name","AttributeType":"S"}},
     "TableName":"favorite-movies-table",
     "TableStatus":"DELETING"
}
```

## Related actions

- [CreateTable \(p. 1346\)](#)
- [DescribeTables \(p. 1358\)](#)

## DescribeTables

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

*For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).*

### Description

Returns information about the table, including the current status of the table, the primary key schema and when the table was created. DescribeTable results are eventually consistent. If you use DescribeTable too early in the process of creating a table, DynamoDB returns a ResourceNotFoundException. If you

use `DescribeTable` too early in the process of updating a table, the new values might not be immediately available.

## Requests

### Syntax

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.DescribeTable
content-type: application/x-amz-json-1.0

{"TableName": "Table1"}
```

Name	Description	Required
TableName	The name of the table to describe.  Type: String	Yes

## Responses

### Syntax

```
HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
Content-Length: 543

{"Table":
    {"CreationDateTime":1.309988345372E9,
    "ItemCount":1,
    "KeySchema":
        {"HashKeyElement":{"AttributeName":"AttributeName1","AttributeType":"S"},
         "RangeKeyElement":{"AttributeName":"AttributeName2","AttributeType":"N"}},
    "ProvisionedThroughput":{"LastIncreaseDateTime": Date, "LastDecreaseDateTime": Date,
    "ReadCapacityUnits":10,"WriteCapacityUnits":10},
    "TableName": "Table1",
    "TableSizeBytes":1,
    "TableStatus": "ACTIVE"
    }
}
```

Name	Description
Table	Container for the table being described.  Type: String
CreationDateTime	Date when the table was created in <a href="#">UNIX epoch time</a> .
ItemCount	Number of items in the specified table. DynamoDB updates this value approximately

Name	Description
	every six hours. Recent changes might not be reflected in this value.  Type: Number
KeySchema	The primary key (simple or composite) structure for the table. A name-value pair for the HashKeyElement is required, and a name-value pair for the RangeKeyElement is optional (only required for composite primary keys). The maximum hash key size is 2048 bytes. The maximum range key size is 1024 bytes. Both limits are enforced separately (i.e. you can have a combined hash + range 2048 + 1024 key). For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .
ProvisionedThroughput	Throughput for the specified table, consisting of values for LastIncreaseDateTime (if applicable), LastDecreaseDateTime (if applicable), ReadCapacityUnits and WriteCapacityUnits. If the throughput for the table has never been increased or decreased, DynamoDB does not return values for those elements. See <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a> .  Type: Array
TableName	The name of the requested table.  Type: String
TableSizeBytes	Total size of the specified table, in bytes. DynamoDB updates this value approximately every six hours. Recent changes might not be reflected in this value.  Type: Number
TableStatus	The current state of the table (CREATING, ACTIVE, DELETING or UPDATING). Once the table is in the ACTIVE state, you can add data.

## Special errors

No errors are specific to this operation.

## Examples

The following examples show an HTTP POST request and response using the DescribeTable operation for a table named "comp-table". The table has a composite primary key.

### Sample Request

```
// This header is abbreviated.
```

```
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.DescribeTable  
content-type: application/x-amz-json-1.0  
  
{"TableName":"users"}
```

## Sample response

```
HTTP/1.1 200  
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375  
content-type: application/x-amz-json-1.0  
content-length: 543  
  
{"Table":  
    {"CreationDateTime":1.309988345372E9,  
     "ItemCount":23,  
     "KeySchema":  
         {"HashKeyElement":{"AttributeName":"user","AttributeType":"S"},  
          "RangeKeyElement":{"AttributeName":"time","AttributeType":"N"}},  
     "ProvisionedThroughput":{"LastIncreaseDateTime": 1.309988345384E9,  
      "ReadCapacityUnits":10,"WriteCapacityUnits":10},  
     "TableName":"users",  
     "TableSizeBytes":949,  
     "TableStatus":"ACTIVE"  
    }  
}
```

## Related actions

- [CreateTable \(p. 1346\)](#)
- [DeleteTable \(p. 1355\)](#)
- [ListTables \(p. 1364\)](#)

## GetItem

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

The GetItem operation returns a set of Attributes for an item that matches the primary key. If there is no matching item, GetItem does not return any data.

The GetItem operation provides an eventually consistent read by default. If eventually consistent reads are not acceptable for your application, use ConsistentRead. Although this operation might take longer than a standard read, it always returns the last updated value. For more information, see [Read consistency \(p. 17\)](#).

## Requests

### Syntax

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.
```

```
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.GetItem
content-type: application/x-amz-json-1.0

{"TableName": "Table1",
 "Key": {
     "HashKeyElement": {"S": "AttributeValue1"},
     "RangeKeyElement": {"N": "AttributeValue2"}
 },
 "AttributesToGet": ["AttributeName3", "AttributeName4"],
 "ConsistentRead": Boolean
}
```

Name	Description	Required
TableName	The name of the table containing the requested item.  Type: String	Yes
Key	The primary key values that define the item. For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .  Type: Map of HashKeyElement to its value and RangeKeyElement to its value.	Yes
AttributesToGet	Array of Attribute names. If attribute names are not specified then all attributes will be returned. If some attributes are not found, they will not appear in the result.  Type: Array	No
ConsistentRead	If set to true, then a consistent read is issued, otherwise eventually consistent is used.  Type: Boolean	No

## Responses

### Syntax

```
HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 144

{"Item": {
    "AttributeName3": {"S": "AttributeValue3"},
    "AttributeName4": {"N": "AttributeValue4"},
    "AttributeName5": {"B": "dmFsdWU="}
},
"ConsumedCapacityUnits": 0.5
```

}

Name	Description
Item	Contains the requested attributes.  Type: Map of attribute name-value pairs.
ConsumedCapacityUnits	The number of read capacity units consumed by the operation. This value shows the number applied toward your provisioned throughput. Requests for non-existent items consume the minimum read capacity units, depending on the type of read. For more information see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a> .  Type: Number

## Special errors

No errors specific to this operation.

## Examples

For examples using the AWS SDK, see [Working with items and attributes \(p. 344\)](#).

### Sample request

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.GetItem
content-type: application/x-amz-json-1.0

{"TableName":"comptable",
 "Key": {
     "HashKeyElement": {"S": "Julie"},
     "RangeKeyElement": {"N": "1307654345"}},
 "AttributesToGet": ["status", "friends"],
 "ConsistentRead": true
}
```

### Sample response

Notice the ConsumedCapacityUnits value is 1, because the optional parameter ConsistentRead is set to true. If ConsistentRead is set to false (or not specified) for the same request, the response is eventually consistent and the ConsumedCapacityUnits value would be 0.5.

```
HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 72

{"Item": {
    "friends": {"SS": ["Lynda, Aaron"]},
    "status": {"S": "online"}
},
```

```
"ConsumedCapacityUnits": 1
}
```

## ListTables

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

Returns an array of all the tables associated with the current account and endpoint.

Each DynamoDB endpoint is entirely independent. For example, if you have two tables called "MyTable," one in dynamodb.us-west-2.amazonaws.com and one in dynamodb.us-east-1.amazonaws.com, they are completely independent and do not share any data. The ListTables operation returns all of the table names associated with the account making the request, for the endpoint that receives the request.

## Requests

### Syntax

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.ListTables
content-type: application/x-amz-json-1.0

{"ExclusiveStartTableName":"Table1","Limit":3}
```

The ListTables operation, by default, requests all of the table names associated with the account making the request, for the endpoint that receives the request.

Name	Description	Required
Limit	A number of maximum table names to return.  Type: Integer	No
ExclusiveStartTableName	The name of the table that starts the list. If you already ran a ListTables operation and received an LastEvaluatedTableName value in the response, use that value here to continue the list.  Type: String	No

## Responses

### Syntax

```
HTTP/1.1 200 OK
```

```
x-amzn-RequestId: S1LEK2DPQP8OJNHVHL8OU2M7KRVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 81
Date: Fri, 21 Oct 2011 20:35:38 GMT

{"TableNames": ["Table1", "Table2", "Table3"], "LastEvaluatedTableName": "Table3"}
```

Name	Description
<code>TableNames</code>	The names of the tables associated with the current account at the current endpoint.  Type: Array
<code>LastEvaluatedTableName</code>	The name of the last table in the current list, only if some tables for the account and endpoint have not been returned. This value does not exist in a response if all table names are already returned. Use this value as the <code>ExclusiveStartTableName</code> in a new request to continue the list until all the table names are returned.  Type: String

## Special errors

No errors are specific to this operation.

## Examples

The following examples show an HTTP POST request and response using the `ListTables` operation.

### Sample request

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.ListTables
content-type: application/x-amz-json-1.0

{"ExclusiveStartTableName": "comp2", "Limit": 3}
```

### Sample response

```
HTTP/1.1 200 OK
x-amzn-RequestId: S1LEK2DPQP8OJNHVHL8OU2M7KRVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 81
Date: Fri, 21 Oct 2011 20:35:38 GMT

{"LastEvaluatedTableName": "comp5", "TableNames": ["comp3", "comp4", "comp5"]}
```

## Related actions

- [DescribeTables \(p. 1358\)](#)

- [CreateTable \(p. 1346\)](#)
- [DeleteTable \(p. 1355\)](#)

## PutItem

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

Creates a new item, or replaces an old item with a new item (including all the attributes). If an item already exists in the specified table with the same primary key, the new item completely replaces the existing item. You can perform a conditional put (insert a new item if one with the specified primary key doesn't exist), or replace an existing item if it has certain attribute values.

Attribute values may not be null; string and binary type attributes must have lengths greater than zero; and set type attributes must not be empty. Requests with empty values will be rejected with a `ValidationException`.

### Note

To ensure that a new item does not replace an existing item, use a conditional put operation with `Exists` set to `false` for the primary key attribute, or attributes.

For more information about using `PutItem`, see [Working with items and attributes \(p. 344\)](#).

## Requests

### Syntax

```
// This header is abbreviated.
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.PutItem
content-type: application/x-amz-json-1.0

{"TableName":"Table1",
 "Item": {
     "AttributeName1":{"S":"AttributeValue1"},
     "AttributeName2":{"N":"AttributeValue2"},
     "AttributeName5":{"B":"dmFsdWU="}
 },
 "Expected":{"AttributeName3":{"Value": {"S":"AttributeValue"}, "Exists":Boolean}},
 "ReturnValues":"ReturnValuesConstant"}
```

Name	Description	Required
TableName	The name of the table to contain the item.  Type: String	Yes
Item	A map of the attributes for the item, and must include the primary key values that define the item. Other attribute name-value pairs can be provided for	Yes

Name	Description	Required
	<p>the item. For more information about primary keys, see <a href="#">Primary key (p. 6)</a>.</p> <p>Type: Map of attribute names to attribute values.</p>	
Expected	<p>Designates an attribute for a conditional put. The <code>Expected</code> parameter allows you to provide an attribute name, and whether or not DynamoDB should check to see if the attribute value already exists; or if the attribute value exists and has a particular value before changing it.</p> <p>Type: Map of an attribute names to an attribute value, and whether it exists.</p>	No
<code>Expected:AttributeName</code>	<p>The name of the attribute for the conditional put.</p> <p>Type: String</p>	No

Name	Description	Required
Expected:AttributeName: ExpectedAttributeValue	<p>Use this parameter to specify whether or not a value already exists for the attribute name-value pair.</p> <p>The following JSON notation replaces the item if the "Color" attribute doesn't already exist for that item:</p> <pre>"Expected" : {"Color":{"Exists":false}}</pre> <p>The following JSON notation checks to see if the attribute with name "Color" has an existing value of "Yellow" before replacing the item:</p> <pre>"Expected" : {"Color":{"Exists":true, "Value":{"S":"Yellow"}}}</pre> <p>By default, if you use the <code>Expected</code> parameter and provide a <code>Value</code>, DynamoDB assumes the attribute exists and has a current value to be replaced. So you don't have to specify <code>{"Exists":true}</code>, because it is implied. You can shorten the request to:</p> <pre>"Expected" : {"Color":{"Value":{"S":"Yellow"}}}</pre> <p><b>Note</b>  If you specify <code>{"Exists":true}</code> without an attribute value to check, DynamoDB returns an error.</p>	No

Name	Description	Required
ReturnValues	<p>Use this parameter if you want to get the attribute name-value pairs before they were updated with the PutItem request. Possible parameter values are <code>NONE</code> (default) or <code>ALL_OLD</code>. If <code>ALL_OLD</code> is specified, and PutItem overwrote an attribute name-value pair, the content of the old item is returned. If this parameter is not provided or is <code>NONE</code>, nothing is returned.</p> <p>Type: String</p>	No

## Responses

### Syntax

The following syntax example assumes the request specified a `ReturnValues` parameter of `ALL_OLD`; otherwise, the response has only the `ConsumedCapacityUnits` element.

```

HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 85

{"Attributes":
  {"AttributeName3":{"S":"AttributeValue3"},
   "AttributeName2":{"SS":"AttributeValue2"},
   "AttributeName1":{"SS":"AttributeValue1"},
  },
  "ConsumedCapacityUnits":1
}

```

Name	Description
Attributes	<p>Attribute values before the put operation, but only if the <code>ReturnValues</code> parameter is specified as <code>ALL_OLD</code> in the request.</p> <p>Type: Map of attribute name-value pairs.</p>
ConsumedCapacityUnits	<p>The number of write capacity units consumed by the operation. This value shows the number applied toward your provisioned throughput. For more information see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a>.</p> <p>Type: Number</p>

## Special errors

Error	Description
ConditionalCheckFailedException	Conditional check failed. An expected attribute value was not found.
ResourceNotFoundException	The specified item or attribute was not found.

## Examples

For examples using the AWS SDK, see [Working with items and attributes \(p. 344\)](#).

### Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.PutItem
content-type: application/x-amz-json-1.0

{"TableName": "comp5",
 "Item":
  {"time": {"N": "300"}, "feeling": {"S": "not surprised"}, "user": {"S": "Riley"}},
 "Expected":
  {"feeling": {"Value": {"S": "surprised"}, "Exists": true}}
 "ReturnValues": "ALL_OLD"
}
```

### Sample response

```
HTTP/1.1 200
x-amzn-RequestId: 8952fa74-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 84

{"Attributes": {"feeling": {"S": "surprised"}, "time": {"N": "300"}, "user": {"S": "Riley"}}, "ConsumedCapacityUnits": 1}
```

## Related actions

- [UpdateItem \(p. 1390\)](#)
- [DeleteItem \(p. 1351\)](#)
- [GetItem \(p. 1361\)](#)
- [BatchGetItem \(p. 1336\)](#)

# Query

## Important

This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

A Query operation gets the values of one or more items and their attributes by primary key (Query is only available for hash-and-range primary key tables). You must provide a specific HashKeyValue, and can narrow the scope of the query using comparison operators on the RangeKeyValue of the primary key. Use the ScanIndexForward parameter to get results in forward or reverse order by range key.

Queries that do not return results consume the minimum read capacity units according to the type of read.

## Note

If the total number of items meeting the query parameters exceeds the 1MB limit, the query stops and results are returned to the user with a LastEvaluatedKey to continue the query in a subsequent operation. Unlike a Scan operation, a Query operation never returns an empty result set *and* a LastEvaluatedKey. The LastEvaluatedKey is only provided if the results exceed 1MB, or if you have used the Limit parameter.

The result can be set for a consistent read using the ConsistentRead parameter.

## Requests

### Syntax

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.Query  
content-type: application/x-amz-json-1.0  
  
{"TableName": "Table1",  
 "Limit": 2,  
 "ConsistentRead": true,  
 "HashKeyValue": {"S": "AttributeValue1"},  
 "RangeKeyCondition": {"AttributeValueList":  
 [{"N": "AttributeValue2"}], "ComparisonOperator": "GT"},  
 "ScanIndexForward": true,  
 "ExclusiveStartKey": {  
 "HashKeyElement": {"S": "AttributeName1"},  
 "RangeKeyElement": {"N": "AttributeName2"}  
 },  
 "AttributesToGet": ["AttributeName1", "AttributeName2", "AttributeName3"]}  
}
```

Name	Description	Required
TableName	The name of the table containing the requested items.  Type: String	Yes
AttributesToGet	Array of Attribute names. If attribute names are not specified then all attributes will	No

Name	Description	Required
	<p>be returned. If some attributes are not found, they will not appear in the result.</p> <p>Type: Array</p>	
Limit	<p>The maximum number of items to return (not necessarily the number of matching items). If DynamoDB processes the number of items up to the limit while querying the table, it stops the query and returns the matching values up to that point, and a <code>LastEvaluatedKey</code> to apply in a subsequent operation to continue the query. Also, if the result set size exceeds 1MB before DynamoDB hits this limit, it stops the query and returns the matching values, and a <code>LastEvaluatedKey</code> to apply in a subsequent operation to continue the query.</p> <p>Type: Number</p>	No
ConsistentRead	<p>If set to <code>true</code>, then a consistent read is issued, otherwise eventually consistent is used.</p> <p>Type: Boolean</p>	No
Count	<p>If set to <code>true</code>, DynamoDB returns a total number of items that match the query parameters, instead of a list of the matching items and their attributes. You can apply the <code>Limit</code> parameter to count-only queries.</p> <p>Do not set <code>Count</code> to <code>true</code> while providing a list of <code>AttributesToGet</code>; otherwise, DynamoDB returns a validation error. For more information, see <a href="#">Counting the items in the results (p. 432)</a>.</p> <p>Type: Boolean</p>	No

Name	Description	Required
HashKeyValue	<p>Attribute value of the hash component of the composite primary key.</p> <p>Type: String, Number, or Binary</p>	Yes
RangeKeyCondition	<p>A container for the attribute values and comparison operators to use for the query. A query request does not require a RangeKeyCondition. If you provide only the HashKeyValue, DynamoDB returns all items with the specified hash key element value.</p> <p>Type: Map</p>	No
RangeKeyCondition: AttributeValueList	<p>The attribute values to evaluate for the query parameters. The AttributeValueList contains one attribute value, unless a BETWEEN comparison is specified. For the BETWEEN comparison, the AttributeValueList contains two attribute values.</p> <p>Type: A map of AttributeValue to a ComparisonOperator.</p>	No

Name	Description	Required
RangeKeyCondition: ComparisonOperator	<p>The criteria for evaluating the provided attributes, such as equals, greater-than, etc. The following are valid comparison operators for a Query operation.</p> <p><b>Note</b>  String value comparisons for greater than, equals, or less than are based on ASCII character code values. For example, a is greater than A, and aa is greater than B. For a list of code values, see <a href="http://en.wikipedia.org/wiki/ASCII#ASCII_printable_characters">http://en.wikipedia.org/wiki/ASCII#ASCII_printable_characters</a>.  For Binary, DynamoDB treats each byte of the binary data as unsigned when it compares binary values, for example when evaluating query expressions.</p> <p>Type: String or Binary</p>	No
	<p><b>EQ</b> : Equal.  For EQ, AttributeValueList can contain only one AttributeValue of type String, Number, or Binary (not a set). If an item contains an AttributeValue of a different type than the one specified in the request, the value does not match. For example, { "S" : "6" } does not equal { "N" : "6" }. Also, { "N" : "6" } does not equal { "NS" : [ "6", "2", "1" ] }.</p>	

Name	Description	Required
	<p><b>LE</b> : Less than or equal.</p> <p>For <b>LE</b>, <b>AttributeValueList</b> can contain only one <b>AttributeValue</b> of type String, Number, or Binary (not a set). If an item contains an <b>AttributeValue</b> of a different type than the one specified in the request, the value does not match. For example, <code>{ "S": "6" }</code> does not equal <code>{ "N": "6" }</code>. Also, <code>{ "N": "6" }</code> does not compare to <code>{ "NS": [ "6", "2", "1" ] }</code>.</p>	
	<p><b>LT</b> : Less than.</p> <p>For <b>LT</b>, <b>AttributeValueList</b> can contain only one <b>AttributeValue</b> of type String, Number, or Binary (not a set). If an item contains an <b>AttributeValue</b> of a different type than the one specified in the request, the value does not match. For example, <code>{ "S": "6" }</code> does not equal <code>{ "N": "6" }</code>. Also, <code>{ "N": "6" }</code> does not compare to <code>{ "NS": [ "6", "2", "1" ] }</code>.</p>	
	<p><b>GE</b> : Greater than or equal.</p> <p>For <b>GE</b>, <b>AttributeValueList</b> can contain only one <b>AttributeValue</b> of type String, Number, or Binary (not a set). If an item contains an <b>AttributeValue</b> of a different type than the one specified in the request, the value does not match. For example, <code>{ "S": "6" }</code> does not equal <code>{ "N": "6" }</code>. Also, <code>{ "N": "6" }</code> does not compare to <code>{ "NS": [ "6", "2", "1" ] }</code>.</p>	

Name	Description	Required
	<p>GT : Greater than.</p> <p>For GT, AttributeValueList can contain only one AttributeValue of type String, Number, or Binary (not a set). If an item contains an AttributeValue of a different type than the one specified in the request, the value does not match. For example, { "S": "6" } does not equal { "N": "6" }. Also, { "N": "6" } does not compare to { "NS": [ "6", "2", "1" ] }.</p>	
	<p>BEGINS_WITH : checks for a prefix.</p> <p>For BEGINS_WITH, AttributeValueList can contain only one AttributeValue of type String or Binary (not a Number or a set). The target attribute of the comparison must be a String or Binary (not a Number or a set).</p>	
	<p>BETWEEN : Greater than, or equal to, the first value and less than, or equal to, the second value.</p> <p>For BETWEEN, AttributeValueList must contain two AttributeValue elements of the same type, either String, Number, or Binary (not a set). A target attribute matches if the target value is greater than, or equal to, the first element and less than, or equal to, the second element. If an item contains an AttributeValue of a different type than the one specified in the request, the value does not match. For example, { "S": "6" } does not compare to { "N": "6" }. Also, { "N": "6" } does not compare to { "NS": [ "6", "2", "1" ] }.</p>	

Name	Description	Required
ScanIndexForward	<p>Specifies ascending or descending traversal of the index. DynamoDB returns results reflecting the requested order determined by the range key: If the data type is Number, the results are returned in numeric order; otherwise, the traversal is based on ASCII character code values.</p> <p>Type: Boolean</p> <p>Default is <code>true</code> (ascending).</p>	No
ExclusiveStartKey	<p>Primary key of the item from which to continue an earlier query. An earlier query might provide this value as the <code>LastEvaluatedKey</code> if that query operation was interrupted before completing the query; either because of the result set size or the <code>Limit</code> parameter. The <code>LastEvaluatedKey</code> can be passed back in a new query request to continue the operation from that point.</p> <p>Type: <code>HashKeyElement</code>, or <code>HashKeyElement</code> and <code>RangeKeyElement</code> for a composite primary key.</p>	No

## Responses

### Syntax

```

HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 308

{"Count":2,"Items":[{"AttributeNames1":{"S":"AttributeValue1"}, "AttributeNames2":{"N":"AttributeValue2"}, "AttributeNames3":{"S":"AttributeValue3"}}, {"AttributeNames1":{"S":"AttributeValue3"}, "AttributeNames2":{"N":"AttributeValue4"}, "AttributeNames3":{"S":"AttributeValue3"}, "AttributeNames5":{"B":"dmFsdWU="}}], "LastEvaluatedKey":{"HashKeyElement":{"AttributeValue3":"S"}, "RangeKeyElement":{"AttributeValue4":"N"}}
}

```

```
    "ConsumedCapacityUnits":1
}
```

Name	Description
Items	Item attributes meeting the query parameters.  Type: Map of attribute names to and their data types and values.
Count	Number of items in the response. For more information, see <a href="#">Counting the items in the results (p. 432)</a> .  Type: Number
LastEvaluatedKey	Primary key of the item where the query operation stopped, inclusive of the previous result set. Use this value to start a new operation excluding this value in the new request.  The LastEvaluatedKey is null when the entire query result set is complete (i.e. the operation processed the “last page”).  Type: HashKeyElement, or HashKeyElement and RangeKeyElement for a composite primary key.
ConsumedCapacityUnits	The number of read capacity units consumed by the operation. This value shows the number applied toward your provisioned throughput. For more information see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a> .  Type: Number

## Special errors

Error	Description
ResourceNotFoundException	The specified table was not found.

## Examples

For examples using the AWS SDK, see [Query operations in DynamoDB \(p. 428\)](#).

### Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.Query
content-type: application/x-amz-json-1.0
```

```
{"TableName": "1-hash-rangetable",
"Limit": 2,
"HashKeyValue": {"S": "John"},
"ScanIndexForward": false,
"ExclusiveStartKey": {
    "HashKeyElement": {"S": "John"},
    "RangeKeyElement": {"S": "The Matrix"}
}
}
```

## Sample response

```
HTTP/1.1 200
x-amzn-RequestId: 3647e778-71eb-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 308

{"Count": 2, "Items": [
    {"fans": {"SS": ["Jody", "Jake"]}, "name": {"S": "John"}, "rating": {"S": "***"}, "title": {"S": "The End"}},
    {"fans": {"SS": ["Jody", "Jake"]}, "name": {"S": "John"}, "rating": {"S": "***"}, "title": {"S": "The Beatles"}}
], "LastEvaluatedKey": {"HashKeyElement": {"S": "John"}, "RangeKeyElement": {"S": "The Beatles"}}, "ConsumedCapacityUnits": 1
}
```

## Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.Query
content-type: application/x-amz-json-1.0

{"TableName": "1-hash-rangetable",
"Limit": 2,
"HashKeyValue": {"S": "Airplane"},
"RangeKeyCondition": {"AttributeValueList": [{"N": "1980"}], "ComparisonOperator": "EQ"},
"ScanIndexForward": false
}
```

## Sample response

```
HTTP/1.1 200
x-amzn-RequestId: 8b9ee1ad-774c-11e0-9172-d954e38f553a
content-type: application/x-amz-json-1.0
content-length: 119

{"Count": 1, "Items": [
    {"fans": {"SS": ["Dave", "Aaron"]}, "name": {"S": "Airplane"}, "rating": {"S": "***"}, "year": {"N": "1980"}}
], "ConsumedCapacityUnits": 1
}
```

}

## Related actions

- [Scan \(p. 1380\)](#)

## Scan

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

The Scan operation returns one or more items and its attributes by performing a full scan of a table. Provide a ScanFilter to get more specific results.

### Note

If the total number of scanned items exceeds the 1MB limit, the scan stops and results are returned to the user with a LastEvaluatedKey to continue the scan in a subsequent operation. The results also include the number of items exceeding the limit. A scan can result in no table data meeting the filter criteria.

The result set is eventually consistent.

## Requests

### Syntax

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_2011205.Scan  
content-type: application/x-amz-json-1.0  
  
{ "TableName": "Table1",  
    "Limit": 2,  
    "ScanFilter":{  
        "AttributeName1": {"AttributeValueList":  
            [{"S": "AttributeValue"}], "ComparisonOperator": "EQ"}  
    },  
    "ExclusiveStartKey":{  
        "HashKeyElement": {"S": "AttributeName1"},  
        "RangeKeyElement": {"N": "AttributeName2"}  
    },  
    "AttributesToGet": ["AttributeName1", "AttributeName2", "AttributeName3"]  
}
```

Name	Description	Required
TableName	The name of the table containing the requested items.  Type: String	Yes
AttributesToGet	Array of Attribute names. If attribute names are not	No

Name	Description	Required
	<p>specified then all attributes will be returned. If some attributes are not found, they will not appear in the result.</p> <p>Type: Array</p>	
Limit	<p>The maximum number of items to evaluate (not necessarily the number of matching items). If DynamoDB processes the number of items up to the limit while processing the results, it stops and returns the matching values up to that point, and a <code>LastEvaluatedKey</code> to apply in a subsequent operation to continue retrieving items. Also, if the scanned data set size exceeds 1MB before DynamoDB reaches this limit, it stops the scan and returns the matching values up to the limit, and a <code>LastEvaluatedKey</code> to apply in a subsequent operation to continue the scan.</p> <p>Type: Number</p>	No
Count	<p>If set to <code>true</code>, DynamoDB returns a total number of items for the Scan operation, even if the operation has no matching items for the assigned filter. You can apply the Limit parameter to count-only scans.</p> <p>Do not set Count to <code>true</code> while providing a list of <code>AttributesToGet</code>, otherwise DynamoDB returns a validation error. For more information, see <a href="#">Counting the items in the results (p. 448)</a>.</p> <p>Type: Boolean</p>	No

Name	Description	Required
ScanFilter	<p>Evaluates the scan results and returns only the desired values. Multiple conditions are treated as "AND" operations: all conditions must be met to be included in the results.</p> <p>Type: A map of attribute names to values with comparison operators.</p>	No
ScanFilter:AttributeValueList	<p>The values and conditions to evaluate the scan results for the filter.</p> <p>Type: A map of AttributeValue to a Condition.</p>	No
ScanFilter:ComparisonOperator	<p>The criteria for evaluating the provided attributes, such as equals, greater-than, etc. The following are valid comparison operators for a scan operation.</p> <p><b>Note</b>  String value comparisons for greater than, equals, or less than are based on ASCII character code values. For example, a is greater than A, and aa is greater than B. For a list of code values, see <a href="http://en.wikipedia.org/wiki/ASCII#ASCII_printable_characters">http://en.wikipedia.org/wiki/ASCII#ASCII_printable_characters</a>. For Binary, DynamoDB treats each byte of the binary data as unsigned when it compares binary values, for example when evaluating query expressions.</p> <p>Type: String or Binary</p>	No

Name	Description	Required
	<p><b>EQ</b> : Equal.</p> <p>For <b>EQ</b>, <b>AttributeValueList</b> can contain only one <b>AttributeValue</b> of type String, Number, or Binary (not a set). If an item contains an <b>AttributeValue</b> of a different type than the one specified in the request, the value does not match. For example, <code>{ "S": "6" }</code> does not equal <code>{ "N": "6" }</code>. Also, <code>{ "N": "6" }</code> does not equal <code>{ "NS": [ "6", "2", "1" ] }</code>.</p>	
	<p><b>NE</b> : Not Equal.</p> <p>For <b>NE</b>, <b>AttributeValueList</b> can contain only one <b>AttributeValue</b> of type String, Number, or Binary (not a set). If an item contains an <b>AttributeValue</b> of a different type than the one specified in the request, the value does not match. For example, <code>{ "S": "6" }</code> does not equal <code>{ "N": "6" }</code>. Also, <code>{ "N": "6" }</code> does not equal <code>{ "NS": [ "6", "2", "1" ] }</code>.</p>	
	<p><b>LE</b> : Less than or equal.</p> <p>For <b>LE</b>, <b>AttributeValueList</b> can contain only one <b>AttributeValue</b> of type String, Number, or Binary (not a set). If an item contains an <b>AttributeValue</b> of a different type than the one specified in the request, the value does not match. For example, <code>{ "S": "6" }</code> does not equal <code>{ "N": "6" }</code>. Also, <code>{ "N": "6" }</code> does not compare to <code>{ "NS": [ "6", "2", "1" ] }</code>.</p>	

Name	Description	Required
	<p><b>LT</b> : Less than.</p> <p>For LT, AttributeValueList can contain only one AttributeValue of type String, Number, or Binary (not a set). If an item contains an AttributeValue of a different type than the one specified in the request, the value does not match. For example, { "S": "6" } does not equal { "N": "6" }. Also, { "N": "6" } does not compare to { "NS": [ "6", "2", "1" ] }.</p>	
	<p><b>GE</b> : Greater than or equal.</p> <p>For GE, AttributeValueList can contain only one AttributeValue of type String, Number, or Binary (not a set). If an item contains an AttributeValue of a different type than the one specified in the request, the value does not match. For example, { "S": "6" } does not equal { "N": "6" }. Also, { "N": "6" } does not compare to { "NS": [ "6", "2", "1" ] }.</p>	
	<p><b>GT</b> : Greater than.</p> <p>For GT, AttributeValueList can contain only one AttributeValue of type String, Number, or Binary (not a set). If an item contains an AttributeValue of a different type than the one specified in the request, the value does not match. For example, { "S": "6" } does not equal { "N": "6" }. Also, { "N": "6" } does not compare to { "NS": [ "6", "2", "1" ] }.</p>	
	<b>NOT_NULL</b> : Attribute exists.	
	<b>NULL</b> : Attribute does not exist.	

Name	Description	Required
	<p>CONTAINS : checks for a subsequence, or value in a set.</p> <p>For CONTAINS, AttributeValueList can contain only oneAttributeValue of type String, Number, or Binary (not a set). If the target attribute of the comparison is a String, then the operation checks for a substring match. If the target attribute of the comparison is Binary, then the operation looks for a subsequence of the target that matches the input. If the target attribute of the comparison is a set ("SS", "NS", or "BS"), then the operation checks for a member of the set (not as a substring).</p>	
	<p>NOT_CONTAINS : checks for absence of a subsequence, or absence of a value in a set.</p> <p>For NOT_CONTAINS, AttributeValueList can contain only oneAttributeValue of type String, Number, or Binary (not a set). If the target attribute of the comparison is a String, then the operation checks for the absence of a substring match. If the target attribute of the comparison is Binary, then the operation checks for the absence of a subsequence of the target that matches the input. If the target attribute of the comparison is a set ("SS", "NS", or "BS"), then the operation checks for the absence of a member of the set (not as a substring).</p>	

Name	Description	Required
	<p><code>BEGINS_WITH</code> : checks for a prefix.</p> <p>For <code>BEGINS_WITH</code>, <code>AttributeValueList</code> can contain only one <code>AttributeValue</code> of type String or Binary (not a Number or a set). The target attribute of the comparison must be a String or Binary (not a Number or a set).</p>	
	<p><code>IN</code> : checks for exact matches.</p> <p>For <code>IN</code>, <code>AttributeValueList</code> can contain more than one <code>AttributeValue</code> of type String, Number, or Binary (not a set). The target attribute of the comparison must be of the same type and exact value to match. A String never matches a String set.</p>	
	<p><code>BETWEEN</code> : Greater than, or equal to, the first value and less than, or equal to, the second value.</p> <p>For <code>BETWEEN</code>, <code>AttributeValueList</code> must contain two <code>AttributeValue</code> elements of the same type, either String, Number, or Binary (not a set). A target attribute matches if the target value is greater than, or equal to, the first element and less than, or equal to, the second element. If an item contains an <code>AttributeValue</code> of a different type than the one specified in the request, the value does not match. For example, <code>{"S": "6"}</code> does not compare to <code>{"N": "6"}</code>. Also, <code>{"N": "6"}</code> does not compare to <code>{"NS": ["6", "2", "1"]}</code>.</p>	

Name	Description	Required
ExclusiveStartKey	<p>Primary key of the item from which to continue an earlier scan. An earlier scan might provide this value if that scan operation was interrupted before scanning the entire table; either because of the result set size or the <code>Limit</code> parameter. The <code>LastEvaluatedKey</code> can be passed back in a new scan request to continue the operation from that point.</p> <p>Type: <code>HashKeyElement</code>, or <code>HashKeyElement</code> and <code>RangeKeyElement</code> for a composite primary key.</p>	No

## Responses

### Syntax

```

HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 229

{"Count":2,"Items":>[
    "AttributeName1":{"S":"AttributeValue1"},
    "AttributeName2":{"S":"AttributeValue2"},
    "AttributeName3":{"S":"AttributeValue3"}
],{
    "AttributeName1":{"S":"AttributeValue4"},
    "AttributeName2":{"S":"AttributeValue5"},
    "AttributeName3":{"S":"AttributeValue6"},
    "AttributeName5":{"B":"dmFsdWU="}
},
"LastEvaluatedKey":
    {"HashKeyElement":{"S":"AttributeName1"},
     "RangeKeyElement":{"N":"AttributeName2"}},
"ConsumedCapacityUnits":1,
"ScannedCount":2
}

```

Name	Description
Items	<p>Container for the attributes meeting the operation parameters.</p> <p>Type: Map of attribute names to and their data types and values.</p>
Count	Number of items in the response. For more information, see <a href="#">Counting the items in the results (p. 448)</a> .

Name	Description
	Type: Number
ScannedCount	<p>Number of items in the complete scan before any filters are applied. A high ScannedCount value with few, or no, Count results indicates an inefficient Scan operation. For more information, see <a href="#">Counting the items in the results (p. 448)</a>.</p> <p>Type: Number</p>
LastEvaluatedKey	<p>Primary key of the item where the scan operation stopped. Provide this value in a subsequent scan operation to continue the operation from that point.</p> <p>The LastEvaluatedKey is null when the entire scan result set is complete (i.e. the operation processed the “last page”).</p>
ConsumedCapacityUnits	<p>The number of read capacity units consumed by the operation. This value shows the number applied toward your provisioned throughput. For more information see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a>.</p> <p>Type: Number</p>

## Special errors

Error	Description
ResourceNotFoundException	The specified table was not found.

## Examples

For examples using the AWS SDK, see [Working with scans in DynamoDB \(p. 445\)](#).

### Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.Scan
content-type: application/x-amz-json-1.0

{"TableName":"1-hash-rangetable","ScanFilter":{}}
```

### Sample response

```
HTTP/1.1 200
x-amzn-RequestId: 4e8a5fa9-71e7-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 465
```

```
{
  "Count":4,
  "Items":[{
    "date":{"S":"1980"},
    "fans":{"SS":["Dave","Aaron"]},
    "name":{"S":"Airplane"},
    "rating":{"S":"****"}
  },{
    "date":{"S":"1999"},
    "fans":{"SS":["Ziggy","Laura","Dean"]},
    "name":{"S":"Matrix"},
    "rating":{"S":"*****"}
  },{
    "date":{"S":"1976"},
    "fans":{"SS":["Riley"]},
    "name":{"S":"The Shaggy D.A."},
    "rating":{"S":"**"}
  },{
    "date":{"S":"1985"},
    "fans":{"SS":["Fox","Lloyd"]},
    "name":{"S":"Back To The Future"},
    "rating":{"S":"****"}
  }],
  "ConsumedCapacityUnits":0.5,
  "ScannedCount":4
}
```

## Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.Scan
content-type: application/x-amz-json-1.0
content-length: 125

{"TableName":"comp5",
 "ScanFilter":
  {"time":
   {"AttributeValueList":[{"N":"400"}],
    "ComparisonOperator":"GT"
   }
 }
```

## Sample response

```
HTTP/1.1 200 OK
x-amzn-RequestId: PD1CQK9QCTERLTJP20VALJ60TRVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 262
Date: Mon, 15 Aug 2011 16:52:02 GMT

{
  "Count":2,
  "Items":[
    {"friends":{"SS":["Dave","Ziggy","Barrie"]},
     "status":{"S":"chatting"},
     "time":{"N":"2000"},
     "user":{"S":"Casey"}},
    {"friends":{"SS":["Dave","Ziggy","Barrie"]},
     "status":{"S":"chatting"},
     "time":{"N":"2000"},
     "user":{"S":"Freddy"}}
  ],
  "ConsumedCapacityUnits":0.5,
  "ScannedCount":4
}
```

```
}
```

## Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.Scan
content-type: application/x-amz-json-1.0

{"TableName":"comp5",
 "Limit":2,
 "ScanFilter":
 {"time":
 {"AttributeValueList":[{"N":"400"}],
 "ComparisonOperator":"GT"
 },
 "ExclusiveStartKey":
 {"HashKeyElement":{"S":"Freddy"}, "RangeKeyElement":{"N":"2000"}}
}
```

## Sample response

```
HTTP/1.1 200 OK
x-amzn-RequestId: PD1CQK9QCTERLTJP20VALJ60TRVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 232
Date: Mon, 15 Aug 2011 16:52:02 GMT

{"Count":1,
 "Items":[
 {"friends":{"SS":["Jane", "James", "John"]},
 "status":{"S":"exercising"},
 "time":{"N":"2200"},
 "user":{"S":"Roger"}}
 ],
 "LastEvaluatedKey":{"HashKeyElement":{"S":"Riley"}, "RangeKeyElement":{"N":"250"}},
 "ConsumedCapacityUnits":0.5
 "ScannedCount":2
}
```

## Related actions

- [Query \(p. 1371\)](#)
- [BatchGetItem \(p. 1336\)](#)

## UpdateItem

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

Edits an existing item's attributes. You can perform a conditional update (insert a new attribute name-value pair if it doesn't exist, or replace an existing name-value pair if it has certain expected attribute values).

**Note**

You cannot update the primary key attributes using UpdateItem. Instead, delete the item and use PutItem to create a new item with new attributes.

The UpdateItem operation includes an `Action` parameter, which defines how to perform the update. You can put, delete, or add attribute values.

Attribute values may not be null; string and binary type attributes must have lengths greater than zero; and set type attributes must not be empty. Requests with empty values will be rejected with a `ValidationException`.

If an existing item has the specified primary key:

- **PUT**— Adds the specified attribute. If the attribute exists, it is replaced by the new value.
- **DELETE**— If no value is specified, this removes the attribute and its value. If a set of values is specified, then the values in the specified set are removed from the old set. So if the attribute value contains [a,b,c] and the delete action contains [a,c], then the final attribute value is [b]. The type of the specified value must match the existing value type. Specifying an empty set is not valid.
- **ADD**— Only use the add action for numbers or if the target attribute is a set (including string sets). ADD does not work if the target attribute is a single string value or a scalar binary value. The specified value is added to a numeric value (incrementing or decrementing the existing numeric value) or added as an additional value in a string set. If a set of values is specified, the values are added to the existing set. For example if the original set is [1,2] and supplied value is [3], then after the add operation the set is [1,2,3], not [4,5]. An error occurs if an Add action is specified for a set attribute and the attribute type specified does not match the existing set type.

If you use ADD for an attribute that does not exist, the attribute and its values are added to the item.

If no item matches the specified primary key:

- **PUT**— Creates a new item with specified primary key. Then adds the specified attribute.
- **DELETE**— Nothing happens.
- **ADD**— Creates an item with supplied primary key and number (or set of numbers) for the attribute value. Not valid for a string or a binary type.

**Note**

If you use ADD to increment or decrement a number value for an item that doesn't exist before the update, DynamoDB uses 0 as the initial value. Also, if you update an item using ADD to increment or decrement a number value for an attribute that doesn't exist before the update (but the item does) DynamoDB uses 0 as the initial value. For example, you use ADD to add +3 to an attribute that did not exist before the update. DynamoDB uses 0 for the initial value, and the value after the update is 3.

For more information about using this operation, see [Working with items and attributes \(p. 344\)](#).

## Requests

### Syntax

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.UpdateItem  
content-type: application/x-amz-json-1.0  
  
{"TableName": "Table1",
```

```

    "Key": {
        "HashKeyElement": {"S": "AttributeValue1"},
        "RangeKeyElement": {"N": "AttributeValue2"}},
        "AttributeUpdates": {"AttributeName3": {"Value": {"S": "AttributeValue3_New"}, "Action": "PUT"}},
        "Expected": {"AttributeName3": {"Value": {"S": "AttributeValue3_Current"}}, "ReturnValues": "ReturnValuesConstant"}
    }
}

```

Name	Description	Required
TableName	The name of the table containing the item to update.  Type: String	Yes
Key	The primary key that defines the item. For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .  Type: Map of HashKeyElement to its value and RangeKeyElement to its value.	Yes
AttributeUpdates	Map of attribute name to the new value and action for the update. The attribute names specify the attributes to modify, and cannot contain any primary key attributes.  Type: Map of attribute name, value, and an action for the attribute update.	
AttributeUpdates:Action	Specifies how to perform the update. Possible values: PUT (default), ADD or DELETE. The semantics are explained in the UpdateItem description.  Type: String  Default: PUT	No
Expected	Designates an attribute for a conditional update. The Expected parameter allows you to provide an attribute name, and whether or not DynamoDB should check to see if the attribute value already exists; or if the attribute value exists and has a particular value before changing it.  Type: Map of attribute names.	No

Name	Description	Required
Expected:AttributeName	<p>The name of the attribute for the conditional put.</p> <p>Type: String</p>	No
Expected:AttributeName: ExpectedAttributeValue	<p>Use this parameter to specify whether or not a value already exists for the attribute name-value pair.</p> <p>The following JSON notation updates the item if the "Color" attribute doesn't already exist for that item:</p> <div style="border: 1px solid black; padding: 5px;"> <pre>"Expected" : {"Color":{"Exists":false}}</pre> </div> <p>The following JSON notation checks to see if the attribute with name "Color" has an existing value of "Yellow" before updating the item:</p> <div style="border: 1px solid black; padding: 5px;"> <pre>"Expected" : {"Color":{"Exists":true}, {"Value":{"S":"Yellow"}}}</pre> </div> <p>By default, if you use the Expected parameter and provide a Value, DynamoDB assumes the attribute exists and has a current value to be replaced. So you don't have to specify {"Exists":true}, because it is implied. You can shorten the request to:</p> <div style="border: 1px solid black; padding: 5px;"> <pre>"Expected" : {"Color":{"Value": {"S":"Yellow"}}}</pre> </div> <p><b>Note</b> If you specify {"Exists":true} without an attribute value to check, DynamoDB returns an error.</p>	No

Name	Description	Required
ReturnValues	<p>Use this parameter if you want to get the attribute name-value pairs before they were updated with the <code>UpdateItem</code> request. Possible parameter values are <code>NONE</code> (default) or <code>ALL_OLD</code>, <code>UPDATED_OLD</code>, <code>ALL_NEW</code> or <code>UPDATED_NEW</code>. If <code>ALL_OLD</code> is specified, and <code>UpdateItem</code> overwrote an attribute name-value pair, the content of the old item is returned. If this parameter is not provided or is <code>NONE</code>, nothing is returned. If <code>ALL_NEW</code> is specified, then all the attributes of the new version of the item are returned. If <code>UPDATED_NEW</code> is specified, then the new versions of only the updated attributes are returned.</p> <p>Type: String</p>	No

## Responses

### Syntax

The following syntax example assumes the request specified a `ReturnValues` parameter of `ALL_OLD`; otherwise, the response has only the `ConsumedCapacityUnits` element.

```

HTTP/1.1 200
x-amzn-RequestId: 8966d095-71e9-11e0-a498-71d736f27375
content-type: application/x-amz-json-1.0
content-length: 140

{"Attributes": {
    "AttributeName1": {"S": "AttributeValue1"},
    "AttributeName2": {"S": "AttributeValue2"},
    "AttributeName3": {"S": "AttributeValue3"},
    "AttributeName5": {"B": "dmFsdWU="}
},
"ConsumedCapacityUnits": 1
}
```

Name	Description
Attributes	<p>A map of attribute name-value pairs, but only if the <code>ReturnValues</code> parameter is specified as something other than <code>NONE</code> in the request.</p> <p>Type: Map of attribute name-value pairs.</p>
ConsumedCapacityUnits	The number of write capacity units consumed by the operation. This value shows the number

Name	Description
	<p>applied toward your provisioned throughput. For more information see <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a>.</p> <p>Type: Number</p>

## Special errors

Error	Description
ConditionalCheckFailedException	Conditional check failed. Attribute ("+ name +") value is ("+ value +") but was expected ("+ expValue +")
ResourceNotFoundExceptions	The specified item or attribute was not found.

## Examples

For examples using the AWS SDK, see [Working with items and attributes \(p. 344\)](#).

### Sample request

```
// This header is abbreviated. For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.UpdateItem
content-type: application/x-amz-json-1.0

{"TableName": "comp5",
 "Key": {
     "HashKeyElement": {"S": "Julie"}, "RangeKeyElement": {"N": "1307654350"}},
 "AttributeUpdates": {
     "status": {"Value": {"S": "online"}, "Action": "PUT"}, "Expected": {"status": {"Value": {"S": "offline"}}, "ReturnValues": "ALL_NEW"}
 }
```

### Sample response

```
HTTP/1.1 200 OK
x-amzn-RequestId: 5IMHO7F01Q9P7Q6QMKMMI3R3QRVV4KQNSO5AEMVJF66Q9ASUAAJG
content-type: application/x-amz-json-1.0
content-length: 121
Date: Fri, 26 Aug 2011 21:05:00 GMT

{"Attributes": {
    "friends": {"SS": ["Lynda", "Aaron"]}, "status": {"S": "online"}, "time": {"N": "1307654350"}, "user": {"S": "Julie"}}, "ConsumedCapacityUnits": 1}
```

## Related actions

- [PutItem \(p. 1366\)](#)
- [DeleteItem \(p. 1351\)](#)

# UpdateTable

### Important

*This section refers to API version 2011-12-05, which is deprecated and should not be used for new applications.*

For documentation on the current low-level API, see the [Amazon DynamoDB API Reference](#).

## Description

Updates the provisioned throughput for the given table. Setting the throughput for a table helps you manage performance and is part of the provisioned throughput feature of DynamoDB. For more information, see [Managing settings on DynamoDB provisioned capacity tables \(p. 286\)](#).

The provisioned throughput values can be upgraded or downgraded based on the maximums and minimums listed in [Service, account, and table quotas in Amazon DynamoDB \(p. 1242\)](#).

The table must be in the ACTIVE state for this operation to succeed. UpdateTable is an asynchronous operation; while executing the operation, the table is in the UPDATING state. While the table is in the UPDATING state, the table still has the provisioned throughput from before the call. The new provisioned throughput setting is in effect only when the table returns to the ACTIVE state after the UpdateTable operation.

## Requests

### Syntax

```
// This header is abbreviated.  
// For a sample of a complete header, see DynamoDB low-level API.  
POST / HTTP/1.1  
x-amz-target: DynamoDB_20111205.UpdateTable  
content-type: application/x-amz-json-1.0  
  
{ "TableName": "Table1",  
    "ProvisionedThroughput": { "ReadCapacityUnits": 5, "WriteCapacityUnits": 15 }  
}
```

Name	Description	Required
TableName	The name of the table to update.  Type: String	Yes
ProvisionedThroughput	New throughput for the specified table, consisting of values for ReadCapacityUnits and WriteCapacityUnits. See <a href="#">Managing settings on DynamoDB provisioned capacity tables (p. 286)</a> .	Yes

Name	Description	Required
	Type: Array	
ProvisionedThroughput. :ReadCapacityUnits	<p>Sets the minimum number of consistent ReadCapacityUnits consumed per second for the specified table before DynamoDB balances the load with other operations.</p> <p>Eventually consistent read operations require less effort than a consistent read operation, so a setting of 50 consistent ReadCapacityUnits per second provides 100 eventually consistent ReadCapacityUnits per second.</p>	Yes
ProvisionedThroughput. :WriteCapacityUnits	<p>Sets the minimum number of WriteCapacityUnits consumed per second for the specified table before DynamoDB balances the load with other operations.</p>	Yes

## Responses

### Syntax

```

HTTP/1.1 200 OK
x-amzn-RequestId: CSOC7TJPLR00OKIRLGOHVAICUFVV4KQNSO5AEMVJF66Q9ASUAAJG
Content-Type: application/json
Content-Length: 311
Date: Tue, 12 Jul 2011 21:31:03 GMT

{
    "TableDescription": {
        "CreationDateTime": 1.321657838135E9,
        "KeySchema": [
            {"HashKeyElement": {"AttributeName": "AttributeValue1", "AttributeType": "S"}, "RangeKeyElement": {"AttributeName": "AttributeValue2", "AttributeType": "N"}},
        "ProvisionedThroughput": {
            "LastDecreaseDateTime": 1.321661704489E9,
            "LastIncreaseDateTime": 1.321663607695E9,
            "ReadCapacityUnits": 5,
            "WriteCapacityUnits": 10},
        "TableName": "Table1",
        "TableStatus": "UPDATING"}}
}

```

Name	Description
CreationDateTime	Date when the table was created.  Type: Number
KeySchema	The primary key (simple or composite) structure for the table. A name-value pair for the HashKeyElement is required, and a name-value pair for the RangeKeyElement is optional (only required for composite primary keys). The maximum hash key size is 2048 bytes. The maximum range key size is 1024 bytes. Both limits are enforced separately (i.e. you can have a combined hash + range 2048 + 1024 key). For more information about primary keys, see <a href="#">Primary key (p. 6)</a> .  Type: Map of HashKeyElement, or HashKeyElement and RangeKeyElement for a composite primary key.
ProvisionedThroughput	Current throughput settings for the specified table, including values for LastIncreaseDateTime (if applicable), LastDecreaseDateTime (if applicable),  Type: Array
TableName	The name of the updated table.  Type: String
TableStatus	The current state of the table (CREATING, ACTIVE, DELETING or UPDATING), which should be UPDATING.  Use the <a href="#">DescribeTables (p. 1358)</a> operation to check the status of the table.  Type: String

## Special errors

Error	Description
ResourceNotFoundException	The specified table was not found.
ResourceInUseException	The table is not in the ACTIVE state.

## Examples

### Sample request

```
// This header is abbreviated.
```

```
// For a sample of a complete header, see DynamoDB low-level API.
POST / HTTP/1.1
x-amz-target: DynamoDB_20111205.UpdateTable
content-type: application/x-amz-json-1.0

{"TableName":"comp1",
 "ProvisionedThroughput":{"ReadCapacityUnits":5,"WriteCapacityUnits":15}
}
```

## Sample response

```
HTTP/1.1 200 OK
content-type: application/x-amz-json-1.0
content-length: 390
Date: Sat, 19 Nov 2011 00:46:47 GMT

{"TableDescription":
 {"CreationDateTime":1.321657838135E9,
 "KeySchema":
  {"HashKeyElement":{"AttributeName":"user","AttributeType":"S"},
   "RangeKeyElement":{"AttributeName":"time","AttributeType":"N"}},
 "ProvisionedThroughput":
  {"LastDecreaseDateTime":1.321661704489E9,
   "LastIncreaseDateTime":1.321663607695E9,
   "ReadCapacityUnits":5,
   "WriteCapacityUnits":10},
 "TableName":"comp1",
 "TableStatus":"UPDATING"}
}
```

## Related actions

- [CreateTable \(p. 1346\)](#)
- [DescribeTables \(p. 1358\)](#)
- [DeleteTable \(p. 1355\)](#)

# AWS SDK for Java 1.x examples

This section contains example code for DAX applications using SDK for Java 1.x.

### Topics

- [Using DAX with AWS SDK for Java 1.x \(p. 1399\)](#)
- [Modifying an existing SDK for Java 1.x application to use DAX \(p. 1408\)](#)
- [Querying global secondary indexes with SDK for Java 1.x \(p. 1412\)](#)

## Using DAX with AWS SDK for Java 1.x

Follow this procedure to run the Java sample for Amazon DynamoDB Accelerator (DAX) on your Amazon EC2 instance.

### Note

These instructions are for applications using AWS SDK for Java 1.x. For applications using AWS SDK for Java 2.x, see [Java and DAX \(p. 684\)](#).

## To run the Java sample for DAX

1. Install the Java Development Kit (JDK).

```
sudo yum install -y java-devel
```

2. Download the AWS SDK for Java (.zip file), and then extract it.

```
wget http://sdk-for-java.amazonwebservices.com/latest/aws-java-sdk.zip
unzip aws-java-sdk.zip
```

3. Download the latest version of the DAX Java client (.jar file).

```
wget http://dax-sdk.s3-website-us-west-2.amazonaws.com/java/DaxJavaClient-latest.jar
```

### Note

The client for the DAX SDK for Java is available on Apache Maven. For more information, see [Using the client as an Apache Maven dependency \(p. 1402\)](#).

4. Set your CLASSPATH variable. In this example, replace *sdkVersion* with the actual version number of the AWS SDK for Java (for example, 1.11.112).

```
export SDKVERSION=sdkVersion
export CLASSPATH=$(pwd)/TryDax/java:$(pwd)/DaxJavaClient-latest.jar:$(pwd)/aws-java-
sdk-$SDKVERSION/lib/aws-java-sdk-$SDKVERSION.jar:$(pwd)/aws-java-sdk-$SDKVERSION/third-
party/lib/*
```

5. Download the sample program source code (.zip file).

```
wget http://docs.aws.amazon.com/amazondynamodb/latest/developerguide/samples/TryDax.zip
```

When the download is complete, extract the source files.

```
unzip TryDax.zip
```

6. Navigate to the Java code directory and compile the code as follows.

```
cd TryDax/java/
javac TryDax*.java
```

7. Run the program.

```
java TryDax
```

You should see output similar to the following.

```
Creating a DynamoDB client
Attempting to create table; please wait...
Successfully created table. Table status: ACTIVE
Writing data to the table...
Writing 10 items for partition key: 1
Writing 10 items for partition key: 2
Writing 10 items for partition key: 3
Writing 10 items for partition key: 4
Writing 10 items for partition key: 5
```

```

Writing 10 items for partition key: 6
Writing 10 items for partition key: 7
Writing 10 items for partition key: 8
Writing 10 items for partition key: 9
Writing 10 items for partition key: 10

Running GetItem, Scan, and Query tests...
First iteration of each test will result in cache misses
Next iterations are cache hits

GetItem test - partition key 1 and sort keys 1-10
Total time: 136.681 ms - Avg time: 13.668 ms
Total time: 122.632 ms - Avg time: 12.263 ms
Total time: 167.762 ms - Avg time: 16.776 ms
Total time: 108.130 ms - Avg time: 10.813 ms
Total time: 137.890 ms - Avg time: 13.789 ms
Query test - partition key 5 and sort keys between 2 and 9
Total time: 13.560 ms - Avg time: 2.712 ms
Total time: 11.339 ms - Avg time: 2.268 ms
Total time: 7.809 ms - Avg time: 1.562 ms
Total time: 10.736 ms - Avg time: 2.147 ms
Total time: 12.122 ms - Avg time: 2.424 ms
Scan test - all items in the table
Total time: 58.952 ms - Avg time: 11.790 ms
Total time: 25.507 ms - Avg time: 5.101 ms
Total time: 37.660 ms - Avg time: 7.532 ms
Total time: 26.781 ms - Avg time: 5.356 ms
Total time: 46.076 ms - Avg time: 9.215 ms

Attempting to delete table; please wait...
Successfully deleted table.

```

Take note of the timing information—the number of milliseconds required for the `GetItem`, `Query`, and `Scan` tests.

8. In the previous step, you ran the program against the DynamoDB endpoint. Now run the program again, but this time, the `GetItem`, `Query`, and `Scan` operations are processed by your DAX cluster.

To determine the endpoint for your DAX cluster, choose one of the following:

- **Using the DynamoDB console** — Choose your DAX cluster. The cluster endpoint is shown on the console, as in the following example.

```
dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

- **Using the AWS CLI** — Enter the following command.

```
aws dax describe-clusters --query "Clusters[*].ClusterDiscoveryEndpoint"
```

The cluster endpoint is shown in the output, as in the following example.

```
{
    "Address": "my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com",
    "Port": 8111,
    "URL": "dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com"
}
```

Now run the program again, but this time, specify the cluster endpoint as a command line parameter.

```
java TryDax dax://my-cluster.16fzcv.dax-clusters.us-east-1.amazonaws.com
```

Look at the rest of the output, and take note of the timing information. The elapsed times for `GetItem`, `Query`, and `Scan` should be significantly lower with DAX than with DynamoDB.

For more information about this program, see the following sections:

- [TryDax.java \(p. 1402\)](#)
- [TryDaxHelper.java \(p. 1404\)](#)
- [TryDaxTests.java \(p. 1406\)](#)

## Using the client as an Apache Maven dependency

Follow these steps to use the client for the DAX SDK for Java in your application as a dependency.

### To use the client as a Maven dependency

1. Download and install Apache Maven. For more information, see [Downloading Apache Maven](#) and [Installing Apache Maven](#).
2. Add the client Maven dependency to your application's Project Object Model (POM) file. In this example, replace `x.x.x.x` with the actual version number of the client (for example, `1.0.200704.0.0`).

```
<!--Dependency:-->
<dependencies>
    <dependency>
        <groupId>com.amazonaws</groupId>
        <artifactId>amazon-dax-client</artifactId>
        <version>x.x.x.x</version>
    </dependency>
</dependencies>
```

## TryDax.java

The `TryDax.java` file contains the `main` method. If you run the program with no command line parameters, it creates an Amazon DynamoDB client and uses that client for all API operations. If you specify a DynamoDB Accelerator (DAX) cluster endpoint on the command line, the program also creates a DAX client and uses it for `GetItem`, `Query`, and `Scan` operations.

You can modify the program in several ways:

- Use the DAX client instead of the DynamoDB client. For more information, see [Java and DAX \(p. 684\)](#).
- Choose a different name for the test table.
- Modify the number of items written by changing the `helper.writeData` parameters. The second parameter is the number of partition keys, and the third parameter is the number of sort keys. By default, the program uses 1–10 for partition key values and 1–10 for sort key values, for a total of 100 items written to the table. For more information, see [TryDaxHelper.java \(p. 1404\)](#).
- Modify the number of `GetItem`, `Query`, and `Scan` tests, and modify their parameters.
- Comment out the lines containing `helper.createTable` and `helper.deleteTable` (if you don't want to create and delete the table each time you run the program).

**Note**

To run this program, you can set up Maven to use the client for the DAX SDK for Java and the AWS SDK for Java as dependencies. For more information, see [Using the client as an Apache Maven dependency \(p. 1402\)](#).

Alternatively, you can download and include both the DAX Java client and the AWS SDK for Java in your classpath. See [Java and DAX \(p. 684\)](#) for an example of setting your CLASSPATH variable.

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
import com.amazonaws.services.dynamodbv2.document.DynamoDB;  
  
public class TryDax {  
  
    public static void main(String[] args) throws Exception {  
  
        TryDaxHelper helper = new TryDaxHelper();  
        TryDaxTests tests = new TryDaxTests();  
  
        DynamoDB ddbClient = helper.getDynamoDBClient();  
        DynamoDB daxClient = null;  
        if (args.length >= 1) {  
            daxClient = helper.getDaxClient(args[0]);  
        }  
  
        String tableName = "TryDaxTable";  
  
        System.out.println("Creating table...");  
        helper.createTable(tableName, ddbClient);  
        System.out.println("Populating table...");  
        helper.writeData(tableName, ddbClient, 10, 10);  
  
        DynamoDB testClient = null;  
        if (daxClient != null) {  
            testClient = daxClient;  
        } else {  
            testClient = ddbClient;  
        }  
  
        System.out.println("Running GetItem, Scan, and Query tests...");  
        System.out.println("First iteration of each test will result in cache misses");  
        System.out.println("Next iterations are cache hits\n");  
  
        // GetItem  
        tests.getItemTest(tableName, testClient, 1, 10, 5);  
  
        // Query  
        tests.queryTest(tableName, testClient, 5, 2, 9, 5);  
  
        // Scan  
        tests.scanTest(tableName, testClient, 5);  
  
        helper.deleteTable(tableName, ddbClient);  
    }  
}
```

```
    }  
}
```

## TryDaxHelper.java

The TryDaxHelper.java file contains utility methods.

The getDynamoDBClient and getDaxClient methods provide Amazon DynamoDB and DynamoDB Accelerator (DAX) clients. For control plane operations (CreateTable, DeleteTable) and write operations, the program uses the DynamoDB client. If you specify a DAX cluster endpoint, the main program creates a DAX client for performing read operations (GetItem, Query, Scan).

The other TryDaxHelper methods (createTable, writeData, deleteTable) are for setting up and tearing down the DynamoDB table and its data.

You can modify the program in several ways:

- Use different provisioned throughput settings for the table.
- Modify the size of each item written (see the stringSize variable in the writeData method).
- Modify the number of GetItem, Query, and Scan tests and their parameters.
- Comment out the lines containing helper.CreateTable and helper.DeleteTable (if you don't want to create and delete the table each time you run the program).

### Note

To run this program, you can set up Maven to use the client for the DAX SDK for Java and the AWS SDK for Java as dependencies. For more information, see [Using the client as an Apache Maven dependency \(p. 1402\)](#).

Or, you can download and include both the DAX Java client and the AWS SDK for Java in your classpath. See [Java and DAX \(p. 684\)](#) for an example of setting your CLASSPATH variable.

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
import java.util.Arrays;  
  
import com.amazonaws.dax.client.dynamodbv2.AmazonDaxClientBuilder;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;  
import com.amazonaws.services.dynamodbv2.document.DynamoDB;  
import com.amazonaws.services.dynamodbv2.document.Item;  
import com.amazonaws.services.dynamodbv2.document.Table;  
import com.amazonaws.services.dynamodbv2.model.AttributeDefinition;  
import com.amazonaws.services.dynamodbv2.model.KeySchemaElement;  
import com.amazonaws.services.dynamodbv2.model.KeyType;  
import com.amazonaws.services.dynamodbv2.model.ProvisionedThroughput;  
import com.amazonaws.services.dynamodbv2.model.ScalarAttributeType;  
import com.amazonaws.util.EC2MetadataUtils;
```

```

public class TryDaxHelper {

    private static final String region = EC2MetadataUtils.getEC2InstanceRegion();

    DynamoDB getDynamoDBClient() {
        System.out.println("Creating a DynamoDB client");
        AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard()
            .withRegion(region)
            .build();
        return new DynamoDB(client);
    }

    DynamoDB getDaxClient(String daxEndpoint) {
        System.out.println("Creating a DAX client with cluster endpoint " + daxEndpoint);
        AmazonDaxClientBuilder daxClientBuilder = AmazonDaxClientBuilder.standard();
        daxClientBuilder.withRegion(region).withEndpointConfiguration(daxEndpoint);
        AmazonDynamoDB client = daxClientBuilder.build();
        return new DynamoDB(client);
    }

    void createTable(String tableName, DynamoDB client) {
        Table table = client.getTable(tableName);
        try {
            System.out.println("Attempting to create table; please wait...");

            table = client.createTable(tableName,
                Arrays.asList(
                    new KeySchemaElement("pk", KeyType.HASH), // Partition key
                    new KeySchemaElement("sk", KeyType.RANGE)), // Sort key
                Arrays.asList(
                    new AttributeDefinition("pk", ScalarAttributeType.N),
                    new AttributeDefinition("sk", ScalarAttributeType.N)),
                new ProvisionedThroughput(10L, 10L));
            table.waitForActive();
            System.out.println("Successfully created table. Table status: " +
                table.getDescription().getTableStatus());
        } catch (Exception e) {
            System.err.println("Unable to create table: ");
            e.printStackTrace();
        }
    }

    void writeData(String tableName, DynamoDB client, int pkmax, int skmax) {
        Table table = client.getTable(tableName);
        System.out.println("Writing data to the table...");

        int stringSize = 1000;
        StringBuilder sb = new StringBuilder(stringSize);
        for (int i = 0; i < stringSize; i++) {
            sb.append('X');
        }
        String someData = sb.toString();

        try {
            for (Integer ipk = 1; ipk <= pkmax; ipk++) {
                System.out.println("Writing " + skmax + " items for partition key: " +
ipk));
                for (Integer isk = 1; isk <= skmax; isk++) {
                    table.putItem(new Item()
                        .withPrimaryKey("pk", ipk, "sk", isk)
                        .withString("someData", someData)));
                }
            }
        } catch (Exception e) {
    }
}

```

```

        System.err.println("Unable to write item:");
        e.printStackTrace();
    }

    void deleteTable(String tableName, DynamoDB client) {
        Table table = client.getTable(tableName);
        try {
            System.out.println("\nAttempting to delete table; please wait...");
            table.delete();
            table.waitForDelete();
            System.out.println("Successfully deleted table.");
        } catch (Exception e) {
            System.err.println("Unable to delete table: ");
            e.printStackTrace();
        }
    }
}

```

## TryDaxTests.java

The `TryDaxTests.java` file contains methods that perform read operations against a test table in Amazon DynamoDB. These methods are not concerned with how they access the data (using either the DynamoDB client or the DAX client), so there is no need to modify the application logic.

You can modify the program in several ways:

- Modify the `queryTest` method so that it uses a different `KeyConditionExpression`.
- Add a `ScanFilter` to the `scanTest` method so that only some of the items are returned to you.

### Note

To run this program, you can set up Maven to use the client for the DAX SDK for Java and the AWS SDK for Java as dependencies. For more information, see [Using the client as an Apache Maven dependency \(p. 1402\)](#).

Or, you can download and include both the DAX Java client and the AWS SDK for Java in your classpath. See [Java and DAX \(p. 684\)](#) for an example of setting your `CLASSPATH` variable.

```

/**
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.
 *
 * This file is licensed under the Apache License, Version 2.0 (the "License").
 * You may not use this file except in compliance with the License. A copy of
 * the License is located at
 *
 * http://aws.amazon.com/apache2.0/
 *
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the
 * specific language governing permissions and limitations under the License.
 */
import java.util.HashMap;
import java.util.Iterator;

import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.Item;
import com.amazonaws.services.dynamodbv2.document.ItemCollection;
import com.amazonaws.services.dynamodbv2.document.QueryOutcome;

```

```

import com.amazonaws.services.dynamodbv2.document.ScanOutcome;
import com.amazonaws.services.dynamodbv2.document.Table;
import com.amazonaws.services.dynamodbv2.document.spec.QuerySpec;

public class TryDaxTests {

    void getItemTest(String tableName, DynamoDB client, int pk, int sk, int iterations) {
        long startTime, endTime;
        System.out.println("GetItem test - partition key " + pk + " and sort keys 1-" +
sk);
        Table table = client.getTable(tableName);

        for (int i = 0; i < iterations; i++) {
            startTime = System.nanoTime();
            try {
                for (Integer ipk = 1; ipk <= pk; ipk++) {
                    for (Integer isk = 1; isk <= sk; isk++) {
                        table.getItem("pk", ipk, "sk", isk);
                    }
                }
            } catch (Exception e) {
                System.err.println("Unable to get item:");
                e.printStackTrace();
            }
            endTime = System.nanoTime();
            printTime(startTime, endTime, pk * sk);
        }
    }

    void queryTest(String tableName, DynamoDB client, int pk, int sk1, int sk2, int
iterations) {
        long startTime, endTime;
        System.out.println("Query test - partition key " + pk + " and sort keys between " +
sk1 + " and " + sk2);
        Table table = client.getTable(tableName);

        HashMap<String, Object> valueMap = new HashMap<String, Object>();
        valueMap.put(":pkval", pk);
        valueMap.put(":skval1", sk1);
        valueMap.put(":skval2", sk2);

        QuerySpec spec = new QuerySpec()
            .withKeyConditionExpression("pk = :pkval and sk between :skval1
and :skval2")
            .withValueMap(valueMap);

        for (int i = 0; i < iterations; i++) {
            startTime = System.nanoTime();
            ItemCollection<QueryOutcome> items = table.query(spec);

            try {
                Iterator<Item> iter = items.iterator();
                while (iter.hasNext()) {
                    iter.next();
                }
            } catch (Exception e) {
                System.err.println("Unable to query table:");
                e.printStackTrace();
            }
            endTime = System.nanoTime();
            printTime(startTime, endTime, iterations);
        }
    }

    void scanTest(String tableName, DynamoDB client, int iterations) {
        long startTime, endTime;
    }
}

```

```
System.out.println("Scan test - all items in the table");
Table table = client.getTable(tableName);

for (int i = 0; i < iterations; i++) {
    startTime = System.nanoTime();
    ItemCollection<ScanOutcome> items = table.scan();
    try {

        Iterator<Item> iter = items.iterator();
        while (iter.hasNext()) {
            iter.next();
        }
    } catch (Exception e) {
        System.err.println("Unable to scan table:");
        e.printStackTrace();
    }
    endTime = System.nanoTime();
    printTime(startTime, endTime, iterations);
}
}

public void printTime(long startTime, long endTime, int iterations) {
    System.out.format("\tTotal time: %.3f ms - ", (endTime - startTime) / (1000000.0));
    System.out.format("Avg time: %.3f ms\n", (endTime - startTime) / (iterations * 1000000.0));
}
```

## Modifying an existing SDK for Java 1.x application to use DAX

If you already have a Java application that uses Amazon DynamoDB, you have to modify it so that it can access your DynamoDB Accelerator (DAX) cluster. You don't have to rewrite the entire application because the DAX Java client is similar to the DynamoDB low-level client included in the AWS SDK for Java.

### Note

These instructions are for applications using AWS SDK for Java 1.x. For applications using AWS SDK for Java 2.x, see [Modifying an existing application to use DAX \(p. 711\)](#).

Suppose that you have a DynamoDB table named `Music`. The partition key for the table is `Artist`, and its sort key is `SongTitle`. The following program reads an item directly from the `Music` table.

```
import java.util.HashMap;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBClientBuilder;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
import com.amazonaws.services.dynamodbv2.model.GetItemRequest;
import com.amazonaws.services.dynamodbv2.model.GetItemResult;

public class GetMusicItem {

    public static void main(String[] args) throws Exception {

        // Create a DynamoDB client
        AmazonDynamoDB client = AmazonDynamoDBClientBuilder.standard().build();

        HashMap<String, AttributeValue> key = new HashMap<String, AttributeValue>();
        key.put("Artist", new AttributeValue().withS("No One You Know"));
        key.put("SongTitle", new AttributeValue().withS("Scared of My Shadow"));
    }
}
```

```
GetItemRequest request = new GetItemRequest()
    .withTableName("Music").withKey(key);

try {
    System.out.println("Attempting to read the item...");
    GetItemResult result = client.getItem(request);
    System.out.println("GetItem succeeded: " + result);

} catch (Exception e) {
    System.err.println("Unable to read item");
    System.err.println(e.getMessage());
}
}
```

To modify the program, replace the DynamoDB client with a DAX client.

```
import java.util.HashMap;

import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazon.dax.client.dynamodbv2.AmazonDaxClientBuilder;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
import com.amazonaws.services.dynamodbv2.model.GetItemRequest;
import com.amazonaws.services.dynamodbv2.model.GetItemResult;

public class GetMusicItem {

    public static void main(String[] args) throws Exception {

        //Create a DAX client

        AmazonDaxClientBuilder daxClientBuilder = AmazonDaxClientBuilder.standard();
        daxClientBuilder.withRegion("us-
east-1").withEndpointConfiguration("mydaxcluster.2cmrw1.clustercfg.dax.usel.cache.amazonaws.com:8111");
        AmazonDynamoDB client = daxClientBuilder.build();

        /*
        ...
        ** Remaining code omitted (it is identical)
        ...
        */

    }
}
```

## Using the DynamoDB document API

The AWS SDK for Java provides a document interface for DynamoDB. The document API acts as a wrapper around the low-level DynamoDB client. For more information, see [Document interfaces](#).

The document interface can also be used with the low-level DAX client, as shown in the following example.

```
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;
import com.amazon.dax.client.dynamodbv2.AmazonDaxClientBuilder;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.services.dynamodbv2.document.GetItemOutcome;
import com.amazonaws.services.dynamodbv2.document.Table;

public class GetMusicItemWithDocumentApi {
```

```
public static void main(String[] args) throws Exception {  
  
    //Create a DAX client  
  
    AmazonDaxClientBuilder daxClientBuilder = AmazonDaxClientBuilder.standard();  
    daxClientBuilder.withRegion("us-  
east-1").withEndpointConfiguration("mydaxcluster.2cmrw1.clustercfg.dax.use1.cache.amazonaws.com:8111");  
    AmazonDynamoDB client = daxClientBuilder.build();  
  
    // Document client wrapper  
    DynamoDB docClient = new DynamoDB(client);  
  
    Table table = docClient.getTable("Music");  
  
    try {  
        System.out.println("Attempting to read the item...");  
        GetItemOutcome outcome = table.tgetItemOutcome(  
            "Artist", "No One You Know",  
            "SongTitle", "Scared of My Shadow");  
        System.out.println(outcome.getItem());  
        System.out.println("GetItem succeeded: " + outcome);  
    } catch (Exception e) {  
        System.err.println("Unable to read item");  
        System.err.println(e.getMessage());  
    }  
}  
}
```

## DAX async client

The `AmazonDaxClient` is synchronous. For a long-running DAX API operation, such as a Scan of a large table, this can block program execution until the operation is complete. If your program needs to perform other work while a DAX API operation is in progress, you can use `ClusterDaxAsyncClient` instead.

The following program shows how to use `ClusterDaxAsyncClient`, along with Java Future, to implement a non-blocking solution.

```
/**  
 * Copyright 2010-2019 Amazon.com, Inc. or its affiliates. All Rights Reserved.  
 *  
 * This file is licensed under the Apache License, Version 2.0 (the "License").  
 * You may not use this file except in compliance with the License. A copy of  
 * the License is located at  
 *  
 * http://aws.amazon.com/apache2.0/  
 *  
 * This file is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR  
 * CONDITIONS OF ANY KIND, either express or implied. See the License for the  
 * specific language governing permissions and limitations under the License.  
 */  
import java.util.HashMap;  
import java.util.concurrent.ExecutionException;  
import java.util.concurrent.Future;  
  
import com.amazon.dax.client.dynamodbv2.ClientConfig;  
import com.amazon.dax.client.dynamodbv2.ClusterDaxAsyncClient;  
import com.amazonaws.auth.profile.ProfileCredentialsProvider;  
import com.amazonaws.handlers.AsyncHandler;  
import com.amazonaws.services.dynamodbv2.AmazonDynamoDBAsync;  
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
```

```
import com.amazonaws.services.dynamodbv2.model.GetItemRequest;
import com.amazonaws.services.dynamodbv2.model.GetItemResult;

public class DaxAsyncClientDemo {
    public static void main(String[] args) throws Exception {

        ClientConfig daxConfig = new ClientConfig().withCredentialsProvider(new
        ProfileCredentialsProvider())
            .withEndpoints("mydaxcluster.2cmrwl.clustercfg.dax.use1.cache.amazonaws.com:8111");

        AmazonDynamoDBAsync client = new ClusterDaxAsyncClient(daxConfig);

        HashMap<String,AttributeValue> key = new HashMap<String,AttributeValue>();
        key.put("Artist", new AttributeValue().withS("No One You Know"));
        key.put("SongTitle", new AttributeValue().withS("Scared of My Shadow"));

        GetItemRequest request = new GetItemRequest()
            .withTableName("Music").withKey(key);

        // Java Futures
        Future<GetItemResult> call = client.getItemAsync(request);
        while (!call.isDone()) {
            // Do other processing while you're waiting for the response
            System.out.println("Doing something else for a few seconds...");
            Thread.sleep(3000);
        }
        // The results should be ready by now

        try {
            call.get();

        } catch (ExecutionException ee) {
            // Futures always wrap errors as an ExecutionException.
            // The *real* exception is stored as the cause of the
            // ExecutionException
            Throwable exception = ee.getCause();
            System.out.println("Error getting item: " + exception.getMessage());
        }

        // Async callbacks
        call = client.getItemAsync(request, new AsyncHandler<GetItemRequest, GetItemResult>() {

            @Override
            public void onSuccess(GetItemRequest request, GetItemResult getItemResult) {
                System.out.println("Result: " + getItemResult);
            }

            @Override
            public void onError(Exception e) {
                System.out.println("Unable to read item");
                System.err.println(e.getMessage());
                // Callers can also test if exception is an instance of
                // AmazonServiceException or AmazonClientException and cast
                // it to get additional information
            }
        });
        call.get();
    }
}
```

# Querying global secondary indexes with SDK for Java 1.x

You can use Amazon DynamoDB Accelerator (DAX) to query [global secondary indexes](#) using [DynamoDB programmatic interfaces](#).

The following example demonstrates how to use DAX to query the `CreateDateIndex` global secondary index that is created in [Example: Global secondary indexes using the AWS SDK for Java document API](#).

The `DAXClient` class instantiates the client objects that are needed to interact with the DynamoDB programming interfaces.

```
import com.amazon.dax.client.dynamodbv2.AmazonDaxClientBuilder;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;
import com.amazonaws.util.EC2MetadataUtils;
import com.amazonaws.services.dynamodbv2.AmazonDynamoDB;

public class DaxClient {

    private static final String region = EC2MetadataUtils.getEC2InstanceRegion();

    DynamoDB getDaxDocClient(String daxEndpoint) {
        System.out.println("Creating a DAX client with cluster endpoint " + daxEndpoint);
        AmazonDaxClientBuilder daxClientBuilder = AmazonDaxClientBuilder.standard();

        daxClientBuilder.withRegion(region).withEndpointConfiguration(daxEndpoint);
        AmazonDynamoDB client = daxClientBuilder.build();

        return new DynamoDB(client);
    }

    DynamoDBMapper getDaxMapperClient(String daxEndpoint) {
        System.out.println("Creating a DAX client with cluster endpoint " + daxEndpoint);
        AmazonDaxClientBuilder daxClientBuilder = AmazonDaxClientBuilder.standard();

        daxClientBuilder.withRegion(region).withEndpointConfiguration(daxEndpoint);
        AmazonDynamoDB client = daxClientBuilder.build();

        return new DynamoDBMapper(client);
    }
}
```

You can query a global secondary index in the following ways:

- Use the `queryIndex` method on the `QueryIndexDax` class defined in the following example. The `QueryIndexDax` takes as a parameter the client object that is returned by the `getDaxDocClient` method on the `DaxClient` class.
- If you are using the [object persistence interface](#), use the `queryIndexMapper` method on the `QueryIndexDax` class defined in the following example. The `queryIndexMapper` takes as a parameter the client object that is returned by the `getDaxMapperClient` method defined on the `DaxClient` class.

```
import java.util.Iterator;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBMapper;
import java.util.List;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBQueryExpression;
import com.amazonaws.services.dynamodbv2.model.AttributeValue;
```

```

import java.util.HashMap;
import com.amazonaws.services.dynamodbv2.document.Item;
import com.amazonaws.services.dynamodbv2.document.utils.ValueMap;
import com.amazonaws.services.dynamodbv2.document.spec.QuerySpec;
import com.amazonaws.services.dynamodbv2.document.QueryOutcome;
import com.amazonaws.services.dynamodbv2.document.ItemCollection;
import com.amazonaws.services.dynamodbv2.document.Index;
import com.amazonaws.services.dynamodbv2.document.Table;
import com.amazonaws.services.dynamodbv2.document.DynamoDB;

public class QueryIndexDax {

    //This is used to query Index using the low-level interface.
    public static void queryIndex(DynamoDB client, String tableName, String indexName) {
        Table table = client.getTable(tableName);

        System.out.println("\n*****\n");
        System.out.print("Querying index " + indexName + "...");

        Index index = table.getIndex(indexName);
        ItemCollection<QueryOutcome> items = null;

        QuerySpec querySpec = new QuerySpec();

        if (indexName == "CreateDateIndex") {
            System.out.println("Issues filed on 2013-11-01");
            querySpec.withKeyConditionExpression("CreateDate = :v_date and
begins_with(IssueId, :v_issue)")
                .withValueMap(new ValueMap().withString(":v_date",
"2013-11-01").withString(":v_issue", "A-"));
            items = index.query(querySpec);
        } else {
            System.out.println("\nNo valid index name provided");
            return;
        }

        Iterator<Item> iterator = items.iterator();

        System.out.println("Query: printing results...");

        while (iterator.hasNext()) {
            System.out.println(iterator.next().toJSONPretty());
        }
    }

    //This is used to query Index using the high-level mapper interface.
    public static void queryIndexMapper(DynamoDBMapper mapper, String tableName, String
indexName) {
        HashMap<String,AttributeValue> eav = new HashMap<String,AttributeValue>();
        eav.put(":v_date", new AttributeValue().withS("2013-11-01"));
        eav.put(":v_issue", new AttributeValue().withS("A-"));
        DynamoDBQueryExpression<CreateDate> queryExpression = new
DynamoDBQueryExpression<CreateDate>()
            .withIndexName("CreateDateIndex").withConsistentRead(false)
            .withKeyConditionExpression("CreateDate = :v_date and begins_with(IssueId, :v_issue)")
            .withExpressionAttributeValues(eav);

        List<CreateDate> items = mapper.query(CreateDate.class, queryExpression);
        Iterator<CreateDate> iterator = items.iterator();

        System.out.println("Query: printing results...");

        while (iterator.hasNext()) {
            CreateDate iterObj = iterator.next();
    
```

```
    System.out.println(iterObj.getCreateDate());
    System.out.println(iterObj.getIssueId());
}
}
```

The class definition below represents the Issues table and is used in the `queryIndexMapper` method.

```
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBTable;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBIndexHashKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBIndexRangeKey;
import com.amazonaws.services.dynamodbv2.datamodeling.DynamoDBHashKey;

@DynamoDBTable(tableName = "Issues")
public class CreateDate {
    private String createDate;
    @DynamoDBHashKey(attributeName = "IssueId")
    private String issueId;

    @DynamoDBIndexHashKey(globalSecondaryIndexName = "CreateDateIndex", attributeName =
    "CreateDate")
    public String getCreateDate() {
        return createDate;
    }

    public void setCreateDate(String createDate) {
        this.createDate = createDate;
    }

    @DynamoDBIndexRangeKey(globalSecondaryIndexName = "CreateDateIndex", attributeName =
    "IssueId")
    public String getIssueId() {
        return issueId;
    }

    public void setIssueId(String issueId) {
        this.issueId = issueId;
    }
}
```

# Document history for DynamoDB

The following table describes the important changes in each release of the *DynamoDB Developer Guide* from July 3, 2018 onward. For notification about updates to this documentation, you can subscribe to the RSS feed (at the top left corner of this page).

update-history-change	update-history-description	update-history-date
<a href="#">Enhanced integration with Service Quotas (p. 1415)</a>	<p><a href="#">Service Quotas</a> now enables you to proactively manage your account and table quotas. You can view current values, set alarms for when your utilization of a quota exceeds a configurable threshold, and more.</p>	June 15, 2022
<a href="#">NoSQL Workbench adds table and GSI support (p. 1415)</a>	<p>You can now use NoSQL Workbench for table and global secondary index (GSI) <a href="#">control plane operations</a> such as CreateTable, UpdateTable, and DeleteTable.</p>	June 2, 2022
<a href="#">Standard-infrequent access table class now available in China (p. 1415)</a>	<p>Amazon DynamoDB Standard-Infrequent Access table class is available in China Regions. Reduce your <a href="#">DynamoDB costs by up to 60 percent</a>, by using this new table class for tables that store infrequently accessed data.</p>	April 18, 2022
<a href="#">Increase in default service quotas and table management operations (p. 1415)</a>	<p>DynamoDB increased the default quota for the number of tables per account and Region from 256 to 2,500 tables, and increased the number of concurrent table management operations from 50 to 500.</p>	March 9, 2022
<a href="#">Optional limiting of items with PartiQL for DynamoDB (p. 1415)</a>	<p>DynamoDB can <a href="#">limit the number of items processed in PartiQL</a> for DynamoDB operations as an optional parameter on each request.</p>	March 8, 2022
<a href="#">AWS Backup integration available in China (Beijing and Ningxia) Regions (p. 1415)</a>	<p>AWS Backup now integrates with DynamoDB in the China (Beijing and Ningxia) Regions. You can meet compliance and business continuity requirements more easily through enhanced backup features in AWS Backup, such as cross-account and cross-Region backups.</p>	January 26, 2022

<a href="#">Throughput capacity information through PartiQL API calls (p. 1415)</a>	DynamoDB can return the throughput capacity consumed by <a href="#">PartiQL API</a> calls to help you optimize your queries and throughput costs.	January 18, 2022
<a href="#">AWS Backup integration (p. 1415)</a>	DynamoDB now helps you meet compliance and business continuity requirements more easily through enhanced backup features in <a href="#">AWS Backup</a> , such as cross-account and cross-Region backups.	November 24, 2021
<a href="#">NoSQL Workbench import/export datasets in CSV (p. 1415)</a>	<a href="#">NoSQL Workbench for Amazon DynamoDB</a> now enables you to import and automatically populate sample data to help build and visualize your data models.	October 11, 2021
<a href="#">Filter and retrieve Amazon DynamoDB Streams data-plane activity with AWS CloudTrail (p. 1415)</a>	Amazon DynamoDB now provides you more granular control of audit logging by enabling you to <a href="#">filter Streams data-plane API activity in AWS CloudTrail</a> .	September 22, 2021
<a href="#">Updated console (p. 1415)</a>	The <a href="#">DynamoDB console</a> is now your default console to help you manage data more easily, simplify your common tasks, and give you faster access to resources and features.	August 25, 2021
<a href="#">DAX SDK For Java 2.x is now available (p. 1415)</a>	<a href="#">DynamoDB Accelerator (DAX) SDK for Java 2.x</a> is now available and is compatible with the AWS SDK for Java 2.x. You can benefit from the latest features, including non-blocking I/O.	July 29, 2021
<a href="#">NoSQL Workbench feature updates including control plane operations (p. 1415)</a>	<a href="#">NoSQL Workbench for Amazon DynamoDB</a> now helps you run frequent operations more easily to modify and access table data.	July 28, 2021
<a href="#">DynamoDB global tables are now available in the Asia Pacific Region (p. 1415)</a>	<a href="#">DynamoDB global tables</a> are now available in the Asia Pacific (Osaka) Region. Replicate your DynamoDB tables automatically across your choice of 22 AWS Regions.	July 28, 2021
<a href="#">DAX is now available in China (p. 1415)</a>	<a href="#">DynamoDB Accelerator (DAX)</a> is now available in the China (Beijing) Region, operated by Sinnet.	July 28, 2021

DAX encryption in transit (p. 1415)	<p><a href="#">DynamoDB Accelerator (DAX)</a> now supports encryption in transit of data between your applications and DAX clusters, and between the nodes within a DAX cluster.</p>	July 24, 2021
CloudFormation and CloudTrail integration (p. 1415)	<p><a href="#">Integration with AWS CloudFormation</a> and security enhancements with CloudFormation data-plane logging.</p>	June 18, 2021
CloudFormation now supported for global tables (p. 1415)	<p><a href="#">Amazon DynamoDB global tables</a> now support <a href="#">AWS CloudFormation</a>, which means you can create global tables and manage their settings with CloudFormation templates.</p>	May 14, 2021
Amazon DynamoDB local support for Java 2.x (p. 1415)	<p>You now can use the <a href="#">AWS SDK for Java 2.x with DynamoDB local</a>, the downloadable version of Amazon DynamoDB. With DynamoDB local, you can develop and test applications by using a version of DynamoDB running in your local development environment without incurring any additional costs.</p>	May 3, 2021
NoSQL Workbench now supports AWS CloudFormation (p. 1415)	<p><a href="#">NoSQL Workbench for Amazon DynamoDB</a> now supports <a href="#">AWS CloudFormation</a>, so you can manage and modify DynamoDB data models with CloudFormation templates. In addition, you now can configure table capacity settings in NoSQL Workbench.</p>	April 22, 2021
DynamoDB and AWS Amplify now feature integration (p. 1415)	<p><a href="#">AWS Amplify</a> now orchestrates multiple DynamoDB global secondary index updates in a single deployment.</p>	April 20, 2021
AWS CloudTrail to log Amazon DynamoDB Streams data-plane APIs (p. 1415)	<p>You now can use <a href="#">AWS CloudTrail to log Amazon DynamoDB Streams data-plane API activity</a>, and monitor and investigate item-level changes in your DynamoDB tables.</p>	April 20, 2021

Amazon Kinesis Data Streams for Amazon DynamoDB now supports AWS CloudFormation (p. 1415)	Amazon Kinesis Data Streams for Amazon DynamoDB now supports AWS CloudFormation, which means you can enable streaming to an Amazon Kinesis data stream on your DynamoDB tables with CloudFormation templates. By streaming your DynamoDB data changes to a Kinesis data stream, you can build advanced streaming applications with AAmazon Kinesis services.	April 12, 2021
Amazon Keyspaces now offers FIPS 140-2 compliant endpoints (p. 1415)	Amazon Keyspaces (for Apache Cassandra) now offers Federal Information Processing Standards (FIPS) 140-2 compliant endpoints to help you run highly regulated workloads more easily. FIPS 140-2 is a US and Canadian government standard that specifies the security requirements for cryptographic modules that protect sensitive information.	April 8, 2021
Amazon EC2 T3 instances for DAX (p. 1415)	DAX now supports Amazon EC2 T3 instance types, which provide a baseline level of CPU performance with the ability to burst above the baseline when needed.	February 15, 2021
NoSQL Workbench for Amazon DynamoDB support for PartiQL (p. 1415)	You now can use the NoSQL Workbench for DynamoDB to build PartiQL statements for DynamoDB.	December 4, 2020
PartiQL for DynamoDB (p. 1415)	You now can use PartiQL for DynamoDB—a SQL-compatible query language—to interact with DynamoDB tables and run ad hoc queries by using the AWS Management Console, AWS Command Line Interface, and DynamoDB APIs for PartiQL.	November 23, 2020
Amazon Kinesis Data Streams for Amazon DynamoDB (p. 1415)	You now can use Amazon Kinesis Data Streams for Amazon DynamoDB with your DynamoDB tables to capture item-level changes and replicate them to a Kinesis data stream.	November 23, 2020

DynamoDB table export (p. 1415)	You can now <a href="#">export your DynamoDB tables to Amazon S3</a> , enabling you to perform analytics and complex queries on your data with services like Athena, AWS Glue, and Lake Formation.	November 9, 2020
Support for empty values (p. 1415)	DynamoDB now supports empty values for non-key String and Binary attributes in DynamoDB tables. Empty value support gives you greater flexibility to use attributes for a broader set of use cases without having to transform such attributes before sending them to DynamoDB. List, Map, and Set data types also support empty String and Binary values.	May 18, 2020
NoSQL Workbench for Amazon DynamoDB support for Linux (p. 1415)	NoSQL Workbench for Amazon DynamoDB is now supported on <a href="#">Linux- Ubuntu , Fedora and Debian</a> .	May 4, 2020
CloudWatch Contributor Insights for DynamoDB – GA (p. 1415)	CloudWatch Contributor Insights for DynamoDB is generally available. CloudWatch Contributor Insights for DynamoDB is a diagnostic tool that provides an at-a-glance view of your DynamoDB table's traffic trends and helps you identify your table's most frequently accessed keys (also known as hot keys).	April 2, 2020
Upgrading global tables (p. 1415)	You now can update your global tables from version 2017.11.29 to the <a href="#">latest version of global tables (2019.11.21)</a> , with a few clicks in the DynamoDB Console. By upgrading the version of your global tables, you can increase the availability of your DynamoDB tables easily by extending your existing tables into additional AWS Regions, with no table rebuilds required.	March 16, 2020
NoSQL Workbench for Amazon DynamoDB – GA (p. 1415)	NoSQL Workbench for Amazon DynamoDB is generally available. Use the NoSQL Workbench to design, create, query, and manage DynamoDB tables.	March 2, 2020

<a href="#">DAX cache cluster metrics (p. 1415)</a>	DAX support for new <a href="#">CloudWatch metrics</a> , that allow you to better understand your DAX cluster's performance.	February 6, 2020
<a href="#">CloudWatch Contributor Insights for DynamoDB – Preview (p. 1415)</a>	<a href="#">CloudWatch Contributor Insights for DynamoDB</a> is a diagnostic tool that provides an at-a-glance view of your DynamoDB table's traffic trends and helps you identify your table's most frequently accessed keys (also known as hot keys).	November 26, 2019
<a href="#">Adaptive capacity support for imbalanced workload (p. 1415)</a>	Amazon DynamoDB adaptive capacity now <a href="#">handles</a> imbalanced workloads better by isolating frequently accessed items automatically. If your application drives disproportionately high traffic to one or more items, DynamoDB will rebalance your partitions such that frequently accessed items do not reside on the same partition.	November 26, 2019
<a href="#">Support for customer managed keys (p. 1415)</a>	DynamoDB now <a href="#">supports customer managed keys</a> , which means you can have full control over how you encrypt and manage the security of your DynamoDB data.	November 25, 2019
<a href="#">NoSQL Workbench support for DynamoDB Local (Downloadable Version) (p. 1415)</a>	The NoSQL Workbench now supports connecting to <a href="#">DynamoDB Local (Downloadable Version)</a> to design, create, query, and manage DynamoDB tables.	November 8, 2019
<a href="#">NoSQL Workbench – Preview (p. 1415)</a>	This is the initial release of NoSQL Workbench for DynamoDB. Use NoSQL Workbench to design, create, query, and manage DynamoDB tables. For more information, see <a href="#">NoSQL Workbench for Amazon DynamoDB (Preview)</a> .	September 16, 2019
<a href="#">DAX adds support for transactional operations using Python and .NET (p. 1415)</a>	DAX supports the <a href="#">TransactWriteItems</a> and <a href="#">TransactGetItems</a> APIs for applications written in Go, Java, .NET, Node.js, and Python. For more information, see <a href="#">In-Memory Acceleration with DAX</a> .	February 14, 2019

<a href="#">Amazon DynamoDB Local (Downloadable Version) Updates (p. 1415)</a>	DynamoDB Local (Downloadable Version) now supports transactional APIs, on-demand read/write capacity, capacity reporting for read and write operations, and 20 global secondary indexes. For more information, see <a href="#">Differences Between Downloadable DynamoDB and the DynamoDB Web Service</a> .	February 4, 2019
<a href="#">Amazon DynamoDB On-Demand (p. 1415)</a>	DynamoDB on-demand is a flexible billing option capable of serving thousands of requests per second without capacity planning. DynamoDB on-demand offers pay-per-request pricing for read and write requests so that you pay only for what you use. For more information, see <a href="#">Read/Write Capacity Mode</a> .	November 28, 2018
<a href="#">Amazon DynamoDB Transactions (p. 1415)</a>	DynamoDB transactions make coordinated, all-or-nothing changes to multiple items both within and across tables, providing atomicity, consistency, isolation, and durability (ACID) in DynamoDB. For more information, see <a href="#">Amazon DynamoDB Transactions</a> .	November 27, 2018
<a href="#">Amazon DynamoDB encrypts all customer data at rest (p. 1415)</a>	DynamoDB encryption at rest provides an additional layer of data protection by securing your data in the encrypted table, including its primary key, local and global secondary indexes, streams, global tables, backups, and DAX clusters whenever the data is stored in durable media. For more information, see <a href="#">Amazon DynamoDB Encryption at Rest</a> .	November 15, 2018
<a href="#">Use Amazon DynamoDB Local More Easily with the New Docker Image (p. 1415)</a>	Now, it's easier to use DynamoDB Local, the downloadable version of DynamoDB, to help you develop and test your DynamoDB applications by using the new DynamoDB Local Docker image. For more information, see <a href="#">DynamoDB (Downloadable Version) and Docker</a> .	August 22, 2018

DynamoDB Accelerator (DAX) Adds Support for Encryption at Rest (p. 1415)	DynamoDB Accelerator (DAX) now supports encryption at rest for new DAX clusters to help you accelerate reads from Amazon DynamoDB tables in security-sensitive applications that are subject to strict compliance and regulatory requirements. For more information, see <a href="#">DAX Encryption at Rest</a> .	August 9, 2018
DynamoDB point-in-time recovery (PITR) adds support for restoring deleted tables (p. 1415)	If you delete a table with point-in-time recovery enabled, a system backup is automatically created and is retained for 35 days (at no additional cost). For more information, see <a href="#">Before You Begin Using Point In Time Recovery</a> .	August 7, 2018
Updates now available over RSS (p. 1415)	You can now subscribe to the <a href="#">RSS feed</a> (at the top left corner of this page) to receive notifications about updates to the Amazon DynamoDB Developer Guide.	July 3, 2018

## Earlier updates

The following table describes important changes of the *DynamoDB Developer Guide* before July 3, 2018.

Change	Description	Date Changed
Go support for DAX	Now, you can enable microsecond read performance for Amazon DynamoDB tables in your applications written in the Go programming language by using the new DynamoDB Accelerator (DAX) SDK for Go. For more information, see <a href="#">DAX SDK for Go (p. 683)</a> .	June 26, 2018
DynamoDB announces SLA	DynamoDB has released a public availability SLA. For more information, see <a href="#">Amazon DynamoDB Service Level Agreement</a> .	June 19, 2018
DynamoDB continuous backups and Point-In-Time Recovery (PITR)	Point-in-time recovery helps protect your Amazon DynamoDB tables from accidental write or delete operations. With point in time recovery, you don't have to worry about creating,	April 25, 2018

Change	Description	Date Changed
	<p>maintaining, or scheduling on-demand backups. For example, suppose that a test script writes accidentally to a production DynamoDB table. With point-in-time recovery, you can restore that table to any point in time during the last 35 days. DynamoDB maintains incremental backups of your table. For more information, see <a href="#">Point-in-time recovery for DynamoDB (p. 649)</a>.</p>	
Encryption at rest for DynamoDB	<p>DynamoDB encryption at rest, available for new DynamoDB tables, helps you secure your application data in Amazon DynamoDB tables by using AWS-managed encryption keys stored in AWS Key Management Service. For more information, see <a href="#">DynamoDB encryption at rest (p. 1062)</a>.</p>	February 8, 2018
DynamoDB Backup and restore	<p>On-Demand Backup allows you to create full backups of your DynamoDB tables data for data archival, helping you meet your corporate and governmental regulatory requirements. You can backup tables from a few megabytes to hundreds of terabytes of data, with no impact on performance and availability to your production applications. For more information, see <a href="#">Using On-Demand backup and restore for DynamoDB (p. 629)</a>.</p>	November 29, 2017

<b>Change</b>	<b>Description</b>	<b>Date Changed</b>
DynamoDB Global tables	<p>Global Tables builds upon DynamoDB's global footprint to provide you with a fully managed, multi-region, and multi-active database that provides fast, local, read and write performance for massively scaled, global applications. Global Tables replicates your Amazon DynamoDB tables automatically across your choice of AWS regions. For more information, see <a href="#">Global tables - multi-Region replication for DynamoDB (p. 305)</a>.</p>	November 29, 2017
Node.js support for DAX	<p>Node.js developers can leverage DynamoDB Accelerator (DAX), using the DAX client for Node.js. For more information, see <a href="#">In-memory acceleration with DynamoDB Accelerator (DAX) (p. 655)</a>.</p>	October 5, 2017
VPC Endpoints for DynamoDB	<p>DynamoDB endpoints allow Amazon EC2 instances in your Amazon VPC to access DynamoDB, without exposure to the public Internet. Network traffic between your VPC and DynamoDB does not leave the Amazon network. For more information, see <a href="#">Using Amazon VPC endpoints to access DynamoDB (p. 1101)</a>.</p>	August 16, 2017

<b>Change</b>	<b>Description</b>	<b>Date Changed</b>
Auto Scaling for DynamoDB	DynamoDB auto scaling eliminates the need for manually defining or adjusting provisioned throughput settings. Instead, DynamoDB auto scaling dynamically adjusts read and write capacity in response to actual traffic patterns. This allows a table or a global secondary index to increase its provisioned read and write capacity to handle sudden increases in traffic, without throttling. When the workload decreases, DynamoDB auto scaling decreases the provisioned capacity. For more information, see <a href="#">Managing throughput capacity automatically with DynamoDB auto scaling (p. 291)</a> .	June 14, 2017
DynamoDB Accelerator (DAX)	DynamoDB Accelerator (DAX) is a fully managed, highly available, in-memory cache for DynamoDB that delivers up to a 10x performance improvement – from milliseconds to microseconds – even at millions of requests per second. For more information, see <a href="#">In-memory acceleration with DynamoDB Accelerator (DAX) (p. 655)</a> .	April 19, 2017
DynamoDB now supports automatic item expiration with Time to Live (TTL)	Amazon DynamoDB Time to Live (TTL) enables you to automatically delete expired items from your tables, at no additional cost. For more information, see <a href="#">Expiring items by using DynamoDB Time to Live (TTL) (p. 378)</a> .	Feb 27, 2017
DynamoDB now supports Cost Allocation Tags	You can now add tags to your Amazon DynamoDB tables for improved usage categorization and more granular cost reporting. For more information, see <a href="#">Adding tags and labels to resources (p. 329)</a> .	Jan 19, 2017

Change	Description	Date Changed
New DynamoDB <code>DescribeLimits</code> API	<p>The <code>DescribeLimits</code> API returns the current provisioned capacity limits for your AWS account in a region, both for the region as a whole and for any one DynamoDB table that you create there. It lets you determine what your current account-level limits are so that you can compare them to the provisioned capacity that you are currently using, and have plenty of time to apply for an increase before you hit a limit. For more information, see <a href="#">Service, account, and table quotas in Amazon DynamoDB (p. 1242)</a> and the <a href="#">DescribeLimits</a> in the <a href="#">Amazon DynamoDB API Reference</a>.</p>	March 1, 2016
DynamoDB Console Update and New Terminology for Primary Key Attributes	<p>The DynamoDB management console has been redesigned to be more intuitive and easy to use. As part of this update, we are introducing new terminology for primary key attributes:</p> <ul style="list-style-type: none"> <li>• <b>Partition Key</b>—also known as a <i>hash attribute</i>.</li> <li>• <b>Sort Key</b>—also known as a <i>range attribute</i>.</li> </ul> <p>Only the names have changed; the functionality remains the same.</p> <p>When you create a table or a secondary index, you can choose either a simple primary key (partition key only), or a composite primary key (partition key and sort key). The DynamoDB documentation has been updated to reflect these changes.</p>	November 12, 2015

Change	Description	Date Changed
Amazon DynamoDB Storage Backend for Titan	<p>The DynamoDB Storage Backend for Titan is a storage backend for the Titan graph database implemented on top of Amazon DynamoDB. When using the DynamoDB Storage Backend for Titan, your data benefits from the protection of DynamoDB, which runs across Amazon's high-availability data centers. The plugin is available for Titan version 0.4.4 (primarily for compatibility with existing applications) and Titan version 0.5.4 (recommended for new applications). Like other storage backends for Titan, this plugin supports the Tinkerpop stack (versions 2.4 and 2.5), including the Blueprints API and the Gremlin shell. For more information, see <a href="#">Amazon DynamoDB Storage Backend for Titan (p. 1309)</a>.</p>	August 20, 2015

Change	Description	Date Changed
DynamoDB Streams, Cross-Region Replication, and Scan with Strongly Consistent Reads	<p>DynamoDB Streams captures a time-ordered sequence of item-level modifications in any DynamoDB table, and stores this information in a log for up to 24 hours. Applications can access this log and view the data items as they appeared before and after they were modified, in near real time. For more information, see <a href="#">Change data capture for DynamoDB Streams (p. 598)</a> and the <a href="#">DynamoDB Streams API Reference</a>.</p> <p>DynamoDB cross-region replication is a client-side solution for maintaining identical copies of DynamoDB tables across different AWS regions, in near real time. You can use cross region replication to back up DynamoDB tables, or to provide low-latency access to data where users are geographically distributed.</p> <p>The DynamoDB Scan operation uses eventually consistent reads, by default. You can use strongly consistent reads instead by setting the <code>ConsistentRead</code> parameter to true. For more information, see <a href="#">Read consistency for scan (p. 449)</a> and <a href="#">Scan</a> in the Amazon DynamoDB API Reference.</p>	July 16, 2015
AWS CloudTrail support for Amazon DynamoDB	DynamoDB is now integrated with CloudTrail. CloudTrail captures API calls made from the DynamoDB console or from the DynamoDB API and tracks them in log files. For more information, see <a href="#">Logging DynamoDB operations by using AWS CloudTrail (p. 1133)</a> and the <a href="#">AWS CloudTrail User Guide</a> .	May 28, 2015

Change	Description	Date Changed
Improved support for Query expressions	<p>This release adds a new <code>KeyConditionExpression</code> parameter to the <code>Query</code> API. A <code>Query</code> reads items from a table or an index using primary key values. The <code>KeyConditionExpression</code> parameter is a string that identifies primary key names, and conditions to be applied to the key values; the <code>Query</code> retrieves only those items that satisfy the expression. The syntax of <code>KeyConditionExpression</code> is similar to that of other expression parameters in DynamoDB, and allows you to define substitution variables for names and values within the expression. For more information, see <a href="#">Query operations in DynamoDB (p. 428)</a>.</p>	April 27, 2015
New comparison functions for conditional writes	<p>In DynamoDB, the <code>ConditionExpression</code> parameter determines whether a <code>PutItem</code>, <code>UpdateItem</code>, or <code>DeleteItem</code> succeeds: The item is written only if the condition evaluates to true. This release adds two new functions, <code>attribute_type</code> and <code>size</code>, for use with <code>ConditionExpression</code>. These functions allow you to perform a conditional writes based on the data type or size of an attribute in a table. For more information, see <a href="#">Condition expressions (p. 361)</a>.</p>	April 27, 2015

Change	Description	Date Changed
Scan API for secondary indexes	<p>In DynamoDB, a Scan operation reads all of the items in a table, applies user-defined filtering criteria, and returns the selected data items to the application. This same capability is now available for secondary indexes too. To scan a local secondary index or a global secondary index, you specify the index name and the name of its parent table. By default, an index Scan returns all of the data in the index; you can use a filter expression to narrow the results that are returned to the application. For more information, see <a href="#">Working with scans in DynamoDB</a> (p. 445).</p>	February 10, 2015
Online operations for global secondary indexes	<p>Online indexing lets you add or remove global secondary indexes on existing tables. With online indexing, you do not need to define all of a table's indexes when you create a table; instead, you can add a new index at any time. Similarly, if you decide you no longer need an index, you can remove it at any time. Online indexing operations are non-blocking, so that the table remains available for read and write activity while indexes are being added or removed. For more information, see <a href="#">Managing Global Secondary Indexes</a> (p. 508).</p>	January 27, 2015

Change	Description	Date Changed
Document model support with JSON	<p>DynamoDB allows you to store and retrieve documents with full support for document models. New data types are fully compatible with the JSON standard and allow you to nest document elements within one another. You can use document path dereference operators to read and write individual elements, without having to retrieve the entire document. This release also introduces new expression parameters for specifying projections, conditions and update actions when reading or writing data items. To learn more about document model support with JSON, see <a href="#">Data types (p. 13)</a> and <a href="#">Using expressions in DynamoDB (p. 354)</a>.</p>	October 7, 2014
Flexible scaling	<p>For tables and global secondary indexes, you can increase provisioned read and write throughput capacity by any amount, provided that you stay within your per-table and per-account limits. For more information, see <a href="#">Service, account, and table quotas in Amazon DynamoDB (p. 1242)</a>.</p>	October 7, 2014
Larger item sizes	<p>The maximum item size in DynamoDB has increased from 64 KB to 400 KB. For more information, see <a href="#">Service, account, and table quotas in Amazon DynamoDB (p. 1242)</a>.</p>	October 7, 2014

Change	Description	Date Changed
Improved conditional expressions	<p>DynamoDB expands the operators that are available for conditional expressions, giving you additional flexibility for conditional puts, updates, and deletes. The newly available operators let you check whether an attribute does or does not exist, is greater than or less than a particular value, is between two values, begins with certain characters, and much more. DynamoDB also provides an optional <i>OR</i> operator for evaluating multiple conditions. By default, multiple conditions in an expression are <i>ANDed</i> together, so the expression is true only if all of its conditions are true. If you specify <i>OR</i> instead, the expression is true if one or more one conditions are true. For more information, see <a href="#">Working with items and attributes (p. 344)</a>.</p>	April 24, 2014
Query filter	<p>The DynamoDB <code>Query</code> API supports a new <code>QueryFilter</code> option. By default, a <code>Query</code> finds items that match a specific partition key value and an optional sort key condition. A <code>Query</code> filter applies conditional expressions to other, non-key attributes; if a <code>Query</code> filter is present, then items that do not match the filter conditions are discarded before the <code>Query</code> results are returned to the application. For more information, see <a href="#">Query operations in DynamoDB (p. 428)</a>.</p>	April 24, 2014

Change	Description	Date Changed
Data export and import using the AWS Management Console	<p>The DynamoDB console has been enhanced to simplify exports and imports of data in DynamoDB tables. With just a few clicks, you can set up an AWS Data Pipeline to orchestrate the workflow, and an Amazon Elastic MapReduce cluster to copy data from DynamoDB tables to an Amazon S3 bucket, or vice-versa. You can perform an export or import one time only, or set up a daily export job. You can even perform cross-region exports and imports, copying DynamoDB data from a table in one AWS region to a table in another AWS region. For more information, see <a href="#">Exporting and importing DynamoDB data using AWS Data Pipeline (p. 1300)</a>.</p>	March 6, 2014
Reorganized higher-level API documentation	<p>Information about the following APIs is now easier to find:</p> <ul style="list-style-type: none"> <li>• Java: DynamoDBMapper</li> <li>• .NET: Document model and object-persistence model</li> </ul> <p>These higher-level APIs are now documented here: <a href="#">Higher-level programming interfaces for DynamoDB (p. 169)</a>.</p>	January 20, 2014

Change	Description	Date Changed
Global secondary indexes	<p>DynamoDB adds support for global secondary indexes. As with a local secondary index, you define a global secondary index by using an alternate key from a table and then issuing Query requests on the index. Unlike a local secondary index, the partition key for the global secondary index does not have to be the same as that of the table; it can be any scalar attribute from the table. The sort key is optional and can also be any scalar table attribute. A global secondary index also has its own provisioned throughput settings, which are separate from those of the parent table. For more information, see <a href="#">Improving data access with secondary indexes (p. 497)</a> and <a href="#">Using Global Secondary Indexes in DynamoDB (p. 500)</a>.</p>	December 12, 2013
Fine-grained access control	<p>DynamoDB adds support for fine-grained access control. This feature allows customers to specify which principals (users, groups, or roles) can access individual items and attributes in a DynamoDB table or secondary index. Applications can also leverage web identity federation to offload the task of user authentication to a third-party identity provider, such as Facebook, Google, or Login with Amazon. In this way, applications (including mobile apps) can handle very large numbers of users, while ensuring that no one can access DynamoDB data items unless they are authorized to do so. For more information, see <a href="#">Using IAM policy conditions for fine-grained access control (p. 1085)</a>.</p>	October 29, 2013

Change	Description	Date Changed
4 KB read capacity unit size	<p>The capacity unit size for reads has increased from 1 KB to 4 KB. This enhancement can reduce the number of provisioned read capacity units required for many applications. For example, prior to this release, reading a 10 KB item would consume 10 read capacity units; now that same 10 KB read would consume only 3 units (10 KB / 4 KB, rounded up to the next 4 KB boundary). For more information, see <a href="#">Read/write capacity mode (p. 17)</a>.</p>	May 14, 2013
Parallel scans	<p>DynamoDB adds support for parallel Scan operations. Applications can now divide a table into logical segments and scan all of the segments simultaneously. This feature reduces the time required for a Scan to complete, and fully utilizes a table's provisioned read capacity. For more information, see <a href="#">Working with scans in DynamoDB (p. 445)</a>.</p>	May 14, 2013
Local secondary indexes	<p>DynamoDB adds support for local secondary indexes. You can define sort key indexes on non-key attributes, and then use these indexes in Query requests. With local secondary indexes, applications can efficiently retrieve data items across multiple dimensions. For more information, see <a href="#">Local Secondary Indexes (p. 539)</a>.</p>	April 18, 2013

Change	Description	Date Changed
New API version	<p>With this release, DynamoDB introduces a new API version (2012-08-10). The previous API version (2011-12-05) is still supported for backward compatibility with existing applications. New applications should use the new API version 2012-08-10. We recommend that you migrate your existing applications to API version 2012-08-10, since new DynamoDB features (such as local secondary indexes) will not be backported to the previous API version. For more information on API version 2012-08-10, see the <a href="#">Amazon DynamoDB API Reference</a>.</p>	April 18, 2013
IAM policy variable support	<p>The IAM access policy language now supports variables. When a policy is evaluated, any policy variables are replaced with values that are supplied by context-based information from the authenticated user's session. You can use policy variables to define general purpose policies without explicitly listing all the components of the policy. For more information about policy variables, go to <a href="#">Policy Variables</a> in the <i>AWS Identity and Access Management Using IAM</i> guide.</p> <p>For examples of policy variables in DynamoDB, see <a href="#">Identity and access management in Amazon DynamoDB (p. 1070)</a>.</p>	April 4, 2013
PHP code examples updated for AWS SDK for PHP version 2	<p>Version 2 of the AWS SDK for PHP is now available. The PHP code examples in the Amazon DynamoDB Developer Guide have been updated to use this new SDK. For more information on Version 2 of the SDK, see <a href="#">AWS SDK for PHP</a>.</p>	January 23, 2013
New endpoint	<p>DynamoDB expands to the AWS GovCloud (US-West) region. For the current list of service endpoints and protocols, see <a href="#">Regions and Endpoints</a>.</p>	December 3, 2012

Change	Description	Date Changed
New endpoint	DynamoDB expands to the South America (São Paulo) region. For the current list of supported endpoints, see <a href="#">Regions and Endpoints</a> .	December 3, 2012
New endpoint	DynamoDB expands to the Asia Pacific (Sydney) region. For the current list of supported endpoints, see <a href="#">Regions and Endpoints</a> .	November 13, 2012
DynamoDB implements support for CRC32 checksums, supports strongly consistent batch gets, and removes restrictions on concurrent table updates.	<ul style="list-style-type: none"> <li>DynamoDB calculates a CRC32 checksum of the HTTP payload and returns this checksum in a new header, <code>x-amz-crc32</code>. For more information, see <a href="#">DynamoDB low-level API (p. 159)</a>.</li> <li>By default, read operations performed by the <code>BatchGetItem</code> API are eventually consistent. A new <code>ConsistentRead</code> parameter in <code>BatchGetItem</code> lets you choose strong read consistency instead, for any table(s) in the request. For more information, see <a href="#">Description (p. 1336)</a>.</li> <li>This release removes some restrictions when updating many tables simultaneously. The total number of tables that can be updated at once is still 10; however, these tables can now be any combination of CREATING, UPDATING or DELETING status. Additionally, there is no longer any minimum amount for increasing or reducing the <code>ReadCapacityUnits</code> or <code>WriteCapacityUnits</code> for a table. For more information, see <a href="#">Service, account, and table quotas in Amazon DynamoDB (p. 1242)</a>.</li> </ul>	November 2, 2012
Best practices documentation	The Amazon DynamoDB Developer Guide identifies best practices for working with tables and items, along with recommendations for query and scan operations.	September 28, 2012

Change	Description	Date Changed
Support for binary data type	<p>In addition to the Number and String types, DynamoDB now supports Binary data type.</p> <p>Prior to this release, to store binary data, you converted your binary data into string format and stored it in DynamoDB. In addition to the required conversion work on the client-side, the conversion often increased the size of the data item requiring more storage and potentially additional provisioned throughput capacity.</p> <p>With the binary type attributes you can now store any binary data, for example compressed data, encrypted data, and images. For more information see <a href="#">Data types (p. 13)</a>. For working examples of handling binary type data using the AWS SDKs, see the following sections:</p> <ul style="list-style-type: none"> <li>• <a href="#">Example: Handling binary type attributes using the AWS SDK for Java document API (p. 400)</a></li> <li>• <a href="#">Example: Handling binary type attributes using the AWS SDK for .NET low-level API (p. 424)</a></li> </ul> <p>For the added binary data type support in the AWS SDKs, you will need to download the latest SDKs and you might also need to update any existing applications. For information about downloading the AWS SDKs, see <a href="#">.NET code examples (p. 276)</a>.</p>	August 21, 2012
DynamoDB table items can be updated and copied using the DynamoDB console	DynamoDB users can now update and copy table items using the DynamoDB Console, in addition to being able to add and delete items. This new functionality simplifies making changes to individual items through the Console.	August 14, 2012

<b>Change</b>	<b>Description</b>	<b>Date Changed</b>
DynamoDB lowers minimum table throughput requirements	DynamoDB now supports lower minimum table throughput requirements, specifically 1 write capacity unit and 1 read capacity unit. For more information, see the <a href="#">Service, account, and table quotas in Amazon DynamoDB (p. 1242)</a> topic in the Amazon DynamoDB Developer Guide.	August 9, 2012
Signature Version 4 support	DynamoDB now supports Signature Version 4 for authenticating requests.	July 5, 2012
Table explorer support in DynamoDB Console	The DynamoDB Console now supports a table explorer that enables you to browse and query the data in your tables. You can also insert new items or delete existing items. The <a href="#">Creating tables and loading data for code examples in DynamoDB (p. 269)</a> and <a href="#">Using the console (p. 60)</a> sections have been updated for these features.	May 22, 2012
New endpoints	DynamoDB availability expands with new endpoints in the US West (N. California) region, US West (Oregon) region, and the Asia Pacific (Singapore) region.  For the current list of supported endpoints, go to <a href="#">Regions and Endpoints</a> .	April 24, 2012
BatchWriteItem API support	DynamoDB now supports a batch write API that enables you to put and delete several items from one or more tables in a single API call. For more information about the DynamoDB batch write API, see <a href="#">BatchWriteItem (p. 1341)</a> .  For information about working with items and using batch write feature using AWS SDKs, see <a href="#">Working with items and attributes (p. 344)</a> and <a href="#">.NET code examples (p. 276)</a> .	April 19, 2012
Documented more error codes	For more information, see <a href="#">Error handling with DynamoDB (p. 163)</a> .	April 5, 2012

<b>Change</b>	<b>Description</b>	<b>Date Changed</b>
New endpoint	DynamoDB expands to the Asia Pacific (Tokyo) region. For the current list of supported endpoints, see <a href="#">Regions and Endpoints</a> .	February 29, 2012
ReturnedItemCount metric added	A new metric, <code>ReturnedItemCount</code> , provides the number of items returned in the response of a Query or Scan operation for DynamoDB is available for monitoring through CloudWatch. For more information, see <a href="#">Logging and monitoring in DynamoDB (p. 1112)</a> .	February 24, 2012
Added examples for incrementing values	DynamoDB supports incrementing and decrementing existing numeric values. Examples show adding to existing values in the "Updating an Item" sections at:  <a href="#">Working with items: Java (p. 383)</a> .  <a href="#">Working with items: .NET (p. 403)</a> .	January 25, 2012
Initial product release	DynamoDB is introduced as a new service in Beta release.	January 18, 2012