




# Expressions and Strings

```
SELECT S.age, age1=S.age-5, 2*S.age AS age2  
FROM Sailors S  
WHERE S.sname LIKE 'B_%B'
```

- Illustrates use of arithmetic expressions and string pattern matching: *Find triples (of ages of sailors and two fields defined by expressions) for sailors whose names begin and end with B and contain at least three characters.*
- **AS** and **=** are two ways to name fields in result.
- **LIKE** is used for string matching. **'\_'** stands for any one character and **'%'** stands for 0 or more arbitrary characters.



## Find sid's of sailors who've reserved a red or a green boat

- **UNION**: Can be used to compute the union of any two *union-compatible* sets of tuples (which are themselves the result of SQL queries).
- If we replace **OR** by **AND** in the first version, what do we get?
- Also available: **EXCEPT** (What do we get if we replace **UNION** by **EXCEPT**?)

```
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND (B.color='red' OR B.color='green')
```

```
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND B.color='red'
```

```
UNION
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND B.color='green'
```




## Find sid's of sailors who've reserved a red and a green boat

- **INTERSECT**: Can be used to compute the intersection of any two *union-compatible* sets of tuples.
- Included in the SQL/92 standard, but some systems don't support it.
- Contrast symmetry of the UNION and INTERSECT queries with how much the other versions differ.

```
SELECT S.sid
FROM Sailors S, Boats B1, Reserves R1,
      Boats B2, Reserves R2
WHERE S.sid=R1.sid AND R1.bid=B1.bid
      AND S.sid=R2.sid AND R2.bid=B2.bid
      AND (B1.color='red' AND
           B2.color='green')
```

```
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND B.color='red'
INTERSECT
SELECT S.sid
FROM Sailors S, Boats B, Reserves R
WHERE S.sid=R.sid AND R.bid=B.bid
      AND B.color='green'
```



# Nested Queries

*Find names of sailors who've reserved boat #103:*

```
SELECT S.sname  
FROM Sailors S  
WHERE S.sid IN (SELECT R.sid  
                FROM Reserves R  
                WHERE R.bid=103)
```

- A very powerful feature of SQL: a WHERE clause can itself contain an SQL query! (Actually, so can FROM and HAVING clauses.)
- To find sailors who've *not* reserved #103, use NOT IN.
- To understand semantics of nested queries, think of a nested loops evaluation: *For each Sailors tuple, check the qualification by computing the subquery.*