

A Kernel-Clean Lean Mechanization of Classical Lottery in Action and the Wakker–Debreu–Koopmans Representation Layer

Jingyuan Li*

Ilia Tsetlin†

Fan Wang‡

May 25, 2026

Abstract

We present a Lean 4/Mathlib formalization of the decision-theoretic infrastructure behind *Classical Lottery in Action* and of the Wakker–Debreu–Koopmans representation layer used by that development. The artifact has two complementary components. The file `ClassicalLotteryInAction.lean` formalizes the local classical-lottery constructions, average-utility consequences, two-prize matching-frequency lemmas, smooth-representation wrappers, and ambiguity-attitude statements used by the Management Science companion paper. It exposes non-local representation and identification steps as named theorem assumptions, so the public theorem path is auditable rather than hidden behind project-specific axioms. The separate Wakker/Debreu–Koopmans development mechanizes, to our knowledge for the first time, Wakker’s Theorem IV.2.7 and the Debreu–Koopmans hard direction from Wakker’s structural axioms. That proof is organized as a certificate-driven closure sequence: topology consumers T1–T6 and construction-side certificates $A4 \rightarrow A1 \rightarrow A3 \rightarrow A2 \rightarrow B \rightarrow C$ discharge the former roadmap hypotheses end-to-end. The resulting Lean files are sorry-free, split into reviewer-sized modules, and kernel-axiom-clean: the public regression files print only `[propxt, Classical.choice, Quot.sound]` for the audited theorem surfaces.

1 Introduction

Formalized mathematics in economics has so far concentrated mainly on ordinal and combinatorial theorem families: social-choice impossibility, matching, allocation, and mechanism-design arguments. The present development targets a different kind of economic mathematics. It formalizes the classical-lottery infrastructure used in *Classical Lottery in Action: Quantifying Risk and Evaluating Uncertainty* and mechanizes the cardinal representation layer on which the smooth-model part of that paper depends. The central mathematical objects are non-empty finite lotteries, acts as state-indexed lotteries, preference relations, additive utility representations, standard sequences, tradeoff consistency, and coordinatewise concavity transfer.

The formalization is written as a formal-methods companion paper because the main contribution is not only a collection of final theorem statements. It is a proof-engineering account of how a long decision-theoretic argument can be made auditable in Lean. The Management Science companion theorem surface is kept stable and readable; the representation-theoretic layer is separated into a dedicated Wakker/Debreu–Koopmans module; and all theorem surfaces are checked by explicit `##print axioms` regression files. This design makes a distinction that is easy to blur in large

*Lingnan University, Hong Kong. jingyuanli@ln.edu.hk

†INSEAD, Singapore. ilia.tsetlin@insead.edu

‡ESSEC Business School, Singapore. wang.fan@essec.edu

mechanizations: a theorem may assume named mathematical hypotheses, but those hypotheses are not hidden global axioms unless they are declared as axioms in Lean.

The development has two public entry points. The applied companion file is

`Classical Lottery/ClassicalLotteryInAction.lean`.

The representation-theoretic proof surface is the barrel file

`Classical Lottery/WakkerDebreuKoopmans.lean`,

with reviewer regression file

`Classical Lottery/Wakker/AxiomCheck.lean`.

The first file records the theorem boundaries consumed by the Management Science paper. The second and third files record the discharged Wakker/Debreu–Koopmans layer and its kernel audit.

Contributions. The paper contributes the following.

1. A Lean 4 formalization of the classical-lottery theorem surface used by the companion economics paper, including the average-utility proposition, matching-frequency gap filling, the smooth-model wrapper theorem, the normalized smooth matching-frequency formula, and the ambiguity-attitude curvature proposition.
2. A named-bridge architecture for the applied file: representation, strict-separation, inverse- ψ , and curvature-recovery obligations are exposed as ordinary theorem assumptions rather than as implicit global axioms.
3. A Lean formalization of Wakker IV.2.7 and the Debreu–Koopmans hard direction, with stable downstream theorem names for the Management Science artifact.
4. A certificate decomposition for monograph-scale measurement proofs. Standard-sequence construction, topology transfer, global gluing, uniqueness, two-coordinate concavity, and per-coordinate concavity transfer are represented by named certificates with audited consumers.
5. An end-to-end closure sequence for the Wakker/Debreu–Koopmans layer: topology consumers T1–T6 and construction certificates $A4 \rightarrow A1 \rightarrow A3 \rightarrow A2 \rightarrow B \rightarrow C$.
6. A reproducible kernel audit. The checked theorem surfaces depend only on the standard Lean/Mathlib foundations [`propext`, `Classical.choice`, `Quot.sound`] and not on project-specific axioms.

2 Mathematical and formalization background

2.1 Classical lotteries and acts

The applied artifact starts from finite classical lotteries. In Lean, a classical lottery is represented as a non-empty list of prizes. An act assigns a lottery to each state. Preferences are binary relations on acts. The file then builds the operations needed by the economics paper: concatenation, replication, deletion of matched sub-lotteries, relative frequencies, average utility, and two-prize matching frequencies.

The average-utility result has the familiar representation-theoretic shape. The easy direction, from a utility representation to cancellation and Archimedeanity, is proved directly in the artifact.

The hard direction, from cancellation and Archimedeanity to an average-utility representation, is exposed as the named bridge `AverageUtilityHardDirection`. This is the first example of the paper’s general design rule: local algebra and order-theoretic consequences are mechanized directly; large imported representation steps are named explicitly until their proof lives in the appropriate representation module.

2.2 Wakker and Debreu–Koopmans

Wakker’s Theorem IV.2.7 is a cardinal measurement theorem for product preferences. It constructs additive representations from structural assumptions such as weak order, separability, restricted solvability, Archimedeanity, and tradeoff consistency. The proof is not a short convexity argument. It passes through standard sequences, calibration of coordinate utilities, comparison of tradeoffs across coordinates, topological continuity inputs, and global gluing of pairwise representations.

The Debreu–Koopmans hard direction supplies the concavity layer needed downstream. Roughly, after additive representation has been established, convexity or quasi-concavity of preference must be converted into concavity of coordinate utilities. In the Lean development this is isolated from the Wakker existence theorem but shares the same representation infrastructure. The result is a theorem-backed route from the structural Wakker assumptions to additive representation and per-coordinate concavity.

3 Artifact architecture

The repository keeps the applied economics artifact and the representation proof in separate but cross-linked modules. The split is deliberate. The applied file should remain stable for readers of the economics paper; the Wakker/Debreu–Koopmans file can expose the finer certificate machinery needed by formal-methods reviewers.

3.1 Applied companion file

The file `ClassicalLotteryInAction.lean` is a single Management Science companion surface. Its five main audited theorem targets are listed in Table 1. The bridge hypotheses appearing in these theorems are ordinary Lean parameters. Therefore the theorem bodies can be audited without conflating theorem assumptions with global axioms.

Lean theorem	Paper role
<code>prop_average_utility</code>	Proposition 1: average-utility characterization for classical lotteries.
<code>lem_gap_filling</code>	Two-prize matching-frequency gap-filling lemma.
<code>thm_smooth_model</code>	Smooth-representation wrapper theorem under explicit sufficiency and regularity interfaces.
<code>matching_freq_smooth_formula</code>	Normalized two-prize smooth matching-frequency formula.
<code>prop_aversion_or_seeking</code>	Ambiguity aversion/seeking and curvature statement.

Table 1: Public theorem surface of `ClassicalLotteryInAction.lean`.

3.2 Representation proof modules

The Wakker/Debreu–Koopmans monolith has been split into a stable barrel plus reviewer-sized submodules, shown in Table 2. Existing imports continue to use `WakkerDebreuKoopmans`; reviewers can inspect the smaller modules independently.

Module	Role
<code>WakkerDebreuKoopmans.Core</code>	Product-preference infrastructure, additive representations, Wakker IV.2.7 wrapper, Debreu–Koopmans easy and hard wrappers, and core consumers.
<code>WakkerDebreuKoopmans.Certificates</code>	Named certificate predicates and early construction-stack interfaces.
<code>WakkerDebreuKoopmans.M2Frontier</code>	Common-scale uniqueness, corrected tradeoff-transfer predicates, bracketing, rational-image, mesh, and affine-lift machinery.
<code>WakkerDebreuKoopmans.ConstructionStack</code>	S23–S33 standard-sequence construction stack, monograph-level bundles, and alignment data.
<code>WakkerDebreuKoopmans.Topology</code>	T1–T6 topology consumers: preference continuity, connectedness, coordinate continuity, monotonicity equivalences, and topological bundle assembly.
<code>WakkerDebreuKoopmans.Closure</code>	O1–O4 and A4–C closure, including the equivalences tying Stage-5 data to additive representation.
<code>WakkerDebreuKoopmans.Audit</code>	Detailed <code>##print axioms</code> block imported by <code>Wakker/AxiomCheck.lean</code> .

Table 2: Split Wakker/Debreu–Koopmans module structure.

4 The named-bridge method

The applied artifact uses named bridges to make the formal boundary inspectable. Table 3 records the bridge interfaces. Each bridge is a Lean proposition consumed by a theorem. It is not a hidden project axiom. When the corresponding mathematics is discharged elsewhere, the consuming theorem does not need to change; only the proof that supplies the bridge changes.

This design is especially important for audit interpretation. A kernel axiom report for `thm_smooth_model` says what the proof term depends on globally. It does not say that the theorem has no assumptions. Instead, it says that the assumptions are visible in the theorem statement and that the proof downstream of those assumptions introduces no additional global axioms. The Wakker/Debreu–Koopmans development then supplies an independent, theorem-backed route for the main representation-theoretic layer.

5 Certificate-driven Wakker/Debreu–Koopmans proof

The Wakker proof is too large to be reviewable as a single black-box theorem. The Lean artifact therefore organizes the proof around certificates. A certificate records a construction output: standard-sequence data, a common scale, a topology bundle, a gluing datum, or a concavity-transfer datum. Each certificate has one or more consumer theorems, and many are tied to downstream goals by equivalence lemmas.

5.1 Certificate families

The main families are as follows.

Bridge	Lean role	Mathematical content named by the bridge
AverageUtility HardDirection P	Input to prop_average_utility.	Cancellation plus Archimedeanity produce an average-utility representation on constant classical lotteries.
MatchingFrequency StrictSeparation P	Reverse input to lem_gap_filling.	On two-prize acts, strict preference implies strict separation of matching frequencies.
SmoothRepresentation Sufficiency Pref	Forward direction of thm_smooth_model.	From non-triviality and Axioms 1–7, obtain a smooth representation.
SmoothRepresentation Regularity Pref	Reverse regularity part of thm_smooth_model.	From a smooth representation, recover Denseness, Continuity, and Consistent Aggregation; other axioms are derived locally.
MatchingFrequency SmoothFormulaBridge Pref R	Input to matching_freq_smooth_formula.	Identify behavioral matching frequency with the inverse- ψ expression.
AmbiguityAttitude CurvatureBridge Pref R	Input to prop_aversion_or_seeking.	Recover concavity or convexity of ψ from ambiguity aversion or seeking.

Table 3: Named bridge interfaces in `ClassicalLotteryInAction.lean`.

- C1. Wakker construction.** Standard-sequence data, pairwise slice representations, grid calibration, and all-pairs additivity.
- C2. Global gluing.** Passage from compatible pairwise data to a single additive representation on the full product.
- C3. Uniqueness.** Common positive scale and coordinate-specific translations for two additive representations of the same essential-coordinate preference.
- C4. Two-coordinate concavity.** The Debreu–Koopmans upgrade from slice quasi-concavity and continuity to two-coordinate concavity.
- C5. Per-coordinate transfer.** The pivot-indexed transfer from pair concavity and coordinate-image coverage to full per-coordinate concavity.

The headline theorem names audited by `Wakker/AxiomCheck.lean` include `WakkerDebreuKoopmans.wakker_IV_2_7`, `WakkerDebreuKoopmans.debreu_koopmans_hard`, `WakkerRoadmap.WakkerExistence.wakker_IV_2_7_consumer`, and `WakkerRoadmap.DebreuKoopmansHard.debreu_koopmans_hard_consumer`. The same regression file also checks supporting consumers such as `global_additive_from_pairwise`, `additive_rep_unique`, `two_coord_concave`, and `concave_transfers`.

5.2 Topology ladder T1–T6

The topology side proves the analytic consumers needed by the construction stack. T1 packages preference continuity and closed indifference sets. T2 supplies connectedness and interval-image

reasoning for real coordinates. T3 proves continuity of coordinate utilities from connectedness, monotonicity, continuity, and unboundedness, and closes the monotonicity-certificate equivalence. T4 proves the alignment theorem: under additive representation, the balance equation plus strict reference ordering supplies the descending/ascending seed alignment. T5 packages these results into `WakkerTopologicalAxiomBundle`. T6 discharges the bracketing-pair component from coordinate-utility unboundedness.

The topology consumers are included in `WakkerDebreuKoopmans.Audit`. They are the bridge from Wakker’s structural assumptions to the construction stack, and they prevent topology-sensitive obligations from being hidden in later algebraic theorems.

5.3 Construction-side chain A4–C

The construction-side closure is recorded as

$$A4 \rightarrow A1 \rightarrow A3 \rightarrow A2 \rightarrow B \rightarrow C.$$

A4 supplies the shared pivot-coordinate representation data for the Step-4 to Step-5 lift. A1 packages all-pairs additivity for one global utility family. A3 proves strict monotonicity for that family, and A2 proves coordinate-image coverage. Priority B closes the quasi-to-concave strengthening. Priority C transfers pivot-based pair concavity to per-coordinate concavity. Together with T1–T6, this produces the end-to-end Wakker/Debreu–Koopmans route recorded in `WakkerDebreuKoopmans.Closure`.

6 M2 uniqueness as a proof-engineering case study

The M2 frontier is a useful case study because it shows why certificate decomposition is not just cosmetic. The public uniqueness consumer `additive_rep_unique` states that two additive representations of an essential-coordinate product preference agree up to a common positive scale and coordinate-specific translations. The proof factors through `AdditiveCommonScaleCertificate` and `TradeoffTransferCertificate`.

A first diagnostic predicate, `UtilityValueRealizingEquivalence`, was too strong: it forced a fixed reference-pair difference to equal an arbitrary prescribed difference. Lean exposed the problem in the simple additive model $\text{Bool} \rightarrow \mathbb{R}$. The corrected predicate lets the reference pair vary. After that correction, the proof decomposes into off-diagonal tradeoff transfer, same-coordinate ratio consistency, coordinate-affine lift, rational-image coverage, and grid-density/refinement certificates.

This episode illustrates a broader lesson for automated reasoning in economics. Paper proofs often compress several existence and normalization choices into prose. In Lean those choices must become data. If the data are exposed as named certificates, false strengthening attempts fail locally and visibly rather than contaminating the main theorem statement.

7 Axiom audit and reproducibility

Both parts of the artifact use explicit kernel audits. The applied file contains `##print axioms` commands for the five public Management Science theorem targets. The representation proof has a dedicated regression file, `Wakker/AxiomCheck.lean`, which imports the detailed Wakker/Debreu–Koopmans audit.

Here “standard foundations” means exactly `[propext, Classical.choice, Quot.sound]`.

The recommended reviewer protocol is:

Audit target	Theorem surface	Lean-reported axioms
<code>ClassicalLotteryInAction.lean</code>	<code>prop_average_utility</code> , <code>lem_gap_filling</code> , <code>thm_smooth_model</code> , <code>matching_freq_smooth_formula</code> , <code>prop_aversion_or_seeking</code> .	standard foundations
<code>Wakker/AxiomCheck.lean</code>	Wakker IV.2.7, Debreu–Koopmans easy and hard wrappers, Wakker existence consumers, uniqueness, two-coordinate concavity, concavity transfer, topology consumers, construction-stack closure, and certificate equivalences imported through <code>WakkerDebreuKoopmans.Audit</code> .	standard foundations

Table 4: Kernel-level axiom audit. The bridge hypotheses in theorem statements are visible assumptions, not global Lean axioms.

1. build the Wakker/Debreu–Koopmans theorem surface with `lake build WakkerDebreuKoopmans`;
2. run the public Wakker/Debreu–Koopmans axiom regression with `lake build Wakker.AxiomCheck`;
3. build the applied companion surface with `lake build ClassicalLotteryInAction`;
4. compile this paper with `latexmk -pdf -interaction=nonstopmode -halt-on-error "Classical Lottery/ClassicalLotteryInAction_companion.tex"`.

The audit criterion is intentionally kernel-level and conservative. The allowed dependencies are `propext`, `Classical.choice`, and `Quot.sound`, which are standard in Lean/Mathlib developments of this kind. No project-specific axiom appears in the audited theorem surfaces.

8 Scope and interpretation

The merged artifact should be read as a two-layer formalization. The Wakker/Debreu–Koopmans representation layer is discharged end-to-end in the dedicated Wakker modules. The Management Science companion file continues to expose several theorem-shaped bridges, including inverse- ψ matching-frequency identification and behavioral curvature recovery. This is intentional. Those statements are not hidden axioms; they are visible mathematical interfaces at the applied theorem boundary. The benefit of the current architecture is that each such interface can be discharged in its natural mathematical home without changing the applied theorem names.

The current submission therefore makes two claims. First, the applied theorem path in `ClassicalLotteryInAction.lean` is formally checked and globally axiom-clean conditional on its named mathematical inputs. Second, the major Wakker/Debreu–Koopmans representation input has now been developed as a separate, theorem-backed, globally axiom-clean Lean artifact.

9 Related work and novelty

Formalized analysis and probability. Large analytic libraries in Isabelle/HOL, Lean, and related systems have made it realistic to formalize measure theory, probability, topology, and convex analysis at scale. The Lean mathematical library provides the ambient topology, order, algebra,

finite-sum, and convex-analysis infrastructure used in this development. Isabelle’s Archive of Formal Proofs provides another benchmark for large reusable formal libraries. Our work follows the same library-first philosophy, but the target theorem family is different: Wakker IV.2.7 is a cardinal measurement theorem about product preferences and tradeoff calibration, not primarily a theorem of measure theory or probability.

Formal economics. Recent economics formalizations have often focused on ordinal social choice, matching, allocation, and mechanism design. Those developments reason about rankings, voters, alternatives, strategyproofness, and allocations. The present project formalizes a cardinal representation theorem. The proof burden lies in additive utility construction, standard sequences, calibration, affine uniqueness, topology transfer, and concavity. This makes the development closer to a mechanized mathematical-economics monograph than to a finite combinatorial impossibility proof.

Wakker and Debreu–Koopmans mechanization. We performed targeted searches for `additive representation`, `tradeoff consistency`, `Debreu`, `Wakker`, and `Koopmans` in Mathlib, Coq-community repositories, Isabelle/AFP, and Mizar/MML-style libraries. We found no prior mechanization of Wakker’s additive representation theorem, tradeoff consistency, or the Debreu–Koopmans hard direction. This is negative search evidence rather than a theorem of bibliographic completeness, but it supports the novelty claim: to our knowledge, this is the first Lean mechanization of this representation-theoretic layer.

Proof-engineering contribution. The main reusable lesson is the certificate architecture. Instead of asserting one very large theorem and hiding all construction work inside it, the development exposes construction outputs as typed certificates with consumer theorems and axiom regressions. This approach made the false fixed-reference uniqueness predicate visible, enabled reviewer-sized module boundaries, and preserved stable theorem names for the applied economics artifact.

10 Conclusion

The merged Lean artifact provides a kernel-clean formal-methods companion to *Classical Lottery in Action*. The applied file formalizes the theorem surface used by the economics paper and makes its non-local mathematical inputs explicit. The Wakker/Debreu–Koopmans development discharges the main representation-theoretic layer through a certificate-driven, end-to-end Lean proof of Wakker IV.2.7 and the Debreu–Koopmans hard direction. The final result is a sorry-free, reviewer-auditable mechanization of a monograph-scale cardinal measurement theorem and its role in a contemporary decision-theory application.

References

- [1] Jingyuan Li, Ilia Tsetlin, and Fan Wang. *Classical Lottery in Action: Quantifying Risk and Evaluating Uncertainty*. Management Science, 2026.
- [2] Peter P. Wakker. *Additive Representations of Preferences: A New Foundation of Decision Analysis*. Kluwer Academic Publishers, 1989.
- [3] Gerard Debreu and Tjalling C. Koopmans. Additively decomposed quasiconvex functions. *Mathematical Programming*, 24:1–38, 1982.

- [4] The Mathlib Community. *The Lean mathematical library*. <https://github.com/leanprover-community/mathlib4>.
- [5] The Isabelle Archive of Formal Proofs. <https://www.isa-afp.org/>.