# Final Project: AI-Based Web Application Development and Deployment



Estimated Time: 1 hour 45 minutes

### Scenario

You have been hired as a software engineer by an e-commerce company to create an AI-based web app that performs analytics on customer feedback for their signature products. To accomplish this requirement, you will create an Emotion Detection system that processes feedback provided by the customer in text format and deciphers the associated emotion expressed.

## Introduction

In this final project, you will be assessed on the knowledge gained on all aspects of app creation and its web deployment throughout this course. You will be required to save screenshots of your results from time to time, with specific nomenclature. These screenshots will have to be uploaded in the peer graded assignment that follows.

In this project, we use the embeddable Watson AI libraries to create an emotion detection application.

Emotion detection extends the concept of sentiment analysis by extracting the finer emotions, like joy, sadness, anger, and so on, from statements rather than the simple polarity that sentiment analysis provides. This makes emotion detection a very important branch of study and businesses use such systems widely for their AI based recommendation systems, automated chat bots, and so on.

## **Project guidelines**

For the completion of this project, you'll have to complete the following 8 tasks, based on the knowledge you have gained through the course.

**Note**: This platform is not persistent. It is recommended that you keep a copy of your code on your local machines and save changes from time to time. In case you revisit the lab, you will need to recreate the files in this lab environment, using the saved copies from your machines.

## Tasks and objectives:

- Task 1: Clone the project repository
- Task 2: Create an emotion detection application using Watson NLP library
- Task 3: Format the output of the application
- Task 4: Package the application
- Task 5: Run Unit tests on your application
- Task 6: Deploy as web application using Flask
- Task 7: Incorporate Error handling
- Task 8: Run static code analysis

Let's get started!

## Task 1: Clone the project repository

The GitHub repository of the project is available on the URL mentioned below.

- 1. 1
- 1. https://github.com/ibm-developer-skills-network/oaqjp-final-project-emb-ai.git

Copied! Executed!

- 1. Clone this GitHub repo using the Cloud IDE terminal to your project to a folder named final project.
- 2. After the cloning is complete, use the terminal to change the current directory final\_project.
- 3. Take the **screenshot** of your folder structure. Save this image as 1\_folder\_structure.png.

# Task 2: Create an emotion detection application using the Watson NLP library

The Watson NLP libraries are embedded. Therefore, there is no need of importing them to your code. You only need to send a post request to the correct function in the library and receive the output.

1. For this project, you'll use the **Emotion Predict** function of the Watson NLP Library. For accessing this function, the URL, the headers, and the input json format is as follows.

```
1. 1
2. 2
3. 3
1. URL: 'https://sn-watson-emotion.labs.skills.network/v1/watson.runtime.nlp.v1/NlpService/EmotionPredict'
2. Headers: {"grpc-metadata-mm-model-id": "emotion_aggregated-workflow_lang_en_stock"}
3. Input json: { "raw_document": { "text": text_to_analyse } }
Copied!
```

Note that the text to analyze is being used as a variable that holds the actual written text that needs to be analyzed.

- 2. Create a file named emotion\_detection.py in final\_project folder.
- 3. In the emotion\_detection.py file, write the function to run emotion detection using the appropriate Emotion Detection function. Name this function emotion\_detector.

**Note:** Assume that that text to be analyzed is passed to the function as an argument and is stored in the variable text\_to\_analyze. The value being returned must be the text attribute of the response object as received from the Emotion Detection function.

- 4. Take a **screenshot** of the code you write and save it as 2a\_emotion\_detection.png.
- 5. The application should now be importable using Python shell. Open a python3.11 shell.
- 6. Import the application.
- 7. After you successfully import the application, test your application with the text: "I love this new technology."
- 8. Take a **screenshot** of the terminal with all three steps included in it along with the final output. Name this file 2b\_application\_creation.png.

Note: In case the python shell shows an error ModuleNotFoundError: No module named 'requests', you may install the requests library to your IDE using the following command on the terminal.

```
    1. 1
    1. python3.11 -m pip install requests
```

Copied!

## Task 3: Format the output of the application

1. Convert the response text into a dictionary using the json library functions.

Note the content formatting in this dictionary.

- 2. Extract the required set of emotions, including anger, disgust, fear, joy and sadness, along with their scores.
- 3. Write the code logic to find the dominant emotion, which is the emotion with the highest score.
- 4. Then, modify the emotion\_predictor function to return the following output format.

about:blank 2/6

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8

1. {
2. 'anger': anger_score,
3. 'disgust': disgust_score,
4. 'fear': fear_score,
5. 'joy': joy_score,
6. 'sadness': sadness_score,
7. 'dominant_emotion': '<name of the dominant emotion>'
8. }
```

### Copied!

- 5. Take a **screenshot** of the modified function code and save it as 3a\_output\_formatting.png.
- 6. Test the application in the python3.11 shell again, with the statement I am so happy I am doing this.
- 7. Verify that the response received has the dominant emotion is joy.
- 8. Take a **screenshot** of the output from the terminal shell and save it as 3b\_formatted\_output\_test.png.

## Task 4: Package the application

In this task, you will package the application created in the previous steps.

- 1. Perform the relevant steps in creation of the package. Set the name of the package to EmotionDetection.
- 2. Once completed, take a **screenshot** of the contents of the init file along with the final folder structure of the final project directory.

Make sure to fit both of the images into a single screenshot and name it 4a\_packaging.png.

- 3. To make sure that the EmotionDetection is a valid package, you need to test the package. To do this:
  - 1. Run a python shell in the terminal.
  - 2. Import the emotion\_detector function from the package.
  - 3. If the package is created accurately, you will not receive any error messages.
  - 4. Test run the function again with the statement I hate working long hours.
  - 5. Verify that the output displays the dominant emotion as anger.
- 4. Take a **screenshot** of this terminal output and save it as 4b\_packaging\_test.png.

# Task 5: Run unit tests on your application

With a functional application being available, you now need to run unit tests to validate the application output.

1. To run unit tests, create a new file, test\_emotion\_detection.py that calls the required application function from the package and tests it for the following statements and dominant emotions.

Statement	<b>Dominant Emotion</b>
I am glad this happened	joy
I am really mad about this	anger
I feel disgusted just hearing about this	disgust
I am so sad about this	sadness
I am really afraid that this will happen	fear

about:blank 3/6

- 2. Once complete, take a **screenshot** of the code and save it as 5a unit testing.png.
- 3. Execute the test emotion\_detection.py file on terminal.
- 4. Check the unit test output to verify that the unit tests have passed.
- 5. Take a **screenshot** of the terminal output of this execution and save it as 5b\_unit\_testing\_result.png.

# Task 6: Web deployment of the application using Flask

After all the tests are successfully completed, you need to deploy the application on the web. This will enable the customer to access and use the application.

**Note:** The index.html file in the templates folder and mywebscript.js file in the static folder have been provided as a part of the repo. These files do not need to be updated in this project.

1. You have to create the server.py file from scratch. Note the following requirements of this task.

**Note:** server.py is a part of final\_project folder.

- 2. Make sure that the Flask decorator for the application calling function is \emotionDetector.
- 3. The customer has requested the output to be displayed in the format as displayed in the example below.

#### **Example Output**

Let's say that you want to evaluate the statement I love my life. The statement is processed as follows:

```
1. 1
2. 2
3. 3
4. 4
5. 5
6. 6
7. 7
8. 8
1. {
2. "anger": 0.006274985,
3. "disgust": 0.0025598293,
4. "fear": 0.009251528,
5. "joy": 0.9680386,
6. "sadness": 0.049744144,
7. "dominant_emotion":"joy"
8. }
Copied!
```

The response is displayed as:

```
For the given statement, the system response is 'anger': 0.006274985, 'disgust': 0.0025598293, 'fear': 0.009251528, 'joy': 0.9680386 and 'sadness': 0.049744144. The dominant emotion is joy.
```

4. Application needs to be deployed on localhost: 5000

For completing this task of the project, you have to first take a snapshot of the final contents of server.py and name it 6a\_server.png. Secondly, you have to take a snapshot of the final deployed application, testing it for the statement "I think I am having fun". Name this image as 6b\_deployment\_test.png.

# Task 7: Incorporate Error handling

Incorporate the error handling capability in your function emotion\_detector to manage blank entries from users, i.e. running the application without any input.

1. Access the status\_code attribute of the server response to correctly display the system response for blank entries.

For status\_code = 400, make the function return the same dictionary, but with values for all keys being None.

2. Take a **screenshot** of the modified function and name it 7a error handling function.png.

about:blank 4/6

3. Modify server.py to incorporate error handling when the dominant\_emotion is None. In this scenario, the response should display a message **Invalid text! Please try again!**.

- 4. Take a **screenshot** of this edited file and save it as 7b\_error\_handling\_server.png.
- 5. Deploy the application and test it for blank entries.
- 6. The output should display the error message, **Invalid text! Please try again!**.
- 7. Take a **screenshot** of the output displaying the error message and name it 7c error handling interface.png

## Task 8: Run static code analysis

Finally, its time to check code compliance.

1. Run static code analysis on the code you created. Use PyLint library on server.py file and try to generate a 10/10 score. You will have to modify the server.py file to get this score. Take a snapshot of the modified file and name it as 8a\_server\_modified.png.

**Note:** The difference between a 9/10 score and a 10/10 score may be use of Docstrings. Include Docstrings in all functions of your codes.

2. Take a **screenshot** of a 10/10 output on the terminal after running static code analysis. Name the screenshot as 8b\_static\_code\_analysis.png.

## **Checklist for the images**

Before you submit the project for evaluation, make sure to verify that you have captured all the images as instructed during the course of the project. Here is a quick summary of the required.

#### Task 1: Clone the project repository

1\_folder\_structure.png

#### Task 2: Create an emotion detection application using Watson NLP library

2a\_emotion\_detection.png
2b\_application\_creation.png

### Task 3: Format the output of the application

3a\_output\_formatting.png
3b\_formatted\_output\_test.png

#### Task 4: Package the application

4a\_packaging.png
4b\_packaging\_test.png

#### Task 5: Run Unit tests on your application

5a\_unit\_testing.png
5b\_unit\_testing\_result.png

#### Task 6: Deploy as web application using Flask

6a\_server.png
6b\_deployment\_test.png

#### Task 7: Incorporate Error handling

7a\_error\_handling\_function.png
7b\_error\_handling\_server.png
7c\_error\_handling\_interface.png

#### Task 8: Run static code analysis

8\_static\_code\_analysis.png

about:blank 5/6

## **Conclusion**

Congratulations on completing the project.

By completing this project, you have:

- 1. Created an Emotion Detection application using the functions from embeddable AI libraries
- 2. Extracted relevant information from the output received from the function
- 3. Tested and packaged the application created using the Emotion Detection function
- 4. Completed web deployment of your application using Flask
- 5. Incorporated error handling in your application to account for invalid input to your application
- 6. Written codes that are in perfect compliance with PEP8 guidelines, getting 10/10 score in static code analysis

## **Next Steps**

Now that you have completed the project, please submit the project for peer review.

Upload all the images, which you captured when building the project, as instructed in the **Peer Graded Review Submission**.

## Author(s)

Abhishek Gagneja

## Changelog

**Date Version Changed by Change Description** 2023-07-12 1.0 Abhishek Gagneja Initial version created

© IBM Corporation 2023. All rights reserved.

about:blank 6/6